DAIKIN

General catalogue

2015



Our promise...

... is to ensure that customers can depend on Daikin for the ultimate in comfort, so that they are free to focus on their own working and home lives.

We promise to dedicate ourselves to technological excellence,

a design focus and the highest quality standards
so that our customers can trust and rely on the comfort we deliver.

Our promise to the planet is absolute. Our products are
at the forefront of low energy-usage and we will innovate to further
reduce the environmental impact of HVACR (Heating, Ventilation,
Air conditioning, Refrigeration) solutions.
We lead where others follow.

We will continue our global leadership in HVACR solutions
as our specialist expertise in all market sectors combined
with 90 years' experience enable us to deliver added value
in long-lasting relationships based on trust, respect and credibility.

We promise to continue our forward-thinking ethos, treating
challenges as opportunities to produce ever-better solutions.
We will drive innovation and go the extra distance for our
customers and our company.
We will be smart and ready to do things differently.

We will deliver on these core values of our brand and enjoy
sustainable success with continued growth.



Table of content

New products 2015 2

Why choose R32 refrigerant? 6

Replacement technology 7

Seasonal efficiency, smart use of energy 9

Tools & Platforms 10

Air purifiers 12

Heating

Source to water heat pumps 17
Daikin Altherma hybrid heat pump 26
Daikin Altherma ground source heat pump 30
Daikin Altherma low temperature 32
Daikin Altherma high temperature split 58
Daikin Altherma Flex Type 64
Gas condensing boiler 70

Source to air heat pumps 72
Residential applications - Split 72
Commercial applications - VRV 73

Air conditioning

Residential applications - Split 75
Pair applications 85
Multi model applications 114

Light commercial applications Sky Air 154
Indoor units 169
Siesta Sky Air 191
Twin, triple, double twin applications 194
Rooftop 198

Commercial applications - VRV 200
VRV outdoor units 214
VRV indoor units 234
Hot water 254
Powerful selection programs 254

Ventilation & Biddle Air Curtains 258

Marine Types 274

Applied systems

Chillers 276
Air cooled chillers (Cooling only) 286
Air cooled chillers (Heat pump) 324
Air cooled condensing units 334
Water cooled chillers 336
Condenserless chillers 346
Water cooled centrifugal chillers 350

Fan coil units 352

Air handling units 376

Refrigeration

ZEAS condensing units 402
Conveni-Pack 404
Booster unit 409
Commercial condensing units 410
Large variable capacity condensing unit 413

Control systems, options & accessories

Control systems 414
Options & accessories 438

New products 2015



p.36

Daikin Altherma low temperature - integrated solar unit

› **Best seasonal efficiencies**, providing the highest savings on running costs
› **Perfect fit for new builds**, as well as low-energy houses
› **Solar support** of domestic hot water with unpressurised solar system
› Lightweight plastic tank
› **Bivalent option**: combinable with a secondary heat source
› **App** control possible



p.70

Gas condensing boiler

› **Low running costs** for both heating and hot water
› **Easy installation** in minimum space
› **Ideal for replacement** of current gas boiler



p.72

Optimised for heating split range

› Wide range of connectable indoor units (wall mounted, floor standing) with guaranteed heating capacity **down to -25°C outdoor temperature**
› Unique **free hanging coil** technology: the defrost cycle is improved, resulting in lower running costs and no ice buildup

R-32



p.88
p.90

R32 range expanded

New ranges launched with R32 to offer better **efficiencies** and **low environmental impact**
› Daikin Emura **FTXJ-LW/S**
› FTXM-K

p.93
p.94
p.95
p.110
p.111
p.112

New wall mounted indoor units

A wide range of **new wall mounted indoor units** launched to fit every customer's requirements and budget with **new designs** and **new features**

› FTX-K
› FTXK-AW/S
› FTXB-C
› ATX-K
› ATXB-C
› ATXN-NB



p.418

Online controller

Mobile app control now available for almost all split indoor units

› **Monitor** the status of your heat pump unit
› **Control** the operation mode, set temperature, air flow rate and direction
› **Schedule** the set temperature and operation mode with up to 4 actions per day for 7 days



p.202
p.216

Integrating VRV IV standard and technologies on all ranges


VRV IV

› Heat recovery, heat pump, water-cooled and replacement series now all available in VRV IV!

NEW VRV IV heat recovery:

› Fully integrated solution with **heat recovery** for maximum efficiency with **COPs of up to 8** !
› Covers all thermal needs of a building via a **single point of contact**: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains
› "**Free**" heating and hot water through heat recovery
› The perfect personal **comfort** for guests/tenants via simultaneous cooling and heating
› Incorporates **VRV IV standards & technologies** such as Variable Refrigerant temperature and continuous heating
› Most extended and compact range of BS boxes









p.176
p.246

FBQ-D / FXSQ-A - Concealed ceiling unit with medium ESP

› Optimum **comfort** guaranteed no matter the length of ductwork or type of grilles
› **Lowest** built-in **height** in the market
› **Lower sound** levels
› External static pressure up to 150Pa
› **Automatic air flow adjustment** function
› **Reduced energy consumption** thanks to DC fan motor
› Air suction direction can be altered for flexible installation






p.190
p.252

FNQ-A/ FXNQ-A- Concealed floor standing unit

› Designed to be **concealed** in floors or walls
› Ideal for installation in offices, hotel and residential applications
› Can even be installed underneath a window
› Requires very **little installation space** as the depth of the unit is only 200mm
› **High ESP** allows flexible installation
› The connecting port faces downward, eliminating the need to attach auxiliary piping



p.265

Extension of the range of air handling unit connection


› Complete **plug & play** solution including AHU, ERQ or VRV condensing unit and all unit control (EKEQ, EKEXV, DDC controller) factory mounted and configured
› Extension of the range of expansion valves with 400 (55,0 kW) and 500 (69,3 kW) models to allow bigger applications
› Addition of w-control: Control of air temperature (discharge temperature, suction temperature, room temperature) via any DDC controller, without reprogramming



p.417

BRC2/3E52A - Simplified wired remote control for hotel applications

› Symbol driven interface for **intuitive control**
› Functions restricted to basic **customer needs**
› **Energy saving** thanks key card, window contact integration and set point limitation
› Flat backpanel for **easy installation**
› 2 versions available:
  • Heat pump type: temperature, fan speed, ON/OFF
  • Heat recovery type: temperature, mode, fan speed, ON/OFF



p.428

EKMBDXA – DIII-net modbus gateway

› **Integrated control** system for seamless connection between split, Sky Air, VRV, chillers and AHU and BMS systems
› Communication via **Modbus** RS485 protocol
› Detailed **monitoring** and **control** of the VRV total solution
› Easy and **fast installation** via DIII-net protocol

p.318

EWAD-TZ
Air cooled inverter screw chiller

› **High efficiencies both at full load and part load**: EER up to 3.57 and ESEER up to 5.73
› Rapid **return on investment**
› **Perfect comfort** level
› **Compact design**
› **Lowest sound** levels
› Unrivaled and proven **reliability**



p.327

SEHVX-AAW+SERHQ-AAW1
Air cooled scroll inverter heat pump, split version

› **Hydronic module for indoor installation** eliminating the need for glycol
› **Ideal for colder climates** as the lack of glycol will allow for high efficiencies
› **Compact dimensions** and **limited pipework** allow for installation in very restricted spaces
› **Easy transportation** as separate units will fit in an elevator



p.386

D-AHU Compact
High-end air handling unit solution with heat recovery

› **Predifined** sizes
› **Plug & Play** concept
› EC fan technology
› **High efficiency** heat wheel
› Compact **design**
› Innovative **controls**



p.410

CCU/SCU
Ideal solution for small food retailers

› Micro channel heat exchanger
› Improved accessibility: **Hinged doors**
› **Efficient** compressor technology
› Plug and play solution
› Compliant to **Eco-design**





Why choose
R32 refrigerant?

Daikin is renowned for its pioneering approach to product development. As part of its commitment to the environment, Daikin aims to develop systems that improve comfort levels while having low environmental impact.


A key factor is the use of refrigerants, assessed on following criteria: Global Warming Potential (GWP), energy efficiency and natural resource efficiency. R32 has a GWP of 675, compared with R410A's GWP of 2,088, a reduction of 68%. R32 products can also achieve higher efficiency levels both in part load and full load conditions and R32 is a single component refrigerant, which makes it easy to recycle.

Wide range of R32 units available

In 2013, R32 was introduced by Daikin with the new Ururu Sarara range.
From 2015 onwards, also Daikin Emura and the FTXM-K are offered with R32 refrigerant.

Lowest environmental impact

SEER AND SCOP up to A+++
› Low GWP refrigerant R32 **R-32**



Replacement day will come... Why wait?



Service and maintenance with R-22 will be prohibited after january 1st, 2015, meaning repairs will be impossible to R-22 systems. Avoid unexpected downtime for your customers and replace these systems now!

Installer benefits

Less installation time

Tackle more projects in less time thanks to **faster installation**. It is more profitable than replacing the full system with new piping.

Lower installation costs

Reducing installation costs enables you to offer customers the most **cost-effective** solution and improve your competitive edge.

Replace competitor systems

It is a trouble-free replacement solution for Daikin systems and for systems made by other manufacturers.

Optimize your business


A simple solution for replacement technology enables you **to handle more projects** for more customers in less time and offer them the best price! Everybody gains.

Customer benefits

Save on running costs

Comparison based on EER

(efficiency of a residential product in cooling mode)



Comparison based on SEER

(efficiency of a residential product according to current seasonal legislation of a product in cooling mode)



No disturbance

Re-use your **existing piping** ensuring a quick and quality replacement allowing work to be done without affecting your comfort or business

Upgrade your comfort

Upgrade your comfort with cutting-edge design, low noise levels, wifi controls and more…



Seasonal efficiency, smart use of energy

The EU wants to make people aware of what units are consuming and ban non-efficient products from the market. Seasonal efficient units reflect the standardised conditions you can expect over an entire heating and cooling season. The standard came into force in January 2013 for air-to-air heat pumps under 12 kW.

From September 2015 onwards, not only air-to-air heat pumps but also heating systems like heat pumps, combustion, domestic hot water tanks or any kind of combination, will receive an energy label to help the customer to make the most efficient choice.

Today, Daikin is leading the way towards more efficient and cost-effective comfort solutions. All Daikin products – residential and commercial as well as industrial – are seasonal efficient, they all reduce energy and costs in a smart way.



SEASONAL EFFICIENCY
Smart use of energy

Find out more on www.daikin.eu

DAIKIN

Seasonal efficiency,


Smart use of energy

Challenging 20-20-20 environmental targets with Europe's energy label

The European Commission has set challenging targets for improving energy efficiency in the EU. These so-called 20-20-20 targets aim at a 20% reduction in CO_2 emissions, 20% share of renewable energy and a 20% reduction in the use of primary energy, all by the year 2020. To realise these objectives, Europe issued the Eco-Design Directive [2009/125/EC]. This sets minimum efficiency requirements for energy related products.

Air-to-Air heat pumps

Since 2013, all air conditioners and air-to-air heat pumps under 12 kW are in scope of this Eco-Design Directive. Products unable to comply with the minimum efficiency requirement (such as non-inverter air conditioners) will lose their CE marking and thus may no longer be sold in the European Union.



To inform consumers concerning these new energy performance standards, Europe also introduced a new energy label. The former European energy label, introduced in 1992, has had its effect. Consumers were able to compare and make purchasing decisions based on uniform labelling criteria. The new label that came into force on 1 January 2013 allows end-users to make even better informed choices, since seasonal efficiency reflects air conditioner efficiency over an entire season.

The energy label includes multiple classifications from A+++ to D reflected in colour shadings ranging from dark green (most energy efficient) to red (least efficient). Information on the label includes not only the new seasonal efficiency ratings for heating (SCOP) and cooling (SEER), but also annual energy consumption and sound levels.

Heating systems

From September 2015 onwards, space heaters, combi heaters (Lot 1) and domestic hot water heaters (Lot 2) will also have to comply with these 20-20-20 targets. This will give the opportunity to the end user to choose the most efficient heating system for his specific solution by for example comparing oil boilers with air-to-water heat pumps.

Next to the legally required labels, Daikin will offer full support to its network to implement the new labels into the market.

Daikin leading the way to seasonal efficiency

SEASONAL EFFICIENCY
Smart use of energy

While the challenges of Eco-Design were immense, Daikin resolutely chose for early implementation of this new legislation. Already in 2010, Daikin launched a new light commercial range fully optimised for seasonal efficiency. The Seasonal Smart series in this range in fact immediately complied with the very challenging 2014 minimum requirements. Today Daikin is proud to indicate the seasonal performance of its entire residential and light commercial range up to 12 kW.

Although legislation for heating will only come into force from September 2015 onwards, Daikin is already preparing their units and communication tools to be ahead of legislation again.

Have a question, looking for specific software applications, need detailed product information or looking for any other marketing tools? This overview gives you an idea of what we can offer …

Mini sites

Some products need slightly more attention than others. That's why we have developed mini sites. These sites provide all information (specifications, video, animation, drawings,…) related to one specific topic.
Below you can find some examples of minisites, which can easily be found on our website.

For your home:


› Daikin Altherma hybrid heatpump
› Daikin Emura

Commercial:

› Fully flat cassette
› Round flow cassette
› VRV IV
› R22 replacement

Industrial:

› EWAD-TZ
› ZEAS



Extranet

The Daikin extranet is a dedicated area with limited access for professionals in HVAC-R. It offers 24/7 access to the most up to date information, such as technical and commercial documentation, e-data, selection software, training sessions, webshop, etc.

No account yet? Visit:

http://www.daikineurope.com/business-partners/index.jsp



There's an app for that

Daikin Europe offers you a variety of building modelling, selection, simulation and quotation software tools to support your sales. Please check out http://www.daikineurope.com/support-and-manuals/software-downloads/index.jsp or contact your local sales representative to learn more about them.



Pure air

Because Daikin cares

MC70L

The streamer technology air purifier, a blend of new technology, improved performance, and ultra quiet operation, is designed to care for you by unobtrusively providing **purified air** to produce a healthy home environment. Purified air improves the perception of **comfort** and, by **removing** and destroying **contaminants** and **odours**, the streamer technology air purifier also plays an essential role for those who suffer from **asthma** or **allergies**. These efforts place the streamer technology air purifier among the best residential air purifiers on the market today.

Three times purification, a good deed for your health

Pollen, dust and pet hair are just some of the potential causes of allergies, asthma and respiratory problems. A Daikin air purifier cleans the air and relieves you of these troubles thanks to a three-part operation:

- allergen removal
- virus and bacteria removal
- odour removal


What is the Daikin streamer technology ?

"Streamer Discharge" is a type of plasma discharge in which high speed electrons capable of **oxidative decomposition** are generated. It has the ability to **eliminate bacteria** and **mould** as well as hazardous **chemical substances** and **allergens**, etc. Compared to standard plasma discharge (glow discharge), the discharge range of Daikin's Streamer Discharge is wider, which makes it easier for electrons to collide with oxygen and nitrogen in the air. This enables high speed electrons to be generated three dimensionally over a wide area, which results in an oxidative decomposition speed that is over 1,000 times greater with the same electrical power. Daikin's Streamer Discharge technology has proven successful in stably generating high speed electrons, a feat that has been considered difficult up to now.

Main specifications

Daikin has already received great praise for its air purifiers: a British Allergy Foundation seal of approval and the TÜV Nord test mark confirm the efficiency of our units.

Six-layer powerful decomposition and removal configuration



1 High-speed electrons are discharged that enable decomposition and removal
Streamer Discharge unit

2 Dust is captured. Bacteria and allergens are removed
Prefilter

3 Dust and pollen are electrically charged and then sent to the filter
Plasma ionizer

4 Dust and pollen are absorbed by the electrically charged filter
Electrostatic dust collection filter (front of pleated dust collection filter)

5 Odours and viruses are kept under control by photocatalyst
Titanium apatite filter (back of pleated dust collection filter)

6 Formaldehyde and odours are decomposed
Deodorising catalyst filter

- Stylish design
- Improved performance
- Unprecedented comfort
- Super quiet operation
- Easy to maintain
- Portable
- No installation

THE BRITISH ALLERGY FOUNDATION SEAL OF APPROVAL

STREAMER



Indoor unit					MC70L
Applicable room area				m^2	46
Dimensions	Unit	HeightxWidthxDepth		mm	576x403x241
Weight	Unit			kg	8.5
Casing	Colour				White
Fan	Type				Multi Blade Fan (Sirocco fan with shroud assembly)
	Air flow rate	Air purifying operation	Turbo/High/ Medium/Low/ Silent	m^3/h	420/285/210/130/55
Sound pressure level	Air purifying operation	Turbo/High/Medium/Low/Silent		dBA	48.0/39.0/32.0/24.0/16.0
Air purifying operation	Power input	Turbo/H/M/L/Silent		kW	0.065/0.026/0.016/0.010/0.007
Deodorizing method					Flash streamer / Titanium apatite photocatalytic filter / Deodorising catalyst
Bacteria filtering method					Flash streamer / Titanium apatite photocatalytic filter
Dust collecting method					Plasma ionizer / Electrostatic dust collection filter
Sign	Item	01/02/03/04/05/06/07/08/09/10/11			Dust: 3 stages/Odour: 3 stages/Automatic operation (LL-H)/Airflow rate (LL/L/M/H)/Turbo mode (HH)/Anti-pollen mode/Sleep mode/Lock (Anti-tamper)/Off timer (1.2.4h)/Maintenance: Filter replacement/Maintenance: Cleaning of ionization/streamer
Power supply	Phase/Voltage			V	1~/220-240/220-230



Humidification and purification in one


MCK75J

There are many substances in the air you breathe such as allergen, bacteria, virus and tobacco smoke, which causes your health to suffer. Above all things, dryness is especially a big issue during wintertime. Daikin Ururu Air Purifier **purifies and moisturizes** the air inside your home and relieves the effects of dry air. Just fill the 4l tank occasionally and it will humidify your room with a maximum volume of 600ml/h. This useful and innovative function stems from the incorporation of a slim line water tank and combined water wheel and vaporisation filter assembly.

- Humidification thanks to the slim water tank
- Air purification

How does the humidification function work?

Water in the tank flows into the receiver tray housing the water wheel, which lifts the water as it rotates and releases it onto the filter. Air blown onto the filter, absorbs its moisture and discharges it into the room as humidification.




Daikin has already received great praise for its air purifiers: the Daikin TüV award confirms the efficiency of this unit.

Electrostatic dust collection filter
Positively charged dust and pollen are adsorbed by the negatively charged filter.

Flash Streamer
High-speed electrons are generated by the Flash Streamer. These electrons powerfully break down odours and formaldehyde.

Titanium Apatite Photocatalytic Filter
Odour, bacteria and viruses are adsorbed and decomposed.

Deodorising catalyst
Odours are adsorbed and broken down before the air is returned into the room.



Pre-filter (with catechin)
Removes large dust particles and pet hairs.

Plasma ionizer
Dust and pollen are positively charged and sent to the electrostatic filter.

Flash Streamer unit

How does the filter work?


Daikin Ururu Air Purifier also removes efficiently allergens (e.g. pollen, house dust mites, dust, etc.), bacteria and viruses. Additionally, it has a high deodorizing efficiency; it eliminates efficiently tobacco smoke whilst decomposing other smells. It quickly collects particles and breaks them down rapidly. Its quiet operation makes it ideal for quiet nights. The unit includes seven pleated filters (one for immediate use and 6 spares).

flash streamer ONLY BY DAIKIN

Ururu



Indoor unit					MCK75J
Application					Floor standing type
Applicable room area				m^2	46
Dimensions	Unit	HeightxWidthxDepth		mm	590x395x268
Weight	Unit			kg	11.0
Casing	Colour				Black (N1) (Panel colour: silver)
Fan	Type				Multi Blade Fan (Sirocco fan with shroud assembly)
	Air flow rate	Air purifying operation	Turbo/High/Medium/Low/Silent	m^3/h	450/330/240/150/60
		Humidifying operation	Turbo/High/Medium/Low/Silent	m^3/h	450/330/240/150/120
Sound pressure level	Air purifying operation	Turbo/High/Medium/Low/Silent		dBA	50.0/43.0/36.0/26.0/17.0
	Humidifying operation	Turbo/High/Medium/Low/Silent		dBA	50/43/36/26/23
Humidifying operation	Power input	Turbo/H/M/L/Silent		kW	0.084/0.037/0.020/0.013/0.012
	Humidification	Turbo/High/Medium/Low/Silent		ml/h	600/470/370/290/240
	Water tank capacity			l	4.0
Air purifying operation	Power input	Turbo/H/M/L/Silent		kW	0.081/0.035/0.018/0.011/0.008
Deodorizing method					Flash streamer / Titanium apatite photocatalytic filter / Deodorising catalyst
Dust collecting method					Plasma ionizer / Electrostatic dust collection filter
Sign	Item	01			Dust: 3 stages / Odour: 3 stages / Air flow rate: auto/LL/L/M/H, Turbo mode HH, anti-pollen mode / Off timer: 1/4/8h / Cleaning: ionization/streamer
Power supply	Name/Phase/Frequency/Voltage			Hz/V	VM/1~/50/60/220-240/220-230
Type					Humidifying air purifier



Daikin offers you all types of **energy-efficient** heating solutions with **low CO_2 emissions,** whether you need a heating system for a replacement project or a new house. You can choose between different technologies based on the requirements of your customer: **air to water** heat pumps, **ground to water** heat pumps, **hybrid** technology and **gas condensing** technology.

Heating

Why choose a Daikin heating system? 18

Products overview 22

Combination tables 24

Daikin Altherma hybrid heat pump 26
EHYHBH-AV32/EHYKOMB-AA / EVLQ-CV3 28
EHYHBX-AV3/EHYKOMB-AA / EVLQ-CV3 29

Daikin Altherma ground source heat pump 31
EGSQH-A9W 31


Daikin Altherma low temperature 32
NEW EHSH-A / ERLQ-CV3/W1 36
NEW EHSHB-A / ERLQ-CV3/W1 37
NEW EHSX-A / ERLQ-CV3/W1 38
NEW EHSXB-A / ERLQ-CV3/W1 39
NEW EHVH-CB / ERLQ-CV3/W1 40
NEW EHVH-CB / ERHQ-BV3/W1 41
NEW EHVX-CB / ERLQ-CV3/CW1 42
NEW EHVX-CB / ERHQ-BV3/BW1 43
NEW EHBH-CB / ERLQ-CV3/CW1 44
NEW EHBH-CB / ERHQ-BV3/BW1 45
NEW EHBX-CB / ERLQ-CV3/CW1 46
NEW EHBX-CB / ERHQ-BV3/BW1 47
NEW EBHQ-BBV3 / EKCB(H/X)-BC 49
NEW EB(L/H)Q-BB6V3/W1 50
ED(L/H)Q-BB6V3/W1 51
Domestic hot water tanks 52
EKHWP-B 52
EKHWS-B 53
EKHWE-A 53
Solar connection 54
EKSRPS 54
EKSOLHW 54
EKSR3P 54
EKS(V/H)-P 55
Room thermostat 56
EKRTR 56
EKTRW 56
Daikin heat pump convector 57
FWXV-A 57

Daikin Altherma high temperature split 58
EKHBRD-AC / ER(R/S)Q-A 60
EKHBRD-AC / EMRQ-A 60
Domestic hot water tanks 61
EKHTS-AC 61
EKHWP-B 62
Solar connection 63
EKS(H/V)-P 63
EKSRPS 63

Daikin Altherma Flex Type 64
EKHVM(R/Y)D-A 65
EKHBRD-AC 66
EMRQ-A 67
Domestic hot water tanks 68
EKHTS-AC 68
EKHWP-B 68
Daikin heat pump convector 69
FWXV-A 69

Gas condensing boiler 70
EKOMB(G)-A 71

For more information on Options & Accessories, please refer to page 440 of this catalogue.



Heating all-in-one Comfort for residential & commercial applications

Why choose a Daikin heating system?


- More than **50 years of experience** in heat pumps
- Innovative heating technologies to **reduce running costs** and optimise renewable energy usage
- Research and development **in Europe for Europe**
- A solution for any application
- Combinable with **all kinds of heat emitters**

Innovative heating technologies to optimise renewable energy usage

Air to water technology: extracting heat from the outside air
› Guaranteed heating capacity down to -25°C: no need to worry in winter time
› Solar connection possible for domestic hot water support to optimise renewable energy use

Hybrid technology: gas condensing technology combined with air-to-water technology
› Most economical operation mode is selected depending on energy prices, outdoor temperature and internal heat load
› Optimisation of both technologies









A solution for any application

Residential applications
› New built
› Low energy houses
› Renovation of complete heating system
› Renovation without changing radiators/piping
› Bivalent solution

Commercial applications
› Apartments
› Hotels
› Restaurants
› Spas and leisure

Combinable with all kinds of heat emitters

Depending on the needs of your customer, you can select a system combinable with
› Under floor heating
› Heat pump convectors
› Low temperature radiators
› High temperature radiators (up to 80°C)

Ground to water technology:
extracting heat from the ground
› Ideal for climates where the average winter ambient temperature drops below 3°C
› High seasonal efficiency thanks to stable underground temperatures

Gas condensing technology:
› Low costs for BOTH heating and hot water thanks to new dual heat exchanger
› Easy installation in minimum space by using our optional pre-assembled B-pack which contains all the components for the functional installation in one module and fits behind the boiler

Optimal comfort
… all combined into one system

› Heating
› Domestic hot water with optional solar support
› Cooling
› Easy control




EHVH(X)-CB


EBHQ-BB


ERLQ-CV3




EHBH(X)-CB



EGSQH-A9W


EKOMB(G)-A


EKHBRD-ACV1/Y1

Products overview

	Hybrid	Ground source	Low temperature split
			
Heating application	› Ideal for new houses or replacement of a gas boiler	› Ideal for new houses or replacement of a ground source heat pump	› ideal for new houses, low energy houses or together with an existing boiler (bivalent)
Installation	› 1 indoor unit + 1 gas condensing boiler › 1 outdoor unit	› 1 indoor unit	› 1 indoor unit › 1 outdoor unit
Connectable heat emitters	› Under floor heating › Low and high temperature radiators	› Low and high temperature radiators	› Under floor heating › Low temperature radiators › Fan coil units › Heat pump convector
Combinable with	› Domestic hot water › Cooling › Solar connection for hot water production	› Domestic hot water	› Domestic hot water › Cooling › Solar connection for hot water production

Daikin Altherma heat pumps			Combustion
Air to water			Gas condensing boiler
Low temperature monobloc	High temperature split	Flex Type	
			
	› Ideal for replacement of a traditional boiler	› Ideal for large hot water and heating requirements in › Apartments › Collective housing › Hotels › Fitness › Spa › Schools › Hospitals › Libraries	› Ideal for replacement of and existing gas boiler
› 1 outdoor unit	› 1 indoor unit › 1 outdoor unit	› Several indoor units › 1 or more outdoor units	› 1 indoor unit
	› High temperature radiators	› Under floor heating › Low temperature radiators › Fan coil units › Heat pump convector	› Under floor heating › Radiators
	› Domestic hot water › Solar connection for hot water production	› Domestic hot water › Cooling (Heat recovery)	› Domestic hot water

Combination tables

Daikin Altherma hybrid heat pump

		Indoor			
		Heat pump module			Gas condensing boiler
		EHYHBH-AV32 heating only		EHYHBX-AV3 heat pump	EHYKOMB-AA2[1] EHYKOMB-AA3[2]
Outdoor		05	08	08	33
EVLQ-CV3	05	x			x
	08		x	x	x

(1) applicable for Germany, Belgium, France, Italy, United Kingdom, Spain, Netherlands, Ireland, Switzerland, Malta

(2) Applicable for Bulgaria, Bosnia Herzegovina, Croatia, Hungary, Slovakia, Slovenia, Portugal, Greece, Cyprus, Poland, Turkey, Lithuania, Latvia

Daikin Altherma low temperature split

			Outdoor						Domestic hot water tank optional			
		Down to -20°C outdoor temp.				ERHQ-BV3 ERHQ-BW1	ERHQ-BV3 ERHQ-BW1	ERHQ-BV3 ERHQ-BW1	EKHWP-B		EKHWS-B	EKHWE-A
		Down to -25°C outdoor temp.	ERLQ-CV3	ERLQ-CV3	ERLQ-CV3	ERLQ-CV3 ERLQ-CW1	ERLQ-CV3 ERLQ-CW1	ERLQ-CV3 ERLQ-CW1				
Indoor		Range	004	006	008	011	014	016	300	500	150-200-300	150-200-300
Wall mounted	EHBH-CB	04	heating only	—		—			unpressurised hot water + solar	—	hot water + pressurised solar (opt.)	
		08	—	heating only								
		16		—		heating only			hot water + unpressurised solar			
	EHBX-CB	04	heating & cooling	—		—			hot water + unpressurised solar	—		
		08	—	heating & cooling								
		16				heating & cooling			hot water + unpressurised solar			
Floor standing with integrated domestic hot water tank	EHVH-CB	04	heating & hot water	—		—			domestic hot water tank is integrated in the indoor unit			
		08	—	heating & hot water								
		16		—		heating & hot water						
	EHVX-CB	04	heating, cooling & hot water	—		—						
		08	—	heating, cooling & hot water								
		16		—		heating, cooling & hot water						
Floor standing with integrated solar supported domestic hot water tank	EHSH-A	04	heating, cooling & hot water with (un)pressurised solar	—		—						
		08	—									
		16				heating, cooling & hot water with (un)pressurised solar (ERLQ only)						
	EHSX-A	04	heating, cooling & hot water with (un)pressurised solar	—		—						
		08	—	heating, cooling & hot water with unpressurised solar								
		16		—		heating, cooling & hot water with (un)pressurised solar (ERLQ only)						
	EHSHB-A bivalent	04	heating, cooling & hot water with (un)pressurised solar	—		—						
		08	—									
		16				heating, cooling & hot water with unpressurised solar (ERLQ only)						
	EHSXB-A bivalent	04	heating, cooling & hot water with pressurised solar			—						
		08	—	heating, cooling & hot water with pressurised solar								
		16		—		heating, cooling & hot water with (un)pressurised solar (ERLQ only)						

Daikin Altherma low temperature monobloc

	Monobloc			Domestic hot water tank optional			
Down to -20°C outdoor temp.		**EBLQ-BB6V3 EBLQ-BB6W1**	**EDLQ-BB6V3 EDLQ-BB6W1**	**EKHWP-B**		**EKHWS-B**	**EKHWE-A**
Down to -25°C outdoor temp.	**EBHQ-BV3 EKCBH(X)-BCV3**	**EBHQ-BB6V3 EVHQ-BB6W1**	**EDHQ-BB6V3 EDHQ-BB6W1**	**300**	**500**	**150-200-300**	**150-200-300**
006	Heating only (EKCBH) heating & cooling (EKCBX)	—	—	hot water + unpressurised solar		hot water + pressurised solar (opt.)	
008		—	—				
011	—	heating & cooling	heating only		hot water + unpressurised solar		
014	—						
016	—						

Daikin Altherma high temperature split

			Outdoor								Domestic hot water tank optional		
			ERRQ-A ERSQ-A	**ERRQ-A ERSQ-A**	**ERRQ-A ERSQ-A**	**EMRQ-A**	**EMRQ-A**	**EMRQ-A**	**EMRQ-A**	**EMRQ-A**	**EKHWP-B**	**EKHTS-AC**	**EKHWP-A**
Indoor		**Range**	011	014	016	8	10	12	14	16	300-500	200-260	300-500
Floor standing	EKHBRD-AC	011	heating only								hot water + unpressurised solar	hot water	hot water + solar (opt.)
		014											
		016											

Daikin Altherma Flex Type

			Outdoor					Domestic hot water tank optional	
			EMRQ-A	**EMRQ-A**	**EMRQ-A**	**EMRQ-A**	**EMRQ-A**	**EKHWP-B**	**EKHTS-AC**
Indoor		**Range**	8	10	12	14	16	300-500	200-260
Floor standing	EKHVMRD-A	50	heating only					hot water + unpressurised solar	hot water
		80							
	EKHVMYD-A	50	heating & cooling						
		80							
	EKHBRD-AC	011	heating only						
		014							
		016							



Daikin Altherma hybrid heat pump, the natural combination

Why choose Daikin Altherma hybrid heat pump?

- **Low running costs** for heating and domestic hot water compared to traditional boilers
- Low investment cost
- **Ideal for renovation** applications with 27 kW gas boiler and 5 or 7 kW heat pump
- Easy and fast installation




Gas condensing boiler



Heat pump indoor unit

Energy prices & Efficiency

MOST ECONOMICAL MODE
heat pump only
hybrid mode
gas only



Domestic hot water

Low running costs

1. Space heating
Daikin Altherma hybrid heat pump smartly chooses between the heat pump and/or the gas boiler, possibly in simultaneous operation based on
› energy prices
› outdoor temperature
› the internal heat load
always selecting the most economical mode to operate.

2. Domestic hot water: heated using gas condensing technology
› Efficiency increase of up to 10-15% compared to traditional gas condensing boilers thanks to a special dual heat exchanger:
› cold tap water flows directly into the heat exchanger
› optimal and continuous condensing of the flue gases during domestic hot water preparation

Marketing tools

› Visit our extranet: go to
extranet.daikineurope.com > Document library
› Visit the website:
http://www.daikineurope.com//hybrid



Low investment cost

› No need to replace the existing radiators
(up to 80°C) and pipe work
› Compact dimensions: space needed for the new
system is very similar to that of an existing system

Ideal for renovation applications

› All heat loads are covered up to 27 kW

Easy and fast installation: 3 components

› Heat pump outdoor unit
› Heat pump indoor unit
› Gas condensing boiler


Case Study

Replacing a gas boiler with a Daikin Altherma hybrid heat pump means saving on running costs for both space heating and the domestic hot water supply.
A running cost comparison is made based on below parameters for a typical Belgian winter.
Thanks to the hybrid principle, the most cost-efficient operation will be used no matter what the ambient outdoor temperature is.

Conditions

Heat load	16 kW
Design temperature	-8°C
Space heating off temperature	16°C
Maximum water temperature	60°C
Minimum water temperature	38°C
Gas price	0.070 €/kWh
Electricity price (day)	0.237 €/kWh
Electricity price (night)	0.152 €/kWh
Total space heating requirement	19,500 kWh
Total DHW heating requirement (4 persons)	3,000 kWh

Heat consumption during winter



A Low temperature zone 100% use of gas boiler
B Mid temperature zone
Heat pump + gas boiler
C High temperature zone 100% use of heat pump

Yearly savings: for space heating and domestic hot water

versus new gas condensing boiler **330 €/year**

-19%

versus existing gas condensing boiler **690 €/year**

-32%

Daikin Altherma hybrid heat pump

Hybrid technology combining gas and air to water heat pump for heating and hot water

› Depending on outdoor temperature, energy prices and internal heat load, Daikin Altherma hybrid heat pump always selects the most economical mode to operate
› Low investment cost: no need to replace the existing radiators (up to 80°C) and pipe work
› Provides sufficient heat in renovation applications as all heat loads are covered up to 27kW
› Easy and fast installation thanks to the compact dimensions and quick interconnections

Efficiency data				**EHYHBH + EVLQ**	**05AV32 + 05CV3**	**08AV32 + 08CV3**
Heating capacity	Min.			kW	1.80 (1) / 1.80 (2)	
	Nom.			kW	4.40 (1) / 4.03 (2)	7.40 (1) / 6.89 (2)
	Max.			kW	5.12 (1) / 4.90 (2)	10.02 (1) / 9.53 (2)
Power input	Heating	Nom.		kW	0.87 (1) / 1.13 (2)	1.66 (1) / 2.01 (2)
COP					5.04 (1) / 3.58 (2)	4.45 (1) / 3.42 (2)

Indoor Unit				**EHYHBH**	**05AV32**	**08AV32**	**EHYKOMB33A2/3**
Gas	Consumption (G20)	Min-Max		m^3/h	-		0.78-3.39
	Consumption (G25)	Min-Max		m^3/h	-		0.90-3.93
	Consumption (G31)	Min-Max		m^3/h	-		0.30-1.29
	Connection	Diameter		mm	-		15
Central heating	Heat input Qn (net calorific value)	Nom	Min-Max	kW	-		7.6-27 (3)
	Output Pn at 80/60°C	Min-Nom		kW	-		8.2-26.6 (3)
	Efficiency	Net calorific value		%	-		98 (4) / 107 (5)
	Operation range	Min-Max		°C	-		15-80
Domestic hot water	Output	Min-Nom		kW	-		7.6-32.7
	Water flow	Rate	Nom	l/min	-		9.0 / 15.0
	Operation range	Min-Max		°C	-		40-65
Supply air	Connection			mm	-		100
	Concentric				-		Yes
Flue gas	Connection			mm	-		60
Casing	Colour				White		White - RAL9010
	Material				Precoated sheet metal		
Dimensions	Unit	HeightxWidthxDepth		mm	902x450x164		820x490x270
Weight	Unit			kg	30	31.2	36
Power supply	Phase/Frequency/Voltage			Hz/V	-		1~/50/230
Electrical power consumption	Max.			W	-		55
	Standby			W	-		2
Operation range	Heating	Ambient	Min.~Max.	°C	-25~25		-
		Water side	Min.~Max.	°C	25~55		-
Notes					-		For water circuit central heating, safety valve: refer to EHYHB*

Outdoor Unit				**EVLQ**	**05CV3**	**08CV3**
Dimensions	Unit	HeightxWidthxDepth		mm	735x832x307	
Weight	Unit			kg	54	56
Compressor	Quantity				1	
	Type				Hermetically sealed swing compressor	
Operation range	Heating	Min.~Max.		°CWB	-25~25	
Refrigerant	Type / GWP				R-410A / 2,087.5	
	Charge			kg	1.45	1.6
	Charge			TCO_2Eq	3.0	3.3
Sound power level	Heating	Nom.		dBA	61	62
Sound pressure level	Heating	Nom.		dBA	48	49
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V3/1~/50/230	
Current	Recommended fuses			A	20	

(1) Condition: Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition: Ta DB/WB 7°C/6°C - LWC 45°C (Dt=5°C) (3) Values according to G20 (4) 80/60 (5) 40/30 (30%)

Daikin Altherma hybrid heat pump

Hybrid technology combining gas and air to water heat pump for heating, **cooling** and hot water



EHYHBH/X-AV32 / EHYKOMB33A2/3



EVLQ-CV3

Efficiency data				EHYHBX + EVLQ
Heating capacity	Min.		kW	1.80 (1) / 1.80 (2)
	Nom.		kW	7.40 (1) / 6.89 (2)
	Max.		kW	10.02 (1) / 9.53 (2)
Cooling capacity	Min.		kW	2.50 (1) / 2.50 (2)
	Nom.		kW	6.86 (1) / 5.36 (2)
Power input	Heating	Nom.	kW	1.66 (1) / 2.01 (2)
	Cooling	Nom.	kW	2.01 (1) / 2.34 (2)
COP				4.45 (1) / 3.42 (2)
EER				3.42 (1) / 2.29 (2)

Indoor Unit				EHYHBX	08AV3	EHYKOMB33A2/3
Gas	Consumption (G20)	Min-Max		m^3/h	-	0.78-3.39
	Consumption (G25)	Min-Max		m^3/h	-	0.90-3.93
	Consumption (G31)	Min-Max		m^3/h	-	0.30-1.29
	Connection	Diameter		mm	-	15
Central heating	Heat input Qn (net calorific value)	Nom	Min-Max	kW	-	7.6-27 (3)
	Output Pn at 80/60°C	Min-Nom		kW	-	8.2-26.6 (3)
	Efficiency	Net calorific value		%	-	98 (4) / 107 (5)
	Operation range	Min-Max		°C	-	15~80
Domestic hot water	Output	Min-Nom		kW	-	7.6-32.7
	Water flow	Rate	Nom	l/min	-	9.0 / 15.0
	Operation range	Min/Max		°C	-	40~65
Supply air	Connection			mm	-	100
	Concentric				-	Yes
Flue gas	Connection			mm	-	60
Casing	Colour				White	White - RAL9010
	Material				Precoated sheet metal	
Dimensions	Unit	HeightxWidthxDepth		mm	902x450x164	820x490x270
Weight	Unit			kg	31.2	36
Power supply	Phase/Frequency/Voltage			Hz/V	-	1~/50/230
Electrical power consumption	Max.			W	-	55
	Standby			W	-	2
Operation range	Heating	Ambient	Min.~Max.	°C	-25~25	-
		Water side	Min.~Max.	°C	25~55	-
	Cooling	Ambient	Min.~Max.	°CDB	10~43	-
		Water side	Min.~Max.	°C	5~22	-
Notes					-	For water circuit central heating, safety valve: refer to EHYHB*

Outdoor Unit				EVLQ	08CV3
Dimensions	Unit	HeightxWidthxDepth		mm	735x832x307
Weight	Unit			kg	56
Compressor	Quantity				1
	Type				Hermetically sealed swing compressor
Operation range	Heating	Min.~Max.		°CWB	-25~25
Refrigerant	Type / GWP				R-410A / 2,087.5
	Charge			kg	1.6
	Charge			TCO_2Eq	3.3
Sound power level	Heating	Nom.		dBA	62
Sound pressure level	Heating	Nom.		dBA	49
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V3/1~/50/230
Current	Recommended fuses			A	20

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C)
(3) Values according to G20 (4) 80/60 (5) 40/30 (30%)



Daikin Altherma ground source heat pump

Why choose Daikin?

The simple answer is that it is more efficient than an on/off ground source heat pump. Due to high efficiencies resulting from our **inverter technology**, the Daikin Altherma ground source heat pump provides a **leading edge performance**.



Highest seasonal efficiency thanks to our inverter heat pump technology

The Daikin inverter heat pump technology has been shown to provide an increase in seasonal efficiency of up to 20% when compared to traditional on/off ground source heat pumps.
Higher brine temperatures during continuous compressor operation, in partial load conditions
Less back up heater operation thanks to the boosting of the inverter compressor frequency.

Quick and easy installation including a domestic hot water tank

Installation time is reduced up to 5 hours thanks to the compact designed unit that includes both the space heating and the brine expansion vessel.

Flexibility covering multiple house types

Providing a solution which can cover heat loads from 3-12kW means replacement of a 6 to 12 KW range is possible with one single unit. This is not only a flexible solution but also space saving.

No affected surroundings

Very limited outdoor space is required, except for the necessary space to prepare the excavation works.

Marketing tools

› Visit our extranet: http://bit.ly/1txOuwj
› Visit the website:
http://www.daikineurope.com/groundsource



Daikin Altherma ground source heat pump

Ground source heat pump for heating & hot water

- Ground source heat pump technology uses stable geothermal energy, unaffected by the outside temperature
- Highest seasonal efficiency thanks to our inverter heat pump technology
- Quick and easy installation thanks to factory-fitted piping on top of the unit and reduced overall weight
- Integrated indoor unit: all-in-one floor standing unit including the domestic hot water tank
- User interface with thermostat function for higher comfort, quick commissioning, easy servicing and energy management to control energy consumption and costs



EGSQH-A9W

Indoor Unit				**EGSQH**	**10S18A9W**
Heating capacity	Min.			kW	3.11 (1) / 2.47 (2)
	Nom.			kW	10.2 (1) / 9.29 (2)
	Max.			kW	13.0 (1) / 11.9 (2)
Power input	Nom.			kW	2.34 (1) / 2.82 (2)
COP					4.35 (1) / 3.29 (2)
Casing	Colour				White
	Material				Precoated sheet metal
Dimensions	Unit	HeightxWidthxDepth		mm	1,732x600x728
Weight	Unit			kg	210
Tank	Water volume			l	180
	Insulation	Heat loss		kWh/24h	1.36
	Corrosion protection				Anode
Operation range	Installation space	Min.~Max.		°C	5~30
	Brine side	Min.~Max.		°C	-5~20
	Heating	Water side	Min.~Max.	°C	24~60 (heat pump)/24-65 (heat pump + back up heater)
	Domestic hot water	Water side	Min.~Max.	°C	(25~55 (heatpump)/25~60 (back up heater)
Refrigerant	Type / GWP				R-410A / 2,087.5
	Charge			kg	1.8
	Charge			TCO_2Eq	3.8
Sound power level	Nom.			dBA	46
Sound pressure level	Nom.			dBA	32
Power supply	Name/Phase/Frequency/Voltage			Hz/V	9W/3~/50/400
Current	Recommended fuses			A	25

(1) EWB/LWB 0°C/-3°C - LWC 35°C (DT=5°C) (2) EWB/LWB 0°C/-3°C - LWC 45°C (DT=5°C)



Daikin Altherma low temperature
The natural choice

Why choose Daikin Altherma low temperature?

Daikin Altherma low temperature offers a wide range to adapt to your customer's needs.

- Ideal for **new builds**
- Heating, domestic hot water and cooling with optional solar support
- Capacities from 4 to 16 kW
- Combinable with **under floor heating**, heat pump convectors and low temperature radiators
- Easy control
- **Flexible solutions**: split floor standing, split wall mounted, monobloc

Daikin Altherma low temperature split


› **Best seasonal efficiencies providing the highest savings on running costs**
› **Perfect fit for new builds, as well as for low-energy houses**



Integrated heating and hot water unit, saving installation space and time
› All components and connections factory-made
› Very small installation footprint required
› Minimum electrical input with constant availability of hot water
› Model with integrated bi-zone kit available from spring 2015



Integrated heating and hot water unit with extended flexibility
› Solar support of domestic hot water with unpressurised (drain-back) and pressurised solar system
› Lightweight plastic tank with exceptional hygienic benefits
› Bivalent option: combinable with a secondary heat source
› App control possible



Wall mounted indoor unit with optional solar energy
The best solution in specific situations:
› Ideal when no domestic hot water is required
› Combinable with a separate domestic hot water tank when solar energy is preferred.

Daikin Altherma low temperature monobloc

› Everything combined in one outdoor
› Quick and easy installation as only water pipes run indoors from the outdoor unit
› Limited installation space required as only outdoor space is required
› Freeze protection of hydraulic parts

Marketing tools

› Visit the extranet: go to extranet.daikineurope.com > Document library
› Visit the website: www.daikineurope.com/minisite/daikin_altherma_lt/
› Download the software: http://www.daikineurope.com/binaries/daikin_alth_tcm524-234758.zip
› Calculate your energy savings: http://ecocalc.daikin.eu/



Eco-calculator



Case Study


Efficient partial-load operation is especially important for the temperature range where the highest heat output is required. Typically, 80% of the total heat output is required in an outdoor temperature range of -2°C to 10°C. Achieving high efficiencies in this temperature range, contributes strongly to high seasonal efficiencies.

› Largest part of heat output delivered at optimal efficiencies
› Less on/off operation when heat load becomes lower than the minimum capacity the heat pump can deliver, optimising efficiency and comfort
› Modulating range doubled vs standard air-to-water heat pumps
› New range delivers around 1kW additional in full-load condition at -7°C (+25%)


Typical application:

› Location: Paris
› Design temperature: -7°C
› Heat load: 7kW
› Heating off temperature: 16°C

Standard heat pump



Daikin Altherma



Resulting in the best possible effficiencies

heat load line
standard heat pump max capacity
standard heat pump min capacity
ERLQ006CAV3 max capacity
ERLQ006CAV3 min capacity

Integrated bi-zone

Optimum efficiency offering full flexibility in heat emitters

› Two different temperature zones can be automatically regulated by the same indoor unit

› Offers flexibility to the end user to combine different heat emitters
e.g. under floor heating and radiators while optimising the efficiency



Under floor heating at 35°C



Available spring 2015

Case study

Typical application

Ground floor: under floor heating
First floor: low temperature radiators

Required water temperature

› Under floor heating: 35°C
› Low temperature radiators: 45°C

Bi-zone principle

Daikin Altherma low temperature is set at the maximum required water temperature, i.e. 45°C. A double water circuit is connected to the indoor unit

› 45°C water circuit for radiators: immediate supply from the indoor unit
› 35°C water circuit for under floor heating: mixing valve between indoor and water circuit, that mixes 45°C with the return water in the system to lower the temperature.

If there is only demand from the under floor heating circuit, the leaving water temperature of the Daikin Altherma will be lowered to 35°C in order to increase the efficiency of the heat pump.

Daikin Altherma low temperature split

Floor standing air to water heat pump for heating and hot water with thermal solar support

- Integrated solar unit, maximising renewable energy and offering top comfort in heating and hot water
- Solar support of domestic hot water with unpressurised (drain-back) solar system
- Lightweight plastic tank with exceptional hygienic benefits
- App control possible for managing heating and hot water operation
- Outdoor unit extracts heat from the outdoor air, even at -25°C



Efficiency data				EHSH + ERLQ	04P30A + 004CV3	08P50A + 006CV3	08P30A + 006CV3	08P30A + 008CV3	08P50A + 008CV3	16P50A + 011CV3	16P50A + 011CW1	16P50A + 014CV3	16P50A + 014CW1	16P50A + 016CV3	16P50A + 016CW1
Heating capacity	Min.		kW		1.80 / 1.81	1.80 / 1.81	1.80 / 1.81	1.80 / 1.81	1.80 / 1.81	-					
	Nom.		kW		4.53 / 3.98 / 4.26 / 3.47	6.06 / 5.78 / 5.14 / 4.60	6.06 / 5.78 / 5.14 / 4.60	7.78 / 7.27 / 5.53 / 5.51	7.78 / 7.27 / 5.53 / 5.51	11.80 / 10.40 / 5.95 / 7.74	11.80 / 10.40 / 5.95 / 7.74	14.81 / 13.73 / 8.28 / 9.57	14.81 / 13.73 / 8.28 / 9.57	15.34 / 14.86 / 8.04 / 10.05	15.34 / 14.86 / 8.04 / 10.05
	Max.		kW		5.12 / 4.90	8.35 / 7.95	8.35 / 7.95	10.02 / 9.53	10.02 / 9.53	11.38 / 11.00	11.38 / 11.00	14.55 / 13.59	14.55 / 13.59	16.10 / 15.22	16.10 / 15.22
Power input	Heating	Nom.	kW		0.87 / 1.04 / 1.49 / 0.85	1.30 / 1.58 / 1.88 / 1.26	1.30 / 1.58 / 1.88 / 1.26	1.69 / 2.04 / 1.98 / 1.56	1.69 / 2.04 / 1.98 / 1.56	2.57 / 3.13 / 2.43 / 2.35	2.57 / 3.13 / 2.43 / 2.35	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93
		Max.	kW		1.12 / 1.44	1.99 / 2.32	1.99 / 2.32	2.54 / 2.96	2.54 / 2.96	2.64 / 3.25	2.64 / 3.25	3.43 / 4.22	3.43 / 4.22	3.83 / 4.71	3.83 / 4.71
COP					5.23 / 3.84 / 2.85 / 4.07	4.65 / 3.66 / 2.73 / 3.64	4.65 / 3.66 / 2.73 / 3.64	4.60 / 3.57 / 2.78 / 3.54	4.60 / 3.57 / 2.78 / 3.54	4.38 / 3.32 / 2.45 / 3.29	4.38 / 3.32 / 2.45 / 3.29	4.27 / 3.34 / 2.58 / 3.22	4.27 / 3.34 / 2.58 / 3.22	4.10 / 3.22 / 2.44 / 3.15	4.10 / 3.22 / 2.44 / 3.15

Indoor Unit				EHSH	04P30A	08P50A	08P30A	08P50A	16P50A
Casing	Colour				Traffic white (RAL9016) / Dark grey (RAL7011)				
	Material				Impact resistant polypropylene				
Dimensions	Unit	HeightxWidthxDepth	mm		1,945x615x595	1,945x790x790	1,945x615x595	1,945x790x790	
Weight	Unit		kg		87	114	87	114	116
Tank	Water volume		l		300	500	300	500	
	Maximum water temperature		°C		85				
Sound power level	Nom.		dBA		40				
Sound pressure level	Nom.		dBA		28				

Outdoor Unit				ERLQ	004CV3	006CV3	008CV3	011CV3	011CW1	014CV3	014CW1	016CV3	016CW1
Dimensions	Unit	HeightxWidthxDepth	mm		735x832x307			1,345x900x320					
Weight	Unit		kg		54	56		113	114	113	114	113	114
Compressor	Quantity				1								
	Type				Hermetically sealed swing compressor			Hermetically sealed scroll compressor					
Operation range	Heating	Min.~Max.	°CWB		-25~25			-25~35					
	Domestic hot water	Min.~Max.	°CDB		-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge		kg		1.45	1.6		3.4					
	Charge		TCO_2Eq		3.0	3.3		7.1					
Sound power level	Heating	Nom.	dBA		61		62	64				66	
Sound pressure level	Heating	Nom.	dBA		48		49	51				52	
Power supply	Name/Phase/Frequency/Voltage		Hz/V		V3/1~/50/230				W1/3N~/ 50/400	V3/1~/ 50/230	W1/3N~/ 50/400	V3/1~/ 50/230	W1/3N~/ 50/400
Current	Recommended fuses		A		20			40	20	40	20	40	20

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) EW 30°C; LW 35°C; ambient conditions: -7°CDB/-8°CWB (4) EW 30°C; LW 35°C; ambient conditions: 2°CDB/1°CWB

Daikin Altherma low temperature split

Floor standing air to water heat pump for bivalent heating and hot water with thermal solar support

› Bivalent system: combinable with a secondary heat source



EHSHB04-08P30A

EHSHB08-16P50A

ERLQ004-008CV3

Efficiency data				EHSHB + ERLQ	04P30A + 004CV3	08P30A + 006CV3	08P50A + 006CV3	08P30A + 008CV3	08P50A + 008CV3	16P50A + 011CV3	16P50A + 011CW1	16P50A + 014CV3	16P50A + 014CW1	16P50A + 016CV3	16P50A + 016CW1
Heating capacity	Min.		kW		1.80 / 1.81	1.80 / 1.81	1.80 / 1.81	1.80 / 1.81	1.80 / 1.81	-					
	Nom.		kW		4.53 / 3.98 / 4.26 / 3.47	6.06 / 5.78 / 5.14 / 4.60	6.06 / 5.78 / 5.14 / 4.60	7.78 / 7.27 / 5.53 / 5.51	7.78 / 7.27 / 5.53 / 5.51	11.80 / 10.40 / 5.95 / 7.74	11.80 / 10.40 / 5.95 / 7.74	14.81 / 13.73 / 8.28 / 9.57	14.81 / 13.73 / 8.28 / 9.57	15.34 / 14.86 / 8.04 / 10.05	15.34 / 14.86 / 8.04 / 10.05
	Max.		kW		5.12 / 4.90	8.35 / 7.95	8.35 / 7.95	10.02 / 9.53	10.02 / 9.53	11.38 / 11.00	11.38 / 11.00	14.55 / 13.59	14.55 / 13.59	16.10 / 15.22	16.10 / 15.22
Power input	Heating	Nom.	kW		0.87 / 1.04 / 1.49 / 0.85	1.30 / 1.58 / 1.88 / 1.26	1.30 / 1.58 / 1.88 / 1.26	1.69 / 2.04 / 1.98 / 1.56	1.69 / 2.04 / 1.98 / 1.56	2.57 / 3.13 / 2.43 / 2.35	2.57 / 3.13 / 2.43 / 2.35	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93
		Max.	kW		1.12 / 1.44	1.99 / 2.32	1.99 / 2.32	2.54 / 2.96	2.54 / 2.96	2.64 / 3.25	2.64 / 3.25	3.43 / 4.22	3.43 / 4.22	3.83 / 4.71	3.83 / 4.71
COP					5.23 / 3.84 / 2.85 / 4.07	4.65 / 3.66 / 2.73 / 3.64	4.65 / 3.66 / 2.73 / 3.64	4.60 / 3.57 / 2.78 / 3.54	4.60 / 3.57 / 2.78 / 3.54	4.38 / 3.32 / 2.45 / 3.29	4.38 / 3.32 / 2.45 / 3.29	4.27 / 3.34 / 2.58 / 3.22	4.27 / 3.34 / 2.58 / 3.22	4.10 / 3.22 / 2.44 / 3.15	4.10 / 3.22 / 2.44 / 3.15
EER					4.21 / 2.85	3.65 / 2.51	3.65 / 2.51	3.65 / 2.51	3.65 / 2.51	3.32 / 2.72	3.32 / 2.72	2.96 / 2.47	2.96 / 2.47	2.72 / 2.29	2.72 / 2.29

Indoor Unit				EHSHB	04P30A	08P30A	08P50A	08P30A	08P50A	16P50A
Casing	Colour				Traffic white (RAL9016) / Dark grey (RAL7011)					
	Material				Impact resistant polypropylene					
Dimensions	Unit	HeightxWidthxDepth	mm		1,945x615x595		1,945x790x790	1,945x615x595		1,945x790x790
Weight	Unit		kg		92		119	92	119	121
Tank	Water volume		l		300		500	300		500
	Maximum water temperature		°C					85		
Sound power level	Nom.		dBA					40		
Sound pressure level	Nom.		dBA					28		

Outdoor Unit				ERLQ	004CV3	006CV3	008CV3	011CV3	011CW1	014CV3	014CW1	016CV3	016CW1
Dimensions	Unit	HeightxWidthxDepth	mm		735x832x307			1,345x900x320					
Weight	Unit		kg		54	56		113	114	113	114	113	114
Compressor	Quantity				1								
	Type				Hermetically sealed swing compressor			Hermetically sealed scroll compressor					
Operation range	Heating	Min.~Max.	°CWB		-25~25			-25~35					
	Domestic hot water	Min.~Max.	°CDB		-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge		kg		1.45	1.6		3.4					
	Charge		TCO_2Eq		3.0	3.3		7.1					
Sound power level	Heating	Nom.	dBA		61		62	64				66	
Sound pressure level	Heating	Nom.	dBA		48		49	51				52	
Power supply	Name/Phase/Frequency/Voltage		Hz/V		V3/1~/50/230				W1/3N~/ 50/400	V3/1~/ 50/230	W1/3N~/ 50/400	V3/1~/ 50/230	W1/3N~/ 50/400
Current	Recommended fuses		A		20			40	20	40	20	40	20

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) EW 30°C; LW 35°C; ambient conditions: -7°CDB/-8°CWB (4) EW 30°C; LW 35°C; ambient conditions: 2°CDB/1°CWB

Daikin Altherma low temperature split

Floor standing air to water heat pump for heating, cooling and hot water with thermal solar support

- Integrated solar unit, maximising renewable energy and offering top comfort in heating, hot water and cooling
- Solar support of domestic hot water with unpressurised (drain-back) solar system
- Lightweight plastic tank with exceptional hygienic benefits
- App control possible for managing heating, hot water and cooling operation
- Outdoor unit extracts heat from the outdoor air, even at -25°C



EHSX04-08P30A



EHSX08-16P50A



ERLQ004-008CV3

Efficiency data				EHSX + ERLQ	04P30A + 004CV3	08P30A + 006CV3	08P50A + 006CV3	08P50A + 008CV3	08P50A + 008CV3	16P50A + 011CV3	16P50A + 011CW1	16P50A + 014CV3	16P50A + 014CW1	16P50A + 016CV3	16P50A + 016CW1
Heating capacity	Min.		kW		1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	-					
	Nom.		kW		4.53 (1) / 3.98 (2) / 4.26 (3) / 3.47 (4)	6.06 (1) / 5.78 (2) / 5.14 (3) / 4.60 (4)	6.06 (1) / 5.78 (2) / 5.14 (3) / 4.60 (4)	7.78 (1) / 7.27 (2) / 5.53 (3) / 5.51 (4)	7.78 (1) / 7.27 (2) / 5.53 (3) / 5.51 (4)	11.80 (1) / 10.40 (2) / 5.95 (3) / 7.74 (4)	11.80 (1) / 10.40 (2) / 5.95 (3) / 7.74 (4)	14.81 (1) / 13.73 (2) / 8.28 (3) / 9.57 (4)	14.81 (1) / 13.73 (2) / 8.28 (3) / 9.57 (4)	15.34 (1) / 14.86 (2) / 8.04 (3) / 10.05 (4)	15.34 (1) / 14.86 (2) / 8.04 (3) / 10.05 (4)
	Max.		kW		5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	10.02 (1) / 9.53 (2)	11.38 (1) / 11.00 (2)	11.38 (1) / 11.00 (2)	14.55 (1) / 13.59 (2)	14.55 (1) / 13.59 (2)	16.10 (1) / 15.22 (2)	16.10 (1) / 15.22 (2)
Cooling capacity	Min.		kW		2.0 (1) / 2.1 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	-	
	Nom.		kW		4.4 (1) / 4.0 (2)	5.2 (1) / 4.6 (2)	5.2 (1) / 4.6 (2)	5.2 (1) / 4.6 (2)	5.2 (1) / 4.6 (2)	15.1 (1) / 11.7 (2)	15.1 (1) / 11.7 (2)	16.1 (1) / 12.6 (2)	16.1 (1) / 12.6 (2)	16.8 (1) / 13.1 (2)	16.8 (1) / 13.1 (2)
	Max.		kW		5.9 (1) / 4.5 (2)	7.3 (1) / 5.5 (2)	7.3 (1) / 5.5 (2)	8.4 (1) / 6.4 (2)	8.4 (1) / 6.4 (2)	15.1 (1) / 11.7 (2)	15.1 (1) / 11.7 (2)	16.1 (1) / 12.6 (2)	16.1 (1) / 12.6 (2)	16.8 (1) / 13.1 (2)	16.8 (1) / 13.1 (2)
Power input	Heating	Nom.	kW		0.87 / 1.04 / 1.49 / 0.85	1.30 / 1.58 / 1.88 / 1.26	1.30 / 1.58 / 1.88 / 1.26	1.69 / 2.04 / 1.98 / 1.56	1.69 / 2.04 / 1.98 / 1.56	2.57 / 3.13 / 2.43 / 2.35	2.57 / 3.13 / 2.43 / 2.35	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93	3.42 / 4.07 / 3.17 / 2.93
		Max.	kW		1.12 (1) / 1.44 (2)	1.99 (1) / 2.32 (2)	1.99 (1) / 2.32 (2)	2.54 (1) / 2.96 (2)	2.54 (1) / 2.96 (2)	2.64 (1) / 3.25 (2)	2.64 (1) / 3.25 (2)	3.43 (1) / 4.22 (2)	3.43 (1) / 4.22 (2)	3.83 (1) / 4.71 (2)	3.83 (1) / 4.71 (2)
	Cooling	Nom.	kW		1.05 (1) / 1.41 (2)	1.43 (1) / 1.85 (2)	1.43 (1) / 1.85 (2)	1.43 (1) / 1.85 (2)	1.43 (1) / 1.85 (2)	4.55 (1) / 4.30 (2)	4.55 (1) / 4.30 (2)	5.44 (1) / 5.10 (2)	5.44 (1) / 5.10 (2)	6.18 (1) / 5.72 (2)	6.18 (1) / 5.72 (2)
		Max.	kW		1.86 (1) / 2.04 (2)	2.27 (1) / 2.51 (2)	2.27 (1) / 2.51 (2)	2.89 (1) / 3.20 (2)	2.89 (1) / 3.20 (2)	4.53 (1) / 4.31 (2)	4.53 (1) / 4.31 (2)	5.42 (1) / 5.09 (2)	5.42 (1) / 5.09 (2)	6.15 (1) / 5.74 (2)	6.15 (1) / 5.74 (2)
COP					5.23 (1) / 3.84 (2) / 2.85 (3) / 4.07 (4)	4.65 (1) / 3.66 (2) / 2.73 (3) / 3.64 (4)	4.65 (1) / 3.66 (2) / 2.73 (3) / 3.64 (4)	4.60 (1) / 3.57 (2) / 2.78 (3) / 3.54 (4)	4.60 (1) / 3.57 (2) / 2.78 (3) / 3.54 (4)	4.38 (1) / 3.32 (2) / 2.45 (3) / 3.29 (4)	4.38 (1) / 3.32 (2) / 2.45 (3) / 3.29 (4)	4.27 (1) / 3.34 (2) / 2.58 (3) / 3.22 (4)	4.27 (1) / 3.34 (2) / 2.58 (3) / 3.22 (4)	4.10 (1) / 3.22 (2) / 2.44 (3) / 3.15 (4)	4.10 (1) / 3.22 (2) / 2.44 (3) / 3.15 (4)
EER					4.21 (1) / 2.85 (2)	3.65 (1) / 2.51 (2)	3.65 (1) / 2.51 (2)	3.65 (1) / 2.51 (2)	3.65 (1) / 2.51 (2)	3.32 (1) / 2.72 (2)	3.32 (1) / 2.72 (2)	2.96 (1) / 2.47 (2)	2.96 (1) / 2.47 (2)	2.72 (1) / 2.29 (2)	2.72 (1) / 2.29 (2)

Indoor Unit				EHSX	04P30A	08P30A	08P50A	08P30A	08P50A	16P50A
Casing	Colour				Traffic white (RAL9016) / Dark grey (RAL7011)					
	Material				Impact resistant polypropylene					
Dimensions	Unit	HeightxWidthxDepth	mm		1,945x615x595		1,945x790x790	1,945x615x595		1,945x790x790
Weight	Unit		kg		87		114	87	114	116
Tank	Water volume		l		300		500	300		500
	Maximum water temperature		°C		85					
Sound power level	Nom.		dBA		40					
Sound pressure level	Nom.		dBA		28					

Outdoor Unit				ERLQ	004CV3	006CV3	008CV3	011CV3	011CW1	014CV3	014CW1	016CV3	016CW1
Dimensions	Unit	HeightxWidthxDepth	mm		735x832x307			1,345x900x320					
Weight	Unit		kg		54	56		113	114	113	114	113	114
Compressor	Quantity				1								
	Type				Hermetically sealed swing compressor			Hermetically sealed scroll compressor					
Operation range	Heating	Min.~Max.	°CWB		-25~25			-25~35					
	Cooling	Min.~Max.	°CDB		10~43			10.0~46.0	10~46	10.0~46.0	10~46	10.0~46.0	10~46
	Domestic hot water	Min.~Max.	°CDB		-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge		kg		1.45	1.6		3.4					
	Charge		TCO_2Eq		3.0	3.3		7.1					
Sound power level	Heating	Nom.	dBA		61		62	64				66	
	Cooling	Nom.	dBA		63			64		66		69	
Sound pressure level	Heating	Nom.	dBA		48		49	51				52	
	Cooling	Nom.	dBA	48	49		50	50		52		54	
Power supply	Name/Phase/Frequency/Voltage		Hz/V		V3/1~/50/230				W1/3N~/ 50/400	V3/1~/ 50/230	W1/3N~/ 50/400	V3/1~/50/230	W1/3N~/ 50/400
Current	Recommended fuses		A		20			40	20	40	20	40	20

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) EW 30°C; LW 35°C; ambient conditions: -7°CDB/-8°CWB (4) EW 30°C; LW 35°C; ambient conditions: 2°CDB/1°CWB

Daikin Altherma low temperature split

Floor standing air to water heat pump for bivalent heating, cooling and hot water with thermal solar support

› Bivalent system: combinable with a secondary heat source



EHSXB04-08P30A



EHSXB08-16P50A



ERLQ004-008CV3

Efficiency data				EHSXB + ERLQ	04P30A + 004CV3	08P30A + 006CV3	08P50A + 006CV3	08P30A + 008CV3	08P50A + 008CV3	16P50A + 011CV3	16P50A + 011CW1	16P50A + 014CV3	16P50A + 014CW1	16P50A + 016CV3	16P50A + 016CW1
Heating capacity	Min.		kW		1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	1.80 (1) / 1.81 (2)	-					
	Nom.		kW		4.53 (1) / 3.98 (2) / 4.26 (3) / 3.47 (4)	6.06 (1) / 5.78 (2) / 5.14 (3) / 4.60 (4)	6.06 (1) / 5.78 (2) / 5.14 (3) / 4.60 (4)	7.78 (1) / 7.27 (2) / 5.53 (3) / 5.51 (4)	7.78 (1) / 7.27 (2) / 5.53 (3) / 5.51 (4)	11.80 (1) / 10.40 (2) / 5.95 (3) / 7.74 (4)	11.80 (1) / 10.40 (2) / 5.95 (3) / 7.74 (4)	14.81 (1) / 13.73 (2) / 8.28 (3) / 9.57 (4)	14.81 (1) / 13.73 (2) / 8.28 (3) / 9.57 (4)	15.34 (1) / 14.86 (2) / 8.04 (3) / 10.05 (4)	15.34 (1) / 14.86 (2) / 8.04 (3) / 10.05 (4)
	Max.		kW		5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	10.02 (1) / 9.53 (2)	11.38 (1) / 11.00 (2)	11.38 (1) / 11.00 (2)	14.55 (1) / 13.59 (2)	14.55 (1) / 13.59 (2)	16.10 (1) / 15.22 (2)	16.10 (1) / 15.22 (2)
Cooling capacity	Min.		kW		2.0 (1) / 2.1 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	2.5 (1) / 2.6 (2)	-	
	Nom.		kW		4.4 (1) / 4.0 (2)	5.2 (1) / 4.6 (2)	5.2 (1) / 4.6 (2)	5.2 (1) / 4.6 (2)	5.2 (1) / 4.6 (2)	15.1 (1) / 11.7 (2)	15.1 (1) / 11.7 (2)	16.1 (1) / 12.6 (2)	16.1 (1) / 12.6 (2)	16.8 (1) / 13.1 (2)	16.8 (1) / 13.1 (2)
	Max.		kW		5.9 (1) / 4.5 (2)	7.3 (1) / 5.5 (2)	7.3 (1) / 5.5 (2)	8.4 (1) / 6.4 (2)	8.4 (1) / 6.4 (2)	15.1 (1) / 11.7 (2)	15.1 (1) / 11.7 (2)	16.1 (1) / 12.6 (2)	16.1 (1) / 12.6 (2)	16.8 (1) / 13.1 (2)	16.8 (1) / 13.1 (2)
Power input	Heating	Nom.	kW		0.87 (1) / 1.04 (2) / 1.49 (3) / 0.85 (4)	1.30 (1) / 1.58 (2) / 1.88 (3) / 1.26 (4)	1.30 (1) / 1.58 (2) / 1.88 (3) / 1.26 (4)	1.69 (1) / 2.04 (2) / 1.98 (3) / 1.56 (4)	1.69 (1) / 2.04 (2) / 1.98 (3) / 1.56 (4)	2.57 (1) / 3.13 (2) / 2.43 (3) / 2.35 (4)	2.57 (1) / 3.13 (2) / 2.43 (3) / 2.35 (4)	3.42 (1) / 4.07 (2) / 3.17 (3) / 2.93 (4)	3.42 (1) / 4.07 (2) / 3.17 (3) / 2.93 (4)	3.42 (1) / 4.07 (2) / 3.17 (3) / 2.93 (4)	3.42 (1) / 4.07 (2) / 3.17 (3) / 2.93 (4)
		Max.	kW		1.12 (1) / 1.44 (2)	1.99 (1) / 2.32 (2)	1.99 (1) / 2.32 (2)	2.54 (1) / 2.96 (2)	2.54 (1) / 2.96 (2)	2.64 (1) / 3.25 (2)	2.64 (1) / 3.25 (2)	3.43 (1) / 4.22 (2)	3.43 (1) / 4.22 (2)	3.83 (1) / 4.71 (2)	3.83 (1) / 4.71 (2)
	Cooling	Nom.	kW		1.05 (1) / 1.41 (2)	1.43 (1) / 1.85 (2)	1.43 (1) / 1.85 (2)	1.43 (1) / 1.85 (2)	1.43 (1) / 1.85 (2)	4.55 (1) / 4.30 (2)	4.55 (1) / 4.30 (2)	5.44 (1) / 5.10 (2)	5.44 (1) / 5.10 (2)	6.18 (1) / 5.72 (2)	6.18 (1) / 5.72 (2)
		Max.	kW		1.86 (1) / 2.04 (2)	2.27 (1) / 2.51 (2)	2.27 (1) / 2.51 (2)	2.89 (1) / 3.20 (2)	2.89 (1) / 3.20 (2)	4.53 (1) / 4.31 (2)	4.53 (1) / 4.31 (2)	5.42 (1) / 5.09 (2)	5.42 (1) / 5.09 (2)	6.15 (1) / 5.74 (2)	6.15 (1) / 5.74 (2)
COP					5.23 (1) / 3.84 (2) / 2.85 (3) / 4.07 (4)	4.65 (1) / 3.66 (2) / 2.73 (3) / 3.64 (4)	4.65 (1) / 3.66 (2) / 2.73 (3) / 3.64 (4)	4.60 (1) / 3.57 (2) / 2.78 (3) / 3.54 (4)	4.60 (1) / 3.57 (2) / 2.78 (3) / 3.54 (4)	4.38 (1) / 3.32 (2) / 2.45 (3) / 3.29 (4)	4.38 (1) / 3.32 (2) / 2.45 (3) / 3.29 (4)	4.27 (1) / 3.34 (2) / 2.58 (3) / 3.22 (4)	4.27 (1) / 3.34 (2) / 2.58 (3) / 3.22 (4)	4.10 (1) / 3.22 (2) / 2.44 (3) / 3.15 (4)	4.10 (1) / 3.22 (2) / 2.44 (3) / 3.15 (4)
EER					4.21 (1) / 2.85 (2)	3.65 (1) / 2.51 (2)	3.65 (1) / 2.51 (2)	3.65 (1) / 2.51 (2)	3.65 (1) / 2.51 (2)	3.32 (1) / 2.72 (2)	3.32 (1) / 2.72 (2)	2.96 (1) / 2.47 (2)	2.96 (1) / 2.47 (2)	2.72 (1) / 2.29 (2)	2.72 (1) / 2.29 (2)

Indoor Unit				EHSXB	04P30A	08P30A	08P50A	08P30A	08P50A	16P50A
Casing	Colour				Traffic white (RAL9016) / Dark grey (RAL7011)					
	Material				Impact resistant polypropylene					
Dimensions	Unit	HeightxWidthxDepth	mm		1,945x615x595		1,945x790x790	1,945x615x595		1,945x790x790
Weight	Unit		kg		92		119	92	119	121
Tank	Water volume		l		300		500	300		500
	Maximum water temperature		°C		85					
Operation range	Domestic hot water	Water side Min.~Max.	°C		25~55					
Sound power level	Nom.		dBA		40					
Sound pressure level	Nom.		dBA		28					

Outdoor Unit				ERLQ	004CV3	006CV3	008CV3	011CV3	011CW1	014CV3	014CW1	016CV3	016CW1
Dimensions	Unit	HeightxWidthxDepth	mm		735x832x307			1,345x900x320					
Weight	Unit		kg		54	56		113	114	113	114	113	114
Compressor	Quantity				1								
	Type				Hermetically sealed swing compressor			Hermetically sealed scroll compressor					
Operation range	Heating	Min.~Max.	°CWB		-25~25			-25~35					
	Cooling	Min.~Max.	°CDB		10~43			10.0~46.0	10~46	10.0~46.0	10~46	10.0~46.0	10~46
	Domestic hot water	Min.~Max.	°CDB		-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge		kg		1.45	1.6		3.4					
	Charge		TCO_2Eq		3.0	3.3		7.1					
Sound power level	Heating	Nom.	dBA		61		62	64				66	
	Cooling	Nom.	dBA		63			64		66		69	
Sound pressure level	Heating	Nom.	dBA		48		49	51				52	
	Cooling	Nom.	dBA	48	49		50	50		52		54	
Power supply	Name/Phase/Frequency/Voltage		Hz/V		V3/1~/50/230				W1/3N~/ 50/400	V3/1~/ 50/230	W1/3N~/ 50/400	V3/1~/5 0/230	W1/3N~/ 50/400
Current	Recommended fuses		A		20			40	20	40	20	40	20

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C)
(3) EW 30°C; LW 35°C; ambient conditions: -7°CDB/-8°CWB (4) EW 30°C; LW 35°C; ambient conditions: 2°CDB/1°CWB

Daikin Altherma low temperature split



Floor standing air to water heat pump for heating and hot water, ideal for low energy houses

- Perfect fit for new built as well as for low energy houses
- Best seasonal efficiencies, providing the highest savings on running costs
- Integrated indoor unit: all-in-one floor standing unit including the domestic hot water tank
- Energy efficient heating only system based on air to water heat pump technology
- Flexible configuration with respect to heat emitters
- Outdoor unit extracts heat from the outdoor air, even at -25°C

Efficiency data				**EHVH + ERLQ**	**04S18CB3V + 004CV3**	**08S18CB3V / 08S26CB9W + 006CV3**	**08S18CB3V / 08S26CB9W + 008CV3**	**11S18CB3V / 11S26CB9W + 011CV3**	**16S18CB3V / 16S26CB9W + 014CV3**	**16S18CB3V / 16S26CB9W + 016CV3**	**11S18CB3V / 11S26CB9W + 011CW1**	**16S18CB3V / 16S26CB9W + 014CW1**	**16S18CB3V / 16S26CB9W + 016CW1**
Heating capacity	Min.			kW	1.80 (1) / 1.80 (2)			-					
	Nom.			kW	4.40 (1) / 4.03 (2)	6.00 (1) / 5.67 (2)	7.40 (1) / 6.89 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)
	Max.			kW	5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)
Power input	Heating	Nom.		kW	0.87 (1) / 1.13 (2)	1.27 (1) / 1.59 (2)	1.66 (1) / 2.01 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)
		Max.		kW	-			3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)	3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)
Nominal efficiency	COP				5.04 (1) / 3.58 (2)	4.74 (1) / 3.56 (2)	4.45 (1) / 3.42 (2)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)

Indoor unit				**EHVH**	**04S18CB3V**	**08S18CB3V / 08S26CB9W**	**11S18CB3V 11S26CB9W**	**16S18CB3V / 16S26CB9W**	**11S18CB3V / 11S26CB9W**	**16S18CB3V / 16S26CB9W**
Casing	Colour				White					
	Material				Precoated sheet metal					
Dimensions	Unit	HeightxWidthxDepth		mm	1,732x600x728					
Weight	Unit			kg	116	117/126	117/126	118/127	117/126	118/127
Tank	Water volume			l	180	180/260				
	Insulation	Heat loss		kWh/24h	1.4	1.4/1.9				
	Corrosion protection				Anode					
Sound power level	Cooling			dBA	42		-			
Sound pressure level	Cooling	Nom.		dBA	28		-			

Outdoor unit				**ERLQ**	**004CV3**	**006CV3**	**008CV3**	**011CV3**	**014CV3**	**016CV3**	**011CW1**	**014CW1**	**016CW1**
Dimensions	Unit	HeightxWidthxDepth		mm	735x832x307			1,345x900x320					
Weight	Unit			kg	54	56		113			114		
Operation range	Heating	Ambient	Min.~Max.	°CDB	-25~25			-25~35					
	Domestic hot water	Ambient	Min.~Max.	°CWB	-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge			kg	1.45	1.6		3.4					
	Charge			TCO_2Eq	3.0	3.3		7.1					
Sound power level	Heating			dBA	61		62	64		66	64		66
Sound pressure level	Heating	Nom.		dBA	48		49	51		52	51		52
Power supply	Phase / Frequency / Voltage			Hz / V	V3/1~/50/230						W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)			A	20			40			20		

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C

Daikin Altherma low temperature split



Efficiency data				EHVH + ERHQ	11S18CB3V / 11S26CB9W + 011BV3	16S18CB3V / 16S26CB9W + 014BV3	16S18CB3V / 16S26CB9W + 016BV3	11S18CB3V / 11S26CB9W + 011BW1	16S18CB3V / 16S26CB9W + 014BW1	16S18CB3V / 16S26CB9W + 016BW1
Heating capacity	Nom.			kW	11.2 (1) / 10.3 (2)	14.0 (1) / 13.1 (2)	16.0 (1) / 15.2 (2)	11.32 (1) / 10.98 (2)	14.50 (1) / 13.57 (2)	16.05 (1) / 15.11 (2)
Power input	Heating	Nom.		kW	2.55 (1) / 3.17 (2)	3.26 (1) / 4.04 (2)	3.92 (1) / 4.75 (2)	2.63 (1) / 3.24 (2)	3.42 (1) / 4.21 (2)	3.82 (1) / 4.69 (2)
Nominal efficiency	COP				4.39 (1) / 3.25 (2)	4.29 (1) / 3.24 (2)	4.08 (1) / 3.20 (2)	4.30 (1) / 3.39 (2)	4.24 (1) / 3.22 (2)	4.20 (1) / 3.22 (2)

Indoor unit				EHVH	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W
Casing	Colour				White			
	Material				Precoated sheet metal			
Dimensions	Unit	HeightxWidthxDepth		mm	1,732x600x728			
Weight	Unit			kg	117/126	118/127	117/126	118/127
Sound power level	Cooling			dBA	-			
Sound pressure level	Cooling	Nom.		dBA	-			

Outdoor unit				ERHQ	011BV3	014BV3	016BV3	011BW1	014BW1	016BW1
Dimensions	Unit	HeightxWidthxDepth		mm	1,170x900x320			1,345x900x320		
Weight	Unit			kg	103			108		
Operation range	Heating	Ambient	Min.~Max.	°CDB	-20~35					
	Domestic hot water	Ambient	Min.~Max.	°CWB	-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Charge			kg	2.7			2.95		
	Charge			TCO_2Eq	5.6			6.2		
Sound power level	Heating			dBA	64		66	64		66
Sound pressure level	Heating	Nom.		dBA	49	51	53	51		52
Power supply	Phase / Frequency / Voltage			Hz / V	V3/1~/50/230			W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)			A	32			20		

(1) DB/WB 7°C/6°C - LWC 35°C (DT=5°C) - (2) DB/WB 7°C/6°C - LWC 45°C (Dt=5°C)

Daikin Altherma low temperature split



Floor standing air to water heat pump for heating, cooling and hot water, ideal for low energy houses

- Perfect fit for new built as well as for low energy houses
- Best seasonal efficiencies, providing the highest savings on running costs
- Integrated indoor unit: all-in-one floor standing unit including the domestic hot water tank
- Energy efficient heating and cooling system based on air to water heat pump technology
- Flexible configuration with respect to heat emitters
- Outdoor unit extracts heat from the outdoor air, even at -25°C

Efficiency data				EHVX + ERLQ	04S18CB3V + 004CV3	08S18CB3V / 08S26CB9W + 006CV3	08S18CB3V / 08S26CB9W + 008CV3	11S18CB3V / 11S26CB9W + 011CV3	16S18CB3V / 16S26CB9W + 014CV3	16S18CB3V / 16S26CB9W + 016CV3	11S18CB3V / 11S26CB9W + 011CW1	16S18CB3V / 16S26CB9W + 014CW1	16S18CB3V / 16S26CB9W + 016CW1
Heating capacity	Min.		kW		1.80 (1) / 1.80 (2)			-					
	Nom.		kW		4.40 (1) / 4.03 (2)	6.00 (1) / 5.67 (2)	7.40 (1) / 6.89 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)
	Max.		kW		5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)
Cooling capacity	Min.				2.00 (1) / 2.00 (2)	2.50 (1) / 2.50 (2)		-					
	Nom.				4.08 (1) / 4.17 (2)	5.88 (1) / 4.84 (2)	6.20 (1) / 5.36 (2)	12.13 (1) / 11.72 (2)	12.72 (1) / 12.55 (2)	13.79 (1) / 13.12 (2)	12.13 (1) / 11.72 (2)	12.72 (1) / 12.55 (2)	13.79 (1) / 13.12 (2)
Power input	Heating	Nom.	kW		0.87 (1) / 1.13 (2)	1.27 (1) / 1.59 (2)	1.66 (1) / 2.01 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)
		Max.	kW		-			3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)	3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)
	Cooling	Nom.	kW		0.90 (1) / 1.80 (2)	1.51 (1) / 2.07 (2)	1.64 (1) / 2.34 (2)	3.05 (1) / 4.31 (2)	3.21 (1) / 5.08 (2)	3.74 (1) / 5.73 (2)	3.05 (1) / 4.31 (2)	3.21 (1) / 5.08 (2)	3.74 (1) / 5.73 (2)
Nominal efficiency	COP				5.04 (1) / 3.58 (2)	4.74 (1) / 3.56 (2)	4.45 (1) / 3.42 (2)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)
	EER				4.55 (1) / 2.32 (2)	3.89 (1) / 2.34 (2)	3.79 (1) / 2.29 (2)	3.98 (1) / 2.72 (2)	3.96 (1) / 2.47 (2)	3.69 (1) / 2.29 (2)	3.98 (1) / 2.72 (2)	3.96 (1) / 2.47 (2)	3.69 (1) / 2.29 (2)

Indoor unit				EHVX	04S18CB3V	08S18CB3V / 08S26CB9W	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W
Casing	Colour				White					
	Material				Precoated sheet metal					
Dimensions	Unit	HeightxWidthxDepth	mm		1,732x600x728					
Weight	Unit		kg		117	119/128		120/129	119/128	120/129
Tank	Water volume		l		180	180/260				
	Insulation	Heat loss	kWh/24h		1.4	1.4/1.9				
	Corrosion protection				Anode					
Sound power level	Cooling		dBA		42		-			
Sound pressure level	Cooling	Nom.	dBA		28		-			

Outdoor unit				ERLQ	004CV3	006CV3	008CV3	011CV3	014CV3	016CV3	011CW1	014CW1	016CW1
Dimensions	Unit	HeightxWidthxDepth	mm		735x832x307			1,345x900x320					
Weight	Unit		kg		54	56		113			114		
Operation range	Heating	Ambient Min.~Max.	°CDB		-25~25			-25~35					
	Cooling	Ambient Min.~Max.	°CWB		10~43			10~46					
	Domestic hot water	Ambient Min.~Max.	°CWB		-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge		kg		1.45	1.6		3.4					
	Charge		TCO_2Eq		3.0	3.3		7.1					
Sound power level	Cooling		dBA		61		62	64		66	64		66
	Heating		dBA		63			64	66	69	64	66	69
Sound pressure level	Cooling	Nom./Silent operation	dBA		48		49	51		52	51		52
	Heating	Nom.	dBA		48	49	50	50	52	54	50	52	54
Power supply	Phase / Frequency / Voltage		Hz / V		V3/1~/50/230						W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)		A		20			40			20		

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C

Daikin Altherma low temperature split



Efficiency data				EHVX + ERHQ	11S18CB3V / 11S26CB9W + 011BV3	16S18CB3V / 16S26CB9W + 014BV3	16S18CB3V / 16S26CB9W + 016BV3	11S18CB3V / 11S26CB9W + 011BW1	16S18CB3V / 16S26CB9W + 014BW1	16S18CB3V / 16S26CB9W + 016BW1
Heating capacity	Nom.			kW	11.2 (1) / 10.30 (2)	14.0 (1) / 13.1 (2)	16.0 (1) / 15.2 (2)	11.32 (1) / 10.98 (2)	14.50 (1) / 13.57 (2)	16.05 (1) / 15.11 (2)
Cooling capacity	Nom.			kW	13.9 (1) / 10.0 (2)	17.3 (1) / 12.5 (2)	17.8 (1) / 13.1 (2)	15.05 (1) / 11.72 (2)	16.06 (1) / 12.55 (2)	16.76 (1) / 13.12 (2)
Power input	Heating	Nom.		kW	2.55 (1) / 3.17 (2)	3.26 (1) / 4.04 (2)	3.92 (1) / 4.75 (2)	2.63 (1) / 3.24 (2)	3.42 (1) / 4.21 (2)	3.82 (1) / 4.69 (2)
	Cooling	Nom.		kW	3.86 (1) / 3.69 (2)	5.86 (1) / 5.39 (2)	6.87 (1) / 5.95 (2)	4.53 (1) / 4.31 (2)	5.43 (1) / 5.08 (2)	6.16 (1) / 5.73 (2)
Nominal efficiency	COP				4.39 (1) / 3.25 (2)	4.29 (1) / 3.24 (2)	4.08 (1) / 3.20 (2)	4.30 (1) / 3.39 (2)	4.24 (1) / 3.22 (2)	4.20 (1) / 3.22 (2)
	EER				3.60 (1) / 2.71 (2)	2.95 (1) / 2.32 (2)	2.59 (1) / 2.20 (2)	3.32 (1) / 2.72 (2)	2.96 (1) / 2.47 (2)	2.72 (1) / 2.29 (2)

Indoor unit				EHVX	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W	11S18CB3V / 11S26CB9W	16S18CB3V / 16S26CB9W
Casing	Colour				White			
	Material				Precoated sheet metal			
Dimensions	Unit	HeightxWidthxDepth		mm	1,732x600x728			
Weight	Unit			kg	119/128	120/129	119/128	120/129
Sound power level	Cooling	Nom.		dBA	-			
Sound pressure level	Cooling	Nom.		dBA	-			

Outdoor unit				ERHQ	011BV3	014BV3	016BV3	011BW1	014BW1	016BW1
Dimensions	Unit	HeightxWidthxDepth		mm	1,170x900x320			1,345x900x320		
Weight	Unit			kg	103			108		
Operation range	Heating	Ambient	Min.~Max.	°CDB	-20~35			-25~35		
	Cooling	Ambient	Min.~Max.	°CDB	10~46					
	Domestic hot water	Ambient	Min.~Max.	°CWB	-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Charge			kg	2.7			2.95		
	Charge			TCO_2Eq	5.6			6.2		
Sound power level	Heating			dBA	64		66	64		66
	Cooling			dBA	64	66	69	64	66	69
Sound pressure level	Heating	Nom.		dBA	49	51	53	51		52
	Cooling	Nom.		dBA	50	52	54	50	52	54
Power supply	Phase / Frequency / Voltage			Hz / V	V3/1~/50/230			W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)			A	32			20		

(1)DB/WB 7°C/6°C - LWC 35°C (DT=5°C) - (2) DB/WB 7°C/6°C - LWC 45°C (Dt=5°C)

Daikin Altherma low temperature split



Wall mounted heating only air to water heat pump ideal for low energy houses

- Perfect fit for new built as well as for low energy houses
- Best seasonal efficiencies, providing the highest savings on running costs
- Wall mounted indoor unit
- Energy efficient heating only system based on air to water heat pump technology
- Flexible configuration with respect to heat emitters
- Possible to combine with domestic hot water
- Outdoor unit extracts heat from the outdoor air, even at -25°C

Efficiency data				EHBH + ERLQ	04CB3V + 004CV3	08CB3V / 08CB9W + 006CV3	08CB3V / 08CB9W + 008CV3	11CB3V / 11CB9W +011CV3	16CB3V / 16CB9W +014CV3	16CB3V / 16CB9W + 016CV3	11CB3V / 11CB9W + 011CW1	16CB3V / 16CB9W + 014CW1	16CB3V / 16CB9W + 016CW1
Heating capacity	Min.		kW		1.80 (1) / 1.80 (2)			-					
	Nom.		kW		4.40 (1) / 4.03 (2)	6.00 (1) / 5.67 (2)	7.40 (1) / 6.89 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)
	Max.		kW		5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)
Power input	Heating	Nom.	kW		0.87 (1) / 1.13 (2)	1.27 (1) / 1.59 (2)	1.66 (1) / 2.01 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)
		Max.	kW		-			3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)	3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)
Nominal efficiency	COP				5.04 (1) / 3.58 (2)	4.74 (1) / 3.56 (2)	4.45 (1) / 3.42 (2)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 3.26 (2) / 2.09 (4)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)

Indoor unit				EHBH	04CB3V	08CB3V / 08CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W
Casing	Colour				White					
	Material				Precoated sheet metal					
Dimensions	Unit	HeightxWidthxDepth	mm		890x480x344					
Weight	Unit		kg		41	43	43	44	43	44
Sound power level	Cooling		dBA		40		-			
Sound pressure level	Cooling	Nom.	dBA		26		-			

Outdoor unit				ERLQ	004CV3	006CV3	008CV3	011CV3	014CV3	016CV3	011CW1	014CW1	016CW1
Dimensions	Unit	HeightxWidthxDepth	mm		735x832x307			1,345x900x320					
Weight	Unit		kg		54	56		113			114		
Operation range	Heating	Ambient Min.~Max.	°CDB		-25~25			-25~35					
	Domestic hot water	Ambient Min.~Max.	°CWB		-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge		kg		1.45	1.6		3.4					
	Charge		TCO_2Eq		3.0	3.3		7.1					
Sound power level	Heating		dBA		61		62	64		66	64		66
Sound pressure level	Heating	Nom./Silent operation	dBA		48		49	51		52	51		52
Power supply	Phase / Frequency / Voltage		Hz / V		V3/1~/50/230						W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)		A		20			40			20		

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C

Daikin Altherma low temperature split



Efficiency data				EHBH + ERHQ	11CB3V / 11CB9W + 011BV3	16CB3V / 16CB9W + 014BV3	16CB3V / 16CB9W + 016BV3	11CB3V / 11CB9W + 011BW1	16CB3V / 16CB9W + 014BW1	16CB3V / 16CB9W + 016BW1
Heating capacity	Nom.			kW	11.2 (1) / 10.3 (2)	14.0 (1) / 13.1 (2)	16.0 (1) / 15.2 (2)	11.32 (1) / 10.98 (2)	14.50 (1) / 13.57 (2)	16.05 (1) / 15.11 (2)
Power input	Heating	Nom.		kW	2.55 (1) / 3.17 (2)	3.26 (1) / 4.04 (2)	3.92 (1) / 4.75 (2)	2.63 (1) / 3.24 (2)	3.42 (1) / 4.21 (2)	3.82 (1) / 4.69 (2)
Nominal efficiency	COP				4.39 (1) / 3.25 (2)	4.29 (1) / 3.24 (2)	4.08 (1) / 3.20 (2)	4.30 (1) / 3.39 (2)	4.24 (1) / 3.22 (2)	4.20 (1) / 3.22 (2)

Indoor unit				EHBH	11CB3V / 11CB9W	16CB3V / 16CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W
Casing	Colour				White			
	Material				Precoated sheet metal			
Dimensions	Unit	HeightxWidthxDepth		mm	890x480x344			
Weight	Unit			kg	43	44	43	44
Sound power level	Cooling			dBA	-			
Sound pressure level	Cooling	Nom.		dBA	-			

Outdoor unit				ERHQ	011BV3	014BV3	016BV3	011BW1	014BW1	016BW1
Dimensions	Unit	HeightxWidthxDepth		mm	1,170x900x320			1,345x900x320		
Weight	Unit			kg	103			108		
Operation range	Heating	Ambient	Min.~Max.	°CDB	-20~35			-25~35		
	Domestic hot water	Ambient	Min.~Max.	°CWB	-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Charge			kg	2.7			2.95		
	Charge			TCO_2Eq	5.6			6.2		
Sound power level	Heating			dBA	64		66	64		66
Sound pressure level	Heating	Nom.		dBA	49	51	53	51		52
Power supply	Phase / Frequency / Voltage			Hz / V	V3/1~/50/230			W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)			A	32			20		

(1)DB/WB 7°C/6°C - LWC 35°C (DT=5°C) - (2) DB/WB 7°C/6°C - LWC 45°C (Dt=5°C)

Daikin Altherma low temperature split



Wall mounted reversible air to water heat pump ideal for low energy houses

- Perfect fit for new built as well as for low energy houses
- Best seasonal efficiencies, providing the highest savings on running costs
- Wall mounted indoor unit
- Energy efficient heating and cooling system based on air to water heat pump technology
- Flexible configuration with respect to heat emitters
- Possible to combine with domestic hot water
- Outdoor unit extracts heat from the outdoor air, even at -25°C

Efficiency data			EHBX-CB + ERLQ	04CB3V + 004CV3	08CB3V / 08CB9W + 006CV3	08CB3V / 08CB9W + 008CV3	11CB3V / 11CB9W + 011CV3	14CB3V / 14CB9W + 014CV3	16CB3V / 16CB9W + 016CV3	11CB3V / 11CB9W + 011CW1	16CB3V / 16CB9W + 014CW1	16CB3V / 16CB9W + 016CW1
Heating capacity	Min.		kW	1.80 (1) / 1.80 (2)			-					
	Nom.		kW	4.40 (1) / 4.03 (2)	6.00 (1) / 5.67 (2)	7.40 (1) / 6.89 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)
	Max.		kW	5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)
Cooling capacity	Min.			2.00 (1) / 2.00 (2)	2.50 (1) / 2.50 (2)		-					
	Nom.			4.08 (1) / 4.17 (2)	5.88 (1) / 4.84 (2)	6.20 (1) / 5.36 (2)	12.13 (1) / 11.72 (2)	12.72 (1) / 12.55 (2)	13.79 (1) / 13.12 (2)	12.13 (1) / 11.72 (2)	12.72 (1) / 12.55 (2)	13.79 (1) / 13.12 (2)
Power input	Heating	Nom.	kW	0.87 (1) / 1.13 (2)	1.27 (1) / 1.59 (2)	1.66 (1) / 2.01 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)
		Max.	kW		-		3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)	3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)
	Cooling	Nom.	kW	0.90 (1) / 1.80 (2)	1.51 (1) / 2.07 (2)	1.64 (1) / 2.34 (2)	3.05 (1) / 4.31 (2)	3.21 (1) / 5.08 (2)	3.74 (1) / 5.73 (2)	3.05 (1) / 4.31 (2)	3.21 (1) / 5.08 (2)	3.74 (1) / 5.73 (2)
Nominal efficiency	COP			5.04 (1) / 3.58 (2)	4.74 (1) / 3.56 (2)	4.45 (1) / 3.42 (2)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)
	EER			4.55 (1) / 2.32 (2)	3.89 (1) / 2.34 (2)	3.79 (1) / 2.29 (2)	3.98 (1) / 2.72 (2)	3.96 (1) / 2.47 (2)	3.69 (1) / 2.29 (2)	3.98 (1) / 2.72 (2)	3.96 (1) / 2.47 (2)	3.69 (1) / 2.29 (2)

Indoor unit			EHBX	04CB3V	08CB3V / 08CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W
Casing	Colour			White					
	Material			Precoated sheet metal					
Dimensions	Unit	HeightxWidthxDepth	mm	890x480x344					
Weight	Unit		kg	42	44	43	44	43	44
Sound power level	Cooling		dBA	40		-			
Sound pressure level	Cooling	Nom.	dBA	26		-			

Outdoor unit				ERLQ	004CV3	006CV3	008CV3	011CV3	014CV3	016CV3	011CW1	014CW1	016CW1
Dimensions	Unit	HeightxWidthxDepth		mm	735x832x307			1,345x900x320					
Weight	Unit			kg	54	56		113			114		
Operation range	Heating	Ambient	Min.~Max.	°CDB	-25~25			-25~35					
	Cooling	Ambient	Min.~Max.	°CWB	10~43			10.0~46.0			10~46		
	Domestic hot water	Ambient	Min.~Max.	°CWB	-25~35			-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5								
	Charge			kg	1.45	1.6		3.4					
	Charge			TCO_2Eq	3.0	3.3		7.1					
Sound power level	Cooling			dBA	61		62	64		66	64		66
	Heating			dBA	63			64	66	69	64	66	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	48		49	51		52	51		52
	Heating	Nom.		dBA	48	49	50	50	52	54	50	52	54
Power supply	Phase / Frequency / Voltage			Hz / V	V3/1~/50/230						W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)			A	20			40			20		

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C

Daikin Altherma low temperature split



Efficiency data				EHBX + ERHQ	11CB3V / 11CB9W + 011BV3	16CB3V / 16CB9W + 014BV3	16CB3V / 16CB9W + 016BV3	11CB3V / 11CB9W + 011BW1	16CB3V / 16CB9W + 014BW1	16CB3V / 16CB9W + 016BW1
Heating capacity	Nom.			kW	11.2 (3) / 10.30 (4)	14.0 (3) / 13.1 (4)	16.0 (3) / 15.2 (4)	11.32 (1) / 10.98 (2)	14.50 (1) / 13.57 (2)	16.05 (1) / 15.11 (2)
Cooling capacity	Nom.			kW	13.9 (2) / 10.0 (1)	17.3 (2) / 12.5 (1)	17.8 (2) / 13.1 (1)	15.05 (1) / 11.72 (2)	16.06 (1) / 12.55 (2)	16.76 (1) / 13.12 (2)
Power input	Heating	Nom.		kW	2.55 (3) / 3.17 (4)	3.26 (3) / 4.04 (4)	3.92 (3) / 4.75 (4)	2.63 (1) / 3.24 (2)	3.42 (1) / 4.21 (2)	3.82 (1) / 4.69 (2)
	Cooling	Nom.		kW	3.86 (2) / 3.69 (1)	5.86 (2) / 5.39 (1)	6.87 (2) / 5.95 (1)	4.53 (1) / 4.31 (2)	5.43 (1) / 5.08 (2)	6.16 (1) / 5.73 (2)
Nominal efficiency	COP				4.39 (3) / 3.25 (4)	4.29 (3) / 3.24 (4)	4.08 (3) / 3.20 (4)	4.30 (1) / 3.39 (2)	4.24 (1) / 3.22 (2)	4.20 (1) / 3.22 (2)
	EER				3.60 (2) / 2.71 (1)	2.95 (2) / 2.32 (1)	2.59 (2) / 2.20 (1)	3.32 (1) / 2.72 (2)	2.96 (1) / 2.47 (2)	2.72 (1) / 2.29 (2)


Indoor unit				EHBX	11CB3V / 11CB9W	16CB3V / 16CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W
Casing	Colour				White			
	Material				Precoated sheet metal			
Dimensions	Unit	HeightxWidthxDepth		mm	890x480x344			
Weight	Unit			kg	43	44	43	44
Sound power level	Cooling			dBA	-			
Sound pressure level	Cooling	Nom.		dBA	-			


Outdoor unit				ERHQ	011BV3	014BV3	016BV3	011BW1	014BW1	016BW1
Dimensions	Unit	HeightxWidthxDepth		mm	1,170x900x320			1,345x900x320		
Weight	Unit			kg	103			108		
Operation range	Heating	Ambient	Min.~Max.	°CDB	-20~35			-25~35		
	Cooling	Ambient	Min.~Max.	°CDB	10~46					
	Domestic hot water	Ambient	Min.~Max.	°CWB	-20~35					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Charge			kg	2.7			2.95		
	Charge			TCO_2Eq	5.6			6.2		
Sound power level	Heating			dBA	64		66	64		66
	Cooling			dBA	64	66	69	64	66	69
Sound pressure level	Heating	Nom.		dBA	49	51	53	51		52
	Cooling	Nom.		dBA	50	52	54	50	52	54
Power supply	Phase / Frequency / Voltage			Hz / V	V3/1~/50/230			W1/3N~/50/400		
Current - 50Hz	Maximum fuse amps (MFA)			A	32			20		

(1)DB/WB 7°C/6°C - LWC 35°C (DT=5°C) - (2) DB/WB 7°C/6°C - LWC 45°C (Dt=5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C

Small capacity monobloc

Available summer 2015





NEW

- Compact dimensions: reduction in height and width compared to the current model.
- New capacities: 5 and 7 kW outdoor unit, guaranteed capacity down to -10°C.
- Free hanging coil: it ensures no ice builds up on the lower part of the outdoor unit, to offer appropriate frost protection.
- Discharge grill: specifically designed to avoid ice accumulation.
- New controller: additional features like detailed information on operational conditions of the unit and full text error codes.

Daikin Altherma low temperature monobloc

- Single phase reversible monobloc
- Energy efficient heating and cooling system based on air to water heat pump technology
- H2O piping between outdoor unit and indoor heat emitters
- Low energy bills and low CO2 emissions
- Eco-label certified
- Built-in electric back-up heater as additional heating during extremely cold outdoor temperature
- Inverter controlled swing compressor
- Possible to combine with domestic hot water



EBHQ-BBV3



EKCB(H/X)-BCV3

Single Unit				EBHQ	006BBV3	008BBV3	EKCB(H/X) 008BCV3
Heating capacity	Nom.			kW	6.00 (2) / 5.58 (4)	8.85 (2) / 8.15 (4)	-
Cooling capacity	Nom.			kW	7.00 (1) / 5.12 (3)	8.37 (1) / 6.08 (3)	-
Power input	Cooling	Nom.		kW	2.20 (1) / 2.16 (3)	2.97 (1) / 2.75 (3)	-
	Heating	Nom.		kW	1.41 (2) / 1.79 (4)	2.21 (2) / 2.72 (4)	-
COP					4.26 (2) / 3.11 (4)	4.00 (2) / 3.00 (4)	-
EER					3.18 (1) / 2.37 (3)	2.82 (1) / 2.21 (3)	-
Dimensions	Unit	Height		mm	805		390
		Width		mm	1,190		412
		Depth		mm	360		100
		Depth with remocon mounted on front plate		mm	-		120
Weight	Unit			kg	95		6
Operation range	Heating	Ambient	Min.~Max.	°CWB	-15~25		-~-
		Water side	Min.~Max.	°C	15~50 (5)		-~-
	Cooling	Ambient	Min.~Max.	°CDB	10~43		-~-
		Water side	Min.~Max.	°C	5~22		-~-
	Domestic hot water	Ambient	Min.~Max.	°CDB	-15~35		-~-
		Water side	Min.~Max.	°C	25~80		-~-
	Indoor installation	Ambient	Min.	°CDB	-		4
			Max.	°CDB	-		35
Refrigerant	Type / GWP				R-410A / 2,087.5		-
	Charge			kg	1.7		-
	Charge			TCO_2Eq	3.5		-
Sound power level	Heating	Nom.		dBA	61	62	-
	Cooling	Nom.		dBA	63		-
Sound pressure level	Heating	Nom.		dBA	48	49	-
	Cooling	Nom.		dBA	48	50	-
Compressor component	Main power supply	Name			V3		-
		Phase			1~		-
		Frequency		Hz	50		-
		Voltage		V	230		-

(1) Tamb 35°C - LWE 18°C (DT=5°C) (2) DB/WB 7°C/6°C - LWC 35°C (DT=5°C) (3) Tamb 35°C - LWE 7°C (DT=5°C) (4) DB/WB 7°C/6°C - LWC 45°C (Dt=5°C)
(5) 15°C-25°C: BUH only, no heat pump operation = during commisioning

Daikin Altherma low temperature monobloc

Reversible air to water monobloc system, ideal when indoor space is limited

- Energy efficient **heating and cooling** system based on air to water heat pump technology
- Low energy bills and low CO_2 emissions
- H_2O piping between outdoor unit and indoor heat emitters
- Inverter controlled scroll compressor
- Built-in electric back-up heater as additional heating during extremely cold outdoor temperature
- Outdoor unit extracts heat from the outdoor air, even at -25°C
- Possible to combine with domestic hot water



EB(L/H)Q-BB

Single Unit				EBLQ/EBHQ	011BB6V3	014BB6V3	016BB6V3	011BB6W1	014BB6W1	016BB6W1
Heating capacity	Nom.			kW	11.20 (1) / 10.87 (2)	14.00 (1) / 13.10 (2)	16.00 (1) / 15.06 (2)	11.20 (1) / 10.87 (2)	14.00 (1) / 13.10 (2)	16.00 (1) / 15.06 (2)
Cooling capacity	Nom.			kW	12.85 (1) / 10.00 (2)	15.99 (1) / 12.50 (2)	16.73 (1) / 13.10 (2)	12.85 (1) / 10.00 (2)	15.99 (1) / 12.50 (2)	16.73 (1) / 13.10 (2)
Power input	Cooling	Nom.		kW	3.87 (1) / 3.69 (2)	5.75 (1) / 5.39 (2)	6.36 (1) / 5.93 (2)	3.87 (1) / 3.69 (2)	5.40 (1) / 5.06 (2)	6.15 (1) / 5.75 (2)
	Heating	Nom.		kW	2.56 (1) / 3.31 (2)	3.29 (1) / 4.01 (2)	3.88 (1) / 4.71 (2)	2.60 (1) / 3.21 (2)	3.30 (1) / 4.07 (2)	3.81 (1) / 4.66 (2)
COP					4.38 (1) / 3.28 (2)	4.25 (1) / 3.27 (2)	4.12 (1) / 3.20 (2)	4.31 (1) / 3.38 (2)	4.24 (1) / 3.22 (2)	4.20 (1) / 3.23 (2)
EER					3.32 (1) / 2.71 (2)	2.78 (1) / 2.32 (2)	2.63 (1) / 2.21 (2)	3.32 (1) / 2.71 (2)	2.96 (1) / 2.47 (2)	2.72 (1) / 2.28 (2)
Dimensions	Unit	Height		mm	1,418					
		Width		mm	1,435					
		Depth		mm	382					
Weight	Unit			kg	180					
Hydraulic component	Back-up heater	Type			6V3			6W1		
	current	Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/230			3~/50/400		
Operation range	Heating	Ambient	Min.~Max.	°CWB	-20~35 (EBLQ)/-15~35 (EBHQ)			-25~35 (EBLQ)/-15~35 (EBHQ)		
		Water side	Min.~Max.	°C	15~55 (3)					
	Cooling	Ambient	Min.~Max.	°CDB	10~46					
		Water side	Min.~Max.	°C	5~22					
	Domestic hot water	Ambient	Min.~Max.	°CDB	-20~43 (EBLQ)/-15~43 (EBHQ)			-25~43 (EBLQ)/-15~43 (EBHQ)		
		Water side	Min.~Max.	°C	25~80					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Charge			kg	2.95					
	Charge			TCO_2Eq	6.2					
Sound power level	Heating	Nom.		dBA	64	65	66	64	65	66
	Cooling	Nom.		dBA	65	66	69	65	66	69
Sound pressure level	Heating	Nom.		dBA	51		52	49	51	53
	Cooling	Nom.		dBA	50	52	54	50	52	54
Compressor component	Main power supply	Name			V3			W1		
		Phase			1~			3N~		
		Frequency		Hz	50					
		Voltage		V	230			400		

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C)
(3) 15°C-25°C: BUH only, no heat pump operation = during commisioning

Daikin Altherma low temperature monobloc

Heating only air to water monobloc system, ideal when indoor space is limited

- Energy efficient **heating only** system based on air to water heat pump technology
- Low energy bills and low CO_2 emissions
- H_2O piping between outdoor unit and indoor heat emitters
- Inverter controlled scroll compressor
- Built-in electric back-up heater as additional heating during extremely cold outdoor temperature
- Outdoor unit extracts heat from the outdoor air, even at -25°C
- Possible to combine with domestic hot water



ED(L/H)Q-BB

Single Unit			EDLQ/EDHQ	011BB6V3	014BB6V3	016BB6V3	011BB6W1	014BB6W1	016BB6W1
Heating capacity	Nom.		kW	11.20 / 10.87	14.00 / 13.10	16.00 / 15.06	11.20 / 10.87	14.00 / 13.10	16.00 / 15.06
Power input	Heating	Nom.	kW	2.56 / 3.31	3.29 / 4.01	3.88 / 4.71	2.60 / 3.21	3.30 / 4.07	3.81 / 4.66
COP				4.38 / 3.28	4.25 / 3.27	4.12 / 3.20	4.31 / 3.38	4.24 / 3.22	4.20 / 3.23
Dimensions	Unit	Height	mm	1,418					
		Width	mm	1,435					
		Depth	mm	382					
Weight	Unit		kg	180					
Hydraulic component	Back-up heater current	Type		6V3			6W1		
		Power supply Phase/Frequency/Voltage	Hz/V	1~/50/230			3~/50/400		
Operation range	Heating	Ambient Min.~Max.	°CWB	-20~35 (EDLQ)/-15~35 (EDHQ)			-25~35 (EDLQ)/-15~35 (EDHQ)		
		Water side Min.~Max.	°C	15~55					
	Domestic hot water	Ambient Min.~Max.	°CDB	-20~43 (EDLQ)/-15~43 (EDHQ)			-25~43 (EDLQ)/-15~43 (EDHQ)		
		Water side Min.~Max.	°C	25~80					
Refrigerant	Type / GWP			R-410A / 2,087.5					
	Charge		kg	2.95					
	Charge		TCO_2Eq	6.2					
Sound power level	Heating	Nom.	dBA	64	65	66	64	65	66
Sound pressure level	Heating	Nom.	dBA	51		52	49	51	53
Compressor component	Main power supply	Name		V3			W1		
		Phase		1~			3N~		
		Frequency	Hz	50					
		Voltage	V	230			400		

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C)
(3) 15°C-25°C: BUH only, no heat pump operation = during commisioning

Domestic hot water tanks

Whether your customer wants domestic hot water only or the advantage of solar energy,
Daikin offers you the domestic hot water tank that meets his or her requirements.

		Domestic hot water tank		
		EKHWP-B	EKHWS-B	EKHWE-A
Indoor		**300-500**	**150-200-300**	**150-200-300**
Wall mounted	EHBH-CB	hot water + unpressurised solar*	hot water + pressurised solar (opt.)	
	EHBX-CB			
Monobloc		**300-500**	**150-200-300**	**150-200-300**
With bottom plate heater	EDLQ-BB6V3 / EDLQ-BB6W1	hot water + unpressurised solar*	hot water + pressurised solar (opt.)	
	EBLQ-BB6V3 / EBLQ-BB6V3			
Without bottom plate heater	EDHQ-BB6V3 / EDHQ-BB6W1			
	EBHQ-BB6V3 / EBHQ-BB6W1			
	EBHQ-BBV3			

* for more details see combination table on page 24.

EKHWP-B

Plastic domestic hot water tank with solar support

Available in 300 and 500 liters
- Large hot water storage tank to provide domestic hot water at any time
- Heat loss is reduced to a minimum thanks to the high quality insulation
- Space heating support possible (500l tank only)



Accessory				EKHWP	300B	500B
Dimensions	Unit	Width		mm	595	790
		Depth		mm	615	790
Weight	Unit	Empty		kg	59	93
Tank	Water volume			l	300	500
	Maximum water temperature			°C	85	
	Insulation	Heat loss		kWh/24h	1.3	1.4
Heat exchanger	Domestic hot water	Tube material			Stainless steel	
		Face area		m^2	5.8	6
		Internal coil volume		l	27.9	29
		Operating pressure		bar	6	
		Average specifc thermal output		W/K	2,790	2,900
	Charging	Tube material			Stainless steel	
		Face area		m^2	2.7	3.8
		Internal coil volume		l	13.2	18.5
		Operating pressure		bar	3	
		Average specifc thermal output		W/K	1,300	1,800
	Auxiliary solar heating	Tube material			Stainless steel	
		Face area		m^2	-	0.5
		Internal coil volume		l	-	2.3
		Operating pressure		bar	3	
		Average specifc thermal output		W/K	-	280

EKHWS-B

Stainless steel domestic hot water tank

› Available in 150, 200 and 300 liters



EKHWS-B

Accessory				EKHWS	150B3V3	200B3V3	300B3V3	200B3Z2	300B3Z2
Casing	Colour				Neutral white				
	Material				Epoxy-coated mild steel				
Dimensions	Unit	Width	mm		580				
		Depth	mm		580				
Weight	Unit	Empty	kg		37	45	59	45	59
Tank	Water volume		l		150	200	300	200	300
	Material				Stainless steel (DIN 1.4521)				
	Maximum water temperature		°C		85				
	Insulation	Heat loss	kWh/24h		1.55	1.77	2.19	1.77	2.19
Heat exchanger	Quantity				1				
	Tube material				Duplex steel LDX 2101				
Booster heater	Capacity		kW		3				
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/230			2~/50/400	

EKHWE-A

Enameled domestic hot water tank

› Available in 150, 200 and 300 liters



EKHWE200A

Accessory				EKHWE	150A3V3	200A3V3	300A3V3	200A3Z2	300A3Z2
Casing	Colour				RAL9010				
	Material				Epoxy coated steel				
Dimensions	Unit	Diameter	mm		545		660	545	660
Weight	Unit	Empty	kg		80	104	140	104	140
Tank	Water volume		l		150	200	300	200	300
	Material				Enamel coated steel acc. DIN4753TL2		-		
	Maximum water temperature		°C		75				
	Insulation	Heat loss	kWh/24h		1.7	1.9	2.5	1.9	2.5
Booster heater	Capacity		kW		3.0				
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/230			2~/50/400	

EKSRPS

Pump station

- Save energy and reduce CO_2 emissions with a solar system for domestic hot water production
- Pump station connectable to unpressurised solar system
- Pump station and control provide the transfer of solar heat to the domestic hot water tank



EKSRPS3

Accessory				EKSRPS3
Mounting				On side of tank
Dimensions	Unit	HeightxWidthxDepth	mm	815x230x142
Control	Type			Digital temperature difference controller with plain text display
	Power consumption		W	2
Power supply	Voltage		V	230
Sensor	Solar panel temperature sensor			Pt1000
	Storage tank sensor			PTC
	Return flow sensor			PTC
	Feed temperature and flow sensor			Voltage signal (3.5V DC)

EKSOLHW

Solar connection

- Transfers solar heat to the domestic hot water tank
- Save energy and reduce CO_2 emissions with a solar system for domestic hot water production



EKSOLHW

Accessory				EKSOLHW
Dimensions	Unit	HeightxWidthxDepth	mm	770x305x270
Weight	Unit		kg	8
Operation range	Ambient temperature	Min.~Max.	°C	1~35
Sound pressure level	Nom.		dBA	27
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240
Power supply intake				Indoor unit

EKSR3P

Wired remote control for pump station EKSRDS1A

- Save energy and reduce CO_2 emissions with a solar system for domestic hot water production
- Wired remote control for pump station EKSRDS1A, connectable to pressurised solar system
- Pump station and control provide the transfer of solar heat to the domestic hot water tank

Accessory				EKSR3PA
Mounting				On wall
Dimensions	Unit	HeightxWidthxDepth	mm	332x230x145
Control	Type			Digital temperature difference controller with plain text display
	Power consumption		W	2
Power supply	Voltage		V	230
Sensor	Solar panel temperature sensor			Pt1000
	Storage tank sensor			PTC
	Return flow sensor			PTC
	Feed temperature and flow sensor			Voltage signal (3.5V DC)

Solar collector

Thermal solar collector for hot water production

- Solar collectors can produce up to 70% of the energy needed for hot water production - a major cost saving
- Vertical or horizontal solar collector for domestic hot water production
- High efficiency collectors transfer all the short-wave solar radiation into heat as a result of their highly selective coating
- Easy to install on roof tiles



EKSH-P




EKSV-P

Accessory				EKSV21P	EKSV26P	EKSH26P
Dimensions	Unit	HeightxWidthxDepth	mm	2,000x1,006x85	2,000x1,300x85	1,300x2,000x85
Weight	Unit		kg	35	42	
Volume			l	1.3	1.7	2.1
Surface	Outer		m^2	2.01	2.6	
	Aperture		m^2	1.79	2.35	
	Absorber		m^2	1.8	2.36	
Coating				Micro-therm (absorption max. 96%, Emission ca. 5% +/-2%)		
Absorber				Harp-shaped copper pipe register with laser-welded highly selective coated aluminium plate		
Glazing				Single pane safety glass, transmission +/- 92%		
Allowed roof angle	Min.~Max.		°	15~80		
Operating pressure	Max.		bar	6		
Stand still temperature	Max.		°C	200		

Wireless remote control

Room thermostat for easy regulation of the indoor temperature

- Easy and convenient regulation of the indoor temperature, resulting in ideal comfort and energy efficiency
- Heating and cooling mode, with possibility to disable cooling mode if not required
- Comfort function mode activates the programmed temperature levels intended for a home occupied during the day; default setpoints are 21°C in heating mode and 24°C in cooling mode and can be changed by the user
- Reduced function mode activates the programmed temperature levels for periods when the house is unoccupied or at night; default setpoints are 17°C in heating, 28°C in cooling mode and can be changed by the user
- Scheduled function mode: uses a timer to schedule heatin and cooling setpoints throughout the day; up to 12 setpoints can be programmed per day; the selected setpoints will be automatically activated at the scheduled time
- Holiday function mode: intended for setting reduced and fuel-efficient setpoints when the house is unoccupied for long periods. The default setpoints are 14°C for heating and 30°C for cooling.
- Off function: switches the system off; however, the integrated frost protection remains activated (set by default at 4°C).
- Setpoint limitation sets the upper and lower setpoint limits within which the user can programme the desired comfort levels and can only be modified by the installer
- Number of setpoint changes: 12/day
- Key lock function: possible to lock the keys of the room thermostat



EKRTR

EKRTWA

Accessory				EKRTR 1	EKRTWA
	Thermostat	HeightxWidthxDepth	mm	87x125x34	
	Receiver	HeightxWidthxDepth	mm	170x50x28	-x-x-
Weight	Unit		g	-	215
	Thermostat		g	210	-
	Receiver		g	125	-
Ambient	Storage	Min./Max.	°C	-20/60	
temperature	Operation	Min./Max.	°C	0/50	
Temperature	Heating	Min./Max.	°C	4/37	
setting range	Cooling	Min./Max.	°C	4/37	
Clock				Yes	
Regulation function				Proportional band	
Power supply	Thermostat	Voltage	V	Battery powered 3x AA-LRG (alkaline)	Battery powered 3* AA-LR6 (alkaline)
	Receiver	Voltage	V	230	-
	Frequency		Hz	50	-
	Phase			1~	-
Connection	Type			-	Wired
	Thermostat			Wireless	-
	Receiver			Wired	-
Maximum distance	Indoor		m	approx.30m	-
to receiver	Outdoor		m	approx.100m	-

Heat pump convector

Floor standing unit saving on running costs when combined with under floor heating thanks to its low leaving water temperatures

- Its low height enables the unit to fit perfectly beneath a window
- Can be installed against a wall or recessed
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- Energy efficient heating and cooling system based on air source heat pump technology
- Optimum energy efficiency when connected to a Daikin Altherma low temperature system
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Weekly timer can be set to start heating or cooling anytime on a daily or weekly basis
- Powerful mode can be selected for rapid cooling; after the powerful mode is turned off, the unit returns to the preset mode.




FWXV-A



ARC452A15



Indoor Unit			FWXV	15A	20A
Heating capacity	Total capacity	Nom.	kW	1.5	2.0
			Btu/h	5,100	6,800
Cooling capacity	Total capacity	Nom.	kW	1.2	1.7
	Sensible capacity	Nom.	kW	0.98	1.4
Power input	Heating	Nom.	kW	0.013	0.015
	Cooling	Nom.	kW	0.013	0.015
Dimensions	Unit	HeightxWidthxDepth	mm	600x700x210	
Weight	Unit		kg	15	
Piping connections	Drain/OD/Inlet/Outlet		mm/inch	18/G 1/2/G 1/2	
Sound pressure	Heating	Nom.	dBA	19	29
level	Cooling	Nom.	dBA	19	29
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220	




Heating & domestic hot water for renovations

Why choose Daikin Altherma high temperature?

Daikin Altherma high temperature is ideal **to replace your current oil boiler**, without replacing your existing radiators. It offers a wide range to adapt to your customer's needs.

- Heating and domestic hot water with optional solar connection
- Capacities from 11 to 16 kW
- Combinable with existing high temperature radiators
- Easy control

› Low running costs and optimum comfort at even the coldest outdoor temperatures, thanks to the unique cascade compressor approach
› No need to change your existing radiators and piping as water temperatures can be increased up to 80°C for heating and domestic hot water use
› Only limited installation space needed as the indoor unit and domestic hot water tank can be stacked on each other



A Indoor unit
B Outdoor unit
C Domestic hot water tank

Marketing tools

Visit our extranet: go to
extranet.daikineurope.com > Document library
Download the software:
http://www.daikineurope.com/binaries/daikin_alth_tcm524-234758.zip





Accessories for high temperature applications

User interface

With Daikin Altherma's user interface, the ideal temperature can be easily, quickly and conveniently regulated. It allows for more precise measurement and can regulate your comfort even more optimally and energy efficiently.

Heat emitters

The Daikin Atherma high temperature system is designed to work only with high-temperature radiators, which come in various sizes and formats to suit the interior design as well as the heating requirement. Our radiators can be individually controlled or they can be regulated by the central heating control programme.

Solar connection

The Daikin Altherma high temperature heating system can optionally use solar energy for hot water production.
If the solar energy is not required immediately, the purpose-built hot water tank (EKHWP) can store large quantities of heated water for up to a day for later use as domestic hot water or for heating.

EKHBRD-ACV1/Y1 +
ER(R/S)Q-AV1/AY1/EMRQ-A

Daikin Altherma high temperature split

Floor standing heating only air to water heat pump combinable with existing radiators

- Easy replacement of existing boiler, without changing heating pipes
- Low energy bills and low CO_2 emissions
- Energy efficient heating only system based on air to water heat pump technology
- Combinable with high temperature radiators
- High temperature application: up to 80°C without electric heater
- Floor standing indoor unit up to 16kW
- Inverter controlled scroll compressor
- Outdoor unit extracts heat from the outdoor air, even at -20°C



EKHBRD_ACV1/Y1



ER(R/S)Q-AV1/Y1



EMRQ14-16A

Efficiency data				EKHBRD	011ACV1 + ERSQ 011AV1	014ACV1 + ERSQ 014AV1	016ACV1 + ERSQ 016AV1	011ACV1 + ERRQ 011AV1	014ACV1 + ERRQ 014AV1	016ACV1 + ERRQ 016AV1	011ACY1 + ERSQ 011AY1	014ACY1 + ERSQ 014AY1	016ACY1 + ERSQ 016AY1	011ACY1 + ERRQ 011AY1	014ACY1 + ERRQ 014AY1	016ACY1 + ERRQ 016AY1
Heating capacity	Nom.			kW	11 (3) / 11 (4) / 11 (5)	14 (3) / 14 (4) / 14 (5)	16 (3) / 16 (4) / 16 (5)	11 (3) / 11 (4)	14 (3) / 14 (4)	16 (3) / 16 (4)	11 (3) / 11 (4) / 11 (5)	14 (3) / 14 (4) / 14 (5)	16 (3) / 16 (4) / 16 (5)	11 (3) / 11 (4)	14 (3) / 14 (4)	16 (3) / 16 (4)
Power input	Heating	Nom.		kW	3.57 (3) / 4.40 (4) / 2.61 (5)	4.66 (3) / 5.65 (4) / 3.55 (5)	5.57 (3) / 6.65 (4) / 4.31 (5)	3.57 (3) / 4.40 (4)	4.66 (3) / 5.65 (4)	5.57 (3) / 6.65 (4)	3.57 (3) / 4.40 (4) / 2.61 (5)	4.66 (3) / 5.65 (4) / 3.55 (5)	5.57 (3) / 6.65 (4) / 4.31 (5)	3.57 (3) / 4.40 (4)	4.66 (3) / 5.65 (4)	5.57 (3) / 6.65 (4)
COP					3.08 (3) / 2.50 (4) / 4.22 (5)	3.00 (3) / 2.48 (4) / 3.94 (5)	2.88 (3) / 2.41 (4) / 3.72 (5)	3.08 (3) / 2.50 (4)	3.00 (3) / 2.48 (4)	2.88 (3) / 2.41 (4)	3.08 (3) / 2.50 (4) / 4.22 (5)	3.00 (3) / 2.48 (4) / 3.94 (5)	2.88 (3) / 2.41 (4) / 3.72 (5)	3.08 (3) / 2.50 (4)	3.00 (3) / 2.48 (4)	2.88 (3) / 2.41 (4)

Indoor Unit				EKHBRD	011ACV1	014ACV1	016ACV1	011ACV1	014ACV1	016ACV1	011ACY1	014ACY1	016ACY1	011ACY1	014ACY1	016ACY1
Casing	Colour				Metallic grey											
	Material				Precoated sheet metal											
Dimensions	Unit	HeightxWidthxDepth		mm	705x600x695											
Weight	Unit			kg	144						147					
Operation range	Heating	Ambient	Min.~Max.	°C	-20~20											
		Water side	Min.~Max.	°C	25~80											
	Domestic hot water	Ambient	Min.~Max.	°CDB	-20~35											
		Water side	Min.~Max.	°C	25~80											
Sound pressure level	Nom.			dBA	43 (1) / 46 (2)	45 (1) / 46 (2)	46 (1) / 46 (2)	43 (1) / 46 (2)	45 (1) / 46 (2)	46 (1) / 46 (2)	43 (1) / 46 (2)	45 (1) / 46 (2)	46 (1) / 46 (2)	43 (1) / 46 (2)	45 (1) / 46 (2)	46 (1) / 46 (2)
	Night quiet mode	Level 1		dBA	40 (1)	43 (1)	45 (1)	40 (1)	43 (1)	45 (1)	40 (1)	43 (1)	45 (1)	40 (1)	43 (1)	45 (1)

					ERSQ			ERRQ			ERSQ			ERRQ		
Outdoor Unit				ERSQ/ERRQ	011AV1	014AV1	016AV1	011AV1	014AV1	016AV1	011AY1	014AY1	016AY1	011AY1	014AY1	016AY1
Dimensions	Unit	HeightxWidthxDepth		mm	1,345x900x320											
Weight	Unit			kg	120											
Compressor	Quantity				1											
	Type				Hermetically sealed scroll compressor											
Operation range	Heating	Min.~Max.		°CWB	-20~20											
	Domestic hot water	Min.~Max.		°CDB	-20~35											
Refrigerant	Type / GWP				R-410A / 2,087.5											
	Charge			kg	4.5											
	Charge			TCO_2Eq	9.4											
Sound power level	Heating	Nom.		dBA	68	69	71	68	69	71	68	69	71	68	69	71
Sound pressure level	Heating	Nom.		dBA	52	53	55	52	53	55	52	53	55	52	53	55
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V1/1~/50/220-440			V1/1~/50/220-240			Y1/3~/50/380-415					
Current	Recommended fuses			A	25						16					

Outdoor Unit				EMRQ	8A	10A	12A	14A	16A
Heating capacity	Nom.			kW	22.4	28	33.6	39.2	44.8
Dimensions	Unit	HeightxWidthxDepth		mm	1,680x1,300x765				
Weight	Unit			kg	331			339	
Operation range	Heating	Min.~Max.		°CWB	-15~20				
	Domestic hot water	Ambient	Min.~Max.	°CDB	-15~35				
Refrigerant	Type / GWP				R-410A / 2,087.5				
	Charge			kg	10.3	10.6	10.8	11.1	
	Charge			TCO_2Eq	21.5	22.1	22.5	23.2	
Piping connections	Liquid	OD		mm	9.52		12.7	13	12.7
	Suction	OD		mm	19.1	22.2		28.6	
	High and low pressure gas	OD		mm	15.9	19.1		22.2	
	Piping length	OU - IU	Max.	m	100				
		System	Equivalent	m	120				
	Total piping length	System	Actual	m	300				
Sound power level	Heating	Nom.		dBA	78		80	83	84
Sound pressure level	Heating	Nom.		dBA	58		60	62	63
Power supply	Phase/Voltage			V	3~/380-415				

(1) Sound levels are measured at: EW 55°C; LW 65°C; Dt 10°C; ambient conditions 7°CDB/6°CWB (2) Sound levels are measured at: EW 70°C; LW 80°C; Dt 10°C; ambient conditions 7°CDB/6°CWB
(3) EW 55°C; LW 65°C; Dt 10°C; ambient conditions 7°CDB/6°CWB (4) EW 70°C; LW 80°C; Dt 10°C; ambient conditions 7°CDB/6°CWB (5)EW 30°C; LW 35°C; Dt 5°C; ambient conditions 7°CDB/6°CWB (ERSQ only)

Domestic hot water tank

Stackable stainless steel domestic hot water tank

- The indoor unit and domestic hot water tank can be stacked to save space, or installed next to each other, if only limited height is available
- Available in 200 and 260 liters
- Heat loss is reduced to a minimum thanks to the high quality insulation
- At necessary intervals, the indoor unit can heat up the water to 60°C to prevent the risk of bacteria growth
- Efficient temperature heat-up: from 10°C to 50°C in only 60 minutes



EKHTS200AC



EKHTS260AC

Accessory				EKHTS	200AC	260AC
Casing	Colour				Metallic grey	
	Material				Galvanised steel (precoated sheet metal)	
Dimensions	Unit	Height	Integrated on indoor unit	mm	2,010	2,285
		Width		mm	600	
		Depth		mm	695	
Weight	Unit	Empty		kg	70	78
Tank	Water volume			l	200	260
	Material				Stainless steel (EN 1.4521)	
	Maximum water temperature			°C	75	
	Insulation	Heat loss		kWh/24h	1.2	1.5
Heat exchanger	Quantity				1	
	Tube material				Duplex steel (EN 1.4162)	
	Face area			m^2	1.56	
	Internal coil volume			l	7.5	

Plastic domestic hot water tank with solar support

- Available in 300 and 500 liters
- Large hot water storage tank to provide domestic hot water at any time
- Heat loss is reduced to a minimum thanks to the high quality insulation
- Space heating support possible (500l tank only)



EKHWP300B

Accessory				EKHWP	300B	500B
Dimensions	Unit	Width		mm	595	790
		Depth		mm	615	790
Weight	Unit	Empty		kg	59	93
Tank	Water volume			l	300	500
	Maximum water temperature			°C	85	
	Insulation	Heat loss		kWh/24h	1.3	1.4
Heat exchanger	Domestic hot water	Tube material			Stainless steel	
		Face area		m^2	5.8	6
		Internal coil volume		l	27.9	29
		Operating pressure		bar	6	
		Average specifc thermal output		W/K	2,790	2,900
	Charging	Tube material			Stainless steel	
		Face area		m^2	2.7	3.8
		Internal coil volume		l	13.2	18.5
		Operating pressure		bar	3	
		Average specifc thermal output		W/K	1,300	1,800
	Auxiliary solar heating	Tube material			Stainless steel	
		Face area		m^2	-	0.5
		Internal coil volume		l	-	2.3
		Operating pressure		bar	3	
		Average specifc thermal output		W/K	-	280

EKS(H/V)-P

Solar collector

Thermal solar collector for hot water production

- Solar collectors can produce up to 70% of the energy needed for hot water production - a major cost saving
- Vertical or horizontal solar collector for domestic hot water production
- High efficiency collectors transfer all the short-wave solar radiation into heat as a result of their highly selective coating
- Easy to install on roof tiles



EKSH-P



EKSV-P

Accessory				EKSV21P	EKSV26P	EKSH26P
Dimensions	Unit	HeightxWidthxDepth	mm	2,000x1,006x85	2,000x1,300x85	1,300x2,000x85
Weight	Unit		kg	35	42	
Volume			l	1.3	1.7	2.1
Surface	Outer		m^2	2.01	2.6	
	Aperture		m^2	1.79	2.35	
	Absorber		m^2	1.8	2.36	
Coating				Micro-therm (absorption max. 96%, Emission ca. 5% +/-2%)		
Absorber				Harp-shaped copper pipe register with laser-welded highly selective coated aluminium plate		
Glazing				Single pane safety glass, transmission +/- 92%		
Allowed roof angle	Min.~Max.		°	15~80		
Operating pressure	Max.		bar	6		
Stand still temperature	Max.		°C	200		

EKSRPS

Pump station

- Save energy and reduce CO_2 emissions with a solar system for domestic hot water production
- Pump station connectable to unpressurised solar system
- Pump station and control provide the transfer of solar heat to the domestic hot water tank



EKSRPS3

Accessory				EKSRPS3
Mounting				On side of tank
Dimensions	Unit	HeightxWidthxDepth	mm	815x230x142
Control	Type			Digital temperature difference controller with plain text display
	Power consumption		W	2
Power supply	Voltage		V	230
Sensor	Solar panel temperature sensor			Pt1000
	Storage tank sensor			PTC
	Return flow sensor			PTC
	Feed temperature and flow sensor			Voltage signal (3.5V DC)

Daikin Altherma Flex Type

for large residential and commercial applications

Why choose Daikin Altherma Flex Type

Daikin Altherma Flex Type is a flexible solution for space heating, domestic hot water and cooling for e.g. apartments, spas, hotels and restaurants

- Low operating costs thanks to high efficiency
- Large hot water volume
- Cooling in the most efficient way thanks to heat recovery technology
- Limited installation space thanks to small footprint of indoor unit and outdoor unit

Heat emitters


All types of heat emitters can be connected thanks to its wide water temperature range (up to 80°C) and its ability to work with multiple set points, allowing a combination of different heat emitters operating at different water temperatures.

Modular system


One or more outdoor units can be connected to several indoor units (maximum 10 indoor units per outdoor unit).

Advanced control and monitoring

To further increase the efficiency, an RTD-W per indoor unit and a sequencing controller for the full heating system can be installed to monitor the exact heating demand.



1 Heating
2 Cooling
3 Hot water



Marketing tools

› Visit the extranet: http://bit.ly/1yfMSKM
› Download the software: http://bit.ly/1ma4se5

Daikin Altherma Flex Type

Floor standing air to water heat pump for large residential and commercial applications

- Floor standing indoor unit up to 9kW
- Low energy bills and low CO_2 emissions
- Energy efficient heating only system based on air to water heat pump technology
- High temperature application: up to 80°C without electric heater
- Flexible configuration with respect to heat emitters
- Inverter controlled scroll compressor



EKHVM(R/Y)D-A

Indoor Unit				EKHVMRD/EKHVMYD	50A	80A	50A	80A
Casing	Colour				Metallic grey			
	Material				Precoated sheet metal			
Dimensions	Unit	HeightxWidthxDepth		mm	705x600x695			
Weight	Unit			kg	92		120	
Operation range	Heating	Ambient	Min./Max.	°C	-15/20			
		Water side	Min./Max.	°C	25/80			
	Cooling	Ambient	Min./Max.	°CDB	-/-		10/43	
		Water side	Min./Max.	°C	-/-		5/20	
	Domestic hot water	Ambient	Min.~Max.	°CDB	-15~35			
		Water side	Min./Max.	°C	45/75			
Refrigerant	Type / GWP				R-134A / 1,430			
	Charge			kg	2			
	Charge			TCO_2Eq	2.9			
Sound pressure level	Nom.			dBA	40 (1) / 43 (2)	42 (1) / 43 (2)	40 (1) / 43 (2)	42 (1) / 43 (2)
	Night quiet mode	Level 1		dBA	38 (1)			
Power supply	Name/Phase/Frequency/Voltage			Hz/V	V1/1~/50/220-240			
Current	Recommended fuses			A	20			

(1) Sound levels are measured at: EW 55°C; LW 65°C (2) Sound levels are measured at: EW 70°C; LW 80°C

Daikin Altherma Flex Type

Floor standing heating only air to water heat pump combinable with existing radiators

- Single or three phase floor standing indoor unit up to 16kW
- Low energy bills and low CO_2 emissions
- Energy efficient heating only system based on air to water heat pump technology
- Combinable with high temperature radiators
- Easy replacement of existing boiler, without changing heating pipes
- High temperature application: up to 80°C without electric heater
- Inverter controlled scroll compressor



EKHBRD_ACV1/Y1

Indoor Unit					EKHBRD	011ACV1	014ACV1	016ACV1	011ACY1	014ACY1	016ACY1
Casing	Colour					Metallic grey					
	Material					Precoated sheet metal					
Dimensions	Unit	HeightxWidthxDepth			mm	705x600x695					
Weight	Unit				kg	144			147		
Operation range	Heating	Ambient	Min./Max.		°C	-20/20					
		Water side	Min./Max.		°C	25/80					
	Domestic hot water	Ambient	Min.~Max.		°CDB	-20~35					
		Water side	Min./Max (booster heater)/ Max.		°C	25/-/80					
Refrigerant	Type / GWP					R-134A / 1,430					
	Charge				kg	2.6					
	Charge				TCO_2Eq	3.7					
Sound pressure level	Nom.				dBA	43 (1) / 46 (2)	45 (1) / 46 (2)	46 (1) / 46 (2)	43 (1) / 46 (2)	45 (1) / 46 (2)	46 (1) / 46 (2)
	Night quiet mode	Level 1			dBA	40 (1)	43 (1)	45 (1)	40 (1)	43 (1)	45 (1)
Power supply	Name/Phase/Frequency/Voltage				Hz/V	V1/1~/50/220-240			Y1/3~/50/380-415		
Current	Recommended fuses				A	25			16		

(1) Sound levels are measured at: EW 55°C; LW 65°C; Dt 10°C; ambient conditions 7°CDB/6°CWB (2) Sound levels are measured at: EW 70°C; LW 80°C; Dt 10°C; ambient conditions 7°CDB/6°CWB

Daikin Altherma Flex Type

- Low energy bills and low CO_2 emissions
- Easy installation and maintenance
- Integrated heat recovery system
- The ultimate heating solution for residential and commercial applications based on air to water heat pump technology
- Customised to meet your building's needs: up to 10 indoor units can be connected to 1 outdoor unit



EMRQ-A

Outdoor Unit					EMRQ	8A	10A	12A	14A	16A
Heating capacity	Nom.				kW	22.4 (1)	28 (1)	33.6 (1)	39.2 (1)	44.8 (1)
Cooling capacity	Nom.				kW	20 (2)	25 (2)	30 (2)	35 (2)	40 (2)
Casing	Colour					Daikin White				
	Material					Painted galvanized steel plate				
Dimensions	Unit	HeightxWidthxDepth			mm	1,680x1,300x765				
Weight	Unit				kg	331			339	
Operation range	Heating	Min.			°CWB	-15				
		Max.			°CWB	20				
	Domestic hot water	Ambient	Min.~Max.		°CDB	-15~35				
	Cooling	Min.			°CDB	10				
		Max.			°CDB	43				
Refrigerant	Type / GWP					R-410A / 2,087.5				
	Charge				kg	10.3	10.6	10.8	11.1	
	Charge				TCO_2Eq	21.5	22.1	22.5	23.2	
Piping connections	Liquid	OD			mm	9.52		12.7	13	12.7
	Suction	OD			mm	19.1	22.2		28.6	
	High and low pressure gas	OD			mm	15.9	19.1		22.2	
	Piping length	OU - IU	Max.		m	100				
		System	Equivalent		m	120				
	Total piping length	System	Actual		m	300				
Sound power level	Heating	Nom.			dBA	78		80	83	84
Sound pressure level	Heating	Nom.			dBA	58		60	62	63
Power supply	Phase/Voltage				V	3~/380-415				
Current	Recommended fuses				A	20	25		40	

(1) Condition: Ta=7°CDB/6°CWB, 100% connection ratio (2) Condition: Ta=35°CDB, 100% connection ratio

EKHTS-AC

Domestic hot water tank

Stackable stainless steel domestic hot water tank

- The indoor unit and domestic hot water tank can be stacked to save space, or installed next to each other, if only limited height is available
- Available in 200 and 260 liters
- Heat loss is reduced to a minimum thanks to the high quality insulation
- At necessary intervals, the indoor unit can heat up the water to 60°C to prevent the risk of bacteria growth
- Efficient temperature heat-up: from 10°C to 50°C in only 60 minutes



Accessory				EKHTS	200AC	260AC
Casing	Colour				Metallic grey	
	Material				Galvanised steel (precoated sheet metal)	
Dimensions	Unit	Height	Integrated on indoor unit	mm	2,010	2,285
		Width		mm	600	
		Depth		mm	695	
Weight	Unit	Empty		kg	70	78
Tank	Water volume			l	200	260
	Material				Stainless steel (EN 1.4521)	
	Maximum water temperature			°C	75	
	Insulation	Heat loss		kWh/24h	1.2	1.5
Heat exchanger	Quantity				1	
	Tube material				Duplex steel (EN 1.4162)	
	Face area			m^2	1.56	
	Internal coil volume			l	7.5	

EKHWP-B

Plastic domestic hot water tank with solar support

- Available in 300 and 500 liters
- Large hot water storage tank to provide domestic hot water at any time
- Heat loss is reduced to a minimum thanks to the high quality insulation
- Space heating support possible (500l tank only)



Accessory			EKHWP	300B	500B
Dimensions	Unit	Width	mm	595	790
		Depth	mm	615	790
Weight	Unit	Empty	kg	59	93
Tank	Water volume		l	300	500
	Maximum water temperature		°C	85	
	Insulation	Heat loss	kWh/24h	1.3	1.4
Heat exchanger	Domestic hot water	Tube material		Stainless steel	
		Face area	m^2	5.8	6
		Internal coil volume	l	27.9	29
		Operating pressure	bar	6	
		Average specifc thermal output	W/K	2,790	2,900
	Charging	Tube material		Stainless steel	
		Face area	m^2	2.7	3.8
		Internal coil volume	l	13.2	18.5
		Operating pressure	bar	3	
		Average specifc thermal output	W/K	1,300	1,800
	Auxiliary solar heating	Tube material		Stainless steel	
		Face area	m^2	-	0.5
		Internal coil volume	l	-	2.3
		Operating pressure	bar	3	
		Average specifc thermal output	W/K	-	280

Heat pump convector

Floor standing unit saving on running costs when combined with under floor heating thanks to its low leaving water temperatures

- Its low height enables the unit to fit perfectly beneath a window
- Can be installed against a wall or recessed
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- Energy efficient heating and cooling system based on air source heat pump technology
- Optimum energy efficiency when connected to a Daikin Altherma low temperature system
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Weekly timer can be set to start heating or cooling anytime on a daily or weekly basis
- Powerful mode can be selected for rapid cooling; after the powerful mode is turned off, the unit returns to the preset mode.



FWXV-A



ARC452A15



Indoor Unit				FWXV	15A	20A
Heating capacity	Total capacity	Nom.	kW		1.5	2.0
			Btu/h		5,100	6,800
Cooling capacity	Total capacity	Nom.	kW		1.2	1.7
	Sensible capacity	Nom.	kW		0.98	1.4
Power input	Heating	Nom.	kW		0.013	0.015
	Cooling	Nom.	kW		0.013	0.015
Dimensions	Unit	HeightxWidthxDepth	mm		600x700x210	
Weight	Unit		kg		15	
Piping connections	Drain/OD/Inlet/Outlet		mm/inch		18/G 1/2/G 1/2	
Sound pressure level	Heating	Nom.	dBA		19	29
	Cooling	Nom.	dBA		19	29
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/60/220-240/220	

Gas condensing boiler

Reliability and peace of mind

Why choose the Daikin gas condensing boiler?


- Low costs for both heating and hot water thanks to new dual heat exchanger resulting in high efficiencies
- Easy installation in minimum space

Low costs for both heating and hot water thanks to new dual heat exchanger

1. With the first heat exchanger, maximum efficiency is reached when heating your home through condensation of the flue gases


[Unique Daikin feature]

2. Also when producing hot water the efficiency is maximised thanks to condensation with the unique second heat exchanger



Unique in the market:
double condensation, not only for heating but also for domestic hot water
resulting in low running costs

Gas condensing boiler



B-pack

Easy installation in minimum space

Installation time can be reduced to the minimum by using our optional pre-assembled B-pack which contains all the components for the functional installation in one module and fits behind the boiler. And as there are fewer parts, the Daikin condensing gas boiler is more reliable and easier to service

Marketing tools

› Visit the extranet: go to extranet.daikineurope.com > Document library

Gas condensing boiler

Top efficiency gas condensing boiler for heating and hot water

› Low running costs for both heating and hot water thanks to new dual heat exchanger
› Maximum heating comfort and domestic hot water when it is most needed
› Quick, easy and compact installation thanks to our optional pre-assembled B-pack, containing all auxiliary components



EKOMB(G)-A

Indoor Unit				EKOMB/EKOMBG	22A	28A	33A	22A	28A	33A
Gas	Consumption (G20)	Min-Max		m^3/h	0.58-2.29	0.74-2.46	0.75-3.39	0.57-2.42	0.75-3.02	0.78-3.39
	Consumption (G31)	Min-Max		m^3/h	0.22-0.87	0.28-0.94	0.28-1.29	0.22-0.92	0.28-1.15	0.30-1.29
	Connection	Diameter		mm	15					
Central heating	Heat input Qn (net calorific value)	Nom	Min-Max	kW	5.6-18.7	7.1-23.7	7.2-27.3	5.5-23.3	7.2-29.1	7.5-32.7
	Heat input Qn (gross calorific value)	Nom	Min-Max	kW	6.2-20.8	7.9-26.3	8.0-30.3	6.1-25.9	8.0-32.3	8.3-36.3
	Output Pn at 80/60°C	Min-Nom		kW	5.4-17.8	6.9-22.8	7.1-26.3	5.4-22.7	7.1-28.4	7.4-32.1
	Output Pnc at 50/30°C	Min-Nom		kW	5.9-18.5	7.6-23.4	7.8-27.1	5.9-23.8	7.7-31.1	8.2-35.0
	Output at 40/30°C	Min		kW	6.0	7.6	7.7	5.9	7.7	8.2
	Water pressure (PMS)	Max		bar	3					
	Water temperature	Max		°C	90					
	Efficiency	Net calorific value		%	107					109
Domestic hot water	Heat input (net calorific value) Qnw	Nom	Min-Max	kW	5.6-22.1	7.1-28.0	7.2-32.7	5.5-23.3	7.2-29.1	7.5-32.7
	Heat input (gross calorific value) Qnw	Nom	Min-Max	kW	6.2-24.6	7.9-31.1	8.0-36.3	6.1-25.9	8.0-32.3	8.3-36.3
	Output	Min-Nom		kW	6.1-21.0	6.6-26.2	7.9-31.5	5.9-22.7	7.7-28.4	8.2-32.1
	Domestic hot water threshold			l/min	1.5					
	Water flow	Rate	Nom	l/min	10 (1)/ 6 (2)	12.5 (1)/ 7.5 (2)	15 (1)/ 9 (2)	10 (1)/ 6 (2)	12.5 (1)/ 7.5 (2)	15 (1)/ 9 (2)
	Temperature	Factory setting		°C	60					
	Operation range	Min/Max		°C	-/-					
Supply air	Connection			mm	100					
	Concentric				Yes					
Flue gas	Connection			mm	60					
Casing	Colour				White - RAL9010					
	Material				Precoated sheet metal					
Dimensions	Unit	HeightxCasingxIntegrated on indoor unitxWidthxDepth		mm	590x-x450x240	650x-x450x240	710x-x450x240	590x-x450x240	650x-x450x240	710x-x450x240
Weight	Unit	Empty		kg	30	33	36	30	33	36
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230					
Electrical power consumption	Max.			W	105			80		
	Standby			W	2					

(1) Setpoint 40°C (2) Setpoint 60°C

Air to air heat pumps optimised for heating for residential use


For more details on the air to air split solutions optimised for heating, please refer to p 101-106



A whole range of energy efficient heat pumps for commercial use

For more details on the commercial line up, please refer to following chapters:

- Sky Air for smaller applications, see p 154
- VRV for medium to large applications, see p 200
- Chillers for large applications, see p 276
- Refrigeration for specific refrigeration needs, see p 394





Comfort all year round

The choice of the right system mostly depends on the specific project. Every home is unique. Furthermore, it concerns the daily living environment. Whether you are talking in terms of construction or renovation, small areas or large spaces, Daikin heat pumps adapt to each layout with efficiency.

Residential applications - split

Why choose a Daikin split system? 76

Products overview 80

Benefits overview 82

Pair applications

	Wall mounted units	84
	FTXZ-N / RXZ-N	85
NEW	FTXJ-LW/S / RXJ-L	88
	FTXG-LW/S / RXG-L	89
NEW	FTXM-K / RXM-L	90
	C/FTXS-K / RXS-L(3)/F8	91
	FTX-J3/GV / RX-K/GV(B)	92
NEW	FTX-K / RX-K	93
NEW	FTXK-AW/S / RXK-A	94
NEW	FTXB-C / RXB-C	95
	Floor standing units	97
	FVXG-K / RXG-L	97
	FVXS-F / RXS-L(3)	98
	Concealed ceiling units	99
	FDXS-F(9) / RXS-L(3)	99
	Flexi type unit	100
	FLXS-B(9) / RXS-L(3)	100
	Optimised for heating	102
	FTXG-LW/S / RXLG-M	102
	FVXG-K / RXLG-M	103
	FTXLS-K / RXLS-M	104
NEW	FTXL-JV / RXL-M3	105
	FVXS-F / RXL-M3	106
	Siesta range	107
NEW	ATXL-JV / ARXL-M	108
	ATXS-K / ARXS-L(3)	109
	ATX-J3 / ARX-K	110
NEW	ATX-K / ARX-K	111
NEW	ATXN-NB / ARXN-NB	112
NEW	ATXB-C / ARXB-C	113

Multi model applications 114

MXS-E/F/G/H/K	116
Combination tables	117
RXYSQ-P8V1	148
Siesta range	150
AMX-E/G	150
Combination tables	151

For more information on Options & Accessories, please refer to page 442 of this catalogue.



Total comfort at home

Why choose a Daikin split system?

- The ideal solution for each application thanks to the **wide range of available products** both for cooling and heating
- **Low energy** bills thanks to high seasonal efficiencies up to A+++ and energy saving features such as intelligent eye and weekly timer
- Control via a **smartphone app** or a user friendly remote controller
- Perfect indoor climate: **whisper quiet sound** level & **perfect airflow** pattern



reddot award 2014
winner

1. Daikin Emura



2. Nexura


Any kind of indoor unit

1. Wall mounted unit:
a wide range from top efficiency and design units to units offering good value for money

2. Floor standing unit:
ideal for bedroom applications to be mounted low on the wall or recessed, offering features like a radiant heat panel.

3. Concealed ceiling unit:
as it can be mounted in a ceiling void, it blends unobtrusively with any décor as only the grilles are visible.

4. Flexi type unit:
can fit on either ceiling or lower wall.



3. FDXS-F(9)

One or multiple rooms?
The choice is yours.

With **1** multi **outdoor unit**, up to **9 indoor units** can be connected. All indoor units can be **individually controlled** with remote control and do not need to be installed in the same room or even at the same time.



5MXS90E

R32 - the refrigerant of the future

R-32

Daikin is leading the way to the most energy efficient product range with the lowest environmental impact

- **68% Reduction in environmental impact** compared to R-410A
- **High energy efficiency** leading directly to lower energy consumption
- Already a wide range of wall mounted units available in R32 (FTXZ-N, FTXJ-LW/S, FTXM-K)

Online controller
Always in control, no matter where you are

Control your indoor from any location with an app (available for iOS & Android), via your local network or internet. It is now connectable to most of the split indoors.

Optimised for heating

Our special split range optimised for heating is suitable for colder climates, even withstanding severe winter conditions

- Guaranteed capacity down to -25°C
- High heating energy efficiency with SCOP up to A++
- Improved defrost thanks to unique **free hanging coil** technology





FVXS-F



FTXS-K



NEXURA FVXG-K




URURU SARARA FTXZ-N



DAIKIN EMURA FTXG-LS

Products overview

Indoor units

Type	Model	Product name		15	20	25	35	42	50	60	71
Wall mounted	Ururu Sarara Complete climate control with (de)humidification, air purification & ventilation with top efficiencies in heating & cooling	FTXZ-N R-32				● (pair only)	● (pair only)		● (pair only)		
	Daikin Emura Design at its best, delivering superior efficiency and comfort	FTXJ-LW/S R-32			● (pair only)	● (pair only)	● (pair only)		● (pair only)		
		FTXG-LW/S			●	●	●		●		
	Wall mounted unit Discreet, modern design for optimal efficiency and comfort thanks to 2 area intelligent eye	CTXS-K		● (multi only)			● (multi only)				
		FTXS-K			●	●	●	●	●		
		FTXM-K R-32			● (pair only)	● (pair only)	● (pair only)	● (pair only)	● (pair only)		
		FTXLS-K				● (pair only)	● (pair only)				
	Wall mounted unit For optimal efficiency and comfort, ideal for large rooms	FTXS-G								●	●
	Wall mounted unit Providing high efficiency and comfort	FTX-J3			● (2-port multi only)	● (2-port multi only)	● (2-port multi only)				
		FTX-GV							● (pair only)	● (pair only)	● (pair only)
		FTXL-JV				● (pair only)	● (pair only)				
		FTX-K			● (2-port multi only)	● (2-port multi only)	● (2-port multi only)		● (pair only)	● (pair only)	
	Wall mounted unit For low energy consumption and pleasant comfort	FTXK-AW/S				● (pair only)	● (pair only)		● (pair only)	● (pair only)	
		FTXB-C				● (pair only)	● (pair only)		● (pair only)	● (pair only)	
Floor standing	Nexura - floor standing unit with radiant heat panel Stylish floor standing unit with radiant heat panel for comfortable heat and very low noise	FVXG-K				●	●		●		
	Floor standing unit Floor standing unit for optimal heating comfort thanks to dual airflow	FVXS-F				●	●		●		
Ceiling concealed	Slim concealed ceiling unit Compact concealed ceiling unit, with a height of only 200mm	FDXS-F(9)				●	●		●	●	
Flexi type	Flexi type unit Flexible unit, ideal for rooms without false ceiling, can fit on either ceiling or wall	FLXS-B(9)				●	●		●	● (multi only)	
Wall mounted Siesta	Wall mounted unit Siesta, discreet, modern unit for optimal efficiency and comfort thanks to 2 area intelligent eye	ATXS-K			● (multi only)	●	●		●		
	Wall mounted unit Siesta, providing high efficiency and comfort even at low ambient temperatures	ATXL-JV				● (pair only)	● (pair only)				
	Wall mounted unit Siesta, providing high efficiency and comfort	ATX-J3			● (2-port multi only)	● (2-port multi only)	● (2-port multi only)				
		ATX-K			● (2-port multi only)	● (2-port multi only)	● (2-port multi only)				
	Wall mounted unit Siesta, offering good value for money and ensuring a steady supply of clean air	ATXN-NB				pair only	pair only		pair only	pair only	
	Wall mounted unit Siesta, for low energy consumption and pleasant comfort	ATXB-C				pair only	pair only		pair only	pair only	

Outdoor units

Type	Model	Product name		20	25	35	40	42	50	52	60	68	71	80	90	4HP	5HP	6HP
Air cooled	Pair heat pump	RXZ-N	R-32		●	●			●									
		RXJ-L	R-32	●	●	●			●									
		RXG-L		●	●	●			●									
		RXM-L	R-32	●	●	●		●	●									
		RXS-L3		●	●	●												
		RXS-L						●	●		●							
		RXS-F8											●					
		RX-K		●	●	●			●		●							
		RX-GV (B)							●		●		●					
		RXK-A			●	●			●		●							
		RXB-C			●	●			●		●							
	Pair heat pump down to -25°C	RXLG-M			●	●												
		RXLS-M			●	●												
		RXL-M3			●	●												
	Multi heat pump	2-port MXS-H					●		●									
		3-port MXS-K					●											
		3-port MXS-E								●								
		3-port MXS-G										●						
		4-port MXS-F										●						
		4-port MXS-E												●				
		5-port MXS-E													●			
		RXYSQ-P8V1 VRV III-S														●	●	●
Air cooled Siesta	Pair heat pump	ARXS-L3			●	●												
		ARXS-L							●									
	Pair heat pump down to -25°C	ARXL-M			●	●												
	Pair heat pump	ARX-K		●	●	●												
		ARXN-NB			●	●			●		●							
		ARXB-C			●	●			●		●							
	Multi heat pump	2-port AMX-G					●		●									
		3-port AMX-E								●								

Benefits overview

Split

		Wall mounted								
		FTXZ-N R-32	FTXJ-LW/S R-32	FTXG-LW/S	FTXM-K R-32	CTXS-K	FTXS-K	FTXLS-K	FTXS-G	FTX-J3
										
We care icons	Econo mode	•	•	•	•	•	•	•	•	•
	2-area intelligent eye		•	•	• 35,42,50 class		• 35,42,50 class	•		
	3- area intelligent eye	•								
	Movement sensor				• 20,25 class	•	• 20,25 class		•	
	Energy saving during operation standby	•	•	•	•	•	•	•		•
	Home leave operation									
	Night set mode		•	•	•	•	•	•	•	•
	Fan only	•	•	•	•	•	•	•	•	•
	Auto cleaning filter	•								
Comfort	Comfort mode	•	•	•	•	•	•	•	•	•
	Powerful mode	•	•	•	•	•	•	•	•	•
	Auto cooling-heating changeover	•	•	•	•	•	•	•	•	•
	Whisper quiet (down to 19dBA)	•	•	•	•	•	•	•		
	Radiant heat									
	Indoor unit silent operation	•	•	•	•	•	•	•	•	•
	Comfortable sleeping mode	•								
	Outdoor unit silent operation	•	•	•	•	•	•	•	•	•
Air flow	3-D Air flow	•	•	•	• 35,42,50 class		• 35,42,50 class	•	•	
	Vertical auto swing	•	•	•	•	•	•	•	•	•
	Horizontal auto swing	•	•	•	• 35,42,50 class		• 35,42,50 class	•	•	
	Auto fan speed	•	•	•	•	•	•	•	•	•
Humidity control	Fan speed steps	5	5	5	5	5	5	5	5	5
	Ururu - humidification	•								
	Sarara - dehumidification	•								
	Dry programme		•	•	•	•	•	•	•	•
Air treatment	Flash streamer	•								
	Titanium photocatalytic air purification filter	•	•	•	•	•	•	•	•	•
	Photocatalytic deodorising filter									
	Air filter									
Remote control & timer	Online controller	• available from Jan '15	•	•	•	•	•	•	•	•
	Weekly timer		•	•	•	•	•	•	•	
	24 Hour timer	•	•	•	•	•	•	•	•	•
	Infrared remote control	•	•	•	•	•	•	•	•	•
	Wired remote control		•	•	•	•	•	•	•	•
	Centralised remote control	•	•	•	•	•	•	•	•	
Other funtions	Auto-restart	•	•	•	•	•	•	•	•	•
	Self-diagnosis	•	•	•	•	•	•	•	•	•
	Multi model application			•		•	•		•	•
	VRV for residential application			•		•	•		•	
	Guaranteed operation down to -25°C			• with RXLG-M				•		

For explanation on the benefits, see the end of this catalogue.

					Floor standing		Concealed ceiling	Flexi type	Siesta Wall mounted					
FTXL-JV	**FTX-GV**	**FTX-K**	**FTXK-AW/S**	**FTXB-C**	**FVXG-K**	**FVXS-F**	**FDXS-F(9)**	**FLXS-B(9)**	**ATXS-K**	**ATXL-JV**	**ATX-J3**	**ATX-K**	**ATXB-C**	**ATXN-NB**
														
		●		●	●	●			●		●		●	
									● 35,50 class					
	●								● 20,25 class					
		●		●					●		●	●	●	
	●							●						
●	●			●	●	●			●		●		●	
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●				●					●	●	●		●	
●	●			●	●	●		●	●	●	●		●	●
●	●	●	●	●	●	●		●	●	●	●	●	●	●
		●	●	●	●				●			●	●	●
					●									
●	●			●	●	●		●	●		●		●	
			●	●									●	●
	●				●	●		●			●			
	●								● 35,50 class					
●	●	●	●	●	●	●		●	●	●	●	●	●	●
	●								● 35,50 class					
●	●	●	●	●	●	●		●	●	●	●	●	●	●
5	5	5	3	3	5	5	3	5	5	5	5	3	3	5
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●			●	●			●	●	●	●		
								●						
			●	●			●	●					●	●
●	●	●			●	●		●	●	●	●	●		
					●	●	● depending on controller		●					
●	●	●	●	●	●	●	● depending on controller	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●			●		●		●	●	●	●		
	●				●	●	●	●	●					
●	●			●	●	●	●	●	●	●	●		●	●
●	●			●	●	●	●	●	●	●	●		●	●
		●			●	●	●	●	●		●	●		
					●	●		●						
●					● with RXLG-M	● with RXL-M3				●				

*Note: blue cells contain preliminary data

Ururu Sarara

The best of the best



reddot design award
winner 2013

Why choose Ururu Sarara?

- First R32 air to air heat pump in the European market at lowest environmental impact thanks to high energy efficiency and use of low GWP refrigerant.
- **Market leader in terms of seasonal efficiency.**
- Advanced technologies have been integrated to create the perfect indoor climate by controlling not only the room temperature but **also air quality and humidity**.

Benefits

› Low energy bill thanks to very high seasonal energy efficiency (A+++ in heating and cooling)
› Perfect indoor comfort thanks to 5 air treatment technologies and 3 area intelligent eye
› Optimal airflow distribution: cools down spaces in a fast, efficient and controllable way.
› Award winning design
› No need to clean filters thanks to self cleaning filter
› New remote control: user friendly with backlight and information on actual energy consumption
› As easy to install as any R-410A unit
› Wide operation range, from -20°C to +43°C
› Online controller: always in control, no matter where you are (available from January 2015)

Marketing tools

› Visit our extranet: extranet.daikineurope.com > document library
› Visit the website: www.daikineurope.com/for-your-home/needs/ventilation-and-air-purification/ventilation/index.jsp
› Download the software: http://seasoncalc.daikin.eu




5 air treatment techniques

Perfect indoor climate
› Cooling & heating
› Fresh air (ventilation)
› Ururu Humidification
› Sarara Dehumidification
› Air purification

Lowest environmental impact

› SEER AND SCOP A+++
› Low GWP refrigerant R32 R-32



Perfect comfort thanks to 3 area intelligent eye:

› Air flow is sent to a zone other than where the person is located at that moment. Detection is done in 3 directions: left, front & right.
› If no people are detected, the unit automatically switches over to energy-efficient setting and eventually switches off.

Ururu Sarara

R-32

Wall mounted unit

Complete climate control with (de)humidification, air purification & ventilation with top efficiencies in heating & cooling

- SEER + SCOP = A+++ on the entire range
- Unique combination of humidification, dehumidification, ventilation, air purification and heating & cooling in 1 system
- 3 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment. Detection is done in 3 directions: left, front and right. If no people are detected, the unit will automatically switch over to the energy-efficient setting
- No need to clean filters manually
- Reddot design award winner 2013



Efficiency data				FTXZ + RXZ	25N + 25N	35N + 35N	50N + 50N
Cooling capacity	Min./Nom./Max.			kW	0.6/2.5/3.9	0.6/3.5/5.3	0.6/5.0/5.8
Heating capacity	Min./Nom./Max.			kW	0.6/3.6/7.5	0.6/5.0/9.0	0.6/6.3/9.4
Power input	Cooling	Min./Nom./Max.		kW	0.11/0.41/0.88	0.11/0.66/1.33	0.11/1.10/1.60
	Heating	Min./Nom./Max.		kW	0.10/0.62/2.01	0.10/1.00/2.53	0.10/1.41/2.64
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+++		
		Pdesign		kW	2.50	3.50	5.00
		SEER			9.54	9.00	8.60
		Annual energy consumption		kWh	92	136	203
	Heating (Average climate)	Energy label			A+++		
		Pdesign		kW	3.50	4.50	5.60
		SCOP			5.90	5.73	5.50
		Annual energy consumption		kWh	831	1,100	1,427
Nominal efficiency	EER				6.10	5.30	4.55
	COP				5.80	5.00	4.47
	Annual energy consumption			kWh	205	330	550
	Energy label	Cooling/Heating			A/A		

Indoor unit				FTXZ	25N	35N	50N
Casing	Colour				White		
Dimensions	Unit	HeightxWidthxDepth		mm	295x798x372		
Weight	Unit			kg	15		
Air filter	Type				Auto cleaning filter		
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	10.7/7.5/5.3/4.0	12.1/8.4/5.6/4.0	15.0/9.2/6.6/4.6
	Heating	High/Nom./Low/Silent operation		m^3/min	11.7/8.6/6.7/4.8	13.3/9.2/6.9/4.8	14.4/10.7/7.7/5.9
Sound power level	Cooling			dBA	54	57	60
	Heating			dBA	56	57	59
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/33/26/19	42/35/27/19	47/38/30/23
	Heating	High/Nom./Low/Silent operation		dBA	39/35/28/19	42/36/29/19	44/38/31/24
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Control systems	Infrared remote control				ARC477A1		

Outdoor unit				RXZ	25N	35N	50N
Dimensions	Unit	HeightxWidthxDepth		mm	693x795x300		
Weight	Unit			kg	50		
Sound power level	Cooling			dBA	59	61	63
	Heating			dBA	59	61	64
Sound pressure level	Cooling	High		dBA	46	48	49
	Heating	High		dBA	46	48	50
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~43		
	Heating	Ambient	Min.~Max.	°CWB	-20~18		
Refrigerant	Type/Charge/GWP			kg	R-32 / 1.34 / 675		
	Charge			TCO_2Eq	0.9		
Piping connections	Liquid	OD		mm	6		
	Gas	OD		mm	9.5		
	Piping length	OU - IU	Max.	m	10		
	Level difference	IU - OU	Max.	m	8		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load



Daikin Emura
Form. Function. Redesigned

Why choose Daikin Emura?

- Unique **design**. Designed in Europe for Europe.
- High seasonal **efficiency**, further improved by energy saving techniques like weekly timer and intelligent eye.
- Optimal **comfort** thanks to advanced technologies e.g. 2-area intelligent eye, whisper quiet operation and online controller.

Benefits


› A remarkable blend between iconic design and engineering excellence
› Stylish design in matt crystal white and silver
› The choice between R32 and R-410A model
› Whisper quiet with sound levels down to 19 dBA
› Horizontal and vertical autoswing
› 2-area intelligent eye saves energy by reducing the set point if nobody is present and directs airflow away from people, thus avoiding cold draught
› Weekly timer
› Guaranteed operation down to -25°C (with RXLG-M)
› Connectable to pair, multi and (mini) VRV
› Online controller:
Always in control no matter where you are





Marketing tools

› Visit the extranet:
extranet.daikineurope.com > document library
› Visit the website: www.daikinemura.eu
› Download the software:
http://seasoncalc.daikin.eu



reddot award 2014
winner

Unique design

Daikin Emura's most obvious asset is its looks.
The sober but stylish appearance adds an additional dimension to Daikin's well-known brand values of superior comfort and quality.
Daikin is the only manufacturer offering a design model designed in Europe for the European market, using European technical and design standards to meet exactly with the customer's needs.
Daikin Europe N.V. is also proud to announce that Daikin Emura has been awarded with Reddot design award 2014.

Improved energy efficiency

Seasonal efficiency gives a more realistic indication on how efficient air conditioners operate over an entire heating or cooling season. The label includes multiple classifications from A+++ to G.
Daikin Emura achieves high energy efficiencies:

› SEER up to A+++
› SCOP up to A++

Lowest environmental impact

› Possible to choose between an R32 and R-410A model

R-32 R-410A

Comfort

› 2-Area intelligent eye : Air flow is sent to a zone other than where the person is located at that moment. If no people are detected, the unit will automatically switch over to the energy efficient setting.
› Whisper quiet : Daikin Emura is whisper quiet with sound levels down to 19dBA.

DAIKIN emura

R-32

Wall mounted unit

Design at its best, delivering superior efficiency and comfort

- Seasonal efficiency values up to A+++
- Choosing for an R32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Remarkable blend of iconic design and engineering excellence with an elegant finish in silver and anthracite or in matt crystal white
- Daikin Emura has been awarded with Reddot design award 2014 by an international jury, thanks to its excellent design
- Designed to perfectly balance technological leadership and the beauty of aerodynamics
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!



Efficiency data				FTXJ + RXJ	*20LW/S + 20L	*25LW/S + 25L	*35LW/S + 35L	*50LW/S + 50L
Cooling capacity	Min./Nom./Max.			kW	1.3/2.3/2.8	1.3/2.4/3.0	1.4/3.5/3.8	1.7/4.8/5.3
Heating capacity	Min./Nom./Max.			kW	1.3/2.5/4.3	1.3/3.4/4.5	1.4/4.0/5.0	1.7/5.8/6.5
Power input	Cooling	Nom.		kW	0.5	0.52	0.88	1.36
	Heating	Nom.		kW	0.5	0.77	0.98	1.59
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+++		A++	
		Pdesign		kW	2.30	2.40	3.50	4.80
		SEER			8.58	8.53	7.03	6.70
		Annual energy consumption		kWh	94	99	175	251
	Heating (Average climate)	Energy label			A++			A+
		Pdesign		kW	2.10	2.70	3.00	4.60
		SCOP			4.60			4.24
		Annual energy consumption		kWh	639	821	913	1,519
Nominal efficiency	EER				4.61		3.98	3.54
	COP				5	4.42	4.06	3.65
	Annual energy consumption			kWh	249	260	440	678
	Energy label	Cooling			A			
		Heating			A			

Indoor unit				FTXJ	*20LW/S	*25LW/S	*35LW/S	*50LW/S
Casing	Colour				White/Silver			
Dimensions	Unit	HeightxWidthxDepth		mm	303x998x212			
Weight	Unit			kg	12			
Fan - Air flow rate	Cooling	High		m^3/min	8.9		10.9	
	Heating	High		m^3/min	10.2	11	12.4	12.6
Sound power level	Cooling			dBA	54		59	60
	Heating			dBA	56		59	60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/25/19		45/34/26/20	46/40/35/32
	Heating	High/Nom./Low/Silent operation		dBA	40/34/28/19	41/34/28/19	45/37/29/20	47/41/35/32
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control system	Infrared remote control				ARC466A1			

Outdoor unit				RXJ	*20L	*25L	*35L	*50L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285			735x825x300
Weight	Unit			kg	34			47
Sound power level	Cooling			dBA	61		63	
Sound pressure level	Cooling	High/Low		dBA	46/43		48/44	
	Heating	High/Low		dBA	47/44		48/45	48/44
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46			
	Heating	Ambient	Min.~Max.	°CWB	-15~20			
Refrigerant	Type/Charge/GWP			kg	R-32 / 0.9 / 675			R-32 / 1.1 / 675
	Charge			TCO_2Eq	0.6			0.7
Piping connections	Liquid	OD		mm	6.35			
	Gas	OD		mm	9.5			12.7
	Piping length	OU - IU	Max.	m	20			30
		System	Chargeless	m	10			
	Level difference	IU - OU	Max.	m	15			20
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Design at its best, delivering superior efficiency and comfort

- Seasonal efficiency values up to A+++
- Remarkable blend of iconic design and engineering excellence with an elegant finish in silver and anthracite or in matt crystal white
- Daikin Emura has been awarded with Reddot design award 2014 by an international jury, thanks to its excellent design
- Designed to perfectly balance technological leadership and the beauty of aerodynamics
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!



FTXG-LS



RXG20-25-35L



ARC466A1

Efficiency data				FTXG + RXG	20LW/S + 20L	25LW/S + 25L	35LW/S + 35L	50LW/S + 50L
Cooling capacity	Min./Max.			kW	1.3/2.8	1.3/3.0	1.4/3.8	1.7/5.3
Heating capacity	Min./Max.			kW	1.3/4.3	1.3/4.5	1.4/5.0	1.7/6.5
Power input	Cooling	Min./Nom./Max.		kW	0.32/0.50/0.76	0.32/0.52/0.82	0.35/0.88/1.19	0.37/1.36/1.88
	Heating	Min./Nom./Max.		kW	0.31/0.50/1.12	0.31/0.77/1.32	0.32/0.99/1.49	0.31/1.59/2.49
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+++		A++	
		Pdesign		kW	2.30	2.40	3.50	4.80
		SEER			8.52	8.50	7.00	6.70
		Annual energy consumption		kWh	94	99	175	251
	Heating (Average climate)	Energy label			A++			A+
		Pdesign		kW	2.10	2.70	3.00	4.60
		SCOP			4.60			4.24
		Annual energy consumption		kWh	639	821	913	1,519
Nominal efficiency	EER				4.59		3.97	3.53
	COP				5.00	4.42	4.06	3.65
	Annual energy consumption			kWh	250	262	441	680
	Energy label	Cooling/Heating			A/A			

Indoor unit				FTXG	20LW/S	25LW/S	35LW/S	50LW/S
Casing	Colour				White/Silver			
Dimensions	Unit	HeightxWidthxDepth		mm	303x998x212			
Weight	Unit			kg	12			
Air filter	Type				Removable / washable / mildew proof			
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	8.9/6.6/4.4/2.6		10.9/7.8/4.8/2.9	10.9/8.9/6.8/3.6
	Heating	High/Nom./Low/Silent operation		m^3/min	10.2/8.4/6.3/3.8	11.0/8.6/6.3/3.8	12.4/9.6/6.9/4.1	12.6/10.5/8.1/5.0
Sound power level	Cooling			dBA	54		59	60
	Heating			dBA	56		59	60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/25/19		45/34/26/20	46/40/35/32
	Heating	High/Nom./Low/Silent operation		dBA	40/34/28/19	41/34/28/19	45/37/29/20	47/41/35/32
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				ARC466A1			

Outdoor unit				RXG	20L	25L	35L	50L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285			735x825x300
Weight	Unit			kg	35			48
Sound power level	Cooling			dBA	61		63	
	Heating			dBA	62		63	
Sound pressure level	Cooling	High/Silent operation		dBA	46/43		48/44	
	Heating	High/Silent operation		dBA	47/44		48/45	48/44
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46 (3)			
	Heating	Ambient	Min.~Max.	°CWB	-15~18			
Refrigerant	Type/Charge/GWP			kg	R-410A / 1.05 / 2,087.5			R-410A / 1.6 / 2,087.5
	Charge			TCO_2Eq	2.2			3.3
Piping connections	Liquid	OD		mm	6			
	Gas	OD		mm	9.5			12.7
	Piping length	OU - IU	Max.	m	20			30
		System	Chargeless	m	10			
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)			
	Level difference	IU - OU	Max.	m	15			20
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (3) Operation range in combination with Nexura, FVXG-K, cooling: min. 10°CDB - max. 46°CDB; heating: min. -15°CWB - max. 18°CWB

R-32

Wall mounted unit

Discreet, modern design for optimal efficiency and comfort thanks to 2 area intelligent eye

- Choosing for an R32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- Discreet, modern design. Its smooth curve blends beautifully with the wall resulting in an unobtrusive presence that matches all interior décors.
- High quality matt crystal white finish
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Ideal for installation in bedrooms (20,25 class) and larger or irregular shaped living areas (35,42,50 class)
- 2 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting (35,42,50 class)
- Online controller (optional): control your indoor from any location with an app, via your local network or internet



Efficiency data				FTXM + RXM	*20K + 20L	*25K + 25L	*35K + 35L	*42K + 42L	*50K + 50L
Cooling capacity	Min./Nom./Max.			kW	1.3/2.0/2.8	1.3/2.5/3.2	1.4/3.5/4.0	1.7/4.2/5.0	1.7/5.0/5.3
Heating capacity	Min./Nom./Max.			kW	1.3/2.5/4.3	1.3/2.8/4.7	1.4/4.0/5.2	1.7/5.4/6	1.7/5.8/6.5
Power input	Cooling	Nom.		kW	0.43	0.57	0.84	1.18	1.41
	Heating	Nom.		kW	0.55	0.62	0.84	1.31	1.45
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++				
		Pdesign		kW	2.00	2.50	3.50	4.20	5
		SEER			7.78	8.23	7.74	7.02	7
		Annual energy consumption		kWh	95	111	164	216	257
	Heating (Average climate)	Energy label			A++			A+	
		Pdesign		kW	2.30	2.50	3.60	4.00	4.6
		SCOP			4.90		4.85	4.21	
		Annual energy consumption		kWh	675	732	1,039	1,334	1,535
Nominal efficiency	EER				4.6	4.58	4.78	4.14	4.02
	COP				4.65	4.39	4.17	3.56	3.55
	Annual energy consumption			kWh	217	273	366	507	622
	Energy label	Cooling			A				
		Heating			A			B	

Indoor unit				FTXM	*20K	*25K	*35K	*42K	*50K
Casing	Colour				White				
Dimensions	Unit	HeightxWidthxDepth		mm	289x780x215		289x900x215		
Weight	Unit			kg	8		11		
Fan - Air flow rate	Cooling	High		m^3/min	8.8	9.1	11.2		11.9
	Heating	High		m^3/min	9.5	10.0	12.1	12.4	13.3
Sound power level	Cooling			dBA	56	57	59		60
	Heating			dBA	56	57	59		60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	40/32/24/19	41/33/25/19	45/37/29/19	45/39/33/21	46/40/34/23
	Heating	High/Nom./Low/Silent operation		dBA	40/34/27/19	41/34/27/19	45/39/29/19	45/39/33/22	47/40/34/24
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				
Control system	Infrared remote control				ARC466A6				

Outdoor unit				RXM	*20L	*25L	*35L	*42L	*50L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285			735x825x300	
Weight	Unit			kg	34			47	
Sound power level	Cooling			dBA	61		63		
	Heating			dBA	62		63		
Sound pressure level	Cooling	High/Low		dBA	46/43		48/44	47/44	
	Heating	High/Low		dBA	47/44		48/45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46				
	Heating	Ambient	Min.~Max.	°CWB	-15~24				
Refrigerant	Type/Charge/GWP			kg	R-32 / 0.9 / 675		R-32 / 0.9 / 675	R-32 / 1.35 / 675	R-32 / 1.5 / 675
	Charge			TCO_2Eq	0.6			0.9	1.0
Piping connections	Liquid	OD		mm	6.35				
	Gas	OD		mm	9.5			12.7	
	Piping length	OU - IU	Max.	m	20			30	
		System	Chargeless	m	10				
	Level difference	IU - OU	Max.	m	15			20	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Discreet, modern design for optimal efficiency and comfort thanks to 2 area intelligent eye

- Discreet, modern design. Its smooth curve blends beautifully with the wall resulting in an unobtrusive presence that matches all interior décors.
- High quality matt crystal white finish
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Ideal for installation in bedrooms (20,25 class) and larger or irregular shaped living areas (35,42,50 class)
- 2 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting (FTXS35,42,50K)
- Online controller (optional): control your indoor from any location with an app, via your local network or internet



C/FTXS-K

RXS42L

ARC466A6

Efficiency data				FTXS + RXS		*20K + 20L3	*25K + 25L3	*35K + 35L3	42K + 42L	50K + 50L	60G + 60L	71G + 71F8
Cooling capacity	Min./Nom./Max.			kW	Only available in multi model application	1.3/2.0/2.6	1.3/2.5/3.2	1.4/3.5/4.0	1.7/4.20/5.0	1.7/5.00/5.3	1.7/6.0/6.7	2.3/7.10/8.5
Heating capacity	Min./Nom./Max.			kW		1.3/2.5/3.5	1.3/2.8/4.7	1.4/4.0/5.2	1.7/5.40/6.0	1.7/5.80/6.5	1.7/7.0/8.0	2.3/8.20 /10.2
Power input	Cooling	Min./Nom./Max.		kW		-/0.43/-	-/0.57/-	-/0.86/-	0.32/1.18 /2.33	0.35/1.41 /1.81	0.44/1.99 /2.40	0.57/2.35 /3.20
	Heating	Min./Nom./Max.		kW		-/0.53/-	-/0.60/-	-/0.84/-	0.40/1.31 /1.98	0.30/1.45 /2.00	0.40/2.04 /2.81	0.52/2.55/ 3.82
Seasonal efficiency (according to EN14825)	Cooling	Energy label				A++			A++		A	
		Pdesign		kW		2.00	2.50	3.50	4.20	5.00	6.00	7.10
		SEER				7.40	7.90	7.47	6.80		5.58	5.28
		Annual energy consumption		kWh		95	111	164	216	257	376	471
	Heating (Average climate)	Energy label				A++			A+		A	
		Pdesign		kW		2.30	2.50	3.60	4.00	4.60	4.80	6.20
		SCOP				4.77	4.78	4.85	4.20		3.89	3.81
		Annual energy consumption		kWh		675	732	1,039	1,334	1,535	1,728	2,276
Nominal efficiency	EER					4.65	4.39	4.07	3.56	3.55	3.02	
	COP					4.72	4.67	4.76	4.12	4.00	3.43	3.22
	Annual energy consumption			kWh		215	285	430	590	705	995	1,175
	Energy label	Cooling				A			A		B	
		Heating				A			A		B	C

Indoor unit				*CTXS15K	*CTXS35K	* FTXS 20K	* FTXS 25K	* FTXS 35K	FTXS 42K	FTXS 50K	FTXS 60G	FTXS 71G
Casing	Colour			White					White			
Dimensions	Unit	HeightxWidthxDepth	mm	289x780x215				289x900x215	298x900x215		290x1,050x250	
Weight	Unit		kg	8				11	11		12	
Air filter	Type			Removable / washable / mildew proof					Removable / washable / mildew proof			
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation	m^3/min	-		8.80/-/-/-	9.10/-/-/-	11.2/-/-/-	11.2/11.2/7.0/4.1	11.9/11.9/7.4/4.5	16.0/16.0/11.3/10.1	17.2/17.2/11.5/10.5
	Heating	High/Nom./Low/Silent operation	m^3/min	-/-/-/-					12.4/10.0/7.8/5.2	13.3/10.8/8.4/5.5	17.2/14.9/12.6/11.3	19.5/16.7/14.2/12.6
Sound power level	Cooling		dBA	-	58			59	59	60		63
	Heating		dBA	-	58			59	59	60	59	62
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dBA	-	40/32/24/19	41/33/25/19		45/37/29/19	45/39/33/21	46/40/34/23	45/41/36/33	46/42/37/34
	Heating	High/Nom./Low/Silent operation	dBA	-	40/34/27/19	41/34/27/19		45/39/29/19	45/39/33/22	47/40/34/24	44/40/35/32	46/42/37/34
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 220-240					1~ / 50 / 220-240			
Control systems	Infrared remote control			-					ARC466A6		ARC452A3	

Outdoor unit				RXS		*20L3	*25L3	*35L3	42L	50L	60L	71F8
Dimensions	Unit	HeightxWidthxDepth	mm		Only available in multi model application	550x765x285			550x765x285	735x825x300		770x900x320
Weight	Unit		kg			31.5			39	47	48	71
Sound power level	Cooling		dBA			59		61	61	62		65
	Heating		dBA			59		61	61	62		66
Sound pressure level	Cooling	High/Low/Silent operation	dBA			-/-/-			48/-/44	48/44/-	49/46/-	52/-/49
	Heating	High/Low/Silent operation	dBA			-/-/-			48/-/45	48/45/-	49/46/-	52/-/49
Operation range	Cooling	Ambient Min.~Max.	°CDB			-10~46			-10~46			
	Heating	Ambient Min.~Max.	°CWB			-15~18			-15~18			
Refrigerant	Type/Charge/GWP		kg			R-410A / 1 / 2,087.5		R-410A / 1 .2 / 2,087.5	R-410A / 1 .3 / 2,087.5	R-410A / 1 .7 / 2,087.5	R-410A / 1 .5 / 2,087.5	R-410A / 2.3 / 2,087.5
	Charge		TCO_2Eq			2.1		2.5	2.7	3.5	3.1	4.8
Piping connections	Liquid	OD	mm			6			6.35			
	Gas	OD	mm			9.5			9.5	12.7		15.9
	Piping length	OU - IU Max.	m			-			-	30		
		System Chargeless	m			-			-			10
	Additional refrigerant charge		kg/m			-			-	0.020 (for piping length exceeding 10m)		
	Level difference	IU - OU Max.	m			-			-	20.0		
Power supply	Phase / Frequency / Voltage		Hz / V			1~ / 50 / 220-240			1~ / 50 / 220-230-240			
Current - 50Hz	Maximum fuse amps (MFA)		A			16			16	20		-

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Wall mounted unit providing high efficiency and comfort

- ECONO mode decreases power consumption so that other appliances that need large power consumption can be used
- Comfort mode guarantees draught free operation by preventing that warm or cold air is directly blown on to the body
- Titanium apatite photocatalytic air purification filter removes airborne microscopic particles, powerfully decomposes odours and helps to prevent the propagation of bacteria, viruses, microbes to ensure a steady supply of clean air
- Online controller (optional): control your indoor from any location with an app, via your local network or internet



Efficiency data				FTX + RX	*20J3 + 20K	*25J3 + 25K	*35J3 + 35K	50GV + 50GV	60GV + 60GVB	71GV + 71GVB
Cooling capacity	Min./Nom./Max.			kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.3/3.8	1.7/5.0/6.0	1.7/6.0/6.7	2.3/7.10/8.5
Heating capacity	Min./Nom./Max.			kW	1.3/2.5/3.5	1.3/2.8/4.0	1.3/3.5/4.8	1.7/5.8/7.7	1.7/7.0/8.0	2.3/8.20/10.2
Power input	Cooling	Min./Nom./Max.		kW	-/0.55/-	-/0.71/-	-/0.97/-	0.44/1.55/2.08	0.44/1.99/2.40	0.57/2.35/3.20
	Heating	Min./Nom./Max.		kW	-/0.59/-	-/0.68/-	-/0.92/-	0.40/1.60/2.53	0.40/2.04/2.81	0.52/2.55/3.82
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++			A+	A	B
		Pdesign		kW	2.00	2.50	3.30	5.00	6.00	7.10
		SEER			6.10			5.63	5.37	4.97
		Annual energy consumption		kWh	115	143	189	311	391	500
	Heating (Average climate)	Energy label			A+			A+	A	
		Pdesign		kW	2.20	2.40	2.80	4.60	4.80	6.20
		SCOP			4.26	4.10		4.08	3.88	3.81
		Annual energy consumption		kWh	723	820	956	1,578	1,730	2,276
Nominal efficiency	EER				3.64	3.54	3.4	3.23	3.02	3.02
	COP				4.24	4.1	3.8	3.63	3.43	3.22
	Annual energy consumption			kWh	275	353	485	775	995	1175
	Energy label	Cooling			A			A	B	B
		Heating			A			A	B	C

Indoor unit				FTX	*20J3	*25J3	*35J3	50GV	60GV	71GV
Casing	Colour				White			White		
Dimensions	Unit	HeightxWidthxDepth		mm	283x770x198			290x1,050x238		
Weight	Unit			kg	7			12		
Air filter	Type				-			Removable / washable / mildew proof		
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	9.10/-/-/-	9.20/-/-/-	9.30/-/-/-	14.7/14.7/10.3/9.5	16.2/16.2/11.4/10.2	17.4/14.6/11.6/10.6
	Heating	High/Nom./Low/Silent operation		m^3/min	-/-/-/-			16.1/13.9/11.5/10.2	17.4/15.1/12.7/11.4	19.7/16.9/14.3/12.7
Sound power level	Cooling			dBA	55		58	59	60	63
	Heating			dBA	55		58	58	59	62
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	39/33/25/22	40/33/26/22	41/34/27/23	43/39/34/31	45/41/36/33	46/42/37/34
	Heating	High/Nom./Low/Silent operation		dBA	39/34/28/25	40/34/28/25	41/35/29/26	42/38/33/30	44/40/35/32	46/42/37/34
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			1~ / 50 / 220-240		
Control systems	Infrared remote control				ARC433A8			ARC433B70		

Outdoor unit				RX	*20K	*25K	*35K	50GV	60GVB	71GVB
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275			735x825x300		770x900x320
Weight	Unit			kg	26		28	48	47	71
Sound power level	Cooling			dBA	60		62	63	62	65
	Heating			dBA	60		62	64	62	66
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	39/33/25/22	40/33/26/22	41/34/27/23	47/-/44/-	49/-/46/-	52/-/49/-
	Heating	High/Nom./Low/Silent operation		dBA	39/34/28/25	40/34/28/25	41/35/29/26	48/-/45/-	49/-/46/-	52/-/49/-
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46			-10~46		
	Heating	Ambient	Min.~Max.	°CWB	-15~18			-15~18		
Refrigerant	Type/Charge/GWP			kg	R-410A / 0.74 / 2,087.5		R-410A / 1 / 2,087.5	R-410A / 1.5 /2,087.5		R-410A / 2.3 /2,087.5
	Charge			TCO_2Eq	1.5		2.1	3.1		4.8
Piping connections	Liquid	OD		mm	-			6.35		
	Gas	OD		mm	-			12.7		15.9
	Piping length	OU - IU	Max.	m	-			30		
		System	Chargeless	m	-			10		
	Additional refrigerant charge			kg/m	-			0.020 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-			20		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			1~ / 50 / 220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20		

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Discreet wall mounted unit providing high efficiency and comfort

- SEER / SCOP up to A++
- Discreet, stylish front panel blends easily with the wall, and matches all interior décors
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Dry programme allows humidity levels to be reduced without variations in room temperature



Efficiency data				**FTX + RX**	***20K + 20K**	***25K + 25K**	***35K + 35K**	***50K + 50K**	***60K + 60K**
Cooling capacity	Min./Nom./Max.			kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.5/4.0	1.7/5.0/6.0	1.7/6.0/7.0
Heating capacity	Min./Nom./Max.			kW	1.3/2.5/3.5	1.3/3.0/4.0	1.3/4.0/4.8	1.7/6.0/7.7	1.7/7.0/8.0
Power input	Cooling	Nom.		kW	0.50	0.74	1.07	1.40	1.64
	Heating	Nom.		kW	0.52	0.69	1.00	1.58	1.93
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++				
		Pdesign		kW	2.00	2.50	3.50	5.00	6.00
		SEER			6.66	6.33	6.42	6.59	7.76
		Annual energy consumption		kWh	105	138	191	266	271
	Heating (Average climate)	Energy label			A++			A+	
		Pdesign		kW	2.20	2.40	2.80	4.60	4.80
		SCOP			5.02	4.70	4.74	4.39	4.34
		Annual energy consumption		kWh	614	715	827	1,467	1,548
Nominal efficiency	EER				3.97	3.37	3.3	3.58	3.65
	COP				4.77	4.4	4.0	3.80	3.63
	Annual energy consumption			kWh	252	371	537	698	822
	Energy label	Cooling/Heating			A/A				

Indoor unit				**FTX**	***20K**	***25K**	***35K**	***50K**	***60K**
Dimensions	Unit	HeightxWidthxDepth		mm	-x-x-				
Weight	Unit			kg	7			12	
Fan - Air flow rate	Cooling	High		m^3/min	9.10	9.20	9.30	14.7	16.2
Sound power level	Cooling			dBA	55		58	59	60
	Heating			dBA	55		58	59	60
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				

Outdoor unit				**RX**	***20K**	***25K**	***35K**	***50K**	***60K**
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275			735x870x320	
Weight	Unit			kg	26		28	42	
Sound power level	Cooling			dBA	60		62	63	62
	Heating			dBA	60		62	63	62
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46			-~-	
	Heating	Ambient	Min.~Max.	°CWB	-15~18			-~-	
Refrigerant	Type/Charge/GWP			kg	R-410A / - / 2,087.5				
	Charge			TCO_2Eq	-				
Piping connections	Piping length	OU - IU	Max.	m	-				
	Level difference	IU - OU	Max.	m	-				
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				
Current - 50Hz	Maximum fuse amps (MFA)			A	16			20	


*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Stylish wall mounted unit for low energy consumption and pleasant comfort

- Seasonal efficiency values up to A+
- Stylish, modern casing in white or silver
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- 24 hour timer can be set to start heating or cooling anytime during a 24 hour period



FTXK-AW

RXK25-35A

Efficiency data				FTXK + RXK	*25AW/S + 25A	*35AW/S + 35A	*50AW/S + 50A	*60AW/S + 60A
Cooling capacity	Nom.			kW	2.56	3.41	5.48	6.23
Heating capacity	Nom.			kW	2.84	3.58	5.62	6.40
Power input	Cooling	Nom.		kW	0.69	1.06	1.70	1.93
	Heating	Nom.		kW	0.70	0.95	1.50	1.68
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+			
		Pdesign		kW	-			
		SEER			5.61		5.88	6.05
		Annual energy consumption		kWh	-			
	Heating (Average climate)	Energy label			A			
		Pdesign		kW	-			
		SCOP			3.81		3.99	3.81
		Annual energy consumption		kWh	-			
Nominal efficiency	EER				3.69	3.22		3.23
	COP				4.06	3.77	3.75	3.81
	Annual energy consumption			kWh	347	530	851	964
	Energy label	Cooling/Heating			A/A			

Indoor unit				FTXK	*25AW/S	*35AW/S	*50AW/S	*60AW/S
Casing	Colour				white/silver			
Dimensions	Unit	HeightxWidthxDepth		mm	298x890x210		320x1,172x242	
Weight	Unit			kg	9		14	
Air filter	Type				Saranet (with titanium apatite)			
Sound power level	Cooling			dBA	53	54	55	61
	Heating			dBA	53	54	55	61
Sound pressure level	Cooling	Super high/High/Nom./ Low/Silent operation		dBA	41/40/34/29/21	42/41/34/30/22	44/40/38/35/32	46/43/41/37/33
	Heating	Super high/High/Nom./ Low/Silent operation		dBA	41/40/34/29/21	42/41/34/30/22	44/40/38/35/32	46/43/41/37/33
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			

Outdoor unit				RXK	*25A	*35A	*50A	*60A
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x289		753x855x328	
Weight	Unit			kg	31		44	
Sound power level	Cooling			dBA	58	60	64	65
	Heating			dBA	58	60	64	65
Sound pressure level	Cooling	Nom.		dBA	45	46	51	
	Heating	Nom.		dBA	45	46	51	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46			
	Heating	Ambient	Min.~Max.	°CWB	-15~18			
Refrigerant	Type / GWP				R-410A/2,087.5			
Piping connections	Liquid	OD		mm	6.35			
	Gas	OD		mm	9.52		12.70	15.90
	Piping length	OU - IU	Max.	m	-			
	Level difference	IU - OU	Max.	m	-			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)			A	16		20	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Wall mounted unit for low energy consumption and pleasant comfort

- Seasonal efficiency values up to A+
- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- 24 hour timer can be set to start heating or cooling anytime during a 24 hour period



Efficiency data				FTXB + RXB	*25C + 25C	*35C + 35C	*50C + 50C	*60C + 60C
Cooling capacity	Min./Nom./Max.			kW	1.3/2.5/3.0	1.3/3.3/3.8	-/5.48/-	-/6.23/-
Heating capacity	Min./Nom./Max.			kW	1.3/2.8/4.0	1.3/3.5/4.8	-/5.6/-	-/6.4/-
Power input	Cooling	Nom.		kW	0.77	0.99	1.71	1.93
	Heating	Nom.		kW	0.69	0.93	1.49	1.77
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+			
		Pdesign		kW	2.50	3.30	5.48	6.23
		SEER			6.00	6.05	5.93	6.09
		Annual energy consumption		kWh	146	191	323	358
	Heating (Average climate)	Energy label			A+			
		Pdesign		kW	2.40	2.80	3.64	3.80
		SCOP			4.01	4.06	4.27	4.06
		Annual energy consumption		kWh	838	966	1,193	1,310
Nominal efficiency	EER				3.25	3.32	3.21	3.23
	COP				4.06	3.76	3.75	3.61
	Annual energy consumption			kWh	385	497	854	964
	Energy label	Cooling			A			
		Heating			A			

Indoor unit				FTXB	*25C	*35C	*50C	*60C
Dimensions	Unit	HeightxWidthxDepth		mm	316x870x310		386x1136x314	
Weight	Unit			kg	8		14	
Fan - Air flow rate	Cooling	High		m^3/min	9.20	9.30	14.7	16.2
Sound power level	Cooling			dBA	55	58	55	61
	Heating			dBA	55	58	55	61
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				ARC470A1		AP GS02	

Outdoor unit				RXB	*25C	*35C	*50C	*60C
Dimensions	Unit	HeightxWidthxDepth		mm	616x788x359		793x990x415	
Weight	Unit			kg	27	29	49	
Sound power level	Cooling			dBA	60	62	64	65
	Heating			dBA	60	62	64	65
Operation range	Cooling	Ambient	Min.~Max.	°CDB	--~-			
	Heating	Ambient	Min.~Max.	°CWB	--~-			
Refrigerant	Type / GWP				R-410A/2,087.5			
Piping connections	Piping length	OU - IU	Max.	m	-			
	Level difference	IU - OU	Max.	m	-			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)			A	-			

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

The best of two worlds united

Pure comfort and design



Why choose Nexura?

- Unique radiant heat panel that heats up just like a traditional radiator
- Whisper quiet operation down to 19 dBA
- Unobtrusive yet stylish design
- Reduced air flow, creating an even distribution of air through the room

Comfort is key

Nexura makes your world a comfortable one. The coolness of a summer breeze or the cosiness of an extra heat source brings a feeling of well-being to your living space all year round. Its unobtrusive yet stylish design with a front panel that radiates additional heat, its low noise level and reduced air flow turn your room into a haven.

Radiant heat panel

To add even more comfort on cold days, the aluminium front panel of the Nexura unit has tahe capability of warming up, just like a traditional radiator. The result? A comfortable feeling of warm air that envelopes you. And all you have to do to activate this unique feature is push the "radiant" button on your remote control.

Benefits

› Vertical autoswing
› Weekly timer
› Guaranteed operation down to -25°C (with RXLG-M)

Online controller

Always in control, no matter where you are. Control your indoor from any location with an app, via your local network or internet.

Marketing tools

› Visit the extranet: extranet.daikineurope.com > document library
› Visit the website: http://www.daikineurope.com/minisite/nexura/



Floor standing unit with radiant heat panel

Stylish floor standing unit with radiant heat panel for comfortable heat and very low noise

- The aluminium part of the front panel of the Nexura indoor unit has the capability of warming up, just like a traditional radiator, to add even more comfort on cold days
- Quiet and discrete, Nexura offers you the best in heating and cooling, in comfort and design
- The indoor unit distributes air at the sound of a whisper. The noise produced amounts to barely 22dB(A) in cooling and 19dB(A) in radiant heat mode. In comparison, the ambient sound in a quiet room amounts to 40dB(A) on average.
- Comfortable vertical auto swing ensures draughtfree operation and prevents ceiling soiling
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Can be installed against a wall or recessed



FVXG-K



RXG20-25-35L



ARC466A2

Efficiency data				FVXG + RXG	25K + 25L	35K + 35L	50K + 50L
Cooling capacity	Min./Nom./Max.			kW	1.3/2.5/3.0	1.4/3.5/3.8	1.7/5.0/5.6
Heating capacity	Min./Nom./Max.			kW	1.3/3.4/4.5	1.4/4.5/5.0	1.7/5.8/8.1
Cooling Power input	Min./Nom./Max.			kW	-/0.54/-	-/0.94/-	-/1.51/-
Heating Power input	Min./Nom./Max.			kW	-/0.77/-	-/1.21/-	-/1.57/-
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A
		Pdesign		kW	2.50	3.50	5.00
		SEER			6.53	6.48	5.41
		Annual energy consumption		kWh	134	189	324
	Heating (Average climate)	Energy label			A++	A+	
		Pdesign		kW	2.80	3.10	4.60
		SCOP			4.65	4.00	4.18
		Annual energy consumption		kWh	842	1,087	1,543
Nominal efficiency	EER				4.63	3.72	3.31
	COP				4.42	3.72	3.69
	Annual energy consumption			kWh	270	470	755
	Energy label	Cooling/Heating			A/A	A/A	A/A

Indoor unit				FVXG	25K	35K	50K
Casing	Colour				Fresh white (6.5Y 9.5/0.5)		
Dimensions	Unit	HeightxWidthxDepth		mm	600x950x215		
Weight	Unit			kg	22		
Air filter	Type				Removable / washable / mildew proof		
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	8.9/8.9/5.3/4.5	9.1/9.1/5.3/4.5	10.6/10.3/7.3/6.0
	Heating	High/Nom./Low/Silent operation		m^3/min	9.9/7.8/5.7/4.7	10.2/8.0/5.8/5.0	12.2/10.0/7.8/6.8
Sound power level	Cooling			dBA	52		58
	Heating			dBA	53		60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/26/23	39/33/27/24	44/40/36/32
	Heating	High/Nom./Low/Silent operation/Radiant heat		dBA	39/32/26/22/19	40/33/27/23/19	46/40/34/30/26
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Control systems	Infrared remote control				ARC466A2		

Outdoor unit				RXG	25L	35L	50L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300
Weight	Unit			kg	35		48
Sound power level	Cooling			dBA	61	63	
	Heating			dBA	62	63	
Sound pressure level	Cooling	High/Silent operation		dBA	46/43	48/44	
	Heating	High/Silent operation		dBA	47/44	48/45	48/44
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46		
	Heating	Ambient	Min.~Max.	°CWB	-15~18		
Refrigerant	Type/Charge/GWP			kg	R-410A / 1.05 / 2,087.5		R-410A / 1.6 / 2,087.5
	Charge			TCO_2Eq	2.2		3.3
Piping connections	Liquid	OD		mm	6		
	Gas	OD		mm	9.5		12.7
	Piping length	OU - IU	Max.	m	20		30
		System	Chargeless	m	10		
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)		
	Level difference	IU - OU	Max.	m	15		20
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16		20

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Floor standing unit

Floor standing unit for optimal heating comfort thanks to dual airflow

› Its low height enables the unit to fit perfectly beneath a window
› Can be installed against a wall or recessed
› Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
› Online controller (optional): control your indoor from any location with an app, via your local network or internet



FVXS-F

RXS25-35L3

ARC452A1

Efficiency data				**FVXS + RXS**	**25F + 25L3**	**35F + 35L3**	**50F + 50L**
Cooling capacity	Min./Nom./Max.			kW	-/2.5/-	-/3.5/-	1.4/5.0/5.6
Heating capacity	Min./Nom./Max.			kW	-/3.4/-	-/4.5/-	1.4/5.8/8.1
Power input	Cooling	Min./Nom./Max.		kW	-/0.57/-	-/1.02/-	0.50/1.55/2.00
	Heating	Min./Nom./Max.		kW	-/0.77/-	-/1.19/-	0.50/1.60/2.60
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+		A+
		Pdesign		kW	2.5	3.5	5.00
		SEER			5.74	5.60	5.89
		Annual energy consumption		kWh	152	219	297
	Heating (Average climate)	Energy label			A+	A	A
		Pdesign		kW	2.6	2.9	4.20
		SCOP			4.56	3.93	3.80
		Annual energy consumption		kWh	798	1,033	1,546
Nominal efficiency	EER				4.39	3.43	3.23
	COP				4.42	3.78	3.63
	Annual energy consumption			kWh	285	510	775
	Energy label	Cooling			A		A
		Heating			A		A

Indoor unit				**FVXS**	**25F**	**35F**	**50F**
Casing	Colour				White		
Dimensions	Unit	HeightxWidthxDepth		mm	600x700x210		
Weight	Unit			kg	14		
Air filter	Type				Removable / washable / mildew proof		
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	8.2/8.2/4.8/4.1	8.5/8.5/4.9/4.5	10.7/10.7/7.8/6.6
	Heating	High/Nom./Low/Silent operation		m^3/min	8.8/6.9/5.0/4.4	9.4/7.3/5.2/4.7	11.8/10.1/8.5/7.1
Sound power level	Cooling			dBA	52		60
	Heating			dBA	52		60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/26/23	39/33/27/24	44/40/36/32
	Heating	High/Nom./Low/Silent operation		dBA	38/32/26/23	39/33/27/24	45/40/36/32
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Control systems	Infrared remote control				ARC452A1		

Outdoor unit				**RXS**	***25L3**	***35L3**	**50L**
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300
Weight	Unit			kg	31.5		47
Sound power level	Cooling			dBA	59	61	62
	Heating			dBA	59	61	62
Sound pressure level	Cooling	High/Low		dBA	-/-		48/44
	Heating	High/Low		dBA	-/-		48/45
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		-10~46
	Heating	Ambient	Min.~Max.	°CWB	-15~18		-15~18
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	R-410A / 1.2 / 2,087.5	R-410A / 1 .7 / 2,087.5
	Charge			TCO_2Eq	2.1	2.5	3.5
Piping connections	Liquid	OD		mm	6.35		6.35
	Gas	OD		mm	9.5		12.7
	Piping length	OU - IU	Max.	m	-		30
	Additional refrigerant charge			kg/m	-		0.020 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m	-		20.0
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 / 220-230-240
Current - 50Hz	Maximum fuse amps (MFA)			A	16		20


*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load


Concealed ceiling unit

Compact concealed ceiling unit, with a height of only 200mm

› Compact dimensions, can easily be mounted in a ceiling void of only 240mm



› Discretely concealed in the ceiling: only the suction and discharge grilles are visible
› Low energy consumption thanks to DC fan motor
› Medium external static pressure up to 40Pa facilitates unit use with flexible ducts of varying lengths



FDXS25-35F



RXS25-35L3



BRC1E52A

Efficiency data				FDXS + RXS	25F + 25L3	35F + 35L3	50F9 + 50L	60F + 60L
Cooling capacity	Min./Nom./Max.			kW	-/2.4/-	-/3.4/-	1.7/5.0/5.3	1.7/6.0/6.5
Heating capacity	Min./Nom./Max.			kW	-/3.2/-	-/4/-	1.7/5.8/6.0	1.7/7.0/8.0
Power input	Cooling	Nom.		kW	0.65	1.06	1.65	2.06
	Heating	Nom.		kW	0.8	1.15	1.87	2.18
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+	A	A+	A
		Pdesign		kW	2.4	3.40	5.00	6.00
		SEER			5.63	5.21	5.72	5.51
		Annual energy consumption		kWh	149	228	306	381
	Heating (Average climate)	Energy label			A+	A	A	
		Pdesign		kW	2.3	2.57	4.00	4.60
		SCOP			4.24	3.88	3.93	3.80
		Annual energy consumption		kWh	759	927	1,425	1,693
Nominal efficiency	EER				3.72	3.21	3.03	2.91
	COP				4	3.48	3.10	3.21
	Annual energy consumption			kWh	323	530	825	1,030
	Energy label	Cooling			A		B	C
		Heating			A	B	D	C

Indoor unit				FDXS	25F	35F	50F9	60F
Dimensions	Unit	HeightxWidthxDepth		mm	200x750x620		200x1,150x620	
Weight	Unit			kg	21		30	
Air filter	Type				Removable / washable / mildew proof			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	8.7/8.7/7.3		12.0/11.0/10.0	16.0/16.0/13.5
	Heating	High/Nom./Low		m^3/min	8.7/8.0/7.3		16.0/14.8/13.5	
Fan - External static pressure	Nom./Maximum available/High			Pa	30/-		40/-	
Sound power level	Cooling			dBA	53		55	56
	Heating			dBA	53		55	56
Sound pressure level	Cooling	High/Nom./Low		dBA	35/33/27		38/36/30	
	Heating	High/Nom./Low		dBA	35/33/27		38/36/30	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 230		1~ / 50 / 220-240	
Control systems	Wired remote control				BRC1E52A/B			

Outdoor unit				RXS	*25L3	*35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300	
Weight	Unit			kg	31.5		47	48
Sound power level	Cooling			dBA	59	61	62	
	Heating			dBA	59	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-		48/44	49/46
	Heating	High/Low		dBA	-/-		48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18		-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	R-410A / 1.2 / 2,087.5	R-410A / 1.7 / 2,087.5	R-410A / 1.5 / 2,087.5
	Charge			TCO_2Eq	2.1	2.5	3.5	3.1
Piping connections	Liquid	OD		mm	6.35		6.35	
	Gas	OD		mm	9.5		12.7	
	Piping length	OU - IU	Max.	m	-		30	
	Additional refrigerant charge			kg/m	-		0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-		20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-		-	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Flexi type unit

Flexible unit, ideal for rooms without false ceiling, can fit on either ceiling or wall

- Can fit on either ceiling or lower wall; its low height enables the unit to fit beneath a window
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- Home leave operation maintains the indoor temperature at your specified comfort level during absence, thus saving energy
- Online controller (optional): control your indoor unit from any location via smartphone, laptop, pc, tablet or touch screen



FLXS-B



RXS25-35L3



ARC433B67

Efficiency data				FLXS + RXS	25B + 25L3	35B9 + 35L3	50B + 50L	60B
Cooling capacity	Min./Nom./Max.			kW	-/2.5/-	-/3.5/-	0.9/4.9/5.3	-
Heating capacity	Min./Nom./Max.			kW	-/3.4/-	-/4.0/-	0.9/6.1/7.5	-
Power input	Cooling	Min./Nom./Max.		kW	-/0.65/-	-/1.13/-	0.45/1.72/1.95	-
	Heating	Min./Nom./Max.		kW	-/0.96/-	-/1.12/-	0.31/1.82/3.54	-
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A	B	A	Only available in multi model application
		Pdesign		kW	2.5	3.5	4.90	
		SEER			5.19	4.87	5.25	
		Annual energy consumption		kWh	169	252	326	
	Heating (Average climate)	Energy label			A		A	
		Pdesign		kW	2.5	2.9	4.20	
		SCOP			3.80		3.80	
		Annual energy consumption		kWh	921	1,068	1,546	
Nominal efficiency	EER				3.85	3.1	2.85	
	COP				3.54	3.57	3.35	
	Annual energy consumption			kWh	325	565	860	
	Energy label	Cooling			A	B	C	
		Heating			B		C	

Indoor unit				FLXS	25B	35B9	50B	60B
Casing	Colour				Almond white			Almond white
Dimensions	Unit	HeightxWidthxDepth		mm	490x1,050x200			490x1,050x200
Weight	Unit			kg	16		17	
Air filter	Type				Removable / washable / mildew proof			
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	7.6/7.6/6.0/5.2	8.6/7.6/6.6/5.6	11.4/11.4/8.5/7.5	12.0/10.7/9.3/8.3
	Heating	High/Nom./Low/Silent operation		m^3/min	9.2/8.3/7.4/6.6	12.8/10.4/8.0/7.2	12.1/9.8/7.5/6.8	12.8/10.6/8.4/7.5
Sound power level	Cooling			dBA	51	53	60	
	Heating			dBA	51	59	-	59
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	37/34/31/28	38/35/32/29	47/43/39/36	48/45/41/39
	Heating	High/Nom./Low/Silent operation		dBA	37/34/31/29	46/36/33/30	46/41/35/33	47/42/37/34
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220-230	1~ / 50 / 220-240	1~ / 50/60 / 220-240/220-230	
Control systems	Infrared remote control				ARC433B67			

Outdoor unit				RXS	*25L3	*35L3	50L	60B
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300	Only available in multi model application
Weight	Unit			kg	31.5		47	
Sound power level	Cooling			dBA	59	61	62	
	Heating			dBA	59	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-		48/44	
	Heating	High/Low		dBA	-/-		48/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18		-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	R-410A / 1.2 / 2,087.5	R-410A / 1 .7 / 2,087.5	
	Charge			TCO_2Eq	2.1	2.5	3.5	
Piping connections	Liquid	OD		mm	6.35		6.35	
	Gas	OD		mm	9.5		12.7	
	Piping length	OU - IU	Max.	m	-		30	
	Additional refrigerant charge			kg/m	-		0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-		20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-		-	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Optimised for heating

Designed for living: solutions for even the coldest regions

› Wide range of connectable indoor units (wall mounted, floor standing) with guaranteed heating capacity down to -25C outdoor temperature
› Unique free hanging coil technology: the defrost cycle is improved, resulting in lower running costs and no ice build-up

For most people, total indoor climate control means having the ability to select a desirable temperature for each space in a house and to have that temperature maintained no matter what the temperature outside – even when it is down to -25°C.In a domestic setting, this means heating, cooling and high air quality is needed for year round comfort.

At Daikin for the coldest regions, the outdoor units of this heat pump have been redesigned to withstand extreme weather conditions with excellent energy efficiency ratings.Our indoor units have won prestigious design awards for their almost iconic designs that will fit into any décor.

The indoor units are designed to operate in a whisper-quiet mode and to distribute purified air in a way that does not produce unpleasant air currents. Truly, climate control by design.





Wall mounted unit

Design at its best, delivering superior efficiency and comfort, even at ambient temperatures **down to -25°C**

- Remarkable blend of iconic design and engineering excellence with an elegant finish in silver and anthracite or in matt crystal white
- Daikin Emura has been awarded with Reddot design award 2014 by an international jury, thanks to its excellent design
- Designed to perfectly balance technological leadership and the beauty of aerodynamics
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Guaranteed heating capacity at low ambient temperature, down to -25°C
- Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup



Efficiency data				FTXG + RXLG	25LW/S + 25M	35LW/S + 35M
Cooling capacity	Min./Nom./Max.			kW	1.3/2.5/4.0	1.4/3.5/4.6
Heating capacity	Min./Nom./Max.			kW	1.0/4.4/6.1 / 3.64 (3) / 3.79 (4)	1.0/ 5.1/ 6.7 / 4.22 (3) / 4.36 (4)
Power input	Cooling	Nom.		kW	0.68	0.98
	Heating	Nom.		kW	1.02	1.31
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	
		Pdesign		kW	2.50	3.50
		SEER			7.04	6.67
		Annual energy consumption		kWh	124	184
	Heating (Average climate)	Energy label			A++	
		Pdesign		kW	2.50	3.00
		SCOP			4.64	4.60
		Annual energy consumption		kWh	754	913
Nominal efficiency	EER				3.68	3.57
	COP				4.31	3.89
	Annual energy consumption			kWh	340	490
	Energy label	Cooling			A	A
		Heating			A	A

Indoor unit				FTXG	25LW/S	35LW/S
Casing	Colour				White/Silver	
Dimensions	Unit	HeightxWidthxDepth		mm	303x998x212	
Weight	Unit			kg	12	
Air filter	Type				Removable / washable / mildew proof	
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	8.9/6.6/4.4/2.6	10.9/7.8/4.8/2.9
	Heating	High/Nom./Low/Silent operation		m^3/min	11.0/8.6/6.3/3.8	12.4/9.6/6.9/4.1
Sound power level	Cooling			dBA	54	59
	Heating			dBA	56	59
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/25/19	45/34/26/20
	Heating	High/Nom./Low/Silent operation		dBA	41/34/28/19	45/37/29/20
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Control systems	Infrared remote control				ARC466A1	

Outdoor unit				RXLG	*25M	*35M
Dimensions	Unit	HeightxWidthxDepth		mm	550x858x330	
Weight	Unit			kg	40	
Sound power level	Cooling			dBA	61	
	Heating			dBA	61	
Sound pressure level	Cooling	High/Low		dBA	48/44	
	Heating	High/Low		dBA	49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-25~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	
	Charge			TCO_2Eq	2.1	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	20	
	Level difference	IU - OU	Max.	m	15	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
(3) Maximum average heating capacity at -15°C (4) Maximum peak heating capacity at -15°C

nexura

Floor standing unit with radiant heat panel

Stylish floor standing unit with radiant heat panel for comfortable heat and very low noise, even at ambient temperatures **down to -25°C**

- The aluminium part of the front panel of the Nexura indoor unit has the capability of warming up, just like a traditional radiator, to add even more comfort on cold days
- Quiet and discrete, Nexura offers you the best in heating and cooling, in comfort and design
- The indoor unit distributes air at the sound of a whisper. The noise produced amounts to barely 22dB(A) in cooling and 19dB(A) in radiant heat mode. In comparison, the ambient sound in a quiet room amounts to 40dB(A) on average.
- Comfortable vertical auto swing ensures draughtfree operation and prevents ceiling soiling
- Online controller (optional): control your indoor unit from any location with an app, via your local network or internet
- Can be installed against a wall or recessed
- Guaranteed heating capacity at low ambient temperature, down to -25°C



- Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup

Efficiency data				**FVXG + RXLG**	**25K + 25M**	**35K + 35M**
Cooling capacity	Min./Nom./Max.			kW	1.2/2.5/5.1	1.4/3.5/5.6
Heating capacity	Min./Nom./Max.			kW	1.0/4.5/6.5 / 3.53 (3) / 3.70 (4)	1.1/5.6/7.0 / 4.04 (3) / 4.21 (4)
Power input	Cooling	Nom.		kW	0.71	1.02
	Heating	Nom.		kW	1.16	1.55
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	
		Pdesign		kW	2.50	3.50
		SEER			6.99	6.59
		Annual energy consumption		kWh	125	186
	Heating (Average climate)	Energy label			A+	
		Pdesign		kW	3.00	3.40
		SCOP			4.25	4.01
		Annual energy consumption		kWh	988	1,187
Nominal efficiency	EER				3.52	3.43
	COP				3.88	3.61
	Annual energy consumption			kWh	355	510
	Energy label	Cooling			A	A
		Heating			A	A

Indoor unit				**FVXG**	**25K**	**35K**
Casing	Colour				Fresh white	
Dimensions	Unit	HeightxWidthxDepth		mm	600x950x215	
Weight	Unit			kg	22	
Air filter	Type				Removable / washable / mildew proof	
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	8.9/8.9/5.3/4.5	9.1/9.1/5.3/4.5
	Heating	High/Nom./Low/Silent operation		m^3/min	9.9/7.8/5.7/4.7	10.2/8.0/5.8/5.0
Sound power level	Cooling			dBA	52	
	Heating			dBA	53	
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/26/23	39/33/27/24
	Heating	High/Nom./Low/Silent operation/Radiant heat		dBA	39/32/26/22/19	40/33/27/23/19
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Control systems	Infrared remote control				ARC466A2	

Outdoor unit				**RXLG**	***25M**	***35M**
Dimensions	Unit	HeightxWidthxDepth		mm	550x858x330	
Weight	Unit			kg	40	
Sound power level	Cooling			dBA	61	
	Heating			dBA	61	
Sound pressure level	Cooling	High/Low		dBA	48/44	
	Heating	High/Low		dBA	49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-25~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	
	Charge			TCO_2Eq	2.1	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	20	
	Level difference	IU - OU	Max.	m	15	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
(3) Maximum average heating capacity at -15°C (4) Maximum peak heating capacity at -15°C

Wall mounted unit

Discreet modern design for optimal efficiency and comfort thanks to 2 area intelligent eye, even at ambient temperatures **down to -25°C**

- High quality matt crystal white finish
- Excellent air flow and air distribution
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- New remote control design, also in high quality matt white finish to give a perfect match with the indoor unit
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Guaranteed heating capacity at low ambient temperature, down to -25°C
- Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup



FTXLS-K

RXLS-M

ARC466A9

Efficiency data				FTXLS + RXLS	25K + 25M	35K + 35M
Cooling capacity	Min./Nom./Max.			kW	1.6/2.5/4.4	1.7/3.5/5.0
Heating capacity	Min./Nom./Max.			kW	1.0/4.7/6.6	1.0/5.4/7.2
Power input	Cooling	Min./Nom./Max.		kW	0.32/0.67/2.33	0.32/0.95/2.33
	Heating	Min./Nom./Max.		kW	0.24/1.10/2.36	0.24/1.31/2.88
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	
		Pdesign		kW	2.50	3.50
		SEER			6.62	6.91
		Annual energy consumption		kWh	132	177
	Heating (Average climate)	Energy label			A++	
		Pdesign		kW	3.20	3.80
		SCOP			4.62	4.60
		Annual energy consumption		kWh	947	1,147
Nominal efficiency	EER				3.74	3.69
	COP				4.27	4.12
	Annual energy consumption			kWh	334.5	475.5
	Energy label	Cooling			A	
		Heating			A	

Indoor unit				FTXLS	25K	35K
Casing	Colour				White	
Dimensions	Unit	HeightxWidthxDepth		mm	298x900x215	
Weight	Unit			kg	12	
Air filter	Type				Removable / washable / mildew proof	
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	11.2/9.1/7.0/4.1	
	Heating	High/Nom./Low/Silent operation		m^3/min	13.3/10.0/7.8/4.2	
Sound power level	Cooling			dBA	59	
	Heating			dBA	62	
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	45/39/33/21	
	Heating	High/Nom./Low/Silent operation		dBA	47/39/33/19	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Control systems	Infrared remote control				ARC466A9	

Outdoor unit				RXLS	25M	35M
Dimensions	Unit	HeightxWidthxDepth		mm	550x858x330	
Weight	Unit			kg	40	
Sound power level	Cooling			dBA	61	
	Heating			dBA	61	
Sound pressure level	Cooling	High/Low		dBA	48/44	
	Heating	High/Low		dBA	49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-25~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1.3 / 2,087.5	
	Charge			TCO_2Eq	2.7	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	20	
		System	Chargeless	m	10	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-	
		IU - IU	Max.	m	15	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Wall mounted unit providing high efficiency and comfort, even at ambient temperatures **down to -25°C**

- The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- Excellent air flow and air distribution
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Guaranteed heating capacity at low ambient temperature, down to -25°C
- Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup
- Also available in Siesta range, see page 108



FTXL-JV



RXL-M3



ARC433A87

Efficiency data				FTXL + RXL	25JV + 25M3	35JV + 35M3
Cooling capacity	Min./Nom./Max.			kW	1.2/2.5/3.4	1.3/3.5 /3.8
Heating capacity	Min./Nom./Max.			kW	1.1/3.2/5.5 / 3.2 (3) / 3.49 (4)	1.2/3.8/6.0 / 3.69 (3) / 3.76 (4)
Power input	Cooling	Min./Nom./Max.		kW	0.25/0.80/1.22	0.25/1.14/1.30
	Heating	Min./Nom./Max.		kW	0.25/0.72/1.44	0.25/0.90/1.75
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+	
		Pdesign		kW	2.50	3.50
		SEER			6.01	5.87
		Annual energy consumption		kWh	146	209
	Heating (Average climate)	Energy label			A+	
		Pdesign		kW	2.50	3.00
		SCOP			4.37	4.21
		Annual energy consumption		kWh	793	998
Nominal efficiency	EER				3.12	3.07
	COP				4.43	4.21
	Annual energy consumption			kWh	400.5	570
	Energy label	Cooling			B	
		Heating			A	

Indoor unit				FTXL	25JV	35JV
Casing	Colour				White	
Dimensions	Unit	HeightxWidthxDepth		mm	283x770x198	
Weight	Unit			kg	8	
Air filter	Type				Removable / washable / mildew proof	
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	9.3/7.7/6.1/4.9	
	Heating	High/Nom./Low/Silent operation		m^3/min	10.1/8.4/6.7/5.7	
Sound power level	Cooling			dBA	57	
	Heating			dBA	57	
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	41/34/27/23	
	Heating	High/Nom./Low/Silent operation		dBA	41/35/29/26	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Control systems	Infrared remote control				ARC433A87	

Outdoor unit				RXL	25M3	35M3
Dimensions	Unit	HeightxWidthxDepth		mm	550x858x330	
Weight	Unit			kg	40	
Sound power level	Cooling			dBA	61	
	Heating			dBA	61	
Sound pressure level	Cooling	High/Low		dBA	48/44	
	Heating	High/Low		dBA	49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-25~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	
	Charge			TCO_2Eq	2.1	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	15	
		System	Chargeless	m	10	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-	
		IU - IU	Max.	m	15	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
(3) Maximum average heating capacity at -15°C (4) Maximum peak heating capacity at -15°C

Floor standing unit

Floor standing unit for optimal heating comfort thanks to dual airflow, even at ambient temperatures **down to -25°C**

- Its low height enables the unit to fit perfectly beneath a window
- Can be installed against a wall or recessed
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- Online controller (optional): control your indoor unit from any location with an app, via your local network or internet
- Guaranteed heating capacity at low ambient temperature, down to -25°C
- Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup



FVXS25-35F



RXL-M3



ARC452A1



Efficiency data				FVXS + RXL	25F + 25M3	35F + 35M3
Cooling capacity	Min./Nom./Max.			kW	1.3/2.5/5.1	1.4/3.5/5.6
Heating capacity	Min./Nom./Max.			kW	1.0/4.50/6.5 / 3.44 (3) / 3.58 (4)	1.1/5.6/7.0 / 3.81 (3) / 3.91 (4)
Power input	Cooling	Min./Nom./Max.		kW	0.74	1.07
	Heating	Min./Nom./Max.		kW	1.19	1.62
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A	
		Pdesign		kW	2.50	3.50
		SEER			5.10	5.21
		Annual energy consumption		kWh	172	235
	Heating (Average climate)	Energy label			A+	A
		Pdesign		kW	3.20	3.60
		SCOP			4.04	3.80
		Annual energy consumption		kWh	1,109	1,326
Nominal efficiency	EER				3.38	3.27
	COP				3.78	3.46
	Annual energy consumption			kWh	370	535
	Energy label	Cooling			A	A
		Heating			A	B

Indoor unit				FVXS	25F	35F
Casing	Colour				White	
Dimensions	Unit	HeightxWidthxDepth		mm	600x700x210	
Weight	Unit			kg	14	
Air filter	Type				Removable / washable / mildew proof	
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	8.2/8.2/4.8/4.1	8.5/8.5/4.9/4.5
	Heating	High/Nom./Low/Silent operation		m^3/min	8.8/6.9/5.0/4.4	9.4/7.3/5.2/4.7
Sound power level	Cooling			dBA	52	
	Heating			dBA	52	
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	38/32/26/23	39/33/27/24
	Heating	High/Nom./Low/Silent operation		dBA	38/32/26/23	39/33/27/24
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Control systems	Infrared remote control				ARC452A1	

Outdoor unit				RXL	*25M3	*35M3
Dimensions	Unit	HeightxWidthxDepth		mm	550x858x330	
Weight	Unit			kg	40	
Sound power level	Cooling			dBA	61	
	Heating			dBA	61	
Sound pressure level	Cooling	High/Low		dBA	48/44	
	Heating	High/Low		dBA	49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-25~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	
	Charge			TCO_2Eq	2.1	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	20	
	Level difference	IU - OU	Max.	m	15	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 230	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
(3) Maximum average heating capacity at -15°C (4) Maximum peak heating capacity at -15°C

Siesta

wall mounted units

› Wide range of wall mounted units
› Seasonal efficiency values up to A++
› High comfort levels
› Multi connection possible
(for ATXS-K, ATX-J3, ATX-K)





Siesta

Wall mounted unit

Siesta wall mounted unit providing high efficiency and comfort, even at ambient temperatures **down to -25°C**

- The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- Excellent air flow and air distribution
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Guaranteed heating capacity at low ambient temperature, down to -25°C
- Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup



ATXL-JV



ARXL-M



ARC433A87

Efficiency data				ATXL + ARXL	25JV + 25M	35JV + 35M
Cooling capacity	Min./Nom./Max.			kW	1.2/2.5/3.4	1.3/3.5/3.8
Heating capacity	Min./Nom./Max.			kW	1.1/3.2/5.5	1.2/3.8/6.0
Power input	Cooling	Min./Nom./Max.		kW	0.29/0.80/1.30	0.29/1.14/1.30
	Heating	Min./Nom./Max.		kW	0.24/0.72/2.14	0.24/0.90/2.89
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+	
		Pdesign		kW	2.50	3.50
		SEER			6.01	5.87
		Annual energy consumption		kWh	146	209
	Heating (Average climate)	Energy label			A+	
		Pdesign		kW	2.50	3.00
		SCOP			4.37	4.21
		Annual energy consumption		kWh	793	998
Nominal efficiency	EER				3.12	3.07
	COP				4.43	4.21
	Annual energy consumption			kWh	400.5	570
	Energy label	Cooling			B	
		Heating			A	

Indoor unit				ATXL	25JV	35JV
Casing	Colour				White	
Dimensions	Unit	HeightxWidthxDepth		mm	283x770x198	
Weight	Unit			kg	8	
Air filter	Type				Removable / washable / mildew proof	
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	9.3/7.7/6.1/4.9	
	Heating	High/Nom./Low/Silent operation		m^3/min	10.1/8.4/6.7/5.7	
Sound power level	Cooling			dBA	57	
	Heating			dBA	57	
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	41/34/27/23	
	Heating	High/Nom./Low/Silent operation		dBA	41/35/29/26	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Control systems	Infrared remote control				ARC433A87	

Outdoor unit				ARXL	25M	35M
Dimensions	Unit	HeightxWidthxDepth		mm	550x858x330	
Weight	Unit			kg	40	
Sound power level	Cooling			dBA	61	
	Heating			dBA	61	
Sound pressure level	Cooling	High/Low		dBA	48/44	
	Heating	High/Low		dBA	49/45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-25~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / 1 / 2,087.5	
	Charge			TCO_2Eq	2.1	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	15	
		System	Chargeless	m	10	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-	
		IU - IU	Max.	m	12	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	


(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

Wall mounted unit

Discreet, modern Siesta unit for optimal efficiency and comfort thanks to 2 area intelligent eye

- Discreet, modern design. Its smooth curve blends beautifully with the wall resulting in an unobtrusive presence that matches all interior décors.
- High quality matt crystal white finish
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Ideal for installation in bedrooms (20,25 class) and larger or irregular shaped living areas (35,50 class)
- 2 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting (35,50 class)
- Online controller (optional): control your indoor from any location with an app, via your local network or internet



ATXS20-25K



ARXS25-35L3



ARC466A6

Efficiency data				ATXS + ARXS		*25K + 25L3	*35K + 35L3	50K + 50L
Cooling capacity	Min./Nom./Max.			kW	Only available in multi model application	1.3/2.5/3.2	1.4/3.5/4.0	1.7/5.00/5.3
Heating capacity	Min./Nom./Max.			kW		1.3/2.8/4.7	1.4/4.0/5.2	1.7/5.80/6.5
Power input	Cooling	Min./Nom./Max.		kW		-/0.57/-	-/0.85/-	0.35/1.41/1.81
	Heating	Min./Nom./Max.		kW		-/0.62/-	-/0.83/-	0.30/1.45/2.00
Seasonal efficiency (according to EN14825)	Cooling	Energy label				A++		A++
		Pdesign		kW		2.50	3.50	5.00
		SEER				7.51	7.10	6.46
		Annual energy consumption		kWh		117	173	271
	Heating (Average climate)	Energy label				A++		A+
		Pdesign		kW		2.50	3.60	4.6
		SCOP				4.68	4.61	4.00
		Annual energy consumption		kWh		748	1,093	1,608
Nominal efficiency	EER					4.4	4.1	3.55
	COP					4.5	4.8	4.00
	Annual energy consumption			kWh		284	427	705
	Energy label	Cooling				A		A
		Heating				A		A

Indoor unit				ATXS	*20K	*25K	*35K	50K
Casing	Colour				-			White
Dimensions	Unit	HeightxWidthxDepth		mm	289x780x215		289x900x215	298x900x215
Weight	Unit			kg	8		11	11
Air filter	Type				Removable / washable / mildew proof			Removable / washable / mildew proof
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	-	9.10/-/-/-	11.2/-/-/-	11.9/9.6/7.4/4.5
	Heating	High/Nom./Low/Silent operation		m^3/min	-	-/-/-/-		13.3/10.8/8.4/5.5
Sound power level	Cooling			dBA	-	58	59	60
	Heating			dBA	-	58	59	60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	40/32/24/19	41/33/25/19	45/37/29/19	46/40/34/23
	Heating	High/Nom./Low/Silent operation		dBA	40/34/27/19	41/34/27/19	45/39/29/19	47/40/34/24
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			1~ / 50 / 220-240
Control systems	Infrared remote control				ARC466A6		ARC466A9	ARC466A9

Outdoor unit				ARXS		*25L3	*35L3	50L
Dimensions	Unit	HeightxWidthxDepth		mm	Only available in multi model application	550x765x285		735x825x300
Weight	Unit			kg		34		47
Sound power level	Cooling			dBA		59	61	62
	Heating			dBA		59	61	62
Sound pressure level	Cooling	High/Silent operation		dBA		-/-		48/44
	Heating	High/Silent operation		dBA		-/-		48/45
Operation range	Cooling	Ambient	Min.~Max.	°CDB		10~46		10~46
	Heating	Ambient	Min.~Max.	°CWB		-15~18		-15~18
Refrigerant	Type/Charge/GWP			kg		R-410A / 1 / 2,087.5	R-410A / 1.2 / 2,087.5	R-410A / 1.7 / 2,087.5
	Charge			TCO_2Eq		2.1	2.5	3.5
Piping connections	Liquid	OD		mm		6		6.35
	Gas	OD		mm		9.25		12.7
	Piping length	OU - IU	Max.	m		-		30
		System	Chargeless	m		-		10
	Additional refrigerant charge			kg/m		-		0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m		-		20
Power supply	Phase / Frequency / Voltage			Hz / V		1~ / 50 / 220-240		1~ / 50 / 220-240
Current - 50Hz	Maximum fuse amps (MFA)			A		16		20

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

Wall mounted unit

Siesta wall mounted unit providing high efficiency and comfort

- Seasonal efficiency values up to A++
- ECONO mode decreases power consumption so that other appliances that need large power consumption can be used
- Comfort mode guarantees draught free operation by preventing that warm or cold air is directly blown on to the body
- Titanium apatite photocatalytic air purification filter removes airborne microscopic particles, powerfully decomposes odours and helps to prevent the propagation of bacteria, viruses, microbes to ensure a steady supply of clean air
- Online controller (optional): control your indoor from any location with an app, via your local network or internet



Efficiency data				**ATX + ARX**	***20J3 + 20K**	***25J3 + 25K**	***35J3 + 35K**
Cooling capacity	Min./Nom./Max.			kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.3/3.8
Heating capacity	Min./Nom./Max.			kW	1.3/2.5/3.5	1.3/2.8/4.0	1.3/3.5/4.8
Power input	Cooling	Nom.		kW	0.55	0.73	0.97
	Heating	Nom.		kW	0.59	0.69	1.00
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		
		Pdesign		kW	2.00	2.50	3.30
		SEER			6.10		
		Annual energy consumption		kWh	115	143	189
	Heating (Average climate)	Energy label			A+		
		Pdesign		kW	2.20	2.40	2.80
		SCOP			4.20	4.05	
		Annual energy consumption		kWh	733	830	968
Nominal efficiency	EER				3.64	3.42	3.4
	COP				4.24	4.06	3.5
	Annual energy consumption			kWh	275	365	485
	Energy label	Cooling			A		
		Heating			A		B

Indoor unit				**ATX**	***20J3**	***25J3**	***35J3**
Dimensions	Unit	HeightxWidthxDepth		mm	283x770x198		
Weight	Unit			kg	7		
Fan - Air flow rate	Cooling	High		m^3/min	9.10	9.20	9.30
Sound power level	Cooling			dBA	55		58
	Heating			dBA	55		58
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	39/33/25/22	40/33/26/22	41/34/27/23
	Heating	High/Nom./Low/Silent operation		dBA	39/34/28/25	40/34/28/25	41/35/29/26
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Control systems	Infrared remote control				ARC433A89		

Outdoor unit				**ARX**	***20K**	***25K**	***35K**
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275		
Weight	Unit			kg	26		28
Sound power level	Cooling			dBA	60		62
	Heating			dBA	60		62
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46		
	Heating	Ambient	Min.~Max.	°CWB	-15~18		
Refrigerant	Type/Charge/GWP			kg	R-410A / 0.74 / 2,087.5		R-410A / 1 / 2.087,5
	Charge			TCO_2Eq	1.5		2.1
Piping connections	Piping length	OU - IU	Max.	m	-		
	Level difference	IU - OU	Max.	m	-		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16		

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

Wall mounted unit

Discreet Siesta wall mounted unit providing high efficiency and comfort

- SEER / SCOP up to A++
- Discreet, stylish front panel blends easily with the wall, and matches all interior décors
- Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- Online controller (optional): control your indoor from any location with an app, via your local network or internet
- Dry programme allows humidity levels to be reduced without variations in room temperature



ATX25-35K



ARX20-35K

Efficiency data				**ATX + ARX**	***20K + 20K**	***25K + 25K**	***35K + 35K**
Cooling capacity	Min./Nom./Max.			kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.5/4.0
Heating capacity	Min./Nom./Max.			kW	1.3/2.5/3.5	1.3/3.0/4.0	1.3/4.0/4.8
Power input	Cooling	Nom.		kW	0.50	0.74	1.07
	Heating	Nom.		kW	0.52	0.69	1.00
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		
		Pdesign		kW	2.00	2.50	3.50
		SEER			6.62	6.23	6.40
		Annual energy consumption		kWh	106	140	191
	Heating (Average climate)	Energy label			A++		
		Pdesign		kW	2.20	2.40	2.80
		SCOP			4.97	4.63	4.69
		Annual energy consumption		kWh	620	726	836
Nominal efficiency	EER				3.97	3.37	3.3
	COP				4.77	4.4	4.0
	Annual energy consumption			kWh	252	371	537
	Energy label	Cooling/Heating			A/A		

Indoor unit				**ATX**	***20K**	***25K**	***35K**
Dimensions	Unit	HeightxWidthxDepth		mm	-x-x-		
Weight	Unit			kg	7		
Fan - Air flow rate	Cooling	High		m^3/min	9.10	9.20	9.30
Sound power level	Cooling			dBA	55		58
	Heating			dBA	55		58
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		

Outdoor unit				**ARX**	***20K**	***25K**	***35K**
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275		
Weight	Unit			kg	26		28
Sound power level	Cooling			dBA	60		62
	Heating			dBA	60		62
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46		
	Heating	Ambient	Min.~Max.	°CWB	-15~18		
Refrigerant	Type/Charge/GWP			kg	R-410A / 0.74 / 2.087,5		R-410A / 1 / 2,087.5
	Charge			TCO_2Eq	1.5		2.1
Piping connections	Piping length	OU - IU	Max.	m	-		
	Level difference	IU - OU	Max.	m	-		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16		


*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

Siesta wall mounted unit, offering good value for money and ensuring a steady supply of clean air

- Seasonal efficiency values up to A+
- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- 24 hour timer can be set to start heating or cooling anytime during a 24 hour period



ATXN25-35NB



ARXN25-35NB



AP GS02

Efficiency data				ATXN + ARXN	*25NB + 25NB	*35NB + 35NB	*50NB + 50NB	*60NB + 60NB
Cooling capacity	Nom.			kW	2.56	3.41	5.48	6.23
Heating capacity	Nom.			kW	2.84	3.58	5.62	6.40
Power input	Cooling	Nom.		kW	0.69	1.06	1.70	1.93
	Heating	Nom.		kW	0.70	0.95	1.50	1.68
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+			
		Pdesign		kW	-			
		SEER			5.61		5.88	6.05
		Annual energy consumption		kWh	-			
	Heating (Average climate)	Energy label			A			
		Pdesign		kW	-			
		SCOP			3.81		3.99	3.81
		Annual energy consumption		kWh	-			
Nominal efficiency	EER				3.69	3.22		3.23
	COP				4.06	3.77	3.75	3.81
	Annual energy consumption			kWh	347	530	851	964
	Energy label	Cooling/Heating			A/A			

Indoor unit				ATXN	*25NB	*35NB	*50NB	*60NB
Dimensions	Unit	HeightxWidthxDepth		mm	288x859x209		310x1,124x237	
Weight	Unit			kg	9		14	
Air filter	Type				Saranet (with titanium apatite)			
Sound power level	Cooling			dBA	53	54	55	61
	Heating			dBA	53	54	55	61
Sound pressure level	Cooling	Super high/High/Nom./ Low/Silent operation		dBA	41/40/34/29/21	42/41/34/30/22	44/40/38/35/32	46/43/41/37/33
	Heating	Super high/High/Nom./ Low/Silent operation		dBA	41/40/34/29/21	42/41/34/30/22	44/40/38/35/32	46/43/41/37/33
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			

Outdoor unit				ARXN	*25NB	*35NB	*50NB	*60NB
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x289		753x855x328	
Weight	Unit			kg	31		44	
Sound power level	Cooling			dBA	58	60	64	65
	Heating			dBA	58	60	64	65
Sound pressure level	Cooling	Nom.		dBA	45	46	51	
	Heating	Nom.		dBA	45	46	51	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46			
	Heating	Ambient	Min.~Max.	°CWB	-15~18			
Refrigerant	Type/GWP				R-410A/2,087.5			
Piping connections	Liquid	OD		mm	6.35			
	Gas	OD		mm	9.52		12.70	15.90
	Piping length	OU - IU	Max.	m	-			
	Level difference	IU - OU	Max.	m	-			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)			A	16		20	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

Wall mounted unit

Siesta wall mounted unit for low energy consumption and pleasant comfort

- Seasonal efficiency values up to A+
- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- 24 hour timer can be set to start heating or cooling anytime during a 24 hour period



ATXB25-35C



ARC470A1

Efficiency data				**ATXB + ARXB**	***25C + 25C**	***35C + 35C**	***50C + 50C**	***60C + 60C**
Cooling capacity	Min./Nom./Max.			kW	1.3/2.5/3.0	1.3/3.3/3.8	-/5.48/-	-/6.23/-
Heating capacity	Min./Nom./Max.			kW	1.3/2.8/4.0	1.3/3.5/4.8	-/5.6/-	-/6.4/-
Power input	Cooling	Nom.		kW	0.77	0.99	1.71	1.93
	Heating	Nom.		kW	0.69	0.93	1.49	1.77
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+			
		Pdesign		kW	2.50	3.30	5.48	6.23
		SEER			5.93	6.02	5.90	6.02
		Annual energy consumption		kWh	148	192	325	362
	Heating (Average climate)	Energy label			A+			
		Pdesign		kW	2.40	2.80	3.64	3.80
		SCOP			4.01	4.04	4.20	4.05
		Annual energy consumption		kWh	838	970	1,213	1,314
Nominal efficiency	EER				3.25	3.32	3.21	3.23
	COP				4.06	3.76	3.75	3.61
	Annual energy consumption			kWh	385	497	854	964
	Energy label	Cooling			A			
		Heating			A			

Indoor unit				**ATXB**	***25C**	***35C**	***50C**	***60C**
Dimensions	Unit	HeightxWidthxDepth		mm	363x870x310		386x1136x314	
Weight	Unit			kg	8		14	
Fan - Air flow rate	Cooling	High		m^3/min	9.20	9.30	14.7	16.2
Sound power level	Cooling			dBA	55	58	55	61
	Heating			dBA	55	58	55	61
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				ARC470A1		AP GS02	

Outdoor unit				**ARXB**	***25C**	***35C**	***50C**	***60C**
Dimensions	Unit	HeightxWidthxDepth		mm	616x788x359		793x990x415	
Weight	Unit			kg	27	29	49	
Sound power level	Cooling			dBA	60	62	64	65
	Heating			dBA	60	62	64	65
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-~-			
	Heating	Ambient	Min.~Max.	°CWB	-~-			
Refrigerant	Type/GWP				R-410A/2,087.5			
Piping connections	Piping length	OU - IU	Max.	m	-			
	Level difference	IU - OU	Max.	m	-			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Current - 50Hz	Maximum fuse amps (MFA)			A	-			

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Make all applications possible

Multi model applications

MXS

Installation flexibility

- A very wide range is available, from 2-port to 5-port units, making all applications possible.
- Up to 5 indoor units can be connected to 1 multi outdoor unit.
- All indoor units can be individually controlled and do not need to be installed in the same room.
- Combine different types of indoor units: wall mounted, floor standing, ceiling suspended, round flow cassette, concealed ceiling.
- Phased installation possible.
- Outdoor multi split units are fitted with the Daikin swing compressor, renowned for its low noise and high energy efficiency.
- The outdoor units are neat and sturdy and can be mounted easily on a roof or terrace or simply placed against an outside wall.




5MXS90E



RXYSQ

Installation flexibility

› Up to 9 indoor units can be connected to 1 VRV outdoor unit
› All indoor units can be individually controlled and do not need to be installed in the same room
› Combine different types of indoor units: wall mounted, floor standing, ceiling suspended, round flow cassette, concealed ceiling
› Phased installation possible
› Maximum total piping length of 145m offers much more flexibility in the choice of installation position
› Branch provider (BP) unit varies the refrigerant volume to meet the cooling or heating requirement



VRV IV S-series

Space saving solution without compromising on efficiency

In 2015 our succesful mini VRV range gets a thorough update to make it even better suited for residential applications where space is limited and performance expectations are high.

› Variable Refrigerant Temperature
› The most compact VRV
› Low height to minimize visual impact
› Lightweight reduces installation time and manpower to an absolute minimum

VRV IV S-series

Variable Refrigerant Temperature



Multi model application

- Outdoor units for multi model application.
- Outdoor units are fitted with a swing compressor, renowned for its low noise and high energy efficiency
- Up to 5 indoor units can be connected to 1 multi outdoor unit; all indoor units are individually controllable and do not need to be installed in the same room or at the same time; they operate simultaneously within the same cooling or heating mode
- Different types of indoor units can be connected: e.g. wall mounted, floor standing, concealed ceiling unit, etc.



3MXS52E/4MXS68E



5MXS90E



2MXS40-50H

CONNECTABLE INDOOR UNITS	Wall mounted																Floor standing						Flexi type				Round flow cassette			Fully flat cassette				Concealed ceiling								Ceiling suspended			Concealed floor standing			
	FTXG-L				CTXS-K		FTXS-K					FTXS-G		FTX-J3			FVXG-K			FVXS-F			FLXS-B(9)				FCQG-F			FFQ-C				FDXS-F(9)				FDBQ-B/ FBQ-D				FHQ-C			FNQ-A			
	20	25	35	50	15	35	20	25	35	42	50	60	71	20	25	35	25	35	50	25	35	50	25	35	50	60	35	50	60	25	35	50	60	25	35	50	60	25	35	50	60	35	50	60	25	35	50	60
2MXS40H	●	●	●		●	●	●	●	●					●	●	●	●	●	●	●	●		●	●										●	●													
2MXS50H	●	●	●	●	●	●	●	●	●	●	●			●	●	●	●	●	●	●	●	●	●	●	●					●	●	●		●	●	●												
3MXS40K	●	●	●		●	●	●	●	●								●	●		●	●		●	●			●			●	●			●	●							●			●	●		
3MXS52E	●	●	●	●	●	●	●	●	●	●	●						●	●	●	●	●	●	●	●	●		●	●		●	●	●		●	●	●		●	●	●		●			●	●	●	
3MXS68G	●	●	●	●	●	●	●	●	●	●	●	●					●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
4MXS68F	●	●	●	●	●	●	●	●	●	●	●	●					●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
4MXS80E	●	●	●	●	●	●	●	●	●	●	●	●	●				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
5MXS90E	●	●	●	●	●	●	●	●	●	●	●	●	●				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Note : blue cells contain preliminary data

Outdoor unit					2MXS40H	2MXS50H	3MXS40K	3MXS52E	3MXS68G	4MXS68F	4MXS80E	5MXS90E
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x936x300				770x900x320	
Weight	Unit			kg	38	42	49		58		72	73
Sound power level	Cooling			dBA	62	63	59		61		62	66
	Heating			dBA	-		60		-			
Sound pressure level	Cooling	Nom.		dBA	47	48	46		48			52
	Heating	Nom.		dBA	48	50	47		49			52
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46		-10~46					
	Heating	Ambient	Min.~Max.	°CWB	-15~18							
Refrigerant	Type/Charge/GWP			kg	R-410A / 1.2 / 2,087.5	R-410A / 1.6 / 2,087.5	R-410A / 2.0 / 2,087.5		R-410A / 2.59 / 2,087.5	R-410A / 2.6 / 2,087.5	R-410A / 2.99 / 2,087.5	
	Charge			TCO_2Eq	2.5	3.3	4.2		5.4		6.2	
Piping connections	Liquid	OD		mm	6.35							
	Gas	OD		mm	9.5				9.52			
	Piping length	OU - IU	Max.	m	20		25					
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 20m)		0.02 (for piping length exceeding 30m)					
	Level difference	IU - OU	Max.	m	15							
		IU - IU	Max.	m	7.5							
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 / 230					
Current - 50Hz	Maximum fuse amps (MFA)			A	16				20			

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
2MXS40H3V1B	1.5+1.5	1.5	1.5	1.75	3.0	3.57	0.35	0.66	0.83	1.60	3.1	3.80	94	4.55	A	330	A++	6.13	3.00	172
	1.5+2.0	1.5	2.0	1.75	3.5	3.96	0.35	0.81	0.99	1.60	3.7	4.60	94	4.32	A	405	A++	6.33	3.50	194
	1.5+2.5	1.5	2.5	1.75	4.0	4.22	0.35	1.02	1.12	1.60	4.7	5.20	94	3.92	A	510	A++	6.47	4.00	217
	1.5+3.5	1.2	2.8	1.75	4.0	4.34	0.35	0.99	1.14	1.60	4.6	5.30	94	4.04	A	495	A++	6.42	4.00	218
	2.0+2.0	2.0	2.0	1.75	4.0	4.20	0.31	1.04	1.12	1.40	4.8	5.20	94	3.85	A	520	A++	6.61	4.00	212
	2.0+2.5	1.9	2.2	1.75	4.0	4.30	0.31	1.03	1.17	1.40	4.8	5.40	94	3.88	A	515	A++	6.63	4.00	212
	2.0+3.5	1.8	2.3	1.75	4.0	4.50	0.31	1.00	1.23	1.40	4.6	5.70	94	4.00	A	500	A++	6.52	4.00	215
	2.5+2.5	2.0	2.0	1.75	4.0	4.40	0.31	1.02	1.23	1.40	4.7	5.70	94	3.92	A	510	A++	6.64	4.00	211
	2.5+3.5	1.8	2.2	1.75	4.0	4.60	0.31	0.99	1.31	1.40	4.6	6.10	94	4.04	A	495	A++	6.53	4.00	215

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
2MXS40H3V1B	1.5+1.5	1.9	1.9	1.30	3.8	4.26	0.30	0.90	1.11	1.40	4.1	5.10	95	4.22	A	A+	4.06	3.01	1038	0,57
	1.5+2.0	1.7	2.3	1.30	4.0	4.44	0.30	0.95	1.15	1.40	4.3	5.30	95	4.21	A	A+	4.10	3.03	1035	0,59
	1.5+2.5	1.6	2.6	1.30	4.2	4.58	0.30	1.02	1.22	1.40	4.7	5.60	95	4.12	A	A+	4.11	3.03	1032	0,58
	1.5+3.5	1.3	3.1	1.30	4.4	4.70	0.29	1.09	1.20	1.30	5.0	5.50	95	4.04	A	A+	4.16	3.00	1011	0,59
	2.0+2.0	2.1	2.1	1.40	4.2	4.60	0.27	1.01	1.17	1.20	4.6	5.40	95	4.16	A	A+	4.12	3.03	1029	0,58
	2.0+2.5	2.1	2.3	1.40	4.4	4.70	0.27	1.08	1.21	1.20	4.9	5.50	96	4.07	A	A+	4.13	3.03	1028	0,58
	2.0+3.5	2.0	2.4	1.40	4.4	4.70	0.26	1.06	1.19	1.20	4.8	5.40	96	4.15	A	A+	4.14	2.97	1004	0,56
	2.5+2.5	2.2	2.2	1.40	4.4	4.70	0.27	1.07	1.20	1.20	4.8	5.40	96	4.11	A	A+	4.18	3.03	1016	0,58
	2.5+3.5	2.1	2.4	1.40	4.4	4.70	0.26	1.05	1.18	1.20	4.8	5.30	96	4.19	A	A+	4.13	2.96	1003	0,56

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB(Outdoor temperature)
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB(Outdoor temperature).
2. The total ability of connected indoor unit is up to 6.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5kW: wall mounted FTXS-K series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
2MXS50H3V1B	1.5+1.5	1.50	1.50	1.88	3.00	3.15	0.33	0.55	0.58	1.60	2.60	2.80	91	5.45	A	275	A++	6.42	3.00	164
	1.5+2.0	1.50	2.00	1.88	3.50	3.73	0.32	0.67	0.75	1.50	3.20	3.60	91	5.22	A	335	A++	6.74	3.50	182
	1.5+2.5	1.50	2.50	1.88	4.00	4.23	0.32	0.87	0.97	1.50	4.20	4.60	91	4.60	A	435	A++	6.68	4.00	210
	1.5+3.5	1.50	3.50	1.88	5.00	5.00	0.32	1.35	1.35	1.50	6.50	6.50	91	3.70	A	675	A++	6.43	5.00	273
	1.5+4.2	1.32	3.68	1.95	5.00	5.37	0.34	1.35	1.67	1.60	6.50	8.00	91	3.70	A	675	A++	6.46	5.00	271
	1.5+5.0	1.15	3.85	1.95	5.00	5.50	0.34	1.35	1.81	1.60	6.50	8.60	91	3.70	A	675	A++	6.45	5.00	272
	2.0+2.0	2.00	2.00	1.95	4.00	5.00	0.34	0.87	1.36	1.60	4.20	6.50	91	4.60	A	435	A++	6.73	4.00	208
	2.0+2.5	2.00	2.50	1.95	4.50	5.10	0.34	1.07	1.45	1.60	5.10	6.90	91	4.21	A	535	A++	6.70	4.50	235
	2.0+3.5	1.82	3.18	1.95	5.00	5.40	0.34	1.35	1.62	1.60	6.50	7.70	91	3.70	A	675	A++	6.50	5.00	270
	2.0+4.2	1.61	3.39	1.95	5.00	5.50	0.34	1.34	1.73	1.60	6.40	8.30	91	3.73	A	670	A++	6.53	5.00	269
	2.0+5.0	1.43	3.57	1.95	5.00	5.50	0.34	1.31	1.71	1.60	6.30	8.20	91	3.82	A	655	A++	6.51	5.00	269
	2.5+2.5	2.50	2.50	1.95	5.00	5.30	0.34	1.38	1.61	1.60	6.60	7.70	91	3.62	A	690	A++	6.61	5.00	265
	2.5+3.5	2.08	2.92	1.95	5.00	5.40	0.34	1.34	1.61	1.60	6.40	7.70	91	3.73	A	670	A++	6.52	5.00	269
	2.5+4.2	1.87	3.13	1.95	5.00	5.50	0.34	1.33	1.72	1.60	6.40	8.20	91	3.76	A	665	A++	6.53	5.00	268
	2.5+5.0	1.67	3.33	1.95	5.00	5.50	0.34	1.30	1.70	1.60	6.20	8.10	91	3.85	A	650	A++	6.53	5.00	269
	3.5+3.5	2.50	2.50	1.98	5.00	5.40	0.34	1.29	1.55	1.60	6.20	7.40	91	3.88	A	645	A++	6.44	5.00	272
	3.5+4.2	2.27	2.73	1.98	5.00	5.50	0.34	1.28	1.65	1.60	6.10	7.90	91	3.91	A	640	A++	6.45	5.00	272
	3.5+5.0	2.06	2.94	1.98	5.00	5.50	0.34	1.27	1.62	1.60	6.10	7.70	91	3.94	A	635	A++	6.44	5.00	272
	4.2+4.2	2.50	2.50	1.98	5.00	5.50	0.34	1.27	1.62	1.60	6.10	7.70	91	3.94	A	635	A++	6.47	5.00	271

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
2MXS50H3V1B	1.5+1.5	1.99	1.99	1.17	3.97	4.54	0.22	0.95	1.20	1.1	4.5	5.7	91	4.18	A	A	3.95	3.3	1169	0.64
	1.5+2.0	1.9	2.53	1.17	4.43	4.89	0.22	1.08	1.29	1.1	5.2	6.2	91	4.10	A	A	3.97	3.32	1172	0.64
	1.5+2.5	1.81	3.02	1.17	4.83	5.19	0.23	1.16	1.39	1.1	5.5	6.6	91	4.16	A	A	3.98	3.88	1364	0.75
	1.5+3.5	1.64	3.82	1.17	5.46	5.7	0.23	1.39	1.60	1.1	6.6	7.6	91	3.93	A	A+	4.09	4.25	1454	0.81
	1.5+4.2	1.5	4.2	1.17	5.7	5.96	0.24	1.41	1.53	1.1	6.7	7.3	91	4.04	A	A+	4.06	4.39	1515	0.84
	1.5+5.0	1.32	4.38	1.17	5.7	6.16	0.24	1.44	1.62	1.1	6.9	7.7	91	3.96	A	A+	4.04	4.37	1514	0.83
	2.0+2.0	2.65	2.65	1.18	5.3	5.7	0.23	1.34	1.51	1.1	6.4	7.2	91	3.96	A	A	3.99	3.89	1367	0.75
	2.0+2.5	2.44	3.06	1.18	5.5	5.8	0.23	1.37	1.52	1.1	6.5	7.3	91	4.01	A	A+	4	3.9	1365	0.75
	2.0+3.5	2.04	3.56	1.24	5.6	5.9	0.24	1.39	1.55	1.1	6.6	7.4	91	4.03	A	A+	4.12	4.27	1453	0.81
	2.0+4.2	1.84	3.86	1.25	5.7	6	0.25	1.35	1.50	1.2	6.5	7.2	91	4.22	A	A+	4.09	4.41	1509	0.86
	2.0+5.0	1.63	4.07	1.29	5.7	6.2	0.25	1.38	1.55	1.2	6.6	7.4	91	4.13	A	A+	4.07	4.39	1510	0.86
	2.5+2.5	2.8	2.8	1.18	5.6	5.8	0.23	1.42	1.52	1.1	6.8	7.3	91	3.94	A	A+	4	4.19	1466	0.8
	2.5+3.5	2.38	3.32	1.24	5.7	6	0.25	1.41	1.58	1.2	6.7	7.5	91	4.04	A	A+	4.1	4.41	1507	0.86
	2.5+4.2	2.13	3.57	1.25	5.7	6.1	0.25	1.36	1.51	1.2	6.5	7.2	91	4.19	A	A+	4.11	4.42	1506	0.86
	2.5+5.0	1.9	3.8	1.35	5.7	6.3	0.26	1.35	1.56	1.2	6.5	7.5	91	4.22	A	A+	4.09	4.4	1508	0.86
	3.5+3.5	2.85	2.85	1.3	5.7	6.1	0.25	1.46	1.63	1.2	7	7.8	91	3.90	A	A+	4.3	4.5	1467	0.87
	3.5+4.2	2.59	3.11	1.31	5.7	6.2	0.26	1.38	1.51	1.2	6.6	7.2	91	4.13	A	A+	4.28	4.51	1476	0.87
	3.5+5.0	2.35	3.35	1.35	5.7	6.4	0.27	1.38	1.56	1.3	6.6	7.5	91	4.13	A	A+	4.21	4.49	1493	0.87
	4.2+4.2	2.85	2.85	1.32	5.7	6.3	0.23	1.31	1.50	1.1	6.3	7.2	91	4.35	A	A+	4.29	4.52	1475	0.88

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 8.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
3MXS40K3V1B	1.5+1.5	1.50	1.50	---	---	1.78	3.00	4.20	0.35	0.63	1.12	1.60	2.80	5.00	98.00	4.76	A	315	A++	6.55	3.00	161
	1.5+2.0	1.50	2.00	---	---	1.78	3.50	4.20	0.35	0.80	1.12	1.50	3.50	4.90	99.00	4.38	A	400	A++	6.77	3.50	182
	1.5+2.5	1.50	2.50	---	---	1.78	4.00	4.20	0.35	0.98	1.12	1.50	4.30	4.90	99.00	4.08	A	490	A++	6.86	4.00	205
	1.5+3.5	1.20	2.80	---	---	1.78	4.00	4.21	0.35	0.98	1.12	1.50	4.30	4.90	99.00	4.08	A	490	A++	6.69	4.00	210
	2.0+2.0	2.00	2.00	---	---	1.88	4.00	4.54	0.35	0.95	1.12	1.50	4.20	4.90	99.00	4.21	A	475	A++	6.90	4.00	203
	2.0+2.5	1.78	2.22	---	---	1.88	4.00	4.54	0.35	0.95	1.12	1.50	4.20	4.90	99.00	4.21	A	475	A++	6.90	4.00	203
	2.0+3.5	1.45	2.55	---	---	1.88	4.00	4.55	0.35	0.95	1.09	1.50	4.20	4.80	99.00	4.21	A	475	A++	6.73	4.00	209
	2.5+2.5	2.00	2.00	---	---	1.88	4.00	4.54	0.35	0.95	1.12	1.50	4.20	4.90	99.00	4.21	A	475	A++	6.90	4.00	203
	2.5+3.5	1.67	2.33	---	---	1.88	4.00	4.54	0.35	0.95	1.12	1.50	4.20	4.90	99.00	4.21	A	475	A++	6.73	4.00	209
	3.5+3.5	2.00	2.00	---	---	1.88	4.00	4.58	0.35	0.95	1.12	1.50	4.20	4.90	99.00	4.21	A	475	A++	6.56	4.00	214
	1.5+1.5+1.5	1.33	1.33	1.33	---	1.80	4.00	4.60	0.35	0.83	0.98	1.50	3.60	4.30	99.00	4.82	A	415	A++	6.97	4.00	201
	1.5+1.5+2.0	1.20	1.20	1.60	---	1.80	4.00	4.60	0.35	0.84	0.98	1.50	3.70	4.30	99.00	4.76	A	420	A++	6.97	4.00	201
	1.5+1.5+2.5	1.09	1.09	1.82	---	1.80	4.00	4.60	0.35	0.84	0.98	1.50	3.70	4.30	99.00	4.76	A	420	A++	6.97	4.00	201
	1.5+1.5+3.5	0.92	0.92	2.15	---	1.80	4.00	4.60	0.37	0.84	0.98	1.60	3.70	4.30	99.00	4.76	A	420	A++	6.80	4.00	206
	1.5+2.0+2.0	1.09	1.45	1.45	---	1.80	4.00	4.60	0.35	0.84	0.98	1.50	3.70	4.30	99.00	4.76	A	420	A++	6.98	4.00	201
	1.5+2.0+2.5	1.00	1.33	1.67	---	1.80	4.00	4.60	0.35	0.84	0.98	1.50	3.70	4.30	99.00	4.76	A	420	A++	6.98	4.00	201
	1.5+2.0+3.5	0.86	1.14	2.00	---	1.80	4.00	4.60	0.37	0.84	0.98	1.60	3.70	4.30	99.00	4.76	A	420	A++	6.81	4.00	206
	1.5+2.5+2.5	0.92	1.54	1.54	---	1.80	4.00	4.60	0.37	0.84	0.98	1.60	3.70	4.30	99.00	4.76	A	420	A++	6.98	4.00	201
	2.0+2.0+2.0	1.33	1.33	1.33	---	1.86	4.00	4.60	0.35	0.81	0.98	1.50	3.60	4.30	99.00	4.94	A	405	A++	7.02	4.00	200
	2.0+2.0+2.5	1.23	1.23	1.54	---	1.86	4.00	4.60	0.35	0.81	0.98	1.50	3.60	4.30	99.00	4.94	A	405	A++	7.02	4.00	200
	2.0+2.5+2.5	1.14	1.43	1.43	---	1.95	4.00	4.60	0.37	0.81	0.98	1.60	3.60	4.30	99.00	4.94	A	405	A++	7.02	4.00	200

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
3MXS40K3V1B	1.5+1.5	2.30	2.30	---	---	1.22	4.60	5.00	0.31	1.11	1.29	1.4	4.9	5.7	99	4.14	A	A+	4.09	3.59	1229	0.68
	1.5+2.0	1.97	2.63	---	---	1.22	4.60	5.00	0.31	1.11	1.29	1.4	4.9	5.7	99	4.14	A	A+	4.12	3.61	1227	0.68
	1.5+2.5	1.73	2.88	---	---	1.22	4.60	5.00	0.31	1.10	1.29	1.4	4.8	5.7	99	4.18	A	A+	4.04	4.73	1640	0.91
	1.5+3.5	1.38	3.22	---	---	1.25	4.60	5.02	0.31	1.10	1.29	1.4	4.8	5.7	99	4.18	A	A+	4.17	4.84	1624	0.93
	2.0+2.0	2.30	2.30	---	---	1.28	4.60	5.00	0.31	1.11	1.29	1.4	4.9	5.7	99	4.14	A	A+	4.05	4.75	1641	0.92
	2.0+2.5	2.04	2.56	---	---	1.28	4.60	5.00	0.31	1.10	1.29	1.4	4.8	5.7	99	4.18	A	A+	4.07	4.76	1636	0.92
	2.0+3.5	1.67	2.93	---	---	1.34	4.60	5.02	0.31	1.10	1.29	1.4	4.8	5.7	99	4.18	A	A+	4.23	4.86	1609	0.93
	2.5+2.5	2.30	2.30	---	---	1.28	4.60	5.00	0.31	1.10	1.29	1.4	4.8	5.7	99	4.18	A	A+	4.08	4.77	1636	0.92
	2.5+3.5	1.92	2.68	---	---	1.34	4.60	5.02	0.31	1.10	1.29	1.4	4.8	5.7	99	4.18	A	A+	4.24	4.87	1610	0.93
	3.5+3.5	2.30	2.30	---	---	1.40	4.60	5.04	0.31	1.10	1.28	1.4	4.8	5.6	99	4.18	A	A+	4.37	4.93	1580	0.94
	1.5+1.5+1.5	1.53	1.53	1.53	---	1.32	4.60	5.00	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.29	4.93	1609	0.94
	1.5+1.5+2.0	1.38	1.38	1.84	---	1.32	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.31	4.94	1605	0.95
	1.5+1.5+2.5	1.25	1.25	2.09	---	1.32	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.31	4.94	1603	0.94
	1.5+1.5+3.5	1.06	1.06	2.48	---	1.32	4.60	5.09	0.32	0.91	1.01	1.4	4.0	4.4	99	5.05	A	A+	4.39	4.95	1578	0.94
	1.5+2.0+2.0	1.25	1.67	1.67	---	1.32	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.32	4.94	1602	0.94
	1.5+2.0+2.5	1.15	1.53	1.92	---	1.33	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.36	4.94	1588	0.94
	1.5+2.0+3.5	0.99	1.31	2.30	---	1.33	4.60	5.09	0.32	0.91	1.01	1.4	4.0	4.4	99	5.05	A	A+	4.40	4.95	1575	0.95
	1.5+2.5+2.5	1.06	1.77	1.77	---	1.33	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.34	4.95	1596	0.95
	2.0+2.0+2.0	1.53	1.53	1.53	---	1.34	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.34	4.95	1596	0.95
	2.0+2.0+2.5	1.42	1.42	1.77	---	1.34	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.35	4.95	1594	0.95
	2.0+2.5+2.5	1.31	1.64	1.64	---	1.45	4.60	5.07	0.32	0.91	1.02	1.4	4.0	4.5	99	5.05	A	A+	4.36	4.95	1590	0.94

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 7.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5kW: wall mounted FTXS-K series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
3MXS52E4V1B	1.5+1.5	1.50	1.50	---	---	1.88	3.00	4.72	0.35	0.61	1.30	1.5	2.7	5.7	99	4.92	A	305	A++	6.55	3.00	161
	1.5+2.0	1.50	2.00	---	---	1.88	3.50	4.72	0.35	0.77	1.30	1.5	3.4	5.7	99	4.55	A	385	A++	6.77	3.50	182
	1.5+2.5	1.50	2.50	---	---	1.88	4.00	5.68	0.35	0.95	1.91	1.5	4.2	8.4	99	4.21	A	475	A++	6.86	4.00	205
	1.5+3.5	1.50	3.50	---	---	1.88	5.00	5.99	0.35	1.45	2.17	1.5	6.4	9.5	99	3.45	A	725	A++	6.76	5.00	259
	1.5+4.2	1.37	3.83	---	---	1.88	5.20	6.08	0.35	1.55	2.25	1.5	6.8	9.9	99	3.35	A	775	A++	6.81	5.20	268
	1.5+5.0	1.20	---	4.00	---	1.88	5.20	6.29	0.35	1.46	2.27	1.5	6.4	10.0	99	3.56	A	730	A++	6.79	5.20	269
	2.0+2.0	2.00	2.00	---	---	1.88	4.00	5.96	0.35	0.95	1.91	1.5	4.2	8.4	99	4.21	A	475	A++	6.90	4.00	203
	2.0+2.5	2.00	2.50	---	---	1.88	4.50	6.23	0.35	1.18	2.14	1.5	5.2	9.4	99	3.81	A	590	A++	6.90	4.50	229
	2.0+3.5	1.89	3.31	---	---	1.88	5.20	6.24	0.35	1.55	2.07	1.5	6.8	9.1	99	3.35	A	775	A++	6.83	5.20	267
	2.0+4.2	1.68	3.52	---	---	1.88	5.20	6.25	0.35	1.55	2.07	1.5	6.8	9.1	99	3.35	A	775	A++	6.85	5.20	266
	2.0+5.0	1.49	---	3.71	---	1.88	5.20	6.47	0.35	1.42	2.15	1.5	6.2	9.4	99	3.66	A	710	A++	6.83	5.20	267
	2.5+2.5	2.50	2.50	---	---	1.88	5.00	6.23	0.35	1.45	2.14	1.5	6.4	9.4	99	3.45	A	725	A++	6.93	5.00	253
	2.5+3.5	2.17	3.03	---	---	1.88	5.20	6.35	0.35	1.55	2.25	1.5	6.8	9.9	99	3.35	A	775	A++	6.83	5.20	267
	2.5+4.2	1.94	3.26	---	---	1.88	5.20	6.36	0.35	1.55	2.25	1.5	6.8	9.9	99	3.35	A	775	A++	6.85	5.20	266
	2.5+5.0	1.73	---	3.47	---	1.88	5.20	6.47	0.35	1.42	2.07	1.5	6.2	9.1	99	3.66	A	710	A++	6.85	5.20	266
	3.5+3.5	2.60	2.60	---	---	1.88	5.20	6.40	0.35	1.55	2.25	1.5	6.8	9.9	99	3.35	A	775	A++	6.72	5.20	271
	3.5+4.2	2.36	2.84	---	---	1.88	5.20	6.41	0.35	1.55	2.25	1.5	6.8	9.9	99	3.35	A	775	A++	6.72	5.20	271
	3.5+5.0	2.14	---	3.06	---	1.88	5.21	6.49	0.35	1.42	2.09	1.5	6.2	9.2	99	3.67	A	710	A++	6.72	5.20	271
	4.2+4.2	2.60	2.60	---	---	1.88	5.20	6.42	0.35	1.55	2.25	1.5	6.8	9.9	99	3.35	A	775	A++	6.72	5.20	271
	1.5+1.5+1.5	1.50	1.50	1.50	---	1.86	4.50	6.71	0.35	0.97	2.16	1.5	4.3	9.5	99	4.64	A	485	A++	7.06	4.50	223
	1.5+1.5+2.0	1.50	1.50	2.00	---	1.86	5.00	6.71	0.35	1.18	2.16	1.5	5.2	9.5	99	4.24	A	590	A++	7.15	5.00	245
	1.5+1.5+2.5	1.42	1.42	2.36	---	1.86	5.20	6.71	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.17	5.20	254
	1.5+1.5+3.5	1.20	1.20	2.80	---	1.95	5.20	6.72	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.05	5.20	259
	1.5+1.5+4.2	1.08	1.08	3.03	---	1.95	5.20	6.73	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.05	5.20	259
	1.5+1.5+5.0	0.98	0.98	3.25	---	2.11	5.20	6.90	0.35	1.21	2.17	1.5	5.3	9.5	99	4.30	A	605	A++	7.05	5.20	259
	1.5+2.0+2.0	1.42	1.89	1.89	---	1.86	5.20	6.71	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.20	5.20	253
	1.5+2.0+2.5	1.30	1.73	2.17	---	1.86	5.20	6.71	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.20	5.20	253
	1.5+2.0+3.5	1.11	1.49	2.60	---	1.95	5.20	6.72	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.07	5.20	258
	1.5+2.0+4.2	1.01	1.35	2.84	---	1.95	5.20	6.73	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.06	5.20	258
	1.5+2.0+5.0	0.92	1.22	3.06	---	2.11	5.20	6.90	0.35	1.21	2.17	1.5	5.3	9.5	99	4.30	A	605	A++	7.07	5.20	258
	1.5+2.5+2.5	1.20	2.00	2.00	---	1.86	5.20	6.71	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.20	5.20	253
	1.5+2.5+3.5	1.04	1.73	2.43	---	1.95	5.20	6.72	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.06	5.20	258
	1.5+2.5+4.2	0.95	1.59	2.66	---	1.95	5.20	6.73	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.06	5.20	258
	1.5+2.5+5.0	0.87	1.44	2.89	---	2.11	5.20	6.90	0.35	1.21	2.17	1.5	5.3	9.5	99	4.30	A	605	A++	7.06	5.20	258
	1.5+3.5+3.5	0.92	2.14	2.14	---	1.86	5.20	6.73	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	6.93	5.20	263
	2.0+2.0+2.0	1.73	1.73	1.73	---	1.86	5.19	7.04	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.22	5.19	252
	2.0+2.0+2.5	1.60	1.60	1.99	---	1.86	5.19	7.04	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.23	5.19	252
	2.0+2.0+3.5	1.38	1.38	2.43	---	1.95	5.19	7.06	0.37	1.24	2.16	1.6	5.4	9.5	99	4.19	A	620	A++	7.08	5.19	257
	2.0+2.0+4.2	1.27	1.27	2.66	---	1.95	5.20	7.07	0.37	1.24	2.16	1.6	5.4	9.5	99	4.19	A	620	A++	7.09	5.20	257
	2.0+2.0+5.0	1.16	1.16	2.88	---	2.11	5.20	7.30	0.38	1.22	2.26	1.7	5.4	9.9	99	4.26	A	610	A++	7.08	5.20	258
	2.0+2.5+2.5	1.49	1.85	1.85	---	1.86	5.19	7.04	0.35	1.24	2.16	1.5	5.4	9.5	99	4.19	A	620	A++	7.23	5.19	252
	2.0+2.5+3.5	1.30	1.63	2.27	---	1.95	5.20	7.06	0.37	1.24	2.16	1.6	5.4	9.5	99	4.19	A	620	A++	7.08	5.20	258
	2.0+2.5+4.2	1.20	1.49	2.51	---	1.95	5.20	7.07	0.37	1.24	2.16	1.6	5.4	9.5	99	4.19	A	620	A++	7.09	5.20	257
	2.0+3.5+3.5	1.16	2.02	2.02	---	1.95	5.20	7.07	0.37	1.24	2.16	1.6	5.4	9.5	99	4.19	A	620	A++	6.94	5.20	263
	2.5+2.5+2.5	1.73	1.73	1.73	---	1.95	5.19	7.04	0.37	1.24	2.16	1.6	5.4	9.5	99	4.19	A	620	A++	7.23	5.19	252
	2.5+2.5+3.5	1.53	1.53	2.14	---	1.95	5.20	7.06	0.37	1.23	2.16	1.6	5.4	9.5	99	4.23	A	615	A++	7.09	5.20	257

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor Temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°DB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 9.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
3MXS52E4V1B	1.5+1.5	1.81	1.81	---	---	1.28	3.62	5.81	0.31	0.81	1.64	1.4	3.6	7.2	99	4.47	A	A+	4.09	3.59	1229	0.68
	1.5+2.0	1.74	2.33	---	---	1.28	4.07	5.81	0.31	0.94	1.64	1.4	4.1	7.2	99	4.33	A	A+	4.12	3.61	1227	0.68
	1.5+2.5	1.70	2.83	---	---	1.28	4.53	6.93	0.31	1.07	2.28	1.4	4.7	10.0	99	4.23	A	A+	4.04	4.73	1640	0.91
	1.5+3.5	1.63	3.79	---	---	1.28	5.42	6.96	0.31	1.37	2.28	1.4	6.0	10.0	99	3.96	A	A+	4.17	4.84	1624	0.93
	1.5+4.2	1.59	4.46	---	---	1.28	6.05	6.98	0.31	1.64	2.27	1.4	7.2	10.0	99	3.69	A	A+	4.18	4.85	1625	0.93
	1.5+5.0	1.56	---	5.21	---	1.27	6.77	7.20	0.31	1.83	2.32	1.4	8.0	10.2	99	3.70	A	A+	4.16	4.83	1626	0.93
	2.0+2.0	3.05	3.05	---	---	1.28	6.10	7.00	0.31	1.70	2.28	1.4	7.5	10.0	99	3.59	B	A+	4.05	4.75	1641	0.92
	2.0+2.5	2.78	3.47	---	---	1.28	6.25	7.00	0.31	1.75	2.28	1.4	7.7	10.0	99	3.57	B	A+	4.07	4.76	1636	0.92
	2.0+3.5	2.38	4.17	---	---	1.34	6.55	7.04	0.31	1.86	2.28	1.4	8.2	10.0	99	3.52	B	A+	4.23	4.86	1609	0.93
	2.0+4.2	2.16	4.54	---	---	1.34	6.70	7.05	0.31	1.93	2.27	1.4	8.5	10.0	99	3.47	B	A+	4.24	4.87	1610	0.94
	2.0+5.0	1.94	---	4.86	---	1.39	6.80	7.20	0.31	1.87	2.32	1.4	8.2	10.2	99	3.64	A	A+	4.18	4.85	1625	0.93
	2.5+2.5	3.25	3.25	---	---	1.28	6.50	7.00	0.31	1.86	2.31	1.4	8.2	10.1	99	3.49	B	A+	4.08	4.77	1636	0.92
	2.5+3.5	2.79	3.91	---	---	1.34	6.70	7.19	0.31	1.93	2.36	1.4	8.5	10.4	99	3.47	B	A+	4.24	4.87	1610	0.93
	2.5+4.2	2.54	4.26	---	---	1.34	6.80	7.21	0.31	1.93	2.35	1.4	8.5	10.3	99	3.52	B	A+	4.25	4.88	1608	0.94
	2.5+5.0	2.27	---	4.53	---	1.45	6.80	7.35	0.31	1.87	2.32	1.4	8.2	10.2	99	3.64	A	A+	4.23	4.86	1609	0.93
	3.5+3.5	3.40	3.40	---	---	1.40	6.80	7.22	0.31	1.97	2.35	1.4	8.7	10.3	99	3.45	B	A+	4.37	4.93	1580	0.94
	3.5+4.2	3.09	3.71	---	---	1.40	6.80	7.24	0.31	1.97	2.35	1.4	8.7	10.3	99	3.45	B	A+	4.37	4.93	1579	0.94
	3.5+5.0	2.80	---	4.00	---	1.45	6.80	7.50	0.31	1.83	2.31	1.4	8.0	10.1	99	3.72	A	A+	4.36	4.92	1581	0.94
	4.2+4.2	3.40	3.40	---	---	1.40	6.80	7.26	0.31	1.96	2.34	1.4	8.6	10.3	99	3.47	B	A+	4.42	4.94	1566	0.95
	1.5+1.5+1.5	1.66	1.66	1.66	---	1.34	4.97	8.02	0.32	1.02	2.14	1.4	4.5	9.4	99	4.87	A	A+	4.29	4.93	1609	0.94
	1.5+1.5+2.0	1.63	1.63	2.17	---	1.34	5.42	8.02	0.32	1.12	2.14	1.4	4.9	9.4	99	4.84	A	A+	4.31	4.94	1605	0.95
	1.5+1.5+2.5	1.60	1.60	2.67	---	1.34	5.87	8.02	0.32	1.26	2.14	1.4	5.5	9.4	99	4.66	A	A+	4.31	4.94	1603	0.94
	1.5+1.5+3.5	1.56	1.56	3.65	---	1.45	6.77	8.05	0.32	1.56	2.14	1.4	6.9	9.4	99	4.34	A	A+	4.39	4.95	1578	0.94
	1.5+1.5+4.2	1.42	1.42	3.97	---	1.45	6.80	8.06	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.40	4.95	1576	0.95
	1.5+1.5+5.0	1.28	1.28	4.25	---	1.67	6.80	8.27	0.32	1.64	2.11	1.4	7.2	9.3	99	4.15	A	A+	4.39	4.95	1580	0.94
	1.5+2.0+2.0	1.60	2.13	2.13	---	1.34	5.87	8.02	0.32	1.26	2.14	1.4	5.5	9.4	99	4.66	A	A+	4.32	4.94	1602	0.94
	1.5+2.0+2.5	1.58	2.11	2.63	---	1.34	6.32	8.02	0.32	1.41	2.14	1.4	6.2	9.4	99	4.48	A	A+	4.36	4.94	1588	0.94
	1.5+2.0+3.5	1.46	1.94	3.40	---	1.45	6.80	8.05	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.40	4.95	1575	0.95
	1.5+2.0+4.2	1.32	1.77	3.71	---	1.45	6.80	8.06	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.43	4.94	1563	0.94
	1.5+2.0+5.0	1.20	1.60	4.00	---	1.67	6.80	8.27	0.32	1.64	2.11	1.4	7.2	9.3	99	4.15	A	A+	4.40	4.95	1576	0.95
	1.5+2.5+2.5	1.56	2.60	2.60	---	1.34	6.77	8.02	0.32	1.57	2.14	1.4	6.9	9.4	99	4.31	A	A+	4.34	4.95	1596	0.95
	1.5+2.5+3.5	1.36	2.27	3.17	---	1.45	6.80	8.05	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.43	4.94	1563	0.94
	1.5+2.5+4.2	1.24	2.07	3.48	---	1.45	6.80	8.06	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.42	4.94	1564	0.94
	1.5+2.5+5.0	1.13	1.89	3.78	---	1.67	6.80	8.27	0.32	1.64	2.11	1.4	7.2	9.3	99	4.15	A	A+	4.40	4.95	1575	0.95
	1.5+3.5+3.5	1.20	2.80	2.80	---	1.34	6.80	8.08	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.47	4.90	1537	0.93
	2.0+2.0+2.0	2.26	2.26	2.26	---	1.34	6.78	8.02	0.32	1.57	2.14	1.4	6.9	9.4	99	4.32	A	A+	4.34	4.95	1596	0.95
	2.0+2.0+2.5	2.09	2.09	2.60	---	1.34	6.78	8.02	0.32	1.57	2.14	1.4	6.9	9.4	99	4.32	A	A+	4.35	4.95	1594	0.95
	2.0+2.0+3.5	1.80	1.80	3.18	---	1.45	6.78	8.05	0.32	1.56	2.14	1.4	6.9	9.4	99	4.35	A	A+	4.43	4.94	1562	0.94
	2.0+2.0+4.2	1.66	1.66	3.48	---	1.45	6.80	8.06	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.44	4.94	1558	0.94
	2.0+2.0+5.0	1.51	1.51	3.78	---	1.67	6.80	8.27	0.32	1.64	2.11	1.4	7.2	9.3	99	4.15	A	A+	4.43	4.94	1563	0.94
	2.0+2.5+2.5	1.94	2.42	2.42	---	1.34	6.78	8.02	0.32	1.57	2.14	1.4	6.9	9.4	99	4.32	A	A+	4.36	4.95	1590	0.94
	2.0+2.5+3.5	1.70	2.13	2.98	---	1.57	6.80	8.05	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.44	4.94	1557	0.94
	2.0+2.5+4.2	1.56	1.95	3.28	---	1.56	6.80	8.06	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.44	4.94	1559	0.95
	2.0+3.5+3.5	1.52	2.64	2.64	---	1.56	6.80	8.08	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.49	4.89	1525	0.94
	2.5+2.5+2.5	2.26	2.26	2.26	---	1.45	6.78	8.02	0.32	1.57	2.14	1.4	6.9	9.4	99	4.32	A	A+	4.40	4.95	1574	0.94
	2.5+2.5+3.5	2.00	2.00	2.80	---	1.57	6.80	8.05	0.32	1.56	2.14	1.4	6.9	9.4	99	4.36	A	A+	4.46	4.93	1549	0.94

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor Temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°DB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 9.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
3MXS68G3V1B	1.5+1.5	1.50	1.50	---	---	1.97	3.00	4.70	0.43	0.65	1.29	1.9	2.9	5.7	99	4.62	A	325	B	4.98	3.00	211
	1.5+2.0	1.50	2.00	---	---	1.97	3.50	4.86	0.43	0.80	1.37	1.9	3.5	6.0	99	4.38	A	400	B	5.09	3.50	241
	1.5+2.5	1.50	2.50	---	---	1.97	4.00	6.04	0.43	0.99	2.04	1.9	4.3	9.0	99	4.04	A	495	A	5.16	4.00	272
	1.5+3.5	1.50	3.50	---	---	1.97	5.00	6.25	0.42	1.39	2.20	1.8	6.1	9.7	99	3.60	A	695	A	5.14	5.00	341
	1.5+4.2	1.50	4.20	---	---	1.97	5.70	6.26	0.42	1.79	2.20	1.8	7.9	9.7	99	3.18	B	895	A	5.16	5.70	387
	1.5+5.0	1.50	5.00	---	---	1.97	6.50	7.06	0.41	2.22	2.60	1.8	9.7	11.4	99	2.93	C	1110	B	4.94	6.50	461
	1.5+6.0	1.36	5.44	---	---	1.98	6.80	7.38	0.40	2.26	2.60	1.8	9.9	11.4	99	3.01	B	1130	A	5.43	6.80	439
	2.0+2.0	2.00	2.00	---	---	1.97	4.00	5.02	0.43	1.00	1.45	1.9	4.4	6.4	99	4.00	A	500	A	5.18	4.00	271
	2.0+2.5	2.00	2.50	---	---	1.97	4.50	5.33	0.43	1.20	1.61	1.9	5.3	7.1	99	3.75	A	600	A	5.22	4.50	302
	2.0+3.5	2.00	3.50	---	---	1.97	5.50	6.18	0.42	1.66	2.15	1.8	7.3	9.4	99	3.31	A	830	A	5.23	5.50	368
	2.0+4.2	2.00	4.20	---	---	1.97	6.20	6.38	0.42	2.09	2.30	1.8	9.2	10.1	99	2.97	C	1045	B	5.08	6.20	428
	2.0+5.0	1.94	4.86	---	---	1.97	6.80	7.12	0.41	2.41	2.65	1.8	10.6	11.6	99	2.82	C	1205	B	4.93	6.80	483
	2.0+6.0	1.70	5.10	---	---	1.98	6.80	7.56	0.40	2.21	2.75	1.8	9.7	12.1	99	3.08	B	1105	A	5.49	6.80	434
	2.5+2.5	2.50	2.50	---	---	1.97	5.00	5.98	0.45	1.46	2.00	2.0	6.4	8.8	99	3.42	A	730	A	5.26	5.00	333
	2.5+3.5	2.50	3.50	---	---	1.97	6.00	6.44	0.43	2.06	2.37	1.9	9.0	10.4	99	2.91	C	1030	A	5.12	6.00	411
	2.5+4.2	2.50	4.20	---	---	1.97	6.70	6.81	0.43	2.54	2.67	1.9	11.2	11.7	99	2.64	D	1270	B	4.96	6.70	473
	2.5+5.0	2.27	4.53	---	---	1.97	6.80	7.23	0.40	2.41	2.75	1.8	10.6	12.1	99	2.82	C	1205	B	4.93	6.80	483
	2.5+6.0	2.00	4.80	---	---	1.98	6.80	7.56	0.38	2.21	2.75	1.7	9.7	12.1	99	3.08	B	1105	A	5.49	6.80	434
	3.5+3.5	3.40	3.40	---	---	1.97	6.80	6.99	0.41	2.51	2.66	1.8	11.0	11.7	99	2.71	D	1255	B	4.91	6.80	485
	3.5+4.2	3.09	3.71	---	---	1.97	6.80	7.10	0.41	2.51	2.76	1.8	11.0	12.1	99	2.71	D	1255	B	4.95	6.80	481
	3.5+5.0	2.80	4.00	---	---	1.97	6.80	7.61	0.38	2.41	3.12	1.7	10.6	13.7	99	2.82	C	1205	B	4.91	6.80	485
	3.5+6.0	2.51	4.29	---	---	2.28	6.80	7.91	0.43	2.21	3.06	1.9	9.7	13.4	99	3.08	B	1105	A	5.45	6.80	437
	4.2+4.2	3.40	3.40	---	---	1.97	6.80	7.00	0.41	2.51	2.66	1.8	11.0	11.7	99	2.71	D	1255	B	4.96	6.80	480
	4.2+5.0	3.10	3.70	---	---	1.97	6.80	7.62	0.38	2.41	3.12	1.7	10.6	13.7	99	2.82	C	1205	B	4.96	6.80	481
	4.2+6.0	2.80	4.00	---	---	2.28	6.80	7.92	0.43	2.21	3.06	1.9	9.7	13.4	99	3.08	B	1105	A	5.46	6.80	436
	5.0+5.0	3.40	3.40	---	---	2.36	6.80	8.06	0.47	2.31	3.35	2.1	10.1	14.7	99	2.94	C	1155	B	4.92	6.80	485
	5.0+6.0	3.09	3.71	---	---	2.49	6.80	8.28	0.48	2.12	3.28	2.1	9.3	14.4	99	3.21	A	1060	A	5.45	6.80	437
	1.5+1.5+1.5	1.50	1.50	1.50	---	1.98	4.50	6.11	0.42	1.03	1.68	1.8	4.5	7.4	99	4.37	A	515	A	5.27	4.50	300
	1.5+1.5+2.0	1.50	1.50	2.00	---	1.98	5.00	6.19	0.42	1.21	1.72	1.8	5.3	7.6	99	4.13	A	605	A	5.37	5.00	327
	1.5+1.5+2.5	1.50	1.50	2.50	---	1.98	5.50	6.74	0.42	1.44	2.03	1.8	6.3	8.9	99	3.82	A	720	A	5.42	5.50	355
	1.5+1.5+3.5	1.50	1.50	3.50	---	1.98	6.50	7.11	0.41	1.94	2.26	1.8	8.5	9.9	99	3.35	A	970	A	5.33	6.50	427
	1.5+1.5+4.2	1.42	1.42	3.97	---	1.98	6.80	7.32	0.41	2.12	2.40	1.8	9.3	10.5	99	3.21	A	1060	A	5.31	6.80	449
	1.5+1.5+5.0	1.28	1.28	4.25	---	1.98	6.80	7.72	0.39	2.02	2.59	1.7	8.9	11.4	99	3.37	A	1010	A	5.30	6.80	450
	1.5+1.5+6.0	1.13	1.13	4.53	---	2.33	6.80	8.04	0.44	1.88	2.59	1.9	8.3	11.4	99	3.62	A	940	A+	5.75	6.80	415
	1.5+2.0+2.0	1.50	2.00	2.00	---	1.98	5.50	6.35	0.42	1.44	1.81	1.8	6.3	7.9	99	3.82	A	720	A	5.46	5.50	353
	1.5+2.0+2.5	1.50	2.00	2.50	---	1.98	6.00	6.74	0.42	1.68	2.03	1.8	7.4	8.9	99	3.57	A	840	A	5.51	6.00	382
	1.5+2.0+3.5	1.46	1.94	3.40	---	1.98	6.80	7.11	0.41	2.12	2.26	1.8	9.3	9.9	99	3.21	A	1060	A	5.34	6.80	446
	1.5+2.0+4.2	1.32	1.77	3.71	---	1.98	6.80	7.32	0.41	2.12	2.40	1.8	9.3	10.5	99	3.21	A	1060	A	5.38	6.80	443
	1.5+2.0+5.0	1.20	1.60	4.00	---	1.98	6.80	7.72	0.39	2.02	2.59	1.7	8.9	11.4	99	3.37	A	1010	A	5.35	6.80	446
	1.5+2.0+6.0	1.07	1.43	4.29	---	2.33	6.80	8.04	0.44	1.88	2.59	1.9	8.3	11.4	99	3.62	A	940	A+	5.81	6.80	410
	1.5+2.5+2.5	1.50	2.50	2.50	---	1.98	6.50	6.96	0.41	1.94	2.16	1.8	8.5	9.5	99	3.35	A	970	A	5.45	6.50	418
	1.5+2.5+3.5	1.36	2.27	3.17	---	1.98	6.80	7.45	0.39	2.12	2.50	1.7	9.3	11.0	99	3.21	A	1060	A	5.38	6.80	443
	1.5+2.5+4.2	1.24	2.07	3.48	---	1.98	6.80	7.66	0.39	2.12	2.64	1.7	9.3	11.6	99	3.21	A	1060	A	5.38	6.80	443
	1.5+2.5+5.0	1.13	1.89	3.78	---	1.98	6.80	7.79	0.39	2.02	2.64	1.7	8.9	11.6	99	3.37	A	1010	A	5.38	6.80	443
	1.5+2.5+6.0	1.02	1.70	4.08	---	2.33	6.80	8.25	0.45	1.88	2.74	2.0	8.3	12.0	99	3.62	A	940	A+	5.81	6.80	410
	1.5+3.5+3.5	1.20	2.80	2.80	---	1.98	6.80	7.46	0.40	2.12	2.50	1.8	9.3	11.0	99	3.21	A	1060	A	5.32	6.80	448
	1.5+3.5+4.2	1.11	2.59	3.10	---	1.98	6.80	7.67	0.40	2.12	2.64	1.8	9.3	11.6	99	3.21	A	1060	A	5.33	6.80	447
	1.5+3.5+5.0	1.02	2.38	3.40	---	2.30	6.80	8.29	0.44	2.02	3.06	1.9	8.9	13.4	99	3.37	A	1010	A	5.33	6.80	447
	1.5+3.5+6.0	0.93	2.16	3.71	---	2.33	6.80	9.04	0.45	1.88	3.44	2.0	8.3	15.1	99	3.62	A	940	A+	5.75	6.80	414
	1.5+4.2+4.2	1.03	2.88	2.88	---	1.98	6.80	8.10	0.40	2.12	3.01	1.8	9.3	13.2	99	3.21	A	1060	A	5.35	6.80	446
	1.5+4.2+5.0	0.95	2.67	3.18	---	2.30	6.80	8.68	0.44	2.02	3.45	1.9	8.9	15.2	99	3.37	A	1010	A	5.33	6.80	447
	2.0+2.0+2.0	2.00	2.00	2.00	---	1.98	6.00	6.51	0.42	1.64	1.89	1.8	7.2	8.3	99	3.66	A	820	A	5.53	6.00	380
	2.0+2.0+2.5	2.00	2.00	2.50	---	1.98	6.50	6.89	0.42	1.89	2.12	1.8	8.3	9.3	99	3.44	A	945	A	5.49	6.50	415
	2.0+2.0+3.5	1.81	1.81	3.18	---	1.98	6.80	7.25	0.41	2.07	2.35	1.8	9.1	10.3	99	3.29	A	1035	A	5.41	6.80	440
	2.0+2.0+4.2	1.66	1.66	3.48	---	1.98	6.80	7.46	0.41	2.07	2.50	1.8	9.1	11.0	99	3.29	A	1035	A	5.42	6.80	440
	2.0+2.0+5.0	1.51	1.51	3.78	---	1.98	6.80	7.85	0.39	2.02	2.69	1.7	8.9	11.8	99	3.37	A	1010	A	5.41	6.80	440
	2.0+2.0+6.0	1.36	1.36	4.08	---	2.33	6.80	8.11	0.44	1.83	2.64	1.9	8.0	11.6	99	3.72	A	915	A+	5.86	6.80	406
	2.0+2.5+2.5	1.94	2.43	2.43	---	1.98	6.80	7.10	0.41	2.07	2.26	1.8	9.1	9.9	99	3.29	A	1035	A	5.46	6.80	437
	2.0+2.5+3.5	1.70	2.13	2.97	---	1.98	6.80	7.59	0.39	2.07	2.59	1.7	9.1	11.4	99	3.29	A	1035	A	5.42	6.80	440
	2.0+2.5+4.2	1.56	1.95	3.29	---	1.98	6.80	7.78	0.39	2.07	2.75	1.7	9.1	12.1	99	3.29	A	1035	A	5.42	6.80	439
	2.0+2.5+5.0	1.43	1.79	3.58	---	1.98	6.80	7.92	0.39	2.02	2.74	1.7	8.9	12.0	99	3.37	A	1010	A	5.42	6.80	440
	2.0+2.5+6.0	1.30	1.62	3.88	---	2.33	6.80	8.38	0.45	1.83	2.84	2.0	8.0	12.5	99	3.72	A	915	A+	5.87	6.80	406
	2.0+3.5+3.5	1.52	2.64	2.64	---	1.98	6.80	7.91	0.40	2.07	2.85	1.8	9.1	12.5	99	3.29	A	1035	A	5.36	6.80	444
	2.0+3.5+4.2	1.40	2.45	2.95	---	1.98	6.80	8.09	0.40	2.07	3.01	1.8	9.1	13.2	99	3.29	A	1035	A	5.39	6.80	442
	2.0+3.5+5.0	1.30	2.27	3.23	---	2.30	6.80	8.41	0.44	2.02	3.17	1.9	8.9	13.9	99	3.37	A	1010	A	5.36	6.80	444
	2.0+4.2+4.2	1.30	2.75	2.75	---	1.98	6.80	8.21	0.40	2.07	3.11	1.8	9.1	13.7	99	3.29	A	1035	A	5.40	6.80	441
	2.5+2.5+2.5	2.26	2.26	2.26	---	1.98	6.78	7.38	0.41	2.07	2.45	1.8	9.1	10.8	99	3.28	A	1035	A	5.47	6.78	434
	2.5+2.5+3.5	2.00	2.00	2.80	---	1.98	6.80	7.78	0.39	2.07	2.75	1.7	9.1	12.1	99	3.29	A	1035	A	5.42	6.80	440
	2.5+2.5+4.2	1.85	1.85	3.10	---	1.98	6.80	7.96	0.39	2.07	2.90	1.7	9.1	12.7	99	3.29	A	1035	A	5.43	6.80	439
	2.5+2.5+5.0	1.70	1.70	3.40	---	2.30	6.80	8.28	0.44	2.02	3.06	1.9	8.9	13.4	99	3.37	A	1010	A	5.42	6.80	439
	2.5+2.5+6.0	1.55	1.55	3.70	---	2.44	6.80	8.57	0.44	1.83	3.00	1.9	8.0	13.2	99	3.72	A	915	A+	5.87	6.80	406
	2.5+3.5+3.5	1.78	2.51	2.51	---	2.29	6.80	8.14	0.44	2.07	3.06	1.9	9.1	13.4	99	3.29	A	1035	A	5.37	6.80	444
	2.5+3.5+4.2	1.67	2.33	2.80	---	2.29	6.80	8.26	0.44	2.07	3.17	1.9	9.1	13.9	99	3.29	A	1035	A	5.39	6.80	442
	2.5+3.5+5.0	1.55	2.16	3.09	---	2.51	6.80	8.57	0.46	1.98	3.33	2.0	8.7	14.6	99	3.43	A	990	A	5.39	6.80	442
	2.5+4.2+4.2	1.56	2.62	2.62	---	2.29	6.80	8.32	0.44	2.07	3.22	1.9	9.1	14.1	99	3.29	A	1035	A	5.41	6.80	441
	3.5+3.5+3.5	2.26	2.26	2.26	---	2.40	6.78	8.42	0.43	2.07	3.33	1.9	9.1	14.6	99	3.28	A	1035	A	5.34	6.78	445

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 11.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
3MXS68G3V1B	1.5+1.5	2.90	2.90	---	---	1.62	5.80	7.10	0.38	1.57	1.99	1.7	6.9	8.7	99	3.69	A	A	3.83	3.67	1340	0.70
	1.5+2.0	2.64	3.51	---	---	1.62	6.15	7.10	0.38	1.72	1.99	1.7	7.6	8.7	99	3.58	B	A	3.82	3.77	1381	0.69
	1.5+2.5	2.44	4.06	---	---	1.62	6.50	7.64	0.38	1.89	2.24	1.7	8.3	9.8	99	3.44	B	A	3.83	3.82	1397	0.73
	1.5+3.5	2.16	5.04	---	---	1.76	7.20	8.17	0.39	2.25	2.55	1.7	9.9	11.2	99	3.20	D	A	3.85	4.24	1542	0.80
	1.5+4.2	2.02	5.67	---	---	1.76	7.69	8.51	0.39	2.51	2.79	1.7	11.0	12.3	99	3.06	D	A	3.82	4.28	1567	0.83
	1.5+5.0	1.90	6.35	---	---	2.14	8.25	9.98	0.48	2.63	3.16	2.1	11.6	13.9	99	3.14	D	A	3.85	4.20	1526	0.81
	1.5+6.0	1.72	6.88	---	---	2.41	8.60	10.17	0.51	2.51	2.90	2.2	11.0	12.7	99	3.43	B	A	3.89	4.68	1684	0.88
	2.0+2.0	3.25	3.25	---	---	1.62	6.50	7.64	0.38	1.87	2.25	1.7	8.2	9.9	99	3.48	B	A	3.83	3.88	1420	0.74
	2.0+2.5	3.04	3.81	---	---	1.62	6.85	7.81	0.38	2.05	2.33	1.7	9.0	10.2	99	3.34	C	A	3.83	3.93	1439	0.73
	2.0+3.5	2.71	4.74	---	---	1.76	7.45	8.34	0.39	2.34	2.64	1.7	10.3	11.6	99	3.18	D	A	3.83	4.34	1589	0.83
	2.0+4.2	2.58	5.42	---	---	1.76	8.00	8.68	0.39	2.64	2.89	1.7	11.6	12.7	99	3.03	D	A	3.82	4.38	1607	0.82
	2.0+5.0	2.46	6.14	---	---	2.14	8.60	10.15	0.48	2.80	3.26	2.1	12.3	14.3	99	3.07	D	A	3.83	4.30	1572	0.85
	2.0+6.0	2.15	6.45	---	---	2.41	8.60	10.34	0.51	2.43	2.98	2.2	10.7	13.1	99	3.54	B	A	3.91	4.77	1708	0.91
	2.5+2.5	3.60	3.60	---	---	1.62	7.20	8.16	0.38	2.24	2.56	1.7	9.8	11.2	99	3.21	C	A	3.84	3.98	1452	0.77
	2.5+3.5	3.29	4.61	---	---	1.85	7.90	8.68	0.40	2.58	2.89	1.8	11.3	12.7	99	3.06	D	A	3.82	4.39	1610	0.83
	2.5+4.2	3.10	5.20	---	---	1.85	8.30	8.93	0.40	2.80	3.07	1.8	12.3	13.5	99	2.96	D	A	3.85	4.42	1606	0.85
	2.5+5.0	2.87	5.73	---	---	2.23	8.60	10.27	0.49	2.80	3.36	2.2	12.3	14.8	99	3.07	D	A	3.83	4.34	1589	0.83
	2.5+6.0	2.53	6.07	---	---	2.50	8.60	10.46	0.53	2.43	3.01	2.3	10.7	13.2	99	3.54	B	A	3.90	4.81	1725	0.89
	3.5+3.5	4.30	4.30	---	---	2.13	8.60	9.02	0.45	2.93	3.11	2.0	12.9	13.7	99	2.94	D	A	3.90	4.77	1712	0.91
	3.5+4.2	3.91	4.69	---	---	2.13	8.60	9.11	0.45	2.92	3.16	2.0	12.8	13.9	99	2.95	D	A	3.91	4.80	1721	0.93
	3.5+5.0	3.54	5.06	---	---	2.51	8.60	10.48	0.54	2.79	3.40	2.4	12.3	14.9	99	3.08	D	A	3.90	4.73	1697	0.92
	3.5+6.0	3.17	5.43	---	---	2.69	8.60	10.59	0.55	2.42	3.00	2.4	10.6	13.2	99	3.55	B	A	3.99	5.17	1813	1.01
	4.2+4.2	4.30	4.30	---	---	2.13	8.60	9.19	0.45	2.92	3.20	2.0	12.8	14.1	99	2.95	D	A	3.90	4.84	1736	0.92
	4.2+5.0	3.93	4.67	---	---	2.51	8.60	10.49	0.54	2.79	3.47	2.4	12.3	15.2	99	3.08	D	A	3.90	4.76	1709	0.90
	4.2+6.0	3.54	5.06	---	---	2.69	8.60	10.60	0.54	2.42	3.03	2.4	10.6	13.3	99	3.55	B	A+	4.01	5.20	1814	1.00
	5.0+5.0	4.30	4.30	---	---	2.88	8.60	10.67	0.63	2.70	3.38	2.8	11.9	14.8	99	3.19	D	A	3.88	4.69	1692	0.89
	5.0+6.0	3.91	4.69	---	---	3.08	8.60	10.66	0.64	2.39	2.96	2.8	10.5	13.0	99	3.60	B	A	3.99	5.13	1800	0.98
	1.5+1.5+1.5	2.28	2.28	2.28	---	1.97	6.83	9.37	0.44	1.63	2.38	1.9	7.2	10.5	99	4.19	A	A	3.86	4.75	1725	0.89
	1.5+1.5+2.0	2.15	2.15	2.87	---	1.97	7.18	9.37	0.44	1.77	2.38	1.9	7.8	10.5	99	4.06	A	A	3.89	4.84	1742	0.92
	1.5+1.5+2.5	2.06	2.06	3.43	---	2.06	7.54	9.96	0.45	1.89	2.65	2.0	8.3	11.6	99	3.99	A	A	3.90	4.88	1751	0.95
	1.5+1.5+3.5	1.90	1.90	4.44	---	2.26	8.25	10.05	0.47	2.23	2.80	2.1	9.8	12.3	99	3.70	A	A	3.96	5.23	1849	0.98
	1.5+1.5+4.2	1.79	1.79	5.02	---	2.26	8.60	10.06	0.47	2.38	2.79	2.1	10.5	12.3	99	3.61	A	A	3.98	5.26	1851	1.00
	1.5+1.5+5.0	1.61	1.61	5.38	---	2.66	8.60	10.23	0.58	2.38	2.87	2.5	10.5	12.6	99	3.61	A	A	3.96	5.19	1834	0.99
	1.5+1.5+6.0	1.43	1.43	5.73	---	2.87	8.60	10.44	0.58	2.16	2.63	2.5	9.5	11.6	99	3.98	A	A+	4.09	5.59	1913	1.08
	1.5+2.0+2.0	2.06	2.74	2.74	---	1.97	7.54	10.04	0.44	1.91	2.70	1.9	8.4	11.9	99	3.95	A	A	3.90	4.93	1771	0.95
	1.5+2.0+2.5	1.97	2.63	3.29	---	2.06	7.89	10.04	0.45	2.03	2.69	2.0	8.9	11.8	99	3.89	A	A	3.93	4.97	1772	0.94
	1.5+2.0+3.5	1.84	2.46	4.30	---	2.26	8.60	10.05	0.47	2.38	2.80	2.1	10.5	12.3	99	3.61	A	A+	4.00	5.31	1868	1.00
	1.5+2.0+4.2	1.68	2.23	4.69	---	2.26	8.60	10.06	0.47	2.38	2.79	2.1	10.5	12.3	99	3.61	A	A	3.98	5.34	1877	1.03
	1.5+2.0+5.0	1.52	2.02	5.06	---	2.66	8.60	10.46	0.58	2.38	2.87	2.5	10.5	12.6	99	3.61	A	A	3.99	5.27	1850	1.01
	1.5+2.0+6.0	1.36	1.81	5.43	---	2.87	8.60	10.55	0.58	2.16	2.63	2.5	9.5	11.6	99	3.98	A	A+	4.10	5.66	1934	1.10
	1.5+2.5+2.5	1.90	3.17	3.17	---	2.16	8.25	10.15	0.48	2.21	2.69	2.1	9.7	11.8	99	3.73	A	A	3.94	5.01	1780	0.97
	1.5+2.5+3.5	1.72	2.87	4.01	---	2.35	8.60	10.17	0.50	2.38	2.79	2.2	10.5	12.3	99	3.61	A	A	3.99	5.35	1880	1.04
	1.5+2.5+4.2	1.57	2.62	4.40	---	2.36	8.60	10.17	0.50	2.38	2.79	2.2	10.5	12.3	99	3.61	A	A+	4.02	5.38	1876	1.02
	1.5+2.5+5.0	1.43	2.39	4.78	---	2.75	8.60	10.58	0.60	2.38	2.87	2.6	10.5	12.6	99	3.61	A	A	3.98	5.31	1868	1.00
	1.5+2.5+6.0	1.29	2.15	5.16	---	2.96	8.60	10.44	0.61	2.16	2.62	2.7	9.5	11.5	99	3.98	A	A+	4.10	5.69	1945	1.08
	1.5+3.5+3.5	1.52	3.54	3.54	---	2.64	8.60	10.18	0.58	2.38	2.79	2.5	10.5	12.3	99	3.61	A	A+	4.09	5.66	1937	1.10
	1.5+3.5+4.2	1.40	3.27	3.93	---	2.64	8.60	10.18	0.58	2.37	2.78	2.5	10.4	12.2	99	3.63	A	A+	4.08	5.69	1951	1.09
	1.5+3.5+5.0	1.29	3.01	4.30	---	2.94	8.60	10.59	0.66	2.37	2.86	2.9	10.4	12.6	99	3.63	A	A+	4.09	5.62	1926	1.06
	1.5+3.5+6.0	1.17	2.74	4.69	---	2.97	8.60	10.46	0.61	2.15	2.62	2.7	9.4	11.5	99	4.00	A	A+	4.17	5.82	1954	1.11
	1.5+4.2+4.2	1.30	3.65	3.65	---	2.64	8.60	10.19	0.58	2.37	2.78	2.5	10.4	12.2	99	3.63	A	A+	4.10	5.71	1952	1.10
	1.5+4.2+5.0	1.21	3.38	4.02	---	2.85	8.60	10.48	0.63	2.37	2.86	2.8	10.4	12.6	99	3.63	A	A+	4.09	5.65	1935	1.09
	2.0+2.0+2.0	2.63	2.63	2.63	---	1.97	7.89	10.04	0.44	2.05	2.70	1.9	9.0	11.9	99	3.85	A	A	3.94	5.01	1780	0.97
	2.0+2.0+2.5	2.54	2.54	3.17	---	2.06	8.25	10.12	0.45	2.18	2.74	2.0	9.6	12.0	99	3.78	A	A	3.94	5.05	1794	0.96
	2.0+2.0+3.5	2.29	2.29	4.02	---	2.26	8.60	10.22	0.47	2.34	2.88	2.1	10.3	12.6	99	3.68	A	A+	4.02	5.39	1879	1.03
	2.0+2.0+4.2	2.10	2.10	4.40	---	2.26	8.60	10.22	0.47	2.34	2.88	2.1	10.3	12.6	99	3.68	A	A+	4.02	5.42	1888	1.05
	2.0+2.0+5.0	1.91	1.91	4.78	---	2.66	8.60	10.40	0.58	2.34	2.96	2.5	10.3	13.0	99	3.68	A	A	3.99	5.35	1880	1.04
	2.0+2.0+6.0	1.72	1.72	5.16	---	2.87	8.60	10.53	0.58	2.12	2.67	2.5	9.3	11.7	99	4.06	A	A+	4.09	5.73	1960	1.08
	2.0+2.5+2.5	2.46	3.07	3.07	---	2.16	8.60	10.13	0.46	2.35	2.84	2.0	10.3	12.5	99	3.66	A	A	3.94	5.09	1807	0.99
	2.0+2.5+3.5	2.15	2.69	3.76	---	2.35	8.60	10.22	0.49	2.34	2.88	2.2	10.3	12.6	99	3.68	A	A+	4.02	5.42	1888	1.05
	2.0+2.5+4.2	1.98	2.47	4.15	---	2.36	8.60	10.23	0.49	2.34	2.87	2.2	10.3	12.6	99	3.68	A	A+	4.02	5.45	1899	1.04
	2.0+2.5+5.0	1.81	2.26	4.53	---	2.75	8.60	10.63	0.60	2.32	2.99	2.6	10.2	13.1	99	3.71	A	A+	4.02	5.39	1879	1.03
	2.0+2.5+6.0	1.64	2.05	4.91	---	2.96	8.60	10.64	0.60	2.10	2.64	2.6	9.2	11.6	99	4.10	A	A+	4.13	5.76	1952	1.11
	2.0+3.5+3.5	1.92	3.34	3.34	---	2.64	8.60	10.35	0.55	2.31	2.93	2.4	10.1	12.9	99	3.72	A	A+	4.09	5.73	1963	1.08
	2.0+3.5+4.2	1.77	3.10	3.72	---	2.64	8.60	10.35	0.55	2.31	2.92	2.4	10.1	12.8	99	3.72	A	A+	4.12	5.76	1956	1.11
	2.0+3.5+5.0	1.64	2.87	4.09	---	2.94	8.60	10.68	0.62	2.29	3.06	2.7	10.1	13.4	99	3.76	A	A+	4.09	5.70	1951	1.09
	2.0+4.2+4.2	1.65	3.47	3.47	---	2.64	8.60	10.36	0.55	2.31	2.92	2.4	10.1	12.8	99	3.72	A	A+	4.12	5.78	1962	1.13
	2.5+2.5+2.5	2.86	2.86	2.86	---	2.26	8.58	10.24	0.48	2.35	2.87	2.1	10.3	12.6	99	3.65	A	A	3.97	5.13	1809	0.98
	2.5+2.5+3.5	2.53	2.53	3.54	---	2.45	8.60	10.45	0.51	2.34	2.96	2.2	10.3	13.0	99	3.68	A	A+	4.02	5.46	1902	1.05
	2.5+2.5+4.2	2.34	2.34	3.93	---	2.45	8.60	10.46	0.51	2.34	2.96	2.2	10.3	13.0	99	3.68	A	A+	4.02	5.49	1912	1.03
	2.5+2.5+5.0	2.15	2.15	4.30	---	2.85	8.60	10.64	0.62	2.29	3.02	2.7	10.1	13.3	99	3.76	A	A+	4.03	5.43	1889	1.06
	2.5+2.5+6.0	1.95	1.95	4.70	---	3.06	8.60	10.65	0.62	2.08	2.64	2.7	9.1	11.6	99	4.13	A	A+	4.12	5.79	1966	1.10
	2.5+3.5+3.5	2.26	3.17	3.17	---	2.73	8.60	10.58	0.56	2.31	2.96	2.5	10.1	13.0	99	3.72	A	A+	4.12	5.76	1956	1.11
	2.5+3.5+4.2	2.11	2.95	3.54	---	2.74	8.60	10.59	0.56	2.31	2.95	2.5	10.1	13.0	99	3.72	A	A+	4.12	5.79	1970	1.10
	2.5+3.5+5.0	1.95	2.74	3.91	---	3.13	8.60	10.65	0.64	2.29	2.98	2.8	10.1	13.1	99	3.76	A	A+	4.09	5.73	1963	1.08
	2.5+4.2+4.2	1.97	3.31	3.31	---	2.74	8.60	10.59	0.56	2.31	2.95	2.5	10.1	13.0	99	3.72	A	A+	4.13	5.79	1961	1.13
	3.5+3.5+3.5	2.86	2.86	2.86	---	2.92	8.58	10.63	0.61	2.29	3.03	2.7	10.1	13.3	99	3.75	A	A+	4.22	5.83	1933	1.12

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 11.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
4MXS68F3V1B	1.5+1.5	1.50	1.50	---	---	1.97	3.00	4.70	0.43	0.65	1.29	1.9	2.9	5.7	99	4.62	A	325	B	4.98	3.00	211
	1.5+2.0	1.50	2.00	---	---	1.97	3.50	4.86	0.43	0.80	1.37	1.9	3.5	6.0	99	4.38	A	400	B	5.09	3.50	241
	1.5+2.5	1.50	2.50	---	---	1.97	4.00	5.18	0.43	0.99	1.53	1.9	4.3	6.7	99	4.04	A	495	A	5.16	4.00	272
	1.5+3.5	1.50	3.50	---	---	1.97	5.00	6.05	0.42	1.39	2.06	1.8	6.1	9.0	99	3.60	A	695	A	5.14	5.00	341
	1.5+4.2	1.50	4.20	---	---	1.97	5.70	6.26	0.42	1.79	2.20	1.8	7.9	9.7	99	3.18	B	895	A	5.16	5.70	387
	1.5+5.0	1.50	5.00	---	---	1.97	6.50	6.94	0.41	2.22	2.51	1.8	9.7	11.0	99	2.93	C	1110	B	4.94	6.50	461
	1.5+6.0	1.36	5.44	---	---	1.98	6.80	7.44	0.40	2.26	2.65	1.8	9.9	11.6	99	3.01	B	1130	A	5.43	6.80	439
	2.0+2.0	2.00	2.00	---	---	1.97	4.00	5.02	0.43	1.00	1.45	1.9	4.4	6.4	99	4.00	A	500	A	5.18	4.00	271
	2.0+2.5	2.00	2.50	---	---	1.97	4.50	5.33	0.43	1.20	1.61	1.9	5.3	7.1	99	3.75	A	600	A	5.22	4.50	302
	2.0+3.5	2.00	3.50	---	---	1.97	5.50	6.18	0.42	1.66	2.15	1.8	7.3	9.4	99	3.31	A	830	A	5.23	5.50	368
	2.0+4.2	2.00	4.20	---	---	1.97	6.20	6.38	0.42	2.09	2.30	1.8	9.2	10.1	99	2.97	C	1045	B	5.08	6.20	428
	2.0+5.0	1.94	4.86	---	---	1.97	6.80	7.12	0.41	2.41	2.65	1.8	10.6	11.6	99	2.82	C	1205	B	4.93	6.80	483
	2.0+6.0	1.70	5.10	---	---	1.98	6.80	7.56	0.40	2.21	2.75	1.8	9.7	12.1	99	3.08	B	1105	A	5.49	6.80	434
	2.5+2.5	2.50	2.50	---	---	1.97	5.00	5.98	0.45	1.46	2.00	2.0	6.4	8.8	99	3.42	A	730	A	5.26	5.00	333
	2.5+3.5	2.50	3.50	---	---	1.97	6.00	6.44	0.43	2.06	2.37	1.9	9.0	10.4	99	2.91	C	1030	A	5.12	6.00	411
	2.5+4.2	2.50	4.20	---	---	1.97	6.70	6.81	0.43	2.54	2.67	1.9	11.2	11.7	99	2.64	D	1270	B	4.96	6.70	473
	2.5+5.0	2.27	4.53	---	---	1.97	6.80	7.23	0.40	2.41	2.75	1.8	10.6	12.1	99	2.82	C	1205	B	4.93	6.80	483
	2.5+6.0	2.00	4.80	---	---	1.98	6.80	7.56	0.38	2.21	2.75	1.7	9.7	12.1	99	3.08	B	1105	A	5.49	6.80	434
	3.5+3.5	3.40	3.40	---	---	1.97	6.80	6.99	0.41	2.51	2.66	1.8	11.0	11.7	99	2.71	D	1255	B	4.91	6.80	485
	3.5+4.2	3.09	3.71	---	---	1.97	6.80	7.10	0.41	2.51	2.76	1.8	11.0	12.1	99	2.71	D	1255	B	4.95	6.80	481
	3.5+5.0	2.80	4.00	---	---	1.97	6.80	7.61	0.38	2.41	3.12	1.7	10.6	13.7	99	2.82	C	1205	B	4.91	6.80	485
	3.5+6.0	2.51	4.29	---	---	2.28	6.80	7.91	0.43	2.21	3.06	1.9	9.7	13.4	99	3.08	B	1105	A	5.45	6.80	437
	4.2+4.2	3.40	3.40	---	---	1.97	6.80	7.00	0.41	2.51	2.66	1.8	11.0	11.7	99	2.71	D	1255	B	4.96	6.80	480
	4.2+5.0	3.10	3.70	---	---	1.97	6.80	7.62	0.38	2.41	3.12	1.7	10.6	13.7	99	2.82	C	1205	B	4.96	6.80	481
	4.2+6.0	2.80	4.00	---	---	2.28	6.80	7.92	0.43	2.21	3.06	1.9	9.7	13.4	99	3.08	B	1105	A	5.46	6.80	436
	5.0+5.0	3.40	3.40	---	---	2.36	6.80	8.06	0.47	2.31	3.35	2.1	10.1	14.7	99	2.94	C	1155	B	4.92	6.80	485
	5.0+6.0	3.09	3.71	---	---	2.49	6.80	8.28	0.48	2.12	3.28	2.1	9.3	14.4	99	3.21	A	1060	A	5.45	6.80	437
	1.5+1.5+1.5	1.50	1.50	1.50	---	1.98	4.50	6.27	0.42	1.03	1.76	1.8	4.5	7.7	99	4.37	A	515	A	5.27	4.50	300
	1.5+1.5+2.0	1.50	1.50	2.00	---	1.98	5.00	6.43	0.42	1.21	1.85	1.8	5.3	8.1	99	4.13	A	605	A	5.37	5.00	327
	1.5+1.5+2.5	1.50	1.50	2.50	---	1.98	5.50	6.59	0.42	1.44	1.94	1.8	6.3	8.5	99	3.82	A	720	A	5.42	5.50	355
	1.5+1.5+3.5	1.50	1.50	3.50	---	1.98	6.50	6.97	0.41	1.94	2.16	1.8	8.5	9.5	99	3.35	A	970	A	5.33	6.50	427
	1.5+1.5+4.2	1.42	1.42	3.97	---	1.98	6.80	7.19	0.41	2.12	2.30	1.8	9.3	10.1	99	3.21	A	1060	A	5.31	6.80	449
	1.5+1.5+5.0	1.28	1.28	4.25	---	1.98	6.80	7.59	0.39	2.02	2.49	1.7	8.9	10.9	99	3.37	A	1010	A	5.30	6.80	450
	1.5+1.5+6.0	1.13	1.13	4.53	---	2.33	6.80	7.83	0.44	1.88	2.44	1.9	8.3	10.7	99	3.62	A	940	A+	5.75	6.80	415
	1.5+2.0+2.0	1.50	2.00	2.00	---	1.98	5.50	6.35	0.42	1.44	1.81	1.8	6.3	7.9	99	3.82	A	720	A	5.46	5.50	353
	1.5+2.0+2.5	1.50	2.00	2.50	---	1.98	6.00	6.74	0.42	1.68	2.03	1.8	7.4	8.9	99	3.57	A	840	A	5.51	6.00	382
	1.5+2.0+3.5	1.46	1.94	3.40	---	1.98	6.80	7.11	0.41	2.12	2.26	1.8	9.3	9.9	99	3.21	A	1060	A	5.34	6.80	446
	1.5+2.0+4.2	1.32	1.77	3.71	---	1.98	6.80	7.32	0.41	2.12	2.40	1.8	9.3	10.5	99	3.21	A	1060	A	5.38	6.80	443
	1.5+2.0+5.0	1.20	1.60	4.00	---	1.98	6.80	7.72	0.39	2.02	2.59	1.7	8.9	11.4	99	3.37	A	1010	A	5.35	6.80	446
	1.5+2.0+6.0	1.07	1.43	4.29	---	2.33	6.80	7.97	0.44	1.88	2.54	1.9	8.3	11.2	99	3.62	A	940	A+	5.81	6.80	410
	1.5+2.5+2.5	1.50	2.50	2.50	---	1.98	6.50	6.96	0.41	1.94	2.16	1.8	8.5	9.5	99	3.35	A	970	A	5.45	6.50	418
	1.5+2.5+3.5	1.36	2.27	3.17	---	1.98	6.80	7.45	0.39	2.12	2.50	1.7	9.3	11.0	99	3.21	A	1060	A	5.38	6.80	443
	1.5+2.5+4.2	1.24	2.07	3.48	---	1.98	6.80	7.66	0.39	2.12	2.64	1.7	9.3	11.6	99	3.21	A	1060	A	5.38	6.80	443
	1.5+2.5+5.0	1.13	1.89	3.78	---	1.98	6.80	7.79	0.39	2.02	2.64	1.7	8.9	11.6	99	3.37	A	1010	A	5.38	6.80	443
	1.5+2.5+6.0	1.02	1.70	4.08	---	2.33	6.80	8.25	0.45	1.88	2.74	2.0	8.3	12.0	99	3.62	A	940	A+	5.81	6.80	410
	1.5+3.5+3.5	1.20	2.80	2.80	---	1.98	6.80	7.78	0.40	2.12	2.75	1.8	9.3	12.1	99	3.21	A	1060	A	5.32	6.80	448
	1.5+3.5+4.2	1.11	2.59	3.10	---	1.98	6.80	7.97	0.40	2.12	2.90	1.8	9.3	12.7	99	3.21	A	1060	A	5.33	6.80	447
	1.5+3.5+5.0	1.02	2.38	3.40	---	1.98	6.80	8.29	0.36	2.02	3.06	1.6	8.9	13.4	99	3.37	A	1010	A	5.33	6.80	447
	1.5+3.5+6.0	0.93	2.16	3.71	---	2.33	6.80	8.39	0.45	1.88	2.84	2.0	8.3	12.5	99	3.62	A	940	A+	5.75	6.80	414
	1.5+4.2+4.2	1.03	2.88	2.88	---	1.98	6.80	8.10	0.40	2.12	3.01	1.8	9.3	13.2	99	3.21	A	1060	A	5.35	6.80	446
	1.5+4.2+5.0	0.95	2.67	3.18	---	1.98	6.80	8.36	0.36	2.02	3.11	1.6	8.9	13.7	99	3.37	A	1010	A	5.33	6.80	447
	2.0+2.0+2.0	2.00	2.00	2.00	---	1.98	6.00	6.51	0.42	1.64	1.89	1.8	7.2	8.3	99	3.66	A	820	A	5.53	6.00	380
	2.0+2.0+2.5	2.00	2.00	2.50	---	1.98	6.50	6.89	0.42	1.89	2.12	1.8	8.3	9.3	99	3.44	A	945	A	5.49	6.50	415
	2.0+2.0+3.5	1.81	1.81	3.18	---	1.98	6.80	7.25	0.41	2.07	2.35	1.8	9.1	10.3	99	3.29	A	1035	A	5.41	6.80	440
	2.0+2.0+4.2	1.66	1.66	3.48	---	1.98	6.80	7.46	0.41	2.07	2.50	1.8	9.1	11.0	99	3.29	A	1035	A	5.42	6.80	440
	2.0+2.0+5.0	1.51	1.51	3.78	---	1.98	6.80	7.85	0.39	2.02	2.69	1.7	8.9	11.8	99	3.37	A	1010	A	5.41	6.80	440
	2.0+2.0+6.0	1.36	1.36	4.08	---	2.33	6.80	8.11	0.44	1.83	2.64	1.9	8.0	11.6	99	3.72	A	915	A+	5.86	6.80	406
	2.0+2.5+2.5	1.94	2.43	2.43	---	1.98	6.80	7.10	0.41	2.07	2.26	1.8	9.1	9.9	99	3.29	A	1035	A	5.46	6.80	437
	2.0+2.5+3.5	1.70	2.13	2.97	---	1.98	6.80	7.59	0.39	2.07	2.59	1.7	9.1	11.4	99	3.29	A	1035	A	5.42	6.80	440
	2.0+2.5+4.2	1.56	1.95	3.29	---	1.98	6.80	7.78	0.39	2.07	2.75	1.7	9.1	12.1	99	3.29	A	1035	A	5.42	6.80	439
	2.0+2.5+5.0	1.43	1.79	3.58	---	1.98	6.80	7.92	0.39	2.02	2.74	1.7	8.9	12.0	99	3.37	A	1010	A	5.42	6.80	440
	2.0+2.5+6.0	1.30	1.62	3.88	---	2.33	6.80	8.38	0.45	1.83	2.84	2.0	8.0	12.5	99	3.72	A	915	A+	5.87	6.80	406
	2.0+3.5+3.5	1.52	2.64	2.64	---	1.98	6.80	7.91	0.40	2.07	2.85	1.8	9.1	12.5	99	3.29	A	1035	A	5.36	6.80	444
	2.0+3.5+4.2	1.40	2.45	2.94	---	1.98	6.80	8.09	0.40	2.07	3.01	1.8	9.1	13.2	99	3.29	A	1035	A	5.39	6.80	442
	2.0+3.5+5.0	1.30	2.27	3.23	---	2.30	6.80	8.41	0.44	2.02	3.17	1.9	8.9	13.9	99	3.37	A	1010	A	5.36	6.80	444
	2.0+4.2+4.2	1.30	2.75	2.75	---	1.98	6.80	8.21	0.40	2.07	3.11	1.8	9.1	13.7	99	3.29	A	1035	A	5.40	6.80	441
	2.5+2.5+2.5	2.26	2.26	2.26	---	1.98	6.78	7.38	0.41	2.07	2.45	1.8	9.1	10.8	99	3.28	A	1035	A	5.47	6.78	434
	2.5+2.5+3.5	2.00	2.00	2.80	---	1.98	6.80	7.78	0.39	2.07	2.75	1.7	9.1	12.1	99	3.29	A	1035	A	5.42	6.80	440
	2.5+2.5+4.2	1.85	1.85	3.10	---	1.98	6.80	7.96	0.39	2.07	2.90	1.7	9.1	12.7	99	3.29	A	1035	A	5.43	6.80	439
	2.5+2.5+5.0	1.70	1.70	3.40	---	2.30	6.80	8.28	0.44	2.02	3.06	1.9	8.9	13.4	99	3.37	A	1010	A	5.42	6.80	439
	2.5+2.5+6.0	1.55	1.55	3.70	---	2.44	6.80	8.57	0.44	1.83	3.00	1.9	8.0	13.2	99	3.72	A	915	A+	5.87	6.80	406
	2.5+3.5+3.5	1.78	2.51	2.51	---	2.29	6.80	8.14	0.44	2.07	3.06	1.9	9.1	13.4	99	3.29	A	1035	A	5.37	6.80	444
	2.5+3.5+4.2	1.67	2.33	2.80	---	2.29	6.80	8.26	0.44	2.07	3.17	1.9	9.1	13.9	99	3.29	A	1035	A	5.39	6.80	442
	2.5+3.5+5.0	1.55	2.16	3.09	---	2.51	6.80	8.57	0.46	1.98	3.33	2.0	8.7	14.6	99	3.43	A	990	A	5.39	6.80	442
	2.5+4.2+4.2	1.56	2.62	2.62	---	2.29	6.80	8.32	0.44	2.07	3.22	1.9	9.1	14.1	99	3.29	A	1035	A	5.41	6.80	441
	3.5+3.5+3.5	2.26	2.26	2.26	---	2.40	6.78	8.42	0.43	2.07	3.33	1.9	9.1	14.6	99	3.28	A	1035	A	5.34	6.78	445
	1.5+1.5+1.5+1.5	1.50	1.50	1.50	1.50	1.99	6.00	6.95	0.41	1.42	1.83	1.8	6.2	8.0	99	4.23	A	710	A+	5.60	6.00	376
	1.5+1.5+1.5+2.0	1.50	1.50	1.50	2.00	1.99	6.50	7.13	0.41	1.62	1.91	1.8	7.1	8.4	99	4.01	A	810	A+	5.64	6.50	404
	1.5+1.5+1.5+2.5	1.46	1.46	1.46	2.43	1.99	6.80	7.30	0.39	1.73	2.00	1.7	7.6	8.8	99	3.93	A	865	A+	5.63	6.80	423
	1.5+1.5+1.5+3.5	1.28	1.28	1.28	2.98	1.99	6.80	7.72	0.40	1.71	2.24	1.8	7.5	9.8	99	3.98	A	855	A	5.56	6.80	428
	1.5+1.5+1.5+4.2	1.17	1.17	1.17	3.28	1.99	6.80	7.88	0.40	1.71	2.33	1.8	7.5	10.2	99	3.98	A	855	A	5.57	6.80	428
	1.5+1.5+1.5+5.0	1.07	1.07	1.07	3.58	2.47	6.80	8.31	0.46	1.71	2.61	2.0	7.5	11.5	99	3.98	A	855	A	5.57	6.80	428
	1.5+1.5+1.5+6.0	0.97	0.97	0.97	3.89	2.50	6.80	8.22	0.43	1.57	2.34	1.9	6.9	10.3	99	4.33	A	785	A+	5.98	6.80	398

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 11.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
4MXS68F3V1B	1.5+1.5+2.0+2.0	1.46	1.46	1.94	1.94	1.99	6.80	7.30	0.41	1.75	2.00	1.8	7.7	8.8	99	3.89	A	875	A+	5.68	6.80	420
	1.5+1.5+2.0+2.5	1.36	1.36	1.81	2.27	1.99	6.80	7.47	0.39	1.73	2.10	1.7	7.6	9.2	99	3.93	A	865	A+	5.69	6.80	419
	1.5+1.5+2.0+3.5	1.20	1.20	1.60	2.80	1.99	6.80	7.87	0.40	1.71	2.33	1.8	7.5	10.2	99	3.98	A	855	A+	5.62	6.80	424
	1.5+1.5+2.0+4.2	1.11	1.11	1.48	3.10	1.99	6.80	8.03	0.40	1.71	2.43	1.8	7.5	10.7	99	3.98	A	855	A+	5.63	6.80	423
	1.5+1.5+2.0+5.0	1.02	1.02	1.36	3.40	2.47	6.80	8.46	0.46	1.71	2.71	2.0	7.5	11.9	99	3.98	A	855	A+	5.62	6.80	424
	1.5+1.5+2.0+6.0	0.93	0.93	1.24	3.71	2.50	6.80	8.39	0.43	1.57	2.45	1.9	6.9	10.8	99	4.33	A	785	A+	6.02	6.80	396
	1.5+1.5+2.5+2.5	1.28	1.28	2.13	2.13	1.99	6.80	7.55	0.39	1.73	2.14	1.7	7.6	9.4	99	3.93	A	865	A+	5.69	6.80	419
	1.5+1.5+2.5+3.5	1.13	1.13	1.89	2.64	2.34	6.80	7.95	0.50	1.71	2.38	2.2	7.5	10.5	99	3.98	A	855	A+	5.63	6.80	423
	1.5+1.5+2.5+4.2	1.05	1.05	1.75	2.94	2.34	6.80	8.11	0.50	1.71	2.48	2.2	7.5	10.9	99	3.98	A	855	A+	5.63	6.80	423
	1.5+1.5+2.5+5.0	0.97	0.97	1.62	3.24	2.47	6.80	8.53	0.46	1.71	2.76	2.0	7.5	12.1	99	3.98	A	855	A+	5.63	6.80	423
	1.5+1.5+3.5+3.5	1.02	1.02	2.38	2.38	2.34	6.80	8.40	0.50	1.71	2.68	2.2	7.5	11.8	99	3.98	A	855	A	5.58	6.80	427
	1.5+1.5+3.5+4.2	0.95	0.95	2.22	2.67	2.46	6.80	8.48	0.54	1.71	2.74	2.4	7.5	12.0	99	3.98	A	855	A	5.59	6.80	427
	1.5+2.0+2.0+2.0	1.36	1.81	1.81	1.81	1.99	6.80	7.46	0.41	1.75	2.10	1.8	7.7	9.2	99	3.89	A	875	A+	5.72	6.80	417
	1.5+2.0+2.0+2.5	1.28	1.70	1.70	2.13	1.99	6.80	7.63	0.39	1.73	2.19	1.7	7.6	9.6	99	3.93	A	865	A+	5.73	6.80	416
	1.5+2.0+2.0+3.5	1.13	1.51	1.51	2.64	2.34	6.80	8.02	0.50	1.71	2.43	2.2	7.5	10.7	99	3.98	A	855	A+	5.66	6.80	421
	1.5+2.0+2.0+4.2	1.05	1.40	1.40	2.94	2.34	6.80	8.18	0.50	1.71	2.53	2.2	7.5	11.1	99	3.98	A	855	A+	5.67	6.80	420
	1.5+2.0+2.0+5.0	0.97	1.30	1.30	3.24	2.47	6.80	8.60	0.46	1.71	2.82	2.0	7.5	12.4	99	3.98	A	855	A+	5.66	6.80	421
	1.5+2.0+2.5+2.5	1.20	1.60	2.00	2.00	1.99	6.80	7.71	0.39	1.73	2.24	1.7	7.6	9.8	99	3.93	A	865	A+	5.73	6.80	416
	1.5+2.0+2.5+3.5	1.07	1.43	1.79	2.51	2.34	6.80	8.10	0.50	1.71	2.48	2.2	7.5	10.9	99	3.98	A	855	A+	5.67	6.80	420
	1.5+2.0+2.5+4.2	1.00	1.33	1.67	2.80	2.34	6.80	8.26	0.50	1.71	2.58	2.2	7.5	11.3	99	3.98	A	855	A+	5.67	6.80	420
	1.5+2.0+2.5+5.0	0.93	1.24	1.55	3.09	2.47	6.80	8.68	0.46	1.71	2.87	2.0	7.5	12.6	99	3.98	A	855	A+	5.67	6.80	420
	1.5+2.0+3.5+3.5	0.97	1.30	2.27	2.27	2.00	6.80	8.47	0.40	1.71	2.74	1.8	7.5	12.0	99	3.98	A	855	A+	5.60	6.80	425
	1.5+2.5+2.5+2.5	1.13	1.89	1.89	1.89	1.99	6.80	8.02	0.36	1.71	2.43	1.6	7.5	10.7	99	3.98	A	855	A+	5.73	6.80	416
	1.5+2.5+2.5+3.5	1.02	1.70	1.70	2.38	2.34	6.80	8.32	0.43	1.70	2.63	1.9	7.5	11.6	99	4.00	A	850	A+	5.67	6.80	420
	1.5+2.5+2.5+4.2	0.95	1.59	1.59	2.67	2.34	6.80	8.33	0.45	1.73	2.63	2.0	7.6	11.6	99	3.93	A	865	A+	5.67	6.80	420
	1.5+2.5+3.5+3.5	0.93	1.55	2.16	2.16	2.34	6.80	8.54	0.43	1.70	2.79	1.9	7.5	12.3	99	4.00	A	850	A+	5.62	6.80	424
	2.0+2.0+2.0+2.0	1.70	1.70	1.70	1.70	1.99	6.80	7.63	0.41	1.75	2.19	1.8	7.7	9.6	99	3.89	A	875	A+	5.75	6.80	415
	2.0+2.0+2.0+2.5	1.60	1.60	1.60	2.00	1.99	6.80	7.79	0.39	1.73	2.29	1.7	7.6	10.1	99	3.93	A	865	A+	5.75	6.80	414
	2.0+2.0+2.0+3.5	1.43	1.43	1.43	2.51	1.99	6.80	8.17	0.40	1.71	2.53	1.8	7.5	11.1	99	3.98	A	855	A+	5.70	6.80	418
	2.0+2.0+2.0+4.2	1.33	1.33	1.33	2.81	1.99	6.80	8.32	0.40	1.71	2.63	1.8	7.5	11.6	99	3.98	A	855	A+	5.73	6.80	416
	2.0+2.0+2.0+5.0	1.24	1.24	1.24	3.08	2.47	6.80	8.74	0.46	1.67	2.93	2.0	7.3	12.9	99	4.07	A	835	A+	5.70	6.80	418
	2.0+2.0+2.5+2.5	1.51	1.51	1.89	1.89	1.99	6.80	7.94	0.40	1.75	2.38	1.8	7.7	10.5	99	3.89	A	875	A+	5.77	6.80	413
	2.0+2.0+2.5+3.5	1.36	1.36	1.70	2.38	2.34	6.80	8.32	0.45	1.73	2.63	2.0	7.6	11.6	99	3.93	A	865	A+	5.71	6.80	418
	2.0+2.0+2.5+4.2	1.27	1.27	1.59	2.67	2.34	6.80	8.47	0.45	1.73	2.74	2.0	7.6	12.0	99	3.93	A	865	A+	5.73	6.80	416
	2.0+2.0+3.5+3.5	1.24	1.24	2.16	2.16	2.46	6.80	8.61	0.45	1.71	2.84	2.0	7.5	12.5	99	3.98	A	855	A+	5.66	6.80	421
	2.0+2.5+2.5+2.5	1.43	1.79	1.79	1.79	1.99	6.80	8.17	0.40	1.75	2.53	1.8	7.7	11.1	99	3.89	A	875	A+	5.77	6.80	413
	2.0+2.5+2.5+3.5	1.30	1.62	1.62	2.26	2.34	6.80	8.46	0.45	1.73	2.74	2.0	7.6	12.0	99	3.93	A	865	A+	5.73	6.80	416
	2.5+2.5+2.5+2.5	1.70	1.70	1.70	1.70	2.34	6.80	8.39	0.46	1.71	2.68	2.0	7.5	11.8	99	3.98	A	855	A+	5.77	6.80	413
	2.5+2.5+2.5+3.5	1.55	1.55	1.55	2.15	2.46	6.80	8.73	0.46	1.70	2.95	2.0	7.5	13.0	99	4.00	A	850	A+	5.73	6.80	416

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 11.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
4MXS68F3V1B	1.5+1.5	2.62	2.62	---	---	1.62	5.24	7.10	0.38	1.32	1.99	1.7	5.8	8.7	99	3.97	A	A	3.83	3.67	1340	0.70
	1.5+2.0	2.43	3.23	---	---	1.62	5.66	7.46	0.38	1.50	2.16	1.7	6.6	9.5	99	3.77	A	A	3.82	3.77	1381	0.69
	1.5+2.5	2.28	3.80	---	---	1.62	6.08	7.64	0.38	1.70	2.24	1.7	7.5	9.8	99	3.58	B	A	3.83	3.82	1397	0.73
	1.5+3.5	2.08	4.84	---	---	1.76	6.92	8.17	0.39	2.09	2.55	1.7	9.2	11.2	99	3.31	C	A	3.85	4.24	1542	0.80
	1.5+4.2	1.98	5.53	---	---	1.76	7.51	8.51	0.39	2.38	2.79	1.7	10.5	12.3	99	3.16	D	A	3.82	4.28	1567	0.83
	1.5+5.0	1.89	6.29	---	---	2.14	8.18	9.98	0.48	2.58	3.16	2.1	11.3	13.9	99	3.17	D	A	3.85	4.20	1526	0.81
	1.5+6.0	1.72	6.88	---	---	2.41	8.60	10.17	0.51	2.51	2.90	2.2	11.0	12.7	99	3.43	B	A	3.89	4.68	1684	0.88
	2.0+2.0	3.25	3.25	---	---	1.62	6.50	7.64	0.38	1.87	2.25	1.7	8.2	9.9	99	3.48	B	A	3.83	3.88	1420	0.74
	2.0+2.5	3.04	3.81	---	---	1.62	6.85	7.81	0.38	2.05	2.33	1.7	9.0	10.2	99	3.34	C	A	3.83	3.93	1439	0.73
	2.0+3.5	2.71	4.74	---	---	1.76	7.45	8.34	0.39	2.34	2.64	1.7	10.3	11.6	99	3.18	D	A	3.83	4.34	1589	0.83
	2.0+4.2	2.58	5.42	---	---	1.76	8.00	8.68	0.39	2.64	2.89	1.7	11.6	12.7	99	3.03	D	A	3.82	4.38	1607	0.82
	2.0+5.0	2.46	6.14	---	---	2.14	8.60	10.15	0.48	2.80	3.26	2.1	12.3	14.3	99	3.07	D	A	3.83	4.30	1572	0.85
	2.0+6.0	2.15	6.45	---	---	2.41	8.60	10.34	0.51	2.43	2.98	2.2	10.7	13.1	99	3.54	B	A	3.91	4.77	1708	0.91
	2.5+2.5	3.60	3.60	---	---	1.62	7.20	8.16	0.38	2.24	2.56	1.7	9.8	11.2	99	3.21	C	A	3.84	3.98	1452	0.77
	2.5+3.5	3.29	4.61	---	---	1.85	7.90	8.68	0.40	2.58	2.89	1.8	11.3	12.7	99	3.06	D	A	3.82	4.39	1610	0.83
	2.5+4.2	3.10	5.20	---	---	1.85	8.30	8.93	0.40	2.80	3.07	1.8	12.3	13.5	99	2.96	D	A	3.85	4.42	1606	0.85
	2.5+5.0	2.87	5.73	---	---	2.23	8.60	10.27	0.49	2.80	3.36	2.2	12.3	14.8	99	3.07	D	A	3.83	4.34	1589	0.83
	2.5+6.0	2.53	6.07	---	---	2.50	8.60	10.46	0.53	2.43	3.01	2.3	10.7	13.2	99	3.54	B	A	3.90	4.81	1725	0.89
	3.5+3.5	4.30	4.30	---	---	2.13	8.60	9.02	0.45	2.93	3.11	2.0	12.9	13.7	99	2.94	D	A	3.90	4.77	1712	0.91
	3.5+4.2	3.91	4.69	---	---	2.13	8.60	9.11	0.45	2.92	3.16	2.0	12.8	13.9	99	2.95	D	A	3.91	4.80	1721	0.93
	3.5+5.0	3.54	5.06	---	---	2.51	8.60	10.48	0.54	2.79	3.40	2.4	12.3	14.9	99	3.08	D	A	3.90	4.73	1697	0.92
	3.5+6.0	3.17	5.43	---	---	2.69	8.60	10.59	0.55	2.42	3.00	2.4	10.6	13.2	99	3.55	B	A	3.99	5.17	1813	1.01
	4.2+4.2	4.30	4.30	---	---	2.13	8.60	9.19	0.45	2.92	3.20	2.0	12.8	14.1	99	2.95	D	A	3.90	4.84	1736	0.92
	4.2+5.0	3.93	4.67	---	---	2.51	8.60	10.49	0.54	2.79	3.47	2.4	12.3	15.2	99	3.08	D	A	3.90	4.76	1709	0.90
	4.2+6.0	3.54	5.06	---	---	2.69	8.60	10.60	0.54	2.42	3.03	2.4	10.6	13.3	99	3.55	B	A+	4.01	5.20	1814	1.00
	5.0+5.0	4.30	4.30	---	---	2.88	8.60	10.67	0.63	2.70	3.38	2.8	11.9	14.8	99	3.19	D	A	3.88	4.69	1692	0.89
	5.0+6.0	3.91	4.69	---	---	3.08	8.60	10.66	0.64	2.39	2.96	2.8	10.5	13.0	99	3.60	B	A	3.99	5.13	1800	0.98
	1.5+1.5+1.5	2.17	2.17	2.17	---	1.97	6.50	9.54	0.44	1.50	2.46	1.9	6.6	10.8	99	4.33	A	A	3.86	4.75	1725	0.89
	1.5+1.5+2.0	2.08	2.08	2.77	---	1.97	6.92	9.71	0.44	1.67	2.54	1.9	7.3	11.2	99	4.14	A	A	3.89	4.84	1742	0.92
	1.5+1.5+2.5	2.00	2.00	3.34	---	2.06	7.34	9.79	0.45	1.82	2.58	2.0	8.0	11.3	99	4.03	A	A	3.90	4.88	1751	0.95
	1.5+1.5+3.5	1.89	1.89	4.40	---	2.26	8.18	9.89	0.47	2.19	2.71	2.1	9.6	11.9	99	3.74	A	A	3.96	5.23	1849	0.98
	1.5+1.5+4.2	1.79	1.79	5.02	---	2.26	8.60	9.89	0.47	2.38	2.71	2.1	10.5	11.9	99	3.61	A	A	3.98	5.26	1851	1.00
	1.5+1.5+5.0	1.61	1.61	5.38	---	2.66	8.60	10.06	0.58	2.38	2.79	2.5	10.5	12.3	99	3.61	A	A	3.96	5.19	1834	0.99
	1.5+1.5+6.0	1.43	1.43	5.73	---	2.87	8.60	10.18	0.58	2.16	2.51	2.5	9.5	11.0	99	3.98	A	A+	4.09	5.59	1913	1.08
	1.5+2.0+2.0	2.00	2.67	2.67	---	1.97	7.34	9.87	0.44	1.84	2.62	1.9	8.1	11.5	99	3.99	A	A	3.90	4.93	1771	0.95
	1.5+2.0+2.5	1.94	2.59	3.23	---	2.06	7.76	9.96	0.45	2.00	2.65	2.0	8.8	11.6	99	3.88	A	A	3.93	4.97	1772	0.94
	1.5+2.0+3.5	1.84	2.46	4.30	---	2.26	8.60	10.05	0.47	2.38	2.80	2.1	10.5	12.3	99	3.61	A	A	3.98	5.31	1868	1.00
	1.5+2.0+4.2	1.68	2.23	4.69	---	2.26	8.60	10.06	0.47	2.38	2.79	2.1	10.5	12.3	99	3.61	A	A	3.98	5.34	1877	1.03
	1.5+2.0+5.0	1.52	2.02	5.06	---	2.66	8.60	10.46	0.58	2.38	2.87	2.5	10.5	12.6	99	3.61	A	A	3.99	5.27	1850	1.01
	1.5+2.0+6.0	1.36	1.81	5.43	---	2.87	8.60	10.47	0.58	2.16	2.59	2.5	9.5	11.4	99	3.98	A	A+	4.10	5.66	1934	1.10
	1.5+2.5+2.5	1.89	3.15	3.15	---	2.16	8.18	10.07	0.48	2.18	2.65	2.1	9.6	11.6	99	3.75	A	A	3.94	5.01	1780	0.97
	1.5+2.5+3.5	1.72	2.87	4.01	---	2.35	8.60	10.17	0.50	2.38	2.79	2.2	10.5	12.3	99	3.61	A	A	3.99	5.35	1880	1.04
	1.5+2.5+4.2	1.57	2.62	4.40	---	2.36	8.60	10.17	0.50	2.38	2.79	2.2	10.5	12.3	99	3.61	A	A+	4.02	5.38	1876	1.02
	1.5+2.5+5.0	1.43	2.39	4.78	---	2.75	8.60	10.58	0.60	2.38	2.87	2.6	10.5	12.6	99	3.61	A	A	3.98	5.31	1868	1.00
	1.5+2.5+6.0	1.29	2.15	5.16	---	2.96	8.60	10.36	0.61	2.16	2.59	2.7	9.5	11.4	99	3.98	A	A+	4.10	5.69	1945	1.08
	1.5+3.5+3.5	1.52	3.54	3.54	---	2.64	8.60	10.18	0.58	2.38	2.79	2.5	10.5	12.3	99	3.61	A	A+	4.09	5.66	1937	1.10
	1.5+3.5+4.2	1.40	3.27	3.93	---	2.64	8.60	10.18	0.58	2.37	2.78	2.5	10.4	12.2	99	3.63	A	A+	4.08	5.69	1951	1.09
	1.5+3.5+5.0	1.29	3.01	4.30	---	2.94	8.60	10.51	0.66	2.37	2.82	2.9	10.4	12.4	99	3.63	A	A+	4.09	5.62	1926	1.06
	1.5+3.5+6.0	1.17	2.74	4.69	---	2.87	8.60	10.37	0.58	2.15	2.58	2.5	9.4	11.3	99	4.00	A	A+	4.17	5.82	1954	1.11
	1.5+4.2+4.2	1.30	3.65	3.65	---	2.64	8.60	10.27	0.58	2.37	2.82	2.5	10.4	12.4	99	3.63	A	A+	4.10	5.71	1952	1.10
	1.5+4.2+5.0	1.21	3.38	4.02	---	2.94	8.60	10.57	0.66	2.37	2.90	2.9	10.4	12.7	99	3.63	A	A+	4.09	5.65	1935	1.09
	2.0+2.0+2.0	2.63	2.63	2.63	---	1.97	7.89	10.04	0.44	2.05	2.70	1.9	9.0	11.9	99	3.85	A	A	3.94	5.01	1780	0.97
	2.0+2.0+2.5	2.54	2.54	3.17	---	2.06	8.25	10.12	0.45	2.18	2.74	2.0	9.6	12.0	99	3.78	A	A	3.94	5.05	1794	0.96
	2.0+2.0+3.5	2.29	2.29	4.02	---	2.26	8.60	10.22	0.47	2.34	2.88	2.1	10.3	12.6	99	3.68	A	A+	4.02	5.39	1879	1.03
	2.0+2.0+4.2	2.10	2.10	4.40	---	2.26	8.60	10.22	0.47	2.34	2.88	2.1	10.3	12.6	99	3.68	A	A+	4.02	5.42	1888	1.05
	2.0+2.0+5.0	1.91	1.91	4.78	---	2.66	8.60	10.40	0.58	2.34	2.96	2.5	10.3	13.0	99	3.68	A	A	3.99	5.35	1880	1.04
	2.0+2.0+6.0	1.72	1.72	5.16	---	2.87	8.60	10.53	0.58	2.12	2.67	2.5	9.3	11.7	99	4.06	A	A+	4.09	5.73	1960	1.08
	2.0+2.5+2.5	2.46	3.07	3.07	---	2.16	8.60	10.13	0.46	2.35	2.84	2.0	10.3	12.5	99	3.66	A	A	3.94	5.09	1807	0.99
	2.0+2.5+3.5	2.15	2.69	3.76	---	2.35	8.60	10.22	0.49	2.34	2.88	2.2	10.3	12.6	99	3.68	A	A+	4.02	5.42	1888	1.05
	2.0+2.5+4.2	1.98	2.47	4.15	---	2.36	8.60	10.23	0.49	2.34	2.87	2.2	10.3	12.6	99	3.68	A	A+	4.02	5.45	1899	1.04
	2.0+2.5+5.0	1.81	2.26	4.53	---	2.75	8.60	10.63	0.60	2.32	2.99	2.6	10.2	13.1	99	3.71	A	A+	4.02	5.39	1879	1.03
	2.0+2.5+6.0	1.64	2.05	4.91	---	2.96	8.60	10.64	0.60	2.10	2.64	2.6	9.2	11.6	99	4.10	A	A+	4.13	5.76	1952	1.11
	2.0+3.5+3.5	1.92	3.34	3.34	---	2.64	8.60	10.35	0.55	2.31	2.93	2.4	10.1	12.9	99	3.72	A	A+	4.09	5.73	1963	1.08
	2.0+3.5+4.2	1.77	3.10	3.72	---	2.64	8.60	10.35	0.55	2.31	2.92	2.4	10.1	12.8	99	3.72	A	A+	4.12	5.76	1956	1.11
	2.0+3.5+5.0	1.64	2.87	4.09	---	2.94	8.60	10.68	0.62	2.29	3.06	2.7	10.1	13.4	99	3.76	A	A+	4.09	5.70	1951	1.09
	2.0+4.2+4.2	1.65	3.47	3.47	---	2.64	8.60	10.36	0.55	2.31	2.92	2.4	10.1	12.8	99	3.72	A	A+	4.12	5.78	1962	1.13
	2.5+2.5+2.5	2.86	2.86	2.86	---	2.26	8.58	10.24	0.48	2.35	2.87	2.1	10.3	12.6	99	3.65	A	A	3.97	5.13	1809	0.98
	2.5+2.5+3.5	2.53	2.53	3.54	---	2.45	8.60	10.45	0.51	2.34	2.96	2.2	10.3	13.0	99	3.68	A	A+	4.02	5.46	1902	1.05
	2.5+2.5+4.2	2.34	2.34	3.93	---	2.45	8.60	10.46	0.51	2.34	2.96	2.2	10.3	13.0	99	3.68	A	A+	4.02	5.49	1912	1.03
	2.5+2.5+5.0	2.15	2.15	4.30	---	2.85	8.60	10.64	0.62	2.29	3.02	2.7	10.1	13.3	99	3.76	A	A+	4.03	5.43	1889	1.06
	2.5+2.5+6.0	1.95	1.95	4.70	---	3.06	8.60	10.65	0.62	2.08	2.64	2.7	9.1	11.6	99	4.13	A	A+	4.12	5.79	1966	1.10
	2.5+3.5+3.5	2.26	3.17	3.17	---	2.73	8.60	10.58	0.56	2.31	2.96	2.5	10.1	13.0	99	3.72	A	A+	4.12	5.76	1956	1.11
	2.5+3.5+4.2	2.11	2.95	3.54	---	2.74	8.60	10.59	0.56	2.31	2.95	2.5	10.1	13.0	99	3.72	A	A+	4.12	5.79	1970	1.10
	2.5+3.5+5.0	1.95	2.74	3.91	---	3.13	8.60	10.65	0.64	2.29	2.98	2.8	10.1	13.1	99	3.76	A	A+	4.09	5.73	1963	1.08
	2.5+4.2+4.2	1.97	3.31	3.31	---	2.74	8.60	10.59	0.56	2.31	2.95	2.5	10.1	13.0	99	3.72	A	A+	4.13	5.79	1961	1.13
	3.5+3.5+3.5	2.86	2.86	2.86	---	2.92	8.58	10.63	0.61	2.29	3.03	2.7	10.1	13.3	99	3.75	A	A+	4.22	5.83	1933	1.12
	1.5+1.5+1.5+1.5	1.94	1.94	1.94	1.94	2.42	7.76	9.68	0.52	1.62	2.30	2.3	7.1	10.1	99	4.79	A	A+	4.10	5.64	1928	1.08
	1.5+1.5+1.5+2.0	1.89	1.89	1.89	2.52	2.42	8.18	9.86	0.52	1.78	2.38	2.3	7.8	10.5	99	4.60	A	A+	4.14	5.72	1935	1.11
	1.5+1.5+1.5+2.5	1.84	1.84	1.84	3.07	2.52	8.60	9.96	0.53	1.94	2.34	2.3	8.5	10.3	99	4.43	A	A+	4.14	5.75	1946	1.10
	1.5+1.5+1.5+3.5	1.61	1.61	1.61	3.76	2.72	8.60	10.06	0.57	1.94	2.40	2.5	8.5	10.5	99	4.43	A	A+	4.23	5.82	1927	1.11
	1.5+1.5+1.5+4.2	1.48	1.48	1.48	4.15	2.73	8.60	10.06	0.56	1.93	2.39	2.5	8.5	10.5	99	4.46	A	A+	4.26	5.83	1917	1.12
	1.5+1.5+1.5+5.0	1.36	1.36	1.36	4.53	3.04	8.60	10.12	0.63	1.89	2.31	2.8	8.3	10.1	99	4.55	A	A+	4.23	5.82	1929	1.11
	1.5+1.5+1.5+6.0	1.23	1.23	1.23	4.91	2.98	8.60	10.46	0.48	1.66	2.15	2.1	7.3	9.4	99	5.18	A	A+	4.37	5.84	1872	1.12

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 11.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
4MXS68F3V1B	1.5+1.5+2.0+2.0	1.84	1.84	2.46	2.46	2.42	8.60	10.04	0.52	1.94	2.46	2.3	8.5	10.8	99	4.43	A	A+	4.15	5.78	1953	1.13
	1.5+1.5+2.0+2.5	1.72	1.72	2.29	2.87	2.52	8.60	10.13	0.53	1.94	2.42	2.3	8.5	10.6	99	4.43	A	A+	4.15	5.79	1953	1.13
	1.5+1.5+2.0+3.5	1.52	1.52	2.02	3.54	2.72	8.60	10.23	0.57	1.94	2.47	2.5	8.5	10.8	99	4.43	A	A+	4.27	5.83	1913	1.12
	1.5+1.5+2.0+4.2	1.40	1.40	1.87	3.93	2.73	8.60	10.24	0.56	1.93	2.47	2.5	8.5	10.8	99	4.46	A	A+	4.30	5.83	1900	1.11
	1.5+1.5+2.0+5.0	1.29	1.29	1.72	4.30	3.04	8.60	10.30	0.63	1.89	2.39	2.8	8.3	10.5	99	4.55	A	A+	4.26	5.83	1917	1.12
	1.5+1.5+2.0+6.0	1.17	1.17	1.56	4.69	2.98	8.60	10.64	0.48	1.66	2.22	2.1	7.3	9.7	99	5.18	A	A+	4.42	5.84	1852	1.12
	1.5+1.5+2.5+2.5	1.61	1.61	2.69	2.69	2.62	8.60	10.14	0.55	1.94	2.42	2.4	8.5	10.6	99	4.43	A	A+	4.18	5.80	1943	1.10
	1.5+1.5+2.5+3.5	1.43	1.43	2.39	3.34	2.92	8.60	10.24	0.63	1.94	2.47	2.8	8.5	10.8	99	4.43	A	A+	4.30	5.83	1898	1.11
	1.5+1.5+2.5+4.2	1.33	1.33	2.22	3.72	2.92	8.60	10.24	0.62	1.93	2.47	2.7	8.5	10.8	99	4.46	A	A+	4.31	5.84	1897	1.12
	1.5+1.5+2.5+5.0	1.23	1.23	2.05	4.10	3.04	8.60	10.48	0.63	1.89	2.46	2.8	8.3	10.8	99	4.55	A	A+	4.27	5.83	1913	1.12
	1.5+1.5+3.5+3.5	1.29	1.29	3.01	3.01	3.12	8.60	10.34	0.68	1.93	2.50	3.0	8.5	11.0	99	4.46	A	A+	4.41	5.84	1855	1.12
	1.5+1.5+3.5+4.2	1.21	1.21	2.81	3.38	2.93	8.60	10.43	0.62	1.89	2.54	2.7	8.3	11.2	99	4.55	A	A+	4.41	5.84	1854	1.12
	1.5+2.0+2.0+2.0	1.72	2.29	2.29	2.29	2.42	8.60	10.22	0.52	1.94	2.54	2.3	8.5	11.2	99	4.43	A	A+	4.18	5.80	1943	1.10
	1.5+2.0+2.0+2.5	1.61	2.15	2.15	2.69	2.52	8.60	10.31	0.53	1.94	2.49	2.3	8.5	10.9	99	4.43	A	A+	4.19	5.81	1944	1.11
	1.5+2.0+2.0+3.5	1.43	1.91	1.91	3.34	2.72	8.60	10.41	0.57	1.94	2.55	2.5	8.5	11.2	99	4.43	A	A+	4.32	5.84	1895	1.12
	1.5+2.0+2.0+4.2	1.33	1.77	1.77	3.72	2.73	8.60	10.42	0.56	1.93	2.55	2.5	8.5	11.2	99	4.46	A	A+	4.32	5.84	1895	1.12
	1.5+2.0+2.0+5.0	1.23	1.64	1.64	4.10	3.04	8.60	10.48	0.63	1.89	2.46	2.8	8.3	10.8	99	4.55	A	A+	4.30	5.83	1898	1.11
	1.5+2.0+2.5+2.5	1.52	2.02	2.53	2.53	2.62	8.60	10.31	0.55	1.94	2.49	2.4	8.5	10.9	99	4.43	A	A+	4.19	5.81	1942	1.11
	1.5+2.0+2.5+3.5	1.36	1.81	2.26	3.17	2.92	8.60	10.41	0.63	1.94	2.55	2.8	8.5	11.2	99	4.43	A	A+	4.32	5.84	1895	1.12
	1.5+2.0+2.5+4.2	1.26	1.69	2.11	3.54	2.92	8.60	10.42	0.62	1.93	2.55	2.7	8.5	11.2	99	4.46	A	A+	4.33	5.84	1890	1.12
	1.5+2.0+2.5+5.0	1.17	1.56	1.95	3.91	3.04	8.60	10.66	0.63	1.89	2.54	2.8	8.3	11.2	99	4.55	A	A+	4.32	5.84	1895	1.12
	1.5+2.0+3.5+3.5	1.23	1.64	2.87	2.87	3.12	8.60	10.51	0.68	1.93	2.58	3.0	8.5	11.3	99	4.46	A	A+	4.42	5.84	1852	1.12
	1.5+2.5+2.5+2.5	1.43	2.39	2.39	2.39	2.72	8.60	10.32	0.58	1.94	2.49	2.5	8.5	10.9	99	4.43	A	A+	4.19	5.81	1940	1.10
	1.5+2.5+2.5+3.5	1.29	2.15	2.15	3.01	3.02	8.60	10.50	0.66	1.93	2.59	2.9	8.5	11.4	99	4.46	A	A+	4.36	5.84	1877	1.12
	1.5+2.5+2.5+4.2	1.21	2.01	2.01	3.38	2.92	8.60	10.59	0.62	1.93	2.62	2.7	8.5	11.5	99	4.46	A	A+	4.36	5.84	1875	1.12
	1.5+2.5+3.5+3.5	1.17	1.95	2.74	2.74	3.12	8.60	10.60	0.68	1.90	2.62	3.0	8.3	11.5	99	4.53	A	A+	4.48	5.84	1826	1.12
	2.0+2.0+2.0+2.0	2.15	2.15	2.15	2.15	2.42	8.60	10.39	0.52	1.91	2.61	2.3	8.4	11.5	99	4.50	A	A+	4.19	5.81	1942	1.11
	2.0+2.0+2.0+2.5	2.02	2.02	2.02	2.54	2.52	8.60	10.48	0.53	1.91	2.57	2.3	8.4	11.3	99	4.50	A	A+	4.20	5.82	1940	1.11
	2.0+2.0+2.0+3.5	1.81	1.81	1.81	3.17	2.72	8.60	10.58	0.57	1.90	2.63	2.5	8.3	11.6	99	4.53	A	A+	4.36	5.84	1877	1.12
	2.0+2.0+2.0+4.2	1.69	1.69	1.69	3.54	2.73	8.60	10.59	0.56	1.90	2.63	2.5	8.3	11.6	99	4.53	A	A+	4.36	5.84	1875	1.12
	2.0+2.0+2.0+5.0	1.56	1.56	1.56	3.92	3.04	8.60	10.65	0.63	1.86	2.54	2.8	8.2	11.2	99	4.62	A	A+	4.33	5.84	1890	1.12
	2.0+2.0+2.5+2.5	1.91	1.91	2.39	2.39	2.62	8.60	10.49	0.55	1.91	2.57	2.4	8.4	11.3	99	4.50	A	A+	4.23	5.82	1925	1.11
	2.0+2.0+2.5+3.5	1.72	1.72	2.15	3.01	2.92	8.60	10.59	0.60	1.90	2.63	2.6	8.3	11.6	99	4.53	A	A+	4.36	5.84	1875	1.12
	2.0+2.0+2.5+4.2	1.61	1.61	2.01	3.38	2.92	8.60	10.59	0.60	1.90	2.63	2.6	8.3	11.6	99	4.53	A	A+	4.37	5.84	1873	1.12
	2.0+2.0+3.5+3.5	1.56	1.56	2.74	2.74	3.12	8.60	10.69	0.65	1.90	2.66	2.9	8.3	11.7	99	4.53	A	A+	4.48	5.84	1824	1.13
	2.0+2.5+2.5+2.5	1.82	2.26	2.26	2.26	2.72	8.60	10.49	0.57	1.91	2.57	2.5	8.4	11.3	99	4.50	A	A+	4.24	5.82	1923	1.11
	2.0+2.5+2.5+3.5	1.64	2.05	2.05	2.86	3.02	8.60	10.68	0.63	1.90	2.67	2.8	8.3	11.7	99	4.53	A	A+	4.37	5.84	1873	1.12
	2.5+2.5+2.5+2.5	2.15	2.15	2.15	2.15	2.82	8.60	10.67	0.57	1.91	2.59	2.5	8.4	11.4	99	4.50	A	A+	4.26	5.83	1915	1.12
	2.5+2.5+2.5+3.5	1.95	1.95	1.95	2.75	3.12	8.60	10.68	0.64	1.88	2.58	2.8	8.3	11.3	99	4.57	A	A+	4.37	5.84	1871	1.12

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 11.0kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
4MXS80E3V3B	1.5+1.5	1.50	1.50	---	---	1.89	3.00	4.03	0.46	0.83	1.09	2.0	3.7	4.8	98	3.61	A	415	A	5.15	3.00	204
	1.5+2.0	1.50	2.00	---	---	1.91	3.50	4.51	0.50	1.00	1.28	2.2	4.4	5.7	98	3.50	A	500	A	5.38	3.50	228
	1.5+2.5	1.50	2.50	---	---	1.97	4.00	4.97	0.46	1.14	1.38	2.0	5.1	6.1	98	3.51	A	570	A	5.54	4.00	253
	1.5+3.5	1.50	3.50	---	---	2.07	5.00	5.83	0.46	1.52	1.82	2.0	6.7	8.1	98	3.29	A	760	A	5.56	5.00	315
	1.5+4.2	1.50	4.20	---	---	2.14	5.70	6.38	0.50	1.88	2.10	2.2	8.3	9.3	98	3.03	B	940	A+	5.61	5.70	356
	1.5+5.0	1.50	5.00	---	---	2.22	6.50	6.95	0.51	2.22	2.51	2.3	9.8	11.1	98	2.93	C	1110	A+	5.62	6.50	406
	1.5+6.0	1.44	5.75	---	---	2.34	7.19	7.59	0.55	2.42	2.67	2.4	10.7	11.8	98	2.97	C	1210	A+	5.98	7.19	421
	1.5+7.1	1.30	6.15	---	---	2.49	7.45	8.19	0.59	2.61	3.08	2.6	11.6	13.7	98	2.85	C	1305	A+	5.97	7.45	437
	2.0+2.0	2.00	2.00	---	---	1.97	4.00	5.30	0.50	1.23	1.67	2.2	5.5	7.4	98	3.25	A	615	A	5.57	4.00	252
	2.0+2.5	2.00	2.50	---	---	2.02	4.50	5.73	0.50	1.38	1.77	2.2	6.1	7.9	98	3.26	A	690	A+	5.66	4.50	279
	2.0+3.5	2.00	3.50	---	---	2.12	5.50	6.31	0.50	1.77	2.44	2.2	7.9	10.8	98	3.11	B	885	A+	5.64	5.50	342
	2.0+4.2	2.00	4.20	---	---	2.19	6.20	6.77	0.50	2.21	2.56	2.2	9.8	11.4	98	2.81	C	1105	A+	5.73	6.20	379
	2.0+5.0	2.00	5.00	---	---	2.27	7.00	7.30	0.51	2.51	2.76	2.3	11.1	12.2	98	2.79	D	1255	A	5.59	7.00	439
	2.0+6.0	1.83	5.48	---	---	2.41	7.31	7.90	0.55	2.48	2.87	2.4	11.0	12.7	98	2.95	C	1240	A+	6.03	7.31	424
	2.0+7.1	1.66	5.90	---	---	2.56	7.56	8.45	0.59	2.67	3.29	2.6	11.8	14.6	98	2.83	C	1335	A+	6.01	7.56	441
	2.5+2.5	2.50	2.50	---	---	2.07	5.00	6.12	0.46	1.47	2.44	2.0	6.5	10.8	98	3.40	A	735	A+	5.70	5.00	307
	2.5+3.5	2.50	3.50	---	---	2.17	6.00	6.60	0.50	1.99	2.38	2.2	8.8	10.6	98	3.02	B	995	A+	5.70	6.00	369
	2.5+4.2	2.50	4.20	---	---	2.24	6.70	7.11	0.50	2.44	2.63	2.2	10.8	11.7	98	2.75	D	1220	A+	5.69	6.70	412
	2.5+5.0	2.40	4.79	---	---	2.34	7.19	7.59	0.54	2.64	2.96	2.4	11.7	13.1	98	2.72	D	1320	A	5.57	7.19	452
	2.5+6.0	2.18	5.24	---	---	2.48	7.42	8.16	0.59	2.60	3.07	2.6	11.5	13.6	98	2.85	C	1300	A+	6.00	7.42	433
	2.5+7.1	2.00	5.68	---	---	2.63	7.68	8.66	0.59	2.74	3.43	2.6	12.2	15.2	98	2.80	C	1370	A+	5.99	7.68	449
	3.5+3.5	3.50	3.50	---	---	2.27	7.00	7.30	0.50	2.63	2.88	2.2	11.7	12.8	98	2.66	D	1315	A	5.55	7.00	442
	3.5+4.2	3.29	3.95	---	---	2.37	7.24	7.73	0.54	2.82	3.08	2.4	12.5	13.7	98	2.57	E	1410	A	5.53	7.24	458
	3.5+5.0	3.06	4.36	---	---	2.48	7.42	8.16	0.58	2.83	3.37	2.6	12.6	15.0	98	2.62	D	1415	A	5.50	7.42	473
	3.5+6.0	2.82	4.83	---	---	2.61	7.65	8.62	0.59	2.74	4.11	2.6	12.2	18.2	98	2.79	D	1370	A+	5.91	7.65	454
	3.5+7.1	2.61	5.30	---	---	2.77	7.91	8.31	0.63	2.87	3.15	2.8	12.7	14.0	98	2.76	D	1435	A+	5.93	7.91	467
	4.2+4.2	3.70	3.70	---	---	2.46	7.40	8.11	0.58	2.88	3.42	2.6	12.8	15.2	98	2.57	E	1440	A	5.54	7.40	468
	4.2+5.0	3.46	4.12	---	---	2.57	7.58	8.48	0.58	2.96	3.59	2.6	13.1	15.9	98	2.56	E	1480	A	5.49	7.58	484
	4.2+6.0	3.22	4.60	---	---	2.71	7.82	8.89	0.63	2.80	3.66	2.8	12.4	16.2	98	2.79	D	1400	A+	5.92	7.82	463
	4.2+7.1	2.97	5.03	---	---	2.86	8.00	9.16	0.67	2.94	3.82	3.0	13.0	16.9	98	2.72	D	1470	A+	5.93	8.00	472
	5.0+5.0	3.88	3.88	---	---	2.68	7.76	8.66	0.62	2.98	3.62	2.8	13.2	16.1	98	2.60	D	1490	A	5.41	7.76	503
	5.0+6.0	3.64	4.36	---	---	2.82	8.00	9.14	0.67	2.88	3.69	3.0	12.8	16.4	98	2.78	D	1440	A+	5.89	8.00	476
	5.0+7.1	3.31	4.69	---	---	2.97	8.00	9.35	0.67	2.82	3.85	3.0	12.5	17.1	98	2.84	C	1410	A+	5.92	8.00	474
	6.0+6.0	4.00	4.00	---	---	2.96	8.00	9.39	0.67	2.65	3.60	3.0	11.8	16.0	98	3.02	B	1325	A++	6.29	8.00	446
	6.0+7.1	3.66	4.34	---	---	3.11	8.00	9.55	0.71	2.58	3.76	3.1	11.4	16.7	98	3.10	B	1290	A++	6.30	8.00	445
	7.1+7.1	4.00	4.00	---	---	3.26	8.00	9.60	0.75	2.51	3.77	3.3	11.1	16.7	98	3.19	B	1255	A++	6.33	8.00	443
	1.5+1.5+1.5	1.50	1.50	1.50	---	2.02	4.50	5.41	0.48	1.14	1.47	2.1	5.1	6.5	98	3.95	A	570	A+	5.77	4.50	274
	1.5+1.5+2.0	1.50	1.50	2.00	---	2.07	5.00	5.83	0.52	1.28	1.67	2.3	5.7	7.4	98	3.91	A	640	A+	5.90	5.00	297
	1.5+1.5+2.5	1.50	1.50	2.50	---	2.12	5.50	6.23	0.52	1.52	1.89	2.3	6.7	8.4	98	3.62	A	760	A+	5.95	5.50	324
	1.5+1.5+3.5	1.50	1.50	3.50	---	2.22	6.50	6.95	0.52	2.00	2.29	2.3	8.9	10.2	98	3.25	A	1000	A+	5.99	6.50	380
	1.5+1.5+4.2	1.48	1.48	4.15	---	2.30	7.12	7.41	0.52	2.35	2.54	2.3	10.4	11.3	98	3.03	B	1175	A+	5.95	7.12	419
	1.5+1.5+5.0	1.37	1.37	4.57	---	2.41	7.31	7.88	0.56	2.43	2.75	2.5	10.8	12.2	98	3.01	B	1215	A+	5.91	7.31	434
	1.5+1.5+6.0	1.26	1.26	5.03	---	2.55	7.54	8.38	0.60	2.32	2.85	2.7	10.3	12.6	98	3.25	A	1160	A++	6.23	7.54	424
	1.5+1.5+7.1	1.16	1.16	5.48	---	2.70	7.79	8.84	0.64	2.45	3.14	2.8	10.9	13.9	98	3.18	B	1225	A++	6.25	7.79	437
	1.5+2.0+2.0	1.50	2.00	2.00	---	2.12	5.50	6.23	0.52	1.52	1.89	2.3	6.7	8.4	98	3.62	A	760	A+	5.99	5.50	322
	1.5+2.0+2.5	1.50	2.00	2.50	---	2.17	6.00	6.60	0.52	1.73	2.06	2.3	7.7	9.1	98	3.47	A	865	A+	6.05	6.00	348
	1.5+2.0+3.5	1.50	2.00	3.50	---	2.27	7.00	7.28	0.52	2.29	2.48	2.3	10.2	11.0	98	3.06	B	1145	A+	6.01	7.00	408
	1.5+2.0+4.2	1.41	1.88	3.95	---	2.37	7.24	7.71	0.55	2.42	2.74	2.4	10.7	12.2	98	2.99	C	1210	A+	5.99	7.24	424
	1.5+2.0+5.0	1.31	1.75	4.36	---	2.48	7.42	8.14	0.59	2.49	2.95	2.6	11.0	13.1	98	2.98	C	1245	A+	5.96	7.42	436
	1.5+2.0+6.0	1.21	1.61	4.83	---	2.61	7.65	8.60	0.60	2.38	3.00	2.7	10.6	13.3	98	3.21	A	1190	A++	6.30	7.65	425
	1.5+2.0+7.1	1.12	1.49	5.30	---	2.77	7.91	9.01	0.64	2.51	3.29	2.8	11.1	14.6	98	3.15	B	1255	A++	6.28	7.91	442
	1.5+2.5+2.5	1.50	2.50	2.50	---	2.22	6.50	6.95	0.52	2.00	2.29	2.3	8.9	10.2	98	3.25	A	1000	A++	6.12	6.50	373
	1.5+2.5+3.5	1.44	2.40	3.36	---	2.34	7.19	7.59	0.55	2.42	2.67	2.4	10.7	11.8	98	2.97	C	1210	A+	5.97	7.19	422
	1.5+2.5+4.2	1.34	2.24	3.76	---	2.44	7.35	7.99	0.55	2.54	2.94	2.4	11.3	13.0	98	2.89	C	1270	A+	5.97	7.35	431
	1.5+2.5+5.0	1.26	2.09	4.19	---	2.55	7.54	8.38	0.59	2.55	3.10	2.6	11.3	13.8	98	2.96	C	1275	A+	5.96	7.54	443
	1.5+2.5+6.0	1.17	1.94	4.66	---	2.68	7.77	8.80	0.60	2.45	3.14	2.7	10.9	13.9	98	3.17	B	1225	A++	6.26	7.77	435
	1.5+2.5+7.1	1.08	1.80	5.12	---	2.83	8.00	9.16	0.64	2.58	3.37	2.8	11.4	15.0	98	3.10	B	1290	A++	6.26	8.00	448
	1.5+3.5+3.5	1.31	3.06	3.06	---	2.48	7.42	8.14	0.59	2.54	3.08	2.6	11.3	13.7	98	2.92	C	1270	A+	5.90	7.42	441
	1.5+3.5+4.2	1.24	2.88	3.46	---	2.57	7.58	8.47	0.59	2.67	3.29	2.6	11.8	14.6	98	2.84	C	1335	A+	5.94	7.58	447
	1.5+3.5+5.0	1.17	2.72	3.89	---	2.68	7.77	8.80	0.63	2.68	3.46	2.8	11.9	15.4	98	2.90	C	1340	A+	5.88	7.77	463
	1.5+3.5+6.0	1.09	2.55	4.36	---	2.82	8.00	9.13	0.64	2.58	3.37	2.8	11.4	15.0	98	3.10	B	1290	A++	6.17	8.00	454
	1.5+3.5+7.1	0.99	2.31	4.69	---	2.97	8.00	9.39	0.67	2.51	3.61	3.0	11.1	16.0	98	3.19	B	1255	A++	6.19	8.00	453
	1.5+4.2+4.2	1.17	3.29	3.29	---	2.67	7.75	8.76	0.63	2.67	3.51	2.8	11.8	15.6	98	2.90	C	1335	A+	5.93	7.75	458
	1.5+4.2+5.0	1.11	3.11	3.71	---	2.78	7.93	9.04	0.63	2.68	3.61	2.8	11.9	16.0	98	2.96	C	1340	A+	5.87	7.93	474
	1.5+4.2+6.0	1.03	2.87	4.10	---	2.92	8.00	9.30	0.67	2.51	3.53	3.0	11.1	15.7	98	3.19	B	1255	A++	6.18	8.00	453
	1.5+4.2+7.1	0.94	2.63	4.44	---	3.07	8.00	9.50	0.71	2.52	3.69	3.1	11.2	16.4	98	3.17	B	1260	A++	6.19	8.00	453
	1.5+5.0+5.0	1.04	3.48	3.48	---	2.89	8.00	9.26	0.67	2.76	3.72	3.0	12.2	16.5	98	2.90	C	1380	A+	5.86	8.00	478
	1.5+5.0+6.0	0.96	3.20	3.84	---	3.03	8.00	9.45	0.68	2.46	3.55	3.0	10.9	15.7	98	3.25	A	1230	A++	6.17	8.00	454
	1.5+5.0+7.1	0.88	2.94	4.18	---	3.18	8.00	9.57	0.71	2.39	3.63	3.1	10.6	16.1	98	3.35	A	1195	A++	6.19	8.00	453
	1.5+6.0+6.0	0.89	3.56	3.56	---	3.16	8.00	9.56	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.33	8.00	443
	2.0+2.0+2.0	2.00	2.00	2.00	---	2.17	6.00	6.63	0.52	1.73	2.12	2.3	7.7	9.4	98	3.47	A	865	A+	6.07	6.00	346
	2.0+2.0+2.5	2.00	2.00	2.50	---	2.22	6.50	6.95	0.52	2.00	2.29	2.3	8.9	10.2	98	3.25	A	1000	A++	6.20	6.50	367
	2.0+2.0+3.5	1.92	1.92	3.36	---	2.34	7.19	7.61	0.55	2.42	2.67	2.4	10.7	11.8	98	2.97	C	1210	A+	6.05	7.19	417
	2.0+2.0+4.2	1.79	1.79	3.76	---	2.44	7.35	8.01	0.55	2.54	2.87	2.4	11.3	12.7	98	2.89	C	1270	A+	6.06	7.35	425
	2.0+2.0+5.0	1.68	1.68	4.19	---	2.55	7.54	8.40	0.59	2.55	3.17	2.6	11.3	14.1	98	2.96	C	1275	A+	6.04	7.54	438
	2.0+2.0+6.0	1.55	1.55	4.66	---	2.68	7.77	8.82	0.60	2.45	3.14	2.7	10.9	13.9	98	3.17	B	1225	A++	6.28	7.77	433
	2.0+2.0+7.1	1.44	1.44	5.12	---	2.83	8.00	9.18	0.64	2.58	3.45	2.8	11.4	15.3	98	3.10	B	1290	A++	6.29	8.00	446
	2.0+2.5+2.5	2.00	2.50	2.50	---	2.27	7.00	7.30	0.52	2.29	2.48	2.3	10.2	11.0	98	3.06	B	1145	A++	6.16	7.00	398
	2.0+2.5+3.5	1.83	2.28	3.20	---	2.41	7.31	7.90	0.55	2.48	2.87	2.4	11.0	12.7	98	2.95	C	1240	A+	6.05	7.31	423
	2.0+2.5+4.2	1.72	2.15	3.61	---	2.50	7.47	8.26	0.59	2.61	3.01	2.6	11.6	13.4	98	2.86	C	1305	A+	6.04	7.47	434
	2.0+2.5+5.0	1.61	2.01	4.03	---	2.61	7.65	8.62	0.59	2.62	3.31	2.6	11.6	14.7	98	2.92	C	1310	A+	6.02	7.65	445
	2.0+2.5+6.0	1.50	1.88	4.50	---	2.75	7.88	8.99	0.64	2.51	3.29	2.8	11.1	14.6	98	3.14	B	1255	A++	6.29	7.88	439
	2.0+2.5+7.1	1.38	1.72	4.90	---	2.90	8.00	9.30	0.67	2.58	3.53	3.0	11.4	15.7	98	3.10	B	1290	A++	6.29	8.00	446

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
4MXS80E3V3B	2.0+3.5+3.5	1.68	2.93	2.93	---	2.55	7.54	8.40	0.59	2.67	3.22	2.6	11.8	14.3	98	2.82	C	1335	A+	5.99	7.54	441
	2.0+3.5+4.2	1.59	2.78	3.33	---	2.64	7.70	8.70	0.63	2.74	3.37	2.8	12.2	15.0	98	2.81	C	1370	A+	5.97	7.70	452
	2.0+3.5+5.0	1.50	2.63	3.75	---	2.75	7.88	8.99	0.63	2.75	3.61	2.8	12.2	16.0	98	2.87	C	1375	A+	5.92	7.88	467
	2.0+3.5+6.0	1.39	2.43	4.17	---	2.89	8.00	9.28	0.67	2.58	3.52	3.0	11.4	15.6	98	3.10	B	1290	A++	6.20	8.00	452
	2.0+3.5+7.1	1.27	2.22	4.51	---	3.04	8.00	9.10	0.67	2.51	3.30	3.0	11.1	14.6	98	3.19	B	1255	A++	6.21	8.00	451
	2.0+4.2+4.2	1.51	3.17	3.17	---	2.74	7.86	8.99	0.63	2.74	3.66	2.8	12.2	16.2	98	2.87	C	1370	A+	5.95	7.86	463
	2.0+4.2+5.0	1.43	3.00	3.57	---	2.85	8.00	9.23	0.67	2.75	3.77	3.0	12.2	16.7	98	2.91	C	1375	A+	5.92	8.00	473
	2.0+4.2+6.0	1.31	2.75	3.93	---	2.98	8.00	9.45	0.67	2.51	3.60	3.0	11.1	16.0	98	3.19	B	1255	A++	6.21	8.00	451
	2.0+4.2+7.1	1.20	2.53	4.27	---	3.14	8.00	9.60	0.71	2.52	3.69	3.1	11.2	16.4	98	3.17	B	1260	A++	6.25	8.00	449
	2.0+5.0+5.0	1.33	3.33	3.33	---	2.96	8.00	9.39	0.67	2.76	3.80	3.0	12.2	16.9	98	2.90	C	1380	A+	5.90	8.00	475
	2.0+5.0+6.0	1.23	3.08	3.69	---	3.09	8.00	9.54	0.71	2.46	3.63	3.1	10.9	16.1	98	3.25	A	1230	A++	6.21	8.00	451
	2.0+5.0+7.1	1.13	2.84	4.03	---	3.25	8.00	9.60	0.71	2.39	3.63	3.1	10.6	16.1	98	3.35	A	1195	A++	6.24	8.00	449
	2.0+6.0+6.0	1.14	3.43	3.43	---	3.23	8.00	9.60	0.72	2.28	3.37	3.2	10.1	15.0	98	3.51	A	1140	A++	6.36	8.00	441
	2.5+2.5+2.5	2.40	2.40	2.40	---	2.34	7.20	7.61	0.55	2.42	2.67	2.4	10.7	11.8	98	2.98	C	1210	A++	6.12	7.20	412
	2.5+2.5+3.5	2.18	2.18	3.06	---	2.48	7.42	8.16	0.59	2.54	3.08	2.6	11.3	13.7	98	2.92	C	1270	A+	6.04	7.42	431
	2.5+2.5+4.2	2.06	2.06	3.46	---	2.57	7.58	8.49	0.59	2.67	3.29	2.6	11.8	14.6	98	2.84	C	1335	A+	6.03	7.58	441
	2.5+2.5+5.0	1.94	1.94	3.89	---	2.68	7.77	8.82	0.63	2.68	3.46	2.8	11.9	15.4	98	2.90	C	1340	A+	6.01	7.77	453
	2.5+2.5+6.0	1.82	1.82	4.36	---	2.82	8.00	9.15	0.64	2.58	3.45	2.8	11.4	15.3	98	3.10	B	1290	A++	6.26	8.00	448
	2.5+2.5+7.1	1.65	1.65	4.69	---	2.97	8.00	9.41	0.67	2.51	3.61	3.0	11.1	16.0	98	3.19	B	1255	A++	6.29	8.00	446
	2.5+3.5+3.5	2.01	2.82	2.82	---	2.61	7.65	8.34	0.59	2.74	3.01	2.6	12.2	13.4	98	2.79	D	1370	A+	5.98	7.65	448
	2.5+3.5+4.2	1.92	2.68	3.22	---	2.71	7.82	8.89	0.63	2.80	3.44	2.8	12.4	15.3	98	2.79	D	1400	A+	5.96	7.82	460
	2.5+3.5+5.0	1.82	2.55	3.64	---	2.82	8.00	9.15	0.67	2.82	3.69	3.0	12.5	16.4	98	2.84	C	1410	A+	5.90	8.00	475
	2.5+3.5+6.0	1.67	2.33	4.00	---	2.96	8.00	9.39	0.67	2.58	3.60	3.0	11.4	16.0	98	3.10	B	1290	A++	6.21	8.00	451
	2.5+3.5+7.1	1.53	2.14	4.34	---	3.11	8.00	9.10	0.71	2.51	3.30	3.1	11.1	14.6	98	3.19	B	1255	A++	6.25	8.00	449
	2.5+4.2+4.2	1.83	3.07	3.07	---	2.81	7.98	9.02	0.67	2.87	3.67	3.0	12.7	16.3	98	2.78	D	1435	A+	5.93	7.98	471
	2.5+4.2+5.0	1.71	2.87	3.42	---	2.92	8.00	9.35	0.67	2.82	3.85	3.0	12.5	17.1	98	2.84	C	1410	A+	5.93	8.00	473
	2.5+4.2+6.0	1.57	2.65	3.78	---	3.05	8.00	9.53	0.67	2.58	3.68	3.0	11.4	16.3	98	3.10	B	1290	A++	6.21	8.00	451
	2.5+4.2+7.1	1.45	2.43	4.12	---	3.20	8.00	9.63	0.71	2.52	3.77	3.1	11.2	16.7	98	3.17	B	1260	A++	6.25	8.00	449
	2.5+5.0+5.0	1.60	3.20	3.20	---	3.03	8.00	9.47	0.71	2.76	3.88	3.1	12.2	17.2	98	2.90	C	1380	A+	5.90	8.00	475
	2.5+5.0+6.0	1.48	2.96	3.56	---	3.16	8.00	9.58	0.71	2.46	3.63	3.1	10.9	16.1	98	3.25	A	1230	A++	6.21	8.00	451
	2.5+6.0+6.0	1.38	3.31	3.31	---	3.30	8.00	9.60	0.72	2.22	3.37	3.2	9.8	15.0	98	3.60	A	1110	A++	6.36	8.00	441
	3.5+3.5+3.5	2.63	2.63	2.63	---	2.75	7.89	8.67	0.63	2.87	3.15	2.8	12.7	14.0	98	2.75	D	1435	A+	5.86	7.89	472
	3.5+3.5+4.2	2.50	2.50	3.00	---	2.85	8.01	9.29	0.67	2.94	3.66	3.0	13.0	16.2	98	2.72	D	1470	A+	5.87	8.00	478
	3.5+3.5+5.0	2.33	2.33	3.33	---	2.96	8.00	9.35	0.67	2.82	3.85	3.0	12.5	17.1	98	2.84	C	1410	A+	5.86	8.00	478
	3.5+3.5+6.0	2.15	2.15	3.69	---	3.09	8.00	9.11	0.71	2.58	3.37	3.1	11.4	15.0	98	3.10	B	1290	A++	6.14	8.00	456
	3.5+3.5+7.1	1.99	1.99	4.03	---	3.25	8.00	9.60	0.75	2.52	3.77	3.3	11.2	16.7	98	3.17	B	1260	A++	6.18	8.00	454
	3.5+4.2+4.2	2.35	2.82	2.82	---	2.94	8.00	9.18	0.67	2.87	3.82	3.0	12.7	16.9	98	2.79	D	1435	A+	5.88	8.00	477
	3.5+4.2+5.0	2.20	2.65	3.15	---	3.05	8.00	9.36	0.71	2.75	3.85	3.1	12.2	17.1	98	2.91	C	1375	A+	5.88	8.00	477
	3.5+4.2+6.0	2.04	2.45	3.50	---	3.19	8.00	9.59	0.71	2.51	3.77	3.1	11.1	16.7	98	3.19	B	1255	A++	6.17	8.00	455
	3.5+5.0+5.0	2.07	2.96	2.96	---	3.16	8.00	9.55	0.71	2.76	3.88	3.1	12.2	17.2	98	2.90	C	1380	A+	5.86	8.00	478
	3.5+5.0+6.0	1.93	2.76	3.31	---	3.30	8.00	9.60	0.75	2.46	3.63	3.3	10.9	16.1	98	3.25	A	1230	A++	6.14	8.00	456
	4.2+4.2+4.2	2.67	2.67	2.67	---	3.04	8.00	9.19	0.71	2.87	3.82	3.1	12.7	16.9	98	2.79	D	1435	A+	5.88	8.00	476
	4.2+4.2+5.0	2.51	2.51	2.99	---	3.15	8.00	9.37	0.71	2.75	3.85	3.1	12.2	17.1	98	2.91	C	1375	A+	5.88	8.00	477
	4.2+4.2+6.0	2.33	2.33	3.33	---	3.29	8.00	9.60	0.75	2.51	3.77	3.3	11.1	16.7	98	3.19	B	1255	A++	6.17	8.00	454
	4.2+5.0+5.0	2.37	2.82	2.82	---	3.26	8.00	9.56	0.75	2.70	3.88	3.3	12.0	17.2	98	2.96	C	1350	A+	5.88	8.00	477
	1.5+1.5+1.5+1.5	1.50	1.50	1.50	1.50	2.17	6.00	6.60	0.53	1.47	1.73	2.4	6.5	7.7	98	4.08	A	735	A++	6.10	6.00	345
	1.5+1.5+1.5+2.0	1.50	1.50	1.50	2.00	2.22	6.50	6.95	0.53	1.68	1.90	2.4	7.5	8.4	98	3.87	A	840	A++	6.17	6.50	369
	1.5+1.5+1.5+2.5	1.50	1.50	1.50	2.50	2.27	7.00	7.28	0.53	1.90	2.07	2.4	8.4	9.2	98	3.68	A	950	A++	6.22	7.00	394
	1.5+1.5+1.5+3.5	1.37	1.37	1.37	3.20	2.41	7.31	7.88	0.56	2.07	2.38	2.5	9.2	10.6	98	3.53	A	1035	A++	6.16	7.31	416
	1.5+1.5+1.5+4.2	1.29	1.29	1.29	3.61	2.50	7.47	8.24	0.56	2.13	2.58	2.5	9.4	11.4	98	3.51	A	1065	A++	6.17	7.47	424
	1.5+1.5+1.5+5.0	1.21	1.21	1.21	4.03	2.61	7.65	8.60	0.60	2.33	2.87	2.7	10.3	12.7	98	3.28	A	1165	A++	6.16	7.65	435
	1.5+1.5+1.5+6.0	1.13	1.13	1.13	4.50	2.75	7.88	8.97	0.61	2.22	2.91	2.7	9.8	12.9	98	3.55	A	1110	A++	6.31	7.88	438
	1.5+1.5+1.5+7.1	1.03	1.03	1.03	4.90	2.90	8.00	9.28	0.64	2.22	3.06	2.8	9.8	13.6	98	3.60	A	1110	A++	6.30	8.00	445
	1.5+1.5+2.0+2.0	1.50	1.50	2.00	2.00	2.27	7.00	7.28	0.53	1.90	2.07	2.4	8.4	9.2	98	3.68	A	950	A++	6.25	7.00	392
	1.5+1.5+2.0+2.5	1.44	1.44	1.92	2.40	2.34	7.19	7.59	0.56	2.02	2.20	2.5	9.0	9.8	98	3.56	A	1010	A++	6.25	7.19	403
	1.5+1.5+2.0+3.5	1.31	1.31	1.75	3.06	2.48	7.42	8.14	0.56	2.13	2.51	2.5	9.4	11.1	98	3.48	A	1065	A++	6.18	7.42	420
	1.5+1.5+2.0+4.2	1.24	1.24	1.65	3.46	2.57	7.58	8.47	0.60	2.20	2.72	2.7	9.8	12.1	98	3.45	A	1100	A++	6.19	7.58	429
	1.5+1.5+2.0+5.0	1.17	1.17	1.55	3.89	2.68	7.77	8.80	0.60	2.39	3.01	2.7	10.6	13.4	98	3.25	A	1195	A++	6.14	7.77	444
	1.5+1.5+2.0+6.0	1.09	1.09	1.45	4.36	2.82	8.00	9.13	0.64	2.28	2.98	2.8	10.1	13.2	98	3.51	A	1140	A++	6.30	8.00	445
	1.5+1.5+2.0+7.1	0.99	0.99	1.32	4.69	2.97	8.00	9.39	0.68	2.22	3.14	3.0	9.8	13.9	98	3.60	A	1110	A++	6.32	8.00	443
	1.5+1.5+2.5+2.5	1.37	1.37	2.28	2.28	2.41	7.31	7.88	0.56	2.07	2.38	2.5	9.2	10.6	98	3.53	A	1035	A++	6.24	7.31	411
	1.5+1.5+2.5+3.5	1.26	1.26	2.09	2.93	2.55	7.54	8.38	0.60	2.32	2.86	2.7	10.3	12.7	98	3.25	A	1160	A++	6.18	7.54	428
	1.5+1.5+2.5+4.2	1.19	1.19	1.98	3.33	2.64	7.70	8.68	0.60	2.38	3.07	2.7	10.6	13.6	98	3.24	A	1190	A++	6.20	7.70	435
	1.5+1.5+2.5+5.0	1.13	1.13	1.88	3.75	2.75	7.88	8.97	0.64	2.46	3.16	2.8	10.9	14.0	98	3.20	A	1230	A++	6.14	7.88	449
	1.5+1.5+2.5+6.0	1.04	1.04	1.74	4.17	2.89	8.00	9.26	0.64	2.28	3.06	2.8	10.1	13.6	98	3.51	A	1140	A++	6.30	8.00	445
	1.5+1.5+2.5+7.1	0.95	0.95	1.59	4.51	3.04	8.00	9.47	0.68	2.22	3.21	3.0	9.8	14.2	98	3.60	A	1110	A++	6.32	8.00	443
	1.5+1.5+3.5+3.5	1.17	1.17	2.72	2.72	2.68	7.77	8.80	0.60	2.45	3.15	2.7	10.9	14.0	98	3.17	B	1225	A+	6.07	7.77	449
	1.5+1.5+3.5+4.2	1.11	1.11	2.59	3.11	2.78	7.93	9.04	0.64	2.52	3.30	2.8	11.2	14.6	98	3.15	B	1260	A+	6.09	7.93	457
	1.5+1.5+3.5+5.0	1.04	1.04	2.43	3.48	2.89	8.00	9.26	0.64	2.52	3.39	2.8	11.2	15.0	98	3.17	B	1260	A+	6.06	8.00	462
	1.5+1.5+3.5+6.0	0.96	0.96	2.24	3.84	3.03	8.00	9.45	0.68	2.28	3.21	3.0	10.1	14.2	98	3.51	A	1140	A++	6.23	8.00	450
	1.5+1.5+3.5+7.1	0.88	0.88	2.06	4.18	3.18	8.00	9.57	0.72	2.22	3.29	3.2	9.8	14.6	98	3.60	A	1110	A++	6.25	8.00	448
	1.5+1.5+4.2+4.2	1.05	1.05	2.95	2.95	2.87	8.00	9.23	0.64	2.58	3.45	2.8	11.4	15.3	98	3.10	B	1290	A+	6.07	8.00	462
	1.5+1.5+4.2+5.0	0.98	0.98	2.75	3.28	2.98	8.00	9.40	0.68	2.52	3.47	3.0	11.2	15.4	98	3.17	B	1260	A+	6.07	8.00	462
	1.5+1.5+4.2+6.0	0.91	0.91	2.55	3.64	3.12	8.00	9.54	0.68	2.28	3.29	3.0	10.1	14.6	98	3.51	A	1140	A++	6.25	8.00	449
	1.5+1.5+4.2+7.1	0.84	0.84	2.35	3.97	3.27	8.00	9.58	0.72	2.22	3.29	3.2	9.8	14.6	98	3.60	A	1110	A++	6.25	8.00	448
	1.5+1.5+5.0+5.0	0.92	0.92	3.08	3.08	3.09	8.00	9.52	0.68	2.40	3.42	3.0	10.6	15.2	98	3.33	A	1200	A+	6.07	8.00	462
	1.5+1.5+5.0+6.0	0.86	0.86	2.86	3.43	3.23	8.00	9.58	0.72	2.22	3.23	3.2	9.8	14.3	98	3.60	A	1110	A++	6.23	8.00	450
	1.5+2.0+2.0+2.0	1.44	1.92	1.92	1.92	2.34	7.19	7.59	0.56	2.02	2.20	2.5	9.0	9.8	98	3.56	A	1010	A++	6.27	7.19	402
	1.5+2.0+2.0+2.5	1.37	1.83	1.83	2.28	2.41	7.31	7.88	0.56	2.07	2.38	2.5	9.2	10.6	98	3.53	A	1035	A++	6.28	7.31	408
	1.5+2.0+2.0+3.5	1.26	1.68	1.68	2.93	2.55	7.54	8.38	0.60	2.20	2.65	2.7	9.8	11.8	98	3.43	A	1100	A++	6.21	7.54	426
	1.5+2.0+2.0+4.2	1.19	1.59	1.59	3.33	2.64	7.70	8.68	0.60	2.26	2.86	2.7	10.0	12.7	98	3.41	A	1130	A++	6.21	7.70	434
	1.5+2.0+2.0+5.0	1.13	1.50	1.50	3.75	2.75	7.88	8.97	0.64	2.46	3.16	2.8	10.9	14.0	98	3.20	A	1230	A++	6.16	7.88	449
	1.5+2.0+2.0+6.0	1.04	1.39	1.39	4.17	2.89	8.00	9.26	0.64	2.28	3.06	2.8	10.1	13.6	98	3.51	A	1140	A++	6.32	8.00	443

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
4MXS80E3V3B	1.5+2.0+2.0+7.1	0.95	1.27	1.27	4.51	3.04	8.00	9.47	0.68	2.22	3.21	3.0	9.8	14.2	98	3.60	A	1110	A++	6.35	8.00	442
	1.5+2.0+2.5+2.5	1.31	1.75	2.18	2.18	2.48	7.42	8.14	0.56	2.13	2.51	2.5	9.4	11.1	98	3.48	A	1065	A++	6.30	7.42	413
	1.5+2.0+2.5+3.5	1.21	1.61	2.01	2.82	2.61	7.65	8.60	0.60	2.38	3.00	2.7	10.6	13.3	98	3.21	A	1190	A++	6.20	7.65	432
	1.5+2.0+2.5+4.2	1.15	1.53	1.92	3.22	2.71	7.82	8.87	0.64	2.51	3.22	2.8	11.1	14.3	98	3.12	B	1255	A++	6.17	7.82	444
	1.5+2.0+2.5+5.0	1.09	1.45	1.82	3.64	2.82	8.00	9.13	0.64	2.52	3.24	2.8	11.2	14.4	98	3.17	B	1260	A++	6.15	8.00	456
	1.5+2.0+2.5+6.0	1.00	1.33	1.67	4.00	2.96	8.00	9.37	0.68	2.28	3.13	3.0	10.1	13.9	98	3.51	A	1140	A++	6.32	8.00	443
	1.5+2.0+2.5+7.1	0.92	1.22	1.53	4.34	3.11	8.00	9.53	0.68	2.22	3.29	3.0	9.8	14.6	98	3.60	A	1110	A++	6.35	8.00	442
	1.5+2.0+3.5+3.5	1.13	1.50	2.63	2.63	2.75	7.88	8.97	0.64	2.51	3.30	2.8	11.1	14.6	98	3.14	B	1255	A+	6.09	7.88	453
	1.5+2.0+3.5+4.2	1.07	1.43	2.50	3.00	2.85	8.00	9.18	0.64	2.58	3.45	2.8	11.4	15.3	98	3.10	B	1290	A++	6.10	8.00	460
	1.5+2.0+3.5+5.0	1.00	1.33	2.33	3.33	2.96	8.00	9.37	0.68	2.52	3.47	3.0	11.2	15.4	98	3.17	B	1260	A+	6.08	8.00	461
	1.5+2.0+3.5+6.0	0.92	1.23	2.15	3.69	3.09	8.00	9.52	0.68	2.28	3.29	3.0	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	1.5+2.0+3.5+7.1	0.85	1.13	1.99	4.03	3.25	8.00	9.58	0.72	2.22	3.29	3.2	9.8	14.6	98	3.60	A	1110	A++	6.27	8.00	447
	1.5+2.0+4.2+4.2	1.01	1.34	2.82	2.82	2.94	8.00	9.35	0.67	2.58	3.53	3.0	11.4	15.7	98	3.10	B	1290	A++	6.10	8.00	459
	1.5+2.0+4.2+5.0	0.94	1.26	2.65	3.15	3.05	8.00	9.48	0.68	2.52	3.55	3.0	11.2	15.7	98	3.17	B	1260	A++	6.10	8.00	459
	1.5+2.0+4.2+6.0	0.88	1.17	2.45	3.50	3.19	8.00	9.57	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	1.5+2.0+5.0+5.0	0.89	1.19	2.96	2.96	3.16	8.00	9.56	0.71	2.40	3.50	3.1	10.6	15.5	98	3.33	A	1200	A++	6.10	8.00	460
	1.5+2.0+5.0+6.0	0.83	1.10	2.76	3.31	3.30	8.00	9.58	0.72	2.22	3.23	3.2	9.8	14.3	98	3.60	A	1110	A++	6.27	8.00	447
	1.5+2.5+2.5+2.5	1.26	2.09	2.09	2.09	2.55	7.54	8.38	0.60	2.20	2.65	2.7	9.8	11.8	98	3.43	A	1100	A++	6.28	7.54	421
	1.5+2.5+2.5+3.5	1.17	1.94	1.94	2.72	2.68	7.77	8.80	0.60	2.45	3.14	2.7	10.9	13.9	98	3.17	B	1225	A++	6.16	7.77	442
	1.5+2.5+2.5+4.2	1.11	1.85	1.85	3.11	2.78	7.93	9.04	0.64	2.58	3.30	2.8	11.4	14.6	98	3.07	B	1290	A++	6.17	7.93	450
	1.5+2.5+2.5+5.0	1.04	1.74	1.74	3.48	2.89	8.00	9.26	0.64	2.52	3.39	2.8	11.2	15.0	98	3.17	B	1260	A++	6.15	8.00	456
	1.5+2.5+2.5+6.0	0.96	1.60	1.60	3.84	3.03	8.00	9.45	0.68	2.28	3.21	3.0	10.1	14.2	98	3.51	A	1140	A++	6.32	8.00	443
	1.5+2.5+2.5+7.1	0.88	1.47	1.47	4.18	3.18	8.00	9.57	0.72	2.22	3.29	3.2	9.8	14.6	98	3.60	A	1110	A++	6.35	8.00	442
	1.5+2.5+3.5+3.5	1.09	1.82	2.55	2.55	2.82	8.00	9.13	0.64	2.58	3.37	2.8	11.4	15.0	98	3.10	B	1290	A++	6.10	8.00	460
	1.5+2.5+3.5+4.2	1.03	1.71	2.39	2.87	2.92	8.00	9.30	0.67	2.58	3.53	3.0	11.4	15.7	98	3.10	B	1290	A++	6.10	8.00	459
	1.5+2.5+3.5+5.0	0.96	1.60	2.24	3.20	3.03	8.00	9.45	0.68	2.52	3.47	3.0	11.2	15.4	98	3.17	B	1260	A++	6.10	8.00	460
	1.5+2.5+3.5+6.0	0.89	1.48	2.07	3.56	3.16	8.00	9.56	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	1.5+2.5+4.2+4.2	0.97	1.61	2.71	2.71	3.01	8.00	9.44	0.67	2.58	3.61	3.0	11.4	16.0	98	3.10	B	1290	A++	6.15	8.00	456
	1.5+2.5+4.2+5.0	0.91	1.52	2.55	3.03	3.12	8.00	9.54	0.71	2.52	3.55	3.1	11.2	15.7	98	3.17	B	1260	A++	6.10	8.00	459
	1.5+2.5+4.2+6.0	0.85	1.41	2.37	3.38	3.26	8.00	9.58	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	1.5+2.5+5.0+5.0	0.86	1.43	2.86	2.86	3.23	8.00	9.58	0.71	2.40	3.50	3.1	10.6	15.5	98	3.33	A	1200	A++	6.10	8.00	459
	1.5+3.5+3.5+3.5	1.00	2.33	2.33	2.33	2.96	8.00	9.37	0.67	2.58	3.45	3.0	11.4	15.3	98	3.10	B	1290	A+	6.04	8.00	464
	1.5+3.5+3.5+4.2	0.94	2.20	2.20	2.65	3.05	8.00	9.48	0.67	2.58	3.61	3.0	11.4	16.0	98	3.10	B	1290	A+	6.09	8.00	460
	1.5+3.5+3.5+5.0	0.89	2.07	2.07	2.96	3.16	8.00	9.56	0.71	2.52	3.55	3.1	11.2	15.7	98	3.17	B	1260	A+	6.08	8.00	461
	1.5+3.5+3.5+6.0	0.83	1.93	1.93	3.31	3.30	8.00	9.58	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.20	8.00	452
	1.5+3.5+4.2+4.2	0.90	2.09	2.51	2.51	3.15	8.00	9.55	0.71	2.58	3.69	3.1	11.4	16.4	98	3.10	B	1290	A++	6.10	8.00	460
	1.5+3.5+4.2+5.0	0.85	1.97	2.37	2.82	3.26	8.00	9.58	0.71	2.53	3.64	3.1	11.2	16.1	98	3.16	B	1265	A+	6.09	8.00	460
	1.5+4.2+4.2+4.2	0.85	2.38	2.38	2.38	3.25	8.00	9.58	0.75	2.58	3.69	3.3	11.4	16.4	98	3.10	B	1290	A++	6.10	8.00	460
	2.0+2.0+2.0+2.0	1.83	1.83	1.83	1.83	2.41	7.32	7.90	0.56	2.07	2.38	2.5	9.2	10.6	98	3.54	A	1035	A++	6.31	7.32	407
	2.0+2.0+2.0+2.5	1.75	1.75	1.75	2.18	2.48	7.42	8.16	0.56	2.13	2.51	2.5	9.4	11.1	98	3.48	A	1065	A++	6.31	7.42	412
	2.0+2.0+2.0+3.5	1.61	1.61	1.61	2.82	2.61	7.65	8.62	0.60	2.26	2.86	2.7	10.0	12.7	98	3.38	A	1130	A++	6.22	7.65	431
	2.0+2.0+2.0+4.2	1.53	1.53	1.53	3.22	2.71	7.82	8.89	0.64	2.32	3.00	2.8	10.3	13.3	98	3.37	A	1160	A++	6.22	7.82	441
	2.0+2.0+2.0+5.0	1.45	1.45	1.45	3.64	2.82	8.00	9.15	0.64	2.52	3.32	2.8	11.2	14.7	98	3.17	B	1260	A++	6.18	8.00	454
	2.0+2.0+2.0+6.0	1.33	1.33	1.33	4.00	2.96	8.00	9.39	0.68	2.28	3.21	3.0	10.1	14.2	98	3.51	A	1140	A++	6.35	8.00	442
	2.0+2.0+2.0+7.1	1.22	1.22	1.22	4.34	3.11	8.00	9.55	0.68	2.22	3.29	3.0	9.8	14.6	98	3.60	A	1110	A++	6.35	8.00	442
	2.0+2.0+2.5+2.5	1.68	1.68	2.09	2.09	2.55	7.54	8.40	0.60	2.20	2.72	2.7	9.8	12.1	98	3.43	A	1100	A++	6.31	7.54	418
	2.0+2.0+2.5+3.5	1.55	1.55	1.94	2.72	2.68	7.77	8.82	0.60	2.45	3.14	2.7	10.9	13.9	98	3.17	B	1225	A++	6.25	7.77	436
	2.0+2.0+2.5+4.2	1.48	1.48	1.85	3.11	2.78	7.93	9.06	0.64	2.58	3.30	2.8	11.4	14.6	98	3.07	B	1290	A++	6.23	7.93	446
	2.0+2.0+2.5+5.0	1.39	1.39	1.74	3.48	2.89	8.00	9.28	0.64	2.52	3.39	2.8	11.2	15.0	98	3.17	B	1260	A++	6.24	8.00	449
	2.0+2.0+2.5+6.0	1.28	1.28	1.60	3.84	3.03	8.00	9.47	0.68	2.28	3.21	3.0	10.1	14.2	98	3.51	A	1140	A++	6.35	8.00	442
	2.0+2.0+2.5+7.1	1.18	1.18	1.47	4.18	3.18	8.00	9.59	0.72	2.22	3.29	3.2	9.8	14.6	98	3.60	A	1110	A++	6.35	8.00	442
	2.0+2.0+3.5+3.5	1.45	1.45	2.55	2.55	2.82	8.00	8.96	0.64	2.58	3.22	2.8	11.4	14.3	98	3.10	B	1290	A++	6.17	8.00	454
	2.0+2.0+3.5+4.2	1.37	1.37	2.39	2.87	2.92	8.00	9.32	0.67	2.58	3.53	3.0	11.4	15.7	98	3.10	B	1290	A++	6.17	8.00	454
	2.0+2.0+3.5+5.0	1.28	1.28	2.24	3.20	3.03	8.00	9.47	0.68	2.52	3.55	3.0	11.2	15.7	98	3.17	B	1260	A++	6.17	8.00	454
	2.0+2.0+3.5+6.0	1.19	1.19	2.07	3.56	3.16	8.00	9.58	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	2.0+2.0+4.2+4.2	1.29	1.29	2.71	2.71	3.01	8.00	9.46	0.67	2.58	3.61	3.0	11.4	16.0	98	3.10	B	1290	A++	6.18	8.00	454
	2.0+2.0+4.2+5.0	1.21	1.21	2.55	3.03	3.12	8.00	9.56	0.71	2.52	3.55	3.1	11.2	15.7	98	3.17	B	1260	A++	6.17	8.00	454
	2.0+2.0+4.2+6.0	1.13	1.13	2.37	3.38	3.26	8.00	9.60	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	2.0+2.0+5.0+5.0	1.14	1.14	2.86	2.86	3.23	8.00	9.60	0.71	2.44	3.50	3.1	10.8	15.5	98	3.28	A	1220	A++	6.17	8.00	454
	2.0+2.5+2.5+2.5	1.61	2.01	2.01	2.01	2.61	7.65	8.62	0.60	2.26	2.85	2.7	10.0	12.6	98	3.38	A	1130	A++	6.30	7.65	426
	2.0+2.5+2.5+3.5	1.50	1.88	1.88	2.63	2.75	7.88	8.99	0.64	2.51	3.29	2.8	11.1	14.6	98	3.14	B	1255	A++	6.23	7.88	443
	2.0+2.5+2.5+4.2	1.43	1.79	1.79	3.00	2.85	8.00	9.20	0.64	2.58	3.45	2.8	11.4	15.3	98	3.10	B	1290	A++	6.24	8.00	449
	2.0+2.5+2.5+5.0	1.33	1.67	1.67	3.33	2.96	8.00	9.39	0.68	2.52	3.47	3.0	11.2	15.4	98	3.17	B	1260	A++	6.24	8.00	449
	2.0+2.5+2.5+6.0	1.23	1.54	1.54	3.69	3.09	8.00	9.54	0.68	2.25	3.29	3.0	10.0	14.6	98	3.56	A	1125	A++	6.34	8.00	442
	2.0+2.5+2.5+7.1	1.13	1.42	1.42	4.03	3.25	8.00	9.60	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.35	8.00	442
	2.0+2.5+3.5+3.5	1.39	1.74	2.43	2.43	2.89	8.00	9.14	0.67	2.58	3.37	3.0	11.4	15.0	98	3.10	B	1290	A++	6.17	8.00	454
	2.0+2.5+3.5+4.2	1.31	1.64	2.30	2.75	2.98	8.00	9.47	0.67	2.58	3.61	3.0	11.4	16.0	98	3.10	B	1290	A++	6.18	8.00	454
	2.0+2.5+3.5+5.0	1.23	1.54	2.15	3.08	3.09	8.00	9.54	0.71	2.52	3.55	3.1	11.2	15.7	98	3.17	B	1260	A++	6.17	8.00	454
	2.0+2.5+3.5+6.0	1.14	1.43	2.00	3.43	3.23	8.00	9.60	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.27	8.00	447
	2.0+2.5+4.2+4.2	1.24	1.55	2.60	2.60	3.08	8.00	9.53	0.71	2.58	3.69	3.1	11.4	16.4	98	3.10	B	1290	A++	6.18	8.00	454
	2.0+2.5+4.2+5.0	1.17	1.46	2.45	2.92	3.19	8.00	9.59	0.71	2.52	3.63	3.1	11.2	16.1	98	3.17	B	1260	A++	6.18	8.00	454
	2.0+2.5+5.0+5.0	1.10	1.38	2.76	2.76	3.30	8.00	9.60	0.71	2.40	3.50	3.1	10.6	15.5	98	3.33	A	1200	A++	6.17	8.00	454
	2.0+3.5+3.5+3.5	1.28	2.24	2.24	2.24	3.03	8.00	9.23	0.67	2.58	3.30	3.0	11.4	14.6	98	3.10	B	1290	A++	6.11	8.00	459
	2.0+3.5+3.5+4.2	1.21	2.12	2.12	2.55	3.12	8.00	9.56	0.71	2.58	3.69	3.1	11.4	16.4	98	3.10	B	1290	A++	6.11	8.00	459
	2.0+3.5+3.5+5.0	1.14	2.00	2.00	2.86	3.23	8.00	9.60	0.71	2.52	3.63	3.1	11.2	16.1	98	3.17	B	1260	A++	6.11	8.00	459
	2.0+3.5+4.2+4.2	1.15	2.01	2.42	2.42	3.22	8.00	9.60	0.71	2.58	3.77	3.1	11.4	16.7	98	3.10	B	1290	A++	6.11	8.00	459
	2.5+2.5+2.5+2.5	1.94	1.94	1.94	1.94	2.68	7.76	8.82	0.60	2.45	3.14	2.7	10.9	13.9	98	3.17	B	1225	A++	6.27	7.76	433
	2.5+2.5+2.5+3.5	1.82	1.82	1.82	2.55	2.82	8.00	8.98	0.64	2.58	3.22	2.8	11.4	14.3	98	3.10	B	1290	A++	6.24	8.00	449
	2.5+2.5+2.5+4.2	1.71	1.71	1.71	2.87	2.92	8.00	9.32	0.67	2.58	3.53	3.0	11.4	15.7	98	3.10	B	1290	A++	6.24	8.00	449
	2.5+2.5+2.5+5.0	1.60	1.60	1.60	3.20	3.03	8.00	9.47	0.68	2.52	3.55	3.0	11.2	15.7	98	3.17	B	1260	A++	6.24	8.00	449
	2.5+2.5+2.5+6.0	1.48	1.48	1.48	3.56	3.16	8.00	9.58	0.72	2.28	3.29	3.2	10.1	14.6	98	3.51	A	1140	A++	6.35	8.00	442
	2.5+2.5+3.5+3.5	1.67	1.67	2.33	2.33	2.96	8.00	9.10	0.67	2.58	3.37	3.0	11.4	15.0	98	3.10	B	1290	A++	6.17	8.00	454
	2.5+2.5+3.5+4.2	1.57	1.57	2.20	2.65	3.05	8.00	9.50	0.67	2.58	3.69	3.0	11.4	16.4	98	3.10	B	1290	A++	6.18	8.00	454

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
4MXS80E3V3B	2.5+2.5+3.5+5.0	1,48	1,48	2,07	2,96	3,16	8,00	9,58	0,71	2,52	3,63	3,1	11,2	16,1	98	3,17	B	1260	A++	6.18	8.00	454
	2.5+2.5+3.5+6.0	1,38	1,38	1,93	3,31	3,30	8,00	9,60	0,72	2,28	3,29	3,2	10,1	14,6	98	3,51	A	1140	A++	6.27	8.00	447
	2.5+2.5+4.2+4.2	1,49	1,49	2,51	2,51	3,15	8,00	9,57	0,71	2,58	3,69	3,1	11,4	16,4	98	3,10	B	1290	A++	6.18	8.00	454
	2.5+2.5+4.2+5.0	1,41	1,41	2,37	2,82	3,26	8,00	9,60	0,71	2,52	3,63	3,1	11,2	16,1	98	3,17	B	1260	A++	6.18	8.00	454
	2.5+3.5+3.5+3.5	1,54	2,15	2,15	2,15	3,09	8,00	9,35	0,71	2,58	3,30	3,1	11,4	14,6	98	3,10	B	1290	A++	6.11	8.00	459
	2.5+3.5+3.5+4.2	1,46	2,04	2,04	2,45	3,19	8,00	9,59	0,71	2,58	3,77	3,1	11,4	16,7	98	3,10	B	1290	A++	6.11	8.00	459
	2.5+3.5+3.5+5.0	1,38	1,93	1,93	2,76	3,30	8,00	9,60	0,75	2,52	3,63	3,3	11,2	16,1	98	3,17	B	1260	A++	6.11	8.00	459
	2.5+3.5+4.2+4.2	1,39	1,94	2,33	2,33	3,29	8,00	9,60	0,75	2,58	3,77	3,3	11,4	16,7	98	3,10	B	1290	A++	6.11	8.00	459
	3.5+3.5+3.5+3.5	2,00	2,00	2,00	2,00	3,23	8,00	9,60	0,71	2,58	3,77	3,1	11,4	16,7	98	3,10	B	1290	A+	6.04	8.00	464

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
4MXS80E3V3B	1.5+1.5	1.83	1.83	---	---	1.42	3.66	5.36	0.44	0.89	1.31	2.0	3.9	5.8	98	4.11	A	A	3.87	3.37	1219	0.64
	1.5+2.0	1.83	2.44	---	---	1.48	4.27	5.36	0.44	1.01	1.31	2.0	4.5	5.8	98	4.23	A	A	3.85	3.42	1243	0.62
	1.5+2.5	1.83	3.05	---	---	1.62	4.88	7.09	0.48	1.17	1.90	2.1	5.2	8.4	98	4.17	A	A	3.84	3.44	1255	0.64
	1.5+3.5	1.83	4.26	---	---	1.90	6.09	7.23	0.55	1.64	2.08	2.4	7.3	9.2	98	3.71	A	A	3.85	3.72	1353	0.71
	1.5+4.2	1.83	5.12	---	---	2.10	6.95	8.28	0.59	1.95	2.56	2.6	8.7	11.4	98	3.56	B	A	3.83	3.75	1372	0.67
	1.5+5.0	1.83	6.09	---	---	2.33	7.92	8.72	0.53	2.10	2.42	2.4	9.3	10.7	98	3.77	A	A	3.81	3.68	1354	0.67
	1.5+6.0	1.79	7.14	---	---	2.61	8.93	9.67	0.55	2.30	2.64	2.4	10.2	11.7	98	3.88	A	A	3.85	4.15	1508	0.80
	1.5+7.1	1.67	7.93	---	---	2.90	9.60	9.90	0.58	2.48	2.63	2.6	11.0	11.7	98	3.87	A	A	3.84	4.35	1588	0.80
	2.0+2.0	2.44	2.44	---	---	1.62	4.88	6.55	0.34	1.17	1.74	1.5	5.2	7.7	98	4.17	A	A	3.84	3.47	1266	0.67
	2.0+2.5	2.44	3.05	---	---	1.76	5.49	6.85	0.37	1.34	1.82	1.6	5.9	8.1	98	4.10	A	A	3.82	3.50	1282	0.63
	2.0+3.5	2.44	4.26	---	---	2.05	6.70	7.35	0.43	1.86	2.13	1.9	8.3	9.4	98	3.60	A	A	3.84	3.80	1386	0.72
	2.0+4.2	2.44	5.11	---	---	2.24	7.55	8.53	0.47	2.22	2.56	2.1	9.8	11.4	98	3.40	B	A	3.84	3.83	1397	0.75
	2.0+5.0	2.44	6.09	---	---	2.47	8.53	8.72	0.55	2.32	2.42	2.4	10.3	10.7	98	3.68	A	A	3.83	3.76	1374	0.68
	2.0+6.0	2.32	6.95	---	---	2.74	9.27	9.67	0.57	2.44	2.64	2.5	10.8	11.7	98	3.80	A	A	3.85	4.25	1548	0.83
	2.0+7.1	2.11	7.49	---	---	3.04	9.60	10.36	0.61	2.48	2.89	2.7	11.0	12.8	98	3.87	A	A	3.87	4.47	1619	0.85
	2.5+2.5	3.04	3.04	---	---	1.90	6.08	7.16	0.41	1.69	2.14	1.8	7.5	9.5	98	3.60	B	A	3.82	3.53	1293	0.66
	2.5+3.5	3.05	4.26	---	---	2.19	7.31	8.53	0.55	2.13	2.67	2.4	9.4	11.8	98	3.43	B	A	3.82	3.84	1407	0.69
	2.5+4.2	3.04	5.12	---	---	2.39	8.16	9.01	0.57	2.46	2.90	2.5	10.9	12.9	98	3.32	C	A	3.82	3.87	1417	0.72
	2.5+5.0	2.98	5.95	---	---	2.61	8.93	9.31	0.57	2.52	2.72	2.5	11.2	12.1	98	3.54	B	A	3.84	3.80	1386	0.72
	2.5+6.0	2.82	6.78	---	---	2.88	9.60	10.10	0.59	2.65	2.94	2.6	11.8	13.0	98	3.62	A	A	3.84	4.31	1571	0.82
	2.5+7.1	2.50	7.10	---	---	3.17	9.60	10.36	0.63	2.51	2.93	2.8	11.1	13.0	98	3.82	A	A	3.86	4.53	1642	0.84
	3.5+3.5	4.26	4.26	---	---	2.47	8.52	9.18	0.59	2.70	3.04	2.6	12.0	13.5	98	3.16	D	A	3.84	4.25	1551	0.83
	3.5+4.2	4.11	4.94	---	---	2.66	9.05	9.77	0.61	2.98	3.47	2.7	13.2	15.4	98	3.04	D	A	3.83	4.30	1572	0.81
	3.5+5.0	3.95	5.65	---	---	2.88	9.60	9.92	0.62	2.77	2.93	2.8	12.3	13.0	98	3.47	B	A	3.83	4.20	1535	0.78
	3.5+6.0	3.54	6.06	---	---	3.15	9.60	10.34	0.61	2.49	2.90	2.7	11.0	12.9	98	3.86	A	A	3.86	4.84	1756	0.89
	3.5+7.1	3.17	6.43	---	---	3.45	9.60	10.37	0.67	2.43	2.84	3.0	10.8	12.6	98	3.95	A	A	3.89	5.11	1841	0.97
	4.2+4.2	4.78	4.78	---	---	2.85	9.55	9.60	0.63	2.65	2.65	2.8	11.8	11.8	98	3.60	A	A	3.82	4.34	1591	0.79
	4.2+5.0	4.38	5.22	---	---	3.07	9.60	10.12	0.64	2.61	2.87	2.8	11.6	12.7	98	3.68	A	A	3.84	4.25	1551	0.83
	4.2+6.0	3.95	5.65	---	---	3.34	9.60	10.35	0.65	2.44	2.84	2.9	10.8	12.6	98	3.93	A	A	3.90	4.90	1762	0.95
	4.2+7.1	3.57	6.03	---	---	3.63	9.60	10.38	0.70	2.43	2.83	3.1	10.8	12.6	98	3.95	A	A	3.88	5.17	1865	0.96
	5.0+5.0	4.80	4.80	---	---	3.28	9.60	10.24	0.67	2.52	2.83	3.0	11.2	12.6	98	3.81	A	A	3.84	4.15	1512	0.80
	5.0+6.0	4.36	5.24	---	---	3.55	9.60	10.47	0.66	2.40	2.80	2.9	10.6	12.4	98	4.00	A	A	3.87	4.78	1728	0.89
	5.0+7.1	3.97	5.63	---	---	3.85	9.60	10.50	0.70	2.38	2.79	3.1	10.6	12.4	98	4.03	A	A	3.89	5.04	1816	0.96
	6.0+6.0	4.80	4.80	---	---	3.82	9.60	10.70	0.67	2.32	2.77	3.0	10.3	12.3	98	4.14	A	A	3.92	5.56	1987	1.04
	6.0+7.1	4.40	5.20	---	---	4.12	9.60	10.73	0.71	2.31	2.76	3.1	10.2	12.2	98	4.16	A	A	3.93	5.88	2097	1.12
	7.1+7.1	4.80	4.80	---	---	4.42	9.60	10.77	0.78	2.25	2.70	3.5	10.0	12.0	98	4.27	A	A	3.95	6.23	2208	1.18
	1.5+1.5+1.5	1.83	1.83	1.83	---	1.76	5.49	7.22	0.43	1.16	1.71	1.9	5.1	7.6	98	4.73	A	A	3.83	4.23	1547	0.81
	1.5+1.5+2.0	1.83	1.83	2.44	---	1.90	6.09	7.22	0.44	1.34	1.71	2.0	5.9	7.6	98	4.54	A	A	3.84	4.35	1585	0.80
	1.5+1.5+2.5	1.83	1.83	3.05	---	2.05	6.70	7.29	0.46	1.52	1.71	2.0	6.7	7.6	98	4.41	A	A	3.86	4.40	1598	0.84
	1.5+1.5+3.5	1.83	1.83	4.26	---	2.33	7.92	9.03	0.50	1.90	2.30	2.2	8.4	10.2	98	4.17	A	A	3.87	4.95	1789	0.94
	1.5+1.5+4.2	1.82	1.82	5.09	---	2.53	8.72	9.03	0.52	2.20	2.29	2.3	9.8	10.2	98	3.96	A	A	3.87	5.01	1811	0.93
	1.5+1.5+5.0	1.74	1.74	5.79	---	2.74	9.27	9.99	0.53	2.25	2.54	2.4	10.0	11.3	98	4.12	A	A	3.88	4.89	1766	0.94
	1.5+1.5+6.0	1.60	1.60	6.40	---	3.01	9.60	10.71	0.54	2.27	2.72	2.4	10.1	12.1	98	4.23	A	A	3.89	5.70	2052	1.06
	1.5+1.5+7.1	1.43	1.43	6.75	---	3.31	9.60	10.74	0.57	2.26	2.71	2.5	10.0	12.0	98	4.25	A	A	3.94	6.03	2145	1.15
	1.5+2.0+2.0	1.83	2.44	2.44	---	2.05	6.70	7.22	0.46	1.52	1.71	2.0	6.7	7.6	98	4.41	A	A	3.84	4.47	1630	0.85
	1.5+2.0+2.5	1.83	2.44	3.05	---	2.19	7.31	8.41	0.48	1.71	2.12	2.1	7.6	9.4	98	4.27	A	A	3.84	4.53	1654	0.84
	1.5+2.0+3.5	1.83	2.44	4.27	---	2.47	8.53	9.03	0.52	2.11	2.30	2.3	9.4	10.2	98	4.04	A	A	3.87	5.10	1846	0.96
	1.5+2.0+4.2	1.76	2.35	4.94	---	2.66	9.06	9.69	0.54	2.29	2.58	2.4	10.2	11.4	98	3.96	A	A	3.86	5.16	1871	0.95
	1.5+2.0+5.0	1.69	2.26	5.65	---	2.88	9.60	9.99	0.55	2.39	2.54	2.4	10.6	11.3	98	4.02	A	A	3.88	5.03	1817	0.95
	1.5+2.0+6.0	1.52	2.02	6.06	---	3.15	9.60	10.71	0.56	2.27	2.72	2.5	10.1	12.1	98	4.23	A	A	3.93	5.87	2094	1.11
	1.5+2.0+7.1	1.36	1.81	6.43	---	3.45	9.60	10.74	0.60	2.26	2.71	2.7	10.0	12.0	98	4.25	A	A	3.93	6.22	2214	1.17
	1.5+2.5+2.5	1.83	3.05	3.05	---	2.33	7.92	8.93	0.50	1.94	2.30	2.2	8.6	10.2	98	4.08	A	A	3.83	4.59	1677	0.84
	1.5+2.5+3.5	1.79	2.98	4.17	---	2.61	8.93	9.68	0.54	2.25	2.58	2.4	10.0	11.4	98	3.97	A	A	3.87	5.18	1876	0.97
	1.5+2.5+4.2	1.72	2.87	4.82	---	2.80	9.41	9.69	0.56	2.43	2.58	2.5	10.8	11.4	98	3.87	A	A	3.89	5.24	1886	0.97
	1.5+2.5+5.0	1.60	2.67	5.33	---	3.01	9.60	10.48	0.57	2.39	2.80	2.5	10.6	12.4	98	4.02	A	A	3.87	5.11	1849	0.97
	1.5+2.5+6.0	1.44	2.40	5.76	---	3.28	9.60	10.71	0.58	2.27	2.72	2.6	10.1	12.1	98	4.23	A	A	3.94	5.96	2119	1.14
	1.5+2.5+7.1	1.30	2.16	6.14	---	3.58	9.60	10.74	0.62	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A	3.94	6.23	2215	1.18
	1.5+3.5+3.5	1.69	3.95	3.95	---	2.88	9.60	9.89	0.59	2.43	2.58	2.6	10.8	11.4	98	3.95	A	A	3.92	5.87	2098	1.11
	1.5+3.5+4.2	1.57	3.65	4.38	---	3.07	9.60	10.36	0.61	2.43	2.84	2.7	10.8	12.6	98	3.95	A	A	3.92	5.94	2121	1.12
	1.5+3.5+5.0	1.44	3.36	4.80	---	3.28	9.60	10.49	0.61	2.39	2.79	2.7	10.6	12.4	98	4.02	A	A	3.91	5.79	2074	1.09
	1.5+3.5+6.0	1.31	3.05	5.24	---	3.55	9.60	10.72	0.62	2.27	2.72	2.8	10.1	12.1	98	4.23	A	A	3.97	6.23	2200	1.18
	1.5+3.5+7.1	1.19	2.78	5.63	---	3.85	9.60	10.75	0.66	2.26	2.70	2.9	10.0	12.0	98	4.25	A	A+	4.00	6.23	2181	1.17
	1.5+4.2+4.2	1.45	4.07	4.07	---	3.26	9.60	10.37	0.63	2.43	2.84	2.8	10.8	12.6	98	3.95	A	A	3.92	6.01	2144	1.13
	1.5+4.2+5.0	1.35	3.77	4.49	---	3.47	9.60	10.49	0.66	2.39	2.79	2.9	10.6	12.4	98	4.02	A	A	3.92	5.86	2095	1.10
	1.5+4.2+6.0	1.23	3.45	4.92	---	3.74	9.60	10.72	0.64	2.27	2.71	2.8	10.1	12.0	98	4.23	A	A	3.97	6.23	2200	1.18
	1.5+4.2+7.1	1.13	3.15	5.33	---	4.04	9.60	10.76	0.71	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.00	6.23	2179	1.17
	1.5+5.0+5.0	1.25	4.17	4.17	---	3.69	9.60	10.62	0.66	2.30	2.75	2.9	10.2	12.2	98	4.17	A	A	3.89	5.71	2058	1.07
	1.5+5.0+6.0	1.15	3.84	4.61	---	3.96	9.60	10.85	0.67	2.18	2.72	3.0	9.7	12.1	98	4.40	A	A	3.96	6.23	2201	1.18
	1.5+5.0+7.1	1.06	3.53	5.01	---	4.26	9.60	10.88	0.71	2.17	2.71	3.1	9.6	12.0	98	4.42	A	A+	4.00	6.23	2180	1.17
	1.5+6.0+6.0	1.07	4.27	4.27	---	4.23	9.60	11.08	0.68	2.11	2.64	3.0	9.4	11.7	98	4.55	A	A+	4.06	6.23	2147	1.17
	2.0+2.0+2.0	2.43	2.43	2.43	---	2.19	7.29	8.33	0.48	1.76	2.14	2.1	7.8	9.5	98	4.14	A	A	3.83	4.59	1677	0.84
	2.0+2.0+2.5	2.44	2.44	3.04	---	2.33	7.92	8.93	0.50	1.96	2.32	2.2	8.7	10.3	98	4.04	A	A	3.87	4.66	1688	0.90
	2.0+2.0+3.5	2.38	2.38	4.17	---	2.61	8.93	9.68	0.54	2.29	2.63	2.4	10.2	11.7	98	3.90	A	A	3.89	5.26	1893	0.99
	2.0+2.0+4.2	2.30	2.30	4.81	---	2.80	9.41	9.69	0.56	2.48	2.63	2.5	11.0	11.7	98	3.79	A	A	3.88	5.32	1919	0.99
	2.0+2.0+5.0	2.13	2.13	5.34	---	3.01	9.60	10.48	0.57	2.39	2.80	2.5	10.6	12.4	98	4.02	A	A	3.90	5.19	1864	0.98
	2.0+2.0+6.0	1.92	1.92	5.76	---	3.28	9.60	10.71	0.58	2.27	2.72	2.6	10.1	12.1	98	4.23	A	A	3.94	6.06	2154	1.18
	2.0+2.0+7.1	1.73	1.73	6.14	---	3.58	9.60	10.74	0.62	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A	3.94	6.23	2214	1.18
	2.0+2.5+2.5	2.43	3.05	3.05	---	2.47	8.53	8.93	0.52	2.16	2.30	2.3	9.6	10.2	98	3.95	A	A	3.87	4.72	1710	0.90
	2.0+2.5+3.5	2.31	2.90	4.06	---	2.74	9.27	9.68	0.56	2.41	2.61	2.5	10.7	11.6	98	3.85	A	A	3.88	5.33	1921	1.00
	2.0+2.5+4.2	2.21	2.76	4.63	---	2.93	9.60	10.15	0.59	2.56	2.87	2.6	11.4	12.7	98	3.75	A	A	3.89	5.40	1946	1.01
	2.0+2.5+5.0	2.02	2.53	5.05	---	3.15	9.60	10.48	0.59	2.39	2.80	2.6	10.6	12.4	98	4.02	A	A	3.89	5.26	1893	0.99
	2.0+2.5+6.0	1.82	2.29	5.49	---	3.42	9.60	10.71	0.60	2.27	2.72	2.7	10.1	12.1	98	4.23	A	A	3.93	6.14	2185	1.15
	2.0+2.5+7.1	1.65	2.07	5.88	---	3.72	9.60	10.74	0.64	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A	3.97	6.23	2198	1.18

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
4MXS80E3V3B	2.0+3.5+3.5	2.14	3.73	3.73	---	3.01	9.60	10.35	0.59	2.43	2.84	2.6	10.8	12.6	98	3.95	A	A	3.93	6.05	2155	1.17
	2.0+3.5+4.2	1.99	3.46	4.15	---	3.20	9.60	10.36	0.63	2.43	2.84	2.8	10.8	12.6	98	3.95	A	A	3.94	6.13	2179	1.20
	2.0+3.5+5.0	1.83	3.20	4.57	---	3.42	9.60	10.49	0.63	2.39	2.80	2.8	10.6	12.4	98	4.02	A	A	3.93	5.97	2126	1.15
	2.0+3.5+6.0	1.67	2.92	5.01	---	3.69	9.60	10.72	0.64	2.27	2.72	2.8	10.1	12.1	98	4.23	A	A+	4.00	6.23	2180	1.17
	2.0+3.5+7.1	1.52	2.67	5.41	---	3.99	9.60	10.75	0.69	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.03	6.23	2166	1.17
	2.0+4.2+4.2	1.84	3.88	3.88	---	3.39	9.60	10.37	0.65	2.43	2.84	2.9	10.8	12.6	98	3.95	A	A	3.94	6.20	2205	1.21
	2.0+4.2+5.0	1.71	3.60	4.29	---	3.61	9.60	10.49	0.68	2.39	2.79	3.0	10.6	12.4	98	4.02	A	A	3.93	6.04	2152	1.16
	2.0+4.2+6.0	1.58	3.30	4.72	---	3.88	9.60	10.72	0.67	2.27	2.71	3.0	10.1	12.0	98	4.23	A	A+	4.00	6.23	2180	1.17
	2.0+4.2+7.1	1.45	3.03	5.12	---	4.18	9.60	10.76	0.73	2.26	2.70	3.2	10.0	12.0	98	4.25	A	A+	4.04	6.23	2161	1.17
	2.0+5.0+5.0	1.60	4.00	4.00	---	3.82	9.60	10.62	0.68	2.30	2.75	3.0	10.2	12.2	98	4.17	A	A	3.92	5.88	2100	1.12
	2.0+5.0+6.0	1.48	3.69	4.43	---	4.09	9.60	10.85	0.69	2.18	2.72	3.1	9.7	12.1	98	4.40	A	A	3.97	6.23	2198	1.18
	2.0+5.0+7.1	1.37	3.40	4.83	---	4.39	9.60	10.88	0.74	2.17	2.71	3.3	9.6	12.0	98	4.42	A	A+	4.00	6.23	2179	1.17
	2.0+6.0+6.0	1.38	4.11	4.11	---	4.36	9.60	11.08	0.70	2.11	2.64	3.1	9.4	11.7	98	4.55	A	A+	4.08	6.23	2141	1.17
	2.5+2.5+2.5	2.97	2.97	2.97	---	2.61	8.91	9.88	0.54	2.34	2.74	2.4	10.4	12.2	98	3.81	A	A	3.87	4.79	1736	0.90
	2.5+2.5+3.5	2.82	2.82	3.96	---	2.88	9.60	10.12	0.59	2.53	2.79	2.6	11.2	12.4	98	3.79	A	A	3.89	5.41	1949	1.02
	2.5+2.5+4.2	2.61	2.61	4.38	---	3.07	9.60	10.60	0.61	2.53	3.05	2.7	11.2	13.5	98	3.79	A	A	3.90	5.48	1965	1.02
	2.5+2.5+5.0	2.40	2.40	4.80	---	3.28	9.60	10.48	0.61	2.39	2.80	2.7	10.6	12.4	98	4.02	A	A	3.89	5.34	1925	1.01
	2.5+2.5+6.0	2.18	2.18	5.24	---	3.55	9.60	10.71	0.62	2.27	2.72	2.8	10.1	12.1	98	4.23	A	A	3.94	6.23	2217	1.18
	2.5+2.5+7.1	1.98	1.98	5.64	---	3.85	9.60	10.74	0.66	2.26	2.71	2.9	10.0	12.0	98	4.25	A	A	3.97	6.23	2197	1.18
	2.5+3.5+3.5	2.52	3.54	3.54	---	3.15	9.60	10.35	0.61	2.43	2.84	2.7	10.8	12.6	98	3.95	A	A	3.93	6.14	2189	1.15
	2.5+3.5+4.2	2.36	3.29	3.95	---	3.34	9.60	10.36	0.65	2.43	2.84	2.9	10.8	12.6	98	3.95	A	A	3.93	6.22	2217	1.17
	2.5+3.5+5.0	2.19	3.05	4.36	---	3.55	9.60	10.49	0.66	2.39	2.80	2.9	10.6	12.4	98	4.02	A	A	3.93	6.06	2157	1.18
	2.5+3.5+6.0	2.00	2.80	4.80	---	3.82	9.60	10.72	0.67	2.27	2.72	3.0	10.1	12.1	98	4.23	A	A+	4.01	6.23	2178	1.17
	2.5+3.5+7.1	1.84	2.56	5.20	---	4.12	9.60	10.75	0.71	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.04	6.23	2161	1.17
	2.5+4.2+4.2	2.20	3.70	3.70	---	3.53	9.60	10.37	0.68	2.43	2.84	3.0	10.8	12.6	98	3.95	A	A	3.93	6.23	2219	1.18
	2.5+4.2+5.0	2.06	3.45	4.09	---	3.74	9.60	10.49	0.70	2.39	2.79	3.1	10.6	12.4	98	4.02	A	A	3.94	6.13	2179	1.20
	2.5+4.2+6.0	1.90	3.17	4.53	---	4.01	9.60	10.72	0.69	2.27	2.71	3.1	10.1	12.0	98	4.23	A	A+	4.00	6.23	2181	1.17
	2.5+4.2+7.1	1.75	2.92	4.93	---	4.31	9.60	10.76	0.76	2.26	2.70	3.4	10.0	12.0	98	4.25	A	A+	4.07	6.23	2146	1.17
	2.5+5.0+5.0	1.92	3.84	3.84	---	3.96	9.60	10.62	0.71	2.30	2.75	3.1	10.2	12.2	98	4.17	A	A	3.93	5.97	2126	1.15
	2.5+5.0+6.0	1.77	3.56	4.27	---	4.23	9.60	10.85	0.72	2.18	2.72	3.2	9.7	12.1	98	4.40	A	A+	4.00	6.23	2180	1.17
	2.5+6.0+6.0	1.66	3.97	3.97	---	4.50	9.60	11.08	0.72	2.11	2.64	3.2	9.4	11.7	98	4.55	A	A+	4.10	6.23	2125	1.16
	3.5+3.5+3.5	3.20	3.20	3.20	---	3.42	9.60	10.36	0.65	2.43	2.84	2.9	10.8	12.6	98	3.95	A	A	3.99	6.23	2184	1.17
	3.5+3.5+4.2	3.00	3.00	3.60	---	3.61	9.60	10.37	0.70	2.43	2.84	3.1	10.8	12.6	98	3.95	A	A+	4.00	6.23	2184	1.17
	3.5+3.5+5.0	2.80	2.80	4.00	---	3.82	9.60	10.49	0.70	2.39	2.79	3.1	10.6	12.4	98	4.02	A	A	3.96	6.23	2202	1.18
	3.5+3.5+6.0	2.58	2.58	4.44	---	4.09	9.60	10.72	0.71	2.27	2.71	3.1	10.1	12.0	98	4.23	A	A+	4.07	6.23	2144	1.17
	3.5+3.5+7.1	2.38	2.38	4.84	---	4.39	9.60	10.76	0.76	2.26	2.70	3.4	10.0	12.0	98	4.25	A	A+	4.11	6.22	2119	1.21
	3.5+4.2+4.2	2.82	3.39	3.39	---	3.80	9.60	10.38	0.72	2.43	2.83	3.2	10.8	12.6	98	3.95	A	A+	4.00	6.23	2182	1.17
	3.5+4.2+5.0	2.65	3.17	3.78	---	4.01	9.60	10.50	0.75	2.39	2.79	3.3	10.6	12.4	98	4.02	A	A	3.99	6.23	2189	1.17
	3.5+4.2+6.0	2.45	2.94	4.21	---	4.28	9.60	10.73	0.74	2.26	2.71	3.3	10.0	12.0	98	4.25	A	A+	4.07	6.23	2143	1.16
	3.5+5.0+5.0	2.48	3.56	3.56	---	4.23	9.60	10.63	0.76	2.30	2.75	3.4	10.2	12.2	98	4.17	A	A	3.96	6.23	2203	1.18
	3.5+5.0+6.0	2.32	3.31	3.97	---	4.50	9.60	10.86	0.77	2.18	2.72	3.4	9.7	12.1	98	4.40	A	A+	4.06	6.23	2149	1.17
	4.2+4.2+4.2	3.20	3.20	3.20	---	3.99	9.60	10.38	0.75	2.42	2.83	3.3	10.7	12.6	98	3.97	A	A+	4.00	6.23	2183	1.17
	4.2+4.2+5.0	3.01	3.01	3.58	---	4.20	9.60	10.51	0.78	2.38	2.79	3.5	10.6	12.4	98	4.03	A	A+	4.00	6.23	2184	1.17
	4.2+4.2+6.0	2.80	2.80	4.00	---	4.47	9.60	10.74	0.79	2.26	2.71	3.5	10.0	12.0	98	4.25	A	A+	4.10	6.23	2129	1.16
	4.2+5.0+5.0	2.84	3.38	3.38	---	4.42	9.60	10.64	0.81	2.29	2.74	3.6	10.2	12.2	98	4.19	A	A	3.96	6.23	2202	1.18
	1.5+1.5+1.5+1.5	1.83	1.83	1.83	1.83	2.19	7.31	8.47	0.41	1.64	2.00	1.8	7.3	8.9	98	4.46	A	A	3.92	5.84	2085	1.14
	1.5+1.5+1.5+2.0	1.83	1.83	1.83	2.44	2.33	7.92	9.04	0.42	1.83	2.22	1.9	8.1	9.8	98	4.33	A	A	3.92	6.02	2149	1.14
	1.5+1.5+1.5+2.5	1.83	1.83	1.83	3.05	2.47	8.53	9.13	0.44	2.00	2.22	2.0	8.9	9.8	98	4.27	A	A	3.93	6.11	2176	1.18
	1.5+1.5+1.5+3.5	1.74	1.74	1.74	4.06	2.74	9.27	10.18	0.48	2.17	2.51	2.1	9.6	11.1	98	4.27	A	A+	4.00	6.23	2194	1.17
	1.5+1.5+1.5+4.2	1.66	1.66	1.66	4.63	2.93	9.60	10.73	0.51	2.26	2.71	2.3	10.0	12.0	98	4.25	A	A	3.99	6.23	2185	1.17
	1.5+1.5+1.5+5.0	1.52	1.52	1.52	5.05	3.15	9.60	10.86	0.52	2.18	2.72	2.3	9.7	12.1	98	4.40	A	A	3.97	6.23	2195	1.18
	1.5+1.5+1.5+6.0	1.37	1.37	1.37	5.49	3.42	9.60	11.09	0.52	2.10	2.64	2.3	9.3	11.7	98	4.57	A	A+	4.09	6.23	2135	1.17
	1.5+1.5+1.5+7.1	1.24	1.24	1.24	5.88	3.72	9.60	11.12	0.56	2.09	2.63	2.5	9.3	11.7	98	4.59	A	A+	4.13	6.22	2109	1.21
	1.5+1.5+2.0+2.0	1.83	1.83	2.44	2.44	2.47	8.53	9.04	0.44	2.04	2.22	2.0	9.1	9.8	98	4.18	A	A	3.95	6.20	2198	1.21
	1.5+1.5+2.0+2.5	1.79	1.79	2.38	2.98	2.61	8.93	9.87	0.46	2.13	2.51	2.0	9.4	11.1	98	4.19	A	A	3.95	6.23	2211	1.18
	1.5+1.5+2.0+3.5	1.69	1.69	2.26	3.95	2.88	9.60	10.18	0.52	2.27	2.51	2.3	10.1	11.1	98	4.23	A	A+	4.02	6.23	2172	1.17
	1.5+1.5+2.0+4.2	1.57	1.57	2.09	4.38	3.07	9.60	10.73	0.53	2.26	2.71	2.4	10.0	12.0	98	4.25	A	A+	4.02	6.23	2170	1.17
	1.5+1.5+2.0+5.0	1.44	1.44	1.92	4.80	3.28	9.60	10.86	0.54	2.18	2.72	2.4	9.7	12.1	98	4.40	A	A+	4.02	6.23	2172	1.17
	1.5+1.5+2.0+6.0	1.31	1.31	1.75	5.24	3.55	9.60	11.09	0.54	2.10	2.64	2.4	9.3	11.7	98	4.57	A	A+	4.11	6.23	2121	1.16
	1.5+1.5+2.0+7.1	1.19	1.19	1.59	5.63	3.85	9.60	11.12	0.58	2.09	2.63	2.6	9.3	11.7	98	4.59	A	A+	4.14	6.22	2102	1.21
	1.5+1.5+2.5+2.5	1.74	1.74	2.90	2.90	2.74	9.27	10.17	0.48	2.18	2.51	2.1	9.7	11.1	98	4.25	A	A	3.95	6.23	2211	1.18
	1.5+1.5+2.5+3.5	1.60	1.60	2.67	3.73	3.01	9.60	10.72	0.54	2.27	2.71	2.4	10.1	12.0	98	4.23	A	A+	4.02	6.23	2170	1.17
	1.5+1.5+2.5+4.2	1.48	1.48	2.47	4.16	3.20	9.60	10.73	0.55	2.26	2.71	2.4	10.0	12.0	98	4.25	A	A+	4.02	6.23	2168	1.17
	1.5+1.5+2.5+5.0	1.37	1.37	2.29	4.57	3.42	9.60	10.86	0.56	2.18	2.72	2.5	9.7	12.1	98	4.40	A	A+	4.02	6.23	2172	1.17
	1.5+1.5+2.5+6.0	1.25	1.25	2.09	5.01	3.69	9.60	11.09	0.57	2.10	2.64	2.5	9.3	11.7	98	4.57	A	A+	4.13	6.22	2109	1.21
	1.5+1.5+2.5+7.1	1.14	1.14	1.90	5.41	3.99	9.60	11.12	0.62	2.09	2.63	2.8	9.3	11.7	98	4.59	A	A+	4.14	6.22	2104	1.20
	1.5+1.5+3.5+3.5	1.44	1.44	3.36	3.36	3.28	9.60	10.73	0.58	2.26	2.71	2.6	10.0	12.0	98	4.25	A	A+	4.11	6.23	2125	1.16
	1.5+1.5+3.5+4.2	1.35	1.35	3.14	3.77	3.47	9.60	10.74	0.60	2.26	2.71	2.7	10.0	12.0	98	4.25	A	A+	4.12	6.22	2113	1.21
	1.5+1.5+3.5+5.0	1.25	1.25	2.92	4.17	3.69	9.60	10.86	0.62	2.17	2.71	2.8	9.6	12.0	98	4.42	A	A+	4.08	6.23	2139	1.16
	1.5+1.5+3.5+6.0	1.15	1.15	2.69	4.61	3.96	9.60	11.09	0.61	2.10	2.63	2.7	9.3	11.7	98	4.57	A	A+	4.19	6.22	2077	1.20
	1.5+1.5+3.5+7.1	1.06	1.06	2.47	5.01	4.26	9.60	11.13	0.67	2.09	2.62	3.0	9.3	11.6	98	4.59	A	A+	4.22	6.22	2066	1.20
	1.5+1.5+4.2+4.2	1.26	1.26	3.54	3.54	3.66	9.60	10.75	0.64	2.26	2.70	2.8	10.0	12.0	98	4.25	A	A+	4.12	6.22	2113	1.21
	1.5+1.5+4.2+5.0	1.18	1.18	3.30	3.93	3.88	9.60	10.87	0.64	2.17	2.71	2.8	9.6	12.0	98	4.42	A	A+	4.08	6.23	2137	1.16
	1.5+1.5+4.2+6.0	1.09	1.09	3.05	4.36	4.15	9.60	11.10	0.65	2.10	2.63	2.9	9.3	11.7	98	4.57	A	A+	4.21	6.22	2067	1.20
	1.5+1.5+4.2+7.1	1.01	1.01	2.82	4.77	4.45	9.60	11.13	0.69	2.09	2.62	3.1	9.3	11.6	98	4.59	A	A+	4.22	6.22	2062	1.19
	1.5+1.5+5.0+5.0	1.11	1.11	3.69	3.69	4.09	9.60	11.00	0.67	2.13	2.67	3.0	9.4	11.8	98	4.51	A	A+	4.08	6.23	2139	1.17
	1.5+1.5+5.0+6.0	1.03	1.03	3.43	4.11	4.36	9.60	11.23	0.67	2.01	2.59	3.0	8.9	11.5	98	4.78	A	A+	4.19	6.22	2077	1.20
	1.5+2.0+2.0+2.0	1.79	2.38	2.38	2.38	2.61	8.93	9.78	0.46	2.18	2.51	2.0	9.7	11.1	98	4.10	A	A	3.95	6.23	2211	1.18
	1.5+2.0+2.0+2.5	1.74	2.32	2.32	2.90	2.74	9.27	9.87	0.48	2.27	2.51	2.1	10.1	11.1	98	4.08	A	A	3.95	6.23	2209	1.18
	1.5+2.0+2.0+3.5	1.60	2.13	2.13	3.73	3.01	9.60	10.72	0.54	2.27	2.71	2.4	10.1	12.0	98	4.23	A	A+	4.02	6.23	2168	1.17
	1.5+2.0+2.0+4.2	1.48	1.98	1.98	4.16	3.20	9.60	10.73	0.55	2.26	2.71	2.4	10.0	12.0	98	4.25	A	A+	4.03	6.23	2166	1.17
	1.5+2.0+2.0+5.0	1.37	1.83	1.83	4.57	3.42	9.60	10.86	0.56	2.18	2.72	2.5	9.7	12.1	98	4.40	A	A+	4.02	6.23	2170	1.17
	1.5+2.0+2.0+6.0	1.25	1.67	1.67	5.01	3.69	9.60	11.09	0.57	2.10	2.64	2.5	9.3	11.7	98	4.57	A	A+	4.13	6.22	2107	1.21

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
4MXS80E3V3B	1.5+2.0+2.0+7.1	1.14	1.52	1.52	5.41	3.99	9.60	11.12	0.62	2.09	2.63	2.8	9.3	11.7	98	4.59	A	A+	4.17	6.22	2089	1.20
	1.5+2.0+2.5+2.5	1.69	2.26	2.82	2.82	2.88	9.60	10.17	0.52	2.27	2.51	2.3	10.1	11.1	98	4.23	A	A	3.98	6.23	2194	1.18
	1.5+2.0+2.5+3.5	1.52	2.02	2.53	3.54	3.15	9.60	10.72	0.56	2.27	2.71	2.5	10.1	12.0	98	4.23	A	A+	4.03	6.23	2166	1.17
	1.5+2.0+2.5+4.2	1.41	1.88	2.35	3.95	3.34	9.60	10.73	0.58	2.26	2.71	2.6	10.0	12.0	98	4.25	A	A+	4.03	6.23	2165	1.17
	1.5+2.0+2.5+5.0	1.31	1.75	2.18	4.36	3.55	9.60	10.86	0.60	2.18	2.72	2.7	9.7	12.1	98	4.40	A	A+	4.02	6.23	2168	1.17
	1.5+2.0+2.5+6.0	1.20	1.60	2.00	4.80	3.82	9.60	11.09	0.59	2.10	2.64	2.6	9.3	11.7	98	4.57	A	A+	4.14	6.22	2104	1.21
	1.5+2.0+2.5+7.1	1.10	1.47	1.83	5.20	4.12	9.60	11.12	0.65	2.09	2.63	2.9	9.3	11.7	98	4.59	A	A+	4.20	6.22	2074	1.20
	1.5+2.0+3.5+3.5	1.37	1.83	3.20	3.20	3.42	9.60	10.73	0.60	2.26	2.71	2.7	10.0	12.0	98	4.25	A	A+	4.12	6.22	2113	1.21
	1.5+2.0+3.5+4.2	1.29	1.71	3.00	3.60	3.61	9.60	10.74	0.62	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.13	6.22	2108	1.21
	1.5+2.0+3.5+5.0	1.20	1.60	2.80	4.00	3.82	9.60	10.86	0.64	2.17	2.71	2.8	9.6	12.0	98	4.42	A	A+	4.12	6.22	2113	1.21
	1.5+2.0+3.5+6.0	1.11	1.48	2.58	4.43	4.09	9.60	11.09	0.65	2.10	2.63	2.9	9.3	11.7	98	4.57	A	A+	4.22	6.22	2065	1.20
	1.5+2.0+3.5+7.1	1.02	1.36	2.38	4.83	4.39	9.60	11.13	0.69	2.09	2.62	3.1	9.3	11.6	98	4.59	A	A+	4.26	6.22	2047	1.19
	1.5+2.0+4.2+4.2	1.21	1.61	3.39	3.39	3.80	9.60	10.75	0.66	2.26	2.70	2.9	10.0	12.0	98	4.25	A	A+	4.14	6.22	2106	1.21
	1.5+2.0+4.2+5.0	1.13	1.51	3.17	3.78	4.01	9.60	10.87	0.67	2.17	2.71	3.0	9.6	12.0	98	4.42	A	A+	4.12	6.22	2113	1.21
	1.5+2.0+4.2+6.0	1.05	1.40	2.94	4.20	4.28	9.60	11.10	0.67	2.10	2.63	3.0	9.3	11.7	98	4.57	A	A+	4.21	6.22	2067	1.20
	1.5+2.0+5.0+5.0	1.07	1.42	3.56	3.56	4.23	9.60	11.00	0.69	2.13	2.67	3.1	9.4	11.8	98	4.51	A	A+	4.11	6.23	2125	1.16
	1.5+2.0+5.0+6.0	0.99	1.32	3.31	3.97	4.50	9.60	11.23	0.70	2.01	2.59	3.1	8.9	11.5	98	4.78	A	A+	4.21	6.22	2067	1.20
	1.5+2.5+2.5+2.5	1.60	2.67	2.67	2.67	3.01	9.60	10.71	0.54	2.27	2.72	2.4	10.1	12.1	98	4.23	A	A	3.98	6.23	2192	1.18
	1.5+2.5+2.5+3.5	1.44	2.40	2.40	3.36	3.28	9.60	10.72	0.58	2.27	2.71	2.6	10.1	12.0	98	4.23	A	A+	4.03	6.23	2165	1.17
	1.5+2.5+2.5+4.2	1.35	2.24	2.24	3.77	3.47	9.60	10.73	0.60	2.26	2.71	2.7	10.0	12.0	98	4.25	A	A+	4.07	6.23	2142	1.17
	1.5+2.5+2.5+5.0	1.25	2.09	2.09	4.17	3.69	9.60	10.86	0.62	2.18	2.72	2.8	9.7	12.1	98	4.40	A	A+	4.03	6.23	2167	1.17
	1.5+2.5+2.5+6.0	1.15	1.92	1.92	4.61	3.96	9.60	11.09	0.61	2.10	2.64	2.7	9.3	11.7	98	4.57	A	A+	4.14	6.22	2102	1.20
	1.5+2.5+2.5+7.1	1.06	1.76	1.76	5.01	4.26	9.60	11.12	0.67	2.09	2.63	3.0	9.3	11.7	98	4.59	A	A+	4.20	6.22	2074	1.20
	1.5+2.5+3.5+3.5	1.31	2.18	3.05	3.05	3.55	9.60	10.73	0.62	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.13	6.22	2108	1.21
	1.5+2.5+3.5+4.2	1.23	2.05	2.87	3.45	3.74	9.60	10.74	0.64	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.14	6.22	2106	1.21
	1.5+2.5+3.5+5.0	1.15	1.92	2.69	3.84	3.96	9.60	10.86	0.67	2.17	2.71	3.0	9.6	12.0	98	4.42	A	A+	4.13	6.22	2111	1.21
	1.5+2.5+3.5+6.0	1.07	1.78	2.49	4.27	4.23	9.60	11.09	0.67	2.10	2.63	3.0	9.3	11.7	98	4.57	A	A+	4.21	6.22	2067	1.20
	1.5+2.5+4.2+4.2	1.16	1.94	3.25	3.25	3.93	9.60	10.75	0.69	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.13	6.22	2107	1.20
	1.5+2.5+4.2+5.0	1.09	1.82	3.05	3.64	4.15	9.60	10.87	0.69	2.17	2.71	3.1	9.6	12.0	98	4.42	A	A+	4.13	6.22	2108	1.21
	1.5+2.5+4.2+6.0	1.01	1.69	2.84	4.06	4.42	9.60	11.10	0.70	2.10	2.63	3.1	9.3	11.7	98	4.57	A	A+	4.22	6.22	2062	1.20
	1.5+2.5+5.0+5.0	1.03	1.71	3.43	3.43	4.36	9.60	11.00	0.71	2.13	2.67	3.1	9.4	11.8	98	4.51	A	A+	4.12	6.22	2113	1.21
	1.5+3.5+3.5+3.5	1.20	2.80	2.80	2.80	3.82	9.60	10.74	0.66	2.26	2.71	2.9	10.0	12.0	98	4.25	A	A+	4.21	6.22	2069	1.20
	1.5+3.5+3.5+4.2	1.13	2.65	2.65	3.17	4.01	9.60	10.75	0.69	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.21	6.22	2071	1.20
	1.5+3.5+3.5+5.0	1.07	2.49	2.49	3.56	4.23	9.60	10.87	0.71	2.17	2.71	3.1	9.6	12.0	98	4.42	A	A+	4.21	6.22	2071	1.20
	1.5+3.5+3.5+6.0	0.99	2.32	2.32	3.97	4.50	9.60	11.10	0.72	2.10	2.63	3.2	9.3	11.7	98	4.57	A	A+	4.28	6.22	2036	1.19
	1.5+3.5+4.2+4.2	1.07	2.51	3.01	3.01	4.20	9.60	10.75	0.73	2.26	2.70	3.2	10.0	12.0	98	4.25	A	A+	4.21	6.22	2071	1.20
	1.5+3.5+4.2+5.0	1.01	2.37	2.84	3.38	4.42	9.60	10.88	0.74	2.17	2.71	3.3	9.6	12.0	98	4.42	A	A+	4.21	6.22	2071	1.20
	1.5+4.2+4.2+4.2	1.02	2.86	2.86	2.86	4.39	9.60	10.76	0.76	2.25	2.70	3.4	10.0	12.0	98	4.27	A	A+	4.22	6.22	2066	1.19
	2.0+2.0+2.0+2.0	2.32	2.32	2.32	2.32	2.74	9.28	9.78	0.48	2.27	2.51	2.1	10.1	11.1	98	4.09	A	A	3.98	6.23	2194	1.18
	2.0+2.0+2.0+2.5	2.26	2.26	2.26	2.82	2.88	9.60	9.92	0.52	2.36	2.51	2.3	10.5	11.1	98	4.07	A	A	3.98	6.23	2192	1.18
	2.0+2.0+2.0+3.5	2.02	2.02	2.02	3.54	3.15	9.60	10.72	0.56	2.27	2.71	2.5	10.1	12.0	98	4.23	A	A+	4.05	6.23	2152	1.17
	2.0+2.0+2.0+4.2	1.88	1.88	1.88	3.96	3.34	9.60	10.73	0.58	2.26	2.71	2.6	10.0	12.0	98	4.25	A	A+	4.07	6.23	2142	1.17
	2.0+2.0+2.0+5.0	1.75	1.75	1.75	4.35	3.55	9.60	10.86	0.60	2.18	2.72	2.7	9.7	12.1	98	4.40	A	A+	4.03	6.23	2167	1.17
	2.0+2.0+2.0+6.0	1.60	1.60	1.60	4.80	3.82	9.60	11.09	0.59	2.10	2.64	2.6	9.3	11.7	98	4.57	A	A+	4.14	6.22	2102	1.20
	2.0+2.0+2.0+7.1	1.47	1.47	1.47	5.19	4.12	9.60	11.12	0.65	2.09	2.63	2.9	9.3	11.7	98	4.59	A	A+	4.20	6.22	2074	1.20
	2.0+2.0+2.5+2.5	2.13	2.13	2.67	2.67	3.01	9.60	10.71	0.54	2.27	2.72	2.4	10.1	12.1	98	4.23	A	A	3.98	6.23	2191	1.18
	2.0+2.0+2.5+3.5	1.92	1.92	2.40	3.36	3.28	9.60	10.72	0.58	2.27	2.71	2.6	10.1	12.0	98	4.23	A	A+	4.08	6.23	2140	1.17
	2.0+2.0+2.5+4.2	1.79	1.79	2.25	3.77	3.47	9.60	10.73	0.60	2.26	2.71	2.7	10.0	12.0	98	4.25	A	A+	4.08	6.23	2140	1.17
	2.0+2.0+2.5+5.0	1.67	1.67	2.09	4.17	3.69	9.60	10.86	0.62	2.18	2.72	2.8	9.7	12.1	98	4.40	A	A+	4.05	6.23	2152	1.17
	2.0+2.0+2.5+6.0	1.54	1.54	1.92	4.60	3.96	9.60	11.09	0.61	2.10	2.64	2.7	9.3	11.7	98	4.57	A	A+	4.14	6.22	2102	1.20
	2.0+2.0+2.5+7.1	1.41	1.41	1.76	5.02	4.26	9.60	11.12	0.67	2.09	2.63	3.0	9.3	11.7	98	4.59	A	A+	4.20	6.22	2072	1.20
	2.0+2.0+3.5+3.5	1.75	1.75	3.05	3.05	3.55	9.60	10.73	0.62	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.14	6.22	2106	1.20
	2.0+2.0+3.5+4.2	1.64	1.64	2.87	3.45	3.74	9.60	10.74	0.64	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.13	6.22	2107	1.20
	2.0+2.0+3.5+5.0	1.54	1.54	2.69	3.83	3.96	9.60	10.86	0.67	2.17	2.71	3.0	9.6	12.0	98	4.42	A	A+	4.13	6.22	2108	1.21
	2.0+2.0+3.5+6.0	1.42	1.42	2.49	4.27	4.23	9.60	11.09	0.67	2.10	2.63	3.0	9.3	11.7	98	4.57	A	A+	4.22	6.22	2062	1.20
	2.0+2.0+4.2+4.2	1.55	1.55	3.25	3.25	3.93	9.60	10.75	0.66	2.26	2.70	2.9	10.0	12.0	98	4.25	A	A+	4.16	6.22	2092	1.20
	2.0+2.0+4.2+5.0	1.45	1.45	3.06	3.64	4.15	9.60	10.87	0.69	2.17	2.71	3.1	9.6	12.0	98	4.42	A	A+	4.14	6.22	2106	1.21
	2.0+2.0+4.2+6.0	1.35	1.35	2.84	4.06	4.42	9.60	11.10	0.70	2.10	2.63	3.1	9.3	11.7	98	4.57	A	A+	4.22	6.22	2062	1.19
	2.0+2.0+5.0+5.0	1.37	1.37	3.43	3.43	4.36	9.60	11.00	0.72	2.13	2.67	3.2	9.4	11.8	98	4.51	A	A+	4.13	6.22	2111	1.21
	2.0+2.5+2.5+2.5	2.01	2.53	2.53	2.53	3.15	9.60	10.71	0.56	2.27	2.72	2.5	10.1	12.1	98	4.23	A	A	3.98	6.23	2189	1.18
	2.0+2.5+2.5+3.5	1.82	2.29	2.29	3.20	3.42	9.60	10.72	0.60	2.27	2.71	2.7	10.1	12.0	98	4.23	A	A+	4.08	6.23	2140	1.17
	2.0+2.5+2.5+4.2	1.72	2.14	2.14	3.60	3.61	9.60	10.73	0.62	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.08	6.23	2140	1.17
	2.0+2.5+2.5+5.0	1.60	2.00	2.00	4.00	3.82	9.60	10.86	0.65	2.18	2.72	2.9	9.7	12.1	98	4.40	A	A+	4.08	6.23	2140	1.17
	2.0+2.5+2.5+6.0	1.47	1.85	1.85	4.43	4.09	9.60	11.09	0.65	2.10	2.64	2.9	9.3	11.7	98	4.57	A	A+	4.17	6.22	2089	1.20
	2.0+2.5+2.5+7.1	1.37	1.70	1.70	4.83	4.39	9.60	11.12	0.69	2.09	2.63	3.1	9.3	11.7	98	4.59	A	A+	4.21	6.22	2070	1.20
	2.0+2.5+3.5+3.5	1.67	2.09	2.92	2.92	3.69	9.60	10.73	0.64	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.14	6.22	2105	1.20
	2.0+2.5+3.5+4.2	1.58	1.97	2.75	3.30	3.88	9.60	10.74	0.66	2.26	2.71	2.9	10.0	12.0	98	4.25	A	A+	4.16	6.22	2092	1.20
	2.0+2.5+3.5+5.0	1.48	1.85	2.58	3.69	4.09	9.60	10.86	0.69	2.18	2.71	3.1	9.7	12.0	98	4.40	A	A+	4.14	6.22	2106	1.20
	2.0+2.5+3.5+6.0	1.38	1.71	2.40	4.11	4.36	9.60	11.09	0.70	2.10	2.63	3.1	9.3	11.7	98	4.57	A	A+	4.22	6.22	2062	1.19
	2.0+2.5+4.2+4.2	1.50	1.86	3.12	3.12	4.07	9.60	10.75	0.69	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.17	6.22	2088	1.20
	2.0+2.5+4.2+5.0	1.41	1.75	2.94	3.50	4.28	9.60	10.87	0.71	2.17	2.71	3.1	9.6	12.0	98	4.42	A	A+	4.13	6.22	2107	1.20
	2.0+2.5+5.0+5.0	1.32	1.66	3.31	3.31	4.50	9.60	11.00	0.74	2.13	2.67	3.3	9.4	11.8	98	4.51	A	A+	4.13	6.22	2108	1.21
	2.0+3.5+3.5+3.5	1.53	2.69	2.69	2.69	3.96	9.60	10.74	0.69	2.26	2.71	3.1	10.0	12.0	98	4.25	A	A+	4.22	6.22	2066	1.20
	2.0+3.5+3.5+4.2	1.45	2.55	2.55	3.05	4.15	9.60	10.75	0.71	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.22	6.22	2066	1.19
	2.0+3.5+3.5+5.0	1.37	2.40	2.40	3.43	4.36	9.60	10.87	0.74	2.17	2.71	3.3	9.6	12.0	98	4.42	A	A+	4.21	6.22	2071	1.20
	2.0+3.5+4.2+4.2	1.38	2.42	2.90	2.90	4.34	9.60	10.75	0.76	2.26	2.70	3.4	10.0	12.0	98	4.25	A	A+	4.24	6.22	2052	1.19
	2.5+2.5+2.5+2.5	2.40	2.40	2.40	2.40	3.28	9.60	10.71	0.58	2.27	2.72	2.6	10.1	12.1	98	4.23	A	A+	4.00	6.23	2181	1.17
	2.5+2.5+2.5+3.5	2.18	2.18	2.18	3.06	3.55	9.60	10.72	0.62	2.27	2.71	2.8	10.1	12.0	98	4.23	A	A+	4.08	6.23	2140	1.17
	2.5+2.5+2.5+4.2	2.05	2.05	2.05	3.45	3.74	9.60	10.73	0.64	2.26	2.71	2.8	10.0	12.0	98	4.25	A	A+	4.09	6.23	2135	1.17
	2.5+2.5+2.5+5.0	1.92	1.92	1.92	3.84	3.96	9.60	10.86	0.67	2.18	2.72	3.0	9.7	12.1	98	4.40	A	A+	4.08	6.23	2140	1.17
	2.5+2.5+2.5+6.0	1.78	1.78	1.78	4.26	4.23	9.60	11.09	0.68	2.10	2.64	3.0	9.3	11.7	98	4.57	A	A+	4.20	6.22	2074	1.20
	2.5+2.5+3.5+3.5	2.00	2.00	2.80	2.80	3.82	9.60	10.73	0.67	2.26	2.71	3.0	10.0	12.0	98	4.25	A	A+	4.16	6.22	2092	1.20
	2.5+2.5+3.5+4.2	1.89	1.89	2.65	3.17	4.01	9.60	10.74	0.69	2.26	2.71	3.1	10.0	12.0	98	4.25	A	A+	4.19	6.22	2078	1.20

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)				Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
4MXS80E3V3B	2.5+2.5+3.5+5.0	1.78	1.78	2.49	3.55	4.23	9.60	10.86	0.71	2.18	2.71	3.1	9.7	12.0	98	4.40	A	A+	4.14	6.22	2105	1.20
	2.5+2.5+3.5+6.0	1.66	1.66	2.32	3.96	4.50	9.60	11.09	0.72	2.10	2.63	3.2	9.3	11.7	98	4.57	A	A+	4.26	6.22	2047	1.19
	2.5+2.5+4.2+4.2	1.79	1.79	3.01	3.01	4.20	9.60	10.75	0.71	2.26	2.70	3.1	10.0	12.0	98	4.25	A	A+	4.19	6.22	2078	1.20
	2.5+2.5+4.2+5.0	1.69	1.69	2.85	3.37	4.42	9.60	10.87	0.76	2.17	2.71	3.4	9.6	12.0	98	4.42	A	A+	4.16	6.22	2092	1.20
	2.5+3.5+3.5+3.5	1.86	2.58	2.58	2.58	4.09	9.60	10.74	0.71	2.26	2.71	3.1	10.0	12.0	98	4.25	A	A+	4.22	6.22	2066	1.19
	2.5+3.5+3.5+4.2	1.76	2.45	2.45	2.94	4.28	9.60	10.75	0.74	2.26	2.70	3.3	10.0	12.0	98	4.25	A	A+	4.25	6.22	2051	1.19
	2.5+3.5+3.5+5.0	1.65	2.32	2.32	3.31	4.50	9.60	10.87	0.76	2.17	2.71	3.4	9.6	12.0	98	4.42	A	A+	4.22	6.22	2066	1.20
	2.5+3.5+4.2+4.2	1.67	2.33	2.80	2.80	4.47	9.60	10.75	0.78	2.26	2.70	3.5	10.0	12.0	98	4.25	A	A+	4.25	6.22	2051	1.19
	3.5+3.5+3.5+3.5	2.40	2.40	2.40	2.40	4.36	9.60	10.75	0.76	2.26	2.70	3.4	10.0	12.0	98	4.25	A	A+	4.31	6.22	2021	1.19

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
5MXS90E3V3B	1.5+1.5	1.50	1.50	---	---	---	2.03	3.00	4.03	0.46	0.78	1.14	2.0	3.5	5.1	98	3.85	A	390	A	5.26	3.00	200
	1.5+2.0	1.50	2.00	---	---	---	2.05	3.50	4.50	0.50	0.94	1.34	2.2	4.2	5.9	98	3.72	A	470	A	5.49	3.50	224
	1.5+2.5	1.50	2.50	---	---	---	2.11	4.00	4.96	0.46	1.06	1.38	2.0	4.7	6.1	98	3.77	A	530	A+	5.66	4.00	248
	1.5+3.5	1.50	3.50	---	---	---	2.22	5.00	5.82	0.46	1.43	1.79	2.0	6.3	7.9	98	3.50	A	715	A+	5.67	5.00	309
	1.5+4.2	1.50	4.20	---	---	---	2.29	5.70	6.37	0.46	1.75	2.09	2.0	7.8	9.3	98	3.26	A	875	A+	5.74	5.70	348
	1.5+5.0	1.50	5.00	---	---	---	2.38	6.50	6.97	0.50	2.10	2.42	2.2	9.3	10.7	98	3.10	B	1050	A+	5.74	6.50	397
	1.5+6.0	1.45	5.79	---	---	---	2.51	7.24	7.64	0.54	2.34	2.57	2.4	10.4	11.4	98	3.09	B	1170	A++	6.14	7.24	413
	1.5+7.1	1.33	6.30	---	---	---	2.67	7.63	8.29	0.57	2.57	3.00	2.5	11.4	13.3	98	2.97	C	1285	A+	6.08	7.63	439
	2.0+2.0	2.00	2.00	---	---	---	2.11	4.00	5.30	0.50	1.14	1.79	2.2	5.1	7.9	98	3.51	A	570	A+	5.68	4.00	247
	2.0+2.5	2.00	2.50	---	---	---	2.16	4.50	5.73	0.50	1.30	1.79	2.2	5.8	7.9	98	3.46	A	650	A+	5.80	4.50	272
	2.0+3.5	2.00	3.50	---	---	---	2.27	5.50	6.36	0.50	1.70	2.09	2.2	7.5	9.3	98	3.24	A	850	A+	5.77	5.50	334
	2.0+4.2	2.00	4.20	---	---	---	2.35	6.20	6.75	0.50	1.99	2.35	2.2	8.8	10.4	98	3.12	B	995	A+	5.86	6.20	371
	2.0+5.0	2.00	5.00	---	---	---	2.44	7.00	7.31	0.50	2.42	2.59	2.2	10.7	11.5	98	2.89	C	1210	A+	5.71	7.00	430
	2.0+6.0	1.86	5.56	---	---	---	2.58	7.42	7.96	0.54	2.45	2.81	2.4	10.9	12.5	98	3.03	B	1225	A++	6.10	7.42	426
	2.0+7.1	1.71	6.09	---	---	---	2.74	7.80	8.47	0.57	2.69	3.13	2.5	11.9	13.9	98	2.90	C	1345	A++	6.10	7.80	448
	2.5+2.5	2.50	2.50	---	---	---	2.22	5.00	6.20	0.46	1.39	1.99	2.0	6.2	8.8	98	3.60	A	695	A+	5.84	5.00	300
	2.5+3.5	2.50	3.50	---	---	---	2.33	6.00	6.60	0.50	1.89	2.25	2.2	8.4	10.0	98	3.17	B	945	A+	6.01	6.00	350
	2.5+4.2	2.50	4.20	---	---	---	2.41	6.70	7.11	0.50	2.30	2.57	2.2	10.2	11.4	98	2.91	C	1150	A+	5.82	6.70	404
	2.5+5.0	2.41	4.83	---	---	---	2.51	7.24	7.64	0.53	2.59	2.82	2.4	11.5	12.5	98	2.80	D	1295	A+	5.68	7.24	447
	2.5+6.0	2.23	5.36	---	---	---	2.66	7.59	8.25	0.57	2.57	3.00	2.5	11.4	13.3	98	2.95	C	1285	A++	6.12	7.59	435
	2.5+7.1	2.08	5.90	---	---	---	2.82	7.98	8.47	0.60	2.81	3.13	2.7	12.5	13.9	98	2.84	C	1405	A++	6.10	7.98	458
	3.5+3.5	3.50	3.50	---	---	---	2.44	7.00	7.31	0.53	2.52	2.69	2.4	11.2	11.9	98	2.78	D	1260	A+	5.67	7.00	433
	3.5+4.2	3.32	3.99	---	---	---	2.54	7.31	7.66	0.53	2.69	2.92	2.4	11.9	13.0	98	2.72	D	1345	A+	5.62	7.39	460
	3.5+5.0	3.13	4.46	---	---	---	2.66	7.59	7.83	0.57	2.82	2.94	2.5	12.5	13.0	98	2.69	D	1410	A	5.58	7.59	476
	3.5+6.0	2.93	5.01	---	---	---	2.80	7.94	8.45	0.60	2.81	3.13	2.7	12.5	13.9	98	2.83	C	1405	A+	6.03	7.94	461
	3.5+7.1	2.75	5.58	---	---	---	2.96	8.33	8.47	0.64	3.07	3.13	2.8	13.6	13.9	98	2.71	D	1535	A+	6.00	8.33	487
	4.2+4.2	3.78	3.78	---	---	---	2.64	7.56	7.67	0.56	2.86	2.92	2.5	12.7	13.0	98	2.64	D	1430	A+	5.66	7.40	458
	4.2+5.0	3.58	4.26	---	---	---	2.76	7.84	8.01	0.60	2.94	3.07	2.7	13.0	13.6	98	2.67	D	1470	A	5.56	7.70	485
	4.2+6.0	3.37	4.82	---	---	---	2.91	8.19	8.46	0.60	2.94	3.13	2.7	13.0	13.9	98	2.79	D	1470	A+	5.98	8.19	480
	4.2+7.1	3.19	5.39	---	---	---	3.07	8.58	8.66	0.64	3.26	3.26	2.8	14.5	14.5	98	2.63	D	1630	A+	6.01	8.34	486
	5.0+5.0	4.06	4.06	---	---	---	2.88	8.12	8.18	0.60	3.09	3.19	2.7	13.7	14.2	98	2.63	D	1545	A	5.55	8.12	513
	5.0+6.0	3.85	4.62	---	---	---	3.02	8.47	8.64	0.64	3.09	3.25	2.8	13.7	14.4	98	2.74	D	1545	A+	5.91	8.47	502
	5.0+7.1	3.66	5.20	---	---	---	3.19	8.86	8.88	0.67	3.36	3.39	3.0	14.9	15.0	98	2.64	D	1680	A+	5.90	8.86	526
	6.0+6.0	4.41	4.41	---	---	---	3.17	8.82	9.27	0.64	3.08	3.36	2.8	13.7	14.9	98	2.86	C	1540	A++	6.22	8.82	497
	6.0+7.1	4.12	4.88	---	---	---	3.33	9.00	9.29	0.68	3.08	3.36	3.0	13.7	14.9	98	2.92	C	1540	A++	6.21	9.00	508
	7.1+7.1	4.50	4.50	---	---	---	3.49	9.00	9.31	0.71	3.02	3.36	3.1	13.4	14.9	98	2.98	C	1510	A++	6.23	9.00	506
	1.5+1.5+1.5	1.50	1.50	1.50	---	---	2.16	4.50	5.40	0.47	1.05	1.39	2.1	4.7	6.2	98	4.29	A	525	A+	5.88	4.50	268
	1.5+1.5+2.0	1.50	1.50	2.00	---	---	2.22	5.00	5.82	0.47	1.22	1.57	2.1	5.4	7.0	98	4.10	A	610	A+	6.02	5.00	291
	1.5+1.5+2.5	1.50	1.50	2.50	---	---	2.27	5.50	6.22	0.47	1.43	1.76	2.1	6.3	7.8	98	3.85	A	715	A+	6.09	5.50	317
	1.5+1.5+3.5	1.50	1.50	3.50	---	---	2.38	6.50	6.97	0.50	1.91	2.17	2.2	8.5	9.6	98	3.40	A	955	A++	6.12	6.50	372
	1.5+1.5+4.2	1.49	1.49	4.17	---	---	2.46	7.14	7.45	0.50	2.28	2.45	2.2	10.1	10.9	98	3.13	B	1140	A+	6.06	7.14	413
	1.5+1.5+5.0	1.39	1.39	4.64	---	---	2.58	7.42	7.96	0.54	2.35	2.71	2.4	10.4	12.0	98	3.16	B	1175	A+	6.04	7.42	430
	1.5+1.5+6.0	1.30	1.30	5.18	---	---	2.73	7.77	8.53	0.58	2.38	2.82	2.6	10.6	12.5	98	3.26	A	1190	A++	6.32	7.77	430
	1.5+1.5+7.1	1.21	1.21	5.74	---	---	2.89	8.16	9.07	0.61	2.56	3.22	2.7	11.4	14.3	98	3.19	B	1280	A++	6.32	8.16	452
	1.5+2.0+2.0	1.50	2.00	2.00	---	---	2.27	5.50	6.22	0.50	1.43	1.76	2.2	6.3	7.8	98	3.85	A	715	A++	6.13	5.50	315
	1.5+2.0+2.5	1.50	2.00	2.50	---	---	2.33	6.00	6.60	0.47	1.66	1.96	2.1	7.4	8.7	98	3.61	A	830	A++	6.17	6.00	341
	1.5+2.0+3.5	1.50	2.00	3.50	---	---	2.44	7.00	7.31	0.50	2.17	2.40	2.2	9.6	10.6	98	3.23	A	1085	A++	6.14	7.00	399
	1.5+2.0+4.2	1.42	1.90	3.99	---	---	2.54	7.31	7.77	0.54	2.40	2.69	2.4	10.6	11.9	98	3.05	B	1200	A++	6.11	7.31	419
	1.5+2.0+5.0	1.34	1.79	4.46	---	---	2.66	7.59	8.25	0.54	2.47	2.89	2.4	11.0	12.8	98	3.07	B	1235	A+	6.08	7.59	437
	1.5+2.0+6.0	1.25	1.67	5.01	---	---	2.80	7.94	8.78	0.58	2.44	3.01	2.6	10.8	13.4	98	3.25	A	1220	A++	6.32	7.94	440
	1.5+2.0+7.1	1.18	1.57	5.58	---	---	2.96	8.33	9.12	0.61	2.69	3.22	2.7	11.9	14.3	98	3.10	B	1345	A++	6.31	8.33	462
	1.5+2.5+2.5	1.50	2.50	2.50	---	---	2.38	6.50	6.97	0.50	1.91	2.17	2.2	8.5	9.6	98	3.40	A	955	A++	6.25	6.50	364
	1.5+2.5+3.5	1.45	2.41	3.38	---	---	2.51	7.24	7.64	0.54	2.34	2.57	2.4	10.4	11.4	98	3.09	B	1170	A++	6.11	7.24	416
	1.5+2.5+4.2	1.37	2.28	3.84	---	---	2.61	7.49	8.08	0.54	2.45	2.88	2.4	10.9	12.8	98	3.06	B	1225	A+	6.09	7.49	431
	1.5+2.5+5.0	1.30	2.16	4.32	---	---	2.73	7.77	8.53	0.57	2.59	3.09	2.5	11.5	13.7	98	3.00	C	1295	A+	6.07	7.77	449
	1.5+2.5+6.0	1.22	2.03	4.87	---	---	2.88	8.12	9.03	0.58	2.56	3.22	2.6	11.4	14.3	98	3.17	B	1280	A++	6.32	8.12	450
	1.5+2.5+7.1	1.15	1.92	5.44	---	---	3.04	8.51	9.30	0.61	2.82	3.36	2.7	12.5	14.9	98	3.02	B	1410	A++	6.28	8.51	475
	1.5+3.5+3.5	1.34	3.13	3.13	---	---	2.66	7.59	8.25	0.57	2.57	3.00	2.5	11.4	13.3	98	2.95	C	1285	A+	6.02	7.59	441
	1.5+3.5+4.2	1.28	2.98	3.58	---	---	2.76	7.84	8.48	0.57	2.69	3.13	2.5	11.9	13.9	98	2.91	C	1345	A+	5.99	7.84	459
	1.5+3.5+5.0	1.22	2.84	4.06	---	---	2.88	8.12	8.66	0.61	2.83	3.16	2.7	12.6	14.0	98	2.87	C	1415	A+	5.93	8.12	480
	1.5+3.5+6.0	1.16	2.70	4.62	---	---	3.02	8.47	9.11	0.61	2.82	3.22	2.7	12.5	14.3	98	3.00	B	1410	A++	6.25	8.47	475
	1.5+3.5+7.1	1.10	2.56	5.20	---	---	3.19	8.86	9.31	0.64	3.08	3.36	2.8	13.7	14.9	98	2.88	C	1540	A++	6.18	8.86	502
	1.5+4.2+4.2	1.23	3.43	3.43	---	---	2.86	8.09	8.49	0.60	2.88	3.13	2.7	12.8	13.9	98	2.81	C	1440	A+	5.97	8.09	475
	1.5+4.2+5.0	1.17	3.29	3.91	---	---	2.98	8.37	8.67	0.61	2.96	3.16	2.7	13.1	14.0	98	2.83	C	1480	A+	5.92	8.37	496
	1.5+4.2+6.0	1.12	3.13	4.47	---	---	3.13	8.72	9.30	0.64	2.95	3.36	2.8	13.1	14.9	98	2.96	C	1475	A++	6.17	8.72	495
	1.5+4.2+7.1	1.05	2.95	4.99	---	---	3.29	9.00	9.32	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.17	9.00	511
	1.5+5.0+5.0	1.13	3.76	3.76	---	---	3.10	8.65	9.02	0.64	3.05	3.32	2.8	13.5	14.7	98	2.84	C	1525	A+	5.83	8.65	520
	1.5+5.0+6.0	1.08	3.60	4.32	---	---	3.24	9.00	9.47	0.64	2.97	3.39	2.8	13.2	15.0	98	3.03	B	1485	A++	6.15	9.00	513
	1.5+5.0+7.1	0.99	3.31	4.70	---	---	3.41	9.00	9.49	0.68	2.90	3.39	3.0	12.9	15.0	98	3.10	B	1450	A++	6.17	9.00	511
	1.5+6.0+6.0	1.00	4.00	4.00	---	---	3.39	9.00	9.93	0.68	2.68	3.46	3.0	11.9	15.4	98	3.36	A	1340	A++	6.37	9.00	495
	1.5+6.0+7.1	0.92	3.70	4.38	---	---	3.55	9.00	9.95	0.71	2.61	3.46	3.1	11.6	15.4	98	3.45	A	1305	A++	6.39	9.00	493
	2.0+2.0+2.0	2.00	2.00	2.00	---	---	2.33	6.00	6.63	0.50	1.66	1.96	2.2	7.4	8.7	98	3.61	A	830	A++	6.19	6.00	340
	2.0+2.0+2.5	2.00	2.00	2.50	---	---	2.38	6.50	6.97	0.50	1.91	2.17	2.2	8.5	9.6	98	3.40	A	955	A++	6.30	6.50	361
	2.0+2.0+3.5	1.93	1.93	3.38	---	---	2.51	7.24	7.64	0.54	2.34	2.57	2.4	10.4	11.4	98	3.09	B	1170	A++	6.15	7.24	413
	2.0+2.0+4.2	1.83	1.83	3.83	---	---	2.61	7.49	8.08	0.54	2.45	2.88	2.4	10.9	12.8	98	3.06	B	1225	A++	6.14	7.49	428
	2.0+2.0+5.0	1.72	1.72	4.33	---	---	2.73	7.77	8.53	0.57	2.59	3.09	2.5	11.5	13.7	98	3.00	C	1295	A++	6.11	7.77	446
	2.0+2.0+6.0	1.62	1.62	4.88	---	---	2.88	8.12	9.03	0.58	2.56	3.22	2.6	11.4	14.3	98	3.17	B	1280	A++	6.37	8.12	447
	2.0+2.0+7.1	1.53	1.53	5.45	---	---	3.04	8.51	9.30	0.61	2.82	3.36	2.7	12.5	14.9	98	3.02	B	1410	A++	6.35	8.51	469
	2.0+2.5+2.5	2.00	2.50	2.50	---	---	2.44	7.00	7.31	0.50	2.17	2.40	2.2	9.6	10.6	98	3.23	A	1085	A++	6.26	7.00	392
	2.0+2.5+3.5	1.86	2.32	3.24	---	---	2.58	7.42	7.96	0.54	2.45	2.81	2.4	10.9	12.5	98	3.03	B	1225	A++	6.13	7.42	424
	2.0+2.5+4.2	1.76	2.20	3.70	---	---	2.69	7.66	8.36	0.57	2.57	3.07	2.5	11.4	13.6	98	2.98	C	1285	A++	6.13	7.66	438
	2.0+2.5+5.0	1.67	2.09	4.18	---	---	2.80	7.94	8.65	0.57	2.71	3.15	2.5	12.0	14.0	98	2.93	C	1355	A+	6.05	7.94	460
	2.0+2.5+6.0	1.58	1.98	4.74	---	---	2.95	8.30	9.10	0.61	2.69	3.22	2.7	11.9	14.3	98	3.09	B	1345	A++	6.36	8.30	458

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
5MXS90E3V3B	2.0+2.5+7.1	1.50	1.87	5.31	---	---	3.11	8.68	9.30	0.64	2.95	3.36	2.8	13.1	14.9	98	2.94	C	1475	A++	6.29	8.68	484
	2.0+3.5+3.5	1.73	3.02	3.02	---	---	2.73	7.77	8.47	0.57	2.69	3.13	2.5	11.9	13.9	98	2.89	C	1345	A+	6.05	7.77	450
	2.0+3.5+4.2	1.65	2.89	3.47	---	---	2.83	8.01	8.48	0.60	2.81	3.13	2.7	12.5	13.9	98	2.85	C	1405	A+	5.99	8.01	469
	2.0+3.5+5.0	1.58	2.77	3.95	---	---	2.95	8.30	8.66	0.61	2.96	3.16	2.7	13.1	14.0	98	2.80	C	1480	A+	5.96	8.30	488
	2.0+3.5+6.0	1.50	2.63	4.52	---	---	3.10	8.65	9.29	0.64	2.95	3.36	2.8	13.1	14.9	98	2.93	C	1475	A++	6.21	8.65	488
	2.0+3.5+7.1	1.43	2.50	5.07	---	---	3.26	9.00	9.31	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.19	9.00	509
	2.0+4.2+4.2	1.58	3.34	3.34	---	---	2.94	8.26	8.49	0.60	3.00	3.13	2.7	13.3	13.9	98	2.75	D	1500	A+	6.01	8.15	475
	2.0+4.2+5.0	1.53	3.20	3.81	---	---	3.05	8.54	8.84	0.64	3.09	3.29	2.8	13.7	14.6	98	2.76	D	1545	A+	5.93	8.54	505
	2.0+4.2+6.0	1.46	3.06	4.37	---	---	3.20	8.89	9.30	0.64	3.08	3.36	2.8	13.7	14.9	98	2.89	C	1540	A++	6.19	8.89	503
	2.0+4.2+7.1	1.36	2.84	4.80	---	---	3.36	9.00	9.32	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.19	9.00	509
	2.0+5.0+5.0	1.46	3.68	3.68	---	---	3.17	8.82	9.02	0.64	3.18	3.32	2.8	14.1	14.7	98	2.77	D	1590	A+	5.86	8.82	528
	2.0+5.0+6.0	1.39	3.46	4.15	---	---	3.32	9.00	9.47	0.68	2.97	3.39	3.0	13.2	15.0	98	3.03	B	1485	A++	6.18	9.00	510
	2.0+5.0+7.1	1.28	3.19	4.53	---	---	3.48	9.00	9.49	0.71	2.90	3.39	3.1	12.9	15.0	98	3.10	B	1450	A++	6.19	9.00	509
	2.0+6.0+6.0	1.28	3.86	3.86	---	---	3.46	9.00	9.93	0.68	2.68	3.46	3.0	11.9	15.4	98	3.36	A	1340	A++	6.39	9.00	493
	2.0+6.0+7.1	1.19	3.58	4.23	---	---	3.63	9.00	10.40	0.71	2.61	4.00	3.1	11.6	17.7	98	3.45	A	1305	A++	6.40	9.00	493
	2.5+2.5+2.5	2.41	2.41	2.41	---	---	2.51	7.23	7.64	0.54	2.34	2.57	2.4	10.4	11.4	98	3.09	B	1170	A++	6.23	7.23	407
	2.5+2.5+3.5	2.23	2.23	3.13	---	---	2.66	7.59	8.25	0.57	2.57	3.00	2.5	11.4	13.3	98	2.95	C	1285	A++	6.13	7.59	434
	2.5+2.5+4.2	2.13	2.13	3.58	---	---	2.76	7.84	8.47	0.57	2.69	3.13	2.5	11.9	13.9	98	2.91	C	1345	A++	6.11	7.84	450
	2.5+2.5+5.0	2.03	2.03	4.06	---	---	2.88	8.12	8.65	0.61	2.83	3.15	2.7	12.6	14.0	98	2.87	C	1415	A+	6.06	8.12	470
	2.5+2.5+6.0	1.93	1.93	4.61	---	---	3.02	8.47	9.10	0.61	2.82	3.22	2.7	12.5	14.3	98	3.00	B	1410	A++	6.34	8.47	468
	2.5+2.5+7.1	1.83	1.83	5.20	---	---	3.19	8.86	9.30	0.64	3.08	3.36	2.8	13.7	14.9	98	2.88	C	1540	A++	6.27	8.86	495
	2.5+3.5+3.5	2.08	2.93	2.93	---	---	2.80	7.94	8.47	0.60	2.75	3.13	2.7	12.2	13.9	98	2.89	C	1375	A+	6.01	7.94	463
	2.5+3.5+4.2	2.01	2.81	3.37	---	---	2.91	8.19	8.48	0.60	2.94	3.13	2.7	13.0	13.9	98	2.79	D	1470	A+	5.98	8.19	480
	2.5+3.5+5.0	1.93	2.70	3.84	---	---	3.02	8.47	8.66	0.64	3.02	3.16	2.8	13.4	14.0	98	2.80	C	1510	A+	5.95	8.47	499
	2.5+3.5+6.0	1.84	2.57	4.41	---	---	3.17	8.82	9.29	0.64	3.01	3.36	2.8	13.4	14.9	98	2.93	C	1505	A++	6.19	8.82	499
	2.5+3.5+7.1	1.72	2.40	4.88	---	---	3.33	9.00	9.31	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.19	9.00	509
	2.5+4.2+4.2	1.94	3.25	3.25	---	---	3.01	8.44	8.44	0.64	3.13	3.13	2.8	13.9	13.9	98	2.70	D	1565	A+	5.98	8.20	480
	2.5+4.2+5.0	1.86	3.13	3.73	---	---	3.13	8.72	8.84	0.64	3.22	3.29	2.8	14.3	14.6	98	2.71	D	1610	A+	5.93	8.55	505
	2.5+4.2+6.0	1.77	2.98	4.25	---	---	3.27	9.00	9.30	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.18	9.00	510
	2.5+4.2+7.1	1.63	2.74	4.63	---	---	3.44	9.00	9.32	0.71	3.15	3.36	3.1	14.0	14.9	98	2.86	C	1575	A++	6.19	9.00	509
	2.5+5.0+5.0	1.80	3.60	3.60	---	---	3.24	9.00	9.02	0.67	3.32	3.37	3.0	14.7	15.0	98	2.71	D	1660	A+	5.88	9.00	537
	2.5+5.0+6.0	1.67	3.33	4.00	---	---	3.39	9.00	9.47	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.18	9.00	510
	2.5+5.0+7.1	1.54	3.08	4.38	---	---	3.55	9.00	9.49	0.71	2.97	3.39	3.1	13.2	15.0	98	3.03	B	1485	A++	6.19	9.00	509
	2.5+6.0+6.0	1.56	3.72	3.72	---	---	3.54	9.00	9.93	0.71	2.75	3.46	3.1	12.2	15.4	98	3.27	A	1375	A++	6.39	9.00	493
	2.5+6.0+7.1	1.44	3.46	4.10	---	---	3.70	9.00	10.40	0.71	2.68	4.00	3.1	11.9	17.7	98	3.36	A	1340	A++	6.40	9.00	493
	3.5+3.5+3.5	2.77	2.77	2.77	---	---	2.95	8.31	8.60	0.64	3.07	3.26	2.8	13.6	14.5	98	2.71	D	1535	A+	5.92	8.31	491
	3.5+3.5+4.2	2.67	2.67	3.20	---	---	3.05	8.54	8.66	0.64	3.20	3.26	2.8	14.2	14.5	98	2.67	D	1600	A+	5.91	8.45	501
	3.5+3.5+5.0	2.57	2.57	3.68	---	---	3.17	8.82	8.84	0.67	3.29	3.32	3.0	14.6	14.7	98	2.68	D	1645	A+	5.81	8.82	532
	3.5+3.5+6.0	2.42	2.42	4.16	---	---	3.32	9.00	9.30	0.68	3.08	3.36	3.0	13.7	14.9	98	2.92	C	1540	A++	6.12	9.00	515
	3.5+3.5+7.1	2.23	2.23	4.54	---	---	3.48	9.00	9.32	0.71	3.02	3.36	3.1	13.4	14.9	98	2.98	C	1510	A++	6.18	9.00	510
	3.5+4.2+4.2	2.59	3.10	3.10	---	---	3.16	8.79	8.79	0.67	3.26	3.26	3.0	14.5	14.5	98	2.70	D	1630	A+	5.91	8.46	501
	3.5+4.2+5.0	2.48	2.98	3.54	---	---	3.27	9.00	9.00	0.67	3.29	3.29	3.0	14.6	14.6	98	2.74	D	1645	A+	5.83	8.83	531
	3.5+4.2+6.0	2.30	2.76	3.94	---	---	3.42	9.00	9.31	0.71	3.15	3.36	3.1	14.0	14.9	98	2.86	C	1575	A++	6.13	9.00	515
	3.5+4.2+7.1	2.13	2.55	4.32	---	---	3.58	9.00	9.81	0.75	3.15	3.95	3.3	14.0	17.5	98	2.86	C	1575	A++	6.21	9.00	508
	3.5+5.0+5.0	2.34	3.33	3.33	---	---	3.39	9.00	9.02	0.71	3.32	3.35	3.1	14.7	14.9	98	2.71	D	1660	A+	5.83	9.00	541
	3.5+5.0+6.0	2.18	3.10	3.72	---	---	3.54	9.00	9.48	0.71	3.04	3.39	3.1	13.5	15.0	98	2.96	C	1520	A++	6.12	9.00	515
	3.5+5.0+7.1	2.02	2.88	4.10	---	---	3.70	9.00	9.94	0.75	2.97	3.91	3.3	13.2	17.3	98	3.03	B	1485	A++	6.20	9.00	508
	3.5+6.0+6.0	2.04	3.48	3.48	---	---	3.69	9.00	10.38	0.71	2.75	4.00	3.1	12.2	17.7	98	3.27	A	1375	A++	6.33	9.00	498
	4.2+4.2+4.2	3.00	3.00	3.00	---	---	3.26	9.00	9.00	0.71	3.27	3.27	3.1	14.5	14.5	98	2.75	D	1635	A+	5.92	8.47	501
	4.2+4.2+5.0	2.82	2.82	3.36	---	---	3.38	9.00	9.08	0.71	3.29	3.29	3.1	14.6	14.6	98	2.74	D	1645	A+	5.84	8.84	530
	4.2+4.2+6.0	2.63	2.63	3.74	---	---	3.52	9.00	9.32	0.71	3.15	3.36	3.1	14.0	14.9	98	2.86	C	1575	A++	6.13	9.00	514
	4.2+4.2+7.1	2.44	2.44	4.12	---	---	3.69	9.00	9.82	0.75	3.16	3.95	3.3	14.0	17.5	98	2.85	C	1580	A++	6.21	9.00	508
	4.2+5.0+5.0	2.66	3.17	3.17	---	---	3.49	9.00	9.03	0.74	3.32	3.32	3.3	14.7	14.7	98	2.71	D	1660	A+	5.83	9.00	541
	4.2+5.0+6.0	2.49	2.96	3.55	---	---	3.64	9.00	9.98	0.75	3.04	3.98	3.3	13.5	17.7	98	2.96	C	1520	A++	6.13	9.00	514
	5.0+5.0+5.0	3.00	3.00	3.00	---	---	3.61	9.00	9.78	0.75	3.21	4.07	3.3	14.2	18.1	98	2.80	C	1605	A+	5.80	9.00	544
	1.5+1.5+1.5+1.5	1.50	1.50	1.50	1.50	---	2.33	6.00	6.60	0.48	1.39	1.62	2.1	6.2	7.2	98	4.32	A	695	A++	6.20	6.00	339
	1.5+1.5+1.5+2.0	1.50	1.50	1.50	2.00	---	2.38	6.50	6.97	0.51	1.58	1.82	2.3	7.0	8.1	98	4.11	A	790	A++	6.27	6.50	363
	1.5+1.5+1.5+2.5	1.50	1.50	1.50	2.50	---	2.44	7.00	7.31	0.51	1.82	1.98	2.3	8.1	8.8	98	3.85	A	910	A++	6.32	7.00	388
	1.5+1.5+1.5+3.5	1.39	1.39	1.39	3.25	---	2.58	7.42	7.96	0.54	2.04	2.32	2.4	9.1	10.3	98	3.64	A	1020	A++	6.26	7.42	415
	1.5+1.5+1.5+4.2	1.32	1.32	1.32	3.70	---	2.69	7.66	8.36	0.54	2.26	2.69	2.4	10.0	11.9	98	3.39	A	1130	A++	6.27	7.66	428
	1.5+1.5+1.5+5.0	1.25	1.25	1.25	4.18	---	2.80	7.94	8.78	0.58	2.33	2.90	2.6	10.3	12.9	98	3.41	A	1165	A++	6.20	7.94	449
	1.5+1.5+1.5+6.0	1.19	1.19	1.19	4.74	---	2.95	8.30	9.25	0.58	2.36	2.95	2.6	10.5	13.1	98	3.52	A	1180	A++	6.39	8.30	455
	1.5+1.5+1.5+7.1	1.12	1.12	1.12	5.31	---	3.11	8.68	9.67	0.61	2.62	3.24	2.7	11.6	14.4	98	3.31	A	1310	A++	6.37	8.68	477
	1.5+1.5+2.0+2.0	1.50	1.50	2.00	2.00	---	2.44	7.00	7.31	0.51	1.82	1.98	2.3	8.1	8.8	98	3.85	A	910	A++	6.35	7.00	386
	1.5+1.5+2.0+2.5	1.45	1.45	1.93	2.41	---	2.51	7.24	7.64	0.51	1.93	2.15	2.3	8.6	9.5	98	3.75	A	965	A++	6.37	7.24	398
	1.5+1.5+2.0+3.5	1.34	1.34	1.79	3.13	---	2.66	7.59	8.25	0.54	2.09	2.50	2.4	9.3	11.1	98	3.63	A	1045	A++	6.28	7.59	424
	1.5+1.5+2.0+4.2	1.28	1.28	1.70	3.58	---	2.76	7.84	8.63	0.58	2.38	2.88	2.6	10.6	12.8	98	3.29	A	1190	A++	6.28	7.84	438
	1.5+1.5+2.0+5.0	1.22	1.22	1.62	4.06	---	2.88	8.12	9.03	0.58	2.45	3.11	2.6	10.9	13.8	98	3.31	A	1225	A++	6.22	8.12	457
	1.5+1.5+2.0+6.0	1.16	1.16	1.54	4.62	---	3.02	8.47	9.45	0.61	2.49	3.09	2.7	11.0	13.7	98	3.40	A	1245	A++	6.39	8.47	464
	1.5+1.5+2.0+7.1	1.10	1.10	1.46	5.20	---	3.19	8.86	9.84	0.65	2.68	3.39	2.9	11.9	15.0	98	3.31	A	1340	A++	6.37	8.86	487
	1.5+1.5+2.5+2.5	1.39	1.39	2.32	2.32	---	2.58	7.42	7.96	0.54	2.04	2.32	2.4	9.1	10.3	98	3.64	A	1020	A++	6.36	7.42	409
	1.5+1.5+2.5+3.5	1.30	1.30	2.16	3.02	---	2.73	7.77	8.53	0.58	2.32	2.82	2.6	10.3	12.5	98	3.35	A	1160	A++	6.24	7.78	437
	1.5+1.5+2.5+4.2	1.24	1.24	2.06	3.47	---	2.83	8.01	8.88	0.58	2.50	3.08	2.6	11.1	13.7	98	3.20	A	1250	A++	6.28	8.01	447
	1.5+1.5+2.5+5.0	1.19	1.19	1.98	3.95	---	2.95	8.30	9.25	0.61	2.58	3.25	2.7	11.4	14.4	98	3.22	A	1290	A++	6.22	8.30	468
	1.5+1.5+2.5+6.0	1.13	1.13	1.88	4.51	---	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6.37	8.65	475
	1.5+1.5+2.5+7.1	1.07	1.07	1.79	5.07	---	3.26	9.00	9.96	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6.36	9.00	496
	1.5+1.5+3.5+3.5	1.22	1.22	2.84	2.84	---	2.88	8.12	9.03	0.58	2.56	3.15	2.6	11.4	14.0	98	3.17	B	1280	A++	6.21	8.12	458
	1.5+1.5+3.5+4.2	1.17	1.17	2.74	3.29	---	2.98	8.37	9.14	0.61	2.69	3.22	2.7	11.9	14.3	98	3.11	B	1345	A++	6.18	8.37	475
	1.5+1.5+3.5+5.0	1.13	1.13	2.63	3.76	---	3.10	8.65	9.49	0.64	2.84	3.39	2.8	12.6	15.0	98	3.05	B	1420	A++	6.13	8.65	494
	1.5+1.5+3.5+6.0	1.08	1.08	2.52	4.32	---	3.24	9.00	9.95	0.64	2.75	3.46	2.8	12.2	15.4	98	3.27	A	1375	A++	6.30	9.00	501
	1.5+1.5+3.5+7.1	0.99	0.99	2.32	4.70	---	3.41	9.00	9.97	0.68	2.68	3.46	3.0	11.9	15.4	98	3.36	A	1340	A++	6.30	9.00	501
	1.5+1.5+4.2+4.2	1.13	1.13	3.17	3.17	---	3.08	8.61	9.33	0.64	2.89	3.36	2.8	12.8	14.9	98	2.98	C	1445	A++	6.13	8.61	492
	1.5+1.5+4.2+5.0	1.09	1.09	3.06	3.64	---	3.20	8.89	9.50	0.64	2.97	3.39	2.8	13.2	15.0	98	2.99	C	1485	A++	6.11	8.89	510

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
5MXS90E3V3B	1.5+1.5+4.2+6.0	1.02	1.02	2.86	4.09	---	3.35	9.00	9.96	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6.30	9.00	501
	1.5+1.5+4.2+7.1	0.94	0.94	2.64	4.47	---	3.51	9.00	9.98	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.30	9.00	501
	1.5+1.5+5.0+5.0	1.04	1.04	3.46	3.46	---	3.32	9.00	9.68	0.68	2.92	3.42	3.0	13.0	15.2	98	3.08	B	1460	A+	6.09	9.00	518
	1.5+1.5+5.0+6.0	0.96	0.96	3.21	3.86	---	3.46	9.00	10.14	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6.30	9.00	501
	1.5+1.5+5.0+7.1	0.89	0.89	2.98	4.23	---	3.63	9.00	10.46	0.71	2.70	3.88	3.1	12.0	17.2	98	3.33	A	1350	A++	6.30	9.00	501
	1.5+1.5+6.0+6.0	0.90	0.90	3.60	3.60	---	3.61	9.00	10.45	0.68	2.46	3.48	3.0	10.9	15.4	98	3.66	A	1230	A++	6.32	9.00	499
	1.5+2.0+2.0+2.0	1.45	1.93	1.93	1.93	---	2.51	7.24	7.64	0.51	1.93	2.15	2.3	8.6	9.5	98	3.75	A	965	A++	6.42	7.24	395
	1.5+2.0+2.0+2.5	1.39	1.86	1.86	2.32	---	2.58	7.42	7.96	0.54	2.04	2.32	2.4	9.1	10.3	98	3.64	A	1020	A++	6.41	7.42	406
	1.5+2.0+2.0+3.5	1.30	1.73	1.73	3.02	---	2.73	7.77	8.53	0.58	2.21	2.63	2.6	9.8	11.7	98	3.52	A	1105	A++	6.29	7.78	433
	1.5+2.0+2.0+4.2	1.24	1.65	1.65	3.47	---	2.83	8.01	8.88	0.58	2.50	3.08	2.6	11.1	13.7	98	3.20	A	1250	A++	6.29	8.01	447
	1.5+2.0+2.0+5.0	1.19	1.58	1.58	3.95	---	2.95	8.30	9.25	0.61	2.58	3.25	2.7	11.4	14.4	98	3.22	A	1290	A++	6.28	8.30	463
	1.5+2.0+2.0+6.0	1.13	1.50	1.50	4.51	---	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6.38	8.65	475
	1.5+2.0+2.0+7.1	1.07	1.43	1.43	5.07	---	3.26	9.00	9.96	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6.37	9.00	495
	1.5+2.0+2.5+2.5	1.34	1.79	2.23	2.23	---	2.66	7.59	8.25	0.54	2.09	2.50	2.4	9.3	11.1	98	3.63	A	1045	A++	6.40	7.59	415
	1.5+2.0+2.5+3.5	1.25	1.67	2.09	2.93	---	2.80	7.94	8.78	0.58	2.44	3.02	2.6	10.8	13.4	98	3.25	A	1220	A++	6.31	7.94	441
	1.5+2.0+2.5+4.2	1.20	1.61	2.01	3.37	---	2.91	8.19	9.12	0.61	2.63	3.22	2.7	11.7	14.3	98	3.11	B	1315	A++	6.30	8.19	455
	1.5+2.0+2.5+5.0	1.16	1.54	1.93	3.85	---	3.02	8.47	9.30	0.61	2.71	3.25	2.7	12.0	14.4	98	3.13	B	1355	A++	6.26	8.47	474
	1.5+2.0+2.5+6.0	1.10	1.47	1.84	4.41	---	3.17	8.82	9.81	0.64	2.68	3.38	2.8	11.9	15.0	98	3.29	A	1340	A++	6.39	8.82	484
	1.5+2.0+2.5+7.1	1.03	1.37	1.72	4.88	---	3.33	9.00	9.96	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6.37	9.00	495
	1.5+2.0+3.5+3.5	1.19	1.58	2.77	2.77	---	2.95	8.30	9.13	0.61	2.69	3.22	2.7	11.9	14.3	98	3.09	B	1345	A++	6.21	8.30	468
	1.5+2.0+3.5+4.2	1.14	1.53	2.67	3.20	---	3.05	8.54	9.32	0.61	2.82	3.36	2.7	12.5	14.9	98	3.03	B	1410	A++	6.21	8.54	482
	1.5+2.0+3.5+5.0	1.10	1.47	2.57	3.68	---	3.17	8.82	9.49	0.64	2.90	3.39	2.8	12.9	15.0	98	3.04	B	1450	A++	6.13	8.82	504
	1.5+2.0+3.5+6.0	1.04	1.38	2.42	4.15	---	3.32	9.00	9.95	0.64	2.75	3.46	2.8	12.2	15.4	98	3.27	A	1375	A++	6.30	9.00	501
	1.5+2.0+3.5+7.1	0.96	1.28	2.23	4.53	---	3.48	9.00	9.97	0.68	2.68	3.46	3.0	11.9	15.4	98	3.36	A	1340	A++	6.32	9.00	499
	1.5+2.0+4.2+4.2	1.11	1.48	3.10	3.10	---	3.16	8.79	9.33	0.64	3.02	3.36	2.8	13.4	14.9	98	2.91	C	1510	A++	6.16	8.79	500
	1.5+2.0+4.2+5.0	1.06	1.42	2.98	3.54	---	3.27	9.00	9.50	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.12	9.00	515
	1.5+2.0+4.2+6.0	0.99	1.31	2.76	3.94	---	3.42	9.00	9.96	0.68	2.81	3.46	3.0	12.5	15.4	98	3.20	A	1405	A++	6.30	9.00	500
	1.5+2.0+4.2+7.1	0.91	1.22	2.55	4.32	---	3.58	9.00	10.42	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.32	9.00	499
	1.5+2.0+5.0+5.0	1.00	1.33	3.33	3.33	---	3.39	9.00	9.68	0.68	2.92	3.42	3.0	13.0	15.2	98	3.08	B	1460	A++	6.12	9.00	515
	1.5+2.0+5.0+6.0	0.93	1.24	3.10	3.72	---	3.54	9.00	10.14	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6.30	9.00	500
	1.5+2.0+5.0+7.1	0.87	1.15	2.88	4.10	---	3.70	9.00	10.50	0.71	2.70	3.88	3.1	12.0	17.2	98	3.33	A	1350	A++	6.32	9.00	499
	1.5+2.0+6.0+6.0	0.87	1.16	3.48	3.48	---	3.69	9.00	10.49	0.71	2.46	3.48	3.1	10.9	15.4	98	3.66	A	1230	A++	6.31	9.00	500
	1.5+2.5+2.5+2.5	1.30	2.16	2.16	2.16	---	2.73	7.77	8.53	0.58	2.21	2.69	2.6	9.8	11.9	98	3.52	A	1105	A++	6.37	7.78	428
	1.5+2.5+2.5+3.5	1.22	2.03	2.03	2.84	---	2.88	8.12	9.03	0.58	2.56	3.22	2.6	11.4	14.3	98	3.17	B	1280	A++	6.29	8.12	452
	1.5+2.5+2.5+4.2	1.17	1.96	1.96	3.29	---	2.98	8.37	9.13	0.61	2.69	3.22	2.7	11.9	14.3	98	3.11	B	1345	A++	6.28	8.37	467
	1.5+2.5+2.5+5.0	1.13	1.88	1.88	3.76	---	3.10	8.65	9.49	0.64	2.84	3.39	2.8	12.6	15.0	98	3.05	B	1420	A++	6.21	8.65	488
	1.5+2.5+2.5+6.0	1.08	1.80	1.80	4.32	---	3.24	9.00	9.94	0.64	2.75	3.46	2.8	12.2	15.4	98	3.27	A	1375	A++	6.37	9.00	495
	1.5+2.5+2.5+7.1	0.99	1.65	1.65	4.70	---	3.41	9.00	9.96	0.68	2.68	3.46	3.0	11.9	15.4	98	3.36	A	1340	A++	6.38	9.00	494
	1.5+2.5+3.5+3.5	1.16	1.93	2.70	2.70	---	3.02	8.47	9.13	0.61	2.75	3.22	2.7	12.2	14.3	98	3.08	B	1375	A++	6.20	8.47	479
	1.5+2.5+3.5+4.2	1.12	1.86	2.61	3.13	---	3.13	8.72	9.32	0.64	2.95	3.36	2.8	13.1	14.9	98	2.96	C	1475	A++	6.16	8.72	496
	1.5+2.5+3.5+5.0	1.08	1.80	2.52	3.60	---	3.24	9.00	9.49	0.64	3.04	3.39	2.8	13.5	15.0	98	2.96	C	1520	A++	6.12	9.00	515
	1.5+2.5+3.5+6.0	1.00	1.67	2.33	4.00	---	3.39	9.00	9.95	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.30	9.00	500
	1.5+2.5+3.5+7.1	0.92	1.54	2.16	4.38	---	3.55	9.00	9.97	0.71	2.68	3.46	3.1	11.9	15.4	98	3.36	A	1340	A++	6.32	9.00	499
	1.5+2.5+4.2+4.2	1.08	1.81	3.03	3.03	---	3.23	8.96	9.33	0.64	3.09	3.36	2.8	13.7	14.9	98	2.90	C	1545	A++	6.14	8.96	511
	1.5+2.5+4.2+5.0	1.02	1.70	2.86	3.41	---	3.35	9.00	9.50	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.12	9.00	515
	1.5+2.5+4.2+6.0	0.95	1.58	2.66	3.80	---	3.49	9.00	9.96	0.68	2.81	3.46	3.0	12.5	15.4	98	3.20	A	1405	A++	6.32	9.00	499
	1.5+2.5+4.2+7.1	0.88	1.47	2.47	4.18	---	3.66	9.00	10.47	0.71	2.75	4.09	3.1	12.2	18.1	98	3.27	A	1375	A++	6.32	9.00	499
	1.5+2.5+5.0+5.0	0.96	1.60	3.20	3.20	---	3.23	8.96	9.33	0.64	3.09	3.36	2.8	13.7	14.9	98	2.90	C	1545	A++	6.12	9.00	515
	1.5+2.5+5.0+6.0	0.90	1.50	3.00	3.60	---	3.35	9.00	9.50	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.30	9.00	500
	1.5+3.5+3.5+3.5	1.10	2.57	2.57	2.57	---	3.17	8.82	9.32	0.64	3.02	3.36	2.8	13.4	14.9	98	2.92	C	1510	A+	6.07	8.82	509
	1.5+3.5+3.5+4.2	1.06	2.48	2.48	2.98	---	3.27	9.00	9.33	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A+	6.08	9.00	518
	1.5+3.5+3.5+5.0	1.00	2.33	2.33	3.33	---	3.39	9.00	9.50	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A+	6.08	9.00	518
	1.5+3.5+3.5+6.0	0.93	2.17	2.17	3.72	---	3.54	9.00	9.96	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.25	9.00	505
	1.5+3.5+3.5+7.1	0.87	2.02	2.02	4.10	---	3.70	9.00	10.50	0.71	2.75	4.17	3.1	12.2	18.5	98	3.27	A	1375	A++	6.26	9.00	504
	1.5+3.5+4.2+4.2	1.01	2.35	2.82	2.82	---	3.38	9.00	9.33	0.68	3.16	3.37	3.0	14.0	15.0	98	2.85	C	1580	A++	6.12	9.00	515
	1.5+3.5+4.2+5.0	0.95	2.22	2.66	3.17	---	3.49	9.00	9.51	0.71	3.04	3.39	3.1	13.5	15.0	98	2.96	C	1520	A+	6.08	9.00	518
	1.5+3.5+4.2+6.0	0.89	2.07	2.49	3.55	---	3.64	9.00	10.47	0.71	2.82	4.17	3.1	12.5	18.5	98	3.19	B	1410	A++	6.25	9.00	504
	1.5+3.5+5.0+5.0	0.90	2.10	3.00	3.00	---	3.61	9.00	10.26	0.71	2.92	4.19	3.1	13.0	18.6	98	3.08	B	1460	A+	6.08	9.00	518
	1.5+4.2+4.2+4.2	0.96	2.68	2.68	2.68	---	3.48	9.00	9.34	0.71	3.16	3.37	3.1	14.0	15.0	98	2.85	C	1580	A++	6.13	9.00	514
	1.5+4.2+4.2+5.0	0.91	2.54	2.54	3.02	---	3.60	9.00	10.09	0.71	3.04	4.15	3.1	13.5	18.4	98	2.96	C	1520	A++	6.12	9.00	515
	2.0+2.0+2.0+2.0	1.86	1.86	1.86	1.86	---	2.58	7.44	7.96	0.54	2.04	2.32	2.4	9.1	10.3	98	3.65	A	1020	A++	6.45	7.44	404
	2.0+2.0+2.0+2.5	1.79	1.79	1.79	2.22	---	2.66	7.59	8.25	0.54	2.09	2.50	2.4	9.3	11.1	98	3.63	A	1045	A++	6.42	7.59	415
	2.0+2.0+2.0+3.5	1.67	1.67	1.67	2.93	---	2.80	7.94	8.78	0.58	2.32	2.82	2.6	10.3	12.5	98	3.42	A	1160	A++	6.37	7.94	437
	2.0+2.0+2.0+4.2	1.61	1.61	1.61	3.36	---	2.91	8.19	9.12	0.61	2.63	3.22	2.7	11.7	14.3	98	3.11	B	1315	A++	6.33	8.19	453
	2.0+2.0+2.0+5.0	1.54	1.54	1.54	3.85	---	3.02	8.47	9.30	0.61	2.71	3.25	2.7	12.0	14.4	98	3.13	B	1355	A++	6.27	8.47	473
	2.0+2.0+2.0+6.0	1.47	1.47	1.47	4.41	---	3.17	8.82	9.81	0.65	2.68	3.38	2.9	11.9	15.0	98	3.29	A	1340	A++	6.41	8.82	482
	2.0+2.0+2.0+7.1	1.37	1.37	1.37	4.89	---	3.33	9.00	9.96	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6.39	9.00	493
	2.0+2.0+2.5+2.5	1.73	1.73	2.16	2.16	---	2.73	7.78	8.53	0.58	2.21	2.69	2.6	9.8	11.9	98	3.52	A	1105	A++	6.43	7.78	424
	2.0+2.0+2.5+3.5	1.62	1.62	2.03	2.85	---	2.88	8.12	9.03	0.58	2.56	3.22	2.6	11.4	14.3	98	3.17	B	1280	A++	6.35	8.12	448
	2.0+2.0+2.5+4.2	1.56	1.56	1.96	3.29	---	2.98	8.37	9.13	0.61	2.69	3.22	2.7	11.9	14.3	98	3.11	B	1345	A++	6.31	8.37	465
	2.0+2.0+2.5+5.0	1.50	1.50	1.88	3.77	---	3.10	8.65	9.49	0.64	2.84	3.39	2.8	12.6	15.0	98	3.05	B	1420	A++	6.24	8.65	486
	2.0+2.0+2.5+6.0	1.44	1.44	1.80	4.32	---	3.24	9.00	9.94	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6.38	9.00	494
	2.0+2.0+2.5+7.1	1.32	1.32	1.65	4.71	---	3.41	9.00	9.96	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.39	9.00	493
	2.0+2.0+3.5+3.5	1.54	1.54	2.70	2.70	---	3.02	8.48	9.13	0.61	2.82	3.22	2.7	12.5	14.3	98	3.01	B	1410	A++	6.23	8.48	477
	2.0+2.0+3.5+4.2	1.49	1.49	2.61	3.13	---	3.13	8.72	9.32	0.64	2.95	3.36	2.8	13.1	14.9	98	2.96	C	1475	A++	6.22	8.72	491
	2.0+2.0+3.5+5.0	1.44	1.44	2.52	3.60	---	3.24	9.00	9.49	0.64	3.04	3.39	2.8	13.5	15.0	98	2.96	C	1520	A++	6.18	9.00	510
	2.0+2.0+3.5+6.0	1.33	1.33	2.34	4.00	---	3.39	9.00	9.95	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.32	9.00	499
	2.0+2.0+3.5+7.1	1.23	1.23	2.16	4.38	---	3.55	9.00	9.97	0.71	2.68	3.46	3.1	11.9	15.4	98	3.36	A	1340	A++	6.32	9.00	499
	2.0+2.0+4.2+4.2	1.45	1.45	3.03	3.03	---	3.23	8.96	9.33	0.64	3.09	3.36	2.8	13.7	14.9	98	2.90	C	1545	A++	6.19	8.96	507
	2.0+2.0+4.2+5.0	1.36	1.36	2.87	3.41	---	3.35	9.00	9.50	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.20	9.00	509
	2.0+2.0+4.2+6.0	1.27	1.27	2.66	3.80	---	3.49	9.00	9.96	0.68	2.81	3.46	3.0	12.5	15.4	98	3.20	A	1405	A++	6.32	9.00	499
	2.0+2.0+4.2+7.1	1.18	1.18	2.47	4.17	---	3.66	9.00	10.47	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.32	9.00	499
	2.0+2.0+5.0+5.0	1.29	1.29	3.21	3.21	---	3.46	9.00	9.68	0.68	2.92	3.42	3.0	13.0	15.2	98	3.08	B	1460	A++	6.20	9.00	509

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
5MXS90E3V3B	2.0+2.0+5.0+6.0	1.20	1.20	3.00	3.60	---	3.61	9.00	10.45	0.71	2.70	3.88	3.1	12.0	17.2	98	3.33	A	1350	A++	6.32	9.00	499
	2.0+2.5+2.5+2.5	1.67	2.09	2.09	2.09	---	2.80	7.94	8.78	0.58	2.32	2.82	2.6	10.3	12.5	98	3.42	A	1160	A++	6.45	7.94	432
	2.0+2.5+2.5+3.5	1.57	1.98	1.98	2.77	---	2.95	8.30	9.12	0.61	2.69	3.22	2.7	11.9	14.3	98	3.09	B	1345	A++	6.29	8.30	462
	2.0+2.5+2.5+4.2	1.53	1.91	1.91	3.19	---	3.05	8.54	9.31	0.61	2.82	3.36	2.7	12.5	14.9	98	3.03	B	1410	A++	6.28	8.54	476
	2.0+2.5+2.5+5.0	1.46	1.84	1.84	3.68	---	3.17	8.82	9.49	0.64	2.90	3.39	2.8	12.9	15.0	98	3.04	B	1450	A++	6.22	8.82	497
	2.0+2.5+2.5+6.0	1.39	1.73	1.73	4.15	---	3.32	9.00	9.94	0.65	2.75	3.46	2.9	12.2	15.4	98	3.27	A	1375	A++	6.39	9.00	494
	2.0+2.5+2.5+7.1	1.27	1.60	1.60	4.53	---	3.48	9.00	9.96	0.68	2.68	3.46	3.0	11.9	15.4	98	3.36	A	1340	A++	6.39	9.00	493
	2.0+2.5+3.5+3.5	1.50	1.89	2.63	2.63	---	3.10	8.65	9.31	0.64	2.88	3.36	2.8	12.8	14.9	98	3.00	B	1440	A++	6.22	8.65	487
	2.0+2.5+3.5+4.2	1.46	1.82	2.55	3.06	---	3.20	8.89	9.32	0.64	3.08	3.36	2.8	13.7	14.9	98	2.89	C	1540	A++	6.20	8.89	502
	2.0+2.5+3.5+5.0	1.39	1.73	2.42	3.46	---	3.32	9.00	9.49	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.20	9.00	509
	2.0+2.5+3.5+6.0	1.28	1.61	2.25	3.86	---	3.46	9.00	9.95	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.32	9.00	499
	2.0+2.5+3.5+7.1	1.19	1.49	2.09	4.23	---	3.63	9.00	10.42	0.71	2.68	4.01	3.1	11.9	17.8	98	3.36	A	1340	A++	6.32	9.00	499
	2.0+2.5+4.2+4.2	1.40	1.74	2.93	2.93	---	3.30	9.00	9.33	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.20	9.00	508
	2.0+2.5+4.2+5.0	1.32	1.64	2.76	3.28	---	3.42	9.00	9.50	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.20	9.00	509
	2.0+2.5+4.2+6.0	1.23	1.53	2.57	3.67	---	3.57	9.00	10.41	0.71	2.81	4.00	3.1	12.5	17.7	98	3.20	A	1405	A++	6.33	9.00	498
	2.0+2.5+5.0+5.0	1.25	1.55	3.10	3.10	---	3.54	9.00	9.68	0.71	2.92	3.42	3.1	13.0	15.2	98	3.08	B	1460	A++	6.20	9.00	509
	2.0+2.5+5.0+6.0	1.17	1.45	2.90	3.48	---	3.69	9.00	10.49	0.71	2.70	3.96	3.1	12.0	17.6	98	3.33	A	1350	A++	6.32	9.00	499
	2.0+3.5+3.5+3.5	1.44	2.52	2.52	2.52	---	3.24	9.00	9.32	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.14	9.00	514
	2.0+3.5+3.5+4.2	1.36	2.39	2.39	2.86	---	3.35	9.00	9.33	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.14	9.00	514
	2.0+3.5+3.5+5.0	1.29	2.25	2.25	3.21	---	3.46	9.00	9.50	0.71	3.04	3.39	3.1	13.5	15.0	98	2.96	C	1520	A++	6.14	9.00	514
	2.0+3.5+3.5+6.0	1.20	2.10	2.10	3.60	---	3.61	9.00	10.40	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.26	9.00	504
	2.0+3.5+4.2+4.2	1.29	2.27	2.72	2.72	---	3.45	9.00	9.33	0.71	3.16	3.37	3.1	14.0	15.0	98	2.85	C	1580	A++	6.15	9.00	513
	2.0+3.5+4.2+5.0	1.23	2.14	2.57	3.06	---	3.57	9.00	10.00	0.71	3.04	3.99	3.1	13.5	17.7	98	2.96	C	1520	A++	6.14	9.00	513
	2.0+3.5+5.0+5.0	1.17	2.03	2.90	2.90	---	3.69	9.00	10.26	0.75	2.92	4.19	3.3	13.0	18.6	98	3.08	B	1460	A++	6.14	9.00	514
	2.0+4.2+4.2+4.2	1.23	2.59	2.59	2.59	---	3.55	9.00	9.34	0.71	3.16	3.37	3.1	14.0	15.0	98	2.85	C	1580	A++	6.15	9.00	513
	2.0+4.2+4.2+5.0	1.18	2.45	2.45	2.92	---	3.67	9.00	10.01	0.75	3.04	3.99	3.3	13.5	17.7	98	2.96	C	1520	A++	6.15	9.00	513
	2.5+2.5+2.5+2.5	2.03	2.03	2.03	2.03	---	2.88	8.12	9.03	0.58	2.56	3.22	2.6	11.4	14.3	98	3.17	B	1280	A++	6.43	8.12	443
	2.5+2.5+2.5+3.5	1.93	1.93	1.93	2.68	---	3.02	8.47	9.12	0.61	2.82	3.22	2.7	12.5	14.3	98	3.00	B	1410	A++	6.29	8.47	472
	2.5+2.5+2.5+4.2	1.87	1.86	1.86	3.13	---	3.13	8.72	9.31	0.64	2.95	3.36	2.8	13.1	14.9	98	2.96	C	1475	A++	6.29	8.72	486
	2.5+2.5+2.5+5.0	1.80	1.80	1.80	3.60	---	3.24	9.00	9.49	0.64	3.04	3.39	2.8	13.5	15.0	98	2.96	C	1520	A++	6.21	9.00	508
	2.5+2.5+2.5+6.0	1.67	1.67	1.67	3.99	---	3.39	9.00	9.94	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.39	9.00	493
	2.5+2.5+2.5+7.1	1.54	1.54	1.54	4.38	---	3.55	9.00	9.96	0.71	2.68	3.46	3.1	11.9	15.4	98	3.36	A	1340	A++	6.39	9.00	493
	2.5+2.5+3.5+3.5	1.84	1.84	2.57	2.57	---	3.17	8.82	9.31	0.64	3.02	3.36	2.8	13.4	14.9	98	2.92	C	1510	A++	6.22	8.82	497
	2.5+2.5+3.5+4.2	1.77	1.77	2.48	2.98	---	3.27	9.00	9.32	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.20	9.00	509
	2.5+2.5+3.5+5.0	1.67	1.67	2.33	3.33	---	3.39	9.00	9.49	0.68	3.04	3.39	3.0	13.5	15.0	98	2.96	C	1520	A++	6.20	9.00	509
	2.5+2.5+3.5+6.0	1.55	1.55	2.18	3.72	---	3.54	9.00	9.95	0.71	2.75	3.46	3.1	12.2	15.4	98	3.27	A	1375	A++	6.32	9.00	499
	2.5+2.5+3.5+7.1	1.44	1.44	2.02	4.10	---	3.70	9.00	10.42	0.71	2.68	4.01	3.1	11.9	17.8	98	3.36	A	1340	A++	6.32	9.00	499
	2.5+2.5+4.2+4.2	1.68	1.68	2.82	2.82	---	3.38	9.00	9.33	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.20	9.00	508
	2.5+2.5+4.2+5.0	1.58	1.58	2.67	3.17	---	3.49	9.00	9.50	0.71	3.04	3.39	3.1	13.5	15.0	98	2.96	C	1520	A++	6.20	9.00	508
	2.5+2.5+4.2+6.0	1.48	1.48	2.49	3.55	---	3.64	9.00	10.47	0.71	2.81	4.00	3.1	12.5	17.7	98	3.20	A	1405	A++	6.32	9.00	499
	2.5+2.5+5.0+5.0	1.50	1.50	3.00	3.00	---	3.61	9.00	10.25	0.71	2.92	4.18	3.1	13.0	18.5	98	3.08	B	1460	A++	6.20	9.00	509
	2.5+3.5+3.5+3.5	1.74	2.42	2.42	2.42	---	3.32	9.00	9.34	0.68	3.15	3.36	3.0	14.0	14.9	98	2.86	C	1575	A++	6.14	9.00	514
	2.5+3.5+3.5+4.2	1.64	2.30	2.30	2.76	---	3.42	9.00	9.33	0.71	3.15	3.36	3.1	14.0	14.9	98	2.86	C	1575	A++	6.14	9.00	513
	2.5+3.5+3.5+5.0	1.56	2.17	2.17	3.10	---	3.54	9.00	9.50	0.71	3.04	3.39	3.1	13.5	15.0	98	2.96	C	1520	A++	6.14	9.00	514
	2.5+3.5+3.5+6.0	1.46	2.03	2.03	3.48	---	3.69	9.00	10.40	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.26	9.00	504
	2.5+3.5+4.2+4.2	1.56	2.18	2.63	2.63	---	3.52	9.00	9.33	0.71	3.16	3.37	3.1	14.0	15.0	98	2.85	C	1580	A++	6.15	9.00	513
	2.5+3.5+4.2+5.0	1.48	2.07	2.49	2.96	---	3.64	9.00	10.00	0.75	3.04	3.99	3.3	13.5	17.7	98	2.96	C	1520	A++	6.15	9.00	513
	2.5+4.2+4.2+4.2	1.50	2.50	2.50	2.50	---	3.63	9.00	9.83	0.75	3.16	3.95	3.3	14.0	17.5	98	2.85	C	1580	A++	6.15	9.00	513
	3.5+3.5+3.5+3.5	2.25	2.25	2.25	2.25	---	3.46	9.00	9.32	0.71	3.15	3.36	3.1	14.0	14.9	98	2.86	C	1575	A+	6.08	9.00	518
	3.5+3.5+3.5+4.2	2.14	2.14	2.14	2.58	---	3.57	9.00	9.82	0.75	3.16	3.95	3.3	14.0	17.5	98	2.85	C	1580	A+	6.08	9.00	518
	3.5+3.5+3.5+5.0	2.03	2.03	2.03	2.91	---	3.69	9.00	9.95	0.75	3.04	3.91	3.3	13.5	17.3	98	2.96	C	1520	A+	6.08	9.00	518
	3.5+3.5+4.2+4.2	2.05	2.05	2.45	2.45	---	3.67	9.00	9.83	0.75	3.16	3.95	3.3	14.0	17.5	98	2.85	C	1580	A+	6.08	9.00	518
	1.5+1.5+1.5+1.5	1.45	1.45	1.45	1.45	1.45	2.51	7.24	7.64	0.52	1.79	2.01	2.3	7.9	8.9	98	4.04	A	895	A++	6.39	7.24	397
	1.5+1.5+1.5+2.0	1.39	1.39	1.39	1.39	1.86	2.58	7.42	7.96	0.52	1.90	2.18	2.3	8.4	9.7	98	3.91	A	950	A++	6.40	7.42	407
	1.5+1.5+1.5+2.5	1.34	1.34	1.34	1.34	2.23	2.66	7.59	8.25	0.55	2.01	2.36	2.4	8.9	10.5	98	3.78	A	1005	A++	6.41	7.59	415
	1.5+1.5+1.5+3.5	1.25	1.25	1.25	1.25	2.93	2.80	7.94	8.78	0.58	2.18	2.68	2.6	9.7	11.9	98	3.64	A	1090	A++	6.29	7.94	442
	1.5+1.5+1.5+4.2	1.20	1.20	1.20	1.20	3.37	2.91	8.19	9.12	0.58	2.30	2.88	2.6	10.2	12.8	98	3.56	A	1150	A++	6.29	8.19	456
	1.5+1.5+1.5+5.0	1.16	1.16	1.16	1.16	3.85	3.02	8.47	9.45	0.61	2.37	2.97	2.7	10.5	13.2	98	3.57	A	1185	A++	6.29	8.47	472
	1.5+1.5+1.5+6.0	1.10	1.10	1.10	1.10	4.41	3.17	8.82	9.81	0.62	2.40	3.02	2.8	10.6	13.4	98	3.68	A	1200	A++	6.27	8.82	493
	1.5+1.5+1.5+7.1	1.03	1.03	1.03	1.03	4.88	3.33	9.00	10.12	0.65	2.47	3.17	2.9	11.0	14.1	98	3.64	A	1235	A++	6.25	9.00	505
	1.5+1.5+2.0+2.0	1.34	1.34	1.34	1.79	1.79	2.66	7.59	8.25	0.55	2.01	2.36	2.4	8.9	10.5	98	3.78	A	1005	A++	6.42	7.59	414
	1.5+1.5+2.0+2.5	1.30	1.30	1.30	1.73	2.16	2.73	7.77	8.53	0.55	2.06	2.49	2.4	9.1	11.0	98	3.77	A	1030	A++	6.42	7.78	425
	1.5+1.5+2.0+3.5	1.22	1.22	1.22	1.62	2.84	2.88	8.12	9.03	0.58	2.24	2.81	2.6	9.9	12.5	98	3.63	A	1120	A++	6.31	8.12	451
	1.5+1.5+2.0+4.2	1.17	1.17	1.17	1.56	3.29	2.98	8.37	9.33	0.58	2.42	3.02	2.6	10.7	13.4	98	3.46	A	1210	A++	6.31	8.37	465
	1.5+1.5+2.0+5.0	1.13	1.13	1.13	1.50	3.76	3.10	8.65	9.64	0.61	2.50	3.12	2.7	11.1	13.8	98	3.46	A	1250	A++	6.27	8.65	483
	1.5+1.5+2.0+6.0	1.08	1.08	1.08	1.44	4.32	3.24	9.00	9.96	0.62	2.46	3.09	2.8	10.9	13.7	98	3.66	A	1230	A++	6.25	9.00	505
	1.5+1.5+2.0+7.1	0.99	0.99	0.99	1.32	4.70	3.41	9.00	10.23	0.65	2.47	3.33	2.9	11.0	14.8	98	3.64	A	1235	A++	6.25	9.00	505
	1.5+1.5+2.5+2.5	1.25	1.25	1.25	2.09	2.09	2.80	7.94	8.78	0.58	2.18	2.68	2.6	9.7	11.9	98	3.64	A	1090	A++	6.39	7.94	436
	1.5+1.5+2.5+3.5	1.19	1.19	1.19	1.98	2.77	2.95	8.30	9.25	0.58	2.36	2.95	2.6	10.5	13.1	98	3.52	A	1180	A++	6.31	8.30	461
	1.5+1.5+2.5+4.2	1.14	1.14	1.14	1.91	3.20	3.05	8.54	9.53	0.61	2.49	3.17	2.7	11.0	14.1	98	3.43	A	1245	A++	6.30	8.54	475
	1.5+1.5+2.5+5.0	1.10	1.10	1.10	1.84	3.68	3.17	8.82	9.81	0.61	2.56	3.26	2.7	11.4	14.5	98	3.45	A	1280	A++	6.24	8.82	495
	1.5+1.5+2.5+6.0	1.04	1.04	1.04	1.73	4.15	3.32	9.00	10.09	0.65	2.46	3.17	2.9	10.9	14.1	98	3.66	A	1230	A++	6.25	9.00	505
	1.5+1.5+2.5+7.1	0.96	0.96	0.96	1.60	4.53	3.48	9.00	10.32	0.65	2.47	3.33	2.9	11.0	14.8	98	3.64	A	1235	A++	6.25	9.00	505
	1.5+1.5+3.5+3.5	1.13	1.13	1.13	2.63	2.63	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6.20	8.65	489
	1.5+1.5+3.5+4.2	1.09	1.09	1.09	2.55	3.06	3.20	8.89	9.87	0.65	2.68	3.39	2.9	11.9	15.0	98	3.32	A	1340	A++	6.18	8.89	504
	1.5+1.5+3.5+5.0	1.04	1.04	1.04	2.42	3.46	3.32	9.00	10.09	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6.18	9.00	511
	1.5+1.5+3.5+6.0	0.96	0.96	0.96	2.25	3.86	3.46	9.00	10.31	0.65	2.46	3.32	2.9	10.9	14.7	98	3.66	A	1230	A++	6.18	9.00	510
	1.5+1.5+3.5+7.1	0.89	0.89	0.89	2.09	4.23	3.63	9.00	10.46	0.68	2.47	3.48	3.0	11.0	15.4	98	3.64	A	1235	A++	6.18	9.00	511
	1.5+1.5+4.2+4.2	1.05	1.05	1.05	2.93	2.93	3.30	9.00	9.99	0.65	2.75	3.47	2.9	12.2	15.4	98	3.27	A	1375	A++	6.18	9.00	510
	1.5+1.5+4.2+5.0	0.99	0.99	0.99	2.76	3.28	3.42	9.00	10.16	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6.18	9.00	510
	1.5+1.5+4.2+6.0	0.92	0.92	0.92	2.57	3.67	3.57	9.00	10.41	0.68	2.47	3.40	3.0	11.0	15.1	98	3.64	A	1235	A++	6.18	9.00	510
	1.5+1.5+5.0+5.0	0.93	0.93	0.93	3.10	3.10	3.54	9.00	10.34	0.68	2.58	3.52	3.0	11.4	15.6	98	3.49	A	1290	A++	6.18	9.00	511
	1.5+1.5+5.0+6.0	0.87	0.87	0.87	2.90	3.48	3.69	9.00	10.49	0.68	2.41	3.35	3.0	10.7	14.9	98	3.73	A	1205	A++	6.18	9.00	510

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
5MXS90E3V3B	1MA1A1A1A1A20	1.30	1.30	1.73	1.73	1.73	2.73	7.77	8.53	0.55	2.06	2.49	2.4	9.1	11.0	98	3.77	A	1030	A++	6,42	7,78	424
	1MA1A1A1A1A25	1.25	1.25	1.67	1.67	2.09	2.80	7.94	8.78	0.58	2.18	2.68	2.6	9.7	11.9	98	3.64	A	1090	A++	6,39	7,94	435
	1MA1A1A1A1A35	1.19	1.19	1.58	1.58	2.77	2.95	8.30	9.25	0.58	2.36	2.95	2.6	10.5	13.1	98	3.52	A	1180	A++	6,32	8,30	460
	1MA1A1A1A1A42	1.14	1.14	1.53	1.53	3.20	3.05	8.54	9.53	0.61	2.49	3.17	2.7	11.0	14.1	98	3.43	A	1245	A++	6,31	8,54	474
	1MA1A1A1A1A50	1.10	1.10	1.47	1.47	3.68	3.17	8.82	9.81	0.61	2.56	3.26	2.7	11.4	14.5	98	3.45	A	1280	A++	6,25	8,82	495
	1MA1A1A1A1A60	1.04	1.04	1.38	1.38	4.15	3.32	9.00	10.09	0.65	2.46	3.17	2.9	10.9	14.1	98	3.66	A	1230	A++	6,24	9,00	505
	1MA1A1A1A1A71	0.96	0.96	1.28	1.28	4.53	3.48	9.00	10.32	0.65	2.47	3.33	2.9	11.0	14.8	98	3.64	A	1235	A++	6,24	9,00	506
	1MA1A1A1A1A25	1.22	1.22	1.62	2.03	2.03	2.88	8.12	9.03	0.58	2.24	2.81	2.6	9.9	12.5	98	3.63	A	1120	A++	6,39	8,12	445
	1MA1A1A1A1A35	1.16	1.16	1.54	1.93	2.70	3.02	8.47	9.45	0.61	2.49	3.09	2.7	11.0	13.7	98	3.40	A	1245	A++	6,30	8,47	471
	1MA1A1A1A1A42	1.12	1.12	1.49	1.86	3.13	3.13	8.72	9.71	0.61	2.62	3.31	2.7	11.6	14.7	98	3.33	A	1310	A++	6,29	8,72	486
	1MA1A1A1A1A50	1.08	1.08	1.44	1.80	3.60	3.24	9.00	9.96	0.65	2.70	3.41	2.9	12.0	15.1	98	3.33	A	1350	A++	6,25	9,00	505
	1MA1A1A1A1A60	1.00	1.00	1.33	1.67	4.00	3.39	9.00	10.21	0.65	2.46	3.32	2.9	10.9	14.7	98	3.66	A	1230	A++	6,24	9,00	505
	1MA1A1A1A1A71	0.92	0.92	1.23	1.54	4.38	3.55	9.00	10.40	0.68	2.47	3.40	3.0	11.0	15.1	98	3.64	A	1235	A++	6,24	9,00	506
	1MA1A1A1A1A35	1.10	1.10	1.47	2.57	2.57	3.17	8.82	9.81	0.61	2.68	3.39	2.7	11.9	15.0	98	3.29	A	1340	A++	6,20	8,82	498
	1MA1A1A1A1A42	1.06	1.06	1.42	2.48	2.98	3.27	9.00	9.98	0.65	2.75	3.46	2.9	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	1.00	1.00	1.33	2.33	3.33	3.39	9.00	10.16	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.93	0.93	1.24	2.17	3.72	3.54	9.00	10.38	0.68	2.46	3.40	3.0	10.9	15.1	98	3.66	A	1230	A++	6,18	9,00	511
	1MA1A1A1A1A71	0.87	0.87	1.15	2.02	4.10	3.70	9.00	10.50	0.71	2.47	3.48	3.1	11.0	15.4	98	3.64	A	1235	A++	6,17	9,00	511
	1MA1A1A1A1A42	1.01	1.01	1.34	2.82	2.82	3.38	9.00	9.99	0.68	2.75	3.47	3.0	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.95	0.95	1.27	2.66	3.17	3.49	9.00	10.16	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.89	0.89	1.18	2.49	3.55	3.64	9.00	10.47	0.68	2.47	3.48	3.0	11.0	15.4	98	3.64	A	1235	A++	6,17	9,00	511
	1MA1A1A1A1A60	0.90	0.90	1.20	3.00	3.00	3.61	9.00	10.45	0.68	2.58	3.68	3.0	11.4	16.3	98	3.49	A	1290	A++	6,18	9,00	510
	1MA1A1A1A1A25	1.19	1.19	1.98	1.98	1.98	2.95	8.30	9.25	0.58	2.36	2.95	2.6	10.5	13.1	98	3.52	A	1180	A++	6,39	8,30	455
	1MA1A1A1A1A35	1.13	1.13	1.88	1.88	2.63	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6,30	8,65	481
	1MA1A1A1A1A42	1.09	1.09	1.82	1.82	3.06	3.20	8.89	9.87	0.65	2.68	3.39	2.9	11.9	15.0	98	3.32	A	1340	A++	6,24	8,89	499
	1MA1A1A1A1A50	1.04	1.04	1.73	1.73	3.46	3.32	9.00	10.09	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6,25	9,00	505
	1MA1A1A1A1A60	0.96	0.96	1.61	1.61	3.86	3.46	9.00	10.31	0.65	2.46	3.40	2.9	10.9	15.1	98	3.66	A	1230	A++	6,24	9,00	505
	1MA1A1A1A1A71	0.89	0.89	1.49	1.49	4.23	3.63	9.00	10.46	0.68	2.47	3.48	3.0	11.0	15.4	98	3.64	A	1235	A++	6,24	9,00	506
	1MA1A1A1A1A35	1.08	1.08	1.80	2.52	2.52	3.24	9.00	9.96	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6,18	9,00	510
	1MA1A1A1A1A42	1.02	1.02	1.70	2.39	2.86	3.35	9.00	9.98	0.65	2.75	3.46	2.9	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.96	0.96	1.61	2.25	3.21	3.46	9.00	10.16	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.90	0.90	1.50	2.10	3.60	3.61	9.00	10.45	0.68	2.46	3.48	3.0	10.9	15.4	98	3.66	A	1230	A++	6,17	9,00	511
	1MA1A1A1A1A42	0.97	0.97	1.62	2.72	2.72	3.45	9.00	9.99	0.68	2.75	3.47	3.0	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.92	0.92	1.53	2.57	3.06	3.57	9.00	10.41	0.68	2.70	3.81	3.0	12.0	16.9	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.87	0.87	1.45	2.90	2.90	3.69	9.00	10.49	0.71	2.58	3.68	3.1	11.4	16.3	98	3.49	A	1290	A++	6,18	9,00	510
	1MA1A1A1A1A35	1.00	1.00	2.33	2.33	2.33	3.39	9.00	9.98	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6,12	9,00	515
	1MA1A1A1A1A42	0.95	0.95	2.22	2.22	2.66	3.49	9.00	9.99	0.68	2.75	3.47	3.0	12.2	15.4	98	3.27	A	1375	A++	6,12	9,00	515
	1MA1A1A1A1A50	0.90	0.90	2.10	2.10	3.00	3.61	9.00	10.45	0.71	2.70	3.80	3.1	12.0	16.9	98	3.33	A	1350	A++	6,12	9,00	515
	1MA1A1A1A1A42	0.91	0.91	2.11	2.54	2.54	3.60	9.00	10.44	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6,12	9,00	515
	1MA1A1A1A1A20	1.25	1.67	1.67	1.67	1.67	2.80	7.94	8.78	0.58	2.18	2.68	2.6	9.7	11.9	98	3.64	A	1090	A++	6,41	7,94	434
	1MA1A1A1A1A25	1.22	1.62	1.62	1.62	2.03	2.88	8.12	9.03	0.58	2.24	2.81	2.6	9.9	12.5	98	3.63	A	1120	A++	6,39	8,12	445
	1MA1A1A1A1A35	1.16	1.54	1.54	1.54	2.70	3.02	8.47	9.45	0.61	2.49	3.09	2.7	11.0	13.7	98	3.40	A	1245	A++	6,32	8,47	470
	1MA1A1A1A1A42	1.12	1.49	1.49	1.49	3.13	3.13	8.72	9.71	0.61	2.62	3.31	2.7	11.6	14.7	98	3.33	A	1310	A++	6,29	8,72	486
	1MA1A1A1A1A50	1.08	1.44	1.44	1.44	3.60	3.24	9.00	9.96	0.65	2.70	3.41	2.9	12.0	15.1	98	3.33	A	1350	A++	6,24	9,00	505
	1MA1A1A1A1A60	1.00	1.33	1.33	1.33	4.00	3.39	9.00	10.21	0.65	2.46	3.32	2.9	10.9	14.7	98	3.66	A	1230	A++	6,24	9,00	506
	1MA1A1A1A1A71	0.92	1.23	1.23	1.23	4.38	3.55	9.00	10.40	0.68	2.47	3.40	3.0	11.0	15.1	98	3.64	A	1235	A++	6,23	9,00	506
	1MA1A1A1A1A25	1.19	1.58	1.58	1.98	1.98	2.95	8.30	9.25	0.58	2.36	2.95	2.6	10.5	13.1	98	3.52	A	1180	A++	6,39	8,30	455
	1MA1A1A1A1A35	1.13	1.50	1.50	1.88	2.63	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6,30	8,65	481
	1MA1A1A1A1A42	1.09	1.46	1.46	1.82	3.06	3.20	8.89	9.87	0.65	2.68	3.39	2.9	11.9	15.0	98	3.32	A	1340	A++	6,24	8,89	499
	1MA1A1A1A1A50	1.04	1.38	1.38	1.73	3.46	3.32	9.00	10.09	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6,25	9,00	505
	1MA1A1A1A1A60	0.96	1.29	1.29	1.61	3.86	3.46	9.00	10.31	0.65	2.46	3.40	2.9	10.9	15.1	98	3.66	A	1230	A++	6,23	9,00	506
	1MA1A1A1A1A71	0.89	1.19	1.19	1.49	4.23	3.63	9.00	10.46	0.68	2.47	3.48	3.0	11.0	15.4	98	3.64	A	1235	A++	6,23	9,00	506
	1MA1A1A1A1A35	1.08	1.44	1.44	2.52	2.52	3.24	9.00	9.96	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6,18	9,00	510
	1MA1A1A1A1A42	1.02	1.36	1.36	2.39	2.86	3.35	9.00	9.98	0.65	2.75	3.46	2.9	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.96	1.29	1.29	2.25	3.21	3.46	9.00	10.16	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.90	1.20	1.20	2.10	3.60	3.61	9.00	10.45	0.68	2.46	3.48	3.0	10.9	15.4	98	3.66	A	1230	A++	6,17	9,00	511
	1MA1A1A1A1A42	0.97	1.29	1.29	2.72	2.72	3.45	9.00	9.99	0.68	2.75	3.47	3.0	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.92	1.22	1.22	2.57	3.06	3.57	9.00	10.41	0.68	2.70	3.81	3.0	12.0	16.9	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.87	1.16	1.16	2.90	2.90	3.69	9.00	10.49	0.71	2.58	3.68	3.1	11.4	16.3	98	3.49	A	1290	A++	6,18	9,00	510
	1MA1A1A1A1A25	1.16	1.54	1.93	1.93	1.93	3.02	8.47	9.45	0.61	2.49	3.09	2.7	11.0	13.7	98	3.40	A	1245	A++	6,39	8,47	465
	1MA1A1A1A1A35	1.10	1.47	1.84	1.84	2.57	3.17	8.82	9.81	0.61	2.68	3.39	2.7	11.9	15.0	98	3.29	A	1340	A++	6,27	8,82	493
	1MA1A1A1A1A42	1.06	1.42	1.77	1.77	2.98	3.27	9.00	9.97	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6,25	9,00	505
	1MA1A1A1A1A50	1.00	1.33	1.67	1.67	3.33	3.39	9.00	10.15	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6,25	9,00	505
	1MA1A1A1A1A60	0.93	1.24	1.55	1.55	3.72	3.54	9.00	10.38	0.68	2.46	3.40	3.0	10.9	15.1	98	3.66	A	1230	A++	6,23	9,00	506
	1MA1A1A1A1A71	0.87	1.15	1.44	1.44	4.10	3.70	9.00	10.50	0.71	2.47	3.48	3.1	11.0	15.4	98	3.64	A	1235	A++	6,23	9,00	506
	1MA1A1A1A1A35	1.04	1.38	1.73	2.42	2.42	3.32	9.00	9.97	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6,18	9,00	510
	1MA1A1A1A1A42	0.99	1.31	1.64	2.30	2.76	3.42	9.00	9.98	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.93	1.24	1.55	2.17	3.10	3.54	9.00	10.16	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A60	0.87	1.16	1.45	2.03	3.48	3.69	9.00	10.49	0.71	2.46	3.48	3.1	10.9	15.4	98	3.66	A	1230	A++	6,17	9,00	511
	1MA1A1A1A1A42	0.94	1.25	1.56	2.63	2.63	3.52	9.00	9.99	0.68	2.75	3.47	3.0	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.89	1.18	1.48	2.49	2.96	3.64	9.00	10.47	0.71	2.70	3.89	3.1	12.0	17.3	98	3.33	A	1350	A++	6,18	9,00	510
	1MA1A1A1A1A35	0.96	1.29	2.25	2.25	2.25	3.46	9.00	9.98	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6,12	9,00	515
	1MA1A1A1A1A42	0.92	1.22	2.14	2.14	2.57	3.57	9.00	10.41	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6,12	9,00	515
	1MA1A1A1A1A50	0.87	1.16	2.03	2.03	2.90	3.69	9.00	10.49	0.71	2.70	3.88	3.1	12.0	17.2	98	3.33	A	1350	A++	6,12	9,00	515
	1MA1A1A1A1A42	0.88	1.17	2.05	2.45	2.45	3.67	9.00	10.48	0.71	2.75	4.09	3.1	12.2	18.1	98	3.27	A	1375	A++	6,12	9,00	515
	1MA1A1A1A1A25	1.13	1.88	1.88	1.88	1.88	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6,37	8,65	476
	1MA1A1A1A1A35	1.08	1.80	1.80	1.80	2.52	3.24	9.00	9.96	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6,25	9,00	505
	1MA1A1A1A1A42	1.02	1.70	1.70	1.70	2.86	3.35	9.00	9.97	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6,25	9,00	505
	1MA1A1A1A1A50	0.96	1.61	1.61	1.61	3.21	3.46	9.00	10.15	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6,25	9,00	505
	1MA1A1A1A1A60	0.90	1.50	1.50	1.50	3.60	3.61	9.00	10.45	0.68	2.46	3.48	3.0	10.9	15.4	98	3.66	A	1230	A++	6,23	9,00	506
	1MA1A1A1A1A35	1.00	1.67	1.67	2.33	2.33	3.39	9.00	9.97	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6,18	9,00	510
	1MA1A1A1A1A42	0.95	1.58	1.58	2.22	2.66	3.49	9.00	9.98	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6,18	9,00	510
	1MA1A1A1A1A50	0.90	1.50	1.50	2.10	3.00	3.61	9.00	10.45	0.71	2.70	3.80	3.1	12.0	16.9	98	3.33	A	1350	A++	6,18	9,00	510

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
5MXS90E3V3B	1542542542542	0.91	1.51	1.51	2.54	2.54	3.60	9.00	10.44	0.71	2.75	4.09	3.1	12.2	18.1	98	3.27	A	1375	A++	6.18	9.00	510
1542542542535	0.93	1.55	2.17	2.17	2.17	3.54	9.00	9.98	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.12	9.00	515
1542542542442	0.89	1.48	2.07	2.07	2.49	3.64	9.00	10.47	0.71	2.75	4.09	3.1	12.2	18.1	98	3.27	A	1375	A++	6.12	9.00	515
1542542542435	0.87	2.03	2.03	2.03	2.03	3.69	9.00	10.49	0.71	2.75	4.17	3.1	12.2	18.5	98	3.27	A	1375	A+	6.06	9.00	521
2042042042042	1.63	1.63	1.63	1.63	1.63	2.88	8.15	9.03	0.58	2.30	2.81	2.6	10.2	12.5	98	3.54	A	1150	A++	6.40	8.15	446
2042042042035	1.58	1.58	1.58	1.58	1.98	2.95	8.30	9.25	0.58	2.36	2.95	2.6	10.5	13.1	98	3.52	A	1180	A++	6.39	8.30	455
2042042042035	1.50	1.50	1.50	1.50	2.65	3.10	8.65	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.39	A	1275	A++	6.30	8.65	481
2042042042042	1.46	1.46	1.46	1.46	3.05	3.20	8.89	9.87	0.65	2.68	3.39	2.9	11.9	15.0	98	3.32	A	1340	A++	6.24	8.89	499
2042042042050	1.38	1.38	1.38	1.38	3.48	3.32	9.00	10.09	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6.25	9.00	505
2042042042060	1.29	1.29	1.29	1.29	3.84	3.46	9.00	10.31	0.65	2.50	3.40	2.9	11.1	15.1	98	3.60	A	1250	A++	6.23	9.00	506
2042042042071	1.19	1.19	1.19	1.19	4.24	3.63	9.00	10.46	0.68	2.47	3.48	3.0	11.0	15.4	98	3.64	A	1235	A++	6.21	9.00	508
2042042042025	1.54	1.54	1.54	1.92	1.92	3.02	8.46	9.45	0.61	2.49	3.09	2.7	11.0	13.7	98	3.40	A	1245	A++	6.38	8.46	464
2042042042035	1.47	1.47	1.47	1.84	2.57	3.17	8.82	9.81	0.61	2.68	3.39	2.7	11.9	15.0	98	3.29	A	1340	A++	6.27	8.82	493
2042042042542	1.42	1.42	1.42	1.77	2.97	3.27	9.00	9.97	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6.25	9.00	505
2042042042550	1.33	1.33	1.33	1.67	3.34	3.39	9.00	10.15	0.65	2.70	3.49	2.9	12.0	15.5	98	3.33	A	1350	A++	6.25	9.00	505
2042042042560	1.24	1.24	1.24	1.55	3.73	3.54	9.00	10.38	0.68	2.50	3.40	3.0	11.1	15.1	98	3.60	A	1250	A++	6.22	9.00	507
2042042042571	1.15	1.15	1.15	1.44	4.11	3.70	9.00	10.50	0.71	2.47	3.48	3.1	11.0	15.4	98	3.64	A	1235	A++	6.21	9.00	508
2042042042535	1.54	1.54	1.54	1.92	1.92	3.02	8.46	9.45	0.61	2.49	3.09	2.7	11.0	13.7	98	3.40	A	1245	A++	6.24	8.46	475
2042042042542	1.31	1.31	1.31	2.31	2.76	3.42	9.00	9.98	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.18	9.00	510
2042042042560	1.24	1.24	1.24	2.17	3.11	3.54	9.00	10.16	0.68	2.74	3.49	3.0	12.2	15.5	98	3.28	A	1370	A++	6.18	9.00	510
2042042042560	1.16	1.16	1.16	2.03	3.49	3.69	9.00	10.49	0.71	2.46	3.48	3.1	10.9	15.4	98	3.66	A	1230	A++	6.15	9.00	513
2042042042542	1.24	1.24	1.24	2.64	2.64	3.52	9.00	9.99	0.68	2.75	3.47	3.0	12.2	15.4	98	3.27	A	1375	A++	6.18	9.00	510
2042042042450	1.18	1.18	1.18	2.50	2.96	3.64	9.00	10.47	0.71	2.70	3.89	3.1	12.0	17.3	98	3.33	A	1350	A++	6.18	9.00	510
2042042042535	1.51	1.51	1.88	1.88	1.88	3.10	8.66	9.64	0.61	2.55	3.24	2.7	11.3	14.4	98	3.40	A	1275	A++	6.37	8.66	477
2042042542542	1.44	1.44	1.80	1.80	2.52	3.24	9.00	9.96	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6.25	9.00	505
2042042542542	1.37	1.37	1.70	1.70	2.86	3.35	9.00	9.66	0.65	2.86	3.46	2.9	12.7	15.4	98	3.15	B	1430	A++	6.25	9.00	505
2042042542450	1.29	1.29	1.61	1.61	3.20	3.46	9.00	10.15	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6.25	9.00	505
2042042542460	1.20	1.20	1.50	1.50	3.60	3.61	9.00	10.45	0.68	2.46	3.48	3.0	10.9	15.4	98	3.66	A	1230	A++	6.22	9.00	507
2042042542535	1.33	1.33	1.68	2.33	2.33	3.39	9.00	9.97	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.18	9.00	510
2042042542542	1.27	1.27	1.58	2.22	2.66	3.49	9.00	9.66	0.68	2.79	3.46	3.0	12.4	15.4	98	3.23	A	1395	A++	6.18	9.00	510
2042042542450	1.20	1.20	1.50	2.10	3.00	3.61	9.00	10.45	0.71	2.70	3.80	3.1	12.0	16.9	98	3.33	A	1350	A++	6.18	9.00	510
2042042542442	1.21	1.21	1.50	2.54	2.54	3.60	9.00	10.44	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.18	9.00	510
2042042542535	1.23	1.23	2.18	2.18	2.18	3.54	9.00	9.98	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.12	9.00	515
2042042542542	1.18	1.18	2.07	2.07	2.50	3.64	9.00	10.47	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.12	9.00	515
2042542542535	1.46	1.84	1.84	1.84	1.84	3.17	8.82	9.81	0.61	2.68	3.39	2.7	11.9	15.0	98	3.29	A	1340	A++	6.34	8.82	488
2042542542535	1.39	1.73	1.73	1.73	2.42	3.32	9.00	9.96	0.65	2.82	3.46	2.9	12.5	15.4	98	3.19	B	1410	A++	6.25	9.00	505
2042542542542	1.32	1.64	1.64	1.64	2.76	3.42	9.00	9.97	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.25	9.00	505
2042542542560	1.25	1.55	1.55	1.55	3.10	3.54	9.00	10.15	0.68	2.70	3.49	3.0	12.0	15.5	98	3.33	A	1350	A++	6.25	9.00	505
2042542542560	1.17	1.45	1.45	1.45	3.48	3.69	9.00	10.49	0.71	2.46	3.48	3.1	10.9	15.4	98	3.66	A	1230	A++	6.22	9.00	507
2042542542535	1.28	1.61	1.61	2.25	2.25	3.46	9.00	9.97	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.18	9.00	510
2042542542542	1.23	1.53	1.53	2.14	2.57	3.57	9.00	10.41	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.18	9.00	510
2042542542560	1.17	1.45	1.45	2.03	2.90	3.69	9.00	10.49	0.71	2.70	3.88	3.1	12.0	17.2	98	3.33	A	1350	A++	6.18	9.00	510
2042542542442	1.18	1.46	1.46	2.45	2.45	3.64	9.00	10.47	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.18	9.00	510
2042542542535	1.20	1.50	2.10	2.10	2.10	3.61	9.00	10.42	0.71	2.82	4.01	3.1	12.5	17.8	98	3.19	B	1410	A++	6.12	9.00	515
2542542542535	1.80	1.80	1.80	1.80	1.80	3.24	9.00	9.95	0.65	2.81	3.46	2.9	12.5	15.4	98	3.20	A	1405	A++	6.31	9.00	499
2542542542535	1.67	1.67	1.67	1.67	2.32	3.39	9.00	9.96	0.68	2.75	3.46	3.0	12.2	15.4	98	3.27	A	1375	A++	6.25	9.00	505
2542542542542	1.58	1.58	1.58	1.58	2.68	3.49	9.00	9.97	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.25	9.00	505
2542542542560	1.50	1.50	1.50	1.50	3.00	3.61	9.00	10.45	0.71	2.70	3.88	3.1	12.0	17.2	98	3.33	A	1350	A++	6.25	9.00	505
2542542542535	1.56	1.56	1.56	2.16	2.16	3.54	9.00	9.97	0.68	2.82	3.46	3.0	12.5	15.4	98	3.19	B	1410	A++	6.18	9.00	510
2542542542442	1.48	1.48	1.48	2.07	2.49	3.64	9.00	10.47	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.18	9.00	510
2542542542535	1.44	1.44	2.04	2.04	2.04	3.69	9.00	10.42	0.71	2.75	4.01	3.1	12.2	17.8	98	3.27	A	1375	A++	6.12	9.00	515

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
5MXS90E3V3B	1.5+1.5	1.83	1.83	---	---	---	1.48	3.66	5.75	0.39	0.91	1.48	1.7	4.0	6.6	98	4.02	A	A	3.85	3.41	1239	0.63
	1.5+2.0	1.83	2.44	---	---	---	1.54	4.27	5.75	0.37	1.04	1.48	1.6	4.6	6.6	98	4.11	A	A	3.85	3.47	1262	0.62
	1.5+2.5	1.83	3.05	---	---	---	1.69	4.88	7.46	0.39	1.21	2.09	1.7	5.4	9.3	98	4.03	A	A	3.86	3.50	1269	0.64
	1.5+3.5	1.83	4.26	---	---	---	1.98	6.09	7.46	0.47	1.71	2.29	2.1	7.6	10.2	98	3.56	B	A	3.82	3.82	1399	0.68
	1.5+4.2	1.83	5.12	---	---	---	2.19	6.95	8.53	0.45	2.09	2.81	2.0	9.3	12.5	98	3.33	C	A	3.84	3.86	1409	0.72
	1.5+5.0	1.83	6.09	---	---	---	2.43	7.92	9.09	0.47	2.16	2.66	2.1	9.6	11.8	98	3.67	A	A	3.84	3.78	1377	0.71
	1.5+6.0	1.79	7.14	---	---	---	2.72	8.93	9.88	0.51	2.47	2.96	2.3	11.0	13.1	98	3.62	A	A	3.84	4.30	1567	0.81
	1.5+7.1	1.69	8.00	---	---	---	3.03	9.69	9.90	0.55	2.83	2.94	2.4	12.6	13.0	98	3.42	B	A	3.86	4.53	1643	0.84
	2.0+2.0	2.44	2.44	---	---	---	1.69	4.88	6.85	0.39	1.21	1.87	1.7	5.4	8.3	98	4.03	A	A	3.85	3.54	1289	0.68
	2.0+2.5	2.44	3.05	---	---	---	1.84	5.49	7.25	0.41	1.40	2.05	1.8	6.2	9.1	98	3.92	A	A	3.84	3.57	1303	0.64
	2.0+3.5	2.44	4.26	---	---	---	2.13	6.70	7.74	0.50	1.99	2.44	2.2	8.8	10.8	98	3.37	C	A	3.82	3.91	1432	0.70
	2.0+4.2	2.44	5.11	---	---	---	2.34	7.55	8.53	0.62	2.33	2.81	2.8	10.3	12.5	98	3.24	C	A	3.83	3.95	1446	0.74
	2.0+5.0	2.44	6.09	---	---	---	2.57	8.53	9.09	0.63	2.45	2.66	2.8	10.9	11.8	98	3.48	B	A	3.84	3.87	1412	0.73
	2.0+6.0	2.32	6.95	---	---	---	2.86	9.27	9.88	0.65	2.63	2.96	2.9	11.7	13.1	98	3.52	B	A	3.85	4.42	1606	0.87
	2.0+7.1	2.20	7.83	---	---	---	3.17	10.03	10.37	0.69	3.01	3.18	3.1	13.4	14.1	98	3.33	C	A	3.88	4.66	1684	0.90
	2.5+2.5	3.04	3.04	---	---	---	1.98	6.08	7.46	0.47	1.76	2.35	2.1	7.8	10.4	98	3.45	B	A	3.84	3.60	1312	0.67
	2.5+3.5	3.05	4.26	---	---	---	2.28	7.31	8.53	0.60	2.34	2.94	2.7	10.4	13.0	98	3.12	D	A	3.87	3.96	1434	0.75
	2.5+4.2	3.04	5.12	---	---	---	2.49	8.16	9.02	0.65	2.76	3.18	2.9	12.2	14.1	98	2.96	D	A	3.82	4.00	1465	0.72
	2.5+5.0	2.98	5.95	---	---	---	2.72	8.93	9.70	0.66	2.61	2.99	2.9	11.6	13.3	98	3.42	B	A	3.83	3.92	1435	0.71
	2.5+6.0	2.83	6.79	---	---	---	3.00	9.62	9.88	0.67	2.86	3.03	3.0	12.7	13.4	98	3.36	C	A	3.85	4.48	1629	0.86
	2.5+7.1	2.70	7.68	---	---	---	3.31	10.38	10.77	0.72	3.22	3.46	3.2	14.3	15.4	98	3.22	C	A	3.89	4.73	1701	0.91
	3.5+3.5	4.27	4.27	---	---	---	2.57	8.54	9.02	0.65	2.91	3.15	2.9	12.9	14.0	98	2.93	D	A	3.84	4.42	1610	0.87
	3.5+4.2	4.12	4.94	---	---	---	2.77	9.06	9.60	0.70	3.21	3.53	3.1	14.2	15.7	98	2.82	D	A	3.84	4.47	1630	0.85
	3.5+5.0	3.96	5.66	---	---	---	3.00	9.62	9.70	0.71	2.93	2.98	3.1	13.0	13.2	98	3.28	C	A	3.83	4.36	1595	0.81
	3.5+6.0	3.80	6.51	---	---	---	3.28	10.31	10.75	0.72	3.19	3.43	3.2	14.2	15.2	98	3.23	C	A	3.87	5.06	1830	0.97
	3.5+7.1	3.43	6.97	---	---	---	3.59	10.40	10.78	0.77	3.11	3.35	3.4	13.8	14.9	98	3.34	C	A	3.91	5.35	1917	1.00
	4.2+4.2	4.77	4.77	---	---	---	2.97	9.54	9.61	0.72	3.47	3.53	3.2	15.4	15.7	98	2.75	E	A	3.85	4.52	1644	0.83
	4.2+5.0	4.61	5.49	---	---	---	3.20	10.10	10.12	0.73	3.22	3.28	3.2	14.3	14.6	98	3.14	D	A	3.84	4.41	1607	0.86
	4.2+6.0	4.28	6.12	---	---	---	3.48	10.40	10.76	0.75	3.24	3.42	3.3	14.4	15.2	98	3.21	C	A	3.89	5.12	1845	0.97
	4.2+7.1	3.87	6.53	---	---	---	3.79	10.40	10.78	0.79	3.11	3.34	3.5	13.8	14.8	98	3.34	C	A	3.91	5.41	1940	1.00
	5.0+5.0	5.20	5.20	---	---	---	3.42	10.40	10.64	0.76	3.28	3.40	3.4	14.6	15.1	98	3.17	D	A	3.84	4.31	1573	0.82
	5.0+6.0	4.73	5.67	---	---	---	3.70	10.40	10.88	0.75	3.08	3.31	3.3	13.7	14.7	98	3.38	C	A	3.87	4.99	1806	0.97
	5.0+7.1	4.30	6.10	---	---	---	4.01	10.40	10.51	0.83	3.01	3.06	3.7	13.4	13.6	98	3.46	B	A	3.89	5.28	1900	1.00
	6.0+6.0	5.20	5.20	---	---	---	3.99	10.40	10.71	0.76	2.88	3.04	3.4	12.8	13.5	98	3.61	A	A	3.92	5.83	2080	1.10
	6.0+7.1	4.76	5.64	---	---	---	4.30	10.40	10.74	0.84	2.86	3.03	3.7	12.7	13.4	98	3.64	A	A	3.95	6.17	2187	1.20
	7.1+7.1	5.20	5.20	---	---	---	4.61	10.40	10.77	0.89	2.85	3.02	3.9	12.6	13.4	98	3.65	A	A	3.95	6.46	2289	1.26
	1.5+1.5+1.5	1.83	1.83	1.83	---	---	1.84	5.50	7.52	0.47	1.24	1.92	2.1	5.5	8.5	98	4.44	A	A	3.85	4.40	1599	0.85
	1.5+1.5+2.0	1.83	1.83	2.44	---	---	1.98	6.10	7.52	0.49	1.39	1.92	2.2	6.2	8.5	98	4.39	A	A	3.84	4.52	1648	0.83
	1.5+1.5+2.5	1.83	1.83	3.05	---	---	2.13	6.71	7.52	0.51	1.63	1.92	2.3	7.2	8.5	98	4.12	A	A	3.85	4.58	1667	0.89
	1.5+1.5+3.5	1.83	1.83	4.27	---	---	2.43	7.93	9.22	0.55	2.04	2.57	2.4	9.1	11.4	98	3.89	A	A	3.87	5.18	1874	0.96
	1.5+1.5+4.2	1.82	1.82	5.09	---	---	2.63	8.73	9.22	0.60	2.37	2.57	2.7	10.5	11.4	98	3.68	A	A	3.88	5.24	1890	1.02
	1.5+1.5+5.0	1.74	1.74	5.80	---	---	2.86	9.28	9.99	0.60	2.53	2.84	2.7	11.2	12.6	98	3.67	A	A	3.88	5.11	1842	0.96
	1.5+1.5+6.0	1.66	1.66	6.65	---	---	3.14	9.97	10.71	0.61	2.65	3.04	2.7	11.8	13.5	98	3.76	A	A	3.90	5.97	2143	1.12
	1.5+1.5+7.1	1.55	1.55	7.32	---	---	3.45	10.41	10.75	0.65	2.86	3.03	2.9	12.7	13.4	98	3.64	A	A	3.93	6.32	2252	1.23
	1.5+2.0+2.0	1.83	2.44	2.44	---	---	2.13	6.71	7.52	0.51	1.63	1.92	2.3	7.2	8.5	98	4.12	A	A	3.85	4.65	1693	0.89
	1.5+2.0+2.5	1.83	2.44	3.05	---	---	2.28	7.32	8.67	0.53	1.83	2.32	2.4	8.1	10.3	98	4.00	A	A	3.85	4.72	1718	0.90
	1.5+2.0+3.5	1.83	2.44	4.27	---	---	2.58	8.54	9.22	0.57	2.27	2.57	2.5	10.1	11.4	98	3.76	A	A	3.87	5.34	1931	0.99
	1.5+2.0+4.2	1.77	2.36	4.95	---	---	2.77	9.07	9.89	0.62	2.47	2.89	2.8	11.0	12.8	98	3.67	A	A	3.90	5.40	1937	1.05
	1.5+2.0+5.0	1.70	2.27	5.66	---	---	3.00	9.63	9.99	0.62	2.68	2.84	2.8	11.9	12.6	98	3.59	B	A	3.87	5.27	1906	0.99
	1.5+2.0+6.0	1.63	2.17	6.52	---	---	3.28	10.32	10.71	0.64	2.82	3.04	2.8	12.5	13.5	98	3.66	A	A	3.94	6.16	2189	1.19
	1.5+2.0+7.1	1.47	1.96	6.97	---	---	3.59	10.41	10.75	0.68	2.86	3.03	3.0	12.7	13.4	98	3.64	A	A	3.94	6.46	2297	1.26
	1.5+2.5+2.5	1.83	3.05	3.05	---	---	2.43	7.93	9.21	0.55	2.05	2.58	2.4	9.1	11.4	98	3.87	A	A	3.86	4.78	1734	0.89
	1.5+2.5+3.5	1.79	2.98	4.17	---	---	2.72	8.94	9.89	0.60	2.42	2.89	2.7	10.7	12.8	98	3.69	A	A	3.89	5.42	1951	1.01
	1.5+2.5+4.2	1.72	2.87	4.82	---	---	2.91	9.42	9.89	0.64	2.62	2.89	2.8	11.6	12.8	98	3.60	B	A	3.90	5.48	1967	1.07
	1.5+2.5+5.0	1.66	2.77	5.54	---	---	3.14	9.97	10.48	0.65	2.84	3.07	2.9	12.6	13.6	98	3.51	B	A	3.87	5.34	1931	0.99
	1.5+2.5+6.0	1.56	2.60	6.25	---	---	3.42	10.41	10.71	0.66	2.87	3.04	2.9	12.7	13.5	98	3.63	A	A	3.92	6.25	2233	1.16
	1.5+2.5+7.1	1.41	2.34	6.66	---	---	3.73	10.41	10.75	0.70	2.86	3.03	3.1	12.7	13.4	98	3.64	A	A	3.94	6.46	2298	1.26
	1.5+3.5+3.5	1.70	3.97	3.97	---	---	3.00	9.63	9.89	0.64	2.73	2.89	2.8	12.1	12.8	98	3.53	B	A	3.93	6.16	2193	1.19
	1.5+3.5+4.2	1.65	3.85	4.62	---	---	3.20	10.11	10.37	0.69	3.01	3.12	3.1	13.4	13.8	98	3.36	C	A	3.92	6.23	2224	1.20
	1.5+3.5+5.0	1.56	3.64	5.21	---	---	3.42	10.41	10.49	0.70	3.07	3.07	3.1	13.6	13.6	98	3.39	C	A	3.94	6.07	2157	1.16
	1.5+3.5+6.0	1.42	3.31	5.68	---	---	3.70	10.41	10.72	0.71	2.87	3.04	3.1	12.7	13.5	98	3.63	A	A	3.97	6.46	2280	1.25
	1.5+3.5+7.1	1.29	3.01	6.11	---	---	4.01	10.41	10.75	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A+	4.03	6.46	2245	1.25
	1.5+4.2+4.2	1.58	4.42	4.42	---	---	3.39	10.41	10.48	0.72	3.17	3.17	3.2	14.1	14.1	98	3.28	C	A	3.92	6.31	2255	1.22
	1.5+4.2+5.0	1.46	4.09	4.86	---	---	3.62	10.41	10.61	0.75	3.07	3.07	3.3	13.6	13.6	98	3.39	C	A	3.93	6.14	2187	1.17
	1.5+4.2+6.0	1.33	3.74	5.34	---	---	3.90	10.41	10.84	0.76	2.87	3.04	3.4	12.7	13.5	98	3.63	A	A	3.99	6.46	2267	1.25
	1.5+4.2+7.1	1.22	3.42	5.77	---	---	4.21	10.41	10.87	0.81	2.86	3.02	3.6	12.7	13.4	98	3.64	A	A+	4.04	6.46	2241	1.25
	1.5+5.0+5.0	1.36	4.53	4.53	---	---	3.84	10.41	10.74	0.75	2.96	3.08	3.3	13.1	13.7	98	3.52	B	A	3.90	5.98	2150	1.13
	1.5+5.0+6.0	1.25	4.16	5.00	---	---	4.13	10.41	10.97	0.76	2.77	2.99	3.4	12.3	13.3	98	3.76	A	A	3.97	6.46	2279	1.25
	1.5+5.0+7.1	1.15	3.83	5.43	---	---	4.44	10.41	11.00	0.84	2.75	2.97	3.7	12.2	13.2	98	3.79	A	A+	4.03	6.46	2246	1.25
	1.5+6.0+6.0	1.16	4.63	4.63	---	---	4.41	10.41	11.20	0.77	2.62	2.90	3.4	11.6	12.9	98	3.97	A	A+	4.07	6.46	2224	1.24
	1.5+6.0+7.1	1.07	4.28	5.06	---	---	4.72	10.41	11.23	0.84	2.61	2.89	3.7	11.6	12.8	98	3.99	A	A+	4.10	6.46	2204	1.24
	2.0+2.0+2.0	2.44	2.44	2.44	---	---	2.28	7.32	8.67	0.53	1.84	2.32	2.4	8.2	10.3	98	3.98	A	A	3.86	4.79	1736	0.90
	2.0+2.0+2.5	2.44	2.44	3.04	---	---	2.43	7.92	9.21	0.55	2.05	2.58	2.4	9.1	11.4	98	3.86	A	A	3.86	4.86	1763	0.90
	2.0+2.0+3.5	2.38	2.38	4.17	---	---	2.72	8.93	9.89	0.60	2.42	2.89	2.7	10.7	12.8	98	3.69	A	A	3.89	5.50	1979	1.02
	2.0+2.0+4.2	2.30	2.30	4.81	---	---	2.91	9.41	9.89	0.64	2.62	2.89	2.8	11.6	12.8	98	3.59	B	A	3.89	5.57	2004	1.03
	2.0+2.0+5.0	2.21	2.21	5.54	---	---	3.14	9.96	10.48	0.65	2.84	3.07	2.9	12.6	13.6	98	3.51	B	A	3.89	5.43	1953	1.02
	2.0+2.0+6.0	2.08	2.08	6.24	---	---	3.42	10.40	10.71	0.66	2.87	3.04	2.9	12.7	13.5	98	3.62	A	A	3.92	6.35	2269	1.21
	2.0+2.0+7.1	1.87	1.87	6.66	---	---	3.73	10.40	10.75	0.70	2.86	3.03	3.1	12.7	13.4	98	3.64	A	A	3.94	6.46	2297	1.26
	2.0+2.5+2.5	2.43	3.05	3.05	---	---	2.57	8.53	9.21	0.57	2.28	2.58	2.5	10.1	11.4	98	3.74	A	A	3.86	4.93	1789	0.91
	2.0+2.5+3.5	2.31	2.90	4.06	---	---	2.86	9.27	9.89	0.62	2.57	2.89	2.8	11.4	12.8	98	3.61	A	A	3.89	5.59	2014	1.05
	2.0+2.5+4.2	2.24	2.80	4.71	---	---	3.06	9.75	10.36	0.67	2.78	3.12	3.0	12.3	13.8	98	3.51	B	A	3.88	5.65	2038	1.05
	2.0+2.5+5.0	2.17	2.71	5.43	---	---	3.28	10.31	10.48	0.67	3.02	3.07	3.0	13.4	13.6	98	3.41	B	A	3.89	5.51	1983	1.03
	2.0+2.5+6.0	1.98	2.48	5.94	---	---	3.56	10.40	10.71	0.68	2.87	3.04	3.0	12.7	13.5	98	3.62	A	A	3.94	6.45	2295	1.25

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
5MXS90E3V3B	2.0+2.5+7.1	1.79	2.24	6.37	---	---	3.87	10.40	10.75	0.73	2.86	3.03	3.2	12.7	13.4	98	3.64	A	A	3.97	6.46	2278	1.25
	2.0+3.5+3.5	2.22	3.87	3.87	---	---	3.14	9.96	10.36	0.69	2.89	3.12	3.1	12.8	13.8	98	3.45	B	A	3.91	6.35	2273	1.21
	2.0+3.5+4.2	2.14	3.75	4.51	---	---	3.34	10.40	10.55	0.72	3.18	3.23	3.2	14.1	14.3	98	3.27	C	A	3.93	6.43	2293	1.23
	2.0+3.5+5.0	1.98	3.47	4.95	---	---	3.56	10.40	10.90	0.72	3.07	3.30	3.2	13.6	14.6	98	3.39	C	A	3.91	6.26	2240	1.17
	2.0+3.5+6.0	1.80	3.17	5.43	---	---	3.84	10.40	10.72	0.73	2.87	3.04	3.2	12.7	13.5	98	3.62	A	A+	4.02	6.46	2248	1.25
	2.0+3.5+7.1	1.65	2.89	5.86	---	---	4.15	10.40	10.75	0.81	2.86	3.03	3.6	12.7	13.4	98	3.64	A	A+	4.04	6.46	2241	1.25
	2.0+4.2+4.2	2.00	4.20	4.20	---	---	3.53	10.40	10.56	0.74	3.12	3.23	3.3	13.8	14.3	98	3.33	C	A	3.93	6.46	2301	1.26
	2.0+4.2+5.0	1.86	3.90	4.64	---	---	3.76	10.40	10.91	0.77	3.07	3.30	3.4	13.6	14.6	98	3.39	C	A	3.91	6.34	2270	1.20
	2.0+4.2+6.0	1.70	3.58	5.12	---	---	4.04	10.40	10.73	0.78	2.87	3.04	3.5	12.7	13.5	98	3.62	A	A+	4.03	6.46	2246	1.25
	2.0+4.2+7.1	1.56	3.28	5.56	---	---	4.35	10.40	10.76	0.83	2.86	3.02	3.7	12.7	13.4	98	3.64	A	A+	4.06	6.46	2228	1.25
	2.0+5.0+5.0	1.74	4.33	4.33	---	---	3.99	10.40	10.63	0.80	2.96	3.08	3.5	13.1	13.7	98	3.51	B	A	3.94	6.17	2194	1.20
	2.0+5.0+6.0	1.60	4.00	4.80	---	---	4.27	10.40	10.86	0.79	2.77	2.99	3.5	12.3	13.3	98	3.75	A	A	3.99	6.46	2267	1.25
	2.0+5.0+7.1	1.47	3.69	5.24	---	---	4.58	10.40	10.89	0.86	2.75	2.97	3.8	12.2	13.2	98	3.78	A	A+	4.04	6.46	2240	1.25
	2.0+6.0+6.0	1.48	4.46	4.46	---	---	4.55	10.40	11.09	0.82	2.62	2.90	3.6	11.6	12.9	98	3.97	A	A+	4.09	6.46	2209	1.24
	2.0+6.0+7.1	1.38	4.13	4.89	---	---	4.86	10.40	11.12	0.87	2.61	2.89	3.9	11.6	12.8	98	3.98	A	A+	4.12	6.46	2194	1.24
	2.5+2.5+2.5	2.98	2.98	2.98	---	---	2.72	8.94	9.88	0.60	2.42	2.89	2.7	10.7	12.8	98	3.69	A	A	3.87	5.00	1810	0.98
	2.5+2.5+3.5	2.83	2.83	3.96	---	---	3.00	9.62	9.89	0.67	2.73	2.89	3.0	12.1	12.8	98	3.52	B	A	3.89	5.67	2043	1.07
	2.5+2.5+4.2	2.74	2.74	4.62	---	---	3.20	10.10	10.36	0.69	3.01	3.12	3.1	13.4	13.8	98	3.36	C	A	3.91	5.74	2056	1.08
	2.5+2.5+5.0	2.60	2.60	5.20	---	---	3.42	10.40	10.89	0.70	3.07	3.30	3.1	13.6	14.6	98	3.39	C	A	3.89	5.59	2014	1.05
	2.5+2.5+6.0	2.36	2.36	5.68	---	---	3.70	10.40	10.71	0.71	2.87	3.04	3.1	12.7	13.5	98	3.62	A	A	3.94	6.46	2297	1.26
	2.5+2.5+7.1	2.15	2.15	6.10	---	---	4.01	10.40	10.75	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A	3.97	6.46	2277	1.25
	2.5+3.5+3.5	2.71	3.80	3.80	---	---	3.28	10.31	10.76	0.72	3.12	3.35	3.2	13.8	14.9	98	3.30	C	A	3.93	6.44	2296	1.24
	2.5+3.5+4.2	2.55	3.57	4.28	---	---	3.48	10.40	10.77	0.74	3.18	3.35	3.3	14.1	14.9	98	3.27	C	A	3.93	6.46	2301	1.26
	2.5+3.5+5.0	2.36	3.31	4.73	---	---	3.70	10.40	10.90	0.75	3.07	3.30	3.3	13.6	14.6	98	3.39	C	A	3.91	6.35	2273	1.21
	2.5+3.5+6.0	2.17	3.03	5.20	---	---	3.99	10.40	10.72	0.76	2.87	3.04	3.4	12.7	13.5	98	3.62	A	A+	4.03	6.46	2246	1.25
	2.5+3.5+7.1	1.98	2.78	5.64	---	---	4.30	10.40	10.75	0.83	2.86	3.03	3.7	12.7	13.4	98	3.64	A	A+	4.06	6.46	2226	1.25
	2.5+4.2+4.2	2.38	4.01	4.01	---	---	3.68	10.40	10.77	0.77	3.12	3.35	3.4	13.8	14.9	98	3.33	C	A	3.93	6.46	2302	1.26
	2.5+4.2+5.0	2.23	3.73	4.44	---	---	3.90	10.40	10.91	0.80	3.07	3.30	3.5	13.6	14.6	98	3.39	C	A	3.93	6.43	2293	1.23
	2.5+4.2+6.0	2.05	3.44	4.91	---	---	4.18	10.40	10.73	0.81	2.87	3.04	3.6	12.7	13.5	98	3.62	A	A+	4.03	6.46	2245	1.25
	2.5+4.2+7.1	1.88	3.17	5.35	---	---	4.49	10.40	10.76	0.86	2.86	3.02	3.8	12.7	13.4	98	3.64	A	A+	4.06	6.46	2226	1.25
	2.5+5.0+5.0	2.08	4.16	4.16	---	---	4.13	10.40	10.63	0.83	2.96	3.08	3.7	13.1	13.7	98	3.51	B	A	3.91	6.26	2240	1.17
	2.5+5.0+6.0	1.93	3.85	4.62	---	---	4.41	10.40	10.86	0.84	2.77	2.99	3.7	12.3	13.3	98	3.75	A	A+	4.02	6.46	2248	1.25
	2.5+5.0+7.1	1.78	3.56	5.06	---	---	4.72	10.40	10.89	0.89	2.75	2.97	3.9	12.2	13.2	98	3.78	A	A+	4.04	6.46	2241	1.25
	2.5+6.0+6.0	1.80	4.30	4.30	---	---	4.69	10.40	11.09	0.85	2.62	2.90	3.8	11.6	12.9	98	3.97	A	A+	4.10	6.46	2204	1.24
	2.5+6.0+7.1	1.67	4.00	4.73	---	---	5.00	10.40	11.12	0.90	2.61	2.89	4.0	11.6	12.8	98	3.98	A	A+	4.15	6.46	2181	1.24
	3.5+3.5+3.5	3.46	3.46	3.46	---	---	3.56	10.38	10.76	0.77	3.12	3.35	3.4	13.8	14.9	98	3.33	C	A+	4.02	6.46	2252	1.25
	3.5+3.5+4.2	3.25	3.25	3.90	---	---	3.76	10.40	10.77	0.80	3.12	3.35	3.5	13.8	14.9	98	3.33	C	A+	4.02	6.46	2250	1.25
	3.5+3.5+5.0	3.03	3.03	4.34	---	---	3.99	10.40	10.91	0.83	3.07	3.30	3.7	13.6	14.6	98	3.39	C	A	3.98	6.46	2271	1.25
	3.5+3.5+6.0	2.80	2.80	4.80	---	---	4.27	10.40	10.73	0.84	2.87	3.04	3.7	12.7	13.5	98	3.62	A	A+	4.09	6.46	2213	1.24
	3.5+3.5+7.1	2.58	2.58	5.24	---	---	4.58	10.40	10.76	0.89	2.86	3.02	3.9	12.7	13.4	98	3.64	A	A+	4.12	6.46	2198	1.24
	3.5+4.2+4.2	3.06	3.67	3.67	---	---	3.96	10.40	10.78	0.85	3.11	3.34	3.8	13.8	14.8	98	3.34	C	A+	4.02	6.46	2248	1.25
	3.5+4.2+5.0	2.87	3.44	4.09	---	---	4.18	10.40	10.51	0.85	3.01	3.12	3.8	13.4	13.8	98	3.46	B	A+	4.02	6.46	2252	1.25
	3.5+4.2+6.0	2.66	3.19	4.55	---	---	4.46	10.40	10.74	0.87	2.87	3.03	3.9	12.7	13.4	98	3.62	A	A+	4.09	6.46	2213	1.24
	3.5+4.2+7.1	2.46	2.95	4.99	---	---	4.78	10.40	10.77	0.95	2.85	3.02	4.2	12.6	13.4	98	3.65	A	A+	4.14	6.46	2185	1.24
	3.5+5.0+5.0	2.70	3.85	3.85	---	---	4.41	10.40	10.64	0.89	2.96	3.07	3.9	13.1	13.6	98	3.51	B	A	3.96	6.46	2284	1.25
	3.5+5.0+6.0	2.51	3.59	4.30	---	---	4.69	10.40	10.86	0.90	2.76	2.98	4.0	12.2	13.2	98	3.77	A	A+	4.06	6.46	2228	1.24
	3.5+5.0+7.1	2.34	3.33	4.73	---	---	5.00	10.40	10.90	0.95	2.75	2.97	4.2	12.2	13.2	98	3.78	A	A+	4.10	6.46	2207	1.24
	3.5+6.0+6.0	2.34	4.03	4.03	---	---	4.97	10.40	11.09	0.91	2.62	2.90	4.0	11.6	12.9	98	3.97	A	A+	4.21	6.46	2150	1.23
	4.2+4.2+4.2	3.47	3.47	3.47	---	---	4.15	10.40	10.79	0.88	3.11	3.34	3.9	13.8	14.8	98	3.34	C	A+	4.02	6.46	2249	1.25
	4.2+4.2+5.0	3.26	3.26	3.88	---	---	4.38	10.40	10.52	0.91	3.00	3.12	4.0	13.3	13.8	98	3.47	B	A+	4.02	6.46	2250	1.25
	4.2+4.2+6.0	3.03	3.03	4.34	---	---	4.66	10.40	10.75	0.92	2.86	3.03	4.1	12.7	13.4	98	3.64	A	A+	4.10	6.46	2208	1.24
	4.2+4.2+7.1	2.82	2.82	4.76	---	---	4.97	10.40	10.78	0.98	2.85	3.02	4.3	12.6	13.4	98	3.65	A	A+	4.16	6.46	2172	1.24
	4.2+5.0+5.0	3.08	3.66	3.66	---	---	4.61	10.40	10.64	0.91	2.96	3.07	4.0	13.1	13.6	98	3.51	B	A	3.98	6.46	2271	1.25
	4.2+5.0+6.0	2.87	3.42	4.11	---	---	4.89	10.40	10.87	0.93	2.76	2.98	4.1	12.2	13.2	98	3.77	A	A+	4.09	6.46	2213	1.24
	5.0+5.0+5.0	3.46	3.46	3.46	---	---	4.83	10.38	10.77	0.95	2.85	3.02	4.2	12.6	13.4	98	3.64	A	A	3.96	6.46	2283	1.25
	1.5+1.5+1.5+1.5	1.83	1.83	1.83	1.83	---	2.28	7.32	8.82	0.46	1.72	2.24	2.0	7.6	9.9	98	4.26	A	A	3.98	6.12	2156	1.33
	1.5+1.5+1.5+2.0	1.83	1.83	1.83	2.44	---	2.43	7.93	9.42	0.48	1.93	2.44	2.1	8.6	10.8	98	4.11	A	A	3.93	6.31	2248	1.22
	1.5+1.5+1.5+2.5	1.83	1.83	1.83	3.05	---	2.58	8.54	9.42	0.50	2.10	2.44	2.2	9.3	10.8	98	4.07	A	A	3.95	6.41	2273	1.32
	1.5+1.5+1.5+3.5	1.74	1.74	1.74	4.06	---	2.86	9.28	10.19	0.54	2.39	2.75	2.4	10.6	12.2	98	3.88	A	A+	4.01	6.46	2258	1.25
	1.5+1.5+1.5+4.2	1.68	1.68	1.68	4.71	---	3.06	9.76	10.74	0.59	2.59	3.03	2.6	11.5	13.4	98	3.77	A	A+	4.00	6.46	2260	1.25
	1.5+1.5+1.5+5.0	1.63	1.63	1.63	5.43	---	3.28	10.32	10.86	0.59	2.76	2.98	2.6	12.2	13.2	98	3.74	A	A+	4.00	6.46	2260	1.25
	1.5+1.5+1.5+6.0	1.49	1.49	1.49	5.95	---	3.56	10.41	11.09	0.60	2.62	2.90	2.7	11.6	12.9	98	3.97	A	A+	4.10	6.46	2208	1.24
	1.5+1.5+1.5+7.1	1.35	1.35	1.35	6.37	---	3.87	10.41	11.12	0.66	2.61	2.88	2.9	11.6	12.8	98	3.99	A	A+	4.14	6.46	2182	1.24
	1.5+1.5+2.0+2.0	1.83	1.83	2.44	2.44	---	2.58	8.54	9.42	0.50	2.10	2.44	2.2	9.3	10.8	98	4.07	A	A	3.98	6.46	2270	1.37
	1.5+1.5+2.0+2.5	1.79	1.79	2.38	2.98	---	2.72	8.94	10.18	0.52	2.24	2.76	2.3	9.9	12.2	98	3.99	A	A	3.96	6.46	2286	1.26
	1.5+1.5+2.0+3.5	1.70	1.70	2.27	3.97	---	3.00	9.63	10.19	0.59	2.49	2.75	2.6	11.0	12.2	98	3.87	A	A+	4.01	6.46	2256	1.25
	1.5+1.5+2.0+4.2	1.65	1.65	2.20	4.62	---	3.20	10.11	10.74	0.61	2.75	3.03	2.7	12.2	13.4	98	3.68	A	A+	4.03	6.46	2243	1.25
	1.5+1.5+2.0+5.0	1.56	1.56	2.08	5.21	---	3.42	10.41	10.86	0.64	2.76	2.98	2.8	12.2	13.2	98	3.77	A	A+	4.01	6.46	2258	1.25
	1.5+1.5+2.0+6.0	1.42	1.42	1.89	5.68	---	3.70	10.41	11.09	0.62	2.62	2.90	2.8	11.6	12.9	98	3.97	A	A+	4.11	6.46	2201	1.24
	1.5+1.5+2.0+7.1	1.29	1.29	1.72	6.11	---	4.01	10.41	11.12	0.69	2.61	2.88	3.1	11.6	12.8	98	3.99	A	A+	4.15	6.46	2181	1.24
	1.5+1.5+2.5+2.5	1.74	1.74	2.90	2.90	---	2.86	9.28	10.18	0.57	2.39	2.76	2.5	10.6	12.2	98	3.88	A	A	3.96	6.46	2284	1.26
	1.5+1.5+2.5+3.5	1.66	1.66	2.77	3.88	---	3.14	9.97	10.73	0.61	2.65	3.04	2.7	11.8	13.5	98	3.76	A	A+	4.04	6.46	2241	1.25
	1.5+1.5+2.5+4.2	1.61	1.61	2.68	4.51	---	3.34	10.41	10.74	0.63	2.87	3.03	2.8	12.7	13.4	98	3.63	A	A+	4.06	6.46	2228	1.25
	1.5+1.5+2.5+5.0	1.49	1.49	2.48	4.96	---	3.56	10.41	10.86	0.66	2.76	2.98	2.9	12.2	13.2	98	3.77	A	A+	4.01	6.46	2256	1.25
	1.5+1.5+2.5+6.0	1.36	1.36	2.26	5.43	---	3.84	10.41	11.09	0.67	2.62	2.90	3.0	11.6	12.9	98	3.97	A	A+	4.12	6.46	2196	1.24
	1.5+1.5+2.5+7.1	1.24	1.24	2.07	5.87	---	4.15	10.41	11.12	0.71	2.61	2.88	3.1	11.6	12.8	98	3.99	A	A+	4.17	6.46	2169	1.24
	1.5+1.5+3.5+3.5	1.56	1.56	3.64	3.64	---	3.42	10.41	10.74	0.66	2.87	3.03	2.9	12.7	13.4	98	3.63	A	A+	4.10	6.46	2204	1.24
	1.5+1.5+3.5+4.2	1.46	1.46	3.41	4.09	---	3.62	10.41	10.74	0.68	2.86	3.03	3.0	12.7	13.4	98	3.64	A	A+	4.11	6.46	2200	1.24
	1.5+1.5+3.5+5.0	1.36	1.36	3.17	4.53	---	3.84	10.41	10.87	0.71	2.76	2.98	3.1	12.2	13.2	98	3.77	A	A+	4.09	6.46	2210	1.24
	1.5+1.5+3.5+6.0	1.25	1.25	2.91	5.00	---	4.13	10.41	11.10	0.72	2.61	2.89	3.2	11.6	12.8	98	3.99	A	A+	4.21	6.46	2151	1.23
	1.5+1.5+3.5+7.1	1.15	1.15	2.68	5.43	---	4.44	10.41	11.13	0.79	2.60	2.88	3.5	11.5	12.8	98	4.00	A	A+	4.24	6.46	2133	1.23
	1.5+1.5+4.2+4.2	1.37	1.37	3.84	3.84	---	3.82	10.41	10.75	0.73	2.86	3.03	3.2	12.7	13.4	98	3.64	A	A+	4.14	6.46	2186	1.24
	1.5+1.5+4.2+5.0	1.28	1.28	3.58	4.27	---	4.04	10.41	10.88	0.76	2.76	2.98	3.4	12.2	13.2	98	3.77	A	A+	4.10	6.46	2204	1.24

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
5MXS90E3V3B	1.5+1.5+4.2+6.0	1.18	1.18	3.31	4.73	---	4.32	10.41	11.11	0.77	2.61	2.89	3.4	11.6	12.8	98	3.99	A	A+	4.20	6.46	2152	1.23
	1.5+1.5+4.2+7.1	1.09	1.09	3.06	5.17	---	4.63	10.41	11.14	0.81	2.60	2.88	3.6	11.5	12.8	98	4.00	A	A+	4.25	6.46	2131	1.23
	1.5+1.5+5.0+5.0	1.20	1.20	4.00	4.00	---	4.27	10.41	11.01	0.76	2.71	2.93	3.4	12.0	13.0	98	3.84	A	A+	4.09	6.46	2212	1.24
	1.5+1.5+5.0+6.0	1.12	1.12	3.72	4.46	---	4.55	10.41	11.23	0.77	2.56	2.90	3.4	11.4	12.9	98	4.07	A	A+	4.20	6.46	2156	1.23
	1.5+1.5+5.0+7.1	1.03	1.03	3.45	4.89	---	4.86	10.41	11.27	0.84	2.50	2.88	3.7	11.1	12.8	98	4.16	A	A+	4.22	6.46	2146	1.23
	1.5+1.5+6.0+6.0	1.04	1.04	4.16	4.16	---	4.83	10.41	11.46	0.80	2.43	2.81	3.5	10.8	12.5	98	4.28	A	A+	4.30	6.46	2103	1.22
	1.5+2.0+2.0+2.0	1.79	2.38	2.38	2.38	---	2.72	8.94	10.18	0.52	2.24	2.76	2.3	9.9	12.2	98	3.99	A	A	3.96	6.46	2284	1.26
	1.5+2.0+2.0+2.5	1.74	2.32	2.32	2.90	---	2.86	9.28	10.18	0.57	2.39	2.76	2.5	10.6	12.2	98	3.88	A	A	3.97	6.46	2279	1.25
	1.5+2.0+2.0+3.5	1.66	2.22	2.22	3.88	---	3.14	9.97	10.73	0.61	2.65	3.04	2.7	11.8	13.5	98	3.76	A	A+	4.06	6.46	2226	1.25
	1.5+2.0+2.0+4.2	1.61	2.15	2.15	4.51	---	3.34	10.41	10.74	0.63	2.87	3.03	2.8	12.7	13.4	98	3.63	A	A+	4.06	6.46	2226	1.25
	1.5+2.0+2.0+5.0	1.49	1.98	1.98	4.96	---	3.56	10.41	10.86	0.66	2.76	2.98	2.9	12.2	13.2	98	3.77	A	A+	4.04	6.46	2241	1.25
	1.5+2.0+2.0+6.0	1.36	1.81	1.81	5.43	---	3.84	10.41	11.09	0.67	2.62	2.90	3.0	11.6	12.9	98	3.97	A	A+	4.15	6.46	2181	1.24
	1.5+2.0+2.0+7.1	1.24	1.65	1.65	5.87	---	4.15	10.41	11.12	0.71	2.61	2.88	3.1	11.6	12.8	98	3.99	A	A+	4.17	6.46	2169	1.24
	1.5+2.0+2.5+2.5	1.70	2.27	2.83	2.83	---	3.00	9.63	10.18	0.59	2.54	2.76	2.6	11.3	12.2	98	3.79	A	A	3.97	6.46	2278	1.25
	1.5+2.0+2.5+3.5	1.63	2.17	2.72	3.80	---	3.28	10.32	10.73	0.63	2.81	3.04	2.8	12.5	13.5	98	3.67	A	A+	4.06	6.46	2226	1.25
	1.5+2.0+2.5+4.2	1.53	2.04	2.55	4.29	---	3.48	10.41	10.74	0.66	2.87	3.03	2.9	12.7	13.4	98	3.63	A	A+	4.07	6.46	2224	1.25
	1.5+2.0+2.5+5.0	1.42	1.89	2.37	4.73	---	3.70	10.41	10.86	0.68	2.76	2.98	3.0	12.2	13.2	98	3.77	A	A+	4.06	6.46	2226	1.25
	1.5+2.0+2.5+6.0	1.30	1.74	2.17	5.21	---	3.99	10.41	11.09	0.69	2.62	2.90	3.1	11.6	12.9	98	3.97	A	A+	4.15	6.46	2181	1.24
	1.5+2.0+2.5+7.1	1.19	1.59	1.99	5.64	---	4.30	10.41	11.12	0.74	2.61	2.88	3.3	11.6	12.8	98	3.99	A	A+	4.20	6.46	2154	1.23
	1.5+2.0+3.5+3.5	1.49	1.98	3.47	3.47	---	3.56	10.41	10.74	0.68	2.87	3.03	3.0	12.7	13.4	98	3.63	A	A+	4.14	6.46	2184	1.24
	1.5+2.0+3.5+4.2	1.39	1.86	3.25	3.90	---	3.76	10.41	10.74	0.73	2.86	3.03	3.2	12.7	13.4	98	3.64	A	A+	4.14	6.46	2184	1.24
	1.5+2.0+3.5+5.0	1.30	1.74	3.04	4.34	---	3.99	10.41	10.87	0.73	2.76	2.98	3.2	12.2	13.2	98	3.77	A	A+	4.11	6.46	2200	1.24
	1.5+2.0+3.5+6.0	1.20	1.60	2.80	4.80	---	4.27	10.41	11.10	0.74	2.61	2.89	3.3	11.6	12.8	98	3.99	A	A+	4.21	6.46	2148	1.23
	1.5+2.0+3.5+7.1	1.11	1.48	2.58	5.24	---	4.58	10.41	11.13	0.81	2.60	2.88	3.6	11.5	12.8	98	4.00	A	A+	4.27	6.46	2121	1.23
	1.5+2.0+4.2+4.2	1.31	1.75	3.67	3.67	---	3.96	10.41	10.75	0.75	2.86	3.03	3.3	12.7	13.4	98	3.64	A	A+	4.14	6.46	2185	1.24
	1.5+2.0+4.2+5.0	1.23	1.64	3.44	4.10	---	4.18	10.41	10.88	0.78	2.76	2.98	3.5	12.2	13.2	98	3.77	A	A+	4.14	6.46	2184	1.24
	1.5+2.0+4.2+6.0	1.14	1.52	3.19	4.56	---	4.46	10.41	11.11	0.79	2.61	2.89	3.5	11.6	12.8	98	3.99	A	A+	4.22	6.46	2146	1.23
	1.5+2.0+4.2+7.1	1.06	1.41	2.95	4.99	---	4.78	10.41	11.14	0.84	2.60	2.88	3.7	11.5	12.8	98	4.00	A	A+	4.27	6.46	2119	1.23
	1.5+2.0+5.0+5.0	1.16	1.54	3.86	3.86	---	4.41	10.41	11.01	0.79	2.71	2.93	3.5	12.0	13.0	98	3.84	A	A+	4.10	6.46	2204	1.24
	1.5+2.0+5.0+6.0	1.08	1.44	3.59	4.31	---	4.69	10.41	11.23	0.82	2.56	2.90	3.6	11.4	12.9	98	4.07	A	A+	4.20	6.46	2152	1.23
	1.5+2.0+5.0+7.1	1.00	1.33	3.34	4.74	---	5.00	10.41	11.27	0.87	2.50	2.88	3.9	11.1	12.8	98	4.16	A	A+	4.25	6.46	2131	1.23
	1.5+2.0+6.0+6.0	1.01	1.34	4.03	4.03	---	4.97	10.41	11.46	0.83	2.43	2.81	3.7	10.8	12.5	98	4.28	A	A+	4.31	6.46	2098	1.22
	1.5+2.5+2.5+2.5	1.66	2.77	2.77	2.77	---	3.14	9.97	10.72	0.61	2.65	3.04	2.7	11.8	13.5	98	3.76	A	A+	4.00	6.46	2259	1.25
	1.5+2.5+2.5+3.5	1.56	2.60	2.60	3.64	---	3.42	10.41	10.73	0.66	2.87	3.04	2.9	12.7	13.5	98	3.63	A	A+	4.07	6.46	2224	1.25
	1.5+2.5+2.5+4.2	1.46	2.43	2.43	4.09	---	3.62	10.41	10.74	0.68	2.87	3.03	3.0	12.7	13.4	98	3.63	A	A+	4.07	6.46	2222	1.24
	1.5+2.5+2.5+5.0	1.36	2.26	2.26	4.53	---	3.84	10.41	10.86	0.71	2.76	2.98	3.1	12.2	13.2	98	3.77	A	A+	4.07	6.46	2224	1.25
	1.5+2.5+2.5+6.0	1.25	2.08	2.08	5.00	---	4.13	10.41	11.09	0.72	2.62	2.90	3.2	11.6	12.9	98	3.97	A	A+	4.15	6.46	2181	1.24
	1.5+2.5+2.5+7.1	1.15	1.91	1.91	5.43	---	4.44	10.41	11.12	0.79	2.61	2.88	3.5	11.6	12.8	98	3.99	A	A+	4.20	6.46	2152	1.23
	1.5+2.5+3.5+3.5	1.42	2.37	3.31	3.31	---	3.70	10.41	10.74	0.71	2.87	3.03	3.1	12.7	13.4	98	3.63	A	A+	4.14	6.46	2184	1.24
	1.5+2.5+3.5+4.2	1.33	2.22	3.11	3.74	---	3.90	10.41	10.74	0.76	2.86	3.03	3.4	12.7	13.4	98	3.64	A	A+	4.14	6.46	2185	1.24
	1.5+2.5+3.5+5.0	1.25	2.08	2.91	4.16	---	4.13	10.41	10.87	0.76	2.76	2.98	3.4	12.2	13.2	98	3.77	A	A+	4.14	6.46	2184	1.24
	1.5+2.5+3.5+6.0	1.16	1.93	2.70	4.63	---	4.41	10.41	11.10	0.77	2.61	2.89	3.4	11.6	12.8	98	3.99	A	A+	4.22	6.46	2146	1.23
	1.5+2.5+3.5+7.1	1.07	1.78	2.50	5.06	---	4.72	10.41	11.13	0.84	2.60	2.88	3.7	11.5	12.8	98	4.00	A	A+	4.27	6.46	2119	1.23
	1.5+2.5+4.2+4.2	1.26	2.10	3.53	3.53	---	4.10	10.41	10.75	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A+	4.16	6.46	2173	1.24
	1.5+2.5+4.2+5.0	1.18	1.97	3.31	3.94	---	4.32	10.41	10.88	0.81	2.76	2.98	3.6	12.2	13.2	98	3.77	A	A+	4.14	6.46	2184	1.24
	1.5+2.5+4.2+6.0	1.10	1.83	3.08	4.40	---	4.61	10.41	11.11	0.82	2.61	2.89	3.6	11.6	12.8	98	3.99	A	A+	4.24	6.46	2133	1.23
	1.5+2.5+4.2+7.1	1.02	1.70	2.86	4.83	---	4.92	10.41	11.14	0.90	2.60	2.88	4.0	11.5	12.8	98	4.00	A	A+	4.27	6.46	2119	1.23
	1.5+2.5+5.0+5.0	1.12	1.86	3.72	3.72	---	4.10	10.41	10.75	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A+	4.11	6.46	2200	1.24
	1.5+2.5+5.0+6.0	1.04	1.74	3.47	4.16	---	4.32	10.41	10.88	0.81	2.76	2.98	3.6	12.2	13.2	98	3.77	A	A+	4.21	6.46	2148	1.23
	1.5+3.5+3.5+3.5	1.30	3.04	3.04	3.04	---	3.99	10.41	10.74	0.76	2.86	3.03	3.4	12.7	13.4	98	3.64	A	A+	4.20	6.46	2152	1.23
	1.5+3.5+3.5+4.2	1.23	2.87	2.87	3.44	---	4.18	10.41	10.75	0.81	2.86	3.03	3.6	12.7	13.4	98	3.64	A	A+	4.21	6.46	2150	1.23
	1.5+3.5+3.5+5.0	1.16	2.70	2.70	3.86	---	4.41	10.41	10.88	0.84	2.76	2.98	3.7	12.2	13.2	98	3.77	A	A+	4.19	6.46	2157	1.23
	1.5+3.5+3.5+6.0	1.08	2.51	2.51	4.31	---	4.69	10.41	11.11	0.85	2.61	2.89	3.8	11.6	12.8	98	3.99	A	A+	4.30	6.46	2102	1.22
	1.5+3.5+3.5+7.1	1.00	2.34	2.34	4.74	---	5.00	10.41	11.14	0.90	2.60	2.88	4.0	11.5	12.8	98	4.00	A	A+	4.33	6.46	2088	1.22
	1.5+3.5+4.2+4.2	1.17	2.72	3.26	3.26	---	4.38	10.41	10.76	0.83	2.86	3.02	3.7	12.7	13.4	98	3.64	A	A+	4.23	6.46	2136	1.23
	1.5+3.5+4.2+5.0	1.10	2.57	3.08	3.67	---	4.61	10.41	10.89	0.86	2.75	2.98	3.8	12.2	13.2	98	3.79	A	A+	4.20	6.46	2152	1.23
	1.5+3.5+4.2+6.0	1.03	2.40	2.88	4.11	---	4.89	10.41	11.12	0.87	2.61	2.89	3.9	11.6	12.8	98	3.99	A	A+	4.30	6.46	2102	1.22
	1.5+3.5+5.0+5.0	1.04	2.43	3.47	3.47	---	4.83	10.41	11.01	0.90	2.71	2.93	4.0	12.0	13.0	98	3.84	A	A+	4.20	6.46	2155	1.23
	1.5+4.2+4.2+4.2	1.11	3.10	3.10	3.10	---	4.58	10.41	10.77	0.89	2.85	3.02	3.9	12.6	13.4	98	3.65	A	A+	4.23	6.46	2136	1.23
	1.5+4.2+4.2+5.0	1.05	2.93	2.93	3.49	---	4.80	10.41	10.90	0.92	2.75	2.97	4.1	12.2	13.2	98	3.79	A	A+	4.20	6.46	2152	1.23
	2.0+2.0+2.0+2.0	2.32	2.32	2.32	2.32	---	2.86	9.28	10.18	0.57	2.39	2.76	2.5	10.6	12.2	98	3.88	A	A	3.97	6.46	2278	1.25
	2.0+2.0+2.0+2.5	2.26	2.26	2.26	2.84	---	3.00	9.62	10.18	0.59	2.49	2.76	2.6	11.0	12.2	98	3.86	A	A+	4.00	6.46	2259	1.25
	2.0+2.0+2.0+3.5	2.17	2.17	2.17	3.80	---	3.28	10.31	10.73	0.63	2.81	3.04	2.8	12.5	13.5	98	3.67	A	A+	4.07	6.46	2224	1.25
	2.0+2.0+2.0+4.2	2.04	2.04	2.04	4.28	---	3.48	10.40	10.74	0.66	2.87	3.03	2.9	12.7	13.4	98	3.62	A	A+	4.07	6.46	2222	1.24
	2.0+2.0+2.0+5.0	1.89	1.89	1.89	4.73	---	3.70	10.40	10.86	0.68	2.76	2.99	3.0	12.2	13.3	98	3.77	A	A+	4.07	6.46	2224	1.25
	2.0+2.0+2.0+6.0	1.73	1.73	1.73	5.21	---	3.99	10.40	11.09	0.69	2.62	2.90	3.1	11.6	12.9	98	3.97	A	A+	4.15	6.46	2181	1.24
	2.0+2.0+2.0+7.1	1.59	1.59	1.59	5.63	---	4.30	10.40	11.12	0.74	2.61	2.88	3.3	11.6	12.8	98	3.98	A	A+	4.20	6.46	2152	1.23
	2.0+2.0+2.5+2.5	2.21	2.21	2.77	2.77	---	3.14	9.96	10.72	0.61	2.65	3.04	2.7	11.8	13.5	98	3.76	A	A+	4.01	6.46	2257	1.25
	2.0+2.0+2.5+3.5	2.08	2.08	2.60	3.64	---	3.42	10.40	10.73	0.66	2.87	3.04	2.9	12.7	13.5	98	3.62	A	A+	4.07	6.46	2222	1.24
	2.0+2.0+2.5+4.2	1.94	1.94	2.44	4.08	---	3.62	10.40	10.74	0.68	2.87	3.03	3.0	12.7	13.4	98	3.62	A	A+	4.10	6.46	2209	1.24
	2.0+2.0+2.5+5.0	1.81	1.81	2.26	4.52	---	3.84	10.40	10.86	0.71	2.76	2.99	3.1	12.2	13.3	98	3.77	A	A+	4.07	6.46	2224	1.25
	2.0+2.0+2.5+6.0	1.66	1.66	2.08	5.00	---	4.13	10.40	11.09	0.72	2.62	2.90	3.2	11.6	12.9	98	3.97	A	A+	4.17	6.46	2169	1.24
	2.0+2.0+2.5+7.1	1.53	1.53	1.91	5.43	---	4.44	10.40	11.12	0.79	2.61	2.88	3.5	11.6	12.8	98	3.98	A	A+	4.20	6.46	2152	1.23
	2.0+2.0+3.5+3.5	1.89	1.89	3.31	3.31	---	3.70	10.40	10.74	0.71	2.87	3.03	3.1	12.7	13.4	98	3.62	A	A+	4.14	6.46	2185	1.24
	2.0+2.0+3.5+4.2	1.78	1.78	3.11	3.73	---	3.90	10.40	10.74	0.76	2.86	3.03	3.4	12.7	13.4	98	3.64	A	A+	4.16	6.46	2173	1.24
	2.0+2.0+3.5+5.0	1.66	1.66	2.91	4.17	---	4.13	10.40	10.87	0.76	2.76	2.98	3.4	12.2	13.2	98	3.77	A	A+	4.14	6.46	2184	1.24
	2.0+2.0+3.5+6.0	1.54	1.54	2.70	4.62	---	4.41	10.40	11.10	0.77	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.24	6.46	2133	1.23
	2.0+2.0+3.5+7.1	1.42	1.42	2.49	5.07	---	4.72	10.40	11.13	0.84	2.60	2.88	3.7	11.5	12.8	98	4.00	A	A+	4.27	6.46	2119	1.23
	2.0+2.0+4.2+4.2	1.68	1.68	3.52	3.52	---	4.10	10.40	10.75	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A+	4.16	6.46	2173	1.24
	2.0+2.0+4.2+5.0	1.58	1.58	3.31	3.93	---	4.32	10.40	10.88	0.81	2.76	2.98	3.6	12.2	13.2	98	3.77	A	A+	4.14	6.46	2185	1.24
	2.0+2.0+4.2+6.0	1.46	1.46	3.09	4.39	---	4.61	10.40	11.11	0.82	2.61	2.89	3.6	11.6	12.8	98	3.98	A	A+	4.25	6.46	2131	1.23
	2.0+2.0+4.2+7.1	1.36	1.36	2.85	4.83	---	4.92	10.40	11.14	0.90	2.60	2.88	4.0	11.5	12.8	98	4.00	A	A+	4.27	6.46	2116	1.22
	2.0+2.0+5.0+5.0	1.49	1.49	3.71	3.71	---	4.55	10.40	11.01	0.84	2.71	2.93	3.7	12.0	13.0	98	3.84	A	A+	4.14	6.46	2184	1.24

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
5MXS90E3V3B	2.0+2.0+5.0+6.0	1.39	1.39	3.47	4.15	---	4.83	10.40	11.23	0.85	2.51	2.90	3.8	11.1	12.9	98	4.14	A	A+	4.24	6.46	2133	1.23
	2.0+2.5+2.5+2.5	2.18	2.71	2.71	2.71	---	3.28	10.31	10.72	0.64	2.82	3.04	2.8	12.5	13.5	98	3.66	A	A+	4.01	6.46	2255	1.25
	2.0+2.5+2.5+3.5	1.97	2.48	2.48	3.47	---	3.56	10.40	10.73	0.68	2.87	3.04	3.0	12.7	13.5	98	3.62	A	A+	4.10	6.46	2209	1.24
	2.0+2.5+2.5+4.2	1.86	2.32	2.32	3.90	---	3.76	10.40	10.74	0.73	2.87	3.03	3.2	12.7	13.4	98	3.62	A	A+	4.10	6.46	2207	1.24
	2.0+2.5+2.5+5.0	1.73	2.17	2.17	4.33	---	3.99	10.40	10.86	0.73	2.76	2.99	3.2	12.2	13.3	98	3.77	A	A+	4.07	6.46	2222	1.24
	2.0+2.5+2.5+6.0	1.60	2.00	2.00	4.80	---	4.27	10.40	11.09	0.74	2.62	2.90	3.3	11.6	12.9	98	3.97	A	A+	4.17	6.46	2167	1.24
	2.0+2.5+2.5+7.1	1.48	1.84	1.84	5.24	---	4.58	10.40	11.12	0.82	2.61	2.88	3.6	11.6	12.8	98	3.98	A	A+	4.21	6.46	2147	1.23
	2.0+2.5+3.5+3.5	1.80	2.26	3.17	3.17	---	3.84	10.40	10.74	0.73	2.87	3.03	3.2	12.7	13.4	98	3.62	A	A+	4.16	6.46	2173	1.24
	2.0+2.5+3.5+4.2	1.71	2.13	2.98	3.58	---	4.04	10.40	10.74	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A+	4.16	6.46	2172	1.24
	2.0+2.5+3.5+5.0	1.60	2.00	2.80	4.00	---	4.27	10.40	10.87	0.78	2.76	2.98	3.5	12.2	13.2	98	3.77	A	A+	4.14	6.46	2185	1.24
	2.0+2.5+3.5+6.0	1.48	1.86	2.60	4.46	---	4.55	10.40	11.10	0.82	2.61	2.89	3.6	11.6	12.8	98	3.98	A	A+	4.25	6.46	2131	1.23
	2.0+2.5+3.5+7.1	1.38	1.72	2.41	4.89	---	4.86	10.40	11.13	0.87	2.60	2.88	3.9	11.5	12.8	98	4.00	A	A+	4.27	6.46	2116	1.22
	2.0+2.5+4.2+4.2	1.61	2.01	3.39	3.39	---	4.24	10.40	10.75	0.81	2.86	3.03	3.6	12.7	13.4	98	3.64	A	A+	4.17	6.46	2171	1.23
	2.0+2.5+4.2+5.0	1.52	1.90	3.19	3.79	---	4.46	10.40	10.88	0.84	2.76	2.98	3.7	12.2	13.2	98	3.77	A	A+	4.16	6.46	2173	1.24
	2.0+2.5+4.2+6.0	1.42	1.77	2.97	4.24	---	4.75	10.40	11.11	0.85	2.61	2.89	3.8	11.6	12.8	98	3.98	A	A+	4.27	6.46	2121	1.23
	2.0+2.5+5.0+5.0	1.43	1.79	3.59	3.59	---	4.69	10.40	11.01	0.87	2.71	2.93	3.9	12.0	13.0	98	3.84	A	A+	4.14	6.46	2184	1.24
	2.0+2.5+5.0+6.0	1.34	1.68	3.35	4.03	---	4.97	10.40	11.23	0.88	2.51	2.90	3.9	11.1	12.9	98	4.14	A	A+	4.24	6.46	2133	1.23
	2.0+3.5+3.5+3.5	1.67	2.91	2.91	2.91	---	4.13	10.40	10.74	0.78	2.86	3.03	3.5	12.7	13.4	98	3.64	A	A+	4.23	6.46	2136	1.23
	2.0+3.5+3.5+4.2	1.58	2.76	2.76	3.30	---	4.32	10.40	10.75	0.84	2.86	3.03	3.7	12.7	13.4	98	3.64	A	A+	4.24	6.46	2135	1.23
	2.0+3.5+3.5+5.0	1.49	2.60	2.60	3.71	---	4.55	10.40	10.88	0.87	2.76	2.98	3.9	12.2	13.2	98	3.77	A	A+	4.23	6.46	2136	1.23
	2.0+3.5+3.5+6.0	1.38	2.43	2.43	4.16	---	4.83	10.40	11.11	0.87	2.61	2.89	3.9	11.6	12.8	98	3.98	A	A+	4.31	6.46	2100	1.22
	2.0+3.5+4.2+4.2	1.50	2.62	3.14	3.14	---	4.52	10.40	10.76	0.89	2.86	3.02	3.9	12.7	13.4	98	3.64	A	A+	4.26	6.46	2124	1.23
	2.0+3.5+4.2+5.0	1.41	2.48	2.97	3.54	---	4.75	10.40	10.89	0.89	2.75	2.98	3.9	12.2	13.2	98	3.78	A	A+	4.23	6.46	2136	1.23
	2.0+3.5+5.0+5.0	1.35	2.35	3.35	3.35	---	4.97	10.40	11.01	0.92	2.65	2.93	4.1	11.8	13.0	98	3.92	A	A+	4.20	6.46	2152	1.23
	2.0+4.2+4.2+4.2	1.43	2.99	2.99	2.99	---	4.72	10.40	10.77	0.92	2.85	3.02	4.1	12.6	13.4	98	3.65	A	A+	4.26	6.46	2123	1.23
	2.0+4.2+4.2+5.0	1.35	2.84	2.84	3.37	---	4.94	10.40	10.90	0.95	2.75	2.97	4.2	12.2	13.2	98	3.78	A	A+	4.24	6.46	2135	1.23
	2.5+2.5+2.5+2.5	2.60	2.60	2.60	2.60	---	3.42	10.40	10.72	0.66	2.87	3.04	2.9	12.7	13.5	98	3.62	A	A+	4.01	6.46	2255	1.25
	2.5+2.5+2.5+3.5	2.36	2.36	2.36	3.32	---	3.70	10.40	10.73	0.71	2.87	3.04	3.1	12.7	13.5	98	3.62	A	A+	4.10	6.46	2207	1.24
	2.5+2.5+2.5+4.2	2.22	2.22	2.22	3.74	---	3.90	10.40	10.74	0.76	2.87	3.03	3.4	12.7	13.4	98	3.62	A	A+	4.10	6.46	2206	1.24
	2.5+2.5+2.5+5.0	2.08	2.08	2.08	4.16	---	4.13	10.40	10.86	0.76	2.76	2.99	3.4	12.2	13.3	98	3.77	A	A+	4.10	6.46	2209	1.24
	2.5+2.5+2.5+6.0	1.93	1.93	1.93	4.61	---	4.41	10.40	11.09	0.77	2.62	2.90	3.4	11.6	12.9	98	3.97	A	A+	4.20	6.46	2154	1.23
	2.5+2.5+2.5+7.1	1.78	1.78	1.78	5.06	---	4.72	10.40	11.12	0.84	2.61	2.88	3.7	11.6	12.8	98	3.98	A	A+	4.21	6.46	2147	1.23
	2.5+2.5+3.5+3.5	2.17	2.17	3.03	3.03	---	3.99	10.40	10.74	0.76	2.87	3.03	3.4	12.7	13.4	98	3.62	A	A+	4.17	6.46	2171	1.24
	2.5+2.5+3.5+4.2	2.05	2.05	2.87	3.43	---	4.18	10.40	10.74	0.81	2.86	3.03	3.6	12.7	13.4	98	3.64	A	A+	4.19	6.46	2157	1.23
	2.5+2.5+3.5+5.0	1.93	1.93	2.70	3.84	---	4.41	10.40	10.87	0.84	2.76	2.98	3.7	12.2	13.2	98	3.77	A	A+	4.16	6.46	2173	1.24
	2.5+2.5+3.5+6.0	1.79	1.79	2.51	4.31	---	4.69	10.40	11.10	0.85	2.61	2.89	3.8	11.6	12.8	98	3.98	A	A+	4.27	6.46	2121	1.23
	2.5+2.5+3.5+7.1	1.67	1.67	2.33	4.73	---	5.00	10.40	11.13	0.90	2.60	2.88	4.0	11.5	12.8	98	4.00	A	A+	4.30	6.46	2103	1.22
	2.5+2.5+4.2+4.2	1.94	1.94	3.26	3.26	---	4.38	10.40	10.75	0.84	2.86	3.03	3.7	12.7	13.4	98	3.64	A	A+	4.20	6.46	2155	1.23
	2.5+2.5+4.2+5.0	1.83	1.83	3.08	3.66	---	4.61	10.40	10.88	0.87	2.76	2.98	3.9	12.2	13.2	98	3.77	A	A+	4.16	6.46	2172	1.24
	2.5+2.5+4.2+6.0	1.71	1.71	2.87	4.11	---	4.89	10.40	11.11	0.87	2.61	2.89	3.9	11.6	12.8	98	3.98	A	A+	4.27	6.46	2119	1.23
	2.5+2.5+5.0+5.0	1.73	1.73	3.47	3.47	---	4.83	10.40	11.01	0.90	2.71	2.93	4.0	12.0	13.0	98	3.84	A	A+	4.14	6.46	2185	1.24
	2.5+3.5+3.5+3.5	2.00	2.80	2.80	2.80	---	4.27	10.40	10.74	0.84	2.86	3.03	3.7	12.7	13.4	98	3.64	A	A+	4.24	6.46	2135	1.23
	2.5+3.5+3.5+4.2	1.90	2.66	2.66	3.18	---	4.46	10.40	10.75	0.86	2.86	3.03	3.8	12.7	13.4	98	3.64	A	A+	4.26	6.46	2124	1.23
	2.5+3.5+3.5+5.0	1.79	2.51	2.51	3.59	---	4.69	10.40	10.88	0.89	2.76	2.98	3.9	12.2	13.2	98	3.77	A	A+	4.23	6.46	2136	1.23
	2.5+3.5+3.5+6.0	1.67	2.35	2.35	4.03	---	4.97	10.40	11.11	0.90	2.61	2.89	4.0	11.6	12.8	98	3.98	A	A+	4.33	6.46	2090	1.22
	2.5+3.5+4.2+4.2	1.81	2.53	3.03	3.03	---	4.66	10.40	10.76	0.92	2.86	3.02	4.1	12.7	13.4	98	3.64	A	A+	4.26	6.46	2123	1.23
	2.5+3.5+4.2+5.0	1.72	2.39	2.87	3.42	---	4.89	10.40	10.89	0.92	2.75	2.98	4.1	12.2	13.2	98	3.78	A	A+	4.24	6.46	2135	1.23
	2.5+4.2+4.2+4.2	1.73	2.89	2.89	2.89	---	4.86	10.40	10.77	0.95	2.85	3.02	4.2	12.6	13.4	98	3.65	A	A+	4.26	6.46	2123	1.23
	3.5+3.5+3.5+3.5	2.60	2.60	2.60	2.60	---	4.55	10.40	10.75	0.89	2.86	3.03	3.9	12.7	13.4	98	3.64	A	A+	4.30	6.46	2104	1.22
	3.5+3.5+3.5+4.2	2.48	2.48	2.48	2.96	---	4.75	10.40	10.76	0.92	2.86	3.02	4.1	12.7	13.4	98	3.64	A	A+	4.32	6.46	2094	1.22
	3.5+3.5+3.5+5.0	2.35	2.35	2.35	3.35	---	4.97	10.40	10.89	0.95	2.76	2.98	4.2	12.2	13.2	98	3.77	A	A+	4.30	6.46	2105	1.22
	3.5+3.5+4.2+4.2	2.36	2.36	2.84	2.84	---	4.94	10.40	10.77	0.98	2.85	3.02	4.3	12.6	13.4	98	3.65	A	A+	4.32	6.46	2094	1.22
	1.5+1.5+1.5+1.5	1.79	1.79	1.79	1.79	1.79	2.72	8.93	10.48	0.45	2.12	2.68	2.0	9.4	11.9	98	4.21	A	A+	4.12	6.46	2194	1.24
	1.5+1.5+1.5+2.0	1.74	1.74	1.74	1.74	2.32	2.86	9.27	10.48	0.47	2.21	2.68	2.1	9.8	11.9	98	4.19	A	A+	4.13	6.46	2190	1.24
	1.5+1.5+1.5+2.5	1.70	1.70	1.70	1.70	2.83	3.00	9.62	10.48	0.51	2.31	2.68	2.3	10.2	11.9	98	4.16	A	A+	4.16	6.46	2175	1.24
	1.5+1.5+1.5+3.5	1.63	1.63	1.63	1.63	3.80	3.28	10.31	11.11	0.55	2.56	2.89	2.4	11.4	12.8	98	4.03	A	A+	4.24	6.46	2132	1.23
	1.5+1.5+1.5+4.2	1.53	1.53	1.53	1.53	4.28	3.48	10.40	11.11	0.59	2.61	2.89	2.6	11.6	12.8	98	3.98	A	A+	4.24	6.46	2132	1.23
	1.5+1.5+1.5+5.0	1.42	1.42	1.42	1.42	4.73	3.70	10.40	11.24	0.60	2.51	2.90	2.7	11.1	12.9	98	4.14	A	A+	4.23	6.46	2141	1.23
	1.5+1.5+1.5+6.0	1.30	1.30	1.30	1.30	5.20	3.99	10.40	11.47	0.60	2.38	2.81	2.7	10.6	12.5	98	4.37	A	A+	4.34	6.46	2084	1.22
	1.5+1.5+1.5+7.1	1.19	1.19	1.19	1.19	5.64	4.30	10.40	11.50	0.66	2.36	2.79	2.9	10.5	12.4	98	4.41	A	A+	4.37	6.46	2072	1.22
	1.5+1.5+2.0+2.0	1.70	1.70	1.70	2.26	2.26	3.00	9.62	10.48	0.51	2.31	2.68	2.3	10.2	11.9	98	4.16	A	A+	4.17	6.46	2170	1.24
	1.5+1.5+2.0+2.5	1.66	1.66	1.66	2.21	2.77	3.14	9.96	11.10	0.53	2.46	2.89	2.4	10.9	12.8	98	4.05	A	A+	4.17	6.46	2169	1.24
	1.5+1.5+2.0+3.5	1.56	1.56	1.56	2.08	3.64	3.42	10.40	11.11	0.57	2.61	2.89	2.5	11.6	12.8	98	3.98	A	A+	4.27	6.46	2117	1.23
	1.5+1.5+2.0+4.2	1.46	1.46	1.46	1.94	4.08	3.62	10.40	11.11	0.62	2.61	2.89	2.8	11.6	12.8	98	3.98	A	A+	4.27	6.46	2117	1.23
	1.5+1.5+2.0+5.0	1.36	1.36	1.36	1.81	4.52	3.84	10.40	11.24	0.62	2.51	2.90	2.8	11.1	12.9	98	4.14	A	A+	4.24	6.46	2132	1.23
	1.5+1.5+2.0+6.0	1.25	1.25	1.25	1.66	4.99	4.13	10.40	11.47	0.65	2.38	2.81	2.9	10.6	12.5	98	4.37	A	A+	4.35	6.46	2080	1.22
	1.5+1.5+2.0+7.1	1.15	1.15	1.15	1.53	5.43	4.44	10.40	11.50	0.69	2.36	2.79	3.1	10.5	12.4	98	4.41	A	A+	4.40	6.46	2054	1.22
	1.5+1.5+2.5+2.5	1.63	1.63	1.63	2.71	2.71	3.28	10.31	11.10	0.55	2.56	2.89	2.4	11.4	12.8	98	4.03	A	A+	4.18	6.46	2162	1.24
	1.5+1.5+2.5+3.5	1.49	1.49	1.49	2.48	3.47	3.56	10.40	11.11	0.60	2.61	2.89	2.7	11.6	12.8	98	3.98	A	A+	4.28	6.46	2115	1.23
	1.5+1.5+2.5+4.2	1.39	1.39	1.39	2.32	3.90	3.76	10.40	11.11	0.64	2.61	2.89	2.8	11.6	12.8	98	3.98	A	A+	4.28	6.46	2114	1.23
	1.5+1.5+2.5+5.0	1.30	1.30	1.30	2.17	4.33	3.99	10.40	11.24	0.66	2.51	2.90	2.9	11.1	12.9	98	4.14	A	A+	4.27	6.46	2117	1.23
	1.5+1.5+2.5+6.0	1.20	1.20	1.20	2.00	4.80	4.27	10.40	11.47	0.67	2.38	2.81	3.0	10.6	12.5	98	4.37	A	A+	4.37	6.46	2072	1.22
	1.5+1.5+2.5+7.1	1.11	1.11	1.11	1.84	5.24	4.58	10.40	11.50	0.71	2.36	2.79	3.1	10.5	12.4	98	4.41	A	A+	4.40	6.46	2054	1.22
	1.5+1.5+3.5+3.5	1.36	1.36	1.36	3.17	3.17	3.84	10.40	11.11	0.66	2.61	2.89	2.9	11.6	12.8	98	3.98	A	A+	4.34	6.46	2083	1.22
	1.5+1.5+3.5+4.2	1.28	1.28	1.28	2.98	3.58	4.04	10.40	11.12	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2082	1.22
	1.5+1.5+3.5+5.0	1.20	1.20	1.20	2.80	4.00	4.27	10.40	11.25	0.71	2.51	2.89	3.1	11.1	12.8	98	4.14	A	A+	4.33	6.46	2088	1.22
	1.5+1.5+3.5+6.0	1.11	1.11	1.11	2.60	4.46	4.55	10.40	11.48	0.72	2.37	2.80	3.2	10.5	12.4	98	4.39	A	A+	4.43	6.46	2040	1.27
	1.5+1.5+3.5+7.1	1.03	1.03	1.03	2.41	4.89	4.86	10.40	11.51	0.79	2.36	2.79	3.5	10.5	12.4	98	4.41	A	A+	4.46	6.46	2029	1.26
	1.5+1.5+4.2+4.2	1.21	1.21	1.21	3.39	3.39	4.24	10.40	11.13	0.73	2.60	2.88	3.2	11.5	12.8	98	4.00	A	A+	4.36	6.46	2076	1.22
	1.5+1.5+4.2+5.0	1.14	1.14	1.14	3.19	3.80	4.46	10.40	11.26	0.76	2.50	2.89	3.4	11.1	12.8	98	4.16	A	A+	4.34	6.46	2083	1.22
	1.5+1.5+4.2+6.0	1.06	1.06	1.06	2.97	4.24	4.75	10.40	11.49	0.77	2.37	2.80	3.4	10.5	12.4	98	4.39	A	A+	4.47	6.46	2024	1.26
	1.5+1.5+5.0+5.0	1.08	1.08	1.08	3.59	3.59	4.69	10.40	11.38	0.76	2.46	2.84	3.4	10.9	12.6	98	4.23	A	A+	4.33	6.46	2088	1.22
	1.5+1.5+5.0+6.0	1.01	1.01	1.01	3.35	4.03	4.97	10.40	11.61	0.79	2.32	2.75	3.5	10.3	12.2	98	4.48	A	A+	4.43	6.46	2040	1.27

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0. 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
5MXS90E3V3B	1MA1+1MA1+1MA2	1.66	1.66	2.21	2.21	2.21	3.14	9.96	11.10	0.53	2.46	2.89	2.4	10.9	12.8	98	4.05	A	A+	4.19	6.46	2161	1.24
	1MA1+1MA1+1MA35	1.63	1.63	2.17	2.17	2.71	3.28	10.31	11.10	0.55	2.56	2.89	2.4	11.4	12.8	98	4.03	A	A+	4.19	6.46	2159	1.23
	1MA1+1MA1+1MA35	1.49	1.49	1.98	1.98	3.47	3.56	10.40	11.11	0.60	2.61	2.89	2.7	11.6	12.8	98	3.98	A	A+	4.28	6.46	2114	1.23
	1MA1+1MA1+1MA42	1.39	1.39	1.86	1.86	3.90	3.76	10.40	11.11	0.64	2.61	2.89	2.8	11.6	12.8	98	3.98	A	A+	4.29	6.46	2110	1.23
	1MA1+1MA1+1MA50	1.30	1.30	1.73	1.73	4.33	3.99	10.40	11.24	0.66	2.51	2.90	2.9	11.1	12.9	98	4.14	A	A+	4.28	6.46	2115	1.23
	1MA1+1MA1+1MA60	1.20	1.20	1.60	1.60	4.80	4.27	10.40	11.47	0.67	2.38	2.81	3.0	10.6	12.5	98	4.37	A	A+	4.37	6.46	2072	1.22
	1MA1+1MA1+1MA71	1.11	1.11	1.48	1.48	5.24	4.58	10.40	11.50	0.71	2.36	2.79	3.1	10.5	12.4	98	4.41	A	A+	4.41	6.46	2052	1.22
	1MA1+1MA1+1MA25	1.56	1.56	2.08	2.60	2.60	3.42	10.40	11.10	0.58	2.62	2.89	2.6	11.6	12.8	98	3.97	A	A+	4.22	6.46	2144	1.23
	1MA1+1MA1+1MA35	1.42	1.42	1.89	2.36	3.31	3.70	10.40	11.11	0.62	2.61	2.89	2.8	11.6	12.8	98	3.98	A	A+	4.29	6.46	2110	1.23
	1MA1+1MA1+1MA42	1.33	1.33	1.78	2.22	3.73	3.90	10.40	11.11	0.66	2.61	2.89	2.9	11.6	12.8	98	3.98	A	A+	4.29	6.46	2110	1.23
	1MA1+1MA1+1MA50	1.25	1.25	1.66	2.08	4.16	4.13	10.40	11.24	0.69	2.51	2.90	3.1	11.1	12.9	98	4.14	A	A+	4.28	6.46	2114	1.23
	1MA1+1MA1+1MA60	1.16	1.16	1.54	1.93	4.62	4.41	10.40	11.47	0.69	2.38	2.81	3.1	10.6	12.5	98	4.37	A	A+	4.40	6.46	2057	1.22
	1MA1+1MA1+1MA71	1.07	1.07	1.42	1.78	5.06	4.72	10.40	11.50	0.76	2.36	2.79	3.4	10.5	12.4	98	4.41	A	A+	4.41	6.46	2052	1.21
	1MA1+1MA1+1MA35	1.30	1.30	1.73	3.03	3.03	3.99	10.40	11.11	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.36	6.46	2076	1.22
	1MA1+1MA1+1MA42	1.23	1.23	1.64	2.87	3.44	4.18	10.40	11.12	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.36	6.46	2074	1.22
	1MA1+1MA1+1MA50	1.16	1.16	1.54	2.70	3.85	4.41	10.40	11.25	0.74	2.51	2.89	3.3	11.1	12.8	98	4.14	A	A+	4.36	6.46	2076	1.22
	1MA1+1MA1+1MA60	1.08	1.08	1.43	2.51	4.30	4.69	10.40	11.48	0.74	2.37	2.80	3.3	10.5	12.4	98	4.39	A	A+	4.47	6.46	2024	1.26
	1MA1+1MA1+1MA71	1.00	1.00	1.33	2.33	4.73	5.00	10.40	11.51	0.81	2.36	2.79	3.6	10.5	12.4	98	4.41	A	A+	4.51	6.46	2006	1.26
	1MA1+1MA1+1MA42	1.16	1.16	1.55	3.26	3.26	4.38	10.40	11.13	0.76	2.60	2.88	3.4	11.5	12.8	98	4.00	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA50	1.10	1.10	1.46	3.08	3.66	4.61	10.40	11.26	0.79	2.50	2.89	3.5	11.1	12.8	98	4.16	A	A+	4.36	6.46	2076	1.22
	1MA1+1MA1+1MA60	1.03	1.03	1.37	2.87	4.11	4.89	10.40	11.49	0.79	2.37	2.80	3.5	10.5	12.4	98	4.39	A	A+	4.47	6.46	2022	1.26
	1MA1+1MA1+1MA50	1.04	1.04	1.39	3.47	3.47	4.83	10.40	11.38	0.82	2.46	2.84	3.6	10.9	12.6	98	4.23	A	A+	4.34	6.46	2083	1.22
	1MA1+1MA1+1MA25	1.49	1.49	2.48	2.48	2.48	3.56	10.40	11.10	0.60	2.62	2.89	2.7	11.6	12.8	98	3.97	A	A+	4.23	6.46	2141	1.23
	1MA1+1MA1+1MA35	1.36	1.36	2.26	2.26	3.17	3.84	10.40	11.11	0.67	2.61	2.89	3.0	11.6	12.8	98	3.98	A	A+	4.30	6.46	2103	1.23
	1MA1+1MA1+1MA42	1.28	1.28	2.13	2.13	3.58	4.04	10.40	11.11	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.31	6.46	2098	1.22
	1MA1+1MA1+1MA50	1.20	1.20	2.00	2.00	4.00	4.27	10.40	11.24	0.71	2.51	2.90	3.1	11.1	12.9	98	4.14	A	A+	4.29	6.46	2110	1.23
	1MA1+1MA1+1MA60	1.11	1.11	1.86	1.86	4.46	4.55	10.40	11.47	0.72	2.38	2.81	3.2	10.6	12.5	98	4.37	A	A+	4.40	6.46	2054	1.22
	1MA1+1MA1+1MA71	1.03	1.03	1.72	1.72	4.89	4.86	10.40	11.50	0.79	2.36	2.79	3.5	10.5	12.4	98	4.41	A	A+	4.43	6.46	2043	1.21
	1MA1+1MA1+1MA35	1.25	1.25	2.08	2.91	2.91	4.13	10.40	11.11	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.39	6.46	2061	1.22
	1MA1+1MA1+1MA42	1.18	1.18	1.97	2.76	3.31	4.32	10.40	11.12	0.76	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA50	1.11	1.11	1.86	2.60	3.71	4.55	10.40	11.25	0.76	2.51	2.89	3.4	11.1	12.8	98	4.14	A	A+	4.36	6.46	2076	1.22
	1MA1+1MA1+1MA60	1.04	1.04	1.73	2.43	4.16	4.83	10.40	11.48	0.79	2.37	2.80	3.5	10.5	12.4	98	4.39	A	A+	4.46	6.46	2029	1.26
	1MA1+1MA1+1MA42	1.12	1.12	1.87	3.14	3.14	4.52	10.40	11.13	0.79	2.60	2.88	3.5	11.5	12.8	98	4.00	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA50	1.06	1.06	1.77	2.97	3.54	4.75	10.40	11.26	0.82	2.50	2.89	3.6	11.1	12.8	98	4.16	A	A+	4.36	6.46	2074	1.22
	1MA1+1MA1+1MA60	1.01	1.01	1.68	3.35	3.35	4.97	10.40	11.38	0.84	2.46	2.84	3.7	10.9	12.6	98	4.23	A	A+	4.36	6.46	2076	1.22
	1MA1+1MA1+1MA35	1.16	1.16	2.70	2.70	2.70	4.41	10.40	11.12	0.76	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.46	6.46	2028	1.26
	1MA1+1MA1+1MA42	1.10	1.10	2.56	2.56	3.08	4.61	10.40	11.13	0.81	2.60	2.88	3.6	11.5	12.8	98	4.00	A	A+	4.47	6.46	2025	1.26
	1MA1+1MA1+1MA50	1.04	1.04	2.43	2.43	3.47	4.83	10.40	11.26	0.84	2.50	2.89	3.7	11.1	12.8	98	4.16	A	A+	4.46	6.46	2028	1.26
	1MA1+1MA1+1MA42	1.05	1.05	2.44	2.93	2.93	4.80	10.40	11.14	0.87	2.60	2.88	3.9	11.5	12.8	98	4.00	A	A+	4.45	6.46	2033	1.26
	1MA1+1MA1+1MA25	1.63	2.17	2.17	2.17	2.17	3.28	10.31	11.10	0.55	2.56	2.89	2.4	11.4	12.8	98	4.03	A	A+	4.22	6.46	2144	1.23
	1MA1+1MA1+1MA25	1.56	2.08	2.08	2.08	2.60	3.42	10.40	11.10	0.58	2.62	2.89	2.6	11.6	12.8	98	3.97	A	A+	4.23	6.46	2141	1.23
	1MA1+1MA1+1MA35	1.42	1.89	1.89	1.89	3.31	3.70	10.40	11.11	0.62	2.61	2.89	2.8	11.6	12.8	98	3.98	A	A+	4.31	6.46	2100	1.23
	1MA1+1MA1+1MA42	1.33	1.78	1.78	1.78	3.73	3.90	10.40	11.11	0.66	2.61	2.89	2.9	11.6	12.8	98	3.98	A	A+	4.31	6.46	2098	1.22
	1MA1+1MA1+1MA50	1.25	1.66	1.66	1.66	4.16	4.13	10.40	11.24	0.69	2.51	2.90	3.1	11.1	12.9	98	4.14	A	A+	4.29	6.46	2110	1.23
	1MA1+1MA1+1MA60	1.16	1.54	1.54	1.54	4.62	4.41	10.40	11.47	0.69	2.38	2.81	3.1	10.6	12.5	98	4.37	A	A+	4.40	6.46	2054	1.22
	1MA1+1MA1+1MA71	1.07	1.42	1.42	1.42	5.06	4.72	10.40	11.50	0.76	2.36	2.79	3.4	10.5	12.4	98	4.41	A	A+	4.43	6.46	2043	1.21
	1MA1+1MA1+1MA25	1.49	1.98	1.98	2.48	2.48	3.56	10.40	11.10	0.60	2.62	2.89	2.7	11.6	12.8	98	3.97	A	A+	4.23	6.46	2137	1.23
	1MA1+1MA1+1MA35	1.36	1.81	1.81	2.26	3.17	3.84	10.40	11.11	0.67	2.61	2.89	3.0	11.6	12.8	98	3.98	A	A+	4.31	6.46	2098	1.22
	1MA1+1MA1+1MA42	1.28	1.70	1.70	2.13	3.58	4.04	10.40	11.11	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.31	6.46	2098	1.22
	1MA1+1MA1+1MA50	1.20	1.60	1.60	2.00	4.00	4.27	10.40	11.24	0.71	2.51	2.90	3.1	11.1	12.9	98	4.14	A	A+	4.31	6.46	2100	1.23
	1MA1+1MA1+1MA60	1.11	1.49	1.49	1.86	4.46	4.55	10.40	11.47	0.72	2.38	2.81	3.2	10.6	12.5	98	4.37	A	A+	4.41	6.46	2052	1.22
	1MA1+1MA1+1MA71	1.03	1.38	1.38	1.72	4.89	4.86	10.40	11.50	0.79	2.36	2.79	3.5	10.5	12.4	98	4.41	A	A+	4.44	6.46	2036	1.27
	1MA1+1MA1+1MA35	1.25	1.66	1.66	2.91	2.91	4.13	10.40	11.11	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA42	1.18	1.58	1.58	2.76	3.31	4.32	10.40	11.12	0.76	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA50	1.11	1.49	1.49	2.60	3.71	4.55	10.40	11.25	0.76	2.51	2.89	3.4	11.1	12.8	98	4.14	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA60	1.04	1.39	1.39	2.43	4.16	4.83	10.40	11.48	0.79	2.37	2.80	3.5	10.5	12.4	98	4.39	A	A+	4.49	6.46	2015	1.26
	1MA1+1MA1+1MA42	1.12	1.50	1.50	3.14	3.14	4.52	10.40	11.13	0.79	2.60	2.88	3.5	11.5	12.8	98	4.00	A	A+	4.40	6.46	2056	1.22
	1MA1+1MA1+1MA50	1.06	1.41	1.41	2.97	3.54	4.75	10.40	11.26	0.82	2.50	2.89	3.6	11.1	12.8	98	4.16	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA60	1.01	1.34	1.34	3.35	3.35	4.97	10.40	11.38	0.84	2.46	2.84	3.7	10.9	12.6	98	4.23	A	A+	4.36	6.46	2074	1.22
	1MA1+1MA1+1MA25	1.42	1.89	2.36	2.36	2.36	3.70	10.40	11.10	0.62	2.62	2.89	2.8	11.6	12.8	98	3.97	A	A+	4.24	6.46	2135	1.23
	1MA1+1MA1+1MA35	1.30	1.73	2.17	2.17	3.03	3.99	10.40	11.11	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2085	1.22
	1MA1+1MA1+1MA42	1.23	1.64	2.05	2.05	3.44	4.18	10.40	11.11	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	1MA1+1MA1+1MA50	1.16	1.54	1.93	1.93	3.85	4.41	10.40	11.24	0.74	2.51	2.90	3.3	11.1	12.9	98	4.14	A	A+	4.31	6.46	2098	1.22
	1MA1+1MA1+1MA60	1.08	1.43	1.79	1.79	4.30	4.69	10.40	11.47	0.74	2.38	2.81	3.3	10.6	12.5	98	4.37	A	A+	4.41	6.46	2052	1.22
	1MA1+1MA1+1MA71	1.00	1.33	1.67	1.67	4.73	5.00	10.40	11.50	0.82	2.36	2.79	3.6	10.5	12.4	98	4.41	A	A+	4.47	6.46	2022	1.27
	1MA1+1MA1+1MA35	1.20	1.60	2.00	2.80	2.80	4.27	10.40	11.11	0.74	2.61	2.89	3.3	11.6	12.8	98	3.98	A	A+	4.40	6.46	2056	1.22
	1MA1+1MA1+1MA42	1.14	1.52	1.90	2.66	3.19	4.46	10.40	11.12	0.79	2.61	2.89	3.5	11.6	12.8	98	3.98	A	A+	4.40	6.46	2056	1.22
	1MA1+1MA1+1MA50	1.08	1.43	1.79	2.51	3.59	4.69	10.40	11.25	0.82	2.51	2.89	3.6	11.1	12.8	98	4.14	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA60	1.01	1.34	1.68	2.35	4.03	4.97	10.40	11.48	0.82	2.37	2.80	3.6	10.5	12.4	98	4.39	A	A+	4.49	6.46	2013	1.26
	1MA1+1MA1+1MA42	1.08	1.44	1.81	3.03	3.03	4.66	10.40	11.13	0.81	2.60	2.88	3.6	11.5	12.8	98	4.00	A	A+	4.40	6.46	2056	1.21
	1MA1+1MA1+1MA50	1.03	1.37	1.71	2.87	3.42	4.89	10.40	11.26	0.84	2.50	2.89	3.7	11.1	12.8	98	4.16	A	A+	4.40	6.46	2058	1.22
	1MA1+1MA1+1MA35	1.11	1.49	2.60	2.60	2.60	4.55	10.40	11.12	0.82	2.61	2.89	3.6	11.6	12.8	98	3.98	A	A+	4.48	6.46	2019	1.26
	1MA1+1MA1+1MA42	1.06	1.41	2.48	2.48	2.97	4.75	10.40	11.13	0.84	2.60	2.88	3.7	11.5	12.8	98	4.00	A	A+	4.48	6.46	2019	1.26
	1MA1+1MA1+1MA50	1.01	1.34	2.35	2.35	3.35	4.97	10.40	11.26	0.87	2.50	2.89	3.9	11.1	12.8	98	4.16	A	A+	4.45	6.46	2033	1.26
	1MA1+1MA1+1MA42	1.01	1.35	2.36	2.84	2.84	4.94	10.40	11.14	0.90	2.60	2.88	4.0	11.5	12.8	98	4.00	A	A+	4.50	6.46	2010	1.26
	1MA1+1MA1+1MA25	1.36	2.26	2.26	2.26	2.26	3.84	10.40	11.10	0.67	2.62	2.89	3.0	11.6	12.8	98	3.97	A	A+	4.25	6.46	2128	1.23
	1MA1+1MA1+1MA35	1.25	2.08	2.08	2.08	2.91	4.13	10.40	11.11	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	1MA1+1MA1+1MA42	1.18	1.97	1.97	1.97	3.31	4.32	10.40	11.11	0.76	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	1MA1+1MA1+1MA50	1.11	1.86	1.86	1.86	3.71	4.55	10.40	11.24	0.76	2.51	2.90	3.4	11.1	12.9	98	4.14	A	A+	4.34	6.46	2085	1.22
	1MA1+1MA1+1MA60	1.04	1.73	1.73	1.73	4.16	4.83	10.40	11.47	0.80	2.38	2.81	3.5	10.6	12.5	98	4.37	A	A+	4.41	6.46	2050	1.21
	1MA1+1MA1+1MA35	1.16	1.93	1.93	2.70	2.70	4.41	10.40	11.11	0.76	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.40	6.46	2056	1.22
	1MA1+1MA1+1MA42	1.10	1.83	1.83	2.56	3.08	4.61	10.40	11.12	0.82	2.61	2.89	3.6	11.6	12.8	98	3.98	A	A+	4.40	6.46	2056	1.21
	1MA1+1MA1+1MA50	1.04	1.73	1.73	2.43	3.47	4.83	10.40	11.25	0.84	2.51	2.89	3.7	11.1	12.8	98	4.14	A	A+	4.40	6.46	2056	1.22

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series

Combination tables

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)					Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	Seasonal data				
		A room	B room	C room	D room	E room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.				Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
5MXS90E3V3B	1MXA1A1A1A42	1.05	1.74	1.74	2.93	2.93	4.80	10.40	11.13	0.87	2.60	2.88	3.9	11.5	12.8	98	4.00	A	A+	4.41	6.46	2054	1.21
	1MXA1A1A1A35	1.08	1.79	2.51	2.51	2.51	4.69	10.40	11.12	0.84	2.61	2.89	3.7	11.6	12.8	98	3.98	A	A+	4.49	6.46	2017	1.26
	1MXA1A1A1A42	1.03	1.71	2.39	2.39	2.87	4.89	10.40	11.13	0.87	2.60	2.88	3.9	11.5	12.8	98	4.00	A	A+	4.50	6.46	2010	1.26
	1MXA1A1A1A35	1.01	2.35	2.35	2.35	2.35	4.97	10.40	11.13	0.90	2.60	2.88	4.0	11.5	12.8	98	4.00	A	A+	4.55	6.46	1986	1.25
	2MXA1A1A1A20	2.08	2.08	2.08	2.08	2.08	3.42	10.40	11.10	0.58	2.62	2.89	2.6	11.6	12.8	98	3.97	A	A+	4.23	6.46	2137	1.23
	2MXA1A1A1A25	1.98	1.98	1.98	1.98	2.48	3.56	10.40	11.10	0.60	2.62	2.89	2.7	11.6	12.8	98	3.97	A	A+	4.24	6.46	2135	1.23
	2MXA1A1A1A35	1.81	1.81	1.81	1.81	3.16	3.84	10.40	11.11	0.67	2.61	2.89	3.0	11.6	12.8	98	3.98	A	A+	4.34	6.46	2085	1.22
	2MXA1A1A1A42	1.70	1.70	1.70	1.70	3.60	4.04	10.40	11.11	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	2MXA1A1A1A50	1.60	1.60	1.60	1.60	4.00	4.27	10.40	11.24	0.71	2.51	2.90	3.1	11.1	12.9	98	4.14	A	A+	4.31	6.46	2098	1.22
	2MXA1A1A1A60	1.49	1.49	1.49	1.49	4.44	4.55	10.40	11.47	0.72	2.38	2.81	3.2	10.6	12.5	98	4.37	A	A+	4.41	6.46	2052	1.22
	2MXA1A1A1A71	1.38	1.38	1.38	1.38	4.88	4.86	10.40	11.50	0.79	2.36	2.79	3.5	10.5	12.4	98	4.41	A	A+	4.47	6.46	2022	1.26
	2MXA1A1A1A25	1.90	1.90	1.90	2.35	2.35	3.70	10.40	11.10	0.62	2.62	2.89	2.8	11.6	12.8	98	3.97	A	A+	4.25	6.46	2128	1.23
	2MXA1A1A1A35	1.73	1.73	1.73	2.17	3.04	3.99	10.40	11.11	0.69	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	2MXA1A1A1A42	1.64	1.64	1.64	2.05	3.43	4.18	10.40	11.11	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	2MXA1A1A1A50	1.54	1.54	1.54	1.93	3.85	4.41	10.40	11.24	0.74	2.51	2.90	3.3	11.1	12.9	98	4.14	A	A+	4.34	6.46	2085	1.22
	2MXA1A1A1A60	1.43	1.43	1.43	1.80	4.31	4.69	10.40	11.47	0.74	2.38	2.81	3.3	10.6	12.5	98	4.37	A	A+	4.41	6.46	2050	1.21
	2MXA1A1A1A71	1.33	1.33	1.33	1.67	4.74	5.00	10.40	11.50	0.82	2.36	2.79	3.6	10.5	12.4	98	4.41	A	A+	4.48	6.46	2020	1.26
	2MXA1A1A1A35	1.90	1.90	1.90	2.35	2.35	3.70	10.40	11.10	0.62	2.62	2.89	2.8	11.6	12.8	98	3.97	A	A+	4.40	6.46	2056	1.22
	2MXA1A1A1A42	1.52	1.52	1.52	2.66	3.18	4.46	10.40	11.12	0.79	2.55	2.89	3.5	11.3	12.8	98	4.08	A	A+	4.40	6.46	2056	1.21
	2MXA1A1A1A50	1.43	1.43	1.43	2.51	3.60	4.69	10.40	11.25	0.82	2.51	2.89	3.6	11.1	12.8	98	4.14	A	A+	4.40	6.46	2056	1.22
	2MXA1A1A1A60	1.34	1.34	1.34	2.35	4.03	4.97	10.40	11.48	0.82	2.37	2.80	3.6	10.5	12.4	98	4.39	A	A+	4.51	6.46	2006	1.26
	2MXA1A1A1A42	1.44	1.44	1.44	3.04	3.04	4.66	10.40	11.13	0.81	2.55	2.88	3.6	11.3	12.8	98	4.08	A	A+	4.41	6.46	2054	1.21
	2MXA1A1A1A50	1.37	1.37	1.37	2.87	3.42	4.89	10.40	11.26	0.84	2.56	2.95	3.7	11.4	13.1	98	4.06	A	A+	4.40	6.46	2056	1.22
	2MXA1A1A1A25	1.81	1.81	2.26	2.26	2.26	3.84	10.40	11.10	0.67	2.62	2.89	3.0	11.6	12.8	98	3.97	A	A+	4.25	6.46	2126	1.23
	2MXA1A1A1A35	1.66	1.66	2.08	2.08	2.92	4.13	10.40	11.11	0.71	2.61	2.89	3.1	11.6	12.8	98	3.98	A	A+	4.34	6.46	2084	1.22
	2MXA1A1A1A42	1.58	1.58	1.97	1.97	3.30	4.32	10.40	11.11	0.74	2.56	2.89	3.3	11.4	12.8	98	4.06	A	A+	4.34	6.46	2083	1.22
	2MXA1A1A1A50	1.49	1.49	1.86	1.86	3.70	4.55	10.40	11.24	0.76	2.51	2.90	3.4	11.1	12.9	98	4.14	A	A+	4.34	6.46	2084	1.22
	2MXA1A1A1A60	1.39	1.39	1.73	1.73	4.16	4.83	10.40	11.47	0.80	2.38	2.81	3.5	10.6	12.5	98	4.37	A	A+	4.43	6.46	2043	1.21
	2MXA1A1A1A35	1.54	1.54	1.92	2.70	2.70	4.41	10.40	11.11	0.76	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.41	6.46	2054	1.21
	2MXA1A1A1A42	1.46	1.46	1.84	2.56	3.08	4.61	10.40	11.12	0.82	2.55	2.89	3.6	11.3	12.8	98	4.08	A	A+	4.42	6.46	2047	1.21
	2MXA1A1A1A50	1.39	1.39	1.72	2.43	3.47	4.83	10.40	11.25	0.84	2.51	2.89	3.7	11.1	12.8	98	4.14	A	A+	4.40	6.46	2056	1.22
	2MXA1A1A1A42	1.40	1.40	1.74	2.93	2.93	4.80	10.40	11.13	0.87	2.60	2.94	3.9	11.5	13.0	98	4.00	A	A+	4.44	6.46	2040	1.27
	2MXA1A1A1A35	1.44	1.44	2.52	2.50	2.50	4.69	10.40	11.12	0.84	2.61	2.89	3.7	11.6	12.8	98	3.98	A	A+	4.50	6.46	2010	1.26
	2MXA1A1A1A42	1.37	1.37	2.40	2.39	2.87	4.89	10.40	11.13	0.87	2.60	2.94	3.9	11.5	13.0	98	4.00	A	A+	4.51	6.46	2008	1.26
	2MXA1A1A1A25	1.72	2.17	2.17	2.17	2.17	3.99	10.40	11.10	0.69	2.62	2.89	3.1	11.6	12.8	98	3.97	A	A+	4.28	6.46	2113	1.23
	2MXA1A1A1A35	1.60	2.00	2.00	2.00	2.80	4.27	10.40	11.11	0.74	2.61	2.89	3.3	11.6	12.8	98	3.98	A	A+	4.35	6.46	2081	1.22
	2MXA1A1A1A42	1.52	1.90	1.90	1.90	3.18	4.46	10.40	11.11	0.79	2.56	2.89	3.5	11.4	12.8	98	4.06	A	A+	4.35	6.46	2079	1.22
	2MXA1A1A1A50	1.44	1.79	1.79	1.79	3.59	4.69	10.40	11.24	0.82	2.51	2.90	3.6	11.1	12.9	98	4.14	A	A+	4.34	6.46	2083	1.22
	2MXA1A1A1A60	1.33	1.68	1.68	1.68	4.03	4.97	10.40	11.47	0.82	2.38	2.81	3.6	10.6	12.5	98	4.37	A	A+	4.44	6.46	2036	1.27
	2MXA1A1A1A35	1.48	1.86	1.86	2.60	2.60	4.55	10.40	11.11	0.82	2.61	2.89	3.6	11.6	12.8	98	3.98	A	A+	4.42	6.46	2047	1.21
	2MXA1A1A1A42	1.41	1.77	1.77	2.48	2.97	4.75	10.40	11.12	0.84	2.55	2.89	3.7	11.3	12.8	98	4.08	A	A+	4.44	6.46	2040	1.27
	2MXA1A1A1A50	1.34	1.68	1.68	2.35	3.35	4.97	10.40	11.25	0.87	2.51	2.89	3.9	11.1	12.8	98	4.14	A	A+	4.41	6.46	2054	1.21
	2MXA1A1A1A42	1.34	1.69	1.69	2.84	2.84	4.94	10.40	11.13	0.90	2.60	2.94	4.0	11.5	13.0	98	4.00	A	A+	4.44	6.46	2039	1.27
	2MXA1A1A1A35	1.38	1.73	2.43	2.43	2.43	4.83	10.40	11.12	0.87	2.61	2.89	3.9	11.6	12.8	98	3.98	A	A+	4.51	6.46	2008	1.26
	2MXA1A1A1A25	2.08	2.08	2.08	2.08	2.08	4.13	10.40	11.10	0.72	2.62	2.89	3.2	11.6	12.8	98	3.97	A	A+	4.29	6.46	2110	1.23
	2MXA1A1A1A35	1.93	1.93	1.93	1.93	2.68	4.41	10.40	11.11	0.77	2.61	2.89	3.4	11.6	12.8	98	3.98	A	A+	4.35	6.46	2079	1.22
	2MXA1A1A1A42	1.83	1.83	1.83	1.83	3.08	4.61	10.40	11.11	0.82	2.56	2.89	3.6	11.4	12.8	98	4.06	A	A+	4.37	6.46	2071	1.22
	2MXA1A1A1A50	1.73	1.73	1.73	1.73	3.48	4.83	10.40	11.24	0.85	2.51	2.90	3.8	11.1	12.9	98	4.14	A	A+	4.35	6.46	2081	1.22
	2MXA1A1A1A35	1.80	1.80	1.80	2.50	2.50	4.69	10.40	11.11	0.85	2.61	2.89	3.8	11.6	12.8	98	3.98	A	A+	4.44	6.46	2040	1.27
	2MXA1A1A1A42	1.71	1.71	1.71	2.40	2.87	4.89	10.40	11.12	0.87	2.61	2.89	3.9	11.6	12.8	98	3.98	A	A+	4.47	6.46	2026	1.27
	2MXA1A1A1A35	1.69	1.69	2.34	2.34	2.34	4.97	10.40	11.12	0.90	2.61	2.89	4.0	11.6	12.8	98	3.98	A	A+	4.51	6.46	2008	1.26

Notes:
1. Cooling capacity is based on 27°CDB/19°CWB (Indoor temperature). 35°CDB (Outdoor temperature).
   Heating capacity is based on 20°CDB (Indoor temperature). 7°CDB/6°CWB (Outdoor temperature).
2. The total ability of connected indoor unit is up to 14.5kW.
3. It is impossible to connect the indoor unit for one room only.
4. The above is the value for connecting with the following indoor units.
   1.5kW: wall mounted CTXS-K series; 2.0, 2.5, 3.5, 4.2, 5.0kW: wall mounted FTXS-K series
   6.0, 7.1 kW class; wall mounted G series



VRV IV S-series

Space saving solution without compromising on efficiency

In 2015 our successful mini VRV range gets a thorough update to make it even better suited for residential and light commercial applications where space is limited and performance expectations are high.

VRV IV S-series

Variable Refrigerant Temperature

VRV IV S-series

(expected 2nd half 2015)

- Incorporates VRV IV standards such as Variable Refrigerant Temperature
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains
- Connect either VRV or stylish indoors (Daikin Emura, Nexura, ...)
- Extended range with 8, 10 and 12 HP unit for bigger applications with space limitations (expected end of 2015)

4-5-6-8-10-12 HP



VRV IV S-series compact

(expected 1st half 2015)

- Smaller single fan casing ideally for residential applications or small residential application in city centres
- Incorporates all main VRV IV S-series features

4-5 HP



VRVIII-S heat pump

Space saving solution without compromising on efficiency

- For residential and light commercial applications
- Space saving design for flexible installation
- Wide range of indoor units: either connect VRV or stylish indoor units such as Daikin Emura, Nexura ...
- Energy efficient heating system based on air source heat pump technology, lowering energy bills and CO2 emmisions
- Connect up to 9 indoor units, which can all be individually controlled
- Possibility to combine different types of indoor units: wall mounted, floor standing, concealed ceiling, ceiling suspended, round flow or 4-way blow cassettes
- 3 steps in night quiet mode: step 1: 47dBA, step 2: 44 dBA, step 3: 41 dBA
- Simplified installation & guaranteed optimal efficiency with automatic charging & testing
- The ability to control each conditioned zone individually keeps VRV system running costs to an absolute minimum
- Spread your installation cost by phased installation
- Possibility to limit peak power consumption between 30 and 80%, for example during periods with high power demand



RXYSQ-P8V1

CONNECTABLE INDOOR UNITS	Wall mounted													Floor standing						Flexi type				Round flow cassette			Fully flat cassette				Concealed ceiling								Ceiling suspended		
	FTXG-L				CTXS-K		FTXS-K						FTXS-G	FVXG-K			FVXS-F			FLXS-B(9)				FCQG-F			FFQ-C				FDXS-F(9)				FDBQ-B /FBQ-D				FHQ-C		
	20	25	35	50	15	35	20	25	35	42	50	60	71	25	35	50	25	35	50	25	35	50	60	35	50	60	25	35	50	60	25	35	50	60	25	35	50	60	35	50	60
RXYSQ-P8V1	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Outdoor unit				RXYSQ	4P8V1	5P8V1	6P8V1
Capacity range				HP	4	5	6
Cooling capacity	Nom.			kW	12.6	14.0	15.5
Heating capacity	Nom.			kW	14.2	16.0	18.0
Power input - 50Hz	Cooling	Nom.		kW	3.24	3.51	4.53
	Heating	Nom.		kW	3.12	3.86	4.57
EER					3.89	3.99	3.42
COP					4.55	4.15	3.94
Maximum number of connectable indoor units					8 (1) / 8 (2)	10 (1) / 9 (2)	12 (1) / 9 (2)
Indoor index connection	Min.				50	62.5	70
	Nom.				-		
	Max.				130	162.5	182
Dimensions	Unit	HeightxWidthxDepth		mm	1,345x900x320		
Weight	Unit			kg	120		
Fan	Air flow rate	Cooling	Nom.	m^3/min	106		
Sound power level	Cooling	Nom.		dBA	66	67	69
Sound pressure level	Cooling	Nom.		dBA	50	51	53
	Heating	Nom.		dBA	52	53	55
Operation range	Cooling	Min.~Max.		°CDB	-5~46		
	Heating	Min.~Max.		°CWB	-20~15.5		
Refrigerant	Type/Charge/GWP			kg	R-410A / 4.0 / 2,087.5		
	Charge			TCO_2Eq	8.4		
Piping connections	Liquid	OD		mm	9.52		
	Gas	OD		mm	15.9 (1) / 19.1 (2)	15.9 (1) / 19.1 (2)	19.1
	Total piping length	System	Actual	m	300 (1) / 115 (2)	300 (1) / 135 (2)	300 (1) / 145 (2)
Power supply	Phase/Frequency/Voltage			Hz/V	1N~/50/220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	32.0		

(1) In case VRV indoor units are connected (2) In case RA indoors are connected

Branch provider			BPMKS967B2	BPMKS967B3
Connectable indoor units			1~2	1~3
Max. indoor unit connectable capacity			14.2	20.8
Max. connectable combination			71+71	60+71+71
Dimensions	Height x Width x Depth	mm	180x294x350	
Weight		kg	7	8

Multi model application

- Outdoor units for multi model application.
- Outdoor units are fitted with a swing compressor, renowned for its low noise and high energy efficiency
- Up to 3 indoor units can be connected to 1 multi outdoor unit; all indoor units are individually controllable and do not need to be installed in the same room or at the same time
- Night quiet mode automatically reduces the operation sound of the outdoor unit by 3dBA during nighttime (multi outdoor units in cooling mode only)
- Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall



2AMX40-50G



3AMX52E

	Wall mounted									
	ATXS-K				ATX-J3			ATX-K		
Connectable indoor units	20	25	35	50	20	25	35	20	25	35
2AMX40G	●	●	●		●	●	●	●	●	●
2AMX50G	●	●	●	●	●	●	●	●	●	●
3AMX52E	●	●	●	●						

Indoor unit					2AMX40G	2AMX50G	3AMX52E
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x936x300
Weight	Unit			kg	38	42	49
Sound power level	Cooling			dBA	62	63	59
	Heating			dBA	-		60
Sound pressure level	Cooling	Nom.		dBA	47	48	46
	Heating	Nom.		dBA	48	50	47
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10~46		-10~46
	Heating	Ambient	Min.~Max.	°CWB	-15~18		
Refrigerant	Type/Charge/GWP			kg	R-410A / 1.2 / 2,087.5	R-410A / 1.6 / 2,087.5	R-410A / 2.0 / 2,087.5
	Charge			TCO_2Eq	2.5	3.3	4.2
Piping connections	Liquid	OD		mm	6.35		
	Gas	OD		mm	9.5		
	Piping length	OU - IU	Max.	m	20		25
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 20m)		0.02 (for piping length exceeding 30m)
	Level difference	IU - OU	Max.	m	15		
		IU - IU	Max.	m	7.5		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 / 230
Current - 50Hz	Maximum fuse amps (MFA)			A	16		20

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
2AMX40G3V1B	2.0	2.00	/	1.50	2.00	2.40	0.330	0.440	0.570	1.5	2.0	2.6	94	4.55	A	220	/	/	/	/
	2.5	2.50	/	1.50	2.50	3.00	0.330	0.610	0.800	1.5	2.8	3.7	94	4.10	A	305	/	/	/	/
	3.5	3.50	/	1.50	3.50	4.00	0.330	1.050	1.360	1.5	4.8	6.2	95	3.33	A	525	/	/	/	/
	2.0 + 2.0	2.00	2.00	1.75	4.00	4.20	0.310	1.040	1.120	1.4	4.8	5.2	94	3.85	A	520	A++	6.38	4.00	220
	2.0 + 2.5	1.85	2.15	1.75	4.00	4.30	0.310	1.030	1.170	1.4	4.8	5.4	94	3.88	A	515	A++	6.26	4.00	224
	2.0 + 3.5	1.75	2.25	1.75	4.00	4.50	0.310	1.000	1.230	1.4	4.6	5.7	94	4.00	A	500	A++	6.50	4.00	216
	2.5 + 2.5	2.00	2.00	1.75	4.00	4.40	0.310	1.020	1.230	1.4	4.7	5.7	94	3.92	A	510	A++	6.26	4.00	224
	2.5 + 3.5	1.80	2.20	1.75	4.00	4.60	0.310	0.990	1.310	1.4	4.6	6.1	94	4.04	A	495	A++	6.49	4.00	216

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	AEC (kWh)	Seasonal data				
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
2AMX40G3V1B	2.0	3.00	/	1.10	3.00	3.70	0.260	0.820	1.230	1.2	3.8	5.7	94	3.66	A	410	/	/	/	/	/
	2.5	3.40	/	1.10	3.40	4.10	0.260	1.020	1.480	1.2	4.7	6.8	95	3.33	C	510	/	/	/	/	/
	3.5	3.80	/	1.10	3.80	4.40	0.260	1.280	1.720	1.2	5.9	7.9	95	2.97	D	640	/	/	/	/	/
	2.0 + 2.0	2.10	2.10	1.40	4.20	4.60	0.250	0.960	1.120	1.1	4.4	5.1	95	4.38	A	480	A+	4.15	2.99	1009	0.56
	2.0 + 2.5	2.10	2.30	1.40	4.40	4.70	0.250	1.040	1.170	1.1	4.7	5.3	96	4.23	A	520	A+	4.16	2.99	1006	0.58
	2.0 + 3.5	2.00	2.40	1.40	4.40	4.70	0.240	1.000	1.120	1.1	4.5	5.1	96	4.40	A	500	A+	4.14	2.96	1001	0.56
	2.5 + 2.5	2.20	2.20	1.40	4.40	4.70	0.250	1.030	1.160	1.1	4.7	5.3	96	4.27	A	515	A+	1.16	3.00	1009	0.59
	2.5 + 3.5	2.05	2.35	1.40	4.40	4.70	0.240	0.990	1.110	1.1	4.5	5.0	96	4.44	A	495	A+	4.15	2.96	999	0.58

Notes:
1. The total capacity of each connected indoor unit is up to 8.5 kW.
2. The values above are for connecting with the following indoor unit types:
   2.0, 2.5, 3.5, 5.0 kW class
   Wall-mounted ATXS-K series
3. These indoor units can only be used in a multi-unit setup.
4. Cooling capacity conditions:
   Indoor temperature 27°C DB / 19°C WB
   Outdoor temperature 35°C DB
   Heating capacity conditions:
   Indoor temperature 20°C DB
   Outdoor temperature 7°C DB / 6°C WB
5. Design temperature: -10°C

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
2AMX50G3V1B	2.0	2.00	/	1.60	2.00	2.60	0.330	0.390	0.580	1.6	1.9	2.8	91	5.13	A	195	/	/	/	/
	2.5	2.50	/	1.60	2.50	3.10	0.330	0.560	0.800	1.6	2.7	3.8	91	4.46	A	280	/	/	/	/
	3.5	3.50	/	1.60	3.50	4.00	0.320	0.940	1.240	1.5	4.5	5.9	91	3.72	A	470	/	/	/	/
	5.0	5.00	/	1.60	5.00	5.10	0.320	1.940	2.070	1.5	9.3	9.9	91	2.58	E	970	/	/	/	/
	2.0 + 2.0	2.00	2.00	1.95	4.00	5.00	0.340	0.870	1.360	1.6	4.2	6.5	91	4.60	A	435	A++	6.55	4.00	214
	2.0 + 2.5	2.00	2.50	1.95	4.50	5.10	0.340	1.070	1.450	1.6	5.1	6.9	91	4.21	A	535	A++	6.53	4.50	242
	2.0 + 3.5	1.82	3.18	1.95	5.00	5.40	0.340	1.350	1.620	1.6	6.5	7.7	91	3.70	A	675	A++	6.51	5.00	269
	2.0 + 5.0	1.43	3.57	1.95	5.00	5.50	0.340	1.310	1.710	1.6	6.3	8.2	91	3.82	A	655	A++	6.50	5.00	270
	2.5 + 2.5	2.50	2.50	1.95	5.00	5.30	0.340	1.380	1.610	1.6	6.6	7.7	91	3.62	A	690	A++	6.39	5.00	274
	2.5 + 3.5	2.08	2.92	1.95	5.00	5.40	0.340	1.340	1.610	1.6	6.4	7.7	91	3.73	A	670	A++	6.48	5.00	270
	2.5 + 5.0	1.67	3.33	1.95	5.00	5.50	0.340	1.300	1.700	1.6	6.2	8.1	91	3.85	A	650	A++	6.48	5.00	271
	3.5 + 3.5	2.50	2.50	1.98	5.00	5.40	0.340	1.290	1.550	1.6	6.2	7.4	91	3.88	A	645	A++	6.55	5.00	268
	3.5 + 5.0	2.06	2.94	1.98	5.00	5.50	0.340	1.270	1.620	1.6	6.1	7.7	91	3.94	A	635	A++	6.54	5.00	268

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)		Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	AEC (kWh)	Seasonal data				
		A room	B room	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
2AMX50G3V1B	2.0	3.00	/	1.16	3.00	3.70	0.230	0.780	1.080	1.1	3.7	5.2	91	3.85	A	390	/	/	/	/	/
	2.5	3.40	/	1.16	3.40	4.10	0.220	0.940	1.270	1.1	4.5	6.1	91	3.62	A	470	/	/	/	/	/
	3.5	4.00	/	1.16	4.00	4.60	0.220	1.180	1.460	1.1	5.6	7.0	91	3.39	C	590	/	/	/	/	/
	5.0	5.40	/	1.28	5.40	5.60	0.230	1.770	1.910	1.1	8.5	9.1	91	3.05	D	885	/	/	/	/	/
	2.0 + 2.0	2.65	2.65	1.18	5.30	5.70	0.220	1.260	1.400	1.1	6.0	6.7	91	4.21	A	630	A+	4.12	3.97	1351	0.76
	2.0 + 2.5	2.44	3.06	1.18	5.50	5.80	0.220	1.320	1.430	1.1	6.3	6.8	91	4.17	A	660	A+	4.12	3.97	1351	0.76
	2.0 + 3.5	2.04	3.56	1.24	5.60	5.90	0.230	1.310	1.390	1.1	6.3	6.6	91	4.27	A	655	A+	4.14	4.28	1448	0.82
	2.0 + 5.0	1.63	4.07	1.29	5.70	6.20	0.230	1.330	1.480	1.1	6.4	7.1	91	4.29	A	665	A+	4.11	4.42	1505	0.86
	2.5 + 2.5	2.80	2.80	1.18	5.60	5.80	0.220	1.380	1.430	1.1	6.6	6.8	91	4.06	A	690	A+	4.10	4.25	1452	0.81
	2.5 + 3.5	2.38	3.32	1.24	5.70	6.00	0.230	1.340	1.450	1.1	6.4	6.9	91	4.25	A	670	A+	4.09	4.41	1510	0.84
	2.5 + 5.0	1.90	3.80	1.35	5.70	6.30	0.230	1.320	1.520	1.1	6.3	7.3	91	4.32	A	660	A+	4.10	4.42	1510	0.84
	3.5 + 3.5	2.85	2.85	1.30	5.70	6.10	0.230	1.330	1.460	1.1	6.4	7.0	91	4.29	A	665	A+	4.17	4.43	1489	0.86
	3.5 + 5.0	2.35	3.35	1.35	5.70	6.40	0.230	1.310	1.560	1.1	6.3	7.5	91	4.35	A	655	A+	4.17	4.45	1494	0.84

Notes:
1. The total capacity of each connected indoor unit is up to 6.0 kW.
2. The values above are for connecting with the following indoor unit types:
   2.0, 2.5, 3.5 kW class
   Wall-mounted ATXS-K series
3. These indoor units can only be used in a multi-unit setup.
4. Cooling capacity conditions:
   Indoor temperature 27°C DB / 19°C WB
   Outdoor temperature 35°C DB
   Heating capacity conditions:
   Indoor temperature 20°C DB
   Outdoor temperature 7°C DB / 6°C WB
5. Design temperature: -10°C

Combination tables

Cooling

Outdoor unit	Indoor unit	Cooling capacity (kW)			Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	EER	Energy label	AEC (kWh)	Seasonal data			
		A room	B room		Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SEER	Pdesign	AEC
3AMX52E4V1B	2.0	2.00	/	/	1.76	2.00	2.84	0.350	0.460	0.740	1.6	2.1	3.4	96	4.35	A	230	/	/	/	/
	2.5	2.50	/	/	1.76	2.50	3.12	0.350	0.620	0.750	1.6	2.8	3.4	97	4.03	A	310	/	/	/	/
	3.5	3.50	/	/	1.76	3.50	4.18	0.350	0.970	1.290	1.6	4.3	5.7	98	3.61	A	485	/	/	/	/
	5.0	/	/	5.00	1.79	5.00	5.40	0.350	1.750	2.030	1.5	7.7	8.9	99	2.86	C	875	/	/	/	/
	2.0 + 2.0	2.00	2.00	/	1.88	4.00	5.96	0.350	0.950	1.910	1.5	4.2	8.4	99	4.21	A	475	A++	6.76	4.00	208
	2.0 + 2.5	2.00	2.50	/	1.88	4.50	6.23	0.350	1.180	2.140	1.5	5.2	9.4	99	3.81	A	590	A++	6.78	4.50	233
	2.0 + 3.5	1.89	3.31	/	1.88	5.20	6.24	0.350	1.550	2.070	1.5	6.8	9.1	99	3.35	A	775	A++	6.86	5.20	266
	2.0 + 5.0	1.49	/	3.71	1.88	5.20	6.47	0.350	1.420	2.150	1.5	6.2	9.4	99	3.66	A	710	A++	6.85	5.20	266
	2.5 + 2.5	2.50	2.50	/	1.88	5.00	6.23	0.350	1.450	2.140	1.5	6.4	9.4	99	3.45	A	725	A++	6.71	5.00	261
	2.5 + 3.5	2.17	3.03	/	1.88	5.20	6.35	0.350	1.550	2.250	1.5	6.8	9.9	99	3.35	A	775	A++	6.85	5.20	266
	2.5 + 5.0	1.73	/	3.47	1.88	5.20	6.47	0.350	1.420	2.070	1.5	6.2	9.1	99	3.66	A	710	A++	6.85	5.20	266
	3.5 + 3.5	2.60	2.60	/	1.88	5.20	6.40	0.350	1.550	2.250	1.5	6.8	9.9	99	3.35	A	775	A++	6.89	5.20	265
	3.5 + 5.0	2.14	/	3.06	1.88	5.20	6.49	0.350	1.420	2.090	1.5	6.2	9.2	99	3.66	A	710	A++	6.87	5.20	265
	2.0+2.0+2.0	1.73	1.73	1.73	1.86	5.19	7.04	0.350	1.240	2.160	1.5	5.4	9.5	99	4.19	A	620	A++	7.06	5.19	258
	2.0+2.0+2.5	1.60	1.60	1.99	1.86	5.19	7.04	0.350	1.240	2.160	1.5	5.4	9.5	99	4.19	A	620	A++	7.06	5.19	258
	2.0+2.0+3.5	1.38	1.38	2.43	1.95	5.19	7.06	0.370	1.240	2.160	1.6	5.4	9.5	99	4.19	A	620	A++	7.07	5.19	257
	2.0+2.5+2.5	1.49	1.85	1.85	1.86	5.19	7.04	0.350	1.240	2.160	1.5	5.4	9.5	99	4.19	A	620	A++	7.04	5.19	259
	2.0+2.5+3.5	1.30	1.63	2.27	1.95	5.20	7.06	0.370	1.240	2.160	1.6	5.4	9.5	99	4.19	A	620	A++	7.07	5.20	258
	2.0+3.5+3.5	1.16	2.02	2.02	1.95	5.20	7.07	0.370	1.240	2.160	1.6	5.4	9.5	99	4.19	A	620	A++	7.08	5.20	258
	2.5+2.5+2.5	1.73	1.73	1.73	1.95	5.19	7.04	0.370	1.240	2.160	1.6	5.4	9.5	99	4.19	A	620	A++	7.04	5.19	259
	2.5+2.5+3.5	1.53	1.53	2.14	1.95	5.20	7.06	0.370	1.230	2.160	1.6	5.4	9.5	99	4.23	A	615	A++	7.07	5.20	258
	2.0+2.0+5.0	1.16	1.16	2.88	2.11	5.20	7.30	0.380	1.220	2.260	1.7	5.4	9.9	99	4.26	A	610	A++	7.07	5.20	258

Heating

Outdoor unit	Indoor unit	Heating capacity (kW)			Total capacity (kW)			Power input (kW)			Total current (A)			Power factor (%)	COP	Energy label	AEC (kWh)	Seasonal data				
		A room	B room		Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.					Label	SCOP	Pdesign	AEC	Back-up heater capacity at -10°C
3AMX52E4V1B	2.0	2.72	/	/	1.21	2.72	3.75	0.300	0.720	1.200	1.4	3.3	5.4	96	3.78	A	360	/	/	/	/	/
	2.5	3.40	/	/	1.21	3.40	4.00	0.300	0.990	1.260	1.3	4.4	5.6	97	3.43	B	495	/	/	/	/	/
	3.5	4.20	/	/	1.21	4.20	4.82	0.300	1.390	1.680	1.3	6.2	7.5	98	3.02	D	695	/	/	/	/	/
	5.0	/	/	5.80	1.33	5.80	6.79	0.300	2.160	2.590	1.3	9.5	11.4	99	2.69	E	1080	/	/	/	/	/
	2.0 + 2.0	3.05	3.05	/	1.28	6.10	7.00	0.310	1.700	2.280	1.4	7.5	10.0	99	3.59	B	850	A+	4.18	4.84	1620	0.93
	2.0 + 2.5	2.78	3.47	/	1.28	6.25	7.00	0.310	1.750	2.280	1.4	7.7	10.0	99	3.57	B	875	A+	4.18	4.84	1622	0.93
	2.0 + 3.5	2.38	4.17	/	1.34	6.55	7.04	0.310	1.860	2.280	1.4	8.2	10.0	99	3.52	B	930	A+	4.24	4.87	1608	0.94
	2.0 + 5.0	1.94	/	4.86	1.39	6.80	7.20	0.310	1.870	2.320	1.4	8.2	10.2	99	3.64	A	935	A+	4.26	4.88	1606	0.94
	2.5 + 2.5	3.25	3.25	/	1.28	6.50	7.00	0.310	1.860	2.310	1.4	8.2	10.1	99	3.49	B	930	A+	4.18	4.84	1622	0.93
	2.5 + 3.5	2.79	3.97	/	1.34	6.70	7.19	0.310	1.930	2.360	1.4	8.5	10.4	99	3.47	B	965	A+	4.24	4.87	1608	0.94
	2.5 + 5.0	2.27	/	4.53	1.45	6.80	7.35	0.310	1.870	2.320	1.4	8.2	10.2	99	3.64	A	935	A+	4.25	4.87	1605	0.93
	3.5 + 3.5	3.40	3.40	/	1.40	6.80	7.22	0.310	1.970	2.350	1.4	8.7	10.3	99	3.45	B	985	A+	4.27	4.89	1605	0.94
	3.5 + 5.0	2.80	/	4.00	1.45	6.80	7.50	0.310	1.830	2.310	1.4	8.0	10.1	99	3.72	A	915	A+	4.28	4.90	1603	0.94
	2.0+2.0+2.0	2.26	2.26	2.26	1.34	6.78	8.02	0.320	1.570	2.140	1.4	6.9	9.4	99	4.32	A	785	A+	4.46	4.93	1547	0.94
	2.0+2.0+2.5	2.09	2.09	2.60	1.34	6.78	8.02	0.320	1.570	2.140	1.4	6.9	9.4	99	4.32	A	785	A+	4.46	4.93	1547	0.94
	2.0+2.0+3.5	1.80	1.80	3.18	1.45	6.78	8.05	0.320	1.560	2.140	1.4	6.9	9.4	99	4.35	A	780	A+	4.49	4.92	1535	0.94
	2.0+2.5+2.5	1.94	2.42	2.42	1.34	6.78	8.02	0.320	1.570	2.140	1.4	6.9	9.4	99	4.32	A	785	A+	4.46	4.93	1549	0.94
	2.0+2.5+3.5	1.70	2.13	2.97	1.57	6.80	8.05	0.320	1.560	2.140	1.4	6.9	9.4	99	4.36	A	780	A+	4.47	4.92	1541	0.94
	2.0+3.5+3.5	1.52	2.64	2.64	1.56	6.80	8.08	0.320	1.560	2.140	1.4	6.9	9.4	99	4.36	A	780	A+	4.51	4.91	1524	0.94
	2.5+2.5+2.5	2.26	2.26	2.26	1.45	6.78	8.02	0.320	1.570	2.140	1.4	6.9	9.4	99	4.32	A	785	A+	4.45	4.94	1556	0.95
	2.5+2.5+3.5	2.00	2.00	2.80	1.57	6.80	8.05	0.320	1.560	2.140	1.4	6.9	9.4	99	4.36	A	780	A+	4.47	4.92	1543	0.94
	2.0+2.0+5.0	1.51	1.51	3.78	1.67	6.80	8.27	0.320	1.640	2.110	1.4	7.2	9.3	99	4.15	A	820	A+	4.48	4.92	1536	0.94

Notes:
1. The total capacity of each connected indoor unit is up to 9.0kW.
2. The values above are for connecting with the following indoor unit types:
   2.0, 2.5, 3.5, 5.0 kW class
   Wall-mounted ATXS-K series
3. These indoor units can only be used in a multi-unit setup.
4. Cooling capacity conditions:
   Indoor temperature 27°C DB / 19°C WB
   Outdoor temperature 35°C DB
   Heating capacity conditions:
   Indoor temperature 20°C DB
   Outdoor temperature 7°C DB / 6°C WB
5. Design temperature: -10°C



Sky Air the solution for the light commercial sector

Sky Air is Daikin's industry-leading light commercial range, which has been designed for optimum seasonal energy efficiency. Providing the ideal solution for all kinds of small commercial spaces, the Sky Air series offers a complete comfort solution that puts you in total control of your heating and cooling, ventilation and air curtains.

Sky Air

Light commercial applications

Why choose a Daikin Sky Air 156

Products overview 160

Benefits overview 164

Why choose Seasonal Smart 166

Ceiling mounted cassette units

FCQG-F / RXS-L3/L 169
FCQG-F / RZQG-L9V1/L(8)Y1 170
FCQG-F / RZQSG-L3/9V1/L(8)Y1 171
FCQHG-F / RZQG-L9V1/L(8)Y1 172
FCQHG-F / RZQSG-L3/9V1/L(8)Y1 173
FFQ-C / RXS-L3/L 175

Concealed ceiling units

NEW FBQ-D / RZQG-L9V1/L(8)Y1 176
NEW FBQ-D / RZQSG-L3/9V1/L(8)Y1 177
NEW FBQ-D / RXS-L3/L 178
FDBQ-B 179
FDQ-C / RZQG-L9V1/L(8)Y1 180
FDQ-C / RZQSG-L3/9V1/L(8)Y1 180
FDQ-B / RZQ-C 181

Ceiling suspended units

FHQ-C / RZQG-L9V1/L(8)Y1 182
FHQ-C / RZQSG-L3/9V1/L(8)Y1 183
FHQ-C / RXS-L3/L 184
FUQ-C / RZQG-L9V1/L8Y1 185

Wall mounted unit

FAQ-C / RZQG-L9V1/L8Y1 186
FAQ-C / RZQSG-L3/9V1/L8Y1 187

Floor standing Units

FVQ-C / RZQG-L9V1/L(8)Y1 188
FVQ-C / RZQSG-L3/9V1/L(8)Y1 189
NEW FNQ-A / RXS-L3/L 190

Siesta sky air

4-Way blow ceiling mounted cassette

NEW ACQ-D / AZQS-B8V1/BY1 191

Concealed ceiling units

ABQ-C / AZQS-B8V1/BY1 192

Ceiling suspended units

AHQ-C / AZQS-B8V1/BY1 193

Twin, triple, Double twin applications

RZQG-L9V1/L(8)Y1 195
RZQSG-L3/9V1/L(8)Y1 196
RZQ-C 197

Rooftop

UATYQ-CY1 198
UATYP-AY1(B) 199

For more information on Options & Accessories, please refer to page 444 of this catalogue.

Sky Air



3-layer inverter range combined with a wide range of indoor units to cover a variety of applications



› Why choose a Sky Air?

The ideal solution for the light commercial sector

- Industry-leading product range for small offices, shops, retail stores, restaurants, banks or technical cooling
- From **reliable and high quality comfort** air conditioning, to **smart use of energy** customised applications with **flexible installation and operation.**
- **Extensive range** that meets even the most stringent building specifications.
- Ensures **total control** over your space heating and cooling, ventilation and doorway climate separation requirements.

Benefits for the installer

› Modular designs and factory fitted extras make installation easier to achieve.

Benefits for the consultant


› You will have the confidence of knowing that you can recommend the right climate control systems to meet tomorrow's legislation
› You will have systems that are designed to blend into any décor and provide optimal performance with top seasonal efficiencies
› You will have access to innovative technology to maximize the climate control performance of the entire building
› Your credentials as an eco-conscious consultant and designer will be enhanced.

Benefits for the end user



› Your climate control system will meet legal requirements well beyond the current legislation
› You will obtain optimal seasonal performance thus saving energy and reducing costs
› The climate control system will add value to the building thus protecting your investment
› You will save on installation and running costs, obtain rapid return on investment and contribute to ecological protection objectives.

Marketing tools

› Visit our extranet: extranet.daikineurope.com/
› Download Seasonal calculator software: www.daikineurope.com/support-and-manuals/software-downloads/air-conditioning.jsp





		Seasonal Smart	Seasonal Classic	Siesta Sky Air
				
Seasonal effciency		Up to A++		Up to B
Max. piping		Up to 75m	Up to 50m	
Operation range	Cooling	-15°C~50°C	-15°C ~46°C	-5°C ~46°C
	Heating	-20°C~15.5°C	-15°C ~15.5°C	
EDP settings		Suits technical cooling room applications	-	-
Special features		Operates with variable refrigerant temperature : all Daikin Sky Air outdoor units are able to adapt their operation to meet your unique cooling and heating requirements, without comprimising efficiency. 		
		Variable Refrigerant Temperature Go one step further in improving comfort and efficiency by having the possibility to customize the settings at time of installation. These special settings allow the boundaries of fluctuation of refrigerant's evaporating and condensing temperature to be customized to fit the application. 	-	-
Connectable indoor units		 4-Way blow ceiling suspended cassette  Round flow cassette  Ceiling suspended unit  Fully flat cassette Wall mounted unit	 Concealed floor standing unit NEW  Floor standing unit  Concealed ceiling unit NEW	 NEW 4-Way blow ceiling suspended cassette  Concealed ceiling unit  Ceiling suspended unit
Application		Pair		
		Twin/triple/double twin		-
Benefits		› For all types of commercial applications, even technical rooms › Best efficiency! › Most flexible installation › Widest range of connectable indoor units	› For all types of commercial applications › Good value for money: very efficient and comfortable indoor units	› Basic cooling/heating solution for shops


CONCEALED CEILING UNIT


4-WAY BLOW CEILING
SUSPENDED CASSETTE









WALL MOUNTED UNIT


CEILING SUSPENDED CASSETTE


FULLY FLAT CASSETTE

Products overview SkyAir

Type	Model		Product name	
Ceiling mounted cassette	High COP, round flow cassette	- 360° air discharge for the highest efficiency and comfort - High COP cassette ensures top performance for commercial applications - Auto cleaning function ensures high efficiency - Intelligent sensors save energy and maximize comfort - Lowest installation height in the market! ROUND FLOW	FCQHG-F	
	Round flow cassette	- 360° air discharge for optimum efficiency and comfort - Comfortable environment for commercial applications - Auto cleaning function ensures high efficiency - Intelligent sensors save energy and maximize comfort - Lowest installation height in the market! ROUND FLOW	FCQG-F[1]	
	Fully flat cassette	- Unique design in the market that integrates fully flat into the ceiling - Perfect integration in standard architectural ceiling tiles - Blend of iconic design and engineering excellence with a white or silver and white finish - Intelligent sensors save energy and maximize comfort - Refurbishing the room? Flexibility to suit every room layout without changing the location of the unit!	FFQ-C	
	Siesta, 4-way blow ceiling mounted unit	- For shops requiring basic solutions - 4 different air discharge directions - Air filter ensures steady supply of clean air - Control several indoor units at the same time Siesta	ACQ-D	
Concealed ceiling	Small concealed ceiling unit	- Designed for hotel bedrooms - Compact dimensions enable installation in narrow ceiling voids - Discretely concealed in the ceiling: only the grilles are visible - No disturbing sound to ensure a good night rest - Flexible installation as the the air suction direction can be altered from rear to bottom suction - Easy mounting: drain pan can be located left or right of the unit	FDBQ-B	
	Concealed ceiling unit with medium ESP	- Optimum comfort guaranteed no matter the length of ductwork or type of grilles - Top efficiency in the market: xxx label - Compact dimensions of all units enable installation in narrow ceiling voids - Lowest sound level in the market - Medium external static pressure up to 150Pa - Only grilles are visible	FBQ-D[1]	
	Concealed ceiling unit with high ESP	- ESP up to 200Pa, ideal for large sized buildings - Optimum comfort guaranteed no matter the length of ductwork or type of grilles, thanks to automatic air flow adjustment - High external static pressure up to 200Pa - Discretely concealed in the ceiling: only the grilles are visible - Change ESP to achieve optimal supply of air volume - Flexible installation as the air suction direction can be altered from rear to bottom suction	FDQ-C	
	Concealed ceiling unit with high ESP	- ESP up to 250Pa, Ideal for extra large sized spaces - High external static pressure up to 250Pa - Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible - Up to 26.4kW in heating mode	FDQ-B[1]	
	Concealed ceiling unit	- Ideal for medium sized shops with false ceilings - Discretely concealed in the ceiling: only the grilles are visible - Air filter ensures steady supply of clean air - Easy installation and maintenance - Best protection against possible water leakage Siesta	ABQ-C	
Wall mounted	Wall mounted unit	- For rooms with no false ceilings nor free floor space - Flat, stylish front panel blends easily with any interior décor and is more easy to clean - Can easily be installed in both new and refurbishment projects - Reduced energy consumption thanks to DC fan motor - The air is comfortably spread up- and downwards thanks to 5 different discharge angles - Easy maintenance as this can be done from the front of the unit	FAQ-C	
Ceiling suspended	Ceiling suspended unit	- For wide rooms with no false ceilings nor free floor space - Ideal for comfortable air flow in wide rooms thanks to Coanda effect - Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily! - Can easily be installed in both new and refurbishment projects - Can be mounted in corners or narrow spaces without any problem - Reduced energy consumption thanks to DC fan motor	FHQ-C[1]	
	4-way blow ceiling suspended unit	- Unique Daikin unit for high rooms with no false ceilings nor free floor space - Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily! - Can easily be installed in both new and refurbishment projects - Refurbishing the room? Flexibility to suit every room layout without changing the location of the unit! - Optimum comfort guaranteed with automatic air flow adjustment to the required load - The air is comfortably spread up- and downwards thanks to 5 different discharge angles	FUQ-C[1]	
	Ceiling suspended unit	- For wide rooms with no false ceilings nor free floor space - Can easily be installed in both new and refurbishment projects - Air filter ensures steady supply of clean air - Guarantees a stable temperature - Easy installation and maintenance Siesta	AHQ-C	
Floor standing	Floor standing unit	- For spaces with high ceilings - Ideal solution forvcommercial spaces with no or narrow false ceilings - Can easily be installed in both new and existing buildings - Even rooms with very high ceilings can be heated up or cooled down very easily! - Guarantees a stable temperature - Improved comfort	FVQ-C	
	Concealed floor standing unit	- Designed to be concealed in floors or walls - Ideal for installation beneath a window - Discretely concealed in the floor or wall - Limited installation space - No auxiliry piping needed	FNQ-A	

1) Twin, triple, double twin application is only possible up to 125 class


Capacity class (kW)

25	35	50	60	71	100	125	140	200	250
				●	●	●	●		
	●	●	●	●	●	●	●		
●	●	●	●						
				●	●	●			
●									
	●	●	●	●	●	●	●		
						●			
								●	●
				●	●	●	●		
				●	●				
	●	●	●	●	●	●	●		
				●	●	●	●		
				●	●	●	●		
				●	●	●			
●	●	●	●						

Pair, twin, triple & double twin application

System	Type	Model	Productname	
Air cooled	Heat pump	Seasonal Smart - Industry leading technology for commercial applications and even for technical rooms - Top efficient outdoor units - Variable Refrigerant Temperature - Computer room applications - Re-use technology - Extended operation range down to -20°C in heating - Pair, twin, triple and double twin application	RZQG-L9V1	
			RZQG-L(8)Y1	
		Seasonal Classic - Technology and comfort combined for commercial applications - Top efficient outdoor units - Re-use technology - Operation range down to -15°C in heating - Pair, twin, triple and double twin application	RZQSG-L3/L9V1	
			RZQSG-L(8)Y1	
		Super Inverter - For large commercial applications - Pair, twin, triple and double twin applications	RZQ-C	
		Siesta, outdoor unit - Ideal solution for basic cooling and heating - Easy-to-mount outdoor units: roof, terrace or wall - Outdoor units with swing or scroll compressor - Pair application	AZQS-B8V1	
			AZQS-BY1	

Rooftops

System	Type	Model	Productname	Refrigerant	
Air cooled	Heat pump	Rooftop Unit - Plug and play' for easy installation - High efficiency - Compact unit - Factory pre-charged refrigerant - Belt driven fan	UATYP-AY1(B)	R-407C	
		Rooftop Unit - Plug and play' for easy installation - High efficiency - Free cooling and fresh air intake possible - Field convertible return and supply air - Factory pre-charged refrigerant - Belt driven fan	UATYQ-CY1	R-410A	

Capacity class (kW)

71	100	125	140	200	250
●	●	●	●		
●	●	●	●		
●	●	●	●		
	●	●	●		
				●	●
●	●	●	●		
	●	●	●		

Capacity (class)

250	350	450	550	600	700	850	1000	1200
						●	●	●
●	●	●	●	●	●			

Benefits overview

Sky Air indoor

We care icons	Seasonal efficiency - Smart use of energy	Seasonal efficiency gives a more realistic indication on how efficient air conditioners operate over an entire heating or cooling season.
	Inverter technology	In combination with inverter controlled outdoor units
	Home leave operation	During absence, the indoor temperature can be maintained at a certain level.
	Fan only	The air conditioner can be used as fan, blowing air without cooling or heating.
	Auto cleaning filter	The filter automatically cleans itself once per day. Simplicity of upkeep means optimum energy efficiency and maximum comfort without the need for expensive or time-consuming maintenance.
	Floor and presence sensor	The presence sensor directs the air away from any person detected in the room, when the air flow control is on. The floor sensor detects the average floor temperature and ensures an even temperature distribution between ceiling and floor.
Comfort	Draught prevention	When starting to warm up or when the thermostat is off, the air discharge direction is set horizontally and the fan to low speed, to prevent draught. After warming up, air discharge and fan speed are set as desired.
	Whisper quiet	Daikin indoor units are whisper quiet. Also the outdoor units are guaranteed not to disturb the quiet of the neightbourhood.
	Auto cooling-heating changeover	Automatically selects cooling or heating mode to achieve the set temperature.
Air treatment	Air filter	Removes airborne dust particles to ensure a steady supply of clean air.
Humidity control	Dry programme	Allows humidity levels to be reduced without variations in room temperature.
Air flow	Ceiling soiling prevention	A special function prevents air blowing out too long in horizontal position, to prevent ceiling stains.
	Vertical auto swing	Possibility to select automatic vertical moving of the air discharge louvre, for uniform air flow and temperature distribution.
	Fan speed steps	Allows to select up to the given number of fan speed.
	Individual flap control	Individual flap control via the wired remote controller makes it simple to fix the position of each flap individually, to suit any new room configuration. Optional closure kits are available as well.
Remote control & timer	Weekly timer	Timer can be set to start operation anytime on a daily or weekly basis
	Infrared remote control	Infrared remote control with LCD to start, stop and regulate the air conditioner from a distance.
	Wired remote control	Wired remote control to start, stop and regulate the air conditioner from a distance.
	Centralised control	Centralised control to start, stop and regulate several air conditioners from one central point.
Other funtions	Auto-restart	The unit restarts automatically at the original settings after power failure.
	Self-diagnosis	Simplifies maintenance by indicating system faults or operating anomalies.
	Drain pump kit	Facilitates condensation draining from the indoor unit.
	Twin/triple/double twin application	2, 3 or 4 indoor units can be connected to only 1 outdoor unit even if they have different capacities. All indoor units operate within the same mode (cooling or heating) from one remote control.
	Multi model application	Up to 5 indoor units (even different capacities) can be connected to a single outdoor unit. All indoor units can individually be operated within the same mode.
	VRV for residential application	Up to 9 indoor units (even different capacities and up to 71 class) can be connected to a single outdoor unit. All indoor units can individually be operated within the same mode.

Ceiling mounted cassette units				Concealed ceiling units					Ceiling suspended units		4-Way blow ceiling suspended unit	Wall mounted unit	Floor standing units	
FCQHG-F	**FCQG-F**	**FFQ-C**	**ACQ-D**	**FDBQ-B**	**FBQ-D**	**FDQ-C**	**FDQ-B**	**ABQ-C**	**FHQ-C**	**AHQ-C**	**FUQ-C**	**FAQ-C**	**FNQ-A**	**FVQ-C**
														
●	●	●	●	●	●	●		●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●		●	●	●	●		●		●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●													
●	●	●												
●	●	●	●								●			
●	●	●		●	●									
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●		●	●	●	●		●		●	●	●	●
●	●	●	●											
●	●	●									●	●		●
3	3	3	4	2	3	3	2	3	3	3	3	3	2	3
●	●	●									●			
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
optional	optional	optional	standard		optional				optional	standard	optional	optional	optional	
optional	optional	optional	optional	optional	optional	optional	optional	standard	optional	optional	optional	optional	optional	optional
optional	optional	optional			optional	optional	optional		optional		optional	optional	optional	optional
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
standard	standard	standard	standard		standard	standard			optional		standard	optional		
●	●	●			●	●	●		●		●	●	●	
	●	●		●	●				●				●	
	●	●		●	●				●				●	

*Note: blue cells contain preliminary data

Seasonal Smart outdoor unit



RZQG-L9V1/L(8)Y1

Seasonal Smart

Daikin is leading the way towards more efficient and cost-effective comfort solutions with its Sky Air product range

Why choose Seasonal Smart?

- **Highest quality**
- **Advanced and leading technologies** integrated into 1 system
- **Highest seasonal efficiency values** (when compared with other systems under the same test conditions)
- Optimal **comfort and flexible installation** in all weather conditions

Top Seasonal Efficiency

› Heat exchanger that **optimises the refrigerant flow** at the most frequent operation conditions
› **Control logic** that optimises efficiency at the most frequently encountered operation conditions and that optimises the auxiliary modes
› Swing compressor
And this is enhanced even further thanks to the variable refrigerant temperature settings

Optimal comfort



› Variable refrigerant temperature to better suit application requirements: comfortable office environment or reliable technical cooling environment
› From individualised unit control to centralised management via touch-screen options and code based controllers

Flexible installation



› R-22/R-407C **replacement technology**
› **Wide operation range** in cooling (down to -15°C) and in heating (down to -20°C)
› Long pipe runs (up to 75m)
› Gas cooled PCB (L9V1)
› Easy accesibility of PCB (L9V1)
› Suits computer room applications (EDP)
› Wide range of indoor units connectable

Marketing tools

› Download the software: www.daikineurope.com/support-and-manuals/software-downloads/air-conditioning/

Benefits for the installer

Whatever the installation requirements or restrictions, Seasonal Smart will be able to meet them thanks to:

› R-22/R-407C replacement technology
› Wide operation range in cooling (down to -15°C) to suit even computer room applications
› Wide operation range in heating (down to -20°C) to be able to deliver heating in the most severe winters.
› Long pipe runs up to 75m
› Easy to install discretely against the wall thanks to the limited depth of the unit
› Wide range of indoor units available

Benefits for the consultant

› Market leader in terms of Seasonal efficiency. The unit operates most efficient throughout the whole summer and winter.
› R-22/R-407C replacement technology : delivering major energy savings, rapid payback and cost-effective upgrade solution with minimal downtime
› This system has been optimized to perform well in the most severe conditions.
› Wide range of indoor units available to suit buildings with or without false ceilings
› Control solutions available for all needs: from individualised unit control to centralised management via touch-screen options and code based controllers

Benefits for the end user

› Market leader in terms of seasonal efficiency which reduces the electricity bill to a minimum all year round
› Optimal sound and airflow distribution so neighbours are not disturbed
› Wide range of stylish, comfortable and silent indoor units available
› Possibility to integrate the unit into a Building Management system
› Reliable system in all weather conditions

FCQG-F/FCQHG-F/FXFQ-A

Round flow cassette



Unique functions that help saving costs

› Daikin was the first to launch a cassette using the roundflow principle with sensors* and a unique auto-cleaning panel*.

... Energy efficient as no other

› The auto-cleaning panel* means:
- Running costs are reduced by 50% compared with standard solutions thanks to automatic daily filter cleaning
- Less time is required to maintain the filter: dust can easily be removed with a vacuum cleaner without opening the unit

› Thanks to the presence and floor sensors* the unit changes its setpoint or switches off completely, if there are no people present in the room, resulting in energy savings of up to 27%.

… And improved comfort


› 360° air flow discharge pattern
› The presence sensor* directs the air away from anyone detected in the room
› The floor sensor* detects the average floor temperature and ensure an even temperature distribution between the ceiling and the floor. Cold feet are history!

Flexible installation

› Flaps can be individually controlled or closed using the wired remote control, to suit room configuration.
Optional closure kits are also available.

References

Reference Wolverhampton, UK
Running costs were reduced with up to 50% compared to standard solutions thanks to daily filter cleaning.



Cumulative energy comparison over 12 months

Why choose Round flow cassette?

- 360° air discharge for optimum efficiency and comfort in shops, offices and restaurants
- Unique auto-cleaning panel

Marketing tools

› Visit the website: www.daikineurope.com/minisite/round-flow-cassette/

Benefits for the installer

› Product with unique functions in the market
› Less time needed on site for maintenance
› Use the controller to individually open or close any of the four flaps to easily adapt to a changing room layout
› Easy set-up of the sensor option to improve comfort and save energy.

Benefits for the consultant

› Product with unique functions in the market
› Designed for use in all types and sizes of commercial offices and retail environments
› Ideal product to improve BREEAM score/EPDB in combination with Sky Air Seasonal Smart or VRV IV heat pump units.

Benefits for the end user

› Designed for use in all types and sizes of commercial offices and retail environments
› Perfect environment conditions: no more cold draughts or cold feet
› Save up to 50% on running costs with the auto-cleaning panel, which also facilitates maintenance
› Save up to 27% on your energy bill thanks to the sensor option
› Flexible usage of space thanks to individual flap control.


* available as an option

ROUND FLOW

Round flow cassette


360° air discharge for optimum efficiency and comfort

- Combination with split outdoor units is ideal for smaller applications such as retail or residential applications
- Daily automatic filter cleaning results in higher efficiency & comfort and lower maintenance costs.
- Two optional intelligent sensors improve energy efficiency and comfort.
- Individual flap control. Flexibility to suit every room layout without changing the location of the unit!





- Lowest installation height in the market: 204mm for class 71
- Modern style decoration panel is available in 3 different variations: white (RAL9010) with grey louvers, full white (RAL9010) or auto cleaning panel
- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required
- Standard drain pump with 850mm lift increases flexibility and installation speed





FCQG35-50-60F

RXS-L3

BRC1E52A-B, BRC7FA532F

- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FCQG + RXS	*35F + 35L3	50F + 50L	60F + 60L
Cooling capacity	Min./Nom./Max.			kW	-/3.4/-	1.7/5.0/5.3	1.7/5.7/5.7
Heating capacity	Min./Nom./Max.			kW	-/4.2/-	1.7/6.00/6.0	1.7/7.0/7.0
Power input	Cooling	Nom.		kW	0.95	1.410	1.640
	Heating	Nom.		kW	1.2	1.620	1.990
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	A++	
		Pdesign		kW	3.40	5.00	5.70
		SEER			6.35	6.48	6.22
		Annual energy consumption		kWh	187	270	321
	Heating (Average climate)	Energy label			A++	A++	A+
		Pdesign		kW	3.32	4.36	4.71
		SCOP			4.9	4.29	4.00
		Annual energy consumption		kWh	949	1,426	1,646
Nominal efficiency	EER				3.58	3.55	3.48
	COP				3.5	3.70	3.52
	Annual energy consumption			kWh	475	705	820
	Energy label	Cooling			A	A	A
		Heating			B	A	B

Indoor unit				FCQG	35F	50F	60F
Dimensions	Unit	HeightxWidthxDepth		mm	204x840x840		
Weight	Unit			kg	18	19	
Decoration panel	Model				BYCQ140D7W1 / BYCQ140D7W1W / BYCQ140D7GW1		
	Colour				Pure White (RAL 9010)		
	Dimensions	HeightxWidthxDepth		mm	50x950x950 / 50x950x950 / 130x950x950		
	Weight			kg	5.4 / 5.4 / 10.3		
Air filter	Type				Resin net with mold resistance		
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	12.5/10.6/8.7	12.6/10.7/8.7	13.6/11.2/8.7
	Heating	High/Nom./Low		m^3/min	12.5/10.6/8.7	12.6/10.7/8.7	13.6/11.2/8.7
Sound power level	Cooling			dBA	49		51
	Heating			dBA	49		51
Sound pressure level	Cooling	High/Nom./Low		dBA	31/29/27		33/31/28
	Heating	High/Nom./Low		dBA	31/29/27		33/31/28
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Control systems	Infrared remote control				BRC7FA532F		
	Wired remote control				BRC1D52 / BRC1E52A/B		

Outdoor unit				RXS	*35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285	735x825x300	
Weight	Unit			kg	31.5	47	48
Sound power level	Cooling			dBA	61	62	
	Heating			dBA	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-	48/44	49/46
	Heating	High/Low		dBA	-/-	48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18	-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / - / 2,087.5	R-410A / 1.7 / 2,087.5	R-410A / 1.5 / 2,087.5
	Charge			TCO_2Eq	-	3.5	3.1
Piping connections	Liquid	OD		mm	6.35	6	6.35
	Gas	OD		mm	9.52	12.70	
	Piping length	OU - IU	Max.	m	-	30	
	Additional refrigerant charge			kg/m	-	0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-	20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-230-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-	-	


*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Round flow cassette

360° air discharge for optimum efficiency and comfort


- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- Daily automatic filter cleaning results in higher efficiency & comfort and lower maintenance costs.
- Two optional intelligent sensors improve energy efficiency and comfort.



- Individual flap control. Flexibility to suit every room layout without changing the location of the unit!



- Lowest installation height in the market: 204mm for class 71
- Modern style decoration panel is available in 3 different variations: white (RAL9010) with grey louvers, full white (RAL9010) or auto cleaning panel
- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required
- Standard drain pump with 850mm lift increases flexibility and installation speed



- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FCQG + RZQG	71F + 71L9V1	100F + 100L9V1	125F + 125L9V1	140F + 140L9V1	71F + 71L8Y1	100F + 100L8Y1	125F + 125L8Y1	140F + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	2.01	2.45	3.22	-	2.01	2.45	3.22	4.17
	Heating	Nom.		kW	1.89	2.60	3.72	-	1.89	2.60	3.72	4.30
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A+	-	A++		A+	-
		Pdesign		kW	6.80	9.50	12.00	-	6.80	9.50	12.00	-
		SEER			6.80		6.00	-	6.80		6.00	-
		Annual energy consumption		kWh	350	488.971	700	-	350	489	700	-
	Heating (Average climate)	Energy label			A+	A++	A+	-	A+	A++	A+	-
		Pdesign		kW	6.33	11.30	12.66	-	6.33	11.30	12.66	-
		SCOP			4.20	4.61	4.10	-	4.20	4.61	4.10	-
		Annual energy consumption		kWh	2,110	3,431.67	4,322.927	-	2,110	3,432	4,323	-
Nominal efficiency	EER				3.39	3.87	3.73	3.21	3.39	3.87	3.73	3.21
	COP				3.97	4.15	3.63	3.61	3.97	4.15	3.63	3.61
	Annual energy consumption			kWh	1,005	1,225	1,610	2,085	1,005	1,225	1,610	2,085
	Energy label	Cooling			A			-	A			-
		Heating			A			-	A			-

Indoor unit				FCQG	71F	100F	125F	140F
Dimensions	Unit	HeightxWidthxDepth		mm	204x840x840	246x840x840		
Weight	Unit			kg	21	24		
Decoration panel	Model				BYCQ140D7W1 / BYCQ140D7W1W / BYCQ140D7GW1			
	Colour				Pure White (RAL 9010)			
	Dimensions	HeightxWidthxDepth		mm	50x950x950			
	Weight			kg	5.4 / 5.4 / 10.3			
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	15.0/12.1/9.1	22.8/17.6/12.4	26.0/19.2/12.4	
	Heating	High/Nom./Low		m^3/min	15.0/12.1/9.1	22.8/17.6/12.4	26.0/19.2/12.4	
Sound power level	Cooling			dBA	51	54	58	
	Heating			dBA	51	54	58	
Sound pressure level	Cooling	High/Nom./Low		dBA	33/31/28	37/33/29	41/35/29	
	Heating	High/Nom./Low		dBA	33/31/28	37/33/29	41/35/29	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				BRC7FA532F			
	Wired remote control				BRC1D52 / BRC1E52A/B			

Outdoor unit				RZQG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320			990x940x320	1,430x940x320		
Weight	Unit			kg	77	99			80	101		
Sound power level	Cooling			dBA	64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.		dBA	48	50	51	52	48	50	51	52
	Heating	Nom.		dBA	50	52	53		50	52	53	
	Night quiet mode	Level 1		dBA	43	45			43	45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50							
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5							
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5			R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		
	Charge			TCO_2Eq	6.1	8.4			6.1	8.4		
Piping connections	Liquid	OD		mm	9.52							
	Gas	OD		mm	15.9							
	Piping length	OU - IU	Max.	m	50	75			50	75		
		System	Equivalent	m	70	90			70	90		
			Chargeless	m	30							
	Additional refrigerant charge			kg/m	See installation manual							
	Level difference	IU - OU	Max.	m	30.0							
		IU - IU	Max.	m	0.5							
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A	-				16	20	25	

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (3) The BYCQ140D7W1W has white insulations. Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140D7W1W decoration panel in environments exposed to concentrations of dirt. (4) BYCQ140D7W1: pure white standard panel with grey louvers; BYCQ140D7W1W: pure white standard panel with white louvers; BYCQ140D7GW1: pure white auto cleaning panel.

ROUND FLOW

Seasonal Classic

Round flow cassette

360° air discharge for optimum efficiency and comfort

› Combination with Seasonal Classic ensures good value for money for all types of commercial applications (see pg. 157)



FCQG100-125-140F



RZQG140L9V1



BRC1E52A, BRC7FA532F

Efficiency data				FCQG + RZQSG	71F + 71L3V1	100F + 100L9V1	125F + 125L9V1	140F + 140L9V1	100F + 100L8Y1	125F + 125L8Y1	140F + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	2.12	2.88	3.74	4.45	2.88	3.74	4.45
	Heating	Nom.		kW	2.08	3.05	3.96	4.54	3.05	3.96	4.54
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A	-	A++	A	-
		Pdesign		kW	6.80	9.50	12.00	-	9.50	12.00	-
		SEER			6.10	6.50	5.30	-	6.50	5.30	-
		Annual energy consumption		kWh	390	511.538	792.453	-	512	792	-
	Heating (Average climate)	Energy label			A+			-	A+		-
		Pdesign		kW	6.33	7.60	8.03	-	7.60	8.03	-
		SCOP			4.10		4.01	-	4.10	4.01	-
		Annual energy consumption		kWh	2,162	2,595.122	2,803.491	-	2,595	2,803	-
Nominal efficiency	EER				3.21	3.30	3.21	3.01	3.30	3.21	3.01
	COP				3.61	3.54	3.41		3.54	3.41	
	Annual energy consumption			kWh	1,060	1,440	1,870	2,225	1,440	1,870	2,225
	Energy label	Cooling			A			-	A		
		Heating			A		B	-	A		B

Indoor unit				FCQG	71F	100F	125F	140F
Dimensions	Unit	HeightxWidthxDepth		mm	204x840x840	246x840x840		
Weight	Unit			kg	21	24		
Decoration panel	Model				BYCQ140D7W1 / BYCQ140D7W1W / BYCQ140D7GW1			
	Colour				Pure White (RAL 9010)			
	Dimensions	HeightxWidthxDepth		mm	50x950x950			
	Weight			kg	5.4 / 5.4 / 10.3			
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	15.0/12.1/9.1	22.8/17.6/12.4	26.0/19.2/12.4	
	Heating	High/Nom./Low		m^3/min	15.0/12.1/9.1	22.8/17.6/12.4	26.0/19.2/12.4	
Sound power level	Cooling			dBA	51	54	58	
	Heating			dBA	51	54	58	
Sound pressure level	Cooling	High/Nom./Low		dBA	33/31/28	37/33/29	41/35/29	
	Heating	High/Nom./Low		dBA	33/31/28	37/33/29	41/35/29	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				BRC7FA532F			
	Wired remote control				BRC1D52 / BRC1E52A/B			


Outdoor unit				RZQSG	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	77		99	82		101
Sound power level	Cooling			dBA	65	70		69		70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	51	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	50						
		System	Equivalent	m	70						
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15	30.0					
		IU - IU	Max.	m	0.5						
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			20		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (3) The BYCQ140D7W1W has white insulations. Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140D7W1W decoration panel in environments exposed to concentrations of dirt. (4) BYCQ140D7W1: pure white standard panel with grey louvers; BYCQ140D7W1W: pure white standard panel with white louvers; BYCQ140D7GW1: pure white auto cleaning panel.

High COP, round flow cassette

360° air discharge for optimum efficiency and comfort

- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- High COP cassette ensures top performance, great savings in energy consumption and a comfortable environment for commercial applications
- Daily automatic filter cleaning results in higher efficiency & comfort and lower maintenance costs.
- Two optional intelligent sensors improve energy efficiency and comfort.




presence sensor floor sensor

- Individual flap control. Flexibility to suit every room layout without changing the location of the unit!



- Lowest installation height in the market: 204mm for class 71
- Modern style decoration panel is available in 3 different variations: white (RAL9010) with grey louvers, full white (RAL9010) or auto cleaning panel
- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required
- Standard drain pump with 850mm lift increases flexibility and installation speed



- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FCQHG + RZQG	71F + 71L9V1	100F + 100L9V1	125F + 125L9V1	140F + 140L9V1	71F + 71L8Y1	100F + 100L8Y1	125F + 125L8Y1	140F + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	1.66	2.15	3.00	4.00	1.66	2.15	3.00	4.00
	Heating	Nom.		kW	1.56	2.16	3.07	3.77	1.56	2.16	3.07	3.77
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++			-	A++			-
		Pdesign		kW	6.80	9.50	12.00	-	6.80	9.50	12.00	-
		SEER			7.00		6.61	-	7.00		6.61	-
		Annual energy consumption		kWh	340	475	635.401	-	340	475	635	-
	Heating (Average climate)	Energy label			A+	A++		-	A+	A++		-
		Pdesign		kW	7.60	11.30	12.66	-	7.60	11.30	12.66	-
		SCOP			4.54	4.80	4.63	-	4.54	4.80	4.63	-
		Annual energy consumption		kWh	2,343	3,295.833	3,829	-	2,343	3,296	3,829	-
Nominal efficiency	EER				4.09	4.42	4.00	3.35	4.09	4.42	4.00	3.35
	COP				4.80	4.99	4.40	4.12	4.80	4.99	4.40	4.12
	Annual energy consumption			kWh	830	1,075	1,500	2,000	830	1,075	1,500	2,000
	Energy label	Cooling			A			-	A			-
		Heating			A			-	A			-

Indoor unit				FCQHG	71F	100F	125F	140F
Dimensions	Unit	HeightxWidthxDepth		mm	288x840x840			
Weight	Unit			kg	25	26		
Decoration panel	Model				BYCQ140D7W1 / BYCQ140D7W1W / BYCQ140D7GW1			
	Colour				Pure White (RAL 9010)			
	Dimensions	HeightxWidthxDepth		mm	50x950x950			
	Weight			kg	5.4 / 5.4 / 10.3			
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	21.2/16.7/12.2	32.3/25.7/19.0	33.5/26.7/19.9	33.5/27.3/21.1
	Heating	High/Nom./Low		m^3/min	21.2/16.7/12.2	32.3/25.7/19.0	33.5/26.7/19.9	33.5/27.3/21.1
Sound power level	Cooling			dBA	53	61		
	Heating			dBA	53	61		
Sound pressure level	Cooling	High/Nom./Low		dBA	36/33/29	44/39/33	45/40/35	45/41/37
	Heating	High/Nom./Low		dBA	36/33/29	44/39/33	45/40/35	45/41/37
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				BRC7FA532F			
	Wired remote control				BRC1D52 / BRC1E52A/B			

Outdoor unit				RZQG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320			990x940x320	1,430x940x320		
Weight	Unit			kg	77	99			80	101		
Sound power level	Cooling			dBA	64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.		dBA	48	50	51	52	48	50	51	52
	Heating	Nom.		dBA	50	52	53		50	52	53	
	Night quiet mode	Level 1		dBA	43	45			43	45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50							
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5							
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5			R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		
	Charge			TCO_2Eq	6.1	8.4			6.1	8.4		
Piping connections	Liquid	OD		mm	9.52							
	Gas	OD		mm	15.9							
	Piping length	OU - IU	Max.	m	50	75			50	75		
		System	Equivalent	m	70	90			70	90		
			Chargeless	m	30							
	Additional refrigerant charge			kg/m	See installation manual							
	Level difference	IU - OU	Max.	m	30.0							
		IU - IU	Max.	m	0.5							
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A	-				16	25		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (3) The BYCQ140D7W1W has white insulations. Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140D7W1W decoration panel in environments exposed to concentrations of dirt. (4) BYCQ140D7W1: pure white standard panel with grey louvers; BYCQ140D7W1W: pure white standard panel with white louvers; BYCQ140D7GW1: pure white auto cleaning panel.

ROUND FLOW

Seasonal Classic

High COP, round flow cassette

360° air discharge for optimum efficiency and comfort

› Combination with Seasonal Classic ensures good value for money for all types of commercial applications (see pg. 157)



FCQHG71-100-125-140F



RZQG140L9V1/L(8)Y1



BRC1E52A-B, BRC7FA532F

Efficiency data				FCQHG + RZQSG	71F + 71L3V1	100F + 100L9V1	125F + 125L9V1	140F + 140L9V1	100F + 100L8Y1	125F + 125L8Y1	140F + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	1.94	2.57	3.71	4.17	2.57	3.71	4.17
	Heating	Nom.		kW	1.83	2.51	3.60	4.29	2.51	3.60	4.29
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A	-	A++	A	-
		Pdesign		kW	6.80	9.50	12.00	-	9.50	12.00	-
		SEER			6.50	6.70	5.40	-	6.70	5.40	-
		Annual energy consumption		kWh	366	496.269	777.778	-	496	778	-
	Heating (Average climate)	Energy label			A+			-	A+		-
		Pdesign		kW	7.60	8.03		-	8.03		-
		SCOP			4.15	4.30	4.10	-	4.30	4.10	-
		Annual energy consumption		kWh	2,563	2,614.419	2,741	-	2,614	2,741	-
Nominal efficiency	EER				3.50	3.70	3.23	3.21	3.70	3.23	3.21
	COP				4.10	4.30	3.75	3.61	4.30	3.75	3.61
	Annual energy consumption			kWh	970	1,285	1,855	2,085	1,285	1,855	2,085
	Energy label	Cooling			A			-	A		-
		Heating			A			-	A		-

Indoor unit				FCQHG	71F	100F	125F	140F
Dimensions	Unit	HeightxWidthxDepth		mm	288x840x840			
Weight	Unit			kg	25	26		
Decoration panel	Model				BYCQ140D7W1 / BYCQ140D7W1W / BYCQ140D7GW1			
	Colour				Pure White (RAL 9010)			
	Dimensions	HeightxWidthxDepth		mm	50x950x950			
	Weight			kg	5.4 / 5.4 / 10.3			
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	21.2/16.7/12.2	32.3/25.7/19.0	33.5/26.7/19.9	33.5/27.3/21.1
	Heating	High/Nom./Low		m^3/min	21.2/16.7/12.2	32.3/25.7/19.0	33.5/26.7/19.9	33.5/27.3/21.1
Sound power level	Cooling			dBA	53	61		
	Heating			dBA	53	61		
Sound pressure level	Cooling	High/Nom./Low		dBA	36/33/29	44/39/33	45/40/35	45/41/37
	Heating	High/Nom./Low		dBA	36/33/29	44/39/33	45/40/35	45/41/37
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				BRC7FA532F			
	Wired remote control				BRC1D52 / BRC1E52A/B			

Outdoor unit				RZQSG	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	77		99	82		101
Sound power level	Cooling			dBA	65	70		69		70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	51	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	50						
		System	Equivalent	m	70						
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15	30.0					
		IU - IU	Max.	m	0.5						
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			20		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (3) The BYCQ140D7W1W has white insulations. Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140D7W1W decoration panel in environments exposed to concentrations of dirt. (4) BYCQ140D7W1: pure white standard panel with grey louvers; BYCQ140D7W1W: pure white standard panel with white louvers; BYCQ140D7GW1: pure white auto cleaning panel.

ARGUE CARDS

FFQ-C / FXZQ-A

Fully Flat Cassette

Design & Genius in one



› Why choose fully flat cassette?

- Unique design in the market that integrates fully flat into the ceiling

Benefits for the installer

› Unique product in the market!
› Most silent unit
› The user-friendly remote control, available in several languages, enables the easy set-up of sensor option and control of the individual flap position
› Meeting European design taste.

Benefits for the consultant

› Unique product in the market!
› Blends seamlessly in any modern office interior design
› Ideal product to improve BREEAM score/EPDB in combination with Sky Air Seasonal Smart or VRV IV heat pump units.

Benefits for the end user

› Engineering excellence and unique design in one
› Most silent unit
› Perfect working conditions: no more cold draughts or cold feet
› Save up to 27% on your energy bill thanks to the optional sensors
› Flexible usage of space thanks to individual flap control
› User-friendly remote control, available in several languages.

Unique design

› Designed by German design office to fully meet the European taste.
› Fully flat into the ceiling, leaving only 8mm.
› Fully integrated in the one ceiling tile, enabling lights, speakers and sprinklers to be installed in adjoining ceiling tiles.
› Decoration panel available in 2 colours (white and white-silver).

Differentiating in technology

Optional presence sensor

› When the room is empty, it can adjust the set temperature or switch off the unit – saving energy.
› When people are detected, the direction of the airflow is adapted to avoid cold draughts being directed towards occupants.

Optional floor sensor

› Detects the temperature difference and re-directs the airflow to ensure even temperature distribution.

Top efficiency

› Seasonal labels up to A++*
› When the room is empty, the sensor option can adjust the set temperature or switch off the unit – saving up to 27% energy.
› Individual flap control: easily control one or more flaps via the wired remote controller (BRC1E52) when rearranging the room. When fully closing or blocking the flaps, the option "Sealing member of air discharge outlet" is needed.

* for FFQ25,35C in combination with RXS25,35L3

Other features

› Most silent cassette in the market (25dBA), important for office applications.

Marketing tools

› Download the Seasonal Calculator software: www.daikineurope.com/support-and-manuals/software-downloads/air-conditioning/








Fully flat cassette

Unique design in the market that integrates fully flat into the ceiling

› Combination with split outdoor units is ideal for smaller applications such as retail or residential applications
› Remarkable blend of iconic design and engineering excellence
› Two optional intelligent sensors improve energy efficiency and comfort.




presence sensor floor sensor

› Refurbishing the room? Flexibility to suit every room layout without changing the location of the unit!



› Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
› Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required



FFQ-C



RXS-L3



BRC1E52A-B, BRC7F530W_S

› No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FFQ + RXS	*25C + 25L3	*35C + 35L3	50C + 50L	60C + 60L
Cooling capacity	Min./Nom./Max.			kW	-/2.5/-	-/3.4/-	1.7/5.0/5.3	1.7/5.7/6.5
Heating capacity	Min./Nom./Max.			kW	-/3.2/-	-/4.2/-	1.7/5.8/6.0	1.7/7.0/8.0
Power input	Cooling	Nom.		kW	0.56	0.92	1.560	1.890
	Heating	Nom.		kW	0.82	1.2	1.660	2.050
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A+	
		Pdesign		kW	2.50	3.4	5.00	5.70
		SEER			6.11	6.32	5.93	5.71
		Annual energy consumption		kWh	143	188	295	349
	Heating (Average climate)	Energy label			A+		A	A+
		Pdesign		kW	2.31	3.1	3.84	3.96
		SCOP			4.24	4.1	3.90	4.04
		Annual energy consumption		kWh	763	1,059	1,378	1,373
Nominal efficiency	EER				4.46	3.7	3.21	3.02
	COP				3.9	3.5	3.49	3.41
	Annual energy consumption			kWh	280	459	780	945
	Energy label	Cooling			A		A	B
		Heating			A	B	B	B

Indoor unit				FFQ	25C	35C	50C	60C
Dimensions	Unit	HeightxWidthxDepth		mm	260x575x575			
Weight	Unit			kg	16		17.5	
Decoration panel	Model				BYFQ60CW / BYFQ60CS / BYFQ60B3W1			
	Colour				White (N9.5) / White (N9.5) + Silver / White (RAL9010)			
	Dimensions	HeightxWidthxDepth		mm	46x620x620 / 46x620x620 / 55x700x700			
	Weight			kg	2.8 / 2.8 / 2.7			
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	9/8/6.5	10/8.5/6.5	12/10/7.5	14.5/12.5/9.5
	Heating	High/Nom./Low		m^3/min	9/8/6.5	10/8.5/6.5	12/10/7.5	14.5/12.5/9.5
Sound power level	Cooling			dBA	48	51	56	60
Sound pressure level	Cooling	High/Nom./Low		dBA	31/28.5/25	34/30.5/25	39/34/27	43/40/32
	Heating	High/Nom./Low		dBA	31/28.5/25	34/30.5/25	39/34/27	43/40/32
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Infrared remote control				BRC7EB530 (standard panel) / BRC7F530W (white panel) / BRC7F530S (grey panel)			
	Wired remote control				BRC1D52 / BRC1E52A/B			

Outdoor unit				RXS	*25L3	*35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300	
Weight	Unit			kg	31.5		47	48
Sound power level	Cooling			dBA	59	61	62	
	Heating			dBA	59	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-		48/44	49/46
	Heating	High/Low		dBA	-/-		48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18		-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / - / 2,087.5		R-410A / 1.7 / 2,087.5	R-410A / 1.5 / 2,087.5
	Charge			TCO_2Eq	-		3.5	3.1
Piping connections	Liquid	OD		mm	6.35		6.35	
	Gas	OD		mm	9.52		12.7	
	Piping length	OU - IU	Max.	m	-		30	
	Additional refrigerant charge			kg/m	-		0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-		20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 / 220-230-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-		-	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Concealed ceiling unit with medium ESP

Optimum comfort guaranteed no matter the length of duct work or type of grilles

- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- Top efficiency in the market
- Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, whatever the length of duct, making installation easier and guaranteeing comfort. Moreover, the ESP can be changed via the wired remote control to optimize the supply air volume
- Compact unit, all units can easily be mounted in a ceiling void of only 285mm
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Low sound levels
- Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths
- Reduced energy consumption thanks to specially developed DC fan motor
- Flexible installation, as the air suction direction can be altered from rear to bottom suction
- Standard built-in drain pump increases flexibility and installation speed
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FBQ + RZQG	*71D + 71L9V1	*100D + 100L9V1	*125D + 125L9V1	*140D + 140L9V1	*71D + 71L8Y1	*100D + 100L8Y1	*125D + 125L8Y1	*140D + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	1.93	2.41	3.13	4.00	1.93	2.41	3.13	4.00
	Heating	Nom.		kW	1.89	2.55	3.52	4.29	1.89	2.55	3.52	4.29
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	A+		-	A++	A+		-
		Pdesign		kW	6.80	9.50	12.00	-	6.80	9.50	12.00	-
		SEER			6.16	5.87	5.83	-	6.16	5.87	5.83	-
		Annual energy consumption		kWh	386	566	720	-	386	566	720	-
	Heating (Average climate)	Energy label			A+	A++	A+	-	A+	A++	A+	-
		Pdesign		kW	6.00	11.30	12.70	-	6.00	11.30	12.70	-
		SCOP			4.35	4.78	4.37	-	4.35	4.78	4.37	-
		Annual energy consumption		kWh	1,931	3,310	4,069	-	1,931	3,310	4,069	-
Nominal efficiency	EER				3.53	3.94	3.83	3.35	3.53	3.94	3.83	3.35
	COP				3.96	4.24	3.83	3.61	3.96	4.24	3.83	3.61
	Annual energy consumption			kWh	963	1,206	1,567	2,000	963	1,206	1,567	2,000
	Energy label	Cooling			A			-	A			-
		Heating			A			-	A			-

Indoor unit				FBQ	*71D	*100D	*125D	*140D
Dimensions	Unit	HeightxWidthxDepth		mm	245x1,000x800	245x1,400x800		
Weight	Unit			kg	36.30	47		
Fan - Air flow rate	Cooling	High/Low		m^3/min	18/12.50	29/23	34/25	
Fan - External static pressure	High/Nom./Maximum available/High			Pa	150/30/-	150/40/-	150/50/-	
Sound power level	Cooling			dBA	57	61	66	
Sound pressure level	Cooling	High		dBA	37	38	40	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240			

Outdoor unit				RZQG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320			990x940x320	1,430x940x320		
Weight	Unit			kg	77	99			80	101		
Sound power level	Cooling			dBA	64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.		dBA	48	50	51	52	48	50	51	52
	Heating	Nom.		dBA	50	52	53		50	52	53	
	Night quiet mode	Level 1		dBA	43	45			43	45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50							
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5							
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5			R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		
	Charge			TCO_2Eq	6.1	8.4			6.1	8.4		
Piping connections	Liquid	OD		mm	9.52							
	Gas	OD		mm	15.9							
	Piping length	OU - IU	Max.	m	50	75			50	75		
		System	Equivalent	m	70	90			70	90		
			Chargeless	m	30							
	Additional refrigerant charge			kg/m	See installation manual							
	Level difference	IU - OU	Max.	m	30.0							
		IU - IU	Max.	m	0.5							
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A	-				16	25		

*Note: blue cells contain preliminary data


(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Seasonal Classic

Concealed ceiling unit with medium ESP

Optimum comfort guaranteed no matter the length of duct work or type of grilles

› Combination with Seasonal Classic ensures good value for money for all types of commercial applications (see pg. 157)



FBQ100-140D



RZQG140L9V1/L(8)Y1



BRC1E52A-B,BRC4C65

Efficiency data				FBQ + RZQSG	*71D + 71L3V1	*100D + 100L9V1	*125D + 125L9V1	*140D + 140L9V1	*100D + 100L8Y1	*125D + 125L8Y1	*140D + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	2.06	2.84	3.72	4.38	2.84	3.72	4.38
	Heating	Nom.		kW	1.97	2.94	3.85	4.55	2.94	3.85	4.55
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+	A		-	A		-
		Pdesign		kW	6.80	9.50	12.00	-	9.50	12.00	-
		SEER			5.84	5.57	5.22	-	5.57	5.22	-
		Annual energy consumption		kWh	408	597	805	-	597	805	-
	Heating (Average climate)	Energy label			A+		A	-	A+	A	-
		Pdesign		kW	6.00	11.30	12.70	-	11.30	12.70	-
		SCOP			4.10	4.15	4.05	-	4.15	4.05	-
		Annual energy consumption		kWh	2,049	3,812	4,390	-	3,812	4,390	-
Nominal efficiency	EER				3.30	3.35	3.23	3.06	3.35	3.23	3.06
	COP				3.81	3.67	3.51	3.41	3.67	3.51	3.41
	Annual energy consumption			kWh	1,030	1,418	1,858	2,190	1,418	1,858	2,190
	Energy label	Cooling			A			-	A		-
		Heating			A		B	-	A	B	-

Indoor unit				FBQ	*71D	*100D	*125D	*140D
Dimensions	Unit	HeightxWidthxDepth		mm	245x1,000x800	245x1,400x800		
Weight	Unit			kg	36.30	47		
Fan - Air flow rate	Cooling	High/Low		m^3/min	18/12.50	29/23	34/25	
Fan - External static pressure	High/Nom./High			Pa	150/30/-	150/40/-	150/50/-	
Sound power level	Cooling			dBA	57	61	66	
Sound pressure level	Cooling	High		dBA	37	38	40	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240			

Outdoor unit				RZQSG	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	77		99	82		101
Sound power level	Cooling			dBA	65	70		69		70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	51	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	50						
		System	Equivalent	m	70						
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15	30.0					
		IU - IU	Max.	m	0.5						
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			20		

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Concealed ceiling unit with medium ESP

Optimum comfort guaranteed no matter the length of duct work or type of grilles

- Combination with split outdoor units is ideal for smaller applications such as retail or residential applications
- Top efficiency in the market
- Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, whatever the length of duct, making installation easier and guaranteeing comfort. Moreover, the ESP can be changed via the wired remote control to optimize the supply air volume
- Slimmest unit in class, only 245mm
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Low sound levels
- Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths
- Reduced energy consumption thanks to specially developed DC fan motor
- Flexible installation, as the air suction direction can be altered from rear to bottom suction



- Standard built-in drain pump increases flexibility and installation speed
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FBQ + RXS	*35D + 35L3	*50D + 50L	*60D + 60L
Cooling capacity	Nom.			kW	3.40	-	
Heating capacity	Nom.			kW	4.00	-	
Power input	Cooling	Nom.		kW	1.060	-	
	Heating	Nom.		kW	1.110	-	
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+	-	
		Pdesign		kW	3.4	-	
		SEER			5.97	-	
		Annual energy consumption		kWh	199	-	
	Heating (Average climate)	Energy label			A+	-	
		Pdesign		kW	2.9	-	
		SCOP			3.93	-	
		Annual energy consumption		kWh	1,033	-	
Nominal efficiency	EER				3.21	-	
	COP				3.60	-	
	Annual energy consumption			kWh	530	-	
	Energy label	Cooling			A	-	
		Heating			B	-	

Indoor unit				FBQ	*35D	*50D	*60D
Dimensions	Unit	HeightxWidthxDepth		mm	245x700x800		245x1,000x800
Weight	Unit			kg	27.70		36.30
Fan - Air flow rate	Cooling	High/Low		m^3/min	15/11		18/12.50
Fan - External static pressure	High/Nom.			Pa	150/30		
Sound power level	Cooling			dBA	60		57
Sound pressure level	Cooling	High		dBA	37		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220	1~ / 50/60 / 220-240	

Outdoor unit				RXS	*35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285	735x825x300	
Weight	Unit			kg	31.5	47	48
Sound power level	Cooling			dBA	61	62	
	Heating			dBA	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-	48/44	49/46
	Heating	High/Low		dBA	-/-	48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18	-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / - / 2,087.5	R-410A / 1.7 / 2,087.5	R-410A / 1.5 / 2,087.5
	Charge			TCO_2Eq	-	3.5	3.1
Piping connections	Liquid	OD		mm	6.35	6.35	
	Gas	OD		mm	9.5	12.7	
	Piping length	OU - IU	Max.	m	-	30	
	Additional refrigerant charge			kg/m	-	0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-	20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-230-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-	-	


*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Small concealed ceiling unit

Designed for hotel applications

- Compact unit (230mm high & 652mm deep), can easily be mounted in narrow ceiling voids
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Whisper quiet operation: down to 28dBA sound pressure level
- Flexible installation, as the air suction direction can be altered from rear to bottom suction
- For easy mounting, the drain pan can be located to the left or right of the unit



FDBQ25B



BRC1E52A/B

Indoor unit				**FDBQ**	**25B**
Dimensions	Unit	HeightxWidthxDepth		mm	230x652x502
Weight	Unit			kg	17.0
Air filter	Type				Resin net with mold resistance
Fan - Air flow rate	Cooling	High/Low		m^3/min	6.50/5.20
	Heating	High/Low		m^3/min	6.95/5.20
Sound power level	Cooling			dBA	55
	Heating			dBA	55
Sound pressure level	Cooling	High/Low		dBA	35.0/28.0
	Heating	High/Low		dBA	35.0/29.0
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 230
Control systems	Wired remote control				BRC1D52 / BRC1E52A/B


Outdoor unit					
Dimensions	Unit	HeightxWidthxDepth		mm	only available in multi model application
Weight	Unit			kg	
Sound power level	Cooling			dBA	
Sound pressure level	Cooling	Nom.		dBA	
	Heating	Nom.		dBA	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	
	Heating	Ambient	Min.~Max.	°CWB	
Refrigerant	Type/Charge/GWP			kg	
Piping connections	Liquid	OD		mm	
	Gas	OD		mm	
	Piping length	OU - IU	Max.	m	
	Additional refrigerant charge			kg/m	
	Level difference	IU - OU	Max.	m	
		IU - IU	Max.	m	
Power supply	Phase / Frequency / Voltage			Hz / V	
Current - 50Hz	Maximum fuse amps (MFA)			A	

Seasonal Smart Seasonal Classic

Concealed ceiling unit with high ESP

ESP up to 200, ideal for large sized spaces

- Seasonal Smart ensures the highest quality, Seasonal Classic gives good value for money (see pg. 157 & 167)
- Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, whatever the length of duct, making installation easier and guaranteeing comfort. Moreover, the ESP can be changed via the wired remote control to optimize the supply air volume
- High external static pressure up to 200Pa facilitates using flexible ducts of varying lengths
- Reduced energy consumption thanks to specially developed DC fan motor
- Possibility to change ESP via wired remote control allows optimisation of the supply air volume
- Flexible installation, as the air suction direction can be altered from rear to bottom suction
- Standard built-in drain pump increases flexibility and installation speed
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.



FDQ125C



RZQSG100-125L3/9V1/L(8)Y1



BRC1E52A-B

					Seasonal Smart		Seasonal Classic	
Efficiency data				**FDQ + RZQG/RZQSG**	**125C + 125L9V1**	**125C + 125L8Y1**	**125C + 125L9V1**	**125C + 125L8Y1**
Cooling capacity	Nom.			kW	12.0		12.0	
Heating capacity	Nom.			kW	13.5		13.5	
Power input	Cooling	Nom.		kW	3.20		3.74	
	Heating	Nom.		kW	3.53		3.85	
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+		A	
		Pdesign		kW	12.00		12.00	
		SEER			5.81		5.20	
		Annual energy consumption		kWh	722.892	723	807.692	808
	Heating (Average climate)	Energy label			A+		A	
		Pdesign		kW	12.71		7.60	
		SCOP			4.21		3.90	
		Annual energy consumption		kWh	4,226.603	4,227	2,728.205	2,728
Nominal efficiency	EER				3.75		3.21	
	COP				3.83		3.51	
	Annual energy consumption			kWh	1,600		1,870	
	Energy label	Cooling			A		A	
		Heating			A		B	

Indoor unit				**FDQ**	**125C**
Casing	Colour				Not painted (galvanised)
Dimensions	Unit	HeightxWidthxDepth		mm	300x1,400x700
Required ceiling void >				mm	350
Weight	Unit			kg	45
Decoration panel	Model				BYBS125DJW1
	Colour				White (10Y9/0.5)
	Dimensions	HeightxWidthxDepth		mm	55x1,500x500
	Weight			kg	6.5
Air filter	Type				Resin net with mold resistance
Fan - Air flow rate	Cooling	High/Low		m^3/min	39/28
	Heating	High/Low		m^3/min	39/28
Fan - External static pressure	High/Nom.			Pa	200/50
Sound power level	Cooling			dBA	66
Sound pressure level	Cooling	High/Low		dBA	40/33
	Heating	High/Low		dBA	40/33
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220
Control systems	Infrared remote control				BRC4C65
	Wired remote control				BRC1D52 / BRC1E52A/B


Outdoor unit				**RZQG/RZQSG**	**125L9V1**	**125L8Y1**	**125L9V1**	**125L8Y1**
Dimensions	Unit	HeightxWidthxDepth		mm	1,430x940x320		990x940x320	
Weight	Unit			kg	99	101	77	82
Sound power level	Cooling			dBA	67		70	
Sound pressure level	Cooling	Nom.		dBA	51		54	
	Heating	Nom.		dBA	53		58	
	Night quiet mode	Level 1		dBA	45		49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50		-15~46	
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5		-15~15.5	
Refrigerant	Type/Charge/GWP			kg	R-410A / 4 / 2,087.5		R-410A / 2.9 / 2,087.5	
	Charge			TCO_2Eq	8.4		6.1	
Piping connections	Liquid	OD		mm	9.52			
	Gas	OD		mm	15.9			
	Piping length	OU - IU	Max.	m	75		50	
		System	Equivalent	m	90		70	
			Chargeless	m	30			
	Additional refrigerant charge			kg/m	See installation manual			
	Level difference	IU - OU	Max.	m	30.0			
		IU - IU	Max.	m	0.5			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	3N~ / 50 / 380-415	1~ / 50 / 220-240	3N~ / 50 / 380-415
Current - 50Hz	Maximum fuse amps (MFA)			A	-	25	-	20

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Concealed ceiling unit with high ESP

ESP up to 250, ideal for extra large sized spaces

- High external static pressure up to 250Pa facilitates using flexible ducts of varying lengths
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Up to 26.4kW in heating mode



FDQ-B



RZQ200-250C



BRC1E52A-B

Efficiency data				FDQ + RZQ	200B + 200C	250B + 250C
Cooling capacity	Nom.			kW	20.0	24.1
Heating capacity	Nom.			kW	23.0	26.4
Power input	Cooling	Nom.		kW	6.23	8.58
	Heating	Nom.		kW	6.74	8.22
Nominal efficiency	EER				3.21	2.81
	COP				3.41	3.21
	Annual energy consumption			kWh	3,115	4,290
	Energy label	Cooling/Heating			-/-	

Indoor unit				FDQ	200B	250B
Casing	Colour				Unpainted	
Dimensions	Unit	HeightxWidthxDepth		mm	450x1,400x900	
Required ceiling void >				mm	450	
Weight	Unit			kg	89.0	94.0
Air filter	Type				Resin net with mold resistance	
Fan - Air flow rate	Cooling	Nom.		m^3/min	69.0	89.0
	Heating	Nom.		m^3/min	69.0	89.0
Fan - External static pressure	High/Nom./Low/Maximum available/High			Pa	250/250/250/-	
Sound power level	Cooling			dBA	81	82
Sound pressure level	Cooling	High		dBA	45.0	47.0
	Heating	Low		dBA	45.0	47.0
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 230	
Control systems	Wired remote control				BRC1D52 / BRC1E52A/B	


Outdoor unit				RZQ	200C	250C
Dimensions	Unit	HeightxWidthxDepth		mm	1,680x930x765	
Weight	Unit			kg	183	184
Sound power level	Cooling			dBA	78	
	Heating			dBA	78	
Sound pressure level	Nom.			dBA	57	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5.0~46.0	
	Heating	Ambient	Min.~Max.	°CWB	-15.0~15.0	
Refrigerant	Type/Charge/GWP			kg	R-410A / 8.3 / 2,087.5	R-410A / 9.3 / 2,087.5
	Charge			TCO_2Eq	17.3	19.4
Piping connections	Liquid	OD		mm	9.52	12.7
	Gas	OD		mm	22.2	
	Piping length	OU - IU	Max.	m	100	
	Level difference	IU - OU	Max.	m	-	
Power supply	Phase / Frequency / Voltage			Hz / V	3N~ / 50 / 380-415	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

(1) EER/COP according to Eurovent (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- Ideal for comfortable air flow in wide rooms thanks to Coanda effect: up to 100° discharge angle



- Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily without capacity loss
- Can easily be installed in both new and refurbishment projects
- Can easily be mounted in corners and narrow spaces, as it only needs 30mm lateral service space
- Reduced energy consumption thanks to specially developed DC fan motor and drain pump
- Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FHQ + RZQG	71C + 71L9V1	100C + 100L9V1	125C + 125L9V1	140C + 140L9V1	71C + 71L8Y1	100C + 100L8Y1	125C + 125L8Y1	140C + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	1.78	2.49	3.58	4.05	1.78	2.49	3.58	4.05
	Heating	Nom.		kW	1.82	2.60	3.48	4.27	1.82	2.60	3.48	4.27
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A+	-	A++		A+	-
		Pdesign		kW	6.80	9.50	12.00	-	6.80	9.50	12.00	-
		SEER			6.95	6.11	6.01	-	6.95	6.11	6.01	-
		Annual energy consumption		kWh	342	544	699	-	342	544	699	-
	Heating (Average climate)	Energy label			A+	A++	A+	-	A+	A++	A+	-
		Pdesign		kW	7.60	11.30	14.13	-	7.60	11.30	14.13	-
		SCOP			4.32	4.61	4.23	-	4.32	4.61	4.23	-
		Annual energy consumption		kWh	2,463	3,432	4,677	-	2,463	3,432	4,677	-
Nominal efficiency	EER				3.82	3.81	3.35	3.31	3.82	3.81	3.35	3.31
	COP				4.13	4.15	3.89	3.63	4.13	4.15	3.89	3.63
	Annual energy consumption			kWh	890	1,245	1,790	2,025	890	1,245	1,790	2,025
	Energy label	Cooling			A			-	A			-
		Heating			A			-	A			-

Indoor unit				FHQ	71C	100C	125C	140C
Casing	Colour				Fresh White			
Dimensions	Unit	HeightxWidthxDepth		mm	235x1,270x690	235x1,590x690		
Weight	Unit			kg	32	38		
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	20.5/17/14	28/24/20	31/27/23	34/29/24
	Heating	High/Nom./Low		m^3/min	20.5/17/14	28/24/20	31/27/23	34/29/24
Sound power level	Cooling			dBA	55	60	62	64
	Heating			dBA	55	60	62	64
Sound pressure level	Cooling	High/Nom./Low		dBA	38/36/34	42/38/34	44/41/37	46/42/38
	Heating	High/Nom./Low		dBA	38/36/34	42/38/34	44/41/37	46/42/38
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220			
Control systems	Infrared remote control				BRC7G53			
	Wired remote control				BRC1D52 / BRC1E52A/B			

Outdoor unit				RZQG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320			990x940x320	1,430x940x320		
Weight	Unit			kg	77	99			80	101		
Sound power level	Cooling			dBA	64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.		dBA	48	50	51	52	48	50	51	52
	Heating	Nom.		dBA	50	52	53		50	52	53	
	Night quiet mode	Level 1		dBA	43	45			43	45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50							
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5							
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5			R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		
	Charge			TCO_2Eq	6.1	8.4			6.1	8.4		
Piping connections	Liquid	OD		mm	9.52							
	Gas	OD		mm	15.9							
	Piping length	OU - IU	Max.	m	50	75			50	75		
		System	Equivalent	m	70	90			70	90		
			Chargeless	m	30							
	Additional refrigerant charge			kg/m	See installation manual							
	Level difference	IU - OU	Max.	m	30.0							
		IU - IU	Max.	m	0.5							
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A	-				16	25		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Seasonal Classic

Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

› Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)



FHQ60-71C



RZQSG100-125L3/9V1/L(8)Y1



BRC1E52A-B, BRC7GA53

Efficiency data				FHQ + RZQSG	71C + 71L3V1	100C + 100L9V1	125C + 125L9V1	140C + 140L9V1	100C + 100L8Y1	125C + 125L8Y1	140C + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	1.97	2.96	4.15	4.45	2.96	4.15	4.45
	Heating	Nom.		kW	1.88	2.99	3.73	4.54	2.99	3.73	4.54
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+			-	A+		-
		Pdesign		kW	6.80	9.50	12.00	-	9.50	12.00	-
		SEER			5.61			-	5.61		-
		Annual energy consumption		kWh	424	592.692	748.663	-	593	749	-
	Heating (Average climate)	Energy label			A		A+	-	A	A+	-
		Pdesign		kW	7.60			-	7.60		-
		SCOP			3.90	3.91	4.01	-	3.91	4.01	-
		Annual energy consumption		kWh	2,727	2,721	2,653	-	2,721	2,653	-
Nominal efficiency	EER				3.46	3.21	2.89	3.01	3.21	2.89	3.01
	COP				4.00	3.61	3.62	3.41	3.61	3.62	3.41
	Annual energy consumption			kWh	985	1,480	2,075	2,225	1,480	2,075	2,225
	Energy label	Cooling			A		C	-	A	C	-
		Heating			A			-	A		-

Indoor unit				FHQ	71C	100C	125C	140C
Casing	Colour				Fresh White			
Dimensions	Unit	HeightxWidthxDepth		mm	235x1,270x690	235x1,590x690		
Weight	Unit			kg	32	38		
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	20.5/17/14	28/24/20	31/27/23	34/29/24
	Heating	High/Nom./Low		m^3/min	20.5/17/14	28/24/20	31/27/23	34/29/24
Sound power level	Cooling			dBA	55	60	62	64
	Heating			dBA	55	60	62	64
Sound pressure level	Cooling	High/Nom./Low		dBA	38/36/34	42/38/34	44/41/37	46/42/38
	Heating	High/Nom./Low		dBA	38/36/34	42/38/34	44/41/37	46/42/38
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220			
Control systems	Infrared remote control				BRC7G53			
	Wired remote control				BRC1D52 / BRC1E52A/B			


Outdoor unit				RZQSG	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	77		99	82		101
Sound power level	Cooling			dBA	65	70		69		70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	51	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	50						
		System	Equivalent	m	70						
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15	30.0					
		IU - IU	Max.	m	0.5						
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			20		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

- Combination with split outdoor units is ideal for smaller applications such as retail or residential applications
- Ideal for comfortable air flow in wide rooms thanks to Coanda effect: up to 100° discharge angle



- Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily without capacity loss
- Can easily be installed in both new and refurbishment projects
- Can easily be mounted in corners and narrow spaces, as it only needs 30mm lateral service space
- Reduced energy consumption thanks to specially developed DC fan motor and drain pump
- Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating



FHQ60C

RXS-L3

BRC1E52A-B, BRC7GA53

- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FHQ + RXS	*35C + 35L3	50C + 50L	60C + 60L
Cooling capacity	Min./Nom./Max.			kW	-/3.4/-	1.7/5.0/5.3	1.7/5.7/5.7
Heating capacity	Min./Nom./Max.			kW	-/4/-	1.7/6.0/6.0	1.7/7.20/7.2
Power input	Cooling	Nom.		kW	0.95	1.570	1.750
	Heating	Nom.		kW	0.98	1.790	2.170
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	A+	
		Pdesign		kW	3.4	5.00	5.70
		SEER			6.18	5.87	6.02
		Annual energy consumption		kWh	193	298	332
	Heating (Average climate)	Energy label			A+	A	
		Pdesign		kW	3.1	4.35	4.71
		SCOP			4.43	3.86	3.87
		Annual energy consumption		kWh	980	1,578	1,705
Nominal efficiency	EER				3.58	3.18	3.26
	COP				4.08	3.35	3.32
	Annual energy consumption			kWh	475	785	875
	Energy label	Cooling			A	B	A
		Heating			A	C	C

Indoor unit				FHQ	35C	50C	60C
Casing	Colour				Fresh White		
Dimensions	Unit	HeightxWidthxDepth		mm	235x960x690		235x1,270x690
Weight	Unit			kg	24	25	31
Air filter	Type				Resin net with mold resistance		
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	14/11.5/10	15/12/10	19.5/15/11.5
	Heating	High/Nom./Low		m^3/min	14/11.5/10	15/12/10	19.5/15/11.5
Sound power level	Cooling			dBA	53	54	
	Heating			dBA	53	54	
Sound pressure level	Cooling	High/Nom./Low		dBA	36/34/31	37/35/32	37/35/33
	Heating	High/Nom./Low		dBA	36/34/31	37/35/32	37/35/33
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220		
Control systems	Infrared remote control				BRC7G53		
	Wired remote control				BRC1D52 / BRC1E52A/B		

Outdoor unit				RXS	*35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285	735x825x300	
Weight	Unit			kg	31.5	47	48
Sound power level	Cooling			dBA	61	62	
	Heating			dBA	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-	48/44	49/46
	Heating	High/Low		dBA	-/-	48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46	-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18	-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / - / 2,087.5	R-410A / 1.7 / 2,087.5	R-410A / 1.5 / 2,087.5
	Charge			TCO_2Eq	-	3.5	3.1
Piping connections	Liquid	OD		mm	6.35	6	
	Gas	OD		mm	9.5	12.7	
	Piping length	OU - IU	Max.	m	-	30	
	Additional refrigerant charge			kg/m	-	0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-	20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-230-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-	-	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Seasonal Smart

4-way blow ceiling suspended unit

Unique Daikin unit for high rooms with no false ceilings nor free floor space

- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- Can easily be installed in both new and refurbishment projects
- Refurbishing the room? Flexibility to suit every room layout without changing the location of the unit! Via the wired remote controller you can easily control each flap individually and even close the flaps.
- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating
- Optimum comfort guaranteed with automatic air flow adjustment to the required load
- 5 different discharge angles between 0 and 60° can be programmed via the remote control





FUQ-C



RZQG140L9V1/L(8)Y1



BRC1E52A-B, BRC7CB58

- Standard drain pump with 500mm lift increases flexibility and installation speed
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FUQ + RZQG	71C + 71L9V1	100C + 100L9V1	125C + 125L9V1	71C + 71L8Y1	100C + 100L8Y1	125C + 125L8Y1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	6.8	9.5	12.0
Heating capacity	Nom.			kW	7.5	10.8	13.5	7.5	10.8	13.5
Power input	Cooling	Nom.		kW	1.68	2.46	3.54	1.68	2.46	3.54
	Heating	Nom.		kW	1.84	2.73	3.95	1.84	2.73	3.95
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++		A+	A++		A+
		Pdesign		kW	6.80	9.50	12.00	6.80	9.50	12.00
		SEER			6.50	6.11	5.61	6.50	6.11	5.61
		Annual energy consumption		kWh	366	544	749	366	544	749
	Heating (Average climate)	Energy label			A+					
		Pdesign		kW	7.60	11.30	14.13	7.60	11.30	14.13
		SCOP			4.20	4.50	4.44	4.20	4.50	4.44
		Annual energy consumption		kWh	2,533	3,516	4,456	2,533	3,516	4,456
Nominal efficiency	EER				4.05	3.86	3.39	4.05	3.86	3.39
	COP				4.08	3.95	3.42	4.08	3.95	3.42
	Annual energy consumption			kWh	840	1,230	1,770	840	1,230	1,770
	Energy label	Cooling			A			A		
		Heating			A		B	A		B

Indoor unit				FUQ	71C	100C	125C
Casing	Colour				Fresh White		
Dimensions	Unit	HeightxWidthxDepth		mm	198x950x950		
Weight	Unit			kg	25	26	
Air filter	Type				Resin net with mold resistance		
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	23/19.5/16	31/25.5/20	32.5/26.5/20.5
	Heating	High/Nom./Low		m^3/min	23/19.5/16	31/25.5/20	32.5/26.5/20.5
Sound power level	Cooling			dBA	59	64	65
	Heating			dBA	59	64	65
Sound pressure level	Cooling	High/Nom./Low		dBA	41/38/35	46/42/39	47/43/40
	Heating	High/Nom./Low		dBA	41/38/35	46/42/39	47/43/40
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220		
Control systems	Infrared remote control				BRC7C58		
	Wired remote control				BRC1D52 / BRC1E52A/B		

Outdoor unit				RZQG	71L9V1	100L9V1	125L9V1	71L8Y1	100L8Y1	125L8Y1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320		990x940x320	1,430x940x320	
Weight	Unit			kg	77	99		80	101	
Sound power level	Cooling			dBA	64	66	67	64	66	67
Sound pressure level	Cooling	Nom.		dBA	48	50	51	48	50	51
	Heating	Nom.		dBA	50	52	53	50	52	53
	Night quiet mode	Level 1		dBA	43	45		43	45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50					
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5					
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5	
	Charge			TCO_2Eq	6.1	8.4		6.1	8.4	
Piping connections	Liquid	OD		mm	9.52					
	Gas	OD		mm	15.9					
	Piping length	OU - IU	Max.	m	50	75		50	75	
		System	Equivalent	m	70	90		70	90	
			Chargeless	m	30					
	Additional refrigerant charge			kg/m	See installation manual					
	Level difference	IU - OU	Max.	m	30.0					
		IU - IU	Max.	m	0.5					
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	-			16	25	

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Wall mounted unit

For rooms with no false ceilings nor free floor space

- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- Can easily be installed in both new and refurbishment projects
- Reduced energy consumption thanks to specially developed DC fan motor
- The air is comfortably spread up and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- Maintenance operations can be performed easily from the front of the unit
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FAQ + RZQG	71C + 71L9V1	100C + 100L9V1	71C + 71L8Y1	100C + 100L8Y1
Cooling capacity	Nom.			kW	6.8	9.5	6.8	9.5
Heating capacity	Nom.			kW	7.5	10.8	7.5	10.8
Power input	Cooling	Nom.		kW	2.00	2.63	2.00	2.63
	Heating	Nom.		kW	2.03	3.00	2.03	3.00
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++			
		Pdesign		kW	6.80	9.50	6.80	9.50
		SEER			6.51	6.11	6.51	6.11
		Annual energy consumption		kWh	366	544	366	544
	Heating (Average climate)	Energy label			A+			
		Pdesign		kW	6.33	10.20	6.33	10.20
		SCOP			4.02	4.01	4.02	4.01
		Annual energy consumption		kWh	2,204	3,561	2,204	3,561
Nominal efficiency	EER				3.40	3.62	3.40	3.62
	COP				3.70	3.61	3.70	3.61
	Annual energy consumption			kWh	1,000	1,315	1,000	1,315
	Energy label	Cooling			A			
		Heating			A			

Indoor unit				FAQ	71C	100C
Casing	Colour				Fresh White	
Dimensions	Unit	HeightxWidthxDepth		mm	290x1,050x238	340x1,200x240
Weight	Unit			kg	13	17
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	18/16/14	26/23/19
	Heating	High/Nom./Low		m^3/min	18/16/14	26/23/19
Sound power level	Cooling			dBA	61	65
	Heating			dBA	61	65
Sound pressure level	Cooling	High/Nom./Low		dBA	45/42/40	49/45/41
	Heating	High/Nom./Low		dBA	45/42/40	49/45/41
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220	
Control systems	Infrared remote control				BRC7EB518	
	Wired remote control				BRC1D52 / BRC1E52A/B	

Outdoor unit				RZQG	71L9V1	100L9V1	71L8Y1	100L8Y1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320	990x940x320	1,430x940x320
Weight	Unit			kg	77	99	80	101
Sound power level	Cooling			dBA	64	66	64	66
Sound pressure level	Cooling	Nom./Silent operation		dBA	48/-	50/-	48/-	50/-
	Heating	Nom.		dBA	50	52	50	52
	Night quiet mode	Level 1		dBA	43	45	43	45
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50			
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5			
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	6.1	8.4	6.1	8.4
Piping connections	Liquid	OD		mm	9.52			
	Gas	OD		mm	15.9			
	Piping length	OU - IU	Max.	m	50	75	50	75
		System	Equivalent	m	70	90	70	90
			Chargeless	m	30			
	Additional refrigerant charge			kg/m	See installation manual			
	Level difference	IU - OU	Max.	m	30.0			
		IU - IU	Max.	m	0.5			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		3N~ / 50 / 380-415	
Current - 50Hz	Maximum fuse amps (MFA)			A	-		16	20

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Seasonal Classic

Wall mounted unit

For rooms with no false ceilings nor free floor space

› Combination with Seasonal Classic ensures good value for money for all types of commercial applications (see pg. 157)



FAQ100C



RZQSG100L9V1/L(8)Y1



BRC1E52A-B, BRC7EB518

Efficiency data				FAQ + RZQSG	71C + 71L3V1	100C + 100L9V1	100C + 100L8Y1
Cooling capacity	Nom.			kW	6.8	9.5	
Heating capacity	Nom.			kW	7.5	10.8	
Power input	Cooling	Nom.		kW	2.12	3.16	
	Heating	Nom.		kW	2.08	3.17	
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+		
		Pdesign		kW	6.80	9.50	
		SEER			6.05	5.61	
		Annual energy consumption		kWh	393	593	593
	Heating (Average climate)	Energy label			A	A+	
		Pdesign		kW	6.00	6.81	
		SCOP			3.90	4.01	
		Annual energy consumption		kWh	2,155	2,378	2,378
Nominal efficiency	EER				3.21	3.01	
	COP				3.61	3.41	
	Annual energy consumption			kWh	1,060	1,580	
	Energy label	Cooling			A	B	
		Heating			A	B	

Indoor unit				FAQ	71C	100C
Casing	Colour				Fresh White	
Dimensions	Unit	HeightxWidthxDepth		mm	290x1,050x238	340x1,200x240
Weight	Unit			kg	13	17
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	18/16/14	26/23/19
	Heating	High/Nom./Low		m^3/min	18/16/14	26/23/19
Sound power level	Cooling			dBA	61	65
	Heating			dBA	61	65
Sound pressure level	Cooling	High/Nom./Low		dBA	45/42/40	49/45/41
	Heating	High/Nom./Low		dBA	45/42/40	49/45/41
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50/60 / 220-240/220	
Control systems	Infrared remote control				BRC7EB518	
	Wired remote control				BRC1D52 / BRC1E52A/B	


Outdoor unit				RZQSG	71L3V1	100L9V1	100L8Y1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320	
Weight	Unit			kg	67	77	82
Sound power level	Cooling			dBA	65	70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	
	Heating	Nom.		dBA	51	57	
	Night quiet mode	Level 1		dBA	-	49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15 ~ 46		
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5		
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5	
	Charge			TCO_2Eq	5.7	6.1	
Piping connections	Liquid	OD		mm	9.52		
	Gas	OD		mm	15.9		
	Piping length	OU - IU	Max.	m	50		
		System	Equivalent	m	70		
			Chargeless	m	30		
	Additional refrigerant charge			kg/m	See installation manual		
	Level difference	IU - OU	Max.	m	15	30.0	
		IU - IU	Max.	m	0.5		
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		3N~ / 50 / 380-415
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-	20

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Floor standing unit

For commercial spaces with high ceilings

- Combination with Seasonal Smart ensures high quality, optimal comfort, flexible installation and highest efficiency values (see pg. 167)
- Ideal solution for commercial spaces with no or narrow false ceilings
- Can easily be installed in both new and refurbishment projects
- Decrease of temperature variation by automatic fan speed selection or freely selectable 3-step fan speed.Improved comfort as a result of better airflow distribution from the vertical out blow which allows manual adjustment of air outlet blades at the top of the unit. Selectable horizontal out blow to better suit the layout of the room (via BRC1E52).



- Reduced energy consumption thanks to specially developed DC fan motor
- No optional adapter needed for DIII-connection, link your unit into the wider building management system.

Efficiency data				FVQ + RZQG	71C + 71L9V1	100C + 100L9V1	125C + 125L9V1	140C + 140L9V1	71C + 71L8Y1	100C + 100L8Y1	125C + 125L8Y1	140C + 140LY1
Cooling capacity	Nom.			kW	6.8	9.5	12.0	13.4	6.8	9.5	12.0	13.4
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	2.02	2.49	3.74	4.17	2.02	2.49	3.74	4.17
	Heating	Nom.		kW	2.06	2.61	3.65	4.30	2.06	2.61	3.65	4.30
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A++	A+		-	A++	A+		-
		Pdesign		kW	6.80	9.50	12.00	-	6.80	9.50	12.00	-
		SEER			6.31	5.61		-	6.31	5.61		-
		Annual energy consumption		kWh	377	593	749	-	377	593	749	-
	Heating (Average climate)	Energy label			A+		A	-	A+		A	-
		Pdesign		kW	6.33	11.30		-	6.33	11.30		-
		SCOP			4.05	4.20	3.87	-	4.05	4.20	3.87	-
		Annual energy consumption		kWh	2,188	3,767	4,088	-	2,188	3,767	4,088	-
Nominal efficiency	EER				3.37	3.81	3.21		3.37	3.81	3.21	
	COP				3.64	4.14	3.70	3.61	3.64	4.14	3.70	3.61
	Annual energy consumption			kWh	1,010	1,245	1,870	2,085	1,010	1,245	1,870	2,085
	Energy label	Cooling			A			-	A			-
		Heating			A			-	A			-

Indoor unit				FVQ	71C	100C	125C	140C
Casing	Colour				Fresh White			
Dimensions	Unit	HeightxWidthxDepth	mm		1,850x600x270	1,850x600x350		
Weight	Unit		kg		39	47		
Air filter	Type				Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low	m^3/min		18/16/14	28/25/22	28/26/24	30/28/26
	Heating	High/Nom./Low	m^3/min		18/16/14	28/25/22	28/26/24	30/28/26
Sound power level	Cooling		dBA		55	62	63	65
	Heating		dBA		55	62	63	65
Sound pressure level	Cooling	High/Nom./Low	dBA		43/41/38	50/47/44	51/48/46	53/51/48
	Heating	High/Nom./Low	dBA		43/41/38	50/47/44	51/48/46	53/51/48
Power supply	Phase / Frequency / Voltage		Hz / V		1~ / 50/60 / 220-240/220			
Control systems	Wired remote control				BRC1D52 / BRC1E52A/B			

Outdoor unit					RZQG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm		990x940x320	1,430x940x320			990x940x320	1,430x940x320		
Weight	Unit			kg		77	99			80	101		
Sound power level	Cooling			dBA		64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.		dBA		48	50	51	52	48	50	51	52
	Heating	Nom.		dBA		50	52	53		50	52	53	
	Night quiet mode	Level 1		dBA		43	45			43	45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-15~50							
	Heating	Ambient	Min.~Max.	°CWB		-20~15.5							
Refrigerant	Type/Charge/GWP			kg		R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5			R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		
	Charge			TCO_2Eq		6.1	8.4			6.1	8.4		
Piping connections	Liquid	OD		mm		9.52							
	Gas	OD		mm		15.9							
	Piping length	OU - IU	Max.	m		50	75			50	75		
		System	Equivalent	m		70	90			70	90		
			Chargeless	m		30							
	Additional refrigerant charge			kg/m		See installation manual							
	Level difference	IU - OU	Max.	m		30.0							
		IU - IU	Max.	m		0.5							
Power supply	Phase / Frequency / Voltage			Hz / V		1~ / 50 / 220-240				3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A		-				16	25		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Seasonal Classic

Floor standing unit

For commercial spaces with high ceilings

› Combination with Seasonal Classic ensures good value for money for all types of commercial applications (see pg. 157)



FVQ71C



RZQSG100-125L3/9V1/L(8)Y1



BRC1E52A-B

Efficiency data			FVQ + RZQSG	71C + 71L3V1	100C + 100L9V1	125C + 125L9V1	140C + 140L9V1	100C + 100L8Y1	125C + 125L8Y1	140C + 140LY1
Cooling capacity	Nom.		kW	6.8	9.5	12.0	13.4	9.5	12.0	13.4
Heating capacity	Nom.		kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.	kW	2.12	2.96	4.27	4.45	2.96	4.27	4.45
	Heating	Nom.	kW	2.08	2.99	3.96	4.54	2.99	3.96	4.54
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A			-	A		-
		Pdesign	kW	6.80	9.50	12.00	-	9.50	12.00	-
		SEER		5.50			-	5.50		-
		Annual energy consumption	kWh	433	605	764	-	605	764	-
	Heating (Average climate)	Energy label		A	A+	A	-	A+	A	-
		Pdesign	kW	6.33	7.60		-	7.60		-
		SCOP		3.86	4.01	3.85	-	4.01	3.85	-
		Annual energy consumption	kWh	2,296	2,653	2,764	-	2,653	2,764	-
Nominal efficiency	EER			3.21		2.81	3.01	3.21	2.81	3.01
	COP			3.61		3.41		3.61	3.41	
	Annual energy consumption		kWh	1,060	1,480	2,135	2,225	1,480	2,135	2,225
	Energy label	Cooling		A			-	A		-
		Heating		A		B	-	A	B	-

Indoor unit			FVQ	71C	100C	125C	140C
Casing	Colour			Fresh White			
Dimensions	Unit	HeightxWidthxDepth	mm	1,850x600x270	1,850x600x350		
Weight	Unit		kg	39	47		
Air filter	Type			Resin net with mold resistance			
Fan - Air flow rate	Cooling	High/Nom./Low	m^3/min	18/16/14	28/25/22	28/26/24	30/28/26
	Heating	High/Nom./Low	m^3/min	18/16/14	28/25/22	28/26/24	30/28/26
Sound power level	Cooling		dBA	55	62	63	65
	Heating		dBA	55	62	63	65
Sound pressure level	Cooling	High/Nom./Low	dBA	43/41/38	50/47/44	51/48/46	53/51/48
	Heating	High/Nom./Low	dBA	43/41/38	50/47/44	51/48/46	53/51/48
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50/60 / 220-240/220			
Control systems	Wired remote control			BRC1D52 / BRC1E52A/B			

Outdoor unit				RZQSG	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	77		99	82		101
Sound power level	Cooling			dBA	65	70		69		70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	51	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	50						
		System	Equivalent	m	70						
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15	30.0					
		IU - IU	Max.	m	0.5						
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			20		

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Concealed floor standing unit

Designed to be concealed in walls

- Combination with split outdoor units is ideal for smaller applications such as retail or residential applications
- Ideal for installation in offices, hotels and residential applications
- Its low height enables the unit to fit perfectly beneath a window
- Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- Requires very little installation space as the depth is only 200mm
- High ESP allows flexible installation



FNQ-A



RXS35L3



BRC1E52A-B,BRC4C65

Efficiency data			FNQ + RXS	*25A + 25L3	*35A + 35L3	*50A + 50L	*60A + 60L
Cooling capacity	Nom.		kW	2.4	3.4	5.0	6.0
Heating capacity	Nom.		kW	3.2	4.0	5.8	7.0
Power input	Cooling	Nom.	kW	0.65	1.06	1.65	2.06
	Heating	Nom.	kW	0.80	1.15	1.87	2.18
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+	A	A+	A
		Pdesign	kW	2.4	3.4	5.0	6.0
		SEER		5.63	5.21	5.72	5.51
		Annual energy consumption	kWh	149	228	306	381
	Heating (Average climate)	Energy label		A+	A		
		Pdesign	kW	2.6	2.9	4.0	4.6
		SCOP		4.24	3.88	3.93	3.80
		Annual energy consumption	kWh	858	1,047	1,425	1,693
Nominal efficiency	EER			3.69	3.21	3.03	2.91
	COP			4.00	3.48	3.10	3.21
	Annual energy consumption		kWh	325	530	825	1,031
	Energy label	Cooling		A		B	C
		Heating		A	B	D	C

Indoor unit			FNQ	*25A	*35A	*50A	*60A
Dimensions	Unit	HeightxWidthxDepth	mm	620x760x200		620x1,150x200	
Weight	Unit		kg	21		30	
Fan - Air flow rate	Cooling	High/Low	m^3/min	8.7/7.3		16.0/13.5	
Sound power level	Cooling		dBA	-			
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 230		1~ / 50 / 220-240	
Control systems	Infrared remote control			BRC4C65			
	Wired remote control			BRC1D52 / BRC1E52A/B			

Outdoor unit				RXS	*25L3	*35L3	50L	60L
Dimensions	Unit	HeightxWidthxDepth		mm	550x765x285		735x825x300	
Weight	Unit			kg	31.5		47	48
Sound power level	Cooling			dBA	59	61	62	
	Heating			dBA	59	61	62	
Sound pressure level	Cooling	High/Low		dBA	-/-		48/44	49/46
	Heating	High/Low		dBA	-/-		48/45	49/46
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		-10~46	
	Heating	Ambient	Min.~Max.	°CWB	-15~18		-15~18	
Refrigerant	Type/Charge/GWP			kg	R-410A / - / 2,087.5		R-410A / 1.7 / 2,087.5	R-410A / 1.5 / 2,087.5
	Charge			TCO_2Eq	-		3.5	3.1
Piping connections	Liquid	OD		mm	-		6.35	
	Gas	OD		mm	-		12.7	
	Piping length	OU - IU	Max.	m	-		30	
	Additional refrigerant charge			kg/m	-		0.020 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	-		20.0	
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		1~ / 50 / 220-230-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	-		-	

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012 for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

4-way blow ceiling mounted cassette

For shops requiring basic solutions

- Ideal solution for shops, restaurants or offices requiring maximum floor space for furniture, decorations and fittings
- Air can be discharged in any of 4 directions
- Air filter removes airborne dust particles to ensure a steady supply of clean air
- Easy installation and maintenance
- Control several indoor units at the same time via the Siesta Sky Air group control (optional)
- Standard drain pump
- Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required



ACQ125D



AZQS140B8V1/BY1



ARCWLA

Efficiency data				ACQ + AZQS	71C + 71B2V1	100C + 100B8V1	125C + 125B8V1	100C + 100BY1	125C + 125BY1
Cooling capacity	Nom.			kW	-	-	-	-	-
Heating capacity	Nom.			kW	-	-	-	-	-
Power input	Cooling	Nom.		kW	-	-	-	-	-
	Heating	Nom.		kW	-	-	-	-	-
Seasonal efficiency (according to EN14825)	Cooling	Energy label			A+	A	-	A	-
		Pdesign		kW	-	-	-	-	-
		SEER			5.7	5.5	-	5.5	-
		Annual energy consumption		kWh	-	-	-	-	-
	Heating (Average climate)	Energy label			A+	A	-	A	-
		Pdesign		kW	-	-	-	-	-
		SCOP			4	3.85	-	3.85	-
		Annual energy consumption		kWh	-	-	-	-	-
Nominal efficiency	EER				-	-	3.1	-	3.1
	COP				-	-	3.61	-	3.61
	Annual energy consumption			kWh	-	-	-	-	-
	Energy label	Cooling			-	-	B	-	B
		Heating			-	-	A	-	A

Indoor unit				ACQ	71C	100C	125C
Dimensions	Unit	HeightxWidthxDepth		mm	265x820x820	300x820x820	
Weight	Unit			kg	31	39	
Decoration panel	Colour				White		
	Dimensions	HeightxWidthxDepth		mm	82x990x990		
	Weight			kg	4		
Air filter	Type				Removable / washable		
Fan - Air flow rate	Cooling	High/Nom./Low/Silent operation		m^3/min	24.4/20.5/17.6/15.0	29.2/24.4/21.0/17.6	34.0/29.2/26.3/22.1
	Heating	High/Nom./Low/Silent operation		m^3/min	24.4/20.5/17.6/15.0	29.2/24.4/21.0/17.6	34.0/29.2/26.3/22.1
Sound power level	Cooling			dBA	54	57	60
	Heating			dBA	54	56	60
Sound pressure level	Cooling	High/Nom./Low/Silent operation		dBA	41/38/35/32	44/41/38/36	47/44/43/41
	Heating	High/Nom./Low/Silent operation		dBA	41/38/35/32	44/41/38/36	47/44/43/41
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240		
Control systems	Wired remote control				ARCWB		

Outdoor unit				AZQS	71B2V1	100B8V1	125B8V1	100BY1	125BY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320			
Weight	Unit			kg	67	81		82	
Sound power level	Cooling			dBA	65	70	71	70	71
Sound pressure level	Cooling	Nom./Silent operation		dBA	48/43	53/-	54/-	53/-	54/-
	Heating	Nom.		dBA	50	57	58	57	58
	Night quiet mode	Level 1		dBA	-	49			
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5~46				
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5				
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5			
	Charge			TCO_2Eq	5.7	6.1			
Piping connections	Liquid	OD		mm	9.52				
	Gas	OD		mm	15.9				
	Piping length	OU - IU	Max.	m	30	50			
		System	Equivalent	m	40	70			
			Chargeless	m	30				
	Additional refrigerant charge			kg/m	See installation manual				
	Level difference	IU - OU	Max.	m	15.0	30.0			
		IU - IU	Max.	m	-	0.5			
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			3N~ / 50 / 380-415	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

Concealed ceiling unit

Ideal for medium sized shops with false ceilings

- Ideal solution for shops requiring maximum floor space for furniture, decorations and fittings
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Air filter removes airborne dust particles to ensure a steady supply of clean air
- Easy installation and maintenance
- Double protection drainage system: best protection against possible water leakage



ABQ140C



AZQS140B8V1/BY1



ARCWB

Efficiency data				ABQ + AZQS	71C + 71B2V1	100C + 100B8V1	125C + 125B8V1	140C + 140B8V1	100C + 100BY1	125C + 125BY1	140C + 140BY1
Cooling capacity	Nom.			kW	6.8	9.5	12.1	13.0	9.5	12.1	13.0
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	2.33	3.63	4.31	4.32	3.63	4.31	4.32
	Heating	Nom.		kW	2.13	3.16	3.96	4.55	3.16	3.96	4.55
Seasonal efficiency (according to EN14825)	Cooling	Energy label			B		-		B	-	
		Pdesign		kW	6.80	9.50	-		9.50	-	
		SEER			4.65		-		4.65	-	
		Annual energy consumption		kWh	512	716	-		716	-	
	Heating (Average climate)	Energy label			A		-		A	-	
		Pdesign		kW	5.65	6.78	-		6.78	-	
		SCOP			3.80		-		3.80	-	
		Annual energy consumption		kWh	2,082	2,499	-		2,498	-	
Nominal efficiency	EER				2.91	2.62	2.81	3.01	2.62	2.81	3.01
	COP				3.51	3.42	3.41		3.42	3.41	
	Annual energy consumption			kWh	1,165	1,813	2,153	2,159	1,813	2,153	2,159
	Energy label	Cooling			C	D	C	-	D	C	-
		Heating			B			-	B		-

Indoor unit				ABQ	71C	100C	125C	140C
Dimensions	Unit	HeightxWidthxDepth		mm	285x600x1,007	378x541x1,045	378x541x1,299	378x541x1,499
Weight	Unit			kg	35	44	50	56
Air filter	Type				Saranet			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	18.3/16.8/15.4	22.7/20.5/18.3	40.5/37.4/34.8	48.7/43.9/37.9
	Heating	High/Nom./Low		m^3/min	18.3/16.8/15.4	22.7/20.5/18.3	40.5/37.4/34.8	48.7/43.9/37.9
Fan - External static pressure	High/Nom./Low/Maximum available/High			Pa	90/77/64/-	70/57/45/-	150/128/111/-	150/122/92/-
Sound power level	Cooling			dBA	64	60	-	
	Heating			dBA	64	60	-	
Sound pressure level	Cooling	High/Nom./Low		dBA	-/-/-	41/38/36	53/52/50	55/53/50
	Heating	High/Nom./Low		dBA	-/-/-	41/38/36	53/52/50	55/53/50
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			

Outdoor unit				AZQS	71B2V1	100B8V1	125B8V1	140B8V1	100BY1	125BY1	140BY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	81		102	82		101
Sound power level	Cooling			dBA	65	70	71	70		71	70
Sound pressure level	Cooling	Nom./Silent operation		dBA	48/43	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	50	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A/2.75/2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	30	50					
		System	Equivalent	m	40	70					
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15.0	30.0					
		IU - IU	Max.	m	-	0.5					
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-					

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Siesta

Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

- Ideal solution for commercial spaces with no or narrow false ceilings
- Can easily be installed in both new and refurbishment projects
- Air filter removes airborne dust particles to ensure a steady supply of clean air
- Decrease of temperature variation by automatic fan speed selection or freely selectable 3-step fan speed.
- Easy installation and maintenance



AHQ71C



AZQS71B8V1



ARCWLA

Efficiency data				AHQ + AZQS	71C + 71B2V1	100C + 100B8V1	125C + 125B8V1	140C + 140B8V1	100C + 100BY1	125C + 125BY1	140C + 140BY1
Cooling capacity	Nom.			kW	6.8	9.5	12.1	13.0	9.5	12.1	13.0
Heating capacity	Nom.			kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5
Power input	Cooling	Nom.		kW	2.24	3.62	4.60	4.32	3.62	4.60	4.32
	Heating	Nom.		kW	2.46	3.17	3.74	4.55	3.17	3.74	4.55
Seasonal efficiency (according to EN14825)	Cooling	Energy label			B		-		B	-	
		Pdesign		kW	6.80	9.50	-		9.50	-	
		SEER			4.65	4.60	-		4.60	-	
		Annual energy consumption		kWh	511.85	723	-		723	-	
	Heating (Average climate)	Energy label			A		-		A	-	
		Pdesign		kW	6.33	7.60	-		7.60	-	
		SCOP			3.80		-		3.80	-	
		Annual energy consumption		kWh	2,332.26	2,800	-		2,800	-	
Nominal efficiency	EER				3.03	2.62	2.63	3.01	2.62	2.63	3.01
	COP				3.05	3.41	3.61	3.41		3.61	3.41
	Annual energy consumption			kWh	1,120	1,810	2,300	2,159	1,810	2,300	2,159
	Energy label	Cooling			B	D		-	D		-
		Heating			D	B	A	-	B	A	-

Indoor unit				AHQ	71C	100C	125C	140C
Casing	Colour				White			
Dimensions	Unit	HeightxWidthxDepth		mm	260x1,320x634	260x1,538x634	260x1,786x634	285x1,902x680
Weight	Unit			kg	38	45	54	70
Air filter	Type				Removable / washable			
Fan - Air flow rate	Cooling	High/Nom./Low		m^3/min	23.8/21.3/18.9	31.1/27.8/24.8	34.4/30.6/27.2	43.9/39.1/28.3
	Heating	High/Nom./Low		m^3/min	23.8/21.3/18.9	31.1/27.8/24.8	34.4/30.6/27.2	43.9/39.1/28.3
Fan - External static pressure	High/Nom./Low			Pa	0/0/0			
Sound power level	Cooling			dBA	59	64	69	70
	Heating			dBA	62	64	69	70
Sound pressure level	Cooling	High/Nom./Low		dBA	49/48/46	52/47/46	52/50/49	56/53/46
	Heating	High/Nom./Low		dBA	49/48/46	52/47/46	52/50/49	56/53/46
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			
Control systems	Wired remote control				ARCWB			

Outdoor unit				AZQS	71B2V1	100B8V1	125B8V1	140B8V1	100BY1	125BY1	140BY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	81		102	82		101
Sound power level	Cooling			dBA	65	70	71	70		71	70
Sound pressure level	Cooling	Nom./Silent operation		dBA	48/43	53/-	54/-	53/-		54/-	53/-
	Heating	Nom.		dBA	50	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49					
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A/2.75/2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	30	50					
		System	Equivalent	m	40	70					
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15.0	30.0					
		IU - IU	Max.	m	-	0.5					
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240			3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-					

(1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Twin, triple and double twin applications



The benefits

Air conditioning in long or irregularly shaped rooms
A twin/triple/double twin application allows up to 4 indoor units to operate in L-shaped, U-shaped or long rooms powered by a single outdoor unit.
All indoor units are controlled at the same time.

The widest choice
Different types of indoor units - wall mounted, concealed celling, cassettes etc - can be selected for twin/triple/double twin application

Ideal comfort in every part of the room
Delivery of optimal efficiency and conform in each part of a long or irregularly shaped room.



Benefits for the installer

› Less piping required as all indoor units can be connected to one single outdoor unit

Benefits for the consultant

› Ideal solution for long or irregularly shaped rooms
› Up to 4 indoor units can be connected to a single outdoor unit
› The air flow is evenly spread into the area as smaller indoor units are installed on different locations in the room

Benefits for the end user

› All indoor units are controlled at the same time and via 1 single wired remote controller
› Only 1 outdoor unit standing on a roof, terrace or against an outside wall to control up to 4 indoor units
› Same comfortable feeling through the entire room

Seasonal Classic



Seasonal Smart



Super Inverter



Seasonal Smart

Pair, Twin, Triple, double twin

Industry leading technology for commercial applications and even for technical rooms

› Top efficiency:
- compressor that offers substantial efficiency improvements
- control logic that optimises efficiency at the most frequently encountered operating conditions and that optimises the auxiliary modes (when the unit is not active)
- heat exchangers that optimise the refrigerant flow at the most frequent operating conditions (temperature and load)
- via improved nominal performances

› The perfect balance in efficiency and comfort thanks to Variable Refrigerant Temperature: top seasonal efficiency throughout most of the year and quick reaction speed on the hottest days.

Variable Refrigerant Temperature

› Suits computer room applications (EDP)
› Re-use of existing R-22 or R-407C technology

› Extended operation range down to -20°C in heating
› With gas cooled PCB reliable cooling is guaranteed as it is not influenced by ambient temperature.
› Maximum piping length up to 75m, minimum piping length is 5m.



RZQG140L9V1/L(8)Y1

› Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall
› Units optimised for seasonal efficiency give an indication on how efficient an air conditioner operates over an entire heating or cooling season.
› Compatibility with D-BACS

		FCQHG-F	FCQG-F				FFQ-C			FDXS-F (9)			FBQ-D				FHQ-C				FAQ-C	FUQ-C	FNQ-A		
capacity class		71	35	50	60	71	35	50	60	35	50	60	35	50	60	71	35	50	60	71	71	71	35	50	60
RZQG71L9V1	RZQG71L8Y1		2				2			2			2				2						2		
RZQG100L9V1	RZQG100L8Y1		3	2			3	2		3	2		3	2			3	2					3	2	
RZQG125L9V1	RZQG125L8Y1		4	3	2		4	3	2	4	3	2	4	3	2		4	3	2				4	3	2
RZQG140L9V1	RZQG140LY1	2	4	3		2	4	3		4	3		4	3		2	4	3		2	2	2	4	3	

Outdoor unit				RZQG	71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320			990x940x320	1,430x940x320		
Weight	Unit			kg	77	99			80	101		
Sound power level	Cooling			dBA	64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.		dBA	48	50	51	52	48	50	51	52
	Heating	Nom.		dBA	50	52	53		50	52	53	
	Night quiet mode	Level 1		dBA	43	45			43	45		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50							
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5							
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5			R-410A / 2.9 / 2,087.5	R-410A / 4 / 2,087.5		
	Charge			TCO_2Eq	6.1	8.4			6.1	8.4		
Piping connections	Liquid	OD		mm	9.52							
	Gas	OD		mm	15.9							
	Piping length	OU - IU	Max.	m	50	75			50	75		
		System	Equivalent	m	70	90			70	90		
			Chargeless	m	30							
	Additional refrigerant charge			kg/m	See installation manual							
	Level difference	IU - OU	Max.	m	30.0							
		IU - IU	Max.	m	0.5							
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415			
Current - 50Hz	Maximum fuse amps (MFA)			A	-				16	25		

Seasonal Classic

Pair, Twin, Triple, double twin

Technology and comfort combined for commercial applications

› Top efficiency:
- compressor that offers substantial efficiency improvements
- control logic that optimises efficiency at the most frequently encountered operating conditions and that optimises the auxiliary modes (when the unit is not active)
- heat exchangers that optimise the refrigerant flow at the most frequent operating conditions (temperature and load)
- via improved nominal performances

› Re-use of existing R-22 or R-407C technology

› Guarantees operation in heating mode down to -15°C
› With gas cooled PCB reliable cooling is guaranteed as it is not influenced by ambient temperature.
› Maximum piping length up to 50m, minimum piping length is 5m.
› Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall
› Units optimised for seasonal efficiency give an indication on how efficient an air conditioner operates over an entire heating or cooling season.
› Compatibility with D-BACS



RZQSG100-125L3/9V1/L(8)Y1

		FCQHG-F	FCQG-F				FFQ-C			FDXS-F(9)			FBQ-D				FHQ-C				FAQ-C	FNQ-A		
capacity class		71	35	50	60	71	35	50	60	35	50	60	35	50	60	71	35	50	60	71	71	35	50	60
RZQSG71L3V1			2				2			2			2				2					2		
RZQSG100L9V1	RZQSG100L8Y1		3	2			3	2		3	2		3	2			3	2				3	2	
RZQSG125L9V1	RZQSG125L8Y1		4	3	2		4	3	2	4	3	2	4	3	2		4	3	2			4	3	2
RZQSG140L9V1	RZQSG140LY1	2	4	3		2	4	3		4	3		4	3		2	4	3		2	2	4	3	

Outdoor unit				RZQSG	71L3V1	100L9V1	125L9V1	140L9V1	100L8Y1	125L8Y1	140LY1
Dimensions	Unit	HeightxWidthxDepth		mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Weight	Unit			kg	67	77		99	82		101
Sound power level	Cooling			dBA	65	70		69	69	70	69
Sound pressure level	Cooling	Nom./Silent operation		dBA	49/47	53/-	54/-	53/-	53	54	53
	Heating	Nom.		dBA	51	57	58	54	57	58	54
	Night quiet mode	Level 1		dBA	-	49			49		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~46						
	Heating	Ambient	Min.~Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP			kg	R-410A / 2.75 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5	R-410A / 2.9 / 2,087.5		R-410A / 4 / 2,087.5
	Charge			TCO_2Eq	5.7	6.1		8.4	6.1		8.4
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	15.9						
	Piping length	OU - IU	Max.	m	50						
		System	Equivalent	m	70						
			Chargeless	m	30						
	Additional refrigerant charge			kg/m	See installation manual						
	Level difference	IU - OU	Max.	m	15	30.0					
		IU - IU	Max.	m	0.5						
Power supply	Phase / Frequency / Voltage			Hz / V	1~ / 50 / 220-240				3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20	-			20		

Pair, Twin, Triple, double twin

Packaged system for commercial applications

› Re-use of existing R-22 or R-407C technology

› Guarantees operation in heating mode down to -15°C
› Standard night quiet mode
› Maximum piping length up to 100m
› Maximum installation height difference up to 30m



RZQ200-250C

	FCQG-F					FFQ-C		FDXS-F(9)		FBQ-D					FHQ-C					FUQ-C			FAQ-C		FDQ-C	FNQ-A	
capacity class	50	60	71	100	125	50	60	50	60	50	60	71	100	125	50	60	71	100	125	71	100	125	71	100	125	50	60
RZQ200C	4	3	3	2		4	3	4	3	4	3	3	2		4	3	3	2		3	2		3	2		4	3
RZQ250C		4			2		4		4		4			4		2			2			2			2		4

Outdoor unit				**RZQ**	**200C**	**250C**
Dimensions	Unit	HeightxWidthxDepth		mm	1,680x930x765	
Weight	Unit			kg	183	184
Sound power level	Cooling			dBA	78	
	Heating			dBA	78	
Sound pressure level	Nom.			dBA	57	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5.0~46.0	
	Heating	Ambient	Min.~Max.	°CWB	-15.0~15.0	
Refrigerant	Type/Charge/GWP			kg	R-410A / 8.3 / 2,087.5	R-410A / 9.3 / 2,087.5
	Charge			TCO_2Eq	17.3	19.4
Piping connections	Piping length	OU - IU	Max.	m	100	
	Level difference	IU - OU	Max.	m	-	
Power supply	Phase / Frequency / Voltage			Hz / V	3N~ / 50 / 380-415	
Current - 50Hz	Maximum fuse amps (MFA)			A	20	

Rooftop

- Easy to install 'plug and play' concept plus single installation configuration; no additional piping is required since indoor and outdoor sides are pre-connected
- High efficiency and reliable scroll compressor
- Wide operating range
- Flat top unit design allows maximum use of warehouse and container space
- Free cooling and fresh air intake possible with optional economiser
- Convertible return and supply air: fan can be mounted in two directions
- Factory pre-charged refrigerant ensures clean and efficient operation
- Belt driven fan enables air volume and static pressure to be adjusted as required.
- Adjustable fan pulley as standard to meet a wide range of supply air volumes and external static pressures
- Anti-corrosion treated coil



UATYQ-CY1



Remote control


Indoor unit					UATYQ	250CY1	350CY1	450CY1	550CY1	600CY1	700CY1
Cooling capacity	Nom.				kW	27.340	35.580	44.720	55,690.000	66.820	72.600
Heating capacity	Nom.				kW	24.910	34.790	41.790	53.930	61.690	69.610
Power input	Cooling	Nom.			kW	8.140	10.780	13.040	16.740	19.650	21.610
	Heating	Nom.			kW	7.330	10.840	12.860	15.540	18.580	21.420
EER						3.36	3.30	3.43	3.33	3.40	3.36
COP						3.40	3.21	3.25	3.47	3.32	3.25
Evaporator	Air flow rate	Cooling			m^3/min	93.6	121.8	160.2	189.6	206.7	235.02
	External static pressure				Pa		147			206	
Evaporator piping connections	Condensation drain size	OD			mm			25.4			
Condenser	Dimensions	Unit	Height		mm	1,150	1,028	1,130	1,048	1,302	1,454
			Width		mm	1,638			2,209		
			Depth		mm	2,063		2,113		2,670	
	Weight	Unit			kg	445	580	610	830	880	1,020
	Casing	Colour						Light grey			
	Air flow rate	Cooling			cfm	8,230	12,000	12,100	12,900	20,200	21,200
	Operation range	Cooling	Min.~Max.		°CDB			0~52			
		Heating	Min.~Max.		°CWB			-15~18			
	Sound pressure level	Nom.			dBA	68	64	65	68	70	
	Sound power level	Nom.			dBA	82		83	87	90	
	Refrigerant	Type / GWP						R-410A / 2,087.5			
		Charge			kg	6.1	5.8	7.2	8.7	10.4	11.6
		Charge			TCO_2Eq	12.7	12.1	15.0	18.2	21.7	24.2
Power supply	Phase/Frequency/Voltage				Hz/V			3~/50/380-415			

Economiser option

Indoor unit				ECONO	250AY1	350AY1	450AY1	550AY1	600AY1	700AY1
Dimensions	Packed unit	Height		mm			534			
		Width		mm	1,440		1,430		1,458	
		Depth		mm	1,144		1,124		1,564	
Weight	Unit			kg	51	42	43	53	54	69
Packing	Weight			kg	152	140	141	165	166	181
Fan	Air flow rate	Cooling	Nom.	l/s	1,560	2,030	2,670	3,160	3,445	3,917
				cfm	3,300	4,300	5,650	6,700	7,300	8,300
Power supply	Voltage			V			24 DC			
Option for					UATYQ250CY1	UATYQ350CY1	UATYQ450CY1	UATYQ550CY1	UATYQ600CY1	UATYQ700CY1
Test Standard							ISO 13253			

Rooftop

- Easy to install 'plug and play' concept plus single installation configuration; no additional piping is required since indoor and outdoor sides are pre-connected
- Factory pre-charged refrigerant ensures clean and efficient operation
- Belt driven fan enables air volume and static pressure to be adjusted as required.
- Flat top unit design allows maximum use of warehouse and container space
- High efficiency and reliable scroll compressor
- Anti-corrosion treated coil



UATYP-AY1(B)



Remote control

Outdoor unit					UATYP	850AY1B	10AY1	12AY1
Cooling capacity	Nom.				kW	78.6	101.110	109.609
Heating capacity	Nom.				kW	87.78	102.290	126.314
Power input	Cooling	Nom.			kW	36.10	43.170	48.200
	Heating	Nom.			kW	32.10	41.670	46.800
EER						2.18	2.34	2.27
COP						2.73	2.45	2.70
Evaporator	Air flow rate	Cooling			m^3/min	263.33	312	354
	External static pressure				Pa	294		
Evaporator piping connections	Condensation drain size	OD			mm	25.40		
Condenser	Dimensions	Unit	Height		mm	1,735	1,974	
			Width		mm	2,250	2,252	
			Depth		mm	2,800	3,180	
	Weight	Unit			kg	1,350	1,510	1,600
	Casing	Colour				Light grey		
		Material				-	Electro-galvanised mild steel	
	Air flow rate	Cooling			cfm	-	20,000	
	Operation range	Cooling	Min.~Max.		°CDB	20~46		
		Heating	Min.~Max.		°CWB	-15~20		
	Sound power level	Nom.			dBA	-		
	Refrigerant	Type / GWP				R-407C / 1,773.9	R-407C / 1,773.9	R-407C / 1,773.9
		Charge			kg	9.6	13.5	20.0
		Charge			TCO_2Eq	17.0	23.9	35.5
Power supply	Phase/Frequency/Voltage				Hz/V	3N~/50/380-415	3~/50/380-415	



VRV the solution for the commercial sector

Daikin's VRV technology leads the way in customisation to match individual commercial building requirements in comfort and energy efficiency. Flexible to cover all applications and climate conditions, VRV has the unique products that make the difference for you and your customers.

VRV

Medium to large commercial applications

Why choose Daikin VRV? 202

Total solution concept 210

VRV outdoor - products overview 214

VRV indoor - products overview 234

VRV indoor - benefits overview 236

VRV outdoor units

Heat recovery

NEW REYQ-T 216

Heat pump

RYYQ-T / RXYQ-T 218
RXYSQ-P8V1/P8Y1 221
RTSYQ-PA 222
RXYCQ-A 223

Replacement VRV

RQCEQ-P 226
RXYQQ-T / RQYQ-P 227

Water-cooled VRV

RWEYQ-T 229

Branch selector (BS box)

BS1Q-A 230
BS-Q14A 230
BSVQ-P9B 231
BSV4/6Q-PV 231

VRV indoor units

Ceiling mounted cassette units

FXFQ-A 238
FXZQ-A 240
FXCQ-A 242
FXKQ-MA 243

Concealed ceiling units

FXDQ-M9 244
FXDQ-A 245
NEW FXSQ-A 246
FXMQ-P7 / FXMQ-MA 247

Wall mounted unit

FXAQ-P 249

Ceiling suspended units

FXHQ-A 250
FXUQ-A 251

Floor standing units

NEW FXNQ-A 252
FXLQ-P 253

Hot water

HXY-A 254
HXHD-A 255
Accessories for hot water 256

For more information on Options & Accessories, please refer to page 448 of this catalogue.

VRV IV sets the standard … again



Why choose VRV?

- Over 90 years of expertise in heat pumps
- Inventor and market leader of VRV systems since 1982
- Designed for and produced in Europe
- Unique outdoor unit range covering all applications and climate conditions
- Unique products that make the difference:
  - VRV IV with Variable Refrigerant Temperature and continuous heating
  - Round flow cassette
  - Fully flat cassette
  - 15 class units
  - Daikin Emura
  - 4-way blow ceiling suspended cassette
  - high temperature hot water hydrobox
  - plug&play AHU connection, …

The VRV air conditioning system is the world's first individual air conditioning system with variable refrigerant flow control and was commercialised by Daikin in 1982.
VRV is the trademark of Dakin Industries Ltd, which is derived from the technology we call "variable refrigerant volume".



VRV IV standards

› **Variable refrigerant temperature**
. Customize your VRV for best seasonal efficiency & comfort
. Up to 28% higher seasonal efficiency (ESEER)
. First weather dependent VRV
. No more cold draft by supply of high outblow temperatures

› **Continuous comfort**
. Makes VRV IV the best alternative to traditional heating systems

› **VRV configurator**
. software for the fastest and most accurate commissioning, configuration and customisation

› **Total solution**
. one supplier for heating, cooling, ventilation, hot water, Biddle air curtains and control
. combine both residential and VRV indoor units

› **Free combination of outdoor units to meet installation space or efficiency requirements**

› **Outdoor unit display for quick on-site settings**

Variable Refrigerant Temperature

Heat pump
Heat recovery
Replacement
Water cooled



Benefits for the consultant

Daikin's VRV IV technology leads the way in customisation to match individual building requirements in comfort and energy, facilitating reduced capital and running costs

› Ecological design
› Ideal for reaching top BREEAM/EPDB levels
› No more cold draughts with higher evaporation temperatures up to 11 or 16°C, making VRV IV an ideal alternative to water-based systems
› Unique specification for monovalent heating

Benefits for the installer

Daikin VRV IV sets the standard with latest technology and time saving commissioning & servicing

› Simplified and time saving commissioning with VRV configurator
› Remote refrigerant containment check
› One supplier = one point of contact
› Many options to meet customer requirements

Benefits for the owner

VRV IV is the ultimate in customised comfort and intelligent control tailored to your individual needs and to maximise energy efficiency

› Annual cost savings up to 28% (compared with VRV III)
› No more cold draughts with variable refrigerant temperature
› Single point of contact for the design and maintenance of your climate control system
› Integrated system allows maximum energy efficiency for the end user
› Multiple systems can be managed in exactly the same way for key accounts


NEW VRV IV heat recovery technologies


Improved efficiency

› In heat recovery operation VRV IV is up to 15% more efficient than VRV III
› Overall efficiency is increased with up to 28% thanks to Variable Refrigerant Temperature
› Heat can be re-used to create hot water 'for free'

Maximum comfort

A VRV heat recovery system allows simultaneous cooling
and heating.
› For hotel owners it means a perfect environment for guests as they can freely choose between cooling or heating.
› For offices it means a perfect working climate both for tenants facing south and north.





HXY-A

HXHD-A


Advantages of 3-pipe technology

More free heat


Daikin 3-pipe technology needs less energy to recover heat, meaning significant better efficiency during heat recovery mode. Our system can recover the heat at low condensing temperature because it has dedicated gas, liquid and discharge pipes.

In a 2-pipe system gas and liquid travel as a mixture so the condensing temperature needs to be higher in order to separate the mixed gas and liquid refrigerant. The higher condensing temperature means more energy is used to recover heat resulting in lower efficiency.

*only for heat pump series



More efficient due to lower pressure drop



Smooth refrigerant flow in 3-pipe system thanks to 2 smaller gas pipes leading to higher energy efficiency

Disturbed refrigerant flow in large gas pipe on 2-pipe system leading to bigger pressure drop

Maximum design flexibility and installation speed

- Unique range of single and multi BS boxes for flexible and fast design
- Major reduction in installation time thanks to wide range, compact size and light weight multi BS boxes

Single port




BS1Q10,16,25A

Multi port: 4 – 6 – 8 – 10 – 12 – 16



BS4Q14A



BS6,8Q14A



BS10,12Q14A



BS16Q14A

But VRV is more…
standard VRV features


Low running costs

› Precise zone control and inverter technology
› Up to 50% savings with intelligent sensors and auto cleaning cassette
› Running costs of a water-based fan coil unit can be 40 to 72% higher compared to a VRV heat recovery system

Great design flexibility

› Long refrigerant piping
› Compact units require up to 29% less space than traditional water based systems, offering more lettable space
› Zone by zone phased installation tailored to the needs of the building
› Modular approach to better balance different heat load throughout a building
› Outdoor units can be installed outdoors or indoors
› Widest range of indoor units to fit customer needs
› Solutions for every climate, from -25 to +52°C
› Special VRV S-series designed for small capacities


indoor installation
ESP up to
78pa





Easy installation and servicing

- Automatic testing and refrigerant charging
- Auto adressing of indoor units
- Easy servicing and F-gas compliance with remote refrigerant containment check
- Plug & play connection for VRV to Daikin air handling units, the easiest solution with only one point of contact



High comfort levels


- Individual control and simultaneous cooling and heating for perfect personal environment
- Low indoor sound levels down to 19 dBA
- Intelligent sensors and high outblow temperatures prevent cold draughts
- Uniquely designed units:
  Daikin Emura, Nexura and Fully flat cassette



DAIKIN emura




nexura



FULLY FLAT CASSETTE



- CO_2 sensor in combination with Daikin ventilation (VAM, VKM) units ensures fresh air, while preventing energy losses from over-ventilation




Ease of use

- Smart energy management optimises the performance automatically 24/7



Marketing tools





› Visit the website:
http://www.daikineurope.com/vrv-iv
› Download simulation or selection software: Go to extranet.daikineurope.com > Software downloads > sales supporting apps


Solutions seasonal simulator

With this software tool you can simulate and the seasonal efficiency, the annual power consumption and CO_2 emission for a given climate, load profile (cooling, heating, heat recovery, covalent, bivalent...) and (combination of) system(s). With its intuitive and graphical appealing interface, a simulation can be made in a matter of minutes.

The solution basket system enables you to compare the results of several system configurations. Optionally, a return on investment calculation can be made. The outcome of the simulation can be exported to a printable report. The tool is available both for Windows PC and Tablet (iPad).

Xpress, Quick Quotation tool

Xpress is a software tool that allows creating on the spot quotations for a Daikin VRV system. It provides a result in 6 steps to enable a professional budget quotation:




› Select indoor units
› Connect outdoor units to indoor units
› Automatic generation of piping diagram with joints
› Automatic generation of wiring diagram
› Select possible centralised control systems
› Visualise result in MS Word, MS Excel and AutoCAD


Ventilation Xpress

Selection tool for ventilation devices (VAM, VKM). The selection is based on given supply/extract airflows (including fresh up), and given ESP of the supply/extract ducting:

› Determines size of electrical heaters
› Visualization of psychrometric chart
› Visualization of selected configuration
› Required field settings mentioned in the report

VRV Pro, Design tool





The VRV Pro selection program is a true VRV design tool. The program enables VRV air conditioning systems to be engineered in a precise and economical way, taking into account the realtime thermal properties of any building. By calculating annual energy consumptions, it gives the designer the possibility to make accurate selections and **get competitive quotations** for each project. Moreover, it ensures optimum operating cycles and maximum energy efficiency.

Your References

Porta Fira

"This project reinforces Daikin's position as a leader in the air conditioning of large-scale structures, able to provide solutions that stand out not only for their accuracy and reliability, but also for their energy efficiency."





The Range

"We were very happy to work with Daikin UK to incorporate one of the latest fully integrated renewable systems that would provide heating, hot water, and air conditioning, allowing The Range at Warrington to have a fully controllable system with operation flexibility according to requirements."
Brad Hurter, CDS Group





For more information, please contact your affiliate/distributor.


Windows95, Windows98, WindowsNT, Windows2000, WindowsXP, Windows Vista and Windows 7 are registered trademarks of Microsoft corporation.

The VRV total solution

Many buildings today typically operate quite separate systems for heating, cooling, refrigeration and hot water. As a result, a huge amount of energy is wasted.
To provide a much more efficient alternative, VRV technology has been developed into a total solution managing up to 50% of a buildings energy consumption giving large potential to cost saving.



Manage up to 50% of your building's energy consumption



Source: EIA; Commercial buildings Energy consumption survey

One system, multiple applications



For hotels, offices, retail, home, ...

Heating & cooling







› Combine VRV indoor units with stylish indoor units in one system.
› New round flow cassette sets the standard for efficiency and comfort.

Intelligent control systems





› Mini BMS with integration of Daikin and third party equipment
› Integration with intelligent control solutions with energy management tools to reduce running costs

Low temperature hydrobox for highly efficient space heating through



› Underfloor heating
› Low temperature radiators
› Heat pump convector
› Hot water from 25 to 45°C


High temperature hydrobox* for efficient hot water production for



› Showers
› Sinks
› Tapwater for cleaning
› Hot water from 25 to 80°C

*only for connection to VRV heat recovery

Biddle air curtain



› A highly efficient solution for doorway climate separation

Ventilation



› Combined fresh air treatment and air conditioning





SKY TOWER, OFFICE AND RESIDENTIAL PROJECT;
159 OUTDOOR UNITS, 653 INDOOR UNITS



VRV-S SERIES



PARK PHI
BREEAM ® EXCELLENT OFFICE
BUILDING WATERCOOLED VRV



HOTEL LE PIGONNET, 8 REPLACEMENT VRV



CINEMEERSE, CINEMA, 12 OUTDOOR UNITS WITH AHU

Products overview VRV

Type	Model	Product ame	4	5	6	8	10	12	13	14	16	18	20	22	24	26	28	30
Air cooled	VRV IV heat recovery - Best efficiency & comfort solution - Fully integrated solution with heat recovery for maximum efficiency with COPs of up to 8 ! - Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains - "Free" heating and hot water through heat recovery - The perfect personal comfort for guests/tenants via simultaneous cooling and heating - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature and continuous heating - Allows technical cooling - Widest range of BS boxes on the market	REYQ-T VRV IV				●	●	●		●	●	●	●						
							○		○		○	○	○	○	○	○	○	○
	VRV IV heat pump with continuous heating - Daikin's optimum solution with top comfort - Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains - Connectable to stylish indoor units (Daikin Emura, Nexura) - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature and continuous heating	RYYQ-T VRV IV				●	●	●		●	●	●	●						
											○	○	○	○	○	○	○	○
	VRV IV heat pump without continuous heating - Daikin's solution for comfort & low energy consumption - Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains - Connectable to stylish indoor units (Daikin Emura, Nexura) - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	RXYQ-T VRV IV				●	●	●		●	●	●	●						
											○	○	○	○	○	○	○	○
	VRVIII-S - Space saving solution without compromising on efficiency - For residential and light commercial applications - Space saving design - Either connect VRV of stylish indoor units (Daikin Emura, Nexura)	RXYSQ-P8V1/P8Y1 VRV III-S	●	●	●													
	VRVIV-S series - Space saving solution without compromising on efficiency - Space saving trunk design for flexible installation - Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains - Either connect VRV of stylish indoor units (Daikin Emura, Nexura) - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	VRV IV S-series	●	●	●	●	●	●										
	VRVIV-S series compact - The most compact VRV - Compact and lightweight single fan design saves space and is easy to install - Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains - Either connect VRV of stylish indoor units (Daikin Emura, Nexura) - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	VRV IV S-series		●	●													
	VRV III heat pump, optimised for heating - Where heating is priority without compromising on efficiency - Suitable for single source heating - Extended operation range down to -25°C in heating - Stable heating capacity and high efficiencies at low ambient temperatures	RTSYQ-PA VRV III-C					○			○	○		○					
	VRV Classic - Classic VRV configuration - For standard cooling & heating requirements - Connectable to VRV indoor units, controls and ventilation	RXYCQ-A VRV Classic				○	○	○		○	○	○	○					
	Replacement VRV heat recovery - Quick & quality replacement for R-22 and R-407C systems - Cost-effective and fast replacement through re-use of exisiting piping - Up to 40% more efficient than R-22 systems - No interuption of daily business while replacing your system - Replace Daikin and other manufacturers systems safely	RQCEQ-P VRV III-Q					○		○		○	○	○	○	○	○	○	○
	Replacement VRV heat pump - Quick & quality replacement for R-22 and R-407C systems - Cost-effective and fast replacement through re-use of exisiting piping - Up to 80% more efficient than R-22 systems - No interuption of daily business while replacing your system - Replace Daikin and other manufacturers systems safely - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature	RXYQQ-T VRV IV Q-series		●		●	●	●		●	●	●	●					
											○	○	○	○	○	○	○	○
Water cooled	Water cooled VRV IV - Ideal for high rise buildings, using water as heat source - Reduced CO_2 emissions thanks to the use of geothermal energy as a renewable energy source - No need for an external heating or cooling source when used in geothermal mode - Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains - Compact & lightweight design can be stacked for maximum space saving - Incorporates VRV IV standards & technologies such as Variable Refrigerant temperature - Variable Water Flow control option increases flexibility and control	RWEYQ-T VRV IV W-series				●	●												
											○	○	○		○	○	○	○

● Single unit
○ Multi combination

Capacity (HP)												Description / Combination	**VRV** indoor units	**Residential** indoor units	**LT Hydrobox** HXY-A	**HT Hydrobox** HXHD-A	HRV units VAM-, VKM-	**AHU connection** EKEXV- + EKEQMCB	**AHU connection** EKEXV- + EKEQFCB	**Air curtains** CYV-DK-	Remarks
32	34	36	38	40	42	44	46	48	50	52	54										
												VRV IV Heat Recovery REYQ-T	○	×	○	○	○	○	×	○	Standard total system connection ratio limit: 50 ~ 130%
												with only VRV indoor units	✓								
												with LT/HT Hydroboxes	✓		✓	✓	✓				• Max 32 indoor units, even on 16HP and larger systems • Total system connection ratio up to 200% possible
												HRV units VAM-, VKM-	✓		✓	✓	✓	✓		✓	
●	●	●	●	●	●	●	●	●	●	●	●	AHU connection EKEXV + EKEQMCB	✓				✓	✓		✓	• Dedicated systems (with only ventilation units) not allowed - a mix with standard VRV indoor units is allways neccessary
												Biddle air curtain CYV-DK-	✓				✓	✓		✓	
												VRV IV Heat Pump RYYQ-T / RXYQ-T	○	○	○	×	○	○	○	○	Standard total system connection ratio limit: 50 ~ 130%
												with only VRV indoor units	✓								• 200% total system connection ratio possible under special circumstances
												with residential indoor units	✓	✓			✓				• Only single-module systems (RYYQ 8~20 T / RXYQ 8~20 T) • Max 32 indoor units, even on 16HP, 18HP and 20HP systems
●	●	●	●	●	●	●	●	●	●	●	●	with LT Hydroboxes	✓		✓		✓				• Max 32 indoor units, even on 16HP and larger systems • Contact Daikin in case of multi-module systems (>20HP)
												HRV units VAM-, VKM-	✓	✓	✓		✓	✓		✓	
												AHU connection EKEXV + EKEQMCB	✓				✓	✓		✓	
												AHU connection EKEXV + EKEQMCB							✓		
●	●	●	●	●	●	●	●	●	●	●	●	Biddle air curtain CYV-DK-	✓				✓	✓		✓	
												VRV III-S Mini VRV RXYSQ-P8	○	○	×	×	○	○	×	○	Standard total system connection ratio limit: 50 ~ 130%
												with VRV indoor units	✓				✓	✓		✓	
												with Split indoor units		✓							• Total system connection ratio in terms of VRV indexes: 56 ~ 145%
												VRV IV-S Mini VRV	○	○	×	×	○	○	×	○	Standard total system connection ratio limit: 50 ~ 130%
												with VRV indoor units	✓				✓	✓		✓	
												with Split indoor units		✓							• Total system connection ratio in terms of VRV indexes: 56 ~ 145%
												VRV IV-S Mini VRV	○	○	×	×	○	○	×	○	Standard total system connection ratio limit: 50 ~ 130%
												with VRV indoor units	✓				✓	✓		✓	
												with Split indoor units		✓							• Total system connection ratio in terms of VRV indexes: 56 ~ 145%
												VRV III Cold Region RTSYQ-PA	✓	×	×	×	✓	✓	×	✓	Standard total system connection ratio limit: 50 ~ 130%
												VRV Classic RXYCQ-A	✓	×	×	×	✓	×	×	×	Standard total system connection ratio limit: 50 ~ 120% • In case of using at least one FXFQ20~25 indoor units on 8HP or 10HP models, the maximum connection ratio is 100%.
												VRV III-Q Replacement H/R RQCEQ-P	✓	×	×	×	✓	×	×	×	Standard total system connection ratio limit: 50 ~ 130%
●	●	●	●	●	●							**VRV IV-Q Replacement H/P** RXYQQ-T	✓	×	×	×	✓	✓	×	✓	Standard total system connection ratio limit: 50 ~ 130%
												VRV IV-W Water-cooled VRV RWEYQ-T	✓	×	×	×	✓	✓	×	✓	Standard total system connection ratio limit: 50 ~ 130%

○ ... connection of indoor unit possible, but not neccessarily simultaneously with other allowed indoor units

✓ ... connection of indoor unit possible even simultaneously with other checked units in the same row

× ... connection of indoor not possible on this outdoor unit system

VRV IV heat recovery

Best efficiency & comfort solution

- Fully integrated solution with heat recovery for maximum efficiency with COPs of up to 8 !
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains
- "Free" heating and hot water through heat recovery
- The perfect personal comfort for guests/tenants via simultaneous cooling and heating
- Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, continuous heating, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB, new DC fan motor (see page 203)
- Operation range down to -20°C for technical cooling operation such as server rooms
- Contains all standard VRV features (see page 206)

Outdoor system				**REYQ**	**8T**	**10T**	**12T**	**14T**	**16T**	**18T**	**20T**
Capacity range				HP	8	10	12	14	16	18	20
Cooling capacity	Nom.			kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0
Heating capacity	Nom.			kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0
	Max.			kW	25.0	31.5	37.5	45.0	50.0	56.5	63.0
Power input - 50Hz	Cooling	Nom.		kW	5.31	7.15	9.23	10.7	12.8	15.2	18.6
	Heating	Nom.		kW	4.75	6.29	8.05	9.60	11.2	12.3	14.9
		Max.		kW	5.51	7.38	9.43	11.3	12.9	14.3	17.5
EER					4.22	3.92	3.63	3.74	3.52	3.32	3.01
COP - Max.					4.54	4.27	3.98		3.88	3.95	3.60
COP - Nom.					4.72	4.45	4.16	4.17	4.02	4.10	3.76
ESEER - Automatic					7.41	7.37	6.84	7.05	6.63	6.26	5.68
ESEER - Standard					6.25	5.78	5.36	5.45	5.14	4.84	4.39
Maximum number of connectable indoor units					64 (1)						
Indoor index connection	Min.				100	125	150	175	200	225	250
	Nom.				200	250	300	350	400	450	500
	Max.				260	325	390	455	520	585	650
Dimensions	Unit	HeightxWidthxDepth		mm	1,685x930x765			1,685x1,240x765			
Weight	Unit			kg	210	218		304	305	337	
Fan	Air flow rate	Cooling	Nom.	m^3/min	162	175	185	223	260	251	261
Sound power level	Cooling	Nom.		dBA	78	79	81		86		88
Sound pressure level	Cooling	Nom.		dBA	58		61		64	65	66
Operation range	Cooling	Min.~Max.		°CDB	-5.0~43.0						
	Heating	Min.~Max.		°CWB	-20~15.5						
Refrigerant	Type / GWP				R-410A / 2,087.5						
	Charge			kg	9.7	9.8	9.9	11.8			
	Charge			TCO_2Eq	20.2	20.5	20.7	24.6			
Piping connections	Liquid	OD		mm	9.52		12.7			15.9	
	Gas	OD		mm	19.1	22.2	28.6				
	Discharge gas	OD		mm	15.9	19.1		22.2			28.6
	Total piping length	System	Actual	m	1,000						
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/380-415						
Current - 50Hz	Maximum fuse amps (MFA)			A	20	25		32	40		50

Outdoor system				**REYQ**	**10T**	**13T**	**16T**	**18T**	**20T**	**22T**	**24T**	**26T**	**28T**	**30T**	**32T**
System	Outdoor unit module 1				REMQ5T			REYQ8T		REYQ10T	REYQ8T		REYQ12T		REYQ16T
	Outdoor unit module 2				REMQ5T	REYQ8T		REYQ10T	REYQ12T		REYQ16T	REYQ14T	REYQ16T	REYQ18T	REYQ16T
Capacity range				HP	10	13	16	18	20	22	24	26	28	30	32
Cooling capacity	Nom.			kW	28.0	36.4	44.8	50.4	55.9	61.5	67.4	73.5	78.5	83.9	90.0
Heating capacity	Nom.			kW	28.0	36.4	44.8	50.4	55.9	61.5	67.4	73.5	78.5	83.9	90.0
	Max.			kW	32.0	41.0	50.0	56.5	62.5	69.0	75.0	82.5	87.5	94.0	100.0
Power input - 50Hz	Cooling	Nom.		kW	6.34	8.48	10.62	12.46	14.54	16.38	18.11	19.93	22.03	24.43	25.6
	Heating	Nom.		kW	5.42	7.46	9.50	11.04	12.80	14.34	15.95	17.65	19.25	20.35	22.4
		Max.		kW	6.50	8.76	11.02	12.89	14.94	16.81	18.41	20.73	22.33	23.73	25.8
EER					4.42	4.29	4.22	4.04	3.84	3.75	3.72	3.69	3.56	3.43	3.52
COP - Max.					4.92	4.68	4.54	4.38	4.18	4.10	4.07	3.98	3.92	3.96	3.88
COP - Nom.					5.17	4.88	4.72	4.57	4.37	4.29	4.23	4.16	4.08	4.12	4.02
ESEER - Automatic					7.77	7.54	7.41	7.38	7.06	7.07	6.87	6.95	6.72	6.48	6.63
ESEER - Standard					6.55	6.36	6.25	5.98	5.68	5.54	5.46	5.41	5.23	5.03	5.14
Maximum number of connectable indoor units					64										
Indoor index connection	Min.				125	162.5	200	225	250	275	300	325	350	375	400
	Nom.				250	325.0	400	450	500	550	600	650	700	750	800
	Max.				325	422.5	520	585	650	715	780	845	910	975	1,040
Piping connections	Liquid	OD		mm	9.52	12.7		15.9				19.1			
	Gas	OD		mm	22.2	28.6					34.9				
	Discharge gas	OD		mm	19.1		22.2		28.6						
	Total piping length	System	Actual	m	500				1,000						
Current - 50Hz	Maximum fuse amps (MFA)			A	40			50	63						80
Continuous heating					v										



REYQ-T

Outdoor system					REYQ	34T	36T	38T	40T	42T	44T	46T	48T	50T	52T	54T
System	Outdoor unit module 1					REYQ16T		REYQ8T	REYQ10T		REYQ12T	REYQ14T	REYQ16T			REYQ18T
	Outdoor unit module 2					REYQ18T	REYQ20T	REYQ12T		REYQ16T					REYQ18T	
	Outdoor unit module 3					-		REYQ18T		REYQ16T					REYQ18T	
Capacity range					HP	34	36	38	40	42	44	46	48	50	52	54
Cooling capacity	Nom.				kW	95.4	101.0	106.3	111.9	118.0	123.5	130.0	135.0	140.4	145.8	151.2
Heating capacity	Nom.				kW	95.4	101.0	106.3	111.9	118.0	123.5	130.0	135.0	140.4	145.8	151.2
	Max.				kW	106.5	113.0	119.0	125.5	131.5	137.5	145.0	150.0	156.5	163.0	169.5
Power input - 50Hz	Cooling	Nom.			kW	28.0	31.4	29.74	31.58	32.75	34.83	36.3	38.4	40.8	43.2	45.6
	Heating	Nom.			kW	23.5	26.1	25.10	26.64	28.69	30.45	32.00	33.6	34.7	35.8	36.9
		Max.			kW	27.2	30.4	29.24	31.11	33.18	35.23	37.1	38.7	40.1	41.5	42.9
EER						3.41	3.22	3.57	3.54	3.60	3.55	3.58	3.52	3.44	3.38	3.32
COP - Max.						3.92	3.72	4.07	4.03	3.96	3.90	3.91	3.88	3.90	3.93	3.95
COP - Nom.						4.06	3.87	4.24	4.20	4.11	4.06		4.02	4.05	4.07	4.10
ESEER - Automatic						6.43	6.06	6.66	6.68	6.79	6.68	6.75	6.63	6.49	6.37	6.26
ESEER - Standard						4.97	4.70	5.25	5.20	5.28	5.20	5.23	5.14	5.03	4.93	4.84
Maximum number of connectable indoor units						64										
Indoor index connection	Min.					425	450	475	500	525	550	575	600	625	650	675
	Nom.					850	900	950	1,000	1,050	1,100	1,150	1,200	1,250	1,300	1,350
	Max.					1,105	1,170	1,235	1,300	1,365	1,430	1,495	1,560	1,625	1,690	1,755
Piping connections	Liquid	OD			mm	19.1										
	Gas	OD			mm	34.9	41.3									
	Discharge gas	OD			mm	28.6		34.9								
	Total piping length	System	Actual		m	1,000										
Current - 50Hz	Maximum fuse amps (MFA)				A	80			100			125				
Continuous heating						v										

Outdoor unit module				REMQ	5T
Dimensions	Unit	HeightxWidthxDepth		mm	1,685x930x765
Weight	Unit			kg	210
Fan	Air flow rate	Cooling	Nom.	m^3/min	162
Sound power level	Cooling	Nom.		dBA	77
Sound pressure level	Cooling	Nom.		dBA	56
Operation range	Cooling	Min.~Max.		°CDB	-5.0~43.0
	Heating	Min.~Max.		°CWB	-20~15.5
Refrigerant	Type / GWP				R-410A / 2,087.5
	Charge			kg	9.7
	Charge			TCO_2Eq	20.2
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/380-415
Current - 50Hz	Maximum fuse amps (MFA)			A	20

(1) Actual number of connectable indoor units depends on the indoor unit type (VRV indoor, Hydrobox, RA indoor, etc.) and the connection ratio restriction for the system (50% <= CR <= 130%) (2) Technical cooling setting, refer to the installation manual for more information

VRV IV heat pump

Daikin's optimum solution with top comfort

- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains
- Wide range of indoor units: possibility to combine VRV with stylish indoor units (Daikin Emura, Nexura, ...)
- Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, continuous heating, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB, new DC fan motor (see page 203)
- Available as heating only by irreversible field setting
- Contains all standard VRV features (see page 206)

Outdoor system				**RYYQ/RXYQ**	**8T**	**10T**	**12T**	**14T**	**16T**	**18T**	**20T**
Capacity range				HP	8	10	12	14	16	18	20
Cooling capacity	Nom.			kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0
Heating capacity	Nom.			kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0
	Max.			kW	25.0	31.5	37.5	45.0	50.0	56.5	63.0
Power input - 50Hz	Cooling	Nom.		kW	5.21	7.29	8.98	11.0	13.0	15.0	18.5
	Heating	Nom.		kW	4.75	6.29	7.77	9.52	11.1	12.6	14.5
		Max.		kW	5.51	7.38	9.10	11.2	12.8	14.6	17.0
EER					4.30	3.84	3.73	3.64	3.46	3.36	3.03
ESEER					6.37 (1) / 7.53 (2)	5.67 (1) / 7.20 (2)	5.50 (1) / 6.96 (2)	5.31 (1) / 6.83 (2)	5.05 (1) / 6.50 (2)	4.97 (1) / 6.38 (2)	4.42 (1) / 5.67 (2)
COP					4.72 (3) / 4.54 (4)	4.45 (3) / 4.27 (4)	4.31 (3) / 4.12 (4)	4.20 (3) / 4.02 (4)	4.05 (3) / 3.91 (4)	4.00 (3) / 3.87 (4)	3.86 (3) / 3.71 (4)
Maximum number of connectable indoor units					64 (5)						
Indoor index connection	Min.				100	125	150	175	200	225	250
	Nom.				200	250	300	350	400	450	500
	Max.				260	325	390	455	520	585	650
Dimensions	Unit	HeightxWidthxDepth		mm	1,685x930x765			1,685x1,240x765			
Weight	Unit			kg	261	268		364		398	
Fan	Air flow rate	Cooling	Nom.	m^3/min	162	175	185	223	260	251	261
Sound power level	Cooling	Nom.		dBA	78	79	81		86		88
Sound pressure level	Cooling	Nom.		dBA	58		61		64	65	66
Operation range	Cooling	Min.~Max.		°CDB	-5~43						
	Heating	Min.~Max.		°CWB	-20~15.5						
Refrigerant	Type / GWP				R-410A / 2,087.5						
	Charge			kg	5.9	6	6.3	10.3	10.4	11.7	11.8
	Charge			TCO_2Eq	12.3	12.5	13.2	21.5	21.7	24.4	24.6
Piping connections	Liquid	OD		mm	9.52		12.7			15.9	
	Gas	OD		mm	19.1	22.2	28.6				
	Total piping length	System	Actual	m	1,000						
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/380-415						
Current - 50Hz	Maximum fuse amps (MFA)			A	20	25	32		40		50

Outdoor system				**RYYQ / RXYQ**	**22T**	**24T**	**26T**	**28T**	**30T**	**32T**	**34T**	**36T**	**38T**
System	Outdoor unit module 1				10	8		12			16		8
	Outdoor unit module 2				12	16	14	16	18	16	18	20	10
	Outdoor unit module 3				-								20
Capacity range				HP	22	24	26	28	30	32	34	36	38
Cooling capacity	Nom.			kW	61.5	67.4	73.5	78.5	83.5	90.0	95.0	101.0	106.0
Heating capacity	Nom.			kW	61.5	67.4	73.5	78.5	83.5	90.0	95.0	101.0	106.4
	Max.			kW	69.0	75.0	82.5	87.5	93.5	100.0	106.0	113.0	119.5
Power input - 50Hz	Cooling	Nom.		kW	16.27	18.2	20.0	22.0	23.7	26.0	27.7	31.5	31.0
	Heating	Nom.		kW	14.06	15.85	17.29	18.87	20.17	22.2	23.5	25.6	25.54
		Max.		kW	16.48	18.31	20.30	21.90	23.50	25.6	27.2	29.8	29.89
EER					3.77	3.70	3.68	3.57	3.52	3.46	3.43	3.21	3.42
ESEER					5.58 (1) / 7.07 (2)	5.42 (1) / 6.81 (2)	5.39 (1) / 6.89 (2)	5.23 (1) / 6.69 (2)	5.17 (1) / 6.60 (2)	5.05 (1) / 6.50 (2)	5.01 (1) / 6.44 (2)	4.68 (1) / 6.02 (2)	5.03 (1) / 6.36 (2)
COP					4.37 (3) / 4.19 (4)	4.25 (3) / 4.10 (4)	4.25 (3) / 4.06 (4)	4.16 (3) / 4.00 (4)	4.14 (3) / 3.98 (4)	4.05 (3) / 3.91 (4)	4.04 (3) / 3.90 (4)	3.95 (3) / 3.79 (4)	4.17 (3) / 4.00 (4)
Maximum number of connectable indoor units					64 (5)								
Indoor index connection	Min.				275	300	325	350	375	400	425	450	475
	Nom.				550	600	650	700	750	800	850	900	950
	Max.				715	780	845	910	975	1,040	1,105	1,170	1,235
Piping connections	Liquid	OD		mm	15.9		19.1						
	Gas	OD		mm	28.6	34.9						41.3	
	Total piping length	System	Actual	m	1,000								
Current - 50Hz	Maximum fuse amps (MFA)			A	63				80				100



RYYQ8-12T
RXYQ8-12T

Outdoor system				RYYQ / RXYQ	40T	42T	44T	46T	48T	50T	52T	54T
System	Outdoor unit module 1				10		12	14		16		18
	Outdoor unit module 2				12	16					18	
	Outdoor unit module 3				18	16				18		
Capacity range				HP	40	42	44	46	48	50	52	54
Cooling capacity	Nom.			kW	111.5	118.0	123.5	130.0	135.0	140.0	145.0	150.0
Heating capacity	Nom.			kW	111.5	118.0	123.5	130.0	135.0	140.0	145.0	150.0
	Max.			kW	125.0	131.5	137.5	145.0	150.0	156.0	162.0	168.0
Power input - 50Hz	Cooling	Nom.		kW	31.0	33.3	35.0	37.0	39.0	40.7	42.4	44.1
	Heating	Nom.		kW	26.46	28.49	29.97	31.72	33.3	34.6	35.9	37.2
		Max.		kW	30.88	32.98	34.70	36.8	38.4	40.0	41.6	43.2
EER					3.61	3.54		3.51	3.46	3.44	3.42	3.40
ESEER					5.29 (1) / 6.74 (2)	5.19 (1) / 6.65 (2)	5.17 (1) / 6.62 (2)	5.13 (1) / 6.60 (2)	5.05 (1) / 6.50 (2)	5.02 (1) / 6.46 (2)	4.99 (1) / 6.42 (2)	4.97 (1) / 6.38 (2)
COP					4.21 (3) / 4.05 (4)	4.14 (3) / 3.99 (4)	4.12 (3) / 3.96 (4)	4.10 (3) / 3.94 (4)	4.05 (3) / 3.91 (4)	4.05 (3) / 3.90 (4)	4.04 (3) / 3.89 (4)	4.03 (3) / 3.89 (4)
Maximum number of connectable indoor units					64 (5)							
Indoor index connection	Min.				500	525	550	575	600	625	650	675
	Nom.				1,000	1,050	1,100	1,150	1,200	1,250	1,300	1,350
	Max.				1,300	1,365	1,430	1,495	1,560	1,625	1,690	1,755
Piping connections	Liquid	OD		mm	19.1							
	Gas	OD		mm	41.3							
	Total piping length	System	Actual	m	1,000							
Current - 50Hz	Maximum fuse amps (MFA)			A	100				125			

Outdoor unit module for RYYQ combinations				RYMQ	8T	10T	12T	14T	16T	18T	20T
Dimensions	Unit	HeightxWidthxDepth		mm	1,685x930x765			1,685x1,240x765			
Weight	Unit			kg	188	195		309		319	
Fan	Air flow rate	Cooling	Nom.	m^3/min	162	175	185	223	260	251	261
Sound power level	Cooling	Nom.		dBA	78	79	81		86		88
Sound pressure level	Cooling	Nom.		dBA	58		61		64	65	66
Operation range	Cooling	Min.~Max.		°CDB	-5~43						
	Heating	Min.~Max.		°CWB	-20~15.5						
Refrigerant	Type / GWP				R-410A / 2,087.5						
	Charge			kg	5.9	6	6.3	10.3	10.4	11.7	11.8
	Charge			TCO_2Eq	12.3	12.5	13.2	21.5	21.7	24.4	24.6
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/380-415						
Current - 50Hz	Maximum fuse amps (MFA)			A	20	25	32		40		50

(1) The STANDARD ESEER value corresponds with normal VRV4 Heat Pump operation, not taking into account advanced energy saving operation functionality (2) The AUTOMATIC SEER value corresponds with normal VRV4 Heat Pump operation, taking into account advanced energy saving operation functionality (variable refrigerant temperature control operation) (3) COP nominal; (4) COP maximum
(5) Actual number of connectable indoor units depends on the indoor unit type (VRV indoor, Hydrobox, RA indoor, etc.) and the connection ratio restriction for the system (50% <= CR <= 130%)



VRV IV S-series

Space saving solution without compromising on efficiency

In 2015 our successful mini VRV range gets a thorough update to make it even better suited for light commercial applications where space is limited and performance expectations are high.

VRV IV S-series

Variable Refrigerant Temperature





- Variable Refrigerant Temperature
- Connect a wide range of up to 9 indoor units: either connect VRV or stylish indoor units (Daikin Emura, Nexura, …)
- All indoor units can be individually controlled
- Connects to all VRV control, ventilation, air handling units and Biddle air curtains
- Space saving design
- More flexibility through extension of the range



4-5 HP

- The most compact VRV
- Low height resulting in minimum visual impact
- Lightweight reduces installation time and manpower to an absolute minimum
- Available in single phase



4-5-6-8-10-12 HP

- Trunk design available in single phase and three phase
- Extended range with 8, 10 and 12 HP unit for bigger applications with space limitations (expected end of 2015)

VRVIII-S heat pump

Space saving solution without compromising on efficiency

- For residential and light commercial applications
- Wide range of indoor units: either connect VRV or stylish indoor units such as Daikin Emura, Nexura ...
- Energy efficient heating system based on air source heat pump technology, lowering energy bills and CO_2 emmisions
- Connect up to 9 indoor units, which can all be individually controlled
- Possibility to combine different types of indoor units: wall mounted, floor standing, concealed ceiling, ceiling suspended, round flow or 4-way blow cassettes
- 3 steps in night quiet mode: step 1: 47dBA, step 2: 44 dBA, step 3: 41 dBA
- Contains all standard VRV features (see page 206)



RXYSQ-P8V / RXYSQ-P8Y

Outdoor unit					RXYSQ	4P8V1	5P8V1	6P8V1	4P8Y1	5P8Y1	6P8Y1
Capacity range					HP	4	5	6	4	5	6
Cooling capacity	Nom.				kW	12.6	14.0	15.5	12.6	14.0	15.5
Heating capacity	Nom.				kW	14.2	16.0	18.0	14.2	16.0	18.0
Power input - 50Hz	Cooling	Nom.			kW	3.24	3.51	4.53	3.33	3.61	4.66
	Heating	Nom.			kW	3.12	3.86	4.57	3.21	3.97	4.70
EER						3.89	3.99	3.42	3.78	3.88	3.33
COP						4.55	4.15	3.94	4.42	4.03	3.83
Maximum number of connectable indoor units						8 (1) / 8 (2)	10 (1) / 9 (2)	12 (1) / 9 (2)	8 (1) / 8 (2)	10 (1) / 9 (2)	12 (1) / 9 (2)
Indoor index connection	Min.					50	62.5	70	50	62.5	70
	Nom.					-					
	Max.					130	162.5	182	130	162.5	182
Dimensions	Unit	HeightxWidthxDepth			mm	1,345x900x320					
Weight	Unit				kg	120					
Fan	Air flow rate	Cooling	Nom.		m^3/min	106					
Sound power level	Cooling	Nom.			dBA	66	67	69	66	67	69
Sound pressure level	Cooling	Nom.			dBA	50	51	53	50	51	53
	Heating	Nom.			dBA	52	53	55	52	53	55
Operation range	Cooling	Min.~Max.			°CDB	-5~46					
	Heating	Min.~Max.			°CWB	-20~15.5					
Refrigerant	Type / GWP					R-410A / 2,087.5					
	Charge				kg	4.0					
	Charge				TCO_2Eq	8.4					
Piping connections	Liquid	OD			mm	9.52					
	Gas	OD			mm	15.9 / 19.1		19.1	15.9 / 19.1		19.1
	Total piping length	System	Actual		m	300 / 115	300 / 135	300 / 145	300 / 115	300 / 135	300 / 145
Power supply	Phase/Frequency/Voltage				Hz/V	1N~/50/220-240			3N~/50/380-415		
Current - 50Hz	Maximum fuse amps (MFA)				A	32.0			16.0		

(1) In case VRV indoor units are connected (2) In case RA indoors are connected

VRVIII heat pump, optimised for heating

Where heating is priority without compromising on efficiency

- First system in the industry developed for heating operation in low ambient conditions, making it suitable for single source heating
- Extended operation range down to -25°C in heating
- Stable heating capacity and high COP values at low ambients thanks to the two stage compression technology (COP values of 3.0 and more at -10°C)
- Improved comfort thanks to shorter defrost time
- Shorter heat up time compared to standard VRVIII heat pump
- Contains all standard VRV features (see page 206)



RTSYQ14-16PA

Outdoor system				RTSYQ	10PA	14PA	16PA	20PA
System	Outdoor unit module 1				RTSQ10PAY1	RTSQ14PAY1	RTSQ16PAY1	RTSQ8PAY1
	Outdoor unit module 2				-			RTSQ12PAY1
	Function unit				BTSQ20PY1			
Capacity range				HP	10	14	16	20
Cooling capacity	Nom.			kW	28.0	40.0	45.0	56.0
Heating capacity	Nom.			kW	31.5 / 28.0	45.0 / 40.0	50.0 / 45.0	63.0 / 55.9
Power input - 50Hz	Cooling	Nom.		kW	7.90	12.6	14.9	15.4
	Heating	Nom.		kW	7.78 / 8.18	11.4 / 12.8	13.0 / 15.0	15.4 / 18.7
EER					3.54	3.17	3.02	3.64
COP					4.05 / 3.42	3.95 / 3.13	3.85 / 3.00	4.09 / 2.99
Maximum number of connectable indoor units					21	30	34	43
Indoor index connection	Min.				125	175	200	250
	Nom.				250	350	400	500
	Max.				325	455	520	650
Sound pressure level	Cooling	Max./Nom.		dBA	62/60	63/61	65/63	
Piping connections	Liquid	OD		mm	9.52	12.7		15.9
	Gas	OD		mm	22.2	28.6		
	Oil equalizing	OD		mm	-			19.1
	Total piping length	System	Actual	m	500			
Current - 50Hz	Maximum fuse amps (MFA)			A	25	35	40	50

Outdoor unit module				BTSQ20P	RTSQ8PA	RTSQ10PA	RTSQ12PA	RTSQ14PA	RTSQ16PA
Dimensions	Unit	HeightxWidthxDepth	mm	1,570x460x765	1,680x930x765			1,680x1,240x765	
Weight	Unit		kg	110	205	257		338	344
Fan	Air flow rate	Cooling Nom.	m^3/min	-	185		200	233	239
Sound power level	Cooling	Nom.	dBA	-					
Operation range	Cooling	Min.~Max.	°CDB	-5~43					
	Heating	Min.~Max.	°CWB	-25~15.5					
Refrigerant	Type / GWP			R-410A / 2,087.5					
	Charge		kg	-	9.4	10.5	10.9	11.7	
	Charge		TCO_2Eq	-	19.6	21.9	22.8	24.4	
Power supply	Phase/Frequency/Voltage		Hz/V	3~/50/380-415					
Current - 50Hz	Maximum fuse amps (MFA)		A	20	25			35	40

VRV Classic

Classic VRV configuration

› For standard cooling & heating requirements
› Connectable to all standard VRV indoor units, controls and ventilation
› Contains all standard VRV features (see page 206)



RXYCQ14-20A

Outdoor unit				RXYCQ	8A	10A	12A	14A	16A	18A	20A
Capacity range				HP	8	10	12	14	16	18	20
Cooling capacity	Nom.			kW	20.0	25.0	30.0	35.0	40.0	45.0	50.4
Heating capacity	Nom.			kW	22.4	28.0	33.6	37.5	44.8	50.4	56.5
Power input - 50Hz	Cooling	Nom.		kW	6.60	6.74	8.77	11.4	12.9	15.0	17.9
	Heating	Nom.		kW	5.80	7.00	8.62	9.74	11.8	13.8	16.1
EER					3.03	3.71	3.42	3.07	3.10	3.00	2.81
COP					3.86	4.00	3.90	3.85	3.80	3.65	3.50
Maximum number of connectable indoor units					64						
Indoor index connection	Min.				100	125	150	175	200	225	250
	Nom.				200	250	300	350	400	450	500
	Max.				200	250	360	420	480	540	600
Dimensions	Unit	HeightxWidthxDepth		mm	1,680x635x765	1,680x930x765			1,680x1,240x765		
Weight	Unit			kg	159	187	240		316		324
Fan	Air flow rate	Cooling	Nom.	m^3/min	95	171	185	196	233		239
Sound power level	Cooling	Nom.		dBA	78	81			86		88
Sound pressure level	Cooling	Nom.		dBA	58	59	61		64	65	66
Operation range	Cooling	Min.~Max.		°CDB	-5~43						
	Heating	Min.~Max.		°CWB	-20~15.5						
Refrigerant	Type / GWP				R-410A / 2,087.5						
	Charge			kg	6.2	7.7	8.4	8.6	11.3	11.5	17.7
	Charge			TCO_2Eq	12.9	16.1	17.5	18	23.6	24	24.4
Piping connections	Liquid	OD		mm	9.52				12.7		15.9
	Gas	OD		mm	15.9	19.1	22.2	28.6			
	Total piping length	System	Actual	m	300						
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/380-415						
Current - 50Hz	Maximum fuse amps (MFA)			A	16	25			40		

Replacement technology




The quick and quality way of upgrading R-22 and R-407C systems

The phase-out period for R-22 is over. Act now!

R-22 ban in Europe

Service and maintenance with R-22 will be prohibited after january 1st, 2015, meaning repairs will be impossible to R-22 systems. Avoid unexpected downtime for your customers and replace these systems now!



The Daikin low-cost upgrade solution

! Replace indoor units and BS boxes
Contact your local dealer to check compatibility in case you need to keep the indoor units.

! Replace outdoor units

These benefits willconvince your customer

Always operational

Avoid loss of business

Replacing now prevents unplanned, lengthy downtime of air conditioning systems. It also avoids loss of business for shops, complaints from guests in hotels, lower working efficiency and loss of tenants in offices.

Quick and easy installation

No interruption of daily business while replacing the system thanks to phased-in, fast installation.


Smaller footprint, more performance

Thanks to a smaller footprint, Daikin outdoor units save space. Also, more indoor units can be connected to the new outdoor unit compared to the old system, allowing to increase capacity.

Lower long-term costs

EU Directives prohibit system repairs with R-22 after January 1st, 2015. Delaying the required R-22 replacement until an unplanned system breakdown is a losing game. Replacement day will come. Installing a technically advanced system lowers energy consumption and maintenance costs from day one.

Up to 48% less consumption





VRV-Q benefits to increase your profit

Optimise your business

Less installation time

Tackle more projects in less time thanks to faster installation. It is more profitable than replacing the full system with new piping.

Lower installation costs

Reducing installation costs enables you to offer customers the most cost-effective solution and improve your competitive edge.

Replace non-Daikin systems

It is a trouble-free replacement solution for Daikin systems and for systems made by other manufacturers.

Easy as one-two-three

A simple solution for replacement technology enables you to handle more projects for more customers in less time and offer them the best price! Everybody gains.

Compare installation steps

Conventional solution	VRV-Q
1 Recover refrigerant	1 Recover refrigerant
2 Remove units	2 Remove units
3 Remove refrigerant pipes	Re-use existing piping and wiring
4 Install new piping and wiring	
5 Install new units	3 Install new units
6 Leak test	4 Leak test
7 Vacuum drying	5 Vacuum drying
8 Refrigerant charging	6 Auromatic refrigerant charging, cleaning and testing
9 Collect contamination	
10 Test operation	


Up to 45% shorter installation time

Automatic refrigerant charge

The unique automatic refrigerant charge eliminates the need to calculate refrigerant volume and ensures that the system will operate perfectly. Not knowing the exact piping lengths because of changes or mistakes in case you didn't do the original installation or replacing a competitor installation no longer poses a problem.

Automatic pipe cleaning

There is no need to clean inside piping as this is handled automatically by the VRV-Q unit. Finally the test operation is performed automatically to save time.



One touch convenience:

- Measure and charge refrigerant
- Automatic pipe cleaning
- Test operation

RQCEQ-P (heat recovery) / RQYQ-P /
RXYQQ-T (heat pump)

Replacement VRV

Quick & quality replacement for R-22 and R-407C systems

- Cost-effective and fast replacement through re-use of exisiting piping
- Up to 80% more efficient than R-22 systems
- No interuption of daily business while replacing your system
- Replace Daikin and other manufacturers systems safely
- Automatic cleaning of refrigerant pipe work ensures a quality replacement
- Possibility to increase capacity
- Limited and phased investment cost
- Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature, VRV configurator, 7 segment display and full inverter compressors, 4-side heat exchanger, refrigerant cooled PCB, new DC fan motor (see page 203) (for RXYQQ-T only)
- Contains all standard VRV features (see page 206)



RQCEQ712-848P

Outdoor system					RQCEQ	280P	360P	460P	500P	540P	636P	712P	744P	816P	848P
System	Outdoor unit module 1					RQEQ140P	RQEQ180P	RQEQ140P		RQEQ180P	RQEQ212P	RQEQ140P		RQEQ180P	RQEQ212P
	Outdoor unit module 2					RQEQ140P	RQEQ180P	RQEQ140P	RQEQ180P		RQEQ212P	RQEQ180P		RQEQ212P	
	Outdoor unit module 3					-		RQEQ180P			RQEQ212P	RQEQ180P	RQEQ212P		
	Outdoor unit module 4					-						RQEQ212P			
Capacity range					HP	10	13	16	18	20	22	24	26	28	30
Cooling capacity	Nom.				kW	28.0	36.0	45.0	50.0	54.0	63.6	71.2	74.4	81.6	84.8
Heating capacity	Nom.				kW	32.0	40.0	52.0	56.0	60.0	67.2	78.4	80.8	87.2	89.6
Power input - 50Hz	Cooling	Nom.			kW	7.04	10.3	12.2	13.9	15.5	21.9	21.2	23.3	27.1	29.2
	Heating	Nom.			kW	8.00	10.7	13.4	14.7	16.1	17.7	20.7	21.2	23.1	23.6
EER						3.98	3.48	3.77	3.61	3.48	2.90	3.36	3.19	3.01	2.90
COP						4.00	3.72	3.89	3.80	3.72	3.79	3.80	3.81	3.77	3.79
Maximum number of connectable indoor units						21	28	34	39	43	47	52	56	60	64
Indoor index connection	Min.					140	180	230	250	270	318	356	372	408	424
	Nom.					280	360	500		540	636	712	744	816	848
	Max.					364	468	598	650	702	827	926	967.0	1,061	1,102
Sound pressure level	Cooling	Nom.			dBA	57	61		62	63	64	63	64	65	66
Piping connections	Liquid	OD			mm	9.52	12.7		15.9			19.1			
	Gas	OD			mm	22.2	25.4	28.6				34.9			
	Discharge gas	OD			mm	19.1		22.2			25.4			28.6	
	Total piping length	System	Actual		m	300									
Current - 50Hz	Maximum fuse amps (MFA)				A	30	40	50	60		70	80		90	

Outdoor unit module				RQEQ	140P	180P	212P
Dimensions	Unit	HeightxWidthxDepth		mm	1,680x635x765		
Weight	Unit			kg	175		179
Fan	Air flow rate	Cooling	Nom.	m^3/min	95	110	
Sound power level	Cooling	Nom.		dBA	-		
Sound pressure level	Cooling	Nom.		dBA	54	58	60
Operation range	Cooling	Min.~Max.		°CDB	-5~43		
	Heating	Min.~Max.		°CWB	-20~15.5		
Refrigerant	Type / GWP				R-410A / 2,087.5		
	Charge			kg	10.3	10.6	11.2
	Charge			TCO_2Eq	21.5	22.1	23.4
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	15	20	22.5

VRV IV Q-series

Variable Refrigerant Temperature

Replacement VRV



RXYQQ8-12T

Outdoor system					RXYQQ	RQYQ140P	8T	10T	12T	14T	16T	18T	20T	22T	24T
System	Outdoor unit module 1					-								RXYQQ10T	RXYQQ8T
	Outdoor unit module 2					-				-				RXYQQ12T	RXYQQ16T
Capacity range					HP	5	8	10	12	14	16	18	20	22	24
Cooling capacity	Nom.				kW	14.0	22.4	28.0	33.5	40.0	45.0	50.4	56.0	61.5	67.4
Heating capacity	Nom.				kW	16.0	25.0	31.5	37.5	45.0	50.0	50.4	63.0	69.0	75.0
Power input - 50Hz	Cooling	Nom.			kW	3.36	5.21	7.29	8.98	11.0	13.0	15.0	18.5	16.27	18.21
	Heating	Nom.			kW	3.91	5.51	7.38	9.10	11.2	12.8	12.6	17.0	16.48	18.31
EER						4.17	4.30	3.84	3.73	3.64	3.46	3.36	3.03	3.78	3.70
ESEER						-	6.37 (1) / 7.53 (2)	5.67 (1) / 7.20 (2)	5.50 (1) / 6.96 (2)	5.31 (1) / 6.83 (2)	5.05 (1) / 6.50 (2)	4.00 (1) / 3.87 (2)	4.42 (1) / 5.67 (2)	5.58 (1) / 7.07 (2)	5.42 (1) / 6.81 (2)
COP						4.09	4.54	4.27	4.12	4.02	3.91	4.97	3.71	4.19	4.10
Maximum number of connectable indoor units						10	64 (3)							64 (3)	
Indoor index connection	Min.					62.5	100	125	150	175	200	225	250	275	300
	Nom.					125	200	250	300	350	400	450	500	550	600
	Max.					162.5	260	325	390	455	520	585	650	715	780
Dimensions	Unit	HeightxWidthxDepth			mm	1,680x635x765	1,685x930x765			1,685x1,240x765				-	
Weight	Unit				kg	175	187	194		305		314		-	
Fan	Air flow rate	Cooling	Nom.		m^3/min	95	162	175	185	223	260	251	261	-	
Sound power level	Cooling	Nom.			dBA	-	78	79	81		86		88	-	
Sound pressure level	Cooling	Nom.			dBA	54.0	58		61		64	65	66	-	
Operation range	Cooling	Min.~Max.			°CDB	-5~43								-	
	Heating	Min.~Max.			°CWB	-20~15.5								-	
Refrigerant	Type / GWP					R-410A / 2,087.5								-	
	Charge				kg	11.1	5.9	6	6.3	10.3	10.4	11.7	11.8	-	
	Charge				TCO_2Eq	23.2	12.3	12.5	13.2	21.5	21.7	24.4	24.6	-	
Piping connections	Liquid	OD			mm	9.52	9.52		12.7			15.9			
	Gas	OD			mm	15.9	19.1	22.2	28.6						34.9
	Total piping length	System	Actual		m	300	300								
Power supply	Phase/Frequency/Voltage				Hz/V	3N~/50/380-415								-	
Current - 50Hz	Maximum fuse amps (MFA)				A	15	20	25	32		40		50	63	

Outdoor system					RXYQQ	26T	28T	30T	32T	34T	36T	38T	40T	42T
System	Outdoor unit module 1					RXYQQ12T			RXYQQ16T			RXYQQ8T	RXYQQ10T	
	Outdoor unit module 2					RXYQQ14T	RXYQQ16T	RXYQQ18T	RXYQQ16T	RXYQQ18T	RXYQQ20T	RXYQQ10T	RXYQQ12T	RXYQQ16T
	Outdoor unit module 3					-						RXYQQ20T	RXYQQ18T	RXYQQ16T
Capacity range					HP	26	28	30	32	34	36	38	40	42
Cooling capacity	Nom.				kW	73.5	78.5	83.5	90.0	95.0	101.0	106.4	111.5	118.0
Heating capacity	Nom.				kW	82.5	87.5	93.5	100.0	106.0	113.0	119.5	125.0	131.5
Power input - 50Hz	Cooling	Nom.			kW	19.98	21.98	23.68	26.0	27.7	31.5	31.00	30.97	33.29
	Heating	Nom.			kW	20.30	21.90	23.50	25.6	27.2	29.8	29.89	30.88	32.98
EER						3.68	3.57	3.53	3.5	3.4	3.2	3.43	3.60	3.54
ESEER						5.39 (1) / 6.89 (2)	5.23 (1) / 6.69 (2)	5.17 (1) / 6.60 (2)	5.05 (1) / 6.50 (2)	5.01 (1) / 6.44 (2)	4.68 (1) / 6.02 (2)	5.03 (1) / 6.36 (2)	5.29 (1) / 6.74 (2)	5.19 (1) / 6.65 (2)
COP						4.06	4.00	3.98	3.9		3.8	4.00	4.05	3.99
Maximum number of connectable indoor units						64 (3)								
Indoor index connection	Min.					325	350	375	400	425	450	475	500	525
	Nom.					650	700	750	800	850	900	950	1,000	1,050
	Max.					845	910	975	1,040	1,105	1,170	1,235	1,300	1,365
Sound power level	Cooling	Nom.			dBA	-								
Sound pressure level	Cooling	Nom.			dBA	-								
Piping connections	Liquid	OD			mm	19.1								
	Gas	OD			mm	34.9					41.3			
	Total piping length	System	Actual		m	300								
Current - 50Hz	Maximum fuse amps (MFA)				A	63		80				100		

(1) The STANDARD ESEER value corresponds with normal VRV4 Heat Pump operation, not taking into account advanced energy saving operation functionality (2) The AUTOMATIC SEER value corresponds with normal VRV4 Heat Pump operation, taking into account advanced energy saving operation functionality (variable refrigerant temperature control operation) (3) Actual number of connectable indoor units depends on the indoor unit type (VRV indoor, Hydrobox, RA indoor, etc.) and the connection ratio restriction for the system (50% <= CR <= 130%)



PARK PHI
BREAAM® EXCELLENT OFFICE BUILDING
WATERCOOLED VRV


VRV IV water cooled series

Ideal for high rise buildings, using water as heat source


- Unified range for standard and geothermal series simplifies stock. Geothermal series reduce CO_2 emmisions thanks to the use of geothermal energy as a renewable energy source
- No need for an external heating or cooling source when used in geothermal mode
- Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, hot water, air handling units and Biddle air curtains
- Compact & lightweight design can be stacked for maximum space saving
- Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature and full inverter compressors (see page 203)
- 2-stage heat recovery: first stage between indoor units, second stage between outdoor units thanks to the storage of energy in the water circuit
- Available in heat pump and heat recovery version
- Variable Water Flow control option increases flexibility and control
- Easy compliance with F-gas regulation thanks to automated refrigerant containment check
- Contains all standard VRV features (see page 206)



RWEYQ8-10T



Standard operation




Geothermal operation

Outdoor unit					RWEYQ	8T	10T	16T	18T	20T	24T	26T	28T	30T
System	Outdoor unit module 1					RWEYQ8T	RWEYQ10T	RWEYQ8T		RWEYQ10T	RWEYQ8T			RWEYQ10T
	Outdoor unit module 2					-		RWEYQ8T	RWEYQ10T		RWEYQ8T		RWEYQ10T	
	Outdoor unit module 3							-			RWEYQ8T	RWEYQ10T		
Capacity range					HP	8	10	16	18	20	24	26	28	30
Cooling capacity	Nom.				kW	22.4	28.0	44.8	50.4	56.0	67.2	72.8	78.4	84.0
Heating capacity	Nom.				kW	25.0	31.5	50.0	56.5	63.0	75.0	81.5	88.0	94.5
Power input - 50Hz	Cooling	Nom.			kW	4.42	6.14	8.8	10.6	12.3	13.3	15.0	16.7	18.4
	Heating	Nom.			kW	4.21	6.00	8.4	10.2	12.0	12.6	14.4	16.2	18.0
EER						5.07	4.56	5.07	4.77	4.56	5.07	4.86	4.69	4.56
COP						5.94	5.25	5.94	5.53	5.25	5.94	5.65	5.43	5.25
Maximum number of connectable indoor units						36								
Indoor index connection	Min.					100	125	200	225	250	300	325	350	375
	Nom.					200	250	400	450	500	600	650	700	750
	Max.					260	325	520	585	650	780	845	910	975
Dimensions	Unit	HeightxWidthxDepth			mm	1,000x780x550		-						
Weight	Unit				kg	137		-						
Fan	Air flow rate	Cooling	Nom.		m^3/min	-								
Sound power level	Cooling	Nom.			dBA	-								
Sound pressure level	Cooling	Nom.			dBA	50	51	53	54		55			56
Operation range	Inlet water temperature	Cooling	Min.~Max.		°CDB	10~45								
		Heating	Min.~Max.		°CWB	-10 / 10.0~45								
Refrigerant	Type / GWP					R-410A / 2,087.5								
	Charge				kg	3.5	4.2	-	-	-	-	-	-	-
	Charge				TCO_2Eq	7.3	8.8	-	-	-	-	-	-	-
Piping connections	Liquid	OD			mm	9.52		12.7	15.9			19.1		
	Gas	OD			mm	19.10 (1)	22.2 (1)	28.6 (1)			34.9 (1)			
	Discharge gas	OD			mm	15.9 (2) / 19.10 (3)	19.1 (2) / 22.10 (3)	22.2 (2) / 28.60 (3)			28.6 (2) / 34.90 (3)			
	Water	Inlet/Outlet				PT1 1/4B internal thread/PT1 1/4B internal thread								
	Total piping length	System	Actual		m	300								
Power supply	Phase/Frequency/Voltage				Hz/V	3N~/50/380-415								
Current - 50Hz	Maximum fuse amps (MFA)				A	20		32			50			

(1) In case of heat pump system, gas pipe is not used (2) In case of heat recovery system (3) In case of heat pump system

BS1Q-A

Individual branch selector for VRV IV heat recovery


BS1Q-A

› Unique range of single and multi BS boxes for flexible and fast design
› Compact & light to install
› Ideal for remote rooms as no drain piping is needed
› Allows integration of server rooms into the heat recovery solution thanks to technical cooling function
› Connect up to 250 class unit (28kW)
› Faster installation thanks to open connection
› Allows multi tenant applications
› Connectable to REYQ-T VRV IV heat recovery units

Indoor unit				BS	1Q10A	1Q16A	1Q25A
Power input	Cooling	Nom.		kW	0.005		
	Heating	Nom.		kW	0.005		
Maximum number of connectable indoor units					5	8	
Maximum capacity index of connectable indoor units					15 < x ≤ 100	100<x≤160	160<x≤250
Dimensions	Unit	HeightxWidthxDepth		mm	207x388x326		
Weight	Unit			kg	12		15
Casing	Material				Galvanised steel plate		
Piping connections	Outdoor unit	Liquid	Type/OD	mm	Brazing connection/9.5		
		Gas	Type/OD	mm	Brazing connection/15.9		Brazing connection/22.2
		Discharge gas	Type/OD	mm	Brazing connection/12.7		Brazing connection/19.1
	Indoor unit	Liquid	Type/OD	mm	Brazing connection/9.5		
		Gas	Type/OD	mm	Brazing connection/15.9		Brazing connection/22.2
Sound absorbing thermal insulation					Foamed polyurethane Flame-resistant needle felt		
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240		
Total circuit	Maximum fuse amps (MFA)			A	15		

BS-Q14A

Multi branch selector for VRV IV heat recovery


BS6,8Q14A


› Unique range of single and multi BS boxes for flexible and fast design
› Major reduction in installation time thanks to wide range, compact size and light weight multi BS boxes
› Up to 70% smaller and 66% lighter than previous series
› Faster installation thanks to a reduced number of brazing points and wiring
› All indoor units connectable to one BS box
› Less inspection ports needed compared to installing single BS boxes
› Up to 16kW capacity available per port
› Connect up to 250 class unit (28kW) by combining 2 ports
› No limit on unused ports allowing phased installation
› Faster installation thanks to open connection
› Connectable to REYQ-T VRV IV heat recovery units

Indoor unit				BS	4Q14A	6Q14A	8Q14A	10Q14A	12Q14A	16Q14A
Power input	Cooling	Nom.		kW	0.043	0.064	0.086	0.107	0.129	0.172
	Heating	Nom.		kW	0.043	0.064	0.086	0.107	0.129	0.172
Maximum number of connectable indoor units					20	30	40	50	60	64
Maximum number of connectable indoor units per branch					5					
Number of branches					4	6	8	10	12	16
Maximum capacity index of connectable indoor units					400	600	750			
Maximum capacity index of connectable indoor units per branch					140					
Dimensions	Unit	HeightxWidthxDepth		mm	298x370x430	298x580x430		298x820x430		298x1,060x430
Weight	Unit			kg	17	24	26	35	38	50
Casing	Material				Galvanised steel plate					
Piping connections	Outdoor unit	Liquid	OD	mm	9.5	12.7	12.7 / 15.9	15.9	15.9 / 19.1	19.1
		Gas	OD	mm	22.2 / 19.1	28.6 / 22.2	28.6	28.6 / 34.9		34.9
		Discharge gas	OD	mm	19.1 / 15.9	19.1 / 22.2	19.1 / 22.2 / 28.6	28.6		
	Indoor unit	Liquid	OD	mm	9.5 / 6.4					
		Gas	OD	mm	15.9 / 12.7					
	Drain				VP20 (I.D. 20/O.D. 26)					
Sound absorbing thermal insulation					Urethane foam, polyethylene foam					
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-440					
Total circuit	Maximum fuse amps (MFA)			A	15					

BSVQ-P9B

Individual branch selector for VRV heat recovery

- Allows individual cool / heat switching of 1 group of indoor units
- Maximum design flexibility because individual and multi boxes can be combined in one system
- Low built-in height
- No drain piping needed
- Allows multi tenant applications (option PCB required)
- Connectable to VRV W-IV series (RWEYQ-T)




BSVQ-P9B

Indoor unit					BSVQ	100P9B	160P9B	250P9B
Power input	Cooling	Nom.			kW	0.005		
	Heating	Nom.			kW	0.005		
Maximum number of connectable indoor units						6	8	
Maximum capacity index of connectable indoor units						15 < x ≤ 100	100<x≤160	160<x≤250
Dimensions	Unit	HeightxWidthxDepth			mm	207x388x326		
Weight	Unit				kg	12		15
Casing	Material					Galvanised steel plate		
Piping connections	Outdoor unit	Liquid	Type/OD		mm	Brazing connection/9.5		
		Gas	Type/OD		mm	Brazing connection/15.9		Brazing connection/22.2
		Discharge gas	Type/OD		mm	Brazing connection/12.7	Brazing connection/12.7	Brazing connection/19.1
	Indoor unit	Liquid	Type/OD		mm	Brazing connection/9.5		
		Gas	Type/OD		mm	Brazing connection/15.9	Brazing connection/15.9	Brazing connection/22.2
Sound absorbing thermal insulation						Foamed polyurethane Flame-resistant needle felt		
Power supply	Phase/Frequency/Voltage				Hz/V	1~/50/220-240		
Total circuit	Maximum fuse amps (MFA)				A	15		

BSV4Q-PV/BSV6Q-PV

Multi branch selector for VRV heat recovery

- Faster installation thanks to a reduced number of brazing points and wiring
- Allows individual cool / heat switching for up to 4 or 6 groups of indoor units
- Maximum design flexibility because individual and multi boxes can be combined in one system
- Low built-in height
- No drain piping needed
- Connectable to VRV W-IV series (RWEYQ-T)



BSV4Q100PV

Indoor unit					BSV4Q-PV/BSV6Q-PV	4Q100PV	6Q100PV
Power input	Cooling	Nom.			kW	0.020	0.030
	Heating	Nom.			kW	0.020	0.030
Maximum number of connectable indoor units						24	36
Maximum number of connectable indoor units per branch						6	
Number of branches						4	6
Maximum capacity index of connectable indoor units						400	600
Maximum capacity index of connectable indoor units per branch						100	
Dimensions	Unit	HeightxWidthxDepth			mm	209x1,053x635	209x1,577x635
Weight	Unit				kg	60	89
Casing	Material					Galvanised steel plate	
Piping connections	Outdoor unit	Liquid	Type/OD		mm	Brazing connection/12.7	Brazing connection/15.9
		Gas	Type/OD		mm	Brazing connection/28.6	
		Discharge gas	Type/OD		mm	Brazing connection/19.1	Brazing connection/28.6
	Indoor unit	Liquid	Type/OD		mm	Brazing connection/9.5	
		Gas	Type/OD		mm	Brazing connection/15.9	
Sound absorbing thermal insulation						Foamed polyurethane Flame-resistant needle felt	
Power supply	Phase/Frequency/Voltage				Hz/V	1~/50/220-240	
Total circuit	Maximum fuse amps (MFA)				A	15	







FXMQ-P7


FXFQ-P9


FXDQ-M9


FXZQ-A

Products overview VRV

Type	Model		Product name	
Ceiling mounted cassette	Round flow cassette	- 360° air discharge for optimum efficiency and comfort - Auto cleaning function ensures high efficiency - Intelligent sensors save energy and maximize comfort - Flexibility to suit every room layout - Lowest installation height in the market!	FXFQ-A	
	Fully flat cassette	- Unique design in the market that integrates fully flat into the ceiling - Perfect integration in standard architectural ceiling tiles - Blend of iconic design and engineering excellence with a white or silver and white finish - Intelligent sensors save energy and maximize comfort - Small capacity unit developed for small or well-insulated rooms - Flexibility to suit every room layout	FXZQ-A	
	2-way blow ceiling mounted cassette	- Thin, lightweight design installs easily in narrow ceiling spaces - Depth of all units is 620mm, ideal for narrow ceiling spaces - Flexibility to suit every room layout - Reduced energy consumption thanks to DC fan motor - Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating - Optimum comfort guaranteed with automatic air flow adjustment to the required load	FXCQ-A	
	Ceiling mounted corner cassette	- 1-way blow unit for corner installation - Compact dimensions enable installation in narrow ceiling voids - Flexible installation thanks to different air discharge options	FXKQ-MA	
Concealed ceiling	Small concealed ceiling unit	- Designed for hotel rooms - Compact dimensions enable installation in narrow ceiling voids - Discretely concealed in the ceiling: only the grilles are visible - Flexible installation as the air suction direction can be altered from rear to bottom suction	FXDQ-M9	
	Slim concealed ceiling unit	- Slim design for flexible installation - Compact dimensions enable installation in narrow ceiling voids - Medium external static pressure up to 44Pa - Only grilles are visible - Small capacity unit developted for small of well-insulated rooms - Reduced energy consumption thanks to DC fan motor	FXDQ-A	
	Concealed ceiling unit with medium ESP	- Optimum comfort guaranteed no matter the length of ductwork or type of grilles - Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, guaranteeing comfort - Medium external static pressure up to 140Pa - Only grilles are visible - Reduced energy consumption thanks to DC fan motor - Flexible installation as the air suction direction can be altered from rear to bottom suction	FXSQ-A	
	Concealed ceiling unit with high ESP	- ESP up to 200, ideal for large sized spaces - Optimum comfort guaranteed no matter the length of ductwork or type of grilles, thanks to automatic air flow adjustment - Only grilles are visible - Reduced energy consumption thanks to DC fan motor - Flexible installation as the air suction direction can be altered from rear to bottom suction	FXMQ-P7	
	Concealed ceiling unit with high ESP	- ESP up to 270, ideal for extra large sized spaces - Only grilles are visible - Large capacity unit: up to 31.5 kW heating capacity	FXMQ-MA	
Wall mounted	Wall mounted unit	- For rooms with no false ceilings nor free floor space - Flat, stylish front panel blends easily with any interior décor and is more easy to clean - Can easily be installed in both new and refurbishment projects - Small capacity unit developted for small of well-insulated rooms - Reduced energy consumption thanks to DC fan motor - The air is comfortably spread up- and downwards thanks to 5 different discharge angles	FXAQ-P	
Ceiling suspended	Ceiling suspended unit	- For wide rooms with no false ceilings nor free floor space - Ideal for comfortable air flow in wide rooms thanks to Coanda effect - Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily! - Can easily be installed in both new and refurbishment projects - Can even be mounted in corners or narrow spaces without any problem - Reduced energy consumption thanks to DC fan motor	FXHQ-A	
	4-way blow ceiling suspended unit	- Unique Daikin unit for high rooms with no false ceilings nor free floor space - Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily! - Can easily be installed in both new and refurbishment projects - Flexibility to suit every room layout - Reduced energy consumption thanks to DC fan motor	FXUQ-A	
Floor standing	Floor standing unit	- For perimeter zone air conditioning - Can be installed in front of glass walls or free standing as both the front and the back are finished - Ideal for installation beneath a window - Stylish unit blends easily with any interior - Requires very little installation space - Wall mounted installation facilitates cleaning beneath the unit	FXLQ-P	
	Concealed floor standing unit	- Ideal for installation in offices, hotels and residential applications - Discretely concealed in the wall, leaving only the suction and discharge grilles visible - Can even be installed underneath a window - Requires very little installation space as the depth is only 200mm - High ESP allows flexible installation	FXNQ-A	
Cooling capacity (kW)[1]				
Heating capacity (kW)[2]				

Hot water

Type	Model		Product name	
	High temperature hydrobox for VRV	- For efficient hot water production and space heating - Ideal for hot water in bathrooms, sinks and for underfloor heating, radiators, air handling units, … - Hot water from 25 to 80°C - "Free" heating and hot water through heat recovery - Possibility to connect thermal solar collectors	HXHD-A	
	Low temperature hydrobox for VRV	- For high efficiency space heating and cooling - Ideal for hot or cold water in underfloor, air handling units, low temperature radiators … - Hot/cold water from 5° to 45°C	HXY-A	

(1)Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m.
(2)Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m

Capacity class (kW)


15	20	25	32	40	50	63	71	80	100	125	140	200	250
	●	●	●	●	●	●		●	●	●			
●	●	●	●	●	●								
	●	●	●	●	●	●		●		●			
		●	●	●		●							
	●	●											
●	●	●	●	●	●	●							
●	●	●	●	●	●	●		●	●	●	●		
					●	●		●	●	●			
												●	●
●	●	●	●	●	●	●							
			●			●			●				
							●		●				
	●	●	●	●	●	●							
	●	●	●	●	●	●							
1.7	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0	22.4	28.0
1.9	2.5	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5	16.0	18.0	25.0	31.5

15	20	25	32	40	50	63	71	80	100	125	140	200	250
								●		●			
										●			

Benefits overview

VRV indoor

We care icons		Inverter technology	In combination with inverter controlled outdoor units
		Home leave operation	During absence, the indoor temperature can be maintained at a certain level.
		Fan only	The air conditioner can be used as fan, blowing air without cooling or heating.
		Auto cleaning filter	The filter automatically cleans itself once per day. Simplicity of upkeep means optimum energy efficiency and maximum comfort without the need for expensive or time-consuming maintenance.
		Floor and presence sensor	The presence sensor directs the air away from any person detected in the room, when the air flow control is on. The floor sensor detects the average floor temperature and ensures an even temperature distribution between ceiling and floor.
Comfort		Draught prevention	When starting to warm up or when the thermostat is off, the air discharge direction is set horizontally and the fan to low speed, to prevent draught. After warming up, air discharge and fan speed are set as desired.
		Whisper quiet	Daikin indoor units are whisper quiet. Also the outdoor units are guaranteed not to disturb the quiet of the neightbourhood.
		Auto cooling-heating changeover	Automatically selects cooling or heating mode to achieve the set temperature.
Air treatment		Air filter	Removes airborne dust particles to ensure a steady supply of clean air.
Humidity control		Dry programme	Allows humidity levels to be reduced without variations in room temperature.
Air flow		Ceiling soiling prevention	A special function prevents air blowing out too long in horizontal position, to prevent ceiling stains.
		Vertical auto swing	Possibility to select automatic vertical moving of the air discharge louvre, for uniform air flow and temperature distribution.
		Fan speed steps	Allows to select up to the given number of fan speed.
		Individual flap control	Individual flap control via the wired remote controller makes it simple to fix the position of each flap individually, to suit any new room configuration. Optional closure kits are available as well.
Remote control & timer		Weekly timer	Timer can be set to start operation anytime on a daily or weekly basis
		Infrared remote control	Infrared remote control with LCD to start, stop and regulate the air conditioner from a distance.
		Wired remote control	Wired remote control to start, stop and regulate the air conditioner from a distance.
		Centralised control	Centralised control to start, stop and regulate several air conditioners from one central point.
Other funtions		Auto-restart	The unit restarts automatically at the original settings after power failure.
		Self-diagnosis	Simplifies maintenance by indicating system faults or operating anomalies.
		Drain pump kit	Facilitates condensation draining from the indoor unit.
		Multi tenant	The indoor unit's main power supply can be turned off when leaving the hotel or office building.

Ceiling mounted cassette units				Concealed ceiling units					Wall mounted unit	Ceiling suspended units		Floor standing units	
FXFQ-A	**FXZQ-A**	**FXCQ-A**	**FXKQ-MA**	**FXDQ-M9**	**FXDQ-A**	**FXSQ-A**	**FXMQ-P7**	**FXMQ-MA**	**FXAQ-P**	**FXHQ-A**	**FXUQ-A**	**FXNQ-A**	**FXLQ-P**
													
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●													
●	●												
●	●		●								●		
●	●	●			●	●		●					
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●										
●	●	●	●						●		●		
3	3	3	2	2	3	3	3	2	2	3	3	2	2
●	●										●		
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●
Standard	Standard	Standard	Standard		Standard	Standard	Standard	Optional	Optional	Optional	Standard		
●	●			●	●	●	●		●			●	●

*Note: blue cells contain preliminary data

FCQG-F/FCQHG-F/FXFQ-A

Round flow cassette



Unique functions that help saving costs

› Daikin was the first to launch a cassette using the roundflow principle with sensors* and a unique auto-cleaning decoration panel*.

... Energy efficient as no other

› The auto-cleaning panel* means:
- Running costs are reduced by 50% compared with standard solutions thanks to automatic daily filter cleaning
- Less time is required to maintain the filter: dust can easily be removed with a vacuum cleaner without opening the unit

› Thanks to the presence and floor sensors* the unit changes its setpoint or switches off completely, if there are no people present in the room, resulting in energy savings of up to 27%.

… And improved comfort


› 360° air flow discharge pattern
› The presence sensor* directs the air away from anyone detected in the room
› The floor sensor* detects the average floor temperature and ensure an even temperature distribution between the ceiling and the floor. Cold feet are history!

Flexible installation

› Flaps can be individually controlled or closed using the wired remote control, to suit room configuration.
Optional closure kits are also available.

References

Reference Wolverhampton, UK
Running costs were reduced with up to 50% compared to standard solutions thanks to daily filter cleaning.



Cumulative energy comparison over 12 months

Why choose Round flow cassette?

- 360° air discharge for optimum efficiency and comfort in shops, offices and restaurants.

Marketing tools

› Visit the website: www.daikineurope.com/minisite/round-flow-cassette/

Benefits for the installer

› Product with unique functions in the market
› Less time needed on site for maintenance
› Use the controller to individually open or close any of the four flaps to easily adapt to a changing room layout
› Easy set-up of the sensor option to improve comfort and save energy.

Benefits for the consultant

› Product with unique functions in the market
› Designed for use in all types and sizes of commercial offices and retail environments
› Ideal product to improve BREEAM score/EPDB in combination with Sky Air Seasonal Smart or VRV IV heat pump units.

Benefits for the end user


› Designed for use in all types and sizes of commercial offices and retail environments
› Perfect environment conditions: no more cold draughts or cold feet
› Save up to 50% on running costs with the auto-cleaning panel, which also facilitates maintenance
› Save up to 27% on your energy bill thanks to the sensor option
› Flexible usage of space thanks to individual flap control.

* available as an option


Round flow cassette


360° air discharge for optimum efficiency and comfort

- Daily automatic filter cleaning results in higher efficiency & comfort and lower maintenance costs
- Two optional intelligent sensors improve energy efficiency and comfort
- Individual flap control. Flexibility to suit every room layout without changing the location of the unit!



- Lowest installation height in the market: 214mm for class 20-63
- Modern style decoration panel is available in 3 different variations: white (RAL9010) with grey louvers, full white (RAL9010) or auto cleaning panel
- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required
- Standard drain pump with 850mm lift increases flexibility and installation speed





Indoor unit				FXFQ	20A	25A	32A	40A	50A	63A	80A	100A	125A
Cooling capacity	Nom.			kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0
Heating capacity	Nom.			kW	2.5	3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0
Power input - 50Hz	Cooling	Nom.		kW	0.038				0.053	0.061	0.092	0.115	0.186
	Heating	Nom.		kW	0.038				0.053	0.061	0.092	0.115	0.186
Dimensions	Unit	Height		mm	204						246		288
		Width		mm	840								
		Depth		mm	840								
Weight	Unit			kg	19			20	21		24		26
Casing	Material				Galvanised steel plate								
Decoration panel	Model				BYCQ140D7W1								
	Colour				Pure White (RAL 9010)								
	Dimensions	HeightxWidthxDepth		mm	60x950x950								
	Weight			kg	5.4								
Decoration panel 2	Model				BYCQ140D7W1W								
	Colour				Pure White (RAL 9010)								
	Dimensions	HeightxWidthxDepth		mm	60x950x950								
	Weight			kg	5.4								
Decoration panel 3	Model				BYCQ140D7GW1								
	Colour				Pure White (RAL 9010)								
	Dimensions	HeightxWidthxDepth		mm	145x950x950								
	Weight			kg	10.3								
Fan-Air flow rate	Cooling	High/Nom./Low		m^3/min	12.5/10.6/8.8			13.6/11.6/9.5	15.0/12.8/10.5	16.5/13.5/10.5	22.8/17.6/12.4	26.5/19.5/12.4	33.0/26.5/19.9
- 50Hz	Heating	High/Nom./Low		m^3/min	12.5/10.6/8.8			13.6/11.6/9.5	15.0/12.8/10.5	16.5/13.5/10.5	22.8/17.6/12.4	26.5/19.5/12.4	33.0/26.5/19.9
Air filter	Type				Resin net with mold resistance								
Sound power level	Cooling	High/Nom.		dBA	49/-			51/-		53/-	55/-	60/-	61/-
Sound pressure	Cooling	High/Nom./Low		dBA	31/29/28			33/31/29		35/33/30	38/34/30	43/37/30	45/41/36
level	Heating	High/Nom./Low		dBA	31/29/28			33/31/29		35/33/30	38/34/30	43/37/30	45/41/36
Refrigerant	Type / GWP				R-410A / 2.087,5								
Piping connections	Liquid	OD		mm	6.35					9.52			
	Gas	OD		mm	12.7					15.9			
	Drain				VP25 (O.D. 32 / I.D. 25)								
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220								
Current - 50Hz	Maximum fuse amps (MFA)			A	16								
Control systems	Infrared remote control				BRC7FA532F								
	Simplified wired remote control for hotel applications				-								
	Wired remote control				BRC1D52 / BRC1E52A/B								

BYCQ140D7W1 = pure white panel with grey louvers , BYCQ140D7W1W = pure white standard panel with white louvers, BYCQ140D7GW1 = Pure white auto cleaning panel
The BYCQ140D7W1W has white insulations. Be informed that formations of dirt on white insulation is visibly stronger & that it is consequently not advised to install the decoration panel in environments exposed to concentrations of dirt.

ARGUE CARDS

FFQ-C / FXZQ-A

Fully Flat Cassette

Design & Genius in one



› Why choose fully flat cassette?

- Unique design in the market that integrates fully flat into the ceiling

Benefits for the installer

› Unique product in the market!
› Most silent unit
› The user-friendly remote control, available in several languages, enables the easy set-up of sensor option and control of the individual flap position
› Meeting European design taste.

Benefits for the consultant

› Unique product in the market!
› Blends seamlessly in any modern office interior design
› Ideal product to improve BREEAM score/EPDB in combination with Sky Air Seasonal Smart or VRV IV heat pump units.

Benefits for the end user

› Engineering excellence and unique design in one
› Most silent unit
› Perfect working conditions: no more cold draughts or cold feet
› Save up to 27% on your energy bill thanks to the optional sensors
› Flexible usage of space thanks to individual flap control
› User-friendly remote control, available in several languages.

Unique design

› Designed by German design office to fully meet the European taste.
› Fully flat into the ceiling, leaving only 8mm.
› Fully integrated in the one ceiling tile, enabling lights, speakers and sprinklers to be installed in adjoining ceiling tiles.
› Decoration panel available in 2 colours (white and white-silver).

Differentiating in technology

Optional presence sensor

› When the room is empty, it can adjust the set temperature or switch off the unit – saving energy.
› When people are detected, the direction of the airflow is adapted to avoid cold draughts being directed towards occupants.

Optional floor sensor

› Detects the temperature difference and re-directs the airflow to ensure even temperature distribution.

Top efficiency

› Seasonal labels up to A++*
› When the room is empty, the sensor option can adjust the set temperature or switch off the unit – saving up to 27% energy.
› Individual flap control: easily control one or more flaps via the wired remote controller (BRC1E52) when rearranging the room. When fully closing or blocking the flaps, the option "Sealing member of air discharge outlet" is needed.

* for FFQ25,35C in combination with RXS25,35L3

Other features

› Most silent cassette in the market (25dBA), important for office applications.

Marketing tools

› Download the Seasonal Calculator software: www.daikineurope.com/support-and-manuals/software-downloads/air-conditioning/






Fully flat cassette


Unique design in the market that integrates fully flat into the ceiling

- Remarkable blend of iconic design and engineering excellence
- Two optional intelligent sensors improve energy efficiency and comfort
- 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- Individual flap control. Flexibility to suit every room layout without changing the location of the unit!



- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required
- Standard drain pump with 850mm lift increases flexibility and installation speed






Indoor unit				FXZQ	15A	20A	25A	32A	40A	50A
Cooling capacity	Nom.			kW	1.7	2.2	2.8	3.6	4.5	5.6
Heating capacity	Nom.			kW	1.9	2.5	3.2	4.0	5.0	6.3
Power input - 50Hz	Cooling	Nom.		kW	0.043			0.045	0.059	0.092
	Heating	Nom.		kW	0.036			0.038	0.053	0.086
Dimensions	Unit	Height		mm	260					
		Width		mm	575					
		Depth		mm	575					
Weight	Unit			kg	15.5			16.5		18.5
Casing	Material				Galvanised steel plate					
Decoration panel	Model				BYFQ60CW					
	Colour				White (N9.5)					
	Dimensions	HeightxWidthxDepth		mm	46x620x620					
	Weight			kg	2.8					
Decoration panel 2	Model				BYFQ60CS					
	Colour				White (N9.5) + Silver					
	Dimensions	HeightxWidthxDepth		mm	46x620x620					
	Weight			kg	2.8					
Decoration panel 3	Model				BYFQ60B3W1					
	Colour				White (RAL9010)					
	Dimensions	HeightxWidthxDepth		mm	55x700x700					
	Weight			kg	2.7					
Fan-Air flow rate	Cooling	High/Nom./Low		m^3/min	8.5/7/6.5	8.7/7.5/6.5	9/8/6.5	10/8.5/7	11.5/9.5/8	14.5/12.5/10
- 50Hz	Heating	High/Nom./Low		m^3/min	8.5/7/6.5	8.7/7.5/6.5	9/8/6.5	10/8.5/7	11.5/9.5/8	14.5/12.5/10
Air filter	Type				Resin net with mold resistance					
Sound power level	Cooling	High/Nom.		dBA	49/-		50/-	51/-	54/-	60/-
Sound pressure	Cooling	High/Nom./Low		dBA	31.5/28/25.5	32/29.5/25.5	33/30/25.5	33.5/30/26	37/32/28	43/40/33
level	Heating	High/Nom./Low		dBA	31.5/28/25.5	32/29.5/25.5	33/30/25.5	33.5/30/26	37/32/28	43/40/33
Refrigerant	Type / GWP				R-410A / 2.087,5					
Piping connections	Liquid	OD		mm	6.35					
	Gas	OD		mm	12.7					
	Drain				VP20 (I.D. 20/O.D. 26)					
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240					
Current - 50Hz	Maximum fuse amps (MFA)			A	16					
Control systems	Infrared remote control				BRC7F530W (white panel) / BRC7EB530 (standard panel) / BRC7F530S (grey panel)					
	Simplified wired remote control for hotel applications				-					
	Wired remote control				BRC1D52 / BRC1E52A/B					


Dimensions include control box

2-way blow ceiling mounted cassette

Thin, lightweight design installs easily in narrow ceiling spaces

- Depth of all units is 620mm, ideal for narrow ceiling spaces
- Refurbishing the room ? With individual flap control, one or more flaps can be easily closed via the wired remote control






- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating
- Optimum comfort guaranteed with automatic air flow adjustment to the required load
- Maintenance operations can be performed by removing the front panel
- Standard drain pump with 500mm lift increases flexibility and installation speed

Indoor unit			FXCQ	20A	25A	32A	40A	50A	63A	80A	125A
Cooling capacity	Nom.		kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	14.0
Heating capacity	Nom.		kW	2.5	3.2	4.0	5.0	6.3	8.0	10.0	16.0
Power input - 50Hz	Cooling	Nom.	kW	0.031	0.039		0.041	0.059	0.063	0.090	0.149
	Heating	Nom.	kW	0.028	0.035		0.037	0.056	0.060	0.086	0.146
Dimensions	Unit	Height	mm	305							
		Width	mm	775				990		1,445	
		Depth	mm	620							
Weight	Unit		kg	19				22	25	33	38
Casing	Material			Galvanised steel plate							
Decoration panel	Model			BYBCQ40HW1				BYBCQ63HW1		BYBCQ125HW1	
	Colour			Fresh white (6.5Y 9.5/0.5)							
	Dimensions	HeightxWidthxDepth	mm	55x1,070x700				55x1,285x700		55x1,740x700	
	Weight		kg	10				11		13	
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low	m^3/min	10.5/9/7.5	11.5/9.5/8		12/10.5/8.5	15/13/10.5	16/14/11.5	26/22.5/18.5	32/27.5/22.5
Air filter	Type			Resin net with mold resistance							
Sound power level	Cooling	Nom.	dBA	-							
Sound pressure level	Cooling	High/Nom./Low	dBA	32.0/30.0/28.0	34.0/31.0/29.0	34.0/32.0/30.0	36.0/33.0/31.0	37.0/35.0/31.0	39.0/37.0/32.0	42.0/38.0/33.0	46.0/42.0/38.0
	Heating	High/Nom./Low	dBA	32.0/30.0/28.0	34.0/31.0/29.0	34.0/32.0/30.0	36.0/33.0/31.0	37.0/35.0/31.0	39.0/37.0/32.0	42.0/38.0/33.0	46.0/42.0/38.0
Refrigerant	Type / GWP			R-410A / 2.087,5							
Piping connections	Liquid	OD	mm	6.35					9.52		
	Gas	OD	mm	12.7					15.9		
	Drain			VP25 (O.D. 32 / I.D. 25)							
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240							
Current - 50Hz	Maximum fuse amps (MFA)		A	16							
Control systems	Infrared remote control			BRC7C52							
	Simplified wired remote control for hotel applications			-							
	Wired remote control			BRC1D52 / BRC1E52A/B							

Ceiling mounted corner cassette

1-way blow unit for corner installation

› Compact dimensions, can easily be mounted in a narrow ceiling void (only 220mm ceiling space required, 195 with panel spacer, available as accessory)
› Optimum air flow conditions are created by either downward air discharge or frontal air discharge (via optional grille) or a combination of both



› Standard drain pump with 500mm lift increases flexibility and installation speed



FXKQ-M



BRC1E52A/B



BRC4C61

Indoor unit				FXKQ	25MA	32MA	40MA	63MA
Cooling capacity	Nom.			kW	2.8	3.6	4.5	7.10
Heating capacity	Nom.			kW	3.2	4.0	5.0	8.00
Power input - 50Hz	Cooling	Nom.		kW	0.066		0.076	0.105
	Heating	Nom.		kW	0.046		0.056	0.085
Dimensions	Unit	Height		mm	215			
		Width		mm	1,110			1,310
		Depth		mm	710			
Weight	Unit			kg	31			34
Casing	Material				Galvanised steel plate			
Decoration panel	Model				BYK45FJW1			BYK71FJW1
	Colour				White			
	Dimensions	HeightxWidthxDepth		mm	70x1,240x800			70x1,440x800
	Weight			kg	8.5			9.5
Fan-Air flow rate - 50Hz	Cooling	High/Low		m^3/min	11/9		13/10	18/15
Air filter	Type				Resin net with mold resistance			
Sound power level	Cooling	Nom.		dBA	-			
Sound pressure level	Cooling	High/Low		dBA	38.0/33.0		40.0/34.0	42.0/37.0
Refrigerant	Type / GWP				R-410A / 2.087,5			
Piping connections	Liquid	OD		mm	6.35			9.52
	Gas	OD		mm	12.7			15.9
	Drain				VP25 (O.D. 32 / I.D. 25)			
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220			
Current - 50Hz	Maximum fuse amps (MFA)			A	15			
Control systems	Infrared remote control				BRC4C61			
	Simplified wired remote control for hotel applications				-			
	Wired remote control				BRC1D52 / BRC1E52A/B			

Small concealed ceiling unit

Designed for hotel applications

- Compact unit (230mm high & 652mm deep), can easily be mounted in narrow ceiling voids
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Flexible installation, as the air suction direction can be altered from rear to bottom suction
- For easy mounting, the drain pan can be located to the left or right of the unit



FXDQ-M9



BRC1E52A/B




BRC4C62

Indoor unit			FXDQ	20M9	25M9
Cooling capacity	Nom.		kW	2.2	2.8
Heating capacity	Nom.		kW	2.5	3.2
Power input - 50Hz	Cooling	Nom.	kW	0.050	
	Heating	Nom.	kW	0.050	
Dimensions	Unit	Height	mm	230	
		Width	mm	502	
		Depth	mm	652	
Required ceiling void >			mm	250	
Weight	Unit		kg	17	
Casing	Colour			Unpainted	
	Material			Galvanised steel	
Fan-Air flow rate	Cooling	High/Low	m^3/min	6.7/5.2	7.4/5.8
- 50Hz	Heating	High/Low	m^3/min	6.7/5.2	7.4/5.8
Air filter	Type			Resin net with mold resistance	
Sound power level	Cooling	Nom.	dBA	50	
Sound pressure	Cooling	High/Low	dBA	37/32	
level	Heating	High/Low	dBA	37/32	
Refrigerant	Type / GWP			R-410A / 2.087,5	
Piping connections	Liquid	OD	mm	6.35	
	Gas	OD	mm	12.7	
	Drain			I.D. 21.6, O.D. 27.2	
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230	
Current - 50Hz	Maximum fuse amps (MFA)		A	16	
Control systems	Infrared remote control			BRC4C62	
	Simplified wired remote control for hotel applications			BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)	
	Wired remote control			BRC1D52 / BRC1E52A/B	

Slim concealed ceiling unit

Slim design for flexible installation

› Compact dimensions, can easily be mounted in a ceiling void of only 240mm



› Medium external static pressure up to 44Pa facilitates unit use with flexible ducts of varying lengths
› Discretely concealed in the ceiling: only the suction and discharge grilles are visible
› 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
› Reduced energy consumption thanks to specially developed DC fan motor
› Standard drain pump with 750mm lift increases flexibility and installation speed



FXDQ15-32A


BRC1E52A/B BRC4C65

Indoor unit				FXDQ	15A	20A	25A	32A	40A	50A	63A
Cooling capacity	Nom.			kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.			kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.		kW	0.071				0.078	0.099	0.110
	Heating	Nom.		kW	0.068				0.075	0.096	0.107
Dimensions	Unit	Height		mm	200						
		Width		mm	750				950		1,150
		Depth		mm	620						
Required ceiling void >				mm	240						
Weight	Unit			kg	22				26		29
Casing	Colour				Galvanised steel / Non painted						
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low		m^3/min	7.5/7.0/6.4	8.0/7.2/6.4			10.5/9.5/8.5	12.5/11.0/10.0	16.5/14.5/13.0
Fan-External static pressure - 50Hz		High/Nom.		Pa	30/10				44/15		
Air filter	Type				Removable / washable / mildew proof						
Sound power level	Cooling	Nom.		dBA	50	51			52	53	54
Sound pressure level	Cooling	High/Nom./Low		dBA	32/31/27	33/31/27			34/32/28	35/33/29	36/34/30
Refrigerant	Type / GWP				R-410A / 2.087,5						
Piping connections	Liquid	OD		mm	9.52						
	Gas	OD		mm	12.7						15.9
	Drain				VP20 (I.D. 20/O.D. 26)						
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220						
Current - 50Hz	Maximum fuse amps (MFA)			A	16						
Control systems	Infrared remote control				BRC4C65						
	Simplified wired remote control for hotel applications				BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)						
	Wired remote control				BRC1D52 / BRC1E52A/B						

Concealed ceiling unit with medium ESP

Optimum comfort guaranteed no matter the length of ductwork or type of grilles

- Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, whatever the length of duct, making installation easier and guaranteeing comfort. Moreover, the ESP can be changed via the wired remote control to optimize the supply air volume
- Slimmest unit in class, only 245mm
- Low operating sound level
- Medium external static pressure up to 150Pa facilitates using flexible ducts of varying lengths
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- Reduced energy consumption thanks to specially developed DC fan motor
- Flexible installation, as the air suction direction can be altered from rear to bottom suction
- Standard built-in drain pump increases flexibility and installation speed



FXSQ-A



BRC1E52A/B



BRC4C65

Indoor unit				FXSQ	*15A	*20A	*25A	*32A	*40A	*50A	*63A	*80A	*100A	*125A	*140A
Cooling capacity	Nom.			kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0	16.0
Heating capacity	Nom.			kW	1.9	2.50	3.20	4.00	5.0	6.30	8.00	10.00	12.50	16.00	18.00
Power input - 50Hz	Cooling	Nom.		kW	0.041			0.044	0.094	0.096	0.094	0.111	0.118	0.195	0.206
	Heating	Nom.		kW	0.037			0.04	0.09	0.092	0.09	0.107	0.114	0.191	0.202
Dimensions	Unit	Height		mm	245										
		Width		mm	550				700		1,000		1,400		1,550
		Depth		mm	800										
Weight	Unit			kg	24.3			24.5	28		36.6		47.2		51
Fan-Air flow rate - 50Hz	Cooling	High/Low		m^3/min	TBC	9/9.0		9.5/9.5	15/15	15.2/15.2	21.0/21	23/23	28/28	37/37	39/39
Fan-External static pressure - 50Hz	High/Nom.			Pa	150/30							150/40		150/50	130/50
Sound power level	Cooling	Nom.		dBA	TBC	54		55	63		59	63	60	68	69
Sound pressure level	Cooling	High/Low		dBA	TBC	31/-		32/-	37/-			38/-	37/-	42/-	44/-
Refrigerant	Type / GWP				R-410A / 2.087,5										
Piping connections	Liquid	OD		mm	6.35						9.52				
	Gas	OD		mm	12.7						15.9				
	Drain				VP20 (I.D. 20/O.D. 26)										
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/60/220-240										
Current - 50Hz	Maximum fuse amps (MFA)			A	-										
Control systems	Infrared remote control				BRC4C65										
	Simplified wired remote control for hotel applications				BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)										
	Wired remote control				BRC1D52 / BRC1E52A/B										

*Note: blue cells contain preliminary data

Concealed ceiling unit with high ESP

Ideal for large sized spaces

FXMQ-P: ESP up to 200

- Automatic air flow adjustment function measures the air volume and static pressure and adjusts it towards the nominal air flow, whatever the length of duct, making installation easier and guaranteeing comfort. Moreover, the ESP can be changed via the wired remote control to optimize the supply air volume
- High external static pressure up to 200Pa facilitates using flexible ducts of varying lengths
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Reduced energy consumption thanks to specially developed DC fan motor
- Flexible installation, as the air suction direction can be altered from rear to bottom suction
- Standard built-in drain pump increases increases flexibility and installation speed

FXMQ-MA: ESP up to 270

- High external static pressure up to 270Pa facilitates using flexible ducts of varying lengths
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Large capacity unit: up to 31.5 kW heating capacity



FXMQ50P



BRC1E52A/B



BRC4C65

Indoor unit				FXMQ-P7/FXMQ-MA	50P7	63P7	80P7	100P7	125P7	200MA	250MA
Cooling capacity	Nom.			kW	5.6	7.1	9.0	11.2	14.0	22.4	28.0
Heating capacity	Nom.			kW	6.3	8.0	10.0	12.5	16.0	25.0	31.5
Power input - 50Hz	Cooling	Nom.		kW	0.110	0.120	0.171	0.176	0.241	1.294	1.465
	Heating	Nom.		kW	0.098	0.108	0.159	0.164	0.229	1.294	1.465
Dimensions	Unit	Height		mm	300					470	
		Width		mm	1,000			1,400		1,380	
		Depth		mm	700					1,100	
Required ceiling void >				mm	350					-	
Weight	Unit			kg	35			46		137	
Casing	Colour				Unpainted					-	
	Material				Galvanised steel plate						
Decoration panel	Model				BYBS71DJW1			BYBS125DJW1		-	
	Colour				White (10Y9/0.5)					-	
	Dimensions	HeightxWidthxDepth		mm	55x1,100x500			55x1,500x500		-x-x-	
	Weight			kg	4.5			6.5		-	
Fan-Air flow rate	Cooling	High/Nom./Low		m^3/min	18/16.5/15	19.5/17.8/16	25/22.5/20	32/27.5/23	39/33.5/28	58/-/50	72/-/62
- 50Hz	Heating	High/Nom./Low		m^3/min	18/16.5/15	19.5/17.8/16	25/22.5/20	32/27.5/23	39/33.5/28	-/-/-	
Fan-External static pressure - 50Hz	High/Nom.			Pa	200/100					221/132	270/191
Air filter	Type				Resin net with mold resistance					-	
Sound power level	Cooling	High/Nom.		dBA	61/-	64/-	67/-	65/-	70/-	-/-	
Sound pressure	Cooling	High/Nom./Low		dBA	41/39/37	42/40/38	43/41/39		44/42/40	48/-/45	
level	Heating	High/Nom./Low		dBA	41/39/37	42/40/38	43/41/39		44/42/40	-/-/-	
Refrigerant	Type / GWP				R-410A / 2.087,5						
Piping connections	Liquid	OD		mm	6.35	9.52					
	Gas	OD		mm	12.7	15.9				19.1	22.2
	Drain				VP25 (I.D. 25/O.D. 32)					PS1B	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220						
Current - 50Hz	Maximum fuse amps (MFA)			A	16					15	
Control systems	Infrared remote control				BRC4C65						
	Simplified wired remote control for hotel applications				BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)						
	Wired remote control				BRC1D52 / BRC1E52A/B						



Wall mounted unit

For rooms with no false ceilings nor free floor space

- Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- Can easily be installed in both new and refurbishment projects
- 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- Reduced energy consumption thanks to specially developed DC fan motor
- The air is comfortably spread up and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- Maintenance operations can be performed from the front of the unit



FXAQ15-32P



BRC1E52A/B




BRC7E518

Indoor unit			FXAQ	15P	20P	25P	32P	40P	50P	63P
Cooling capacity	Nom.		kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.	kW	0.017	0.019	0.028	0.030	0.020	0.033	0.050
	Heating	Nom.	kW	0.025	0.029	0.034	0.035	0.020	0.039	0.060
Dimensions	Unit	Height	mm	290						
		Width	mm	795				1,050		
		Depth	mm	238						
Weight	Unit		kg	11				14		
Casing	Colour			White (3.0Y8.5/0.5)						
Fan-Air flow rate - 50Hz	Cooling	High/Low	m^3/min	7.0/4.5	7.5/4.5	8/5	8.5/5.5	12/9	15/12	19/14
Air filter	Type			Washable resin net						
Sound power level	Cooling	Nom.	dBA	-						
Sound pressure level	Cooling	High/Low	dBA	34.0/29.0	35.0/29.0	36.0/29.0	37.5/29.0	39.0/34.0	42.0/36.0	47.0/39.0
Refrigerant	Type / GWP			R-410A / 2.087,5						
Piping connections	Liquid	OD	mm	6.35						9.52
	Gas	OD	mm	12.7						15.9
	Drain			VP13 (I.D. 13/O.D. 18)						
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)		A	16						
Control systems	Infrared remote control			BRC7EB518						
	Simplified wired remote control for hotel applications			-						
	Wired remote control			BRC1E52A/B / BRC1D52						

Ceiling suspended unit

For wide rooms with no false ceilings nor free floor space

› Ideal for comfortable air flow in wide rooms thanks to Coanda effect: up to 100° discharge angle



› Even rooms with ceilings up to 3.8m can be heated up or cooled down very easily without capacity loss
› Can easily be installed in both new and refurbishment projects
› Can easily be mounted in corners and narrow spaces, as it only needs 30mm lateral service space
› Reduced energy consumption thanks to specially developed DC fan motor and drain pump
› Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating




Indoor unit				FXHQ	32A	63A	100A
Cooling capacity	Nom.			kW	3.6	7.1	11.2
Heating capacity	Nom.			kW	4.0	8.0	12.5
Power input - 50Hz	Cooling	Nom.		kW	0.107	0.111	0.237
	Heating	Nom.		kW	0.107	0.111	0.237
Dimensions	Unit	Height		mm	235		
		Width		mm	960	1,270	1,590
		Depth		mm	690		
Weight	Unit			kg	24	33	39
Casing	Colour				Fresh White		
	Material				Resin		
Fan-Air flow rate	Cooling	High/Nom./Low		m^3/min	14.0/12.0/10.0	20.0/17.0/14.0	29.5/24.0/19.0
- 50Hz	Heating	High/Nom./Low		m^3/min	14.0/12.0/10.0	20.0/17.0/14.0	29.5/24.0/19.0
Air filter	Type				Resin net with mold resistance		
Sound power level	Cooling	Nom.		dBA	-		
Sound pressure	Cooling	High/Nom./Low		dBA	36.0/34.0/31.0	37.0/35.0/34.0	44.0/37.0/34.0
level	Heating	High/Nom./Low		dBA	36.0/34.0/31.0	37.0/35.0/34.0	44.0/37.0/34.0
Refrigerant	Type / GWP				R-410A / 2.087,5		
Piping connections	Liquid	OD		mm	6.35	9.52	
	Gas	OD		mm	12.7	15.9	
	Drain				VP20 (I.D. 20/O.D. 26)		
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	16		
Control systems	Infrared remote control				BRC7G53		
	Simplified wired remote control for hotel applications				-		
	Wired remote control				BRC1E52A/B / BRC1D52		


4-way blow ceiling suspended unit

Unique Daikin unit for high rooms with no false ceilings nor free floor space

- Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- Can easily be installed in both new and refurbishment projects
- Refurbishing the room ? With individual flap control, one or more flaps can be easily closed via the wired remote control



- Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating
- Optimum comfort guaranteed with automatic air flow adjustment to the required load
- 5 different discharge angles between 0 and 60°can be programmed via the remote control



- Standard drain pump with 500mm lift increases flexibility and installation speed



FXUQ-A



BRC1E52A/B



BRC7CB58

Indoor unit				FXUQ	71A	100A
Cooling capacity	Nom.			kW	8.0	11.2
Heating capacity	Nom.			kW	9.0	12.5
Power input - 50Hz	Cooling	Nom.		kW	0.090	0.200
	Heating	Nom.		kW	0.073	0.179
Dimensions	Unit	Height		mm	198	
		Width		mm	950	
		Depth		mm	950	
Weight	Unit			kg	26	27
Casing	Colour				Fresh White	
	Material				Resin	
Fan-Air flow rate	Cooling	High/Nom./Low		m^3/min	22.5/19.5/16.0	31.0/26.0/21.0
- 50Hz	Heating	High/Nom./Low		m^3/min	22.5/19.5/16.0	31.0/26.0/21.0
Air filter	Type				Resin net with mold resistance	
Sound power level	Cooling	Nom.		dBA	-	
Sound pressure	Cooling	High/Nom./Low		dBA	40.0/38.0/36.0	47.0/44.0/40.0
level	Heating	High/Nom./Low		dBA	40.0/38.0/36.0	47.0/44.0/40.0
Refrigerant	Type / GWP				R-410A / 2.087,5	
Piping connections	Liquid	OD		mm	9.52	
	Gas	OD		mm	15.9	
	Drain				I.D. 20/O.D. 26	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220-230	
Current - 50Hz	Maximum fuse amps (MFA)			A	16	
Control systems	Infrared remote control				BRC7C58	
	Simplified wired remote control for hotel applications				-	
	Wired remote control				BRC1E52A/B / BRC1D52	

Concealed floor standing unit

Designed to be concealed in walls

› Ideal for installation in offices, hotels and residential applications
› Its low height enables the unit to fit perfectly beneath a window
› Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
› Requires very little installation space as the depth is only 200mm
› High ESP allows flexible installation



FXNQ-A



BRC1E52A-B



BRC4C65

Indoor unit				FXNQ	*20A	*25A	*32A	*40A	*50A	*63A
Cooling capacity	Nom.			kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.			kW	2.50	3.20	4.0	5.0	6.3	8.00
Power input - 50Hz	Cooling	Nom.		kW	0.071			0.078	0.099	0.110
	Heating	Nom.		kW	0.068			0.075	0.096	0.107
Dimensions	Unit	Height		mm	620					
		Width		mm	750			950		1,150
		Depth		mm	200					
Weight	Unit			kg	22			26		29
Fan-Air flow rate - 50Hz	Cooling	High/Low		m^3/min	8.0/6.4			10.5/8.5	12.5/10.0	16.5/13.0
Fan-External static pressure - 50Hz	High/Nom.			Pa	30/10			44/15		
Sound power level	Cooling	Nom.		dBA	-					
Sound pressure level	Cooling	High/Low		dBA	-/-					
Refrigerant	Type / GWP				R-410A / 2.087,5					
Piping connections	Liquid	OD		mm	6.35					9.52
	Gas	OD		mm	12.7					15.9
	Drain				VP20 (I.D. 20/O.D. 26)					
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)			A	-					
Control systems	Infrared remote control				BRC4C65					
	Simplified wired remote control for hotel applications				BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)					
	Wired remote control				BRC1D52 / BRC1E52A/B					

*Note: blue cells contain preliminary data

Floor standing unit

For perimeter zone air conditioning

- Unit can be installed as free standing model by use of optional back plate
- Its low height enables the unit to fit perfectly beneath a window
- Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011) blends easily with any interior
- Requires very little installation space
- Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate



- Wired remote control can easily be integrated in the unit



FXLQ20,25P



BRC1E52A/B



BRC4C65


Indoor unit				FXLQ	20P	25P	32P	40P	50P	63P
Cooling capacity	Nom.			kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.			kW	2.5	3.2	4.0	5.0	6.3	8.000
Power input - 50Hz	Cooling	Nom.		kW	0.049		0.090		0.110	
	Heating	Nom.		kW	0.049		0.090		0.110	
Dimensions	Unit	Height		mm	600					
		Width		mm	1,000		1,140		1,420	
		Depth		mm	232					
Weight	Unit			kg	27		32		38	
Casing	Colour				Fresh white (RAL9010) / Dark grey (RAL7011)					
Fan-Air flow rate - 50Hz	Cooling	High/Low		m^3/min	7/6		8/6	11/8.5	14/11	16/12
Air filter	Type				Resin net					
Sound power level	Cooling	Nom.		dBA	-					
Sound pressure level	Cooling	High/Low		dBA	35/32			38/33	39/34	40/35
Refrigerant	Type / GWP				R-410A / 2.087,5					
Piping connections	Liquid	OD		mm	6.35					9.52
	Gas	OD		mm	12.7					15.9
	Drain				O.D. 21 (Vinyl chloride)					
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)			A	15					
Control systems	Infrared remote control				BRC4C65					
	Simplified wired remote control for hotel applications				BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)					
	Wired remote control				BRC1D52 / BRC1E52A/B					

Low temperature hydrobox for VRV

For high efficiency space heating and cooling

- Air to water connection to VRV for applications such as underfloor, air handling units, low temperature radiators, …
- Leaving water temperature range from 5°C to 45°C without electric heater
- Super wide operating range for hot/cold water production from -20 to +43°C ambient outdoor temperature
- Saves time on system design as all water-side components are fully integrated with direct control over leaving water temperature
- Space saving contemporary wall hung design
- No gas connection or oil tank needed
- Connectable to VRV IV heat pump and heat recovery


HXY-A




Indoor unit				HXY	080A	125A
Cooling capacity	Nom.			kW	8	12.5
Heating capacity	Nom.			kW	9	14
Dimensions	Unit	HeightxWidthxDepth		mm	890x480x344	
Weight	Unit			kg	44	
Casing	Colour				White	
	Material				Precoated sheet metal	
Sound pressure level	Nom.			dBA	-	
Operation range	Heating	Ambient	Min.~Max.	°C	-20~24	
		Water side	Min.~Max.	°C	25~45	
	Domestic hot water	Ambient	Min.~Max.	°CDB	N/A	
		Water side	Min.~Max.	°C	N/A	
Refrigerant	Type / GWP				R-410A / 2.087,5	
Refrigerant circuit	Gas side diameter			mm	15.9	
	Liquid side diameter			mm	9.5	
Water circuit	Piping connections diameter			inch	G 1"1/4 (female)	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240	
Current	Recommended fuses			A	6~16	

High temperature hydrobox for VRV

For efficient hot water production and space heating

- Air to water connection to VRV for applications such as bathrooms, sinks, underfloor heating, radiators and air handling units
- Leaving water temperature range from 25 to 80°C without electric heater
- Free heating provided by transferring heat from areas requiring cooling to areas requiring heating or hot water
- Uses heat pump technology to produce hot water efficiently, providing up to 17% savings compared to a gas boiler
- Possibility to connect thermal solar collectors to the domestic hot water tank
- Super wide operating range for hot water production from -20 to +43°C ambient outdoor temperature
- Saves time on system design as all water-side components are fully integrated with direct control over leaving water temperature
- Various control possibilities with weather dependant set point or thermostat control
- The indoor unit and domestic hot water tank can be stacked to save space, or installed next to each other, if only limited height is available
- No gas connection or oil tank needed
- Connectable to VRV IV heat recovery





Indoor unit				HXHD
				125A
Heating capacity	Nom.			kW
Dimensions	Unit	HeightxWidthxDepth		mm
Weight	Unit			kg
Casing	Colour			
	Material			
Sound pressure level	Nom.			dBA
	Night quiet mode	Level 1		dBA
Operation range	Heating	Ambient	Min.~Max.	°C
		Water side	Min.~Max.	°C
	Domestic hot water	Ambient	Min.~Max.	°CDB
		Water side	Min.~Max.	°C
Refrigerant	Type / GWP			
	Charge			kg
	Charge			TCO_2Eq
Refrigerant circuit	Gas side diameter			mm
	Liquid side diameter			mm
Water circuit	Piping connections diameter			inch
	Heating water system	Water volume	Min.~Max.	l
Power supply	Phase/Frequency/Voltage			Hz/V
Current	Recommended fuses			A
				14.0
				705x600x695
				92
				Metallic grey
				Precoated sheet metal
				42 (1) / 43 (2)
				38
				-20~20 / 24 (3)
				25~80
				-20~43
				45~75
				R-134a / 1,430
				2
				2.9
				12.7
				9.52
				G 1" (female)
				20~200
				1~/50/220-240
				20

(1) Sound levels are measured at: EW 55°C; LW 65°C (2) Sound levels are measured at: EW 70°C; LW 80°C (3) Field setting

EKHTS-AC

Domestic hot water tank

Stackable stainless steel domestic hot water tank

- The indoor unit and domestic hot water tank can be stacked to save space, or installed next to each other, if only limited height is available
- Available in 200 and 260 liters
- Heat loss is reduced to a minimum thanks to the high quality insulation
- At necessary intervals, the indoor unit can heat up the water to 60°C to prevent the risk of bacteria growth
- Efficient temperature heat-up: from 10°C to 50°C in only 60 minutes



EKHTS200AC



EKHTS260AC

Accessory				EKHTS	200AC	260AC
Casing	Colour				Metallic grey	
	Material				Galvanised steel (precoated sheet metal)	
Dimensions	Unit	Height	Integrated on indoor unit	mm	2,010	2,285
		Width		mm	600	
		Depth		mm	695	
Weight	Unit	Empty		kg	70	78
Tank	Water volume			l	200	260
	Material				Stainless steel (EN 1.4521)	
	Maximum water temperature			°C	75	
	Insulation	Heat loss		kWh/24h	1.2	1.5
Heat exchanger	Quantity				1	
	Tube material				Duplex steel (EN 1.4162)	
	Face area			m^2	1.56	
	Internal coil volume			l	7.5	

EKHWP-B

Domestic hot water tank

Plastic domestic hot water tank with solar support

- Available in 300 and 500 liters
- Large hot water storage tank to provide domestic hot water at any time
- Heat loss is reduced to a minimum thanks to the high quality insulation
- Space heating support possible (500l tank only)



EKHWP300B

Accessory			EKHWP	300B	500B
Dimensions	Unit	Width	mm	595	790
		Depth	mm	615	790
Weight	Unit	Empty	kg	59	93
Tank	Water volume		l	300	500
	Maximum water temperature		°C	85	
	Insulation	Heat loss	kWh/24h	1.3	1.4
Heat exchanger	Domestic hot water	Tube material		Stainless steel	
		Face area	m^2	5.8	6
		Internal coil volume	l	27.9	29
		Operating pressure	bar	6	
		Average specifc thermal output	W/K	2,790	2,900
	Charging	Tube material		Stainless steel	
		Face area	m^2	2.7	3.8
		Internal coil volume	l	13.2	18.5
		Operating pressure	bar	3	
		Average specifc thermal output	W/K	1,300	1,800
	Auxiliary solar heating	Tube material		Stainless steel	
		Face area	m^2	-	0.5
		Internal coil volume	l	-	2.3
		Operating pressure	bar	3	
		Average specifc thermal output	W/K	-	280

EKSRPS

Pump station

- Save energy and reduce CO_2 emissions with a solar system for domestic hot water production
- Pump station connectable to unpressurised solar system
- Pump station and control provide the transfer of solar heat to the domestic hot water tank



EKSRPS3

Accessory				EKSRPS
				3
Mounting				On side of tank
Dimensions	Unit	HeightxWidthxDepth	mm	815x230x142
Control	Type			Digital temperature difference controller with plain text display
	Power consumption		W	2
Power supply	Voltage		V	230
Sensor	Solar panel temperature sensor			Pt1000
	Storage tank sensor			PTC
	Return flow sensor			PTC
	Feed temperature and flow sensor			Voltage signal (3.5V DC)

EKS(H/V)-P

Solar collector

Thermal solar collector for hot water production

- Solar collectors can produce up to 70% of the energy needed for hot water production - a major cost saving
- Vertical or horizontal solar collector for domestic hot water production
- High efficiency collectors transfer all the short-wave solar radiation into heat as a result of their highly selective coating
- Easy to install on roof tiles




EKSH-P



EKSV-P

Accessory				EKSV21P	EKSV26P	EKSH26P
Dimensions	Unit	HeightxWidthxDepth	mm	2,000x1,006x85	2,000x1,300x85	1,300x2,000x85
Weight	Unit		kg	35	42	
Volume			l	1.3	1.7	2.1
Surface	Outer		m^2	2.01	2.6	
	Aperture		m^2	1.79	2.35	
	Absorber		m^2	1.8	2.36	
Coating				Micro-therm (absorption max. 96%, Emission ca. 5% +/-2%)		
Absorber				Harp-shaped copper pipe register with laser-welded highly selective coated aluminium plate		
Glazing				Single pane safety glass, transmission +/- 92%		
Allowed roof angle	Min.~Max.		°	15~80		
Operating pressure	Max.		bar	6		
Stand still temperature	Max.		°C	200		



Daikin offers the widest range in DX ventilation in the market.
With a variety of ventilation solutions from small heat recovery ventilation to large scale air handling units we help provide a fresh, healthy and comfortable environment in offices, hotels, stores and other commercial environments.

Ventilation & biddle air curtains

Ventilation 258

Heat reclaim ventilation
VAM-FA/FB 262
VH - electrical heater 263
VKM-GB(M) 264

Air handling applications
Overview & control possibilities 265
VRV 268
ERQ 270
Expansion valves and control boxes 271

Biddle air curtains

Biddle air curtain for ERQ 272
Biddle air curtain for VRV and Conveni-pack 273

For more information on Options & Accessories,
please refer to page 454 of this catalogue.



VAM - HEAT RECLAIM VENTILATION



CYV BIDDLE AIR CURTAIN








DAIKIN AIR HANDLING UNIT AND ERQ/VRV PLUG & PLAY CONNECTION


Heat reclaim ventilation

Ventilation with heat recovery as standard

- Energy saving ventilation using indoor heating, cooling and moisture recovery
- Ideal solution for shops, restaurants or offices requiring maximum floor space for furniture, decorations and fittings
- Free cooling possible when outdoor temperature is below indoor temperature (eg. during nighttime)
- Reduced energy consumption thanks to specially developed DC fan motor
- Prevent energy losses from over-ventilation while maintaining indoor air quality with optional CO2 sensor
- Can be used as stand alone unit or integrated in the VRV system
- Wide range of units: air flow rate from 150 up to 2,000 m^3/h
- High efficiency filters available in F6 ,F7, F8 grades
- Shorter installation time thanks to easy adjustment of nominal air flow rate, so less need for dampers compared with traditional installation.
- Specially developed heat exchange element with High Efficiency Paper (HEP)
- No drain piping needed
- Can operate in over- and under pressure
- Total solution for fresh air with Daikin supply of both VAM and electrical heaters



VAM-FA-FB



Fine dust filter

Ventilation				VAM	150FA	250FA	350FB	500FB	650FB	800FB	1000FB	1500FB	2000FB
Power input - 50Hz	Heat exchange mode	Nom.	Ultra high	kW	0.116	0.141	0.132	0.178	0.196	0.373	0.375	0.828	0.852
	Bypass mode	Nom.	Ultra high	kW	0.116	0.141	0.132	0.178	0.196	0.373	0.375	0.828	0.852
Temperature exchange efficiency - 50Hz	Ultra high/High/Low			%	74/74/79	72/72/77	75/75/80	74/74/77		74/74/76	75/75/76.5	75/75/78	
Enthalpy exchange efficiency - 50Hz	Cooling	Ultra high/High/Low		%	58/58/64	58/58/62	61/61/67	58/58/63		60/60/62	61/61/63	61/61/64	61/61/66
	Heating	Ultra high/High/Low		%	64/64/69	64/64/68	65/65/70	62/62/67	63/63/66	65/65/67	66/66/68		66/66/70
Operation mode					Heat exchange mode / Bypass mode / Fresh-up mode								
Heat exchange system					Air to air cross flow total heat (sensible + latent heat) exchange								
Heat exchange element					Specially processed non-flammable paper								
Dimensions	Unit	HeightxWidthxDepth		mm	285x776x525		301x828x816		364x1,004x868		364x1,004x1,156	726x1,512x868	726x1,512x1,156
Weight	Unit			kg	24		33		52	55	64	131	152
Casing	Material				Galvanised steel plate								
Fan-Air flow rate - 50Hz	Heat exchange mode	Ultra high		m^3/h	150	250	350	500	650	800	1,000	1,500	2,000
	Bypass mode	Ultra high		m^3/h	150	250	350	500	650	800	1,000	1,500	2,000
Fan-External static pressure - 50Hz	Ultra high			Pa	69	64	98		93	137	157	137	
	High			Pa	39		-						
	Low			Pa	20		-						
Air filter	Type				Multidirectional fibrous fleeces								
Sound pressure level - 50Hz	Heat exchange mode	Ultra high		dBA	27 / 28.5	28 / 29	32	33	34.5	36		39.5	40
	Bypass mode	Ultra high		dBA	27 / 28.5	28 / 29	32	33.5	34.5	36		40.5	40
Operation range	Min.			°CDB	-15								
	Max.			°CDB	50								
	Relative humidity			%	80% or less								
Refrigerant	Type / GWP				- / -								
Connection duct diameter				mm	100	150		200		250		350	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220								
Current	Maximum fuse amps (MFA)			A	15		16						

VH

- Total solution for fresh air with Daikin supply of both VAM and electrical heaters
- Increased comfort in low outdoor temperature thanks to the heated outdoor air
- Integrated electrical heater concept (no additional accessories required)
- Standard dual flow and temperature sensor
- Flexible setting with adjustable setpoint
- Increased safety with 2 cut-outs: manual & automatic
- BMS integration thanks to:
  - Volt free relay for error indication
  - 0-10VDC input for setpoint control



ELECTRICAL HEATER FOR VAM VH	(VH)
Supply voltage	220/250V ac 50/60 Hz. +/-10%
Output current (maximum)	19A at 40°C (ambient)
Temperature sensor	5k ohms at 25°C (table 502 1T)
Temperature control range	0 to 40°C / (0-10V 0-100%)
Control fuse	20 x 5mm 250mA
LED indicators	Power ON - Yellow Heater ON - Red (solid or flashing, indicating pulsed control) Airflow fault - Red
Mounting holes	98mm x 181mm centres 5 mm ø holes
Maximum ambient adjacent to terminal box	35°C (during operation)
Auto high temp. cutout	100°C Pre-set
Man. reset high temp. cutout	125°C Pre-set
Run relay	1A 120V AC or 1A 24V DC
BMS setpoint input	0-10VDC

VH		1B	2B	3B	4B	4/AB	5B
Capacity	kW	1	1	1	1.5	2.5	2.5
Duct diameter	mm	100	150	200	250	250	300
Connectable VAM		VAM150FA	VAM250FA	VAM500FB	VAM800FB	VAM800FB	VAM1500FB
		-	VAM350FB	VAM650FB	VAM1000FB	VAM1000FB	VAM2000FB

For the selection of the appropriate capacity, please refer to the VAM selection software.

Heat reclaim ventilation and air processing

Pre heating or cooling of fresh air for lower load on the air conditioning system

- Energy saving ventilation using indoor heating, cooling and moisture recovery
- Creates a high quality indoor environment by pre conditioning incoming fresh air
- Humidification of the incoming air results in comfortable indoor humidity level, even during heating
- Ideal solution for shops, restaurants or offices requiring maximum floor space for furniture, decorations and fittings
- Free cooling possible when outdoor temperature is below indoor temperature (eg. during nighttime)
- Low energy consumption thanks to DC fan motor
- Prevent energy losses from over-ventilation while maintaining indoor air quality with optional CO2 sensor
- Shorter installation time thanks to easy adjustment of nominal air flow rate, so less need for dampers compared with traditional installation.
- Specially developed heat exchange element with High Efficiency Paper (HEP)
- Can operate in over- and under pressure



VKM80-100GB(M)


						Heat reclaim ventilation and air processing			Heat reclaim ventilation, air processing and humidification		
Ventilation					**VKM**	**50GB**	**80GB**	**100GB**	**50GBM**	**80GBM**	**100GBM**
Power input - 50Hz	Heat exchange mode	Nom.	Ultra high		kW	0.270	0.330	0.410	0.270	0.330	0.410
	Bypass mode	Nom.	Ultra high		kW	0.270	0.330	0.410	0.270	0.330	0.410
Fresh air conditioning load	Cooling				kW	4.71 / 1.91 / 3.5	7.46 / 2.96 / 5.6	9.12 / 3.52 / 7.0	4.71 / 1.91 / 3.5	7.46 / 2.96 / 5.6	9.12 / 3.52 / 7.0
	Heating				kW	5.58 / 2.38 / 3.5	8.79 / 3.79 / 5.6	10.69 / 4.39 / 7.0	5.58 / 2.38 / 3.5	8.79 / 3.79 / 5.6	10.69 / 4.39 / 7.0
Temperature exchange efficiency - 50Hz	Ultra high/High/Low				%	76/76/77.5	78/78/79	74/74/76.5	76/76/77.5	78/78/79	74/74/76.5
Enthalpy exchange efficiency - 50Hz	Cooling	Ultra high/High/Low			%	64/64/67	66/66/68	62/62/66	64/64/67	66/66/68	62/62/66
	Heating	Ultra high/High/Low			%	67/67/69	71/71/73	65/65/69	67/67/69	71/71/73	65/65/69
Operation mode						Heat exchange mode / Bypass mode / Fresh-up mode					
Heat exchange system						Air to air cross flow total heat (sensible + latent heat) exchange					
Heat exchange element						Specially processed non-flammable paper					
Humidifier	System					-			Natural evaporating type		
Dimensions	Unit	HeightxWidthxDepth			mm	387x1,764x832	387x1,764x1,214		387x1,764x832	387x1,764x1,214	
Weight	Unit				kg	94	110	112	100	119	123
Casing	Material					Galvanised steel plate					
Fan-Air flow rate - 50Hz	Heat exchange mode	Ultra high			m^3/h	500	750	950	500	750	950
	Bypass mode	Ultra high			m^3/h	500	750	950	500	750	950
Fan-External static pressure - 50Hz	Ultra high				Pa	210		150	200	205	110
	High				Pa	170	160	100	150	155	70
	Low				Pa	140	110	70	120	105	60
Air filter	Type					Multidirectional fibrous fleeces					
Sound pressure level - 50Hz	Heat exchange mode	Ultra high			dBA	39	41.5	41	38	40	
	Bypass mode	Ultra high			dBA	40	41.5	41	39	41	
Operation range	Around unit				°CDB	0°C~40°CDB, 80% RH or less					
	Supply air				°CDB	-15°C~40°CDB, 80% RH or less					
	Return air				°CDB	0°C~40°CDB, 80% RH or less					
	On coil temperature	Cooling	Max.		°CDB	-15					
		Heating	Min.		°CDB	43					
Refrigerant	Type / GWP					R-410A / 2.087,5					
Connection duct diameter					mm	200	250		200	250	
Piping connections	Liquid	OD			mm	6.35					
	Gas	OD			mm	12.7					
	Water supply				mm	-			6.4		
	Drain					PT3/4 external thread					
Power supply	Phase/Frequency/Voltage				Hz/V	1~/50/220-240					
Current	Maximum fuse amps (MFA)				A	15					

Air handling applications

Wide range of air flows

For applications that require big volumes of treated fresh air (large atriums, banquet halls, etc) air handling units represent the ideal solution.
Daikin's wide range of air handling units treat air volumes from 500 m^3/h up to 140,000 m^3/h.

The air handling unit can be designed to deliver whatever air flow you require, via the specific dimensions of flow section available at the installation.



Professional
- Pre-configured sizes
- Tailored to the individual customer
- Modular construction

Energy
- High-end solution for optimised energy consumption
- High efficiency components
- Strong Return on Investment

NEW Compact
- Pre-configured sizes
- Plug & Play concept
- EC Fan Technology
- High Efficiency Heat Wheel
- Compact Design

Dainkin fresh air package - plug & play

The D-AHU Professional and Energy series provide a complete solution including unit control (EKEXV, EKEQ, DDC controller) factory mounted and configured, plug & play with our ERQ and VRV condensing units.
The easiest solution as you save time and only have one point of contact!

Pre-defined sizes

27 fixed sizes are available, optimized to reach the optimum combination between value for money and manufacturing standardisation. Daikin's section by section design means that units can be sized by 1cm increments and assembled on site, without welding, to suit the space constraints of the installation.

Return on investment

The air handling unit (AHU) is critical to an effective climate control system and the savings generated by our advanced designs and operating efficiencies guarantee a rapid return on the investment made. Our AHU Energy series has been designed to deliver exceptional performance thus driving down the energy consumed and so lowering energy bills. Taken over the expected 15-year life-span of the equipment, this will result in a substantial saving, especially in a time of ever increasing energy prices.

High efficiency components


All Daikin air handling units have been designed for optimum energy efficiency. Polyurethane or Mineral wool panels guarantee excellent thermal insulation performance. And the widest range of filters are provided to meet even the most strict demands.

Why use ERQ and VRV condensing units for connection to air handling units?

High Efficiency

Daikin heat pumps are renowned for their high energy efficiency with COPs up to 4.56 in heating1. The VRV range offers both heat pump and heat recovery units with seasonal efficiencies as high as 8, thanks to heat recovery and Variable Refrigerant Temperature. Integrating the AHU with a heat recovery system is highly effective since an office system can frequently be in cooling mode while the outdoor air is too cold to be brought inside in an unconditioned state. In this case heat from the offices is merely transferred to heat up the cold incoming fresh air. In the absence of an AHU this 'free heating' the incoming fresh air would not be possible.

1 ERQ100AV1 heat pump
2 REYQ8P8 50% cooling - 50% heating load. Conditions: outdoor temperature 11°CDB, indoor temperature 18°CWB, 22°CDB



High comfort levels

Daikin ERQ and VRV units respond rapidly to fluctuations in supply air temperature, resulting in a steady indoor temperature and resultant high comfort levels for the end user. Daikin ERQ and VRV units respond rapidly to fluctuations in the supply air temperature, resulting in a steady indoor temperature, together with the dehumidification this results in high comfort levels for the end user. The ultimate is the VRV range which improves comfort even more by offering continuous heating, also during defrost.

Easy Design and Installation

The system is easy to design and install since no additional water systems such as boilers, tanks and gas connections etc. are required. This also reduces both the total system investment and running cost.


In order to maximize installation flexibility, 4 types of control systems are offered

Control w: Off the shelf control of air temperature (discharge temperature, suction temperature, room temperature) via any DDC controller
Control x: Precize control of air temperature (discharge temperature, suction temperature, room temperature) requiring a preprogrammed DDC controller (for special applications)

Control y: Control of refrigerant (Te/Tc) temperature via Daikin control (no DDC controller needed)
Control z: Control of air temperature (suction temperature, room temperature) via Daikin control (no DDC controller needed)


Possibility W (Td/Tr control):

Air temperature control via DDC controller
Room temperature is controlled as a function of the air handling unit suction or discharge air (customer selection). The DDC controller is translating the temperature difference between set point and air suction temperature (or air discharge temperature or room temperature) into a proportional 0-10V signal which is transferred to the Daikin control box (EKEQFCBA). This voltage controls the compressor frequency.




Possibility X (Td/Tr control):

Precise air temperature control via DDC controller
Room temperature is controlled as a function of the air handling unit suction or discharge air (customer selection). The DDC controller is translating the temperature difference between set point and air suction temperature (or air discharge temperature or room temperature) into a reference voltage (0-10V) which is transferred to the Daikin control box (EKEQFCBA). This reference voltage will be used as the main input value for the compressor frequency control.




Possibility Y (Te/Tc control):

By fixed evaporating /condensing temperature
A fixed target evaporating temperature of between 3°C and 8°C can be set by the customer. In this case, room temperature is only indirectly controlled. The cooling load is determined from the actual evaporating temperature (i.e. load to the heat exchanger). A Daikin infrared remote control (BRC1D52 or BRC1E52A/B - optional) can be connected for error indication.



Possibility Z (Ts/Tr control):

Control your AHU just like a VRV indoor unit with 100% fresh air
(BRC1D52 or BRC1E52A/B - optional)
Set point can be fixed via standard Daikin infrared remote control.
Remote ON/OFF can be achieved by an optional adapter KRP4A51.
No external DDC controller should be connected. The cooling load is determined from the air suction temperature and set point on the Daikin controller.



Ts = Air suction temperature	Tr = Room temperature	AHU = Air Handling Unit
Td = Air discharge temperature	Te = Evaporating temperature	DDC = Digital Display Controller

	Option kit	Features
Possibility w	EKEQFCBA	DDC controller is required temperature control using air suction or air discharge temperature
Possibility x		DDC and Microtech controller is required Precise Temperature control using air suction or air discharge temperature
Possibility y		Using fixed evaporating temperature, no set point can be set using remote control
Possibility z	EKEQDCB EKFQMCBA*	Using Daikin infrared remote control BRC1D52 or BRC1E52A/B Temperature control using air suction temperature

* EKEQMCB (for 'multi' application)


A R-410A inverter condensing units range for multi application with air handling units

- Inverter controlled units
- Large capacity range (from 8 to 54HP)
- Heat recovery, heat pump
- R-410A
- Control of room temperature via Daikin control
- Large range of expansion valve kits available
- BRC1E52A/B is used to set the set point temperature (connected to the EKEQMCBA).
- Connectable to all VRV heat recovery and heat pump systems




W, X, Y control for VRV IV heat pump

R*YQ8-20T




R*YQ12-54T





Z control for all VRV outdoor units



Refrigerant piping
F1-F2
other communication


ERQ

A range of R-410A inverter condensing units for pair application with air handling units

- Inverter controlled units
- Large capacity range (from 100 to 250 class)
- Heat pump
- R-410A
- Wide range of expansion valve kits available
- Up to 4 ERQ units can be connected to an interlaced coil in one air handling unit
- Basic DX solution for fresh air

The "Daikin Fresh Air Package" provides a complete Plug & Play Solution including AHU, ERQ or VRV Condensing Unit and all unit control (EKEQ, EKEX, DDC controller) factory mounted and configured. The easiest solution with only one point of contact.

Daikin air handling unit



F1 - F2

Refrigerant piping

Ventilation			ERQ	100AV1	125AV1	140AV1
Capacity range			HP	4	5	6
Cooling capacity	Nom.		kW	11.2	14.0	15.5
Heating capacity	Nom.		kW	12.5	16.0	18.0
Power input	Cooling	Nom.	kW	2.81	3.51	4.53
	Heating	Nom.	kW	2.74	3.86	4.57
EER				3.99		3.42
COP				4.56	4.15	3.94
Dimensions	Unit		mm	1,345x900x320		
Weight	Unit		kg	120		
Fan-Air flow rate	Cooling	Nom.	m^3/min	106		
	Heating	Nom.	m^3/min	102	105	
Sound power level	Cooling	Nom.	dBA	66	67	69
Sound pressure level	Cooling	Nom.	dBA	50	51	53
	Heating	Nom.	dBA	52	53	55
Operation range	Cooling	Min./Max.	°CDB	-5/46		
	Heating	Min./Max.	°CWB	-20/15.5		
	On coil	Heating Min.	°CDB	10		
	temperature	Cooling Max.	°CDB	35		
Refrigerant	Type / GWP			R-410A / 2.087,5		
	Charge		kg	4.0		
	Charge		TCO_2Eq	8.4		
Piping connections	Liquid	OD	mm	9.52		
	Gas	OD	mm	15.9		19.1
	Drain	OD	mm	26x3		
Power supply	Phase/Frequency/Voltage		Hz/V	1N~/50/220-240		
Current	Maximum fuse amps (MFA)		A	32.0		

Ventilation			ERQ	125AW1	200AW1	250AW1
Capacity range			HP	5	8	10
Cooling capacity	Nom.		kW	14.0	22.4	28.0
Heating capacity	Nom.		kW	16.0	25.0	31.5
Power input	Cooling	Nom.	kW	3.52	5.22	7.42
	Heating	Nom.	kW	4.00	5.56	7.70
EER				3.98	4.29	3.77
COP				4.00	4.50	4.09
Dimensions	Unit		mm	1,680x635x765	1,680x930x765	
Weight	Unit		kg	159	187	240
Fan-Air flow rate	Cooling	Nom.	m^3/min	95	171	185
	Heating	Nom.	m^3/min	95	171	185
Sound power level	Nom.		dBA	72	78	
Sound pressure level	Nom.		dBA	54	57	58
Operation range	Cooling	Min./Max.	°CDB	-5/43		
	Heating	Min./Max.	°CWB	-20/15		
	On coil	Heating Min.	°CDB	10		
	temperature	Cooling Max.	°CDB	35		
Refrigerant	Type / GWP			R-410A / 2.087,5		
	Charge		kg	6.2	7.7	8.4
	Charge		TCO_2Eq	12.9	16.1	17.5
Piping connections	Liquid	OD	mm	9.52		
	Gas	OD	mm	15.9	19.1	22.2
Power supply	Phase/Frequency/Voltage		Hz/V	3N~/50/400		
Current	Maximum fuse amps (MFA)		A	16	25	

Daikin also offers a range of expansion valve kits and control boxes to connect ERQ and VRV condensing units to third party air handling units

Combination table

			Control box			Expansion valve kit									
Outdoor unit			EKEQDCBV3	EKEQFCBAV3	EKEQMCBAV3	EKEXV50	EKEXV63	EKEXV80	EKEXV100	EKEXV125	EKEXV140	EKEXV200	EKEXV250	EKEXV400	EKEXV500
System A	1-phase	ERQ100	P	P		-	P	P	P	P	-	-	-	-	-
		ERQ125	P	P		-	P	P	P	P	P	-	-	-	-
		ERQ140	P	P		-	-	P	P	P	P	-	-	-	-
	3-phase	ERQ125	P	P		-	P	P	P	P	P	-	-	-	-
		ERQ200	P	P		-	-	-	P	P	P	P	P	-	-
		ERQ250	P	P		-	-	-	-	P	P	P	P	-	-
System B	VRV III				n1	n1	n1	n1	n1	n1	n1	n1	n1	n1	n1
System B	VRV IV			1 -> 3	n2	n2	n2	n2	n2	n2	n2	n2	n2	n2	n2

- P (pair application): combination depends on the capacity of the air handling unit
- n1 (multi application: combination of air handling units and VRV DX indoor units): to determine the quantity, refer to the engineering data book
- n2 (multi application: multiple air handling units, or the combination of air handling units and VRV DX indoor units): to determine the quantity, refer to the engineering data book
- Control box EKEQFA can be connected to some types of VRV IV outdoor units (with a maximum of 3 boxes per unit). Do not combine EKEQFA control boxes with VRV DX indoor units, RA indoor units or hydroboxes

Capacity table

Cooling

EKEXV Class	Allowed heat exchanger capacity (kW)	
	Minimum	Maximum
50	5,0	6,2
63	6,3	7,8
80	7,9	9,9
100	10,0	12,3
125	12,4	15,4
140	15,5	17,6
200	17,7	24,6
250	24,7	30,8
400	35,4	49,5
500	49,6	61,6

Saturated evaporating temperature: 6°C
Air temperature: 27°C DB / 19°C WB

Heating

EKEXV Class	Allowed heat exchanger capacity (kW)	
	Minimum	Maximum
50	5,6	7,0
63	7,1	8,8
80	8,9	11,1
100	11,2	13,8
125	13,9	17,3
140	17,4	19,8
200	19,9	27,7
250	27,8	34,7
400	39,8	55,0
500	55,1	69,3

Saturated condensing temperature: 46°C
Air temperature: 20°C DB

EKEXV - Expansion valve kit for air handling applications

Ventilation			EKEXV	50	63	80	100	125	140	200	250	400	500
Dimensions	Unit		mm	401x215x78									
Weight	Unit		kg	2.9									
Sound pressure level	Nom.		dBA	45									
Operation range	On coil	Heating Min.	°CDB	10 (1)									
	temperature	Cooling Max.	°CDB	35 (2)									
Refrigerant	Type / GWP			R-410A / 2.087,5									
Piping connections	Liquid	OD	mm	6.35	9.52							12.7	15.9

(1) The temperature of the air entering the coil in heating mode can be reduced to -5°CDB. Contact your local dealer for more information. (2) 45% Relative humidity.


EKEQ - Control box for air handling applications

Ventilation		EKEQ	FCBA	DCB	MCBA
Application			See note	Pair	Multi
Outdoor unit			ERQ / VRV	ERQ	VRV
Dimensions	Unit	mm	132x400x200		
Weight	Unit	kg	3.9	3.6	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/230		

The combination of EKEQFCBA and ERQ is in pair application. The EKEQFCBA can be connected to some type of VRV IV outdoor units with a maximum of 3 control boxes. The combination with DX indoor units, hydroboxes, RA outdoor units, ... is not allowed. Refer to the combination table drawing of the outdoor unit for details.

Biddle air curtain for ERQ

- Connectable to ERQ heat pump
- ERQ is among the first DX systems suitable for connection to air curtains
- Free-hanging model (F): easy wall mounted installation
- Cassette model (C): mounted into a false ceiling leaving only the decoration panel visible
- Recessed model (R): neatly concealed in the ceiling
- A payback period of less then 1.5 years compared to installing an electric air curtain
- Easy and quick to install at reduced costs since no additional water systems, boilers and gas connections are required
- Maximum energy efficiency stemming from almost zero down flow turbulence, optimised air flow and the application of advanced discharge rectifier technology
- Around 85% air separation efficiency, greatly reducing both heat loss and required indoor unit heating capacity






				Small			Medium			
				CYQS150DK80 *BN/*SN	CYQS200DK100 *BN/*SN	CYQS250DK140 *BN/*SN	CYQM100DK80 *BN/*SN	CYQM150DK80 *BN/*SN	CYQM200DK100 *BN/*SN	CYQM250DK140 *BN/*SN
Heating capacity	Speed 3		kW	9.0	11.6	16.2	9.2	11.0	13.4	19.9
Power input	Fan only	Nom.	kW	0.35	0.46	0.58	0.37	0.56	0.75	0.94
	Heating	Nom.	kW	0.35	0.46	0.58	0.37	0.56	0.75	0.94
Delta T	Speed 3		K	15		16	17	14	13	15
Casing	Colour			BN: RAL9010 / SN: RAL9006						
Dimensions	Unit	Height F/C/R	mm	270/270/270						
		Width F/C/R	mm	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548
		Depth F/C/R	mm	590/821/561						
Required ceiling void >			mm	420						
Door height	Max.		m	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)
Door width	Max.		m	1.5	2.0	2.5	1.0	1.5	2.0	2.5
Weight	Unit		kg	66	83	107	57	73	94	108
Fan-Air flow rate	Heating	Speed 3	m^3/h	1,746	2,328	2,910	1,605	2,408	3,210	4,013
Sound pressure level	Heating	Speed 3	dBA	49	50	51	50	51	53	54
Refrigerant	Type / GWP			R-410A / 2.087,5						
Piping connections	Liquid/OD/Gas/OD		mm	9.52/16.0		9.52/19.0	9.52/16.0			9.52/19.0
Required accessories (should be ordered separately)				Daikin wired remote control (BRC1E52A/B or BRC1D52)						
Power supply	Voltage		V	230						

				Large			
				CYQL100DK125 *BN/*SN	CYQL150DK200 *BN/*SN	CYQL200DK250 *BN/*SN	CYQL250DK250 *BN/*SN
Heating capacity	Speed 3		kW	15.6	23.3	29.4	31.1
Power input	Fan only	Nom.	kW	0.75	1.13	1.50	1.88
	Heating	Nom.	kW	0.75	1.13	1.50	1.88
Delta T	Speed 3		K	15		14	12
Casing	Colour			BN: RAL9010 / SN: RAL9006			
Dimensions	Unit	Height F/C/R	mm	370/370/370			
		Width F/C/R	mm	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548
		Depth F/C/R	mm	774/1,105/745			
Required ceiling void >			mm	520			
Door height	Max.		m	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)
Door width	Max.		m	1.0	1.5	2.0	2.5
Weight	Unit		kg	76	100	126	157
Fan-Air flow rate	Heating	Speed 3	m^3/h	3,100	4,650	6,200	7,750
Sound pressure level	Heating	Speed 3	dBA	53	54	56	57
Refrigerant	Type / GWP			R-410A / 2,087.5			
Piping connections	Liquid/OD/Gas/OD		mm	9.52/16.0	9.52/19.0	9.52/22.0	
Required accessories (should be ordered separately)				Daikin wired remote control (BRC1E52A/B or BRC1D52)			
Power supply	Voltage		V	230			

(1) Favorable conditions: covered shopping mall or revolving door entrance (2) Normal conditions: little direct wind, no opposite open doors, building with ground floor only (3) Unfavorable conditions: location at a corner or square, multiple floors and/or open stairway

Biddle air curtain for VRV and Conveni-pack

- Connectable to VRV heat recovery, heat pump and Conveni-pack
- VRV is among the first DX systems suitable for connection to air curtains
- Free-hanging model (F): easy wall mounted installation
- Cassette model (C): mounted into a false ceiling leaving only the decoration panel visible
- Recessed model (R): neatly concealed in the ceiling
- A payback period of less then 1.5 years compared to installing an electric air curtain
- Provides virtually free air curtain heating via recovered heat from indoor units in cooling mode (in case of VRV heat recovery)
- Easy and quick to install at reduced costs since no additional water systems, boilers and gas connections are required
- Maximum energy efficiency stemming from almost zero down flow turbulence, optimised air flow and the application of advanced discharge rectifier technology
- Around 85% air separation efficiency, greatly reducing both heat loss and required indoor unit heating capacity




CYVM150DK80FSN



CYVM150DK80CSN




CYVM150DK80RSN



				Small				Medium			
				CYVS100DK80 *BN/*SN	CYVS150DK80 *BN/*SN	CYVS200DK100 *BN/*SN	CYVS250DK140 *BN/*SN	CYVM100DK80 *BN/*SN	CYVM150DK80 *BN/*SN	CYVM200DK100 *BN/*SN	CYVM250DK140 *BN/*SN
Heating capacity	Speed 3		kW	7.40	9.0	11.6	16.2	9.2	11.0	13.4	19.9
Power input	Fan only	Nom.	kW	0.23	0.35	0.46	0.58	0.37	0.56	0.75	0.94
	Heating	Nom.	kW	0.23	0.35	0.46	0.58	0.37	0.56	0.75	0.94
Delta T	Speed 3		K	19	15		16	17	14	13	15
Casing	Colour			BN: RAL9010 / SN: RAL9006							
Dimensions	Unit	Height F/C/R	mm	270/270/270							
		Width F/C/R	mm	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548
		Depth F/C/R	mm	590/821/561							
Required ceiling void >			mm	420							
Door height	Max.		m	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.3 (1) / 2.15 (2) / 2.0 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)	2.5 (1) / 2.4 (2) / 2.3 (3)
Door width	Max.		m	1.0	1.5	2.0	2.5	1.0	1.5	2.0	2.5
Weight	Unit		kg	56	66	83	107	57	73	94	108
Fan-Air flow rate	Heating	Speed 3	m^3/h	1,164	1,746	2,328	2,910	1,605	2,408	3,210	4,013
Sound pressure level	Heating	Speed 3	dBA	47	49	50	51	50	51	53	54
Refrigerant	Type / GWP			R-410A / 2.087,5							
Piping connections	Liquid/OD/Gas/OD		mm	9.52/16.0			9.52/19.0	9.52/16.0			9.52/19.0
Required accessories (should be ordered separately)				Daikin wired remote control (BRC1E52A/B or BRC1D52)							
Power supply	Voltage		V	230							

				Large			
				CYVL100DK125*BN/*SN	CYVL150DK200*BN/*SN	CYVL200DK250*BN/*SN	CYVL250DK250*BN/*SN
Heating capacity	Speed 3		kW	15.6	23.3	29.4	31.1
Power input	Fan only	Nom.	kW	0.75	1.13	1.50	1.88
	Heating	Nom.	kW	0.75	1.13	1.50	1.88
Delta T	Speed 3		K	15		14	12
Casing	Colour			BN: RAL9010 / SN: RAL9006			
Dimensions	Unit	Height F/C/R	mm	370/370/370			
		Width F/C/R	mm	1,000/1,000/1,048	1,500/1,500/1,548	2,000/2,000/2,048	2,500/2,500/2,548
		Depth F/C/R	mm	774/1,105/745			
Required ceiling void >			mm	520			
Door height	Max.		m	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)	3.0 (1) / 2.75 (2) / 2.5 (3)
Door width	Max.		m	1.0	1.5	2.0	2.5
Weight	Unit		kg	76	100	126	157
Fan-Air flow rate	Heating	Speed 3	m^3/h	3,100	4,650	6,200	7,750
Sound pressure level	Heating	Speed 3	dBA	53	54	56	57
Refrigerant	Type / GWP			R-410A / 2,087.5			
Piping connections	Liquid/OD/Gas/OD		mm	9.52/16.0	9.52/19.0	9.52/22.0	
Required accessories (should be ordered separately)				Daikin wired remote control (BRC1E52A/B or BRC1D52)			
Power supply	Voltage		V	230			

(1) Favorable conditions: covered shopping mall or revolving door entrance (2) Normal conditions: little direct wind, no opposite open doors, building with ground floor only (3) Unfavorable conditions: location at a corner or square, multiple floors and/or open stairway



The marine branch office of Daikin Europe N.V., named Daikin Europe N.V. Hamburg Marine Office is located in the heart of one of the biggest harbour towns in the entire Europe. Through this decision, Daikin Europe N.V. aims to establish a firm basis to further increase its presence in the European Marine A/C market. The portfolio of products are focused on Marine application, such as Daikin - Packaged Marine Air conditioners, Chillers and DX- units in accordance to most of the well known classification societies for which Daikin Europe N.V. Hamburg Marine Office is your competent partner.

USDP*GC / USDN*HA

Daikin Marine Type Deck Units

- Energy saving
- Compact design
- Refrigerants R-404A - R-407C
- Economical maintenance
- Easy installation
- Hermetic scroll compressor
- Minimum piping and field work required
- High performance reliability
- Lesser refrigerant volum with leak proof hermetic structure
- High static pressure fan facilitates the use of long ducts
- Quiet, less vibration operation makes it suitable for installation in accomodation areas

Optional customized modifications:
- Remote controls
- Electrical heater
- Data bus interfaces
- Air plenum or duct connection
- Higher external static pressure
- Cooling water regulating valve
- Higher air volume



USP~HR1 / USP~H

Daikin Marine Type Packaged Series

- Excellent durability
- Hermetic scroll compressor
- Light weight design
- Refrigerants: R-404A - R-407C
- Resilient structure specially designed for marine applications
- Abundant modification parts assures various applications
- Wide operation range
- Easy transportation and installation
- Energy-saving
- Complete set of spare parts provided for certain models

Optional customized modifications:
- Remote controls
- Electrical heater
- Data bus interfaces
- Air plenum or duct connection
- Higher external static pressure
- Cooling water regulating valve
- Higher air volume



USF*J(A)

Daikin Marine Type Galley Series

- Respond to a wide temperature range
- High efficient operation
- Outstanding durable design
- Easy transportation and installation
- Excellent performance reliability
- Spare parts are provided as standard accessories
- Hermetic scroll compressor
- High static pressure system
- R-404A

Optional customized modifications:
- Remote controls
- Electrical heater
- Data bus interfaces
- Air plenum or duct connection
- Higher external static pressure
- Cooling water regulating valve
- Higher air volume



RHSD~A / RKS~FR Unit

Daikin Marine Type Small Size Condensing

RHSD-A (R-134a):
- A semi-hermetic reciprocating compressor with proven reliability
- Saved maintenance work around compressor (without V belts & shaft seal)

RKS-FR (R-404A):
- An open type reciprocating compressor of optimum design for R-404A
- Equal installation & maintenance as R-22



For more information, visit http://www.daikineurope.com/industrial/applications/marine



Daikin chillers offer the ultimate in reliability and flexibility — a reflection of the advanced technology inherent within them. Daikin chillers represent the sure and safe route to a comfortable environment and a process cooling solution that is clean and consistent.

Chillers

Why choose Daikin chillers 278

Products overview - air cooled and condensing units 282

Products overview - water cooled and condenserless units 284

Air cooled chillers (Cooling only)

EWAQ-ADVP 286
EWAQ-ACV3/ACW1 287
EWAQ-BAWN/BAWP 288
EWAQ-E- 290
EWAQ-F- 292
EWAQ-GZ 296
EWAD-E- 298
EWAD-D- 300
EWAD-C- 308
EWAD-CZ 314
EWAD-CF 316
NEW EWAD-TZ 318

Air cooled chillers (Heat pump)

EWYQ-ADVP 324
EWYQ-ACV3/ACW1 325
EWYQ-BAWN/BAWP 326
NEW SEHVX-AAW/SERHQ-AAW1 327
EWYQ-F- 328
EWYQ-GZ 330
EWYD-BZ 332

Air cooled condensing unit

ERAD-E- 334

Water cooled chillers

EWWQ-B- 336
EWWP-KBW1N 338
EWWD-G- 340
EWWD-I- 342
EWWD-J- 344
EWWD-H- 345

Condenserless chillers

EWLP-KBW1N 346
EWLD-J- 347
EWLD-G- 348
EWLD-I- 349

Water cooled centrifugal chillers

EWWD-FZXS 350
DWSC / DWDC 351

For more information on Options & Accessories, please refer to page 456 of this catalogue.



Daikin chillers

Why choose Daikin chillers?

The simple answer is that, as the market leaders, the performance of our equipment is second to none. From the smallest chillers to the very largest, our quality control and attention detail is absolute. Our systems have the **most advanced technologies**, deliver **the highest energy efficiencies** and **lowest running costs**, and are the gold standard for reliability and performance.



Benefits for the installer

- Plug & play solutions
- Maximum serviceability
- Ideal solutions for retrofit projects


Benefits for the consultant

- Energy efficient solutions without compromising on reliability and performance
- Latest technology embedded in all our products

Benefits for the end user

- Remarkable savings on running costs
- "Green" solutions to preserve the environment
- Eurovent and AHRI certification





The widest and most flexible chiller portfolio

› From the smallest mini chiller for residential use to the largest chiller for district cooling
› Tailor made solutions based on the most advanced technologies

Worldwide experience in chiller design and manufacturing

› World's most advanced facilities for air conditioning research and development: the Applied Development Center in Minneapolis, Minnesota
› Inhouse development and manufacturing of chiller main components (compressors, fans, condenser coils, software, etc...)

The highest efficiency for every installation


› The lowest total cost of ownership and fast payback time
› Environmental friendly solutions

Quality and reliability

› Daikin's integrated zero defect policy ensures quality of components and finished products
› Each Daikin chiller is factory run-tested and subjected to quality audit before shipment

Marketing tool

The chiller selection software can be accessed via http://extranet.daikineurope.com/en/software/downloads/default.jsp





PRINTING COMPANY




CHILLER




AIR COOLED CHILLER




EWYQ-GZXR


DATA CENTER



ICE RINK


PROCESS COOLING

Products overview


		Refrigerant	Inverter	Free cooling	Compressor			Efficiency version				Sound version				
					Swing	Scroll	Screw	Standard	High	Premium	High ambient	Standard	Low	Reduced	Extra low	
Cooling only																0
EWAQ~ADVP		R-410A	●		●			●				●				
EWAQ~ACV3/ACW1		R-410A	●			●		●				●				
EWAQ~BA*		R-410A	●			●		●				●				
EWAQ~E-		R-410A				●			●			●	●	●		
EWAQ~F-		R-410A				●		●	●			●	●	●		
EWAQ~GZ		R-410A	●			●			●			●		●		
EWAD~E-		R-134a					●	●				●	●			
EWAD~D-		R-134a					●	●	●		●	●	●	●	●	
EWAD~C-		R-134a					●	●	●	●		●	●	●		
EWAD~CZ		R-134a	●				●		●			●	●	●		
EWAD~CF		R-134a		●			●		●			●	●	●		
EWAD~TZ NEW		R-134a	●				●	●	●			●		●		
Heat pump																0
EWYQ~ADVP		R-410A	●		●			●				●				
EWYQ~ACV3/ACW1		R-410A	●			●		●				●				
EWYQ~BA*		R-410A	●			●		●				●				
SEHVX-AAW SERHQ-AAW1 NEW		R-410A	●			●		●				●				
EWYQ~F-		R-410A				●			●			●	●	●		
EWYQ~GZ		R-410A	●			●			●			●		●		
EWYD~BZ		R-134a	●				●	●				●	●			
Condensing unit																0
ERAD~E-		R-134a					●	●				●	●			

Cooling capacity (kW)
Heating capacity (kW)



Products overview

		Refrigerant	Inverter	Compressor			Efficiency version		Sound version
				Scroll	Screw	Centrifugal	Standard	High	Standard
Water cooled chillers (Cooling only & Heating only)									
EWWP~KBW1N		R-407C		●			●		●
EWWD~J-		R-134a			●		●		●
EWWD~G-		R-134a			●		●	●	●
EWWD~I-		R-134a			●		●	●	●
EWWD~H-		R-134a			●			●	●
Water cooled chillers (Cooling only)									
EWWQ~B-		R-410A			●		●	●	●
Condenserless chillers									
EWLP~KBW1N		R-407C		●			●		●
EWLD~J-		R-134a			●		●		●
EWLD~G-		R-134a			●		●		●
EWLD~I-		R-134a			●		●		●
Water cooled centrifugal chillers									
EWWD~FZ		R-134a	●			●		●	●
DWSC DWDC		R-134a	optional			●		●	●
6,000 RT CENTRIFUGAL		R-134a				●		●	●


Cooling capacity (kW)
Heating capacity (kW)
0
17.5
200
500
1,000
2,000
21800
12.9~194
16.7~249
120~568
142~681
165~602
209~743
332~1,503
424~1,951
368~1,212
454~1,488
379~2,156
12.1~62.4
110~529
160~524
315~1,433
113~1,054
300~4,500
600~9,000
[2 x 10,900]
21,800

Air cooled mini inverter chiller

- Inverter technology to ensure low sound values and **leader-of-class ESEER**
- Wide operating range
- Easy 'plug and play' installation
- Single phase power supply and low starting currents make the unit ideal **for residential applications**
- **Built-in hydronic module**: no buffer tank required and a standard pump and main switch are included



EWAQ-ADVP

Digital controller

Cooling only					EWAQ-ADVP	005	006	007
Cooling capacity	Nom.				kW	5.28 (1)	6.08 (1)	7.18 (1)
Power input	Cooling	Nom.			kW	1.94 (1)	2.40 (1)	3.00 (1)
Capacity control	Method					Inverter controlled		
EER						2.72 (1)	2.53 (1)	2.39 (1)
Dimensions	Unit	Height			mm	805		
		Width			mm	1,190		
		Depth			mm	360		
Weight	Unit				kg	100		
	Operation weight				kg	104		
Water heat	Type					Brazed plate		
exchanger	Water flow rate	Cooling	Nom.		l/min	14.9	17.2	20.4
Air heat exchanger	Type					Tube type		
Hydraulic components	Expansion vessel	Volume			l	6		
Compressor	Type					Hermetically sealed swing compressor		
	Quantity					1		
Fan	Type					Propeller fan		
	Quantity					1		
Sound power level	Cooling	Nom.			dBA	62		63
Sound pressure level	Cooling	Nom.			dBA	48		50
Operation range	Water side	Cooling	Min.~Max.		°CDB	5~20		
	Air side	Cooling	Min.~Max.		°CDB	10~43		
Refrigerant	Type / GWP					R-410A / 2,087.5		
	Control					Inverter		
	Circuits	Quantity				1		
Refrigerant charge	Per circuit				kg	1.7		
	Per circuit				TCO_2Eq	3.5		
Water circuit	Piping connections diameter				inch	1" MBSP		
Piping connections	Water heat exchanger drain					5/16 SAE flare		
Unit	Maximum running current				A	17.3		
Power supply	Phase/Frequency/Voltage				Hz/V	1~/50/230		

(1) Tamb 35°C - LWE 7°C (Dt: 5°C)

Air cooled mini inverter chiller

- Inverter technology to ensure low sound values and **leader-of-class ESEER**
- Wide operating range
- Built-in hydronic module: no buffer tank required and a standard pump and main switch are included
- Easy 'plug and play' installation
- Single phase power supply **for residential applications**, three phase power supply model available **for light commercial applications**



EWAQ-ACV3/ACW1



Digital controller

Cooling only					EWAQ	009ACV3	010ACV3	011ACV3	009ACW1	011ACW1	013ACW1
Cooling capacity	Nom.				kW	12.2 (1) / 8.6 (2)	13.6 (1) / 9.6 (2)	15.7 (1) / 11.1 (2)	12.9 (1) / 9.1 (2)	15.7 (1) / 11.1 (2)	17.0 (1) / 13.3 (2)
Power input	Cooling	Nom.			kW	2.85 (1) / 2.83 (2)	3.41 (1) / 3.28 (2)	4.13 (1) / 3.90 (2)	3.08 (1) / 3.05 (2)	4.13 (1) / 3.90 (2)	5.52 (1) / 5.18 (2)
Capacity control	Method					Inverter controlled					
EER						4.27 (1) / 3.05 (2)	4.00 (1) / 2.93 (2)	3.79 (1) / 2.85 (2)	4.19 (1) / 2.99 (2)	3.79 (1) / 2.85 (2)	3.08 (1) / 2.57 (2)
ESEER						4.31	4.30	4.33	4.43	4.44	4.36
Dimensions	Unit	Height			mm	1,435					
		Width			mm	1,418					
		Depth			mm	382					
Weight	Unit				kg	180					
Water heat exchanger	Type					Brazed plate					
	Quantity					1					
	Water volume				l	1.01					
	Water flow rate	Cooling	Nom.		l/min	24.7	27.6	31.9	26.1	31.9	38.2
Air heat exchanger	Type					Hi-XSS					
Hydraulic components	Expansion vessel	Volume			l	10					
Compressor	Type					Hermetically sealed scroll compressor					
	Quantity					1					
Fan	Type					Propeller fan					
	Quantity					2					
	Air flow rate	Cooling	Nom.		m^3/min	96	100	97	-		
Fan motor	Speed	Cooling	Nom.		rpm	780					
		Steps				8					
Sound power level	Cooling	Nom.			dBA	64					66
Sound pressure level	Cooling	Nom.			dBA	51					52
		Cooling Night quiet mode			dBA	45					46
Operation range	Water side	Cooling	Min.~Max.		°CDB	5~22					
	Air side	Cooling	Min.~Max.		°CDB	10~46					
Refrigerant	Type / GWP					R-410A / 2,087.5					
	Control					Electronic expansion valve					
	Circuits	Quantity				1					
Refrigerant charge	Per circuit				kg	2.95					
	Per circuit				TCO_2Eq	6.2					
Water circuit	Piping connections diameter				inch	G 5/4" (female)					
	Piping				inch	5/4"					
Power supply	Phase/Frequency/Voltage				Hz/V	1~/50/230			3N~/50/400		

(1) Underfloor program: cooling Ta 35°C - LWE 18°C (Dt: 5°C) (2) Fan coil program: cooling Ta 35°C - LWE 7°C (Dt: 5°C)

Air cooled scroll inverter chiller

- High efficiency with **leader-of-class ESEER**
- Minimal starting currents and short payback times
- No buffertank required for standard applications
- **Large operation range** (ambient temperature up to 43°C)
- A modbus gateway (RTD-W) can be installed per unit in order allow the control and monitoring by a Daikin controller or a third-party BMS, which will increase further the efficiency of the system
- All systems that are connected with RTD-W can be controlled and **monitored centrally** with the master/slave control kit: the sequencing controller EKCC-W



EWAQ-BAWN/BAWP BRC21A52

Cooling only					EWAQ-BAWN/BAWP	016	021	025	032	040	050	064
Cooling capacity	Nom.				kW	17.4 (1) / 16.6 (2)	21.7 (1) / 20.7 (2)	25.8 (1) / 24.7 (2)	32.3 (1) / 30.9 (2)	43.4 (1) / 41.5 (2)	51.8 (1) / 49.7 (2)	64.5 (1) / 62.3 (2)
Power input	Cooling	Nom.			kW	5.60 (1) / 5.80 (2)	7.25 (1) / 9.9 (2)	9.29 (1) / 9.74 (2)	13.0 (1) / 13.5 (2)	14.7 (1) / 15.4 (2)	18.8 (1) / 19.7 (2)	26.4 (1) / 27.4 (2)
Capacity control	Method					Inverter controlled						
	Minimum capacity				%	25						
EER						3.11 (1) / 2.86 (2)	2.99 (1) / 2.73 (2)	2.78 (1) / 2.54 (2)	2.48 (1) / 2.29 (2)	2.95 (1) / 2.69 (2)	2.76 (1) / 2.52 (2)	2.44 (1) / 2.27 (2)
ESEER						4.33 (1) / 4.21 (2)	4.08 (1) / 4.18 (2)	3.85 (1) / 4.04 (2)	3.39 (1) / 3.62 (2)	4.19 (1) / 4.24 (2)	3.96 (1) / 4.12 (2)	3.64 (1) / 3.78 (2)
Dimensions	Unit	Height			mm	1,684						
		Width			mm	1,371			1,684	2,358		2,980
		Depth			mm	774				780		
Weight	Unit				kg	264	317		397	571		730
	Operation weight				kg	267	320		401	577		738
Water heat exchanger	Type					Brazed plate						
	Water volume				l	1.9			2.9	3.8		5.7
	Water flow rate	Cooling	Nom.		l/min	50	62	74	93	124	148	185
	Water pressure drop	Cooling	Total		kPa	20	30	42	30		42	30
Air heat exchanger	Type					Hi-XSS						
Compressor	Type					Hermetically sealed scroll compressor						
	Quantity					1	2		3	4		6
Fan	Type					Axial						
	Quantity					1			2			4
	Air flow rate	Cooling	Nom.		m^3/min	171	185		233	370		466
Sound power level	Cooling	Nom.			dBA	78			80	81		83
Operation range	Water side	Cooling	Min.~Max.		°CDB	5~20						
	Air side	Cooling	Min.~Max.		°CDB	-5~43						
Refrigerant	Type / GWP					R-410A / 2,087.5						
	Control					Electronic expansion valve						
	Circuits	Quantity				1						
Refrigerant charge	Per circuit				kg	7.6			9.6	15.2		19.2
	Per circuit				TCO_2Eq	15.9			20.0	31.7		40.1
Water circuit	Piping connections diameter				inch	1-1/4" (female)				2" (female)		
	Piping				inch	1-1/4"				1-1/2"		
Unit	Maximum starting current				A	0	77.7	78.7	88.7	99.8	101.9	120.7
	Maximum running current				A	22.2	25.3	26.4	35.2	47.4	49.6	67.2
Power supply	Phase/Frequency/Voltage				Hz/V	3N~/50/400						

(1) EWAQ-BAWN: Naked version (2) EWAQ-BAWP: Verison with pump



Air cooled multi-scroll chiller, high efficiency, standard/low sound

› Reliable and efficient scroll compressors with high EER values
› A series of advantages thanks to the use of large-capacity scroll compressors: increased competitiveness, reduced weight, clearances around the unit
› **Reduced footprint thanks to the V-shaped frame**
› Large operation range: ambient temperatures up to 52°C and down to -18°C
› Ideal solution for **a broad range of comfort and process applications**
› The unit can be equipped with a hydraulic module optimizing installation time, space and cost
› MicroTech III controller with superior control logic and easy interface

Cooling only				**EWAQ-E-XS/XL**	**180**	**200**	**230**	**260**	**320**	**340**
Cooling capacity	Nom.			kW	178	200	226	263	315	334
Power input	Cooling	Nom.		kW	58.0	65.4	73.8	86.2	103	110
Capacity control	Method				Step					
	Minimum capacity			%	50.0	43.0	50.0	33.0	27.0	33.0
EER					3.06				3.05	
ESEER					4.02	4.11	3.91	4.18	4.17	4.14
IPLV					4.50	4.68	4.51	4.83	4.76	4.66
Dimensions	Unit	Height		mm	2,271				2,447	
		Width		mm	1,224					
		Depth		mm	4,413		5,313		6,213	
Weight (XS)	Unit			kg	1,722	1,807	1,871	2,173	2,304	2,492
	Operation weight			kg	1,734	1,819	1,885	2,188	2,318	2,507
Weight (XL)	Unit			kg	1,876	1,965	2,032	2,370	2,507	2,705
	Operation weight			kg	1,889	1,978	2,047	2,385	2,522	2,719
Water heat exchanger	Type				Plate heat exchanger					
	Water volume			l	12		14			
	Water flow rate	Cooling	Nom.	l/s	8.5	9.6	10.8	12.6	15.1	16.0
	Water pressure drop	Cooling	Nom.	kPa	27	34	35	47		54
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler					
Compressor	Type				Scroll compressor					
	Quantity				2			3		
Fan	Type				Direct propeller					
	Quantity				4		5		6	
	Air flow rate	Nom.		l/s	21,845	21,148	26,874	25,884	32,953	32,065
	Speed			rpm	900					
Sound power level (XS)	Cooling	Nom.		dBA	93	94	96	95	96	97
Sound power level (XL)	Cooling	Nom.		dBA	91	92	93	92	93	94
Sound pressure level (XS)	Cooling	Nom.		dBA	75	76			77	
Sound pressure level (XL)	Cooling	Nom.		dBA	73				74	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~18					
	Air side	Cooling	Min.~Max.	°CDB	-18~52					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Circuits	Quantity			1					
Refrigerant charge	Per circuit			kg	28.0	31.0	34.0	40.0	43.0	53.0
	Per circuit			TCO_2Eq	58.5	64.7	71.0	83.5	89.8	110.6
Piping connections	Evaporator water inlet/outlet (OD)				3"					
Unit	Maximum starting current			A	384	482	500	447	563	577
	Nominal running current (RLA)	Cooling		A	103	115	129	151	179	190
	Maximum running current			A	133	147	165	195	227	241
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400					

Air cooled multi-scroll chiller, high efficiency, reduced sound



EWAQ-E-XS/XL/XR



MicroTech III

Cooling only				EWAQ-E-XR	170	190	220	260	300	320
Cooling capacity	Nom.			kW	172	190	219	254	302	310
Power input	Cooling	Nom.		kW	56.5	63.6	71.8	85.4	102	107
Capacity control	Method				Step					
	Minimum capacity			%	50.0	43.0	50.0	33.0	27.0	33.0
EER					3.05	2.98	3.05	2.97	2.96	2.89
ESEER					4.45	4.57	4.33	4.65	4.62	4.50
IPLV					5.09	4.95	4.90	5.04	5.07	5.20
Dimensions	Unit	Height		mm	2,271					
		Width		mm	1,224					
		Depth		mm	4,413		5,313		6,213	
Weight	Unit			kg	1,970	2,064	2,134	2,489	2,632	2,840
	Operation weight			kg	1,982	2,076	2,148	2,503	2,647	2,855
Water heat exchanger	Type				Plate heat exchanger					
	Water volume			l	12		14			
	Water flow rate	Cooling	Nom.	l/s	8.2	9.1	10.5	12.1	14.5	14.8
	Water pressure drop	Cooling	Nom.	kPa	26	39	33	44	43	52
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler					
Compressor	Type				Scroll compressor					
	Quantity				2			3		
Fan	Type				Direct propeller					
	Quantity				4		5		6	
	Air flow rate	Nom.		l/s	16,743	18,405	20,618	20,056	25,243	28,009
	Speed			rpm	705	784	705			784
Sound power level	Cooling	Nom.		dBA	85	86	87	86	88	89
Sound pressure level	Cooling	Nom.		dBA	66	67	68	67	68	69
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~18					
	Air side	Cooling	Min.~Max.	°CDB	-18~52					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Circuits	Quantity			1					
Refrigerant charge	Per circuit			kg	28.0	31.0	27.0	35.0	43.0	53.0
	Per circuit			TCO_2Eq	58.5	64.7	56.4	73.1	89.8	110.6
Piping connections	Evaporator water inlet/outlet (OD)				3"					
Unit	Maximum starting current			A	379	482	493	440	554	577
	Nominal running current (RLA)	Cooling		A	101	117	127	151	179	193
	Maximum running current			A	127	147	158	188	219	241
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400					

Air cooled multi-scroll chiller, standard efficiency, standard/low sound

- Reliable and efficient scroll compressors with high EER values
- A series of advantages thanks to the use of large-capacity scroll compressors: increased competitiveness, reduced weight, clearances around the unit
- **2 truly independent refrigerant circuits**
- Reduced footprint thanks to the **V-shaped frame** (EWAQ210-350/400F-SS/SL & EWAQ200-330/370F-SR)
- Large operation range: ambient temperatures up to 52°C and down to -18°C
- The unit can be equipped with a hydraulic module optimizing installation time, space and cost
- Ideal solution for a broad range of comfort and process applications
- MicroTech III controller with superior control logic and easy interface

Cooling only				**EWAQ-F-SS/SL**	**210**	**230**	**250**	**280**	**320**	**350**	**360**	**400**	**410**	**480**	**550**	**610**
Cooling capacity	Nom.			kW	206	224	247	283	313	359		423	407	480	551	609
Power input	Cooling	Nom.		kW	73.3	84.9	93.6	109	122	141		154		187	207	229
Capacity control	Method				Step											
	Minimum capacity			%	25.0	22.0	25.0	23.0	25.0	21.0		25.0		17.0	14.0	17.0
EER					2.81	2.64		2.60	2.58	2.55		2.75	2.64	2.57	2.67	2.66
ESEER					3.79	3.77	3.81	3.74	3.78	3.73	4.02	3.74	4.04	4.13	4.05	4.08
IPLV					4.50	4.45	4.50	4.44	4.53	4.29	4.41	4.30	4.46	4.55	4.63	4.72
Dimensions	Unit	Height		mm	2,271						2,221	2,447	2,397	2,221		
		Width		mm	1,224						2,258	1,224	2,258			
		Depth		mm	4,413			5,313		6,213	3,210	6,213	3,210	4,110	5,010	
Weight (SS)	Unit			kg	2,058		2,130	2,202	2,284	2,409	2,509	2,659	2,759	2,990	3,336	3,558
	Operation weight			kg	2,070		2,142	2,216	2,298	2,424	2,524	2,699	2,799	3,036	3,382	3,604
Weight (SL)	Unit			kg	2,297		2,373	2,449	2,535	2,666	2,766	2,968	3,068	3,315	3,679	3,912
	Operation weight			kg	2,309		2,385	2,463	2,549	2,681	2,781	3,008	3,108	3,362	3,725	3,958
Water heat exchanger	Type				Plate heat exchanger											
	Water volume			l	12			14				40		46		
	Water flow rate	Cooling	Nom.	l/s	9.9	10.7	11.8	13.6	15.0	17.2		20.3	19.5	23.0	26.4	29.2
	Water pressure drop	Cooling	Nom.	kPa	37	43	53	56	69	30		27	32	35	46	56
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler											
Compressor	Type				Scroll compressor											
	Quantity				4									6		
Fan	Type				Direct propeller											
	Quantity				4			5		6				8	10	
	Air flow rate	Nom.		l/s	21,845		21,148	27,306	26,435	32,767		36,265	32,513	43,690	54,612	52,870
	Speed			rpm	900							980	900			
Sound power level (SS)	Cooling	Nom.		dBA	93	94	95			97					99	
Sound power level (SL)	Cooling	Nom.		dBA	91	92		93		94				95	96	
Sound pressure level (SS)	Cooling	Nom.		dBA	75		76			77	78				79	
Sound pressure level (SL)	Cooling	Nom.		dBA	73					74	75	74	75		76	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~18											
	Air side	Cooling	Min.~Max.	°CDB	-18~52											
Refrigerant	Type / GWP				R-410A / 2,087.5											
	Circuits	Quantity			2											
Refrigerant charge	Per circuit			kg	14.0		15.5	16.5	20.0	23.0		27.0		28.0	32.5	40.0
	Per circuit			TCO_2Eq	29.2		32.4	34.4	41.8	48.0		56.4		58.5	67.8	83.5
Piping connections	Evaporator water inlet/outlet (OD)				3"											
Unit	Maximum starting current			A	349	404	419	476	505	621		649		634	768	810
	Nominal running current (RLA)	Cooling		A	130	147	161	187	208	242		259	262	322	356	391
	Maximum running current			A	160	176	191	225	254	286		314		383	433	474
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400											

Air cooled multi-scroll chiller, standard efficiency, reduced sound



EWAQ-F-SS/SL/SR



MicroTech III

Cooling only				EWAQ-F-SR	200	220	240	270	300	330	340	370	380	460	530	580
Cooling capacity	Nom.			kW	198	214	235	270	298	341		383		456	527	580
Power input	Cooling	Nom.		kW	73.4	86.0	95.6	110	125	144		159		191	208	233
Capacity control	Method				Step											
	Minimum capacity			%	25.0	22.0	25.0	23.0	25.0	21.0		25.0		17.0	14.0	17.0
EER					2.70	2.49	2.46	2.45	2.38	2.37		2.41		2.39	2.53	2.49
ESEER					4.27	4.20	4.13	4.16	4.08	4.10	4.27	4.03	4.16	4.53	4.49	4.43
IPLV					4.96	4.89	4.82	4.92	4.85	4.71	4.86	4.61	4.73	5.09	5.00	4.93
Dimensions	Unit	Height		mm	2,271						2,221	2,447	2,397	2,221		
		Width		mm	1,224						2,258	1,224	2,258			
		Depth		mm	4,413			5,313		6,213	3,210	6,213	3,210	4,110	5,010	
Weight	Unit			kg	2,412		2,491	2,571	2,661	2,799	2,899	3,116	3,216	3,481	3,863	4,108
	Operation weight			kg	2,424		2,504	2,585	2,676	2,814	2,914	3,156	3,256	3,527	3,909	4,154
Water heat exchanger	Type				Plate heat exchanger											
	Water volume			l	12			14				40		46		
	Water flow rate	Cooling	Nom.	l/s	9.5	10.2	11.3	13.0	14.3	16.3		18.3		21.8	25.2	27.8
	Water pressure drop	Cooling	Nom.	kPa	34	40	48	51	63	27		29		31	42	51
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler											
Compressor	Type				Scroll compressor											
	Quantity				4									6		
Fan	Type				Direct propeller											
	Quantity				4			5		6				8	10	
	Air flow rate	Nom.		l/s	16,743		16,285	20,929	20,356	25,115		24,922		33,487	41,858	40,713
	Speed			rpm	705											
Sound power level	Cooling	Nom.		dBA	85	86	87			89		90		89	91	92
Sound pressure level	Cooling	Nom.		dBA	66	67	68			69	70		71	70	71	72
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~18											
	Air side	Cooling	Min.~Max.	°CDB	-18~52											
Refrigerant	Type / GWP				R-410A / 2,087.5											
	Circuits	Quantity			2											
Refrigerant charge	Per circuit			kg	16.0		18.0	19.0	20.0	23.0		27.0		28.0	32.5	40.0
	Per circuit			TCO_2Eq	33.4		37.6	39.7	41.8	48.0		56.4		58.5	67.8	83.5
Piping connections	Evaporator water inlet/outlet (OD)				3"											
Unit	Maximum starting current			A	344	398	414	469	498	613		641		623	754	796
	Nominal running current (RLA)	Cooling		A	129	149	164	189	214	247		270		328	359	398
	Maximum running current			A	155	170	186	218	247	277		305		372	419	460
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400											

Air cooled multi-scroll chiller, high efficiency, standard/low sound

› Reliable and efficient scroll compressors with **high EER values**
› A series of advantages thanks to the use of large-capacity scroll compressors: increased competitiveness, reduced weight, clearances around the unit
› **2 truly independent refrigerant circuits**
› Reduced footprint thanks to the **V-shaped frame** (EWAQ170-310/350F-XS/XL & EWAQ170-300/330F-XR)
› Large operation range: ambient temperatures up to 52°C and down to -18°C
› The unit can be equipped with a hydraulic module optimizing installation time, space and cost
› Ideal solution for a broad range of comfort and process applications
› MicroTech III controller with superior control logic and easy interface

Cooling only				**EWAQ-F-XS/XL**	**170**	**200**	**220**	**250**	**310**	**320**	**350**	**360**	**400**	**430**	**450**	**520**	**610**	**680**
Cooling capacity	Nom.			kW	170	194	220	244	316		356		403	428	457	528	607	672
Power input	Cooling	Nom.		kW	54.8	62.2	70.6	78.3	102		115		130	137	146	170	198	219
Capacity control	Method				Step													
	Minimum capacity			%	25.0	21.0	25.0	22.0	23.0		25.0		21.0	20.0	25.0	17.0	14.0	17.0
EER					3.11	3.13	3.12		3.09				3.10	3.12		3.10	3.07	
ESEER					3.90	4.10	3.95	4.08	4.04	4.30	4.05	4.33	4.24	4.27	4.23	4.35	4.30	4.23
IPLV					4.56	4.76	4.67	4.70	4.67	4.60	4.64	4.80	4.72	4.65	4.61	4.95	4.82	4.68
Dimensions	Unit	Height		mm	2,271					2,221	2,271		2,221					
		Width		mm	1,224					2,258	1,224		2,258					
		Depth		mm	4,413		5,313		6,213	3,210	6,213	3,210	4,110			5,010		5,910
Weight (XS)	Unit			kg	1,688	1,958	2,210	2,339	2,500	2,600	2,632	2,732	2,744	2,845	2,861	3,569	3,667	4,054
	Operation weight			kg	1,700	1,973	2,225	2,353	2,514		2,672	2,772	2,784	2,891	2,907	3,615	3,727	4,115
Weight (XL)	Unit			kg	1,909	2,193	2,457	2,592	2,761	2,861	2,900	3,000	3,017	3,124	3,141	3,923	4,026	4,434
	Operation weight			kg	1,921	2,207	2,472	2,607	2,776	2,876	2,940	3,040	3,057	3,170	3,187	3,970	4,087	4,494
Water heat exchanger	Type				Plate heat exchanger													
	Water volume			l	12	14					40		46			60		
	Water flow rate	Cooling	Nom.	l/s	8.2	9.3	10.5	11.7	15.1		17.0		19.3	20.5	21.8	25.3	29.0	32.2
	Water pressure drop	Cooling	Nom.	kPa	25	27	34	42	22		23		31	29	30	41	44	55
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler													
Compressor	Type				Scroll compressor													
	Quantity				4											6		
Fan	Type				Direct propeller													
	Quantity				4		5		6				8			10		12
	Air flow rate	Nom.		l/s	21,845	21,148	26,874	25,204	31,722		30,245		42,296	40,326		50,408		60,489
	Speed			rpm	900													
Sound power level (XS)	Cooling	Nom.		dBA	91	93	94	95	96				97	98		99		100
Sound power level (XL)	Cooling	Nom.		dBA	90	91	92		93				95			96		97
Sound pressure level (XS)	Cooling	Nom.		dBA	72	74	75	76	77	76	77		78	79		78	79	
Sound pressure level (XL)	Cooling	Nom.		dBA	71	73			74				75			76		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~18													
	Air side	Cooling	Min.~Max.	°CDB	-18~52													
Refrigerant	Type / GWP				R-410A / 2,087.5													
	Circuits	Quantity			2													
Refrigerant charge	Per circuit			kg	14.0	15.5	16.5	20.0	26.0				31.0			37.0	36.0	41.5
	Per circuit			TCO_2Eq	29.2	32.4	34.4	41.8	54.3				64.7			77.2	75.2	86.6
Piping connections	Evaporator water inlet/outlet (OD)				3"													
Unit	Maximum starting current			A	281	338	353	408	480		509		629	643	657	642	768	818
	Nominal running current (RLA)	Cooling		A	110	117	128	141	181		202		229	240	254	300	343	379
	Maximum running current			A	138	149	164	180	229		258		294	308	322	391	433	482
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400													

Air cooled multi-scroll chiller, high efficiency, reduced sound



EWAQ-F-XS/XL/XR



MicroTech III

Cooling only				EWAQ-F-XR	170	190	210	240	300	310	330	340	390	410	430	500	580	650
Cooling capacity	Nom.			kW	165	188	211	236	304		340		385	407	433	502	579	645
Power input	Cooling	Nom.		kW	53.0	61.2	68.7	77.3	101		117		128	136	146	170	200	219
Capacity control	Method				Step													
	Minimum capacity			%	25.0	21.0	25.0	22.0	23.0		25.0		21.0	20.0	25.0	17.0	14.0	17.0
EER					3.12	3.07	3.08	3.05	3.00		2.92		3.01	2.99	2.96		2.90	2.95
ESEER					4.53	4.64	4.51	4.60	4.53	4.68	4.44	4.63	4.68	4.64	4.54	4.82	4.69	4.65
IPLV					5.25	5.04	5.19	5.27	5.04	5.16	5.01	4.89	5.04	4.90	4.99	5.13	5.15	5.18
Dimensions	Unit	Height		mm	2,271					2,221	2,271		2,221					
		Width		mm	1,224					2,258	1,224		2,258					
		Depth		mm	4,413		5,313		6,213	3,210	6,213	3,210	4,110			5,010		5,910
Weight	Unit			kg	2,004	2,303	2,580	2,722	2,900	3,000	3,045	3,145	3,168	3,280	3,298	4,120	4,228	4,655
	Operation weight			kg	2,017	2,317	2,594	2,736	2,914	3,014	3,085	3,185	3,208	3,326	3,344	4,166	4,288	4,716
Water heat exchanger	Type				Plate heat exchanger													
	Water volume			l	12	14					40			46			60	
	Water flow rate	Cooling	Nom.	l/s	7.9	9.0	10.1	11.3	14.5		16.3		18.4	19.5	20.7	24.0	27.7	30.9
	Water pressure drop	Cooling	Nom.	kPa	24	25	31	39	21				28	26	27	38	40	51
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler													
Compressor	Type				Scroll compressor													
	Quantity				4											6		
Fan	Type				Direct propeller													
	Quantity				4		5		6				8			10		12
	Air flow rate	Nom.		l/s	16,743	16,285	20,618	19,522	24,428		23,426		32,570	31,235		39,044		46,852
	Speed			rpm	705													
Sound power level	Cooling	Nom.		dBA	83	84	85	86	87				89		90	89	90	92
Sound pressure level	Cooling	Nom.		dBA	64	65	66	67		68	67	68	69	70		69	70	71
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~18													
	Air side	Cooling	Min.~Max.	°CDB	-18~52													
Refrigerant	Type / GWP				R-410A / 2,087.5													
	Circuits	Quantity			2													
Refrigerant charge	Per circuit			kg	14.0	15.5	16.5	20.0	24.0	26.0			31.0			35.0	36.0	41.5
	Per circuit			TCO_2Eq	29.2	32.4	34.4	41.8	50.1	54.3			64.7			73.1	75.2	86.6
Piping connections	Evaporator water inlet/outlet (OD)				3"													
Unit	Maximum starting current			A	276	332	346	401	472		501		618	632	646	628	754	801
	Nominal running current (RLA)	Cooling		A	107	116	125	139	180		204		226	239	255	300	347	380
	Maximum running current			A	132	143	157	173	220		249		283	296	310	377	419	465
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400													

Air cooled multi-scroll inverter chiller, high efficiency, standard sound

› High efficiency **DC inverter scroll** compressors
› Advanced compressor and fan design resulting in low operating sound levels
› Dual independent refrigerant circuit for built-in redundancy and reliable operation
› Wide operating range in cooling mode
› Reduced footprint thanks to the **V-shaped frame** (EWAQ210GZXS & EWAQ190GZXR)
› MicroTech III controller with superior control logic and easy interface

Cooling only				**EWAQ-GZXS**	**210**	**270**	**320**	**340**	**400**
Cooling capacity	Nom.			kW	201	270	323	340	395
Power input	Cooling	Nom.		kW	72.5	94.0	122	117	144
Capacity control	Method				Stepless				
	Minimum capacity			%	14.4	14.3	14.9	14.3	14.8
EER					2.77	2.87	2.64	2.92	2.75
ESEER					4.79	4.89	4.90	4.77	4.78
IPLV					5.11	5.26	5.40	5.21	5.23
Dimensions	Unit	Height		mm	2,270	2,223			
		Width		mm	1,290	2,234			
		Depth		mm	4,450	3,560		4,460	
Weight	Unit			kg	1,600	2,100	2,150	2,400	2,500
	Operation weight			kg	1,677	2,233	2,297	2,575	2,688
Water heat exchanger	Type				Plate heat exchanger				
	Water volume			l	29	61	75	79	92
	Water flow rate	Cooling	Nom.	l/s	9.6	12.9	15.4	16.3	18.9
	Water pressure drop	Cooling	Total	kPa	27	14	15	16	18
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler				
Compressor	Type				DC Inverter Scroll				
	Quantity				6	8	10		12
Fan	Type				Direct propeller				
	Quantity				4	6		8	
	Air flow rate	Nom.		l/s	17,473	26,209		34,946	
	Speed			rpm	920				
Sound power level	Cooling	Nom.		dBA	92	94		96	
Sound pressure level	Cooling	Nom.		dBA	75	78			79
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~20				
	Air side	Cooling	Min.~Max.	°CDB	-18~43				
Refrigerant	Type / GWP				R-410A / 2,087.5				
	Circuits	Quantity			1	2			
Refrigerant charge	Per circuit			kg	48.0	36.0		48.0	
	Per circuit			TCO_2Eq	100.2	75.2		100.2	
Piping connections	Evaporator water inlet/outlet (OD)				2.5"	4.5"			
Unit	Maximum starting current			A	2				
	Nominal running current (RLA)	Cooling		A	114	155	195	189	227
	Maximum running current			A	155	236	281	286	309
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400				

Air cooled multi-scroll inverter chiller, high efficiency, reduced sound



EWAQ-GZXS/XR MicroTech III

Cooling only				EWAQ-GZXR	190	270	320	340	390
Cooling capacity	Nom.			kW	196	264	315	334	386
Power input	Cooling	Nom.		kW	73.3	94.8	124	117	145
Capacity control	Method				Stepless				
	Minimum capacity			%	14.4	14.3	14.9	14.3	14.8
EER					2.68	2.79	2.53	2.86	2.65
ESEER					4.88	4.95	5.05	5.07	
IPLV					5.16	5.25		5.27	5.24
Dimensions	Unit	Height		mm	2,270	2,223			
		Width		mm	1,290	2,234			2,241
		Depth		mm	4,450	3,560		4,460	
Weight	Unit			kg	1,618	2,124	2,180	2,430	2,536
	Operation weight			kg	1,695	2,257	2,327	2,605	2,724
Water heat exchanger	Type				Plate heat exchanger				
	Water volume			l	29	61	75	79	92
	Water flow rate	Cooling	Nom.	l/s	9.4	12.6	15.0	16.0	18.5
	Water pressure drop	Cooling	Total	kPa	26	14	15		17
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler				
Compressor	Type				DC Inverter Scroll				
	Quantity				6	8	10		12
Fan	Type				Direct propeller				
	Quantity				4	6		8	
	Air flow rate	Nom.		l/s	15,131	22,697		30,263	
	Speed			rpm	715				
Sound power level	Cooling	Nom.		dBA	89	91		92	
Sound pressure level	Cooling	Nom.		dBA	72	74		75	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~20				
	Air side	Cooling	Min.~Max.	°CDB	-18~43				
Refrigerant	Type / GWP				R-410A / 2,087.5				
	Circuits	Quantity			1	2			
Refrigerant charge	Per circuit			kg	48.0	36.0		48.0	
	Per circuit			TCO_2Eq	100.2	75.2		100.2	
Piping connections	Evaporator water inlet/outlet (OD)				2.5"	4.5"			
Unit	Maximum starting current			A	2				
	Nominal running current (RLA)	Cooling		A	116	157	199	190	231
	Maximum running current			A	153	234	279	283	306
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400				

Air cooled screw chiller, standard efficiency, standard sound

› One refrigerant circuit with single screw compressor
› **Compact design** with brazed plate heat exchanger
› Large operation range (ambient temperature down to -18°C)
› Water supply down to -15°C

Cooling only				**EWAD-E-SS**	**100**	**120**	**140**	**160**	**180**	**210**	**260**	**310**	**360**	**410**
Cooling capacity	Nom.			kW	101	121	138	163	183	213	255	306	359	411
Power input	Cooling	Nom.		kW	39.1	47.5	53.9	60.9	69.0	72.4	87.8	112	134	147
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0									
EER					2.58	2.54	2.55	2.67	2.64	2.95	2.90	2.73	2.67	2.80
ESEER					2.84	2.83	2.66	2.84	2.73	2.93	3.08	2.96	3.13	3.24
IPLV					3.36	3.25	2.98	3.13	3.25	3.48	3.68	3.56	3.61	3.65
Dimensions	Unit	Height		mm	2,273						2,223			
		Width		mm	1,292						2,236			
		Depth		mm	2,165		3,065		3,965		3,070			
Weight	Unit			kg	1,684		1,861		2,086		2,919			
	Operation weight			kg	1,699		1,881		2,116		2,963			
Water heat exchanger	Type				Plate heat exchanger									
	Water volume			l	12	15	17	20	24	30	25	30	36	44
	Water flow rate	Cooling	Nom.	l/s	4.8	5.8	6.6	7.8	8.7	10.2	12.2	14.6	17.2	19.7
	Water pressure drop	Cooling	Nom.	kPa	24	25	23	24	22	21	47	48		45
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler									
Compressor	Type				Single screw compressor						Asymmetric single screw compressor			
	Quantity				1									
Fan	Type				Direct propeller									
	Quantity				2		3		4		6			
	Air flow rate	Nom.		l/s	10,924	10,576	16,386	15,865	21,848	21,153	32,772		31,729	
	Speed			rpm	900									
Sound power level	Cooling	Nom.		dBA	92				93		94			95
Sound pressure level	Cooling	Nom.		dBA	74					75				76
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15									
	Air side	Cooling	Min.~Max.	°CDB	-18~48									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1									
Refrigerant charge	Per circuit			kg	18.0	21.0	23.0	28.0	34.0	39.0	46.0		56.0	74.0
	Per circuit			TCO_2Eq	25.7	30.0	32.9	40.0	48.6	55.8	65.8		80.1	105.8
Piping connections	Evaporator water inlet/outlet (OD)				3"									
Unit	Maximum starting current			A	151		195		288		330	410		
	Nominal running current (RLA)	Cooling		A	67	81	92	102	116	121	148	185	220	241
	Maximum running current			A	86	103	119	132	157	164	198	242	284	298
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Air cooled screw chiller, standard efficiency, low sound



EWAD-E-SS/SL MicroTech III

Cooling only				EWAD-E-SL	100	120	130	160	180	210	250	300	350	400
Cooling capacity	Nom.			kW	97.6	116	134	157	177	208	248	295	344	397
Power input	Cooling	Nom.		kW	39.2	48.3	53.4	60.8	68.3	72.8	85.4	111	135	152
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0									
EER					2.49	2.39	2.50	2.57	2.59	2.86	2.90	2.65	2.55	2.62
ESEER					2.92	2.88	2.76	2.91	2.98	3.22	3.44	3.31	3.24	3.35
IPLV					3.32	3.21	3.30	3.46	3.28	3.48	3.86	3.75	3.63	3.76
Dimensions	Unit	Height		mm	2,273						2,223			
		Width		mm	1,292						2,236			
		Depth		mm	2,165		3,065		3,965		3,070			
Weight	Unit			kg	1,784		1,961		2,186		3,029			
	Operation weight			kg	1,799		1,981		2,216		3,073			
Water heat exchanger	Type				Plate heat exchanger									
	Water volume			l	12	15	17	20	24	30	25	30	36	44
	Water flow rate	Cooling	Nom.	l/s	4.7	5.5	6.4	7.5	8.4	10.0	11.9	14.1	16.5	19.0
	Water pressure drop	Cooling	Nom.	kPa	23		22	23	21	20	45		44	42
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler									
Compressor	Type				Single screw compressor						Asymmetric single screw compressor			
	Quantity				1									
Fan	Type				Direct propeller									
	Quantity				2		3		4		6			
	Air flow rate	Nom.		l/s	8,373	8,144	12,560	12,216	16,747	16,288	25,120		24,432	
	Speed			rpm	700									
Sound power level	Cooling	Nom.		dBA	89		90				92			93
Sound pressure level	Cooling	Nom.		dBA	71						73			74
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15									
	Air side	Cooling	Min.~Max.	°CDB	-18~48									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1									
Refrigerant charge	Per circuit			kg	18.0	21.0	23.0	28.0	34.0	39.0	46.0		56.0	74.0
	Per circuit			TCO_2Eq	25.7	30.0	32.9	40.0	48.6	55.8	65.8		80.1	105.8
Piping connections	Evaporator water inlet/outlet (OD)				3"									
Unit	Maximum starting current			A	151		195		288		330	410		
	Nominal running current (RLA)	Cooling		A	67	83	92	103	116	122	144	184	223	249
	Maximum running current			A	83	100	115	128	151	158	189	234	276	290
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Air cooled screw chiller, standard efficiency, standard sound

› 2 truly independent refrigerant circuits
› Stepless single-screw compressor
› Optimised for use with R-134a
› Large operation range (ambient temperature down to -18°C)
› MicroTech III controller with superior control logic and easy interface

Cooling only				EWAD-D-SS	390	440	470	510	530	560	580
Cooling capacity	Nom.			kW	388	435	463	500	529	553	575
Power input	Cooling	Nom.		kW	154	165	169	186	196	207	199
Capacity control	Method				Stepless						
	Minimum capacity			%	12.5						
EER					2.52	2.63	2.74	2.70		2.67	2.89
ESEER					3.26	3.43	3.44	3.41		3.45	3.29
IPLV					3.75	3.86	3.89	3.96		4.11	3.96
Dimensions	Unit	Height		mm	2,223						
		Width		mm	2,234						
		Depth		mm	3,139	4,040					
Weight	Unit			kg	2,960	4,030	4,220	4,230			4,235
	Operation weight			kg	3,090	4,195	4,395				
Water heat exchanger	Type				Single pass shell & tube						
	Water volume			l	130	165	175	165			160
	Water flow rate	Cooling	Nom.	l/s	18.6	20.8	22.2	24.0	25.4	26.5	27.6
	Water pressure drop	Cooling	Nom.	kPa	46	38	67	47	52	57	51
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler						
Compressor	Type				Single screw compressor	Asymmetric single screw compressor					
	Quantity				2						
Fan	Type				Direct propeller						
	Quantity				6		8				
	Air flow rate	Nom.		l/s	32,772	31,729	43,696				42,306
	Speed			rpm	890						
Sound power level	Cooling	Nom.		dBA	96	97			98	99	
Sound pressure level	Cooling	Nom.		dBA	77				79		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15						
	Air side	Cooling	Min.~Max.	°CDB	-18~48						
Refrigerant	Type / GWP				R-134a / 1,430						
	Circuits	Quantity			2						
Refrigerant charge	Per circuit			kg	28.0	33.0	36.0	38.0	40.0	43.0	47.0
	Per circuit			TCO_2Eq	40.0	47.2	51.5	54.3	57.2	61.5	67.2
Piping connections	Evaporator water inlet/outlet (OD)				5.5"						
Unit	Maximum starting current			A	419	464	485		494		
	Nominal running current (RLA)	Cooling		A	254	274	281	306	321	336	324
	Maximum running current			A	312	330	359	380	391	402	
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400						

Air cooled screw chiller, standard efficiency, low sound



EWAD-D-SS/SL MicroTech III

Cooling only				EWAD-D-SL	180	200	230	250	260	280	300	320	370	400	440	480	510	530
Cooling capacity	Nom.			kW	183	197	224	244	260	274	297	320	368	402	438	475	503	531
Power input	Cooling	Nom.		kW	82.0	80.2	85.6	94.4	102	109	121	125	135	171	172	188	205	197
Capacity control	Method				Stepless													
	Minimum capacity			%	12.5													
EER					2.24	2.46	2.62	2.58	2.54	2.50	2.46	2.56	2.72	2.36	2.55	2.53	2.46	2.70
ESEER					2.91	3.03	3.21	3.11	3.16	3.13	3.10	3.14	3.31	3.54	3.56	3.46	3.56	3.66
IPLV					3.43	3.56	3.73	3.63	3.66	3.63	3.59	3.62	3.84	3.85	4.06	3.96	4.07	4.14
Dimensions	Unit	Height		mm	2,355									2,223				
		Width		mm	2,234													
		Depth		mm	2,239		3,139					4,040						
Weight	Unit			kg	2,475	2,470	2,860					3,187		4,030	4,220	4,230		4,235
	Operation weight			kg	2,500		2,960					3,300		4,195	4,395			
Water heat exchanger	Type				Plate heat exchanger		Single pass shell & tube											
	Water volume			l	25	30	100					130		165	170		165	160
	Water flow rate	Cooling	Nom.	l/s	8.8	9.4	10.7	11.7	12.5	13.1	14.2	15.3	17.7	19.3	21.0	22.8	24.1	25.4
	Water pressure drop	Cooling	Nom.	kPa	29	22	58	49	54	59	60	55	67	48	62	54	48	43
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler													
Compressor	Type				Single screw compressor									Asymmetric single screw compressor				
	Quantity				2													
Fan	Type				Direct propeller													
	Quantity				4		6					8		6	8			
	Air flow rate	Nom.		l/s	15,295	14,868	22,943		22,623	22,302		30,591		24,432	33,493			32,576
	Speed			rpm	900									705				
Sound power level	Cooling	Nom.		dBA	94							95	97	94			96	
Sound pressure level	Cooling	Nom.		dBA	75								78	75			76	77
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15													
	Air side	Cooling	Min.~Max.	°CDB	-18~48													
Refrigerant	Type / GWP				R-134a / 1,430													
	Circuits	Quantity			2													
Refrigerant charge	Per circuit			kg	18.0	21.0	23.0	26.0	28.0	29.0			35.0	36.0	34.0		40.0	43.0
	Per circuit			TCO_2Eq	25.7	30.0	32.9	37.2	40.0	41.5			50.1	51.5	48.6		57.2	61.5
Piping connections	Evaporator water inlet/outlet (OD)				3"		4"					5"						
Unit	Maximum starting current			A	218		234		277	286	298	300	305	460	480		488	
	Nominal running current (RLA)	Cooling		A	135	133	141	155	166	176	192	200	214	281	285	308	334	323
	Maximum running current			A	165		186	202	213	224	238	258	269	322	348	368	379	
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400													

Air cooled screw chiller, standard efficiency, reduced sound

› 2 truly independent refrigerant circuits
› Stepless single-screw compressor
› Optimised for use with R-134a
› Large operation range (ambient temperature down to -18°C)
› MicroTech III controller with superior control logic and easy interface

Cooling only				**EWAD-D-SR**	**180**	**190**	**220**	**240**	**250**	**270**	**280**	**310**	**370**	**400**	**440**	**480**	**510**	**530**
Cooling capacity	Nom.			kW	177	190	218	237	251	263	277	310	364	402	438	475	503	531
Power input	Cooling	Nom.		kW	84.5	83.1	86.2	95.6	104	112	123	127	140	171	172	188	205	197
Capacity control	Method				Stepless													
	Minimum capacity			%	12.5													
EER					2.09	2.28	2.53	2.48	2.41	2.34	2.25	2.45	2.60	2.36	2.55	2.53	2.46	2.70
ESEER					2.80	2.91	3.24	3.11	3.13	3.07	3.04	3.15	3.32	3.54	3.56	3.46	3.56	3.66
IPLV					3.29	3.42	3.74	3.59		3.56	3.53	3.70	3.88	3.90	4.06	3.96	4.07	4.14
Dimensions	Unit	Height		mm	2,355									2,223				
		Width		mm	2,234													
		Depth		mm	2,239		3,139					4,040						
Weight	Unit			kg	2,620		2,890					3,335		4,040	4,240			
	Operation weight			kg	2,650		3,100					3,450		4,342	4,542			
Water heat exchanger	Type				Plate heat exchanger		Single pass shell & tube											
	Water volume			l	25	30	100					130		165	170		165	160
	Water flow rate	Cooling	Nom.	l/s	8.5	9.1	10.4	11.3	12.0	12.6	13.3	14.9	17.4	19.3	21.0	22.8	24.1	25.4
	Water pressure drop	Cooling	Nom.	kPa	27	20	55	47	51	55		53	65	48	62	54	48	43
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler													
Compressor	Type				Single screw compressor									Asymmetric single screw compressor				
	Quantity				2													
Fan	Type				Direct propeller													
	Quantity				4		6					8		6	8			
	Air flow rate	Nom.		l/s	12,389	11,928	18,583		18,237	17,892		24,777		24,432	33,493			32,576
	Speed			rpm	680									705				
Sound power level	Cooling	Nom.		dBA	89							90	92	91			92	93
Sound pressure level	Cooling	Nom.		dBA	70								73	71			73	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15													
	Air side	Cooling	Min.~Max.	°CDB	-18~48													
Refrigerant	Type / GWP				R-134a / 1,430													
	Circuits	Quantity			2													
Refrigerant charge	Per circuit			kg	18.0	21.0	24.0		25.0		29.0		33.0	35.0	40.0	39.0	40.0	43.0
	Per circuit			TCO_2Eq	25.7	30.0	34.3		35.8		41.5		47.2	50.1	57.2	55.8	57.2	61.5
Piping connections	Evaporator water inlet/outlet (OD)				3"		4"					5"						
Unit	Maximum starting current			A	217		232		275	284	295	297	302	460	480		488	
	Nominal running current (RLA)	Cooling		A	140	138	143	157	169	181	199	203	219	281	285	308	334	323
	Maximum running current			A	162		182	198	209	219	234	252	263	322	348	368	379	
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400													

Air cooled screw chiller. standard efficiency. extra low sound



EWAD-D-SX/SR MicroTech III

Cooling only				EWAD-D-SX	210	230	250	270	290	300	310	370	410	450	490
Cooling capacity	Nom.			kW	202	230	252	270	285	298	308	369	412	449	490
Power input	Cooling	Nom.		kW	80.8	86.0	94.4	105	115	127	137	150	171	175	189
Capacity control	Method				Stepless										
	Minimum capacity			%	12.5										
EER					2.50	2.68	2.67	2.56	2.47	2.35	2.25	2.46	2.41	2.56	2.60
ESEER					3.29	3.52	3.41	3.44	3.34	3.29	3.15	3.14	3.39	3.50	3.47
IPLV					3.82	4.08	3.99	4.01	3.92	3.84	3.69	4.03	3.90	3.98	3.90
Dimensions	Unit	Height		mm	2.420										
		Width		mm	2.234										
		Depth		mm	3.139	4.040								4.940	
Weight	Unit			kg	3.110	3.475		3.425	3.430			3.560	4.302	4.506	4.581
	Operation weight			kg	3.200	3.590						3.735	4.472	4.676	4.746
Water heat exchanger	Type				Single pass shell & tube										
	Water volume			l	90	115		165	160			175	170		165
	Water flow rate	Cooling	Nom.	l/s	9.7	11.0	12.1	12.9	13.7	14.3	14.7	17.7	19.7	21.5	23.5
	Water pressure drop	Cooling	Nom.	kPa	45	34	38		35	38	41	45	44	50	45
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler										
Compressor	Type				Single screw compressor								Asymmetric single screw compressor		
	Quantity				2										
Fan	Type				Direct propeller										
	Quantity				6	8								9	10
	Air flow rate	Nom.		l/s	12.876	17.892	17.169					26.496		28.982	33.120
	Speed			rpm	500										
Sound power level	Cooling	Nom.		dBA	84	85								86	
Sound pressure level	Cooling	Nom.		dBA	65									66	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15										
	Air side	Cooling	Min.~Max.	°CDB	-18~48										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			2										
Refrigerant charge	Per circuit			kg	21.0	24.0	26.0	32.0	33.0	34.0			35.0	38.0	40.0
	Per circuit			TCO_2Eq	30.0	34.3	37.2	45.8	47.2	48.6			50.1	54.3	57.2
Piping connections	Evaporator water inlet/outlet (OD)				4"							5"			
Unit	Maximum starting current			A	218	232		276	284	296		406	457	475	
	Nominal running current (RLA)	Cooling		A	135	143	157	173	188	204	220	231	272	280	298
	Maximum running current			A	164	183	199	210	221	235	250	291	316	338	360
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

Air cooled screw chiller, high efficiency, standard sound

› 2 truly independent refrigerant circuits
› Stepless single-screw compressor
› Optimised for use with R-134a
› Large operation range (ambient temperature down to -18°C)
› MicroTech III controller with superior control logic and easy interface

Cooling only				EWAD-D-XS	250	280	300	330	350	380	400	470	520	580	620
Cooling capacity	Nom.			kW	246	274	300	326	350	374	399	467	522	573	620
Power input	Cooling	Nom.		kW	80.1	88.2	95.4	105	114	121	129	152	169	183	196
Capacity control	Method				Stepless										
	Minimum capacity			%	12.5										
EER					3.07	3.11	3.15	3.10	3.06	3.08	3.10	3.07	3.09	3.12	3.16
ESEER					3.45	3.49	3.51	3.73	3.56	3.47	3.48	3.72	3.88	3.89	3.75
IPLV					3.98	4.00		4.08	4.07	4.06	3.98	4.16	4.83		4.61
Dimensions	Unit	Height		mm	2,355							2,223			
		Width		mm	2,234										
		Depth		mm	3,138	4,040							4,940		
Weight	Unit			kg	2,905	3,285		3,235	3,240			3,510	4,670	4,685	
	Operation weight			kg	3,000	3,400						3,780	4,940		
Water heat exchanger	Type				Single pass shell & tube										
	Water volume			l	95	115		165	160			270		255	
	Water flow rate	Cooling	Nom.	l/s	11.8	13.1	14.4	15.6	16.7	17.9	19.1	22.4	25.0	27.4	29.7
	Water pressure drop	Cooling	Nom.	kPa	48	45	49	46	51	58	64	47	63	56	38
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler										
Compressor	Type				Single screw compressor								Asymmetric single screw compressor		
	Quantity				2										
Fan	Type				Direct propeller										
	Quantity				6	8							10		
	Air flow rate	Nom.		l/s	22,302	30,591	29,736			43,001	42,306	43,696	54,620		
	Speed			rpm	900					890					
Sound power level	Cooling	Nom.		dBA	97					99					
Sound pressure level	Cooling	Nom.		dBA	78					79					
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15										
	Air side	Cooling	Min.~Max.	°CDB	-18~48										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			2										
Refrigerant charge	Per circuit			kg	29.0	33.0	35.0	38.0	35.0		39.0	42.0	45.0		50.0
	Per circuit			TCO_2Eq	41.5	47.2	50.1	54.3	50.1		55.8	60.1	64.4		71.5
Piping connections	Evaporator water inlet/outlet (OD)				4"							6"			
Unit	Maximum starting current			A	224	240		283	292	312		423	480	498	
	Nominal running current (RLA)	Cooling		A	132	145	158	172	185	203	213	253	283	305	324
	Maximum running current			A	178	199	216	227	239	268	283	328	365	387	410
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

Air cooled screw chiller, high efficiency, reduced sound



EWAD-D-XS/XR MicroTech III

Cooling only				EWAD-D-XR	240	270	300	320	350	370	390	460	510	560	600
Cooling capacity	Nom.			kW	242	271	294	321	343	369	393	453	510	559	598
Power input	Cooling	Nom.		kW	81.6	88.0	96.3	107	117	121	129	154	169	185	200
Capacity control	Method				Stepless										
	Minimum capacity			%	12.5										
EER					2.96	3.07	3.06	3.00	2.94	3.06	3.05	2.95	3.01	3.02	2.99
ESEER					3.52	3.59	3.58	3.71	3.60	3.89	3.71	3.77	3.99		3.81
IPLV					4.03	4.11	4.12	4.17	4.13	4.28	4.25	4.36	4.79	4.78	4.47
Dimensions	Unit	Height		mm	2,355							2,223			
		Width		mm	2,234										
		Depth		mm	3,138	4,040							4,940		
Weight	Unit			kg	3,005	3,385		3,335	3,340			3,610	4,770	4,785	
	Operation weight			kg	3,100	3,500						3,880	5,040		
Water heat exchanger	Type				Single pass shell & tube										
	Water volume			l	95	115		165	160			270		255	
	Water flow rate	Cooling	Nom.	l/s	11.6	13.0	14.1	15.4	16.4	17.7	18.8	21.7	24.4	26.8	28.6
	Water pressure drop	Cooling	Nom.	kPa	47	44	48	45	49	56		45	60	54	36
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler										
Compressor	Type				Single screw compressor								Asymmetric single screw compressor		
	Quantity				2										
Fan	Type				Direct propeller										
	Quantity				6	8							10		
	Air flow rate	Nom.		l/s	17,892	24,777	23,856			33,035	32,576	33,493	41,867		
	Speed			rpm	680					705					
Sound power level	Cooling	Nom.		dBA	92					93			94		
Sound pressure level	Cooling	Nom.		dBA	73					74					
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15										
	Air side	Cooling	Min.~Max.	°CDB	-18~48										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			2										
Refrigerant charge	Per circuit			kg	30.0	31.0	38.0	39.0	40.0	39.0		34.0	45.0	47.0	50.0
	Per circuit			TCO_2Eq	42.9	44.3	54.3	55.8	57.2	55.8		48.6	64.4	67.2	71.5
Piping connections	Evaporator water inlet/outlet (OD)				4"							6"			
Unit	Maximum starting current			A	222	237		280	289	306		417	473	491	
	Nominal running current (RLA)	Cooling		A	134	144	160	175	188	200	213	256	283	308	330
	Maximum running current			A	173	193	210	222	233	257	272	317	351	373	396
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

Air cooled screw chiller, high ambient, standard sound

- **High ambient**
- Stepless single-screw compressor
- Optimised for use with R-134a
- Large operation range (ambient temperature down to -18°C)
- MicroTech III controller with superior control logic and easy interface



EWAD-D-HS MicroTech III

Cooling only				EWAD-D-HS	200	210	230	260	270	290	310	340	380	420	450	480	510	550	590
Cooling capacity	Nom.			kW	194	208	233	255	272	288	305	334	379	413	446	476	512	545	585
Power input	Cooling	Nom.		kW	77.9	76.0	83.9	92.1	98.9	105	114	122	129	143	152	164	177	185	194
Capacity control	Method				Stepless														
	Minimum capacity			%	12.5														
EER					2.49	2.73	2.77		2.75	2.73	2.68	2.75	2.93	2.90	2.93	2.90	2.89	2.95	3.02
ESEER					3.02	3.16	3.24	3.11	3.20	3.18	3.17	3.15	3.46	3.50	3.57		3.55	3.60	3.68
IPLV					3.56	3.74	3.77	3.66	3.74	3.73	3.72	3.64	3.99	4.00	4.05	3.99	4.10	4.18	4.50
Dimensions	Unit	Height		mm	2,223														
		Width		mm	2,234														
		Depth		mm	2,239		3,339					4,040				4,940			
Weight	Unit			kg	2,475	2,470	2,865		2,870			3,185		3,277	3,942	4,356	4,361		4,366
	Operation weight			kg	2,500		2,960					3,300		3,447	4,112		4,526		
Water heat exchanger	Type				Plate heat exchanger		Single pass shell & tube												
	Water volume			l	25	30	95		90			115		170			165		160
	Water flow rate	Cooling	Nom.	l/s	9.3	9.9	11.1	12.2	13.1	13.8	14.6	16.0	18.2	19.8	21.4	22.8	24.5	26.1	28.0
	Water pressure drop	Cooling	Nom.	kPa	32	24	46	52	54	59	64	58	70	46	53	58	51	56	53
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler														
Compressor	Type				Single screw compressor										Asymmetric single screw compressor				
	Quantity				2														
Fan	Type				Direct propeller														
	Quantity				4		6					8				10			
	Air flow rate	Nom.		l/s	21,848	21,153	32,772		32,251	31,729		43,696			42,306	54,620			
	Speed	Cooling	Nom.	rpm	890														
Sound power level	Cooling	Nom.		dBA	96							97	99	97	98		99		100
Sound pressure level	Cooling	Nom.		dBA	77								79	77	78		79		80
Operation range	Water side	Cooling	Min.~Max.	°CDB	-15~15														
	Air side	Cooling	Min.~Max.	°CDB	-18~48														
Refrigerant	Type / GWP				R-134a / 1,430														
	Circuits	Quantity			2														
Refrigerant charge	Per circuit			kg	18.0	21.0	22.0	26.0	28.0	31.0	28.0		34.0	30.0	45.0	47.5	46.0		47.0
	Per circuit			TCO_2Eq	25.7	30.0	31.5	37.2	40.0	44.3	40.0		48.6	42.9	64.4	67.9	65.8		67.2
Piping connections	Evaporator water inlet/outlet (OD)				3"		4"							5"					
Unit	Maximum starting current			A	222		239		283	291	303	307	312	423	468	489		498	
	Nominal running current (RLA)	Cooling		A	134	131	145	157	169	180	191	204	214	239	258	275	295	306	320
	Maximum running current			A	172		197	213	224	234	249	272	283	320	338	367	388	399	410
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400														



Air cooled screw chiller, standard efficiency, standard/low sound

- Stepless single-screw compressor
- Optimised for use with R-134a
- Large operation range (ambient temperature down to -18°C and up to 46°C)
- All models are PED pressure vessel approved
- 2-3 truly independent refrigerant circuits
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side to minimize pressure drops
- Partial and total heat recovery option available
- MicroTech III controller with superior control logic and easy interface

Cooling only				EWAD-C-SS/SL	650	740	830	910	970	C11	C12	C13	H14	C15	C16	C17	C18	C19	C20
Cooling capacity	Nom.			kW	645	741	829	908	962	1,059	1,146	1,315	1,412	1,532	1,615	1,706	1,797	1,870	1,917
Power input	Cooling	Nom.		kW	223	265	302	322	355	382	408	446	479	557	586	627	669	687	721
Capacity control	Method				Stepless														
	Minimum capacity			%	12.5									7.0					
EER					2.89	2.80	2.74	2.82	2.71	2.77	2.81	2.95		2.75		2.72	2.69	2.72	2.66
ESEER					3.79	3.69	3.72	3.65	3.60	3.69	3.63	3.88	3.86	3.73	3.68	3.59	3.71	3.68	
IPLV					4.32	4.17	4.18	4.25	4.16	4.17	4.21	4.42		4.28	4.18	4.15	4.24	4.19	4.21
Dimensions	Unit	Height		mm	2,540														
		Width		mm	2,285														
		Depth		mm	6,285					7,185	8,085	8,985		10,285	11,185			12,085	
Weight (SS)	Unit			kg	5,330	5,740	5,760	6,280	6,560	7,010	7,280	7,900		10,320	10,710	10,770	11,240	11,600	
	Operation weight			kg	5,610	5,990	6,010	6,530	6,810	7,250	7,520	8,280		10,730	11,110	11,260	12,110	12,480	
Weight (SL)	Unit			kg	5,920	6,030	6,050	6,570	6,850	7,300	7,570	8,190		10,770	11,150	11,210	11,680	12,040	
	Operation weight			kg	6,200	6,280	6,300	6,820	7,100	7,540	7,810	8,570		11,170	11,550	11,700	12,560	12,920	
Water heat exchanger	Type				Single pass shell & tube														
	Water volume			l	266			251		243		386		408		474	850		
	Water flow rate	Cooling	Nom.	l/s	30.9	35.5	39.7	43.5	46.1	50.8	55.0	62.9	67.6	73.4	77.4	81.8	86.0	89.5	91.7
	Water pressure drop	Cooling	Nom.	kPa	47	54	53	62	69	64	74	54	58	62	68	75	36	39	40
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler														
Compressor	Type				Asymmetric single screw compressor														
	Quantity				2									3					
Fan	Type				Direct propeller														
	Quantity				10			12		14	16	18		20	22			24	
	Air flow rate	Nom.		l/s	53,442			64,131		74,819	85,508	96,196		106,885	117,573			128,262	
	Speed			rpm	900														
Sound power level (SS)	Cooling	Nom.		dBA	102	100		101		102				103			104		
Sound power level (SL)	Cooling	Nom.		dBA	96			98	97	98				99	100			101	
Sound pressure level (SS)	Cooling	Nom.		dBA	81	80				81							82		
Sound pressure level (SL)	Cooling	Nom.		dBA	76			77									78		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15														
	Air side	Cooling	Min.~Max.	°CDB	-18~46														
Refrigerant	Type / GWP				R-134a / 1,430														
	Circuits	Quantity			2									3					
Refrigerant charge	Per circuit			kg	64.0			76.5	80.0	91.0	94.0	110.0	130.0	73.3	86.7			91.7	101.7
	Per circuit			TCO_2Eq	91.5			109.4	114.4	130.1	134.4	157.3	185.9	104.9	123.9			131.1	145.4
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm							219.1mm					273mm		
Unit	Maximum starting current			A	604	649		915	962	1,017	1,021	1,068	1,081	1,312	1,363	1,367	1,410	1,456	1,470
	Nominal running current (RLA)	Cooling		A	366	432	492	524	577	624	667	726	773	909	959.0	1,023	1,092	1,116	1,164
	Maximum running current			A	476	545	589	656	715	787	859	921	974	1,144	1,217	1,281	1,334	1,395	1,449
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400														

Air cooled screw chiller, standard efficiency, reduced sound



EWAD-C-SS/SL/SR



MicroTech III

Cooling only				EWAD-C-SR	620	720	790	880	920	C10	C11	C12	H14	C13	C14	C15	C16	C17	C18	C19
Cooling capacity	Nom.			kW	617	712	786	872	918	1,016	1,107	1,266	1,316	1,363	1,465	1,550	1,616	1,710	1,790	1,828
Power input	Cooling	Nom.		kW	226	276	317	334	373	398	422	461	499	522	582	609	654	706	722	762
Capacity control	Method				Stepless															
	Minimum capacity			%	12.5									7.0						
EER					2.74	2.59	2.48	2.61	2.46	2.55	2.63	2.75	2.63	2.61	2.52	2.54	2.47	2.42	2.48	2.40
ESEER					3.91	3.78	3.81	3.79	3.98	3.76	3.95	3.92	3.81	3.78	3.70	3.72	3.66	3.70	3.71	3.66
IPLV					4.39	4.41	4.19	4.29	4.21		4.33	4.52	4.35	4.29	4.27	4.28	4.23	4.24	4.27	4.21
Dimensions	Unit	Height		mm	2,540															
		Width		mm	2,285															
		Depth		mm	6,285					7,185	8,085	8,985		10,285		11,185			12,085	
Weight	Unit			kg	5,920	6,030	6,050	6,570	6,850	7,300	7,570	8,190		10,750	10,770	11,150	11,210	11,680	12,040	
	Operation weight			kg	6,200	6,280	6,300	6,820	7,100	7,540	7,810	8,570		11,170		11,550	11,700	12,560	12,920	
Water heat exchanger	Type				Single pass shell & tube															
	Water volume			l	266		251			243		386		421		408		474	850	
	Water flow rate	Cooling	Nom.	l/s	29.5	34.1	37.6	41.8	44.0	48.7	53.1	60.6	63.0	65.2	70.2	74.2	77.4	81.8	85.6	87.5
	Water pressure drop	Cooling	Nom.	kPa	43	50	48	58	63	60	69	50	54	45	57	63	69	33	36	37
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler															
Compressor	Type				Asymmetric single screw compressor															
	Quantity				2									3						
Fan	Type				Direct propeller															
	Quantity				10			12		14	16	18		20		22			24	
	Air flow rate	Nom.		l/s	41,007			49,208		57,410	65,611	73,812		82,014		90,215			98,417	
	Speed			rpm	700															
Sound power level	Cooling	Nom.		dBA	92				93	94				95				96		
Sound pressure level	Cooling	Nom.		dBA	71	72				73								74		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15															
	Air side	Cooling	Min.~Max.	°CDB	-18~46															
Refrigerant	Type / GWP				R-134a / 1,430															
	Circuits	Quantity			2									3						
Refrigerant charge	Per circuit			kg	64.0			76.5	80.0	91.0	94.0	110.0		86.7				91.7	101.7	
	Per circuit			TCO_2Eq	91.5			109.4	114.4	130.1	134.4	157.3		123.9				131.1	145.4	
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm							219.1mm						273mm		
Unit	Maximum starting current			A	597	642		906	953	1,007	1,010	1,055	1,068	1,241	1,292	1,344	1,346	1,389	1,434	1,447
	Nominal running current (RLA)	Cooling		A	371	450	518	548	609	654	694	755	811	857	954	1,002	1,075	1,158	1,179	1,238
	Maximum running current			A	462	531	575	639	698	767	837	895	949	1,052	1,116	1,186	1,250	1,303	1,362	1,415
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400															

Air cooled screw chiller, high efficiency, standard/low sound

- Stepless single-screw compressor
- Optimised for use with R-134a
- Large operation range (ambient temperature down to -18°C and up to 50°C)
- All models are PED pressure vessel approved
- 2-3 truly independent refrigerant circuits
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side to minimize pressure drops
- Partial and total heat recovery option available
- MicroTech III controller with superior control logic and easy interface

Cooling only				EWAD-C-XS/XL	760	830	890	990	C10	C11	C12	C13	H14	H15	C16	C17	C18	C19	C20	C21	C22
Cooling capacity	Nom.			kW	752	827	885	997	1,069	1,192	1,276	1,343	1,408	1,517	1,590	1,678	1,760	1,849	1,896	1,947	2,002
Power input	Cooling	Nom.		kW	237	256	282	311	343	367	404	416	450	483	510	541	569	598	619	648	678
Capacity control	Method				Stepless																
	Minimum capacity			%	12.5										7.0						
EER					3.17	3.22	3.14	3.20	3.12	3.25	3.15	3.23	3.13	3.14	3.12	3.10	3.09		3.06	3.00	2.95
ESEER					3.77	3.92	3.81	3.91	3.84	3.99	3.86	4.05	4.04	4.06	4.00	3.96	3.94	3.93	4.02	3.91	3.89
IPLV					4.48		4.52	4.50	4.44	4.50	4.47	4.60	4.71	4.81	4.58	4.59	4.51	4.53	4.57	4.42	4.47
Dimensions	Unit	Height		mm	2,540																
		Width		mm	2,285																
		Depth		mm	6,285	7,185		8,085		9,885					12,085	12,985	13,885	14,785			
Weight (XS)	Unit			kg	5,990	6,340	6,360	7,190	7,470	8,220	8,240	8,900			11,570	11,900	12,260	12,600			
	Operation weight			kg	6,240	6,580	6,600	7,600	7,870	8,610	8,630	9,890			12,430	12,760	13,140	13,470			
Weight (XL)	Unit			kg	6,280	6,630	6,650	7,480	7,760	8,510	8,530	9,190			12,010	12,350	12,700	13,040			
	Operation weight			kg	6,520	6,870	6,890	7,880	8,160	8,900	8,920	10,180			12,870	13,200	13,580	13,910			
Water heat exchanger	Type				Single pass shell & tube																
	Water volume			l	251	243		403		386		979			850		871	850			
	Water flow rate	Cooling	Nom.	l/s	36.1	39.6	42.4	47.8	51.2	57.1	61.1	64.4	67.5	72.8	76.1	80.4	84.4	88.6	90.7	93.2	95.8
	Water pressure drop	Cooling	Nom.	kPa	81	57	64	61	69	45	51	68	77	84	62	68		74	39	41	43
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler																
Compressor	Type				Asymmetric single screw compressor																
	Quantity				2										3						
Fan	Type				Direct propeller																
	Quantity				12	14		16		20					24	26	28	30			
	Air flow rate	Nom.		l/s	64,131	74,819		85,508		106,885					128,262	138,950	149,639	160,327			
	Speed			rpm	900																
Sound power level (XS)	Cooling	Nom.		dBA	100	101			102		103				104						
Sound power level (XL)	Cooling	Nom.		dBA	97			98		99					100						
Sound pressure level (XS)	Cooling	Nom.		dBA	80				81	80					81						
Sound pressure level (XL)	Cooling	Nom.		dBA	76	77											78				
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15																
	Air side	Cooling	Min.~Max.	°CDB	-18~50																
Refrigerant	Type / GWP				R-134a / 1,430																
	Circuits	Quantity			2										3						
Refrigerant charge	Per circuit			kg	75.0	81.0		91.0	100.0	115.0	117.5	125.0	145.5	125.0	82.7	99.0	103.3	109.0	113.3	120.0	
	Per circuit			TCO_2Eq	107.3	115.8		130.1	143.0	164.5	168.0	178.8	208.1	178.8	118.2	141.6	147.8	155.9	162.1	171.6	
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm			219.1mm							273mm						
Unit	Maximum starting current			A	618	657		923	970	1,029			1,072	1,085	1,268	1,328	1,387		1,430	1,472	1,486
	Nominal running current (RLA)	Cooling		A	387	423	463	511	559	607	667	686	731	778	835	885	934.0	984	1,018	1,059	1,100
	Maximum running current			A	510	561	605	672	731	811	875		929	982	1,096	1,168	1,241	1,313	1,366	1,419	1,473
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400																

Air cooled screw chiller, high efficiency, reduced sound



EWAD-C-XS/XL/XR

MicroTech III

Cooling only				EWAD-C-XR	740	810	870	970	C10	C11	C12	C13	H14	H15	C16	C17	C18	C19	C20	C21	C22
Cooling capacity	Nom.			kW	732	808	862	970	1,036	1,164	1,243	1,297	1,360	1,460	1,544	1,632	1,715	1,805	1,849	1,897	1,947
Power input	Cooling	Nom.		kW	238	257	285	313	348	369	409	420	460	498	518	548	574	604	629	662	696
Capacity control	Method				Stepless																
	Minimum capacity			%	12.5										7.0						
EER					3.07	3.15	3.03	3.10	2.98	3.16	3.04	3.09	2.96	2.93	2.98		2.99		2.94	2.87	2.80
ESEER					4.01	4.16	4.01	4.12	4.01	4.21	4.07	4.10		4.12	4.08	4.00	4.05	4.00	4.09	3.96	3.94
IPLV					4.56	4.62	4.51	4.63	4.59	4.65	4.61	4.63	4.74	4.83	4.67	4.65		4.63	4.69	4.54	4.53
Dimensions	Unit	Height		mm	2,540																
		Width		mm	2,285																
		Depth		mm	6,285	7,185		8,085		9,885					12,085	12,985	13,885	14,785			
Weight	Unit			kg	6,280	6,630	6,650	7,480	7,760	8,510	8,530	9,190			12,010	12,350	12,700	13,040			
	Operation weight			kg	6,520	6,870	6,890	7,880	8,160	8,900	8,920	10,180			12,870	13,200	13,580	13,910			
Water heat exchanger	Type				Single pass shell & tube																
	Water volume			l	251	243		403		386		979			850		871	850			
	Water flow rate	Cooling	Nom.	l/s	35.1	38.7	41.3	46.5	49.7	55.7	59.5	62.1	65.2	70.0	74.0	78.2	82.2	86.5	88.5	90.7	93.1
	Water pressure drop	Cooling	Nom.	kPa	77	54	61	58	65	43	49	64	73	79	59	65		71	37	39	41
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler																
Compressor	Type				Asymmetric single screw compressor																
	Quantity				2										3						
Fan	Type				Direct propeller																
	Quantity				12	14		16		20					24	26	28	30			
	Air flow rate	Nom.		l/s	49,208	57,410		65,611		82,014					98,417	106,618	114,819	123,021			
	Speed			rpm	700																
Sound power level	Cooling	Nom.		dBA	92			94			95					96				97	
Sound pressure level	Cooling	Nom.		dBA	72				73	72			73							74	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15																
	Air side	Cooling	Min.~Max.	°CDB	-18~50																
Refrigerant	Type / GWP				R-134a / 1,430																
	Circuits	Quantity			2										3						
Refrigerant charge	Per circuit			kg	75.0	81.0		91.0	100.0	115.0	117.5	125.0		124.0	103.3	109.0	113.3	120.0			125.0
	Per circuit			TCO_2Eq	107.3	115.8		130.1	143.0	164.5	168.0	178.8		177.3	147.8	155.9	162.1	171.6			178.8
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm			219.1mm				273mm									
Unit	Maximum starting current			A	610	647		911	959	1,015			1,058	1,071	1,246	1,303	1,359		1,402	1,444	1,458
	Nominal running current (RLA)	Cooling		A	392	426	470	518	572	613	679	699	753	807	854	903	951	1,000	1,040	1,087	1,136
	Maximum running current			A	493	542	585	649	708	783	847		901	954	1,063	1,132	1,201	1,271	1,324	1,377	1,431
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400																

Air cooled screw chiller, premium efficiency, standard/low sound

- Excellent part load efficiency
- Stepless single-screw compressor
- Optimised for use with R-134a
- Large operation range (ambient temperature down to -18°C and up to 52°C)
- All models are PED pressure vessel approved
- 2 truly independent refrigerant circuits
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side to minimize pressure drops
- Partial and total heat recovery option available
- MicroTech III controller with superior control logic and easy interface

Cooling only				EWAD-C-PS/PL	820	890	980	C11	C12	C13	C14	C15	C16
Cooling capacity	Nom.			kW	818	886	973	1,070	1,153	1,274	1,384	1,467	1,554
Power input	Cooling	Nom.		kW	229	253	276	306	335	368	402	432	461
Capacity control	Method				Stepless								
	Minimum capacity			%	12.5								
EER					3.57	3.51	3.52	3.49	3.44	3.46	3.44	3.40	3.37
ESEER					4.22	4.25	4.30	4.29	4.14	4.23	4.07	4.06	4.03
IPLV					4.78	4.67	4.79	4.69	4.73	4.68	4.73		4.71
Dimensions	Unit	Height		mm	2,540								
		Width		mm	2,285								
		Depth		mm	8,985			9,885		11,185	12,085		
Weight (PS)	Unit			kg	7,530		7,660	8,290	8,550	9,390	9,730		
	Operation weight			kg	8,130		8,700	9,330	9,590	10,380	10,720		
Weight (PL)	Unit			kg	7,820		7,950	8,580	8,840	10,380	10,720		
	Operation weight			kg	8,420		8,990	9,620	9,880	10,670	11,010		
Water heat exchanger	Type				Single pass shell & tube								
	Water volume			l	599		1,043	1,027		995	979		
	Water flow rate	Cooling	Nom.	l/s	39.2	42.5	46.5	51.2	55.2	61.0	66.3	70.3	74.5
	Water pressure drop	Cooling	Nom.	kPa	58	67	31	61	70	60	70	81	88
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler								
Compressor	Type				Asymmetric single screw compressor								
	Quantity				2								
Fan	Type				Direct propeller								
	Quantity				18			20		22	24		
	Air flow rate	Nom.		l/s	96,196			106,885		117,573	128,262		
	Speed			rpm	900								
Sound power level (PS)	Cooling	Nom.		dBA	101			102			103		104
Sound power level (PL)	Cooling	Nom.		dBA	98			99	100	99	100		
Sound pressure level (PS)	Cooling	Nom.		dBA	80				81	80	81		
Sound pressure level (PL)	Cooling	Nom.		dBA	77							78	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15								
	Air side	Cooling	Min.~Max.	°CDB	-18~52								
Refrigerant	Type / GWP				R-134a / 1,430								
	Circuits	Quantity			2								
Refrigerant charge	Per circuit			kg	102.0			115.0	120.0	137.5	140.0		
	Per circuit			TCO_2Eq	145.9			164.5	171.6	196.6	200.2		
Piping connections	Evaporator water inlet/outlet (OD)				219.1mm		273mm						
Unit	Maximum starting current			A	630	665		702	978	1,037		1,080	1,093
	Nominal running current (RLA)	Cooling		A	386	424	465	511	555	614	671	711	752
	Maximum running current			A	534	577	621	670	747	819	891	945	998
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400								

Air cooled screw chiller, premium efficiency, reduced sound



EWAD-C-PS/PL/PR

MicroTech III

Cooling only				EWAD-C-PR	810	880	960	C10	C11	C13	C14	C15	C16
Cooling capacity	Nom.			kW	806	871	954	1,049	1,127	1,246	1,353	1,432	1,513
Power input	Cooling	Nom.		kW	222	248	275	303	335	369	402	432	465
Capacity control	Method				Stepless								
	Minimum capacity			%	12.5								
EER					3.63	3.51	3.47	3.46	3.36	3.38	3.36	3.32	3.25
ESEER					4.39	4.33	4.40	4.35	4.25	4.33	4.26	4.23	4.15
IPLV					5.07	4.89		4.92	4.82	4.81	4.85		4.79
Dimensions	Unit	Height		mm	2,540								
		Width		mm	2,285								
		Depth		mm	8,985			9,885		11,185	12,085		
Weight	Unit			kg	7,820		7,950	8,580	8,840	10,380	10,720		
	Operation weight			kg	8,420		8,990	9,620	9,880	10,670	11,010		
Water heat exchanger	Type				Single pass shell & tube								
	Water volume			l	599		1,043	1,027		995	979		
	Water flow rate	Cooling	Nom.	l/s	38.6	41.7	45.6	50.2	54.0	59.7	64.8	68.7	72.6
	Water pressure drop	Cooling	Nom.	kPa	56	65	30	59	67	58	67	77	84
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler								
Compressor	Type				Asymmetric single screw compressor								
	Quantity				2								
Fan	Type				Direct propeller								
	Quantity				18			20		22	24		
	Air flow rate	Nom.		l/s	73,812			82,014		90,215	98,417		
	Speed			rpm	700								
Sound power level	Cooling	Nom.		dBA	93				94			95	
Sound pressure level	Cooling	Nom.		dBA	71			72					73
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15								
	Air side	Cooling	Min.~Max.	°CDB	-18~52								
Refrigerant	Type / GWP				R-134a / 1,430								
	Circuits	Quantity			2								
Refrigerant charge	Per circuit			kg	102.0			115.0	120.0	137.5	140.0		
	Per circuit			TCO_2Eq	145.9			164.5	171.6	196.6	200.2		
Piping connections	Evaporator water inlet/outlet (OD)				219.1mm			273mm					
Unit	Maximum starting current			A	618	653		917	964	1,020		1,063	1,076
	Nominal running current (RLA)	Cooling		A	375	416	461	506	555	614	671	717	764
	Maximum running current			A	509	552	596	660	719	788	858	911	964
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400								

Air cooled screw inverter chiller, high efficiency, standard/low sound

- High efficiency with leader-of-class ESEER
- Inverter stepless single-screw compressor
- Highly efficient fans with patented blade profile for quiet operation
- Extensive option list (heat recovery option available)
- Wide operating range
- Low starting current
- Optimised for use with R-134a
- MicroTech III controller with superior control logic and easy interface

Cooling only				**EWAD-CZXS/XL**	**740**	**830**	**900**	**C10**	**C11**	**C12**	**C13**	**C14**	**C15**	**C16**	**C17**	**C18**
Cooling capacity	Nom.			kW	734	828	898	1,033	1,090	1,232	1,303	1,444	1,538	1,616	1,701	1,795
Power input	Cooling	Nom.		kW	239	269	309	343	380	404	447	494	538	564	596	619
Capacity control	Method				Stepless											
	Minimum capacity			%	20.0										13.0	
EER					3.07		2.90	3.01	2.87	3.05	2.92	2.93	2.86		2.85	2.90
ESEER					4.72	4.89	4.88	4.91	4.70		4.51	4.73	4.83	4.59	4.62	4.61
IPLV					5.68	5.72	5.79	5.73	5.56	5.58	5.45	5.61	5.75	5.65	5.46	5.29
Dimensions	Unit	Height		mm	2,540											
		Width		mm	2,285											
		Depth		mm	6,725	7,625		8,525		10,325		11,625	12,525		13,425	14,325
Weight (XS)	Unit			kg	6,000	6,620	6,870	7,440		8,570	8,970	9,600	9,940	11,370	12,190	12,920
	Operation weight			kg	6,250	6,860	7,110	7,880		8,960	9,360	9,980	10,320	12,220	13,040	13,790
Weight (XL)	Unit			kg	6,280	6,900	7,150	7,720		8,850	9,250	9,880	10,220	11,790	12,610	13,340
	Operation weight			kg	6,530	7,140	7,390	8,160		9,240	9,640	10,260	10,600	12,640	13,460	14,210
Water heat exchanger	Type				Single pass shell & tube											
	Water volume			l	248	241		441		383		374		850		871
	Water flow rate	Cooling	Nom.	l/s	35.2	39.7	43.0	49.5	52.3	59.0	62.4	69.2	73.7	77.4	81.5	86.0
	Water pressure drop	Cooling	Nom.	kPa	83	58	65	63	70	47	52	62	72	63	69	65
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler											
Compressor	Type				Asymmetric single screw compressor											
	Quantity				2										3	
Fan	Type				Direct propeller											
	Quantity				12	14		16		20		22	24		26	28
	Air flow rate	Nom.		l/s	65,026	75,863		86,701		108,376		119,214	130,051	129,455	140,143	151,130
	Speed			rpm	900											
Sound power level (XS)	Cooling	Nom.		dBA	102	103				104				106		
Sound power level (XL)	Cooling	Nom.		dBA	99	100				101				103		
Sound pressure level (XS)	Cooling	Nom.		dBA	81									83		
Sound pressure level (XL)	Cooling	Nom.		dBA	78									80		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15											
	Air side	Cooling	Min.~Max.	°CDB	-18~50											
Refrigerant	Type / GWP				R-134a / 1,430											
	Circuits	Quantity			2									3		
Refrigerant charge	Per circuit			kg	73.0	81.0		100.0		125.0			140.0	106.7	113.3	116.7
	Per circuit			TCO_2Eq	104.4	115.8		143.0		178.8			200.2	152.5	162.1	166.8
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm			219.1mm						273mm		
Unit	Maximum starting current			A	374	416	447	496	534	585	620	703	765	840	890	940
	Nominal running current (RLA)	Cooling		A	403	438	481	532	586	630	692	762	829	873	922	962
	Maximum running current			A	524	579	626	691	748	816	869	970	1,072	1,121	1,182	1,243
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400											

Air cooled screw inverter chiller, high efficiency, reduced sound



EWAD-CZXS/XL/XR

MicroTech III

Cooling only				EWAD-CZXR	700	790	850	980	C10	C11	C12	C13	C14	C15	C16	C17
Cooling capacity	Nom.			kW	696	786	849	972	1,027	1,166	1,231	1,327	1,437	1,539	1,624	1,706
Power input	Cooling	Nom.		kW	246	274	318	351	393	412	459	493	523	585	617	638
Capacity control	Method				Stepless											
	Minimum capacity			%	20.0									13.0		
EER					2.83	2.86	2.67	2.77	2.61	2.83	2.68	2.69	2.75	2.63		2.67
ESEER					5.23	5.39	5.36	5.41	5.11	5.15	4.80	5.12	5.22	5.10	4.83	4.77
IPLV					6.14	6.32	6.37	6.34	6.05	5.96	5.67	6.03	6.21	6.17	5.89	5.85
Dimensions	Unit	Height		mm	2,540											
		Width		mm	2,285											
		Depth		mm	6,725	7,625		8,525		10,325		11,625	12,525		13,425	14,325
Weight	Unit			kg	6,470	7,100	7,360	7,950		9,120	9,530	10,180	10,530	12,150	12,990	13,740
	Operation weight			kg	6,720	7,340	7,600	8,390		9,500	9,920	10,550	10,910	13,000	13,840	14,610
Water heat exchanger	Type				Single pass shell & tube											
	Water volume			l	248	241		441		383		374		850		871
	Water flow rate	Cooling	Nom.	l/s	33.4	37.6	40.7	46.6	49.2	55.8	58.9	63.6	68.8	73.7	77.8	81.7
	Water pressure drop	Cooling	Nom.	kPa	76	54	59	58	64	43	48	57	66	57	63	60
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler											
Compressor	Type				Asymmetric single screw compressor											
	Quantity				2									3		
Fan	Type				Direct propeller											
	Quantity				12	14		16		20		22	24		26	28
	Air flow rate	Nom.		l/s	49,843	58,151		66,458		83,072		91,380	99,687		107,994	116,301
	Speed			rpm	700											
Sound power level	Cooling	Nom.		dBA	95	96				97				99		
Sound pressure level	Cooling	Nom.		dBA	74									76		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15											
	Air side	Cooling	Min.~Max.	°CDB	-18~50											
Refrigerant	Type / GWP				R-134a / 1,430											
	Circuits	Quantity			2									3		
Refrigerant charge	Per circuit			kg	73.0	81.0		100.0		125.0			140.0	106.7	113.3	116.7
	Per circuit			TCO_2Eq	104.4	115.8		143.0		178.8			200.2	152.5	162.1	166.8
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm			219.1mm						273mm		
Unit	Maximum starting current			A	365	406	437	485	523	571	606	686	748	817	865	912
	Nominal running current (RLA)	Cooling		A	412	445	493	544	605	641	709	782	851	903	951	989
	Maximum running current			A	507	560	607	668	725	788	841	940	1,038	1,088	1,146	1,204
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400											

Air cooled screw chiller with free cooling, high efficiency, standard/low sound

- Free cooling chiller for space cooling and industrial processes
- Stepless single-screw compressor
- Optimised for use with R-134a
- Greater energy savings and reduced CO_2 emissions during cold season
- Wide operating range
- MicroTech III controller with superior control logic and easy interface

Cooling only				EWAD-CFXS/XL	640	770	850	900	C10	C11	C12	C13	C14	C15	C16
Cooling capacity	Nom.			kW	640 (1)	772 (1)	852 (1)	902 (1)	1,027 (1)	1,089 (1)	1,269 (1)	1,349 (1)	1,435 (1)	1,493 (1)	1,555 (1)
Free cooling capacity	Nom.			kW	415 (2)	510 (2)	583 (2)	612 (2)	701 (2)	734 (2	902 (2)	957 (2)	963 (2)	1,013 (2)	1,039 (2)
Mechanical capacity				kW	225 (2)	262 (2)	269 (2)	290 (2)	325 (2)	355 (2)	366 (2)	392 (2)	472 (2)	480 (2)	517 (2)
Air temperature for free cooling 100%				°C	-0.8	-0.1	1.2	0.4	0.9	0.1	2.9	2.1	1.3	0.7	0.1
Power input	Cooling	Nom.		kW	257 (1) / 53.7 (2)	272 (1) / 62.0 (2)	293 (1) / 64.7 (2)	324 (1) / 69.8 (2)	360 (1) / 75.7 (2)	399 (1) / 83.4 (2)	397 (1) / 86.4 (2)	439 (1) / 92.8 (2)	454 (1) / 101 (2)	492 (1) / 109 (2)	530 (1) / 115 (2)
Capacity control	Method				Stepless										
	Minimum capacity			%	12.5										
EER					2.49 (1) / 11.91 (2)	2.84 (1) / 12.44 (2)	2.90 (1) / 13.17 (2)	2.78 (1) / 12.93 (2)	2.85 (1) / 13.56 (2)	2.73 (1) / 13.05 (2)	3.19 (1) / 14.68 (2)	3.08 (1) / 14.55 (2)	3.16 (1) / 14.21 (2)	3.04 (1) / 13.72 (2)	2.93 (1) / 13.50 (2)
ESEER					3.44	3.52	3.78	3.50	3.74	3.54	3.88	3.78	4.01	3.96	3.85
IPLV					3.86	4.03	4.10	4.05	4.00	3.95	4.36	4.25	4.36	4.35	4.26
Dimensions	Unit	Height		mm	2,565										
		Width		mm	2,480										
		Depth		mm	6,300	7,200	8,100		9,000		10,800				
Weight (XS)	Unit			kg	7,760	8,340	8,900		10,160	10,420	11,900		12,540	12,620	12,670
	Operation weight			kg	8,515	9,100	9,705		11,169	11,429	13,276		14,516	14,596	14,646
Weight (XL)	Unit			kg	8,050	8,620	9,190		10,450	10,710	12,190		12,830	12,910	12,960
	Operation weight			kg	8,795	9,390	9,995		11,459	11,719	13,566		14,806	14,886	14,936
Water heat exchanger	Type				Single pass shell & tube										
	Water volume			l	741	771	808		1,012		1,372		1,965		
	Water flow rate	Cooling	Nom.	l/s	27.8 (1) / 27.8 (2)	33.5 (1) / 33.5 (2)	37.0 (1) / 37.0 (2)	39.2 (1) / 39.2 (2)	44.6 (1) / 44.6 (2)	47.3 (1) / 47.3 (2)	55.1 (1) / 55.1 (2)	58.6 (1) / 58.6 (2)	62.4 (1) / 62.4 (2)	64.9 (1) / 64.9 (2)	67.6 (1) / 67.6 (2)
	Water pressure drop	Cooling	Nom.	kPa	85 (1) / 128 (2)	105 (1) / 172 (2)	90 (1) / 178 (2)	101 (1) / 198 (2)	111 (1) / 245 (2)	124 (1) / 272 (2)	98 (1) / 232 (2)	110 (1) / 259 (2)	139 (1) / 305 (2)	150 (1) / 328 (2)	162 (1) / 354 (2)
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler										
Compressor	Type				Asymmetric single screw compressor										
	Quantity				2										
Fan	Type				Direct propeller										
	Quantity				10	12	14		16		20				
	Air flow rate	Nom.		l/s	50,368	60,441	70,515		80,588		95,253				
	Speed			rpm	920										
Sound power level (XS)	Cooling	Nom.		dBA	100		101			102		103			
Sound power level (XL)	Cooling	Nom.		dBA	96	97			98		99				
Sound pressure level (XS)	Cooling	Nom.		dBA	79	80				81	80				
Sound pressure level (XL)	Cooling	Nom.		dBA	76	77									
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15										
	Air side	Cooling	Min.~Max.	°CDB	-20~45										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			2										
Refrigerant charge	Per circuit			kg	64.0	73.0	81.0		91.0		107.0		112.5	124.0	
	Per circuit			TCO_2Eq	91.5	104.4	115.8		130.1		153.0		160.9	177.3	
Piping connections	Evaporator water inlet/outlet (OD)				DN150PN16(168.3mm)				DN200PN16(219.1mm)				DN250PN16(273mm)		
Unit	Maximum starting current			A	605	619	658		924	971	1,030			1,073	1,086
	Nominal running current (RLA)	Cooling		A	404	430	467	515	568	628	636	701	720	773	825
	Maximum running current			A	476	510	561	605	672	731	811	875		929	982
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

(1) Cooling: entering evaporator water temp. 16°C; leaving evaporator water temp. 10°C; ambient air temp. 35°C; full load operation. (2) Data is calculated at ambient air temperature 5°C, inlet water temperature 16°C.

Air cooled screw chiller with free cooling, high efficiency, reduced sound



EWAD-CFXS/XL/XR

MicroTech III

Cooling only				EWAD-CFXR	600	740	820	870	980	C10	C11	C12	C13	C14	C15
Cooling capacity	Nom.			kW	602 (1)	739 (1)	821 (1)	866 (1)	981 (1)	1,034 (1)	1,229 (1)	1,302 (1)	1,374 (1)	1,424 (1)	1,476 (1)
Free cooling capacity	Nom.			kW	374 (2)	468 (2)	539 (2)	562 (2)	644 (2)	670 (2)	825 (2)	866 (2)	889 (2)	909 (2)	929 (2)
Mechanical capacity				kW	228 (2)	271 (2)	282 (2)	304 (2)	337 (2)	364 (2)	404 (2)	435 (2)	486 (2)	515 (2)	547 (2)
Air temperature for free cooling 100%				°C	-2.3	-1.9	-0.6	-1.5	-0.9	-1.7	0.7	-0.2	-1.1	-1.6	-2.3
Power input	Cooling	Nom.		kW	263 (1) / 46.6 (2)	278 (1) / 56.2 (2)	299 (1) / 58.5 (2)	334 (1) / 63.1 (2)	368 (1) / 68.5 (2)	412 (1) / 74.4 (2)	403 (1) / 80.0 (2)	450 (1) / 87.5 (2)	466 (1) / 93.4 (2)	511 (1) / 103 (2)	556 (1) / 109 (2)
Capacity control	Method				Stepless										
	Minimum capacity			%	12.5										
EER					2.29 (1) / 12.91 (2)	2.66 (1) / 13.17 (2)	2.75 (1) / 14.04 (2)	2.59 (1) / 13.71 (2)	2.67 (1) / 14.33 (2)	2.51 (1) / 13.89 (2)	3.05 (1) / 15.36 (2)	2.90 (1) / 14.87 (2)	2.95 (1) / 14.7(2)	2.79 (1) / 13.85 (2)	2.66 (1) / 13.56 (2)
ESEER					3.59	3.66	3.89	3.62	3.83	3.63	4.13	3.89	4.09	4.02	3.92
IPLV					4.09	4.15	4.16	4.20	4.10	4.08	4.42	4.37	4.42		4.28
Dimensions	Unit	Height		mm	2,565										
		Width		mm	2,480										
		Depth		mm	6,300	7,200	8,100		9,000		10,800				
Weight	Unit			kg	8,050	8,620	9,190		10,450	10,710	12,190		12,830	12,910	12,960
	Operation weight			kg	8,795	9,390	9,995		11,459	11,719	13,566		14,806	14,886	14,936
Water heat exchanger	Type				Single pass shell & tube										
	Water volume			l	741	771	808		1,012		1,372		1,965		
	Water flow rate	Cooling	Nom.	l/s	26.2 (1) / 26.2 (2)	32.1 (1) / 32.1 (2)	35.7 (1) / 35.7 (2)	37.6 (1) / 37.6 (2)	42.6 (1) / 42.6 (2)	44.9 (1) / 44.9 (2)	53.4 (1) / 53.4 (2)	56.6 (1) / 56.6 (2)	59.7 (1) / 59.7 (2)	61.9 (1) / 61.9 (2)	64.1 (1) / 64.1 (2)
	Water pressure drop	Cooling	Nom.	kPa	76 (1) / 115 (2)	97 (1) / 159 (2)	84 (1) / 167 (2)	93 (1) / 184 (2)	102 (1) / 225 (2)	113 (1) / 248 (2)	92 (1) / 219 (2)	103 (1) / 243 (2)	128 (1) / 282 (2)	137 (1) / 301 (2)	146 (1) / 321 (2)
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler										
Compressor	Type				Asymm single screw										
	Quantity				2										
Fan	Type				Direct propeller										
	Quantity				10	12	14		16		20				
	Air flow rate	Nom.		l/s	38,935	46,722	54,508		62,295		73,011				
	Speed			rpm	715										
Sound power level	Cooling	Nom.		dBA	92				94			95			
Sound pressure level	Cooling	Nom.		dBA	71	72				73	72			73	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15										
	Air side	Cooling	Min.~Max.	°CDB	-20~45										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			2										
Refrigerant charge	Per circuit			kg	64.0	73.0	81.0		91.0		107.0		112.5	124.0	
	Per circuit			TCO_2Eq	91.5	104.4	115.8		130.1		153.0		160.9	177.3	
Piping connections	Evaporator water inlet/outlet (OD)				DN150PN16(168.3mm)				DN200PN16(219.1mm)				DN250PN16(273mm)		
Unit	Maximum starting current			A	598	611	648		912	960	1,016			1,059	1,072
	Nominal running current (RLA)	Cooling		A	411	439	473	526	580	647	645	717	738	800	862
	Maximum running current			A	462	493	542	585	649	708	783	847		901	954
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

(1) Cooling: entering evaporator water temp. 16°C; leaving evaporator water temp. 10°C; ambient air temp. 35°C; full load operation. (2) Data is calculated at ambient air temperature 5°C, inlet water temperature 16°C.

Air cooled chiller with inverter driven screw compressor: EWAD-TZ (170-710 kW)



Benefits for the installer

- Easy to install: The EWAD-TZ chiller is set, adjusted and tested in the factory
- Highly serviceable
- User-friendly smart controls which can be integrated easily with building management systems

Benefits for the consultant

- Advanced compressor technology with in-built inverter and Variable Volume Ratio (VVR) and new chiller controller software
- Multiple options available, e.g. rapid restart, variable speed water pumps, smart energy meter, EC fans
- Ideal for both new and retrofit projects: same footprints of non-inverter unit with higher efficiencies and performance


Benefits for the end user

- Rapid payback within 3 years of installation
- 50% reduction of energy consumption
- Designed for sound-sensitive environments

Why choose EWAD-TZ?

With almost 10 years of experience, Daikin is pioneer in inverter applications for air cooled screw chillers. Hundreds and hundreds inverter driven single screw compressors are running on sites to satisfy clients' requests for efficiency to grant the lowest running costs.

EWAD-TZ chiller with the new Daikin compressor...



... is demonstrating that we will never stop developing the most advanced technology with highest quality level to offer the best chiller experience to our customers.

Marketing tools

› Video
https://www.youtube.com/watch?v=QQCYajRWZFQ

› Mini-site
http://www.daikineurope.com/minisite/process-cooling-comfort-cooling-chiller-EWAD-TZ

› Selection software
http://extranet.daikineurope.com/en/software/downloads/default.jsp







High efficiencies both at full load and part load: EER up to 3.57 and ESEER up to 5.73

› New Daikin compressor with in-built inverter and Variable Volume Ratio (VVR) for an optimized efficiency
› New in-house chiller controller software with dynamic condensing pressure management and innovative economizer control logic

Rapid return on investment

› 3 years ROI compared to a non-inverter unit for comfort cooling application
› 1 year ROI for process cooling



Perfect comfort level

› Infinitely variable load regulation
› Precise leaving water temperature control thanks to stepless regulation

Compact design

› More compact heat exchanger with superior efficiencies
› Reduced electrical panel dimensions thanks to the inverter compressor mounted

Lowest sound levels

› Down to 86 dB(A) sound power at full load and even lower at part load thanks to fans and compressors variable speed
› Quiet compressor thanks to special acoustic executions
› Unique Daikin fans design with reduced noise impact and vibrations

Unrivaled and proven reliability

› Extensive testing in laboratories, Daikin factories and specific job sites
› Reduced energy demand without compromising on reliability and performance

Extensive option list

› Rapid restart after power failure
› Variable speed water pumps
› Integrated smart energy meter
› EC fans

Air cooled screw inverter chiller, standard efficiency, standard/reduced sound

- **Optimized energy efficiency both at full and part load conditions**
- Stepless single-screw compressor
- Optimised for use with R-134a
- Advanced compressor technology featuring **integrated inverter** and **variable volume ratio (VVR)**
- Compact design for small footprint and minimized installation space
- Low operating sound levels are achieved by the latest compressor and fan design
- One or two truly independent refrigerant circuits for outstanding reliability

Cooling only				**EWAD-TZSS/SR**	**170**	**205**	**235**	**270**	**320**	**365**	**370**	**415**	**465**	**500**	**540**	**590**	**640**	**710**
Cooling capacity	Nom.			kW	170	205	229	268	317	365	366	412	463	499	536	589	640	710
Power input	Cooling	Nom.		kW	62.2	72.5	79.1	96.0	116	133	134	145	164	178	190	217	235	267
Capacity control	Method				Stepless													
	Minimum capacity			%	33.3	28.6	33.3	28.6	25.0	22.2	15.4	14.3	16.7	15.4	14.3	13.3	12.5	11.1
EER					2.73	2.83	2.90	2.79		2.74		2.85	2.83	2.80	2.82	2.72	2.73	2.66
ESEER					4.48	4.61	4.67	4.64	4.67	4.65	4.61	4.73	4.81	4.82	4.75	4.79	4.75	4.71
IPLV					5.33	5.44	5.90	5.68	5.69	5.67	5.73	5.86		5.83	5.91	5.88	5.95	5.78
Dimensions	Unit	Height		mm	2,270						2,222							
		Width		mm	1,224						2,258							
		Depth		mm	3,461	4,361		5,261		3,218		4,117			5,015			5,917
Weight (SS)	Unit			kg	1,898	1,977	2,083	2,478	2,444	2,756	3,906	4,256	4,426	4,481	4,709	4,892	4,969	5,291
	Operation weight			kg	1,915	2,077	2,183	2,504	2,596	2,806	3,995	4,426	4,590	4,645	4,873	5,162	5,231	5,553
Weight (SR)	Unit			kg	1,996	2,075	2,181	2,576	2,541	2,854	4,101	4,452	4,621	4,676	4,904	5,087	5,164	5,486
	Operation weight			kg	2,013	2,174	2,280	2,602	2,693	2,903	4,190	4,622	4,785	4,840	5,068	5,357	5,426	5,748
Water heat exchanger	Type				Plate heat exchanger						Single pass shell & tube							
	Water volume			l	17	24		26	39	50	89	170	164		270	262		
	Water flow rate	Cooling	Nom.	l/s	8.1	9.8	11.0	12.8	15.1	17.4	17.5	19.7	22.1	23.9	25.6	28.2	30.6	34.0
	Water pressure drop	Cooling	Nom.	kPa	25	24	29	33	26	27	36	50	33	37	43	36	47	57
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler													
Compressor	Type				Inverter driven single screw compressor													
	Quantity				1						2							
Fan	Type				Direct propeller													
	Quantity				3	4		5		6	8			10				12
	Air flow rate	Cooling	Nom.	l/s	12,399	16,532	16,015	20,665	20,019	24,023	33,064		32,030	41,330		40,038		48,046
	Speed	Cooling	Nom.	rpm	700													
Sound power level (SS)	Cooling	Nom.		dBA	96	97	96	97	98	101	99	100	99		100		101	104
Sound power level (SR)	Cooling	Nom.		dBA	89			90		92						93		95
Sound pressure level (SS)	Cooling	Nom.		dBA	77			78		82	80		79	80			81	84
Sound pressure level (SR)	Cooling	Nom.		dBA	70		69	70	71	73	72					73		74
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15													
	Air side	Cooling	Min.~Max.	°CDB	-18~47													
Refrigerant	Type / GWP				R-134a / 1,430													
	Circuits	Quantity			1						2							
Refrigerant charge	Per circuit			kg	29.0	35.0	39.0	46.0	54.0	62.0	31.0	35.0	39.5	42.5	45.5	50.0	54.5	60.5
	Per circuit			TCO_2Eq	41.5	50.1	55.8	65.8	77.2	88.7	44.3	50.1	56.5	60.8	65.1	71.5	77.9	86.5
Piping connections	Evaporator water inlet/outlet (OD)				88.9mm						114.3mm	139.7mm				168.3mm		
Unit	Maximum starting current			A	3													
	Nominal running current (RLA)	Cooling		A	106	123	134	161	194	221	226	245	277	299	319	365	392	441
	Maximum running current			A	121	144	158	187	217	248	262	287	316	342	374	406	434	496
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400													

Air cooled screw inverter chiller, high efficiency, standard/reduced sound



EWAD-TZSS/SR/XS/XR MicroTech III

Cooling only				EWAD-TZXS/XR	180	220	265	290	330	360	380	410	440	490	540	580	630	690
Cooling capacity	Nom.			kW	180	216	265	288	332	360	366	407	441	490	536	577	629	682
Power input	Cooling	Nom.		kW	56.1	68.4	84.6	89.8	106	113	116	128	139	156	169	185	201	216
Capacity control	Method				Stepless													
	Minimum capacity			%	33.3	28.6	30.8	28.6	25.0	23.5	16.7	15.4	14.3	16.7	15.4	14.3	13.3	12.5
EER					3.20	3.16	3.14	3.21	3.14	3.18	3.16	3.17		3.15	3.17	3.12		3.16
ESEER					5.02	5.09	5.10	5.16	5.23		5.02	5.10	5.05	5.02	5.18	5.15	5.12	
IPLV					6.32	6.20	6.33	6.26	6.32	6.37	6.38	6.47	6.39	6.42	6.48	6.44	6.53	6.51
Dimensions	Unit	Height		mm	2,270			2,222										
		Width		mm	1,224			2,258										
		Depth		mm	4,361	5,261		3,218	4,117				5,015			5,917		6,817
Weight (XS)	Unit			kg	2,060	2,304	2,434	2,582	2,986	3,039	4,247	4,321	4,704	4,706	4,882	5,185	5,275	5,588
	Operation weight			kg	2,081	2,404	2,586	2,734	3,035	3,088	4,417	4,479	4,864		5,152	5,455	5,537	5,843
Weight (XR)	Unit			kg	2,158	2,402	2,532	2,679	3,084	3,136	4,442	4,516	4,901		5,077	5,381	5,471	5,783
	Operation weight			kg	2,178	2,502	2,684	2,831	3,133	3,186	4,612	4,674	5,059		5,347	5,651	5,733	6,038
Water heat exchanger	Type				Plate heat exchanger						Single pass shell & tube							
	Water volume			l	20	24	39		50		170	158			270		262	255
	Water flow rate	Cooling	Nom.	l/s	8.6	10.4	12.7	13.8	15.9	17.2	17.5	19.5	21.1	23.5	25.7	27.6	30.1	32.7
	Water pressure drop	Cooling	Nom.	kPa	24	25	19	22	23	26	40	41	48	56	30	34	44	57
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler													
Compressor	Type				Inverter driven single screw compressor													
	Quantity				1						2							
Fan	Type				Direct propeller													
	Quantity				4	5		6	8				10			12		14
	Air flow rate	Nom.		l/s	16,015	20,665	20,019	24,023	33,064	32,030	33,064	32,030	41,330		40,038	49,597	48,046	56,053
	Speed	Cooling	Nom.	rpm	700													
Sound power level (XS)	Cooling	Nom.		dBA	96	97	96	97	98	99			100	99		100		101
Sound power level (XR)	Cooling	Nom.		dBA	89				91	92							93	94
Sound pressure level (XS)	Cooling	Nom.		dBA	77				78	80	79	80		79			80	
Sound pressure level (XR)	Cooling	Nom.		dBA	69	70	69	70	71	72								73
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15													
	Air side	Cooling	Min.~Max.	°CDB	-18~49													
Refrigerant	Type / GWP				R-134a / 1,430													
	Circuits	Quantity			1						2							
Refrigerant charge	Per circuit			kg	31.0	37.0	45.0	49.0	57.0	61.0	31.0	34.5	37.5	42.0	45.5	49.0	53.5	58.0
	Per circuit			TCO_2Eq	44.3	52.9	64.4	70.1	81.5	87.2	44.3	49.3	53.6	60.1	65.1	70.1	76.5	82.9
Piping connections	Evaporator water inlet/outlet (OD)				88.9mm						139.7mm				168.3mm			
Unit	Maximum starting current			A	3													
	Nominal running current (RLA)	Cooling		A	98	118	144	153	182	194	202	220	239	267	289	315	344	368
	Maximum running current			A	124	146	174	190	225	239	247	267	292	321	347	379	411	444
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400													

Air cooled screw inverter chiller, premium efficiency, standard/reduced sound

- **Premium energy efficiency both at full and part load conditions**
- Stepless single-screw compressor
- Optimised for use with R-134a
- Advanced compressor technology featuring **integrated inverter** and **variable volume ratio (VVR)**
- Compact design for small footprint and minimized installation space
- Low operating sound levels are achieved by the latest compressor and fan design
- One or two truly independent refrigerant circuits for outstanding reliability



EWAD-TZPS/PR MicroTech III

Cooling only					EWAD-TZPS/PR	190	225	250	270	295	320	345	380	415	460	505	560	600	645
Cooling capacity	Nom.				kW	185	221	247	271	294	316	339	369	418	452	495	554	598	639
Power input	Cooling	Nom.			kW	52.7	64.9	69.2	77.4	85.1	94.4	102	110	123	134	146	168	183	200
Capacity control	Method					Stepless													
	Minimum capacity				%	33.3	28.6	33.3	30.8	28.6	26.7	18.2	16.7	15.4	14.3	16.7	15.4	14.3	13.3
EER						3.52	3.41	3.57	3.50	3.45	3.35	3.34	3.36	3.38	3.39	3.38	3.30	3.28	3.20
ESEER						5.50	5.45	5.73	5.66	5.65	5.62	5.46	5.47	5.59	5.61	5.67		5.62	5.53
IPLV						6.95	6.70	7.22	7.04	7.08	6.81	6.87	7.03	7.05		7.14	7.13	7.11	6.93
Dimensions	Unit	Height			mm	2,222													
		Width			mm	2,258													
		Depth			mm	3,218		4,117					5,015		5,917			6,817	
Weight (PS)	Unit				kg	2,436	2,565	2,810	2,815	3,026	3,031	4,290	4,517	4,764	5,007	5,241	5,269	5,489	5,591
	Operation weight				kg	2,536	2,591	2,962	2,967	3,076	3,080	4,460	4,687	5,034	5,277	5,511	5,524	5,744	5,838
Weight (PR)	Unit				kg	2,533	2,662	2,908	2,913	3,124	3,128	4,485	4,712	4,960	5,203	5,436	5,465	5,685	5,786
	Operation weight				kg	2,633	2,688	3,060	3,065	3,173	3,178	4,655	4,882	5,230	5,473	5,706	5,720	5,940	6,033
Water heat exchanger	Type					Plate heat exchanger						Single pass shell & tube							
	Water volume				l	24	26	39		50		170		270			255		
	Water flow rate	Cooling	Nom.		l/s	8.9	10.6	11.8	13.0	14.0	15.1	16.2	17.7	20.0	21.6	23.7	26.5	28.7	30.6
	Water pressure drop	Cooling	Nom.		kPa	20	23	18	20	18	21	34	41	30	35	26	39	44	50
Air heat exchanger	Type					High efficiency fin and tube type with integral subcooler													
Compressor	Type					Inverter driven single screw compressor													
	Quantity					1						2							
Fan	Type					Direct propeller													
	Quantity					6		8				10		12				14	
	Air flow rate	Cooling	Nom.		l/s	20,172	19,284	26,896		25,712		33,621	32,140	40,345		38,568		47,069	44,996
	Speed	Cooling	Nom.		rpm	600													
Sound power level (PS)	Cooling	Nom.			dBA	96				97		99						100	
Sound power level (PR)	Cooling	Nom.			dBA	87					88	89		90					
Sound pressure level (PS)	Cooling	Nom.			dBA	77		76		77		79				78	79		
Sound pressure level (PR)	Cooling	Nom.			dBA	67	68	67		68		69							
Operation range	Water side	Cooling	Min.~Max.		°CDB	-8~15													
	Air side	Cooling	Min.~Max.		°CDB	-18~51													
Refrigerant	Type / GWP					R-134a / 1,430													
	Circuits	Quantity				1						2							
Refrigerant charge	Per circuit				kg	32.0	38.0	42.0	46.0	50.0	54.0	29.0	31.5	35.5	38.5	42.0	47.0	51.0	54.5
	Per circuit				TCO_2Eq	45.8	54.3	60.1	65.8	71.5	77.2	41.5	45	50.8	55.1	60.1	67.2	72.9	77.9
Piping connections	Evaporator water inlet/outlet (OD)					88.9mm						139.7mm		168.3mm					
Unit	Maximum starting current				A	3													
	Nominal running current (RLA)	Cooling			A	88	107	115	127	139	156	170	182	204	219	242	274	295	327
	Maximum running current				A	117	137	152	165	179	195	211	232	252	273	302	328	356	388
Power supply	Phase/Frequency/Voltage				Hz/V	3~/50/400													



Air cooled mini inverter heat pump

- Inverter technology to ensure low sound values and **leader-of-class ESEER**
- Wide operating range
- Easy 'plug and play' installation
- Single phase power supply and low starting currents make the unit **ideal for residential applications**
- Built-in hydronic module: no buffer tank required and a standard pump and main switch are included



EWYQ-ADVP

Digital controller

Heating & Cooling					EWYQ-ADVP	EWYQ005ADVP	EWYQ006ADVP	EWYQ007ADVP
Cooling capacity	Nom.				kW	5.28 (1)	6.08 (1)	7.18 (1)
Heating capacity	Nom.				kW	6.02 (2) / 5.57 (3)	6.72 (2) / 6.27 (3)	8.18 (2) / 7.67 (3)
Power input	Cooling	Nom.			kW	1.94 (1)	2.40 (1)	3.00 (1)
	Heating	Nom.			kW	1.65 (2) / 2.02 (3)	1.89 (2) / 2.29 (3)	2.41 (2) / 2.88 (3)
Capacity control	Method					Inverter controlled		
EER						2.72 (1)	2.53 (1)	2.39 (1)
COP						3.65 (2) / 2.76 (3)	3.58 (2) / 2.74 (3)	3.39 (2) / 2.66 (3)
Dimensions	Unit	Height			mm	805		
		Width			mm	1,190		
		Depth			mm	360		
Weight	Unit				kg	100		
	Operation weight				kg	104		
Water heat exchanger	Type					Brazed plate		
	Water flow rate	Cooling	Nom.		l/min	14.9	17.2	20.4
		Heating	Nom.		l/min	17.5	19.5	23.5
Air heat exchanger	Type					Tube type		
Hydraulic components	Expansion vessel	Volume			l	6		
Compressor	Type					Hermetically sealed swing compressor		
	Quantity					1		
Fan	Type					Propeller fan		
	Quantity					1		
Sound power level	Cooling	Nom.			dBA	62		63
Sound pressure level	Cooling	Nom.			dBA	48		50
	Heating	Nom.			dBA	48		49
Operation range	Water side	Cooling	Min.~Max.		°CDB	5~20		
		Heating	Min.~Max.		°CDB	25~50		
	Air side	Cooling	Min.~Max.		°CDB	10~43		
		Heating	Min.~Max.		°CDB	-15~25		
Refrigerant	Type / GWP					R-410A / 2,087.5		
	Control					Inverter		
	Circuits	Quantity				1		
Refrigerant charge	Per circuit				kg	1.7		
	Per circuit				TCO_2Eq	3.5		
Water circuit	Piping connections diameter				inch	1" MBSP		
Piping connections	Water heat exchanger drain					5/16 SAE flare		
Unit	Maximum running current				A	19		
Power supply	Phase/Frequency/Voltage				Hz/V	1~/50/230		

(1) Tamb 35°C - LWE 7°C (DT=5°C) (2) DB/WB 7°C/6°C - LWC 35°C (DT=5°C) (3) DB/WB 7°C/6°C - LWC 45°C (Dt=5°C)

Air cooled mini inverter heat pump

- Inverter technology to ensure low sound values and **leader-of-class ESEER**
- Wide operating range
- Built-in hydronic module: no buffer tank required and a standard pump and main switch are included
- Easy 'plug and play' installation
- Single phase power supply **for residential applications**, three phase power supply model available **for light commercial applications**



EWYQ-ACV3/ACW1



Digital controller

Heating & Cooling				EWYQ-ACV3/EWYQ-ACW1	009ACV3	010ACV3	011ACV3	009ACW1	011ACW1	013ACW1
Cooling capacity	Nom.			kW	12.2 (1) / 8.6 (2)	13.6 (1) / 9.6 (2)	15.7 (1) / 11.1 (2)	12.9 (1) / 9.1 (2)	15.7 (1) / 11.1 (2)	17.0 (1) / 13.3 (2)
Heating capacity	Nom.			kW	10.2 (1) / 9.9 (2)	11.7 (1) / 11.4 (2)	13.8 (1) / 12.9 (2)	11.2 (1) / 10.9 (2)	13.2 (1) / 12.4 (2)	14.8 (1) / 13.9 (2)
Power input	Cooling	Nom.		kW	2.85 (1) / 2.83 (2)	3.41 (1) / 3.28 (2)	4.13 (1) / 3.90 (2)	3.08 (1) / 3.05 (2)	4.13 (1) / 3.90 (2)	5.52 (1) / 5.18 (2)
	Heating	Nom.		kW	2.43 (1) / 2.99 (2)	2.81 (1) / 3.46 (2)	3.20 (1) / 3.94 (2)	2.69 (1) / 3.31 (2)	3.07 (1) / 3.78 (2)	3.47 (1) / 4.27 (2)
Capacity control	Method				Inverter controlled					
EER					4.27 (1) / 3.05 (2)	4.00 (1) / 2.93 (2)	3.79 (1) / 2.85 (2)	4.19 (1) / 2.99 (2)	3.79 (1) / 2.85 (2)	3.08 (1) / 2.57 (2)
ESEER					4.31	4.30	4.33	4.43	4.44	4.36
COP					4.19 (1) / 3.30 (2)	4.17 (1) / 3.29 (2)	4.30 (1) / 3.27 (2)	4.17 (1) / 3.28 (2)	4.31 (1) / 3.27 (2)	4.28 (1) / 3.25 (2)
Dimensions	Unit	Height		mm	1,435					
		Width		mm	1,418					
		Depth		mm	382					
Weight	Unit			kg	180					
Water heat exchanger	Type				Brazed plate					
	Quantity				1					
	Water volume			l	1.01					
	Nominal water flow	Cooling		l/min	24.7	27.6	31.9	26.1	31.9	38.2
		Heating		l/min	28.3	32.6	36.9	31.2	35.5	39.8
Air heat exchanger	Type				Hi-XSS					
Hydraulic components	Expansion vessel	Volume		l	10					
Compressor	Type				Hermetically sealed scroll compressor					
	Quantity				1					
Fan	Type				Propeller fan					
	Quantity				2					
	Air flow rate	Cooling	Nom.	m^3/min	96	100	97	-		
		Heating	Nom.	m^3/min	90			-		
Fan motor	Speed	Cooling	Nom.	rpm	780					
		Heating	Nom.	rpm	760					
		Steps			8					
Sound power level	Cooling	Nom.		dBA	64					66
	Heating	Nom.		dBA	64					
Sound pressure level	Cooling	Nom.		dBA	51					52
	Heating	Nom.		dBA	51					
	Cooling	Night quiet mode		dBA	45					46
	Heating	Night quiet mode		dBA	42					43
Operation range	Water side	Cooling	Min.~Max.	°CDB	5~22					
		Heating	Min.~Max.	°CDB	25~50					
	Air side	Cooling	Min.~Max.	°CDB	10~46					
		Heating	Min.~Max.	°CDB	-15~35					
Refrigerant	Type / GWP				R-410A / 2,087.5					
	Control				Electronic expansion valve					
	Circuits	Quantity			1					
Refrigerant charge	Per circuit			kg	2.95					
	Per circuit			TCO_2Eq	6.2					
Water circuit	Piping connections diameter			inch	G 5/4" (female)					
	Piping			inch	5/4"					
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230			3N~/50/400		

(1) Underfloor program: cooling Ta 35°C - LWE 18°C (Dt: 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (Dt: 5°C) (2) Fan coil program: cooling Ta 35°C - LWE 7°C (Dt: 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (Dt: 5°C)

Air cooled scroll inverter heat pump

- High efficiency with **leader-of-class ESEER**
- Minimal starting currents and short payback times
- No buffertank required for standard applications
- **Large operation range** (ambient temperature up to 43°C)
- A modbus gateway (RTD-W) can be installed per unit in order allow the control and monitoring by a Daikin controller or a third-party BMS, which will increase further the efficiency of the system
- All systems that are connected with RTD-W can be controlled and **monitored centrally** with the master/slave control kit: the sequencing controller EKCC-W



EWYQ-BAWN/BAWP BRC21A52

Heating & Cooling				EWYQ-BAWN/BAWP	016	021	025	032	040	050	064
Cooling capacity	Nom.			kW	17.4 (1) / 16.6 (2)	21.7 (1) / 20.7 (2)	25.8 (1) / 24.7 (2)	32.3 (1) / 30.9 (2)	43.4 (1) / 41.5 (2)	51.8 (1) / 49.7 (2)	64.5 (1) / 62.3 (2)
Heating capacity	Nom.			kW	16.2 (1) / 17.0 (2)	20.3 (1) / 21.3 (2)	24.6 (1) / 25.7 (2)	30.7 (1) / 32.1 (2)	40.6 (1) / 42.5 (2)	49.0 (1) / 51.1 (2)	61.5 (1) / 63.7 (2)
Power input	Cooling	Nom.		kW	5.60 (1) / 5.80 (2)	7.25 (1) / 7.59 (2)	9.29 (1) / 9.74 (2)	13.0 (1) / 13.5 (2)	14.7 (1) / 15.4 (2)	18.8 (1) / 19.7 (2)	26.4 (1) / 27.4 (2)
	Heating	Nom.		kW	5.53 (1) / 5.73 (2)	7.10 (1) / 7.44 (2)	8.91 (1) / 9.36 (2)	10.6 (1) / 11.1 (2)	14.0 (1) / 14.7 (2)	17.6 (1) / 18.5 (2)	20.7 (1) / 21.7 (2)
Capacity control	Method				Inverter controlled						
	Minimum capacity			%	25						
EER					3.11 (1) / 2.86 (2)	2.99 (1) / 2.73 (2)	2.78 (1) / 2.54 (2)	2.48 (1) / 2.29 (2)	2.95 (1) / 2.69 (2)	2.76 (1) / 2.52 (2)	2.44 (1) / 2.27 (2)
ESEER					4.33 (1) / 4.21 (2)	4.08 (1) / 4.18 (2)	3.85 (1) / 4.04 (2)	3.39 (1) / 3.62 (2)	4.19 (1) / 4.24 (2)	3.96 (1) / 4.12 (2)	3.64 (1) / 3.78 (2)
COP					2.93 (1) / 2.97 (2)	2.86 (1) / 2.86 (2)	2.76 (1) / 2.75 (2)	2.90 (1) / 2.89 (2)	2.90 (1) / 2.89 (2)	2.78 (1) / 2.76 (2)	2.97 (1) / 2.94 (2)
Dimensions	Unit	Height		mm	1,684						
		Width		mm	1,371			1,684	2,358		2,980
		Depth		mm	774				780		
Weight	Unit			kg	264	317		397	571		730
	Operation weight			kg	267	320		401	577		738
Water heat exchanger	Type				Brazed plate						
	Water volume			l	1.9			2.9	3.8		5.7
	Water flow rate	Cooling	Nom.	l/min	50	62	74	93	124	148	185
		Heating	Nom.	l/min	46	58	71	88	116	140	176
	Water pressure drop	Cooling	Total	kPa	20	30	42	30		42	30
Air heat exchanger	Type				Hi-XSS						
Compressor	Type				Hermetically sealed scroll compressor						
	Quantity				1	2		3	4		6
Fan	Type				Axial						
	Quantity				1			2			4
	Air flow rate	Cooling	Nom.	m^3/min	171	185		233	370		466
		Heating	Nom.	m^3/min	171	185		233	370		466
Sound power level	Cooling	Nom.		dBA	78			80	81		83
Operation range	Water side	Cooling	Min.~Max.	°CDB	5~20						
		Heating	Min.~Max.	°CDB	25~50						
	Air side	Cooling	Min.~Max.	°CDB	-5~43						
		Heating	Min.~Max.	°CDB	-15~35						
Refrigerant	Type / GWP				R-410A / 2,087.5						
	Control				Electronic expansion valve						
	Circuits	Quantity			1						
Refrigerant charge	Per circuit			kg	7.6			9.6	15.2		19.2
	Per circuit			TCO_2Eq	15.9			20.0	31.7		40.1
Water circuit	Piping connections diameter			inch	1-1/4" (female)				2" (female)		
	Piping			inch	1-1/4"				1-1/2"		
Unit	Maximum starting current			A	0	77.7	78.7	88.7	99.8	101.9	120.7
	Maximum running current			A	22.2	25.3	26.4	35.2	47.4	49.6	67.2
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/400						

(1) EWYQ-BAWN: Naked version (2) EWYQ-BAWP: Verison with pump

Air cooled scroll inverter heat pump, split version

- **Hydronic module for indoor installation** eliminating the need for glycol
- **Ideal for colder climates** as the lack of glycol will allow for high efficiencies
- Compact dimensions and limited pipework allow for **installation in very restricted spaces**
- Easy transportation as separate units will fit in an elevator



SEHVX-AAW+SERHQ-AAW1 BRC21A52

Heating & Cooling					SEHVX20AAW/ SERHQ020AAW1	SEHVX32AAW/ SERHQ032AAW1	SEHVX40AAW/ SERHQ020AAW1+SERHQ020AAW1	SEHVX64AAW/ SERHQ032AAW1+SERHQ032AAW1
Cooling capacity	Nom.			kW	20.7	30.9	41.5	62.3
	Max.			kW	24.7	36.9	49.5	74.3
Heating capacity	Nom.			kW	21.3 (1) / 21.3 (2)	32.1 (1) / 32.1 (2)	42.5 (1) / 42.5 (2)	63.7 (1) / 63.7 (2)
Power input	Cooling	Nom.		kW	7.59	13.5	15.4	27.4
	Heating	Nom.		kW	6.12 (1) / 7.44 (2)	8.72 (1) / 11.1 (2)	12.0 (1) / 14.7 (2)	16.9 (1) / 21.7 (2)
EER					2.73	2.29	2.69	2.27
COP					3.48 (1) / 2.86 (2)	3.68 (1) / 2.89 (2)	3.54 (1) / 2.89 (2)	3.77 (1) / 2.94 (2)

Unit for indoor installation				SEHVX-AAW	SEHVX20AAW	SEHVX32AAW	SEHVX40AAW	SEHVX64AAW
Dimensions	Unit	Height		mm	1,573			
		Width		mm	766			
		Depth		mm	396			
Weight	Unit			kg	60	62	64	66
	Packed unit			kg	70	72	74	76
Sound power level	Nom.			dBA	63		66	
Operation range	Heating	Ambient	Min.~Max.	°C~°CDB	-15~35			
		Water side	Min.~Max.	°C	25~50			
	Indoor installation	Ambient	Min.	°CDB	5			
			Max.	°CDB	35			
	Cooling	Ambient	Min.~Max.	°CDB	-5~43			
		Water side	Min.~Max.	°C	5~20			
Refrigerant	Type / GWP				R-410A / 2,087.5			
	Circuits	Quantity			1			
	Control				Electronic expansion valve			
Water circuit	Piping connections diameter			inch	G 1"1/4 (female)		G 2" (female)	
	Piping			inch	1-1/4"		1-1/2"	
	Water pressure drop	Cooling	Nom.	kPa	176	151	231	141
		Heating	Nom.	kPa	174	149	229	139
	Total water volume			l	3.2	4.2	5.8	7.7
Water side Heat exchanger	Type				Brazed plate			
	Water volume			l	1.9	2.9	3.8	5.7
	Water flow rate	Heating	Nom.	l/min	61	92	122	183
		Cooling	Nom.	l/min	59	89	119	179
Current	Maximum running current	Cooling		A	5.54	5.64	7.24	
		Heating		A	5.54	5.64	7.24	
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/400			

Outdoor Unit				SERHQ-AAW1	SERHQ020AAW1	SERHQ032AAW1
Dimensions	Unit	Height		mm	1,680	
		Width		mm	930	1,240
		Depth		mm	765	
Weight	Unit			kg	240.00	316.00
	Packed unit			kg	273.00	355.95
Compressor	Quantity				2	3
	Type				Hermetically sealed scroll compressor	
Fan	Type				Propeller fan	
	Quantity				1	2
	Air flow rate	Cooling	Nom.	m^3/min	185	233
		Heating	Nom.	m^3/min	185	233

(1) Heating Ta DB/WB 7/6°C - LWC 35°C (DT=5°C) (2) Heating Ta DB/WB 7/6°C - LWC 45°C

Air cooled multi-scroll heat pump, high efficiency, standard/low sound

- **Class A efficiency in heating mode**
- Extended operation range: ambient temperatures from -10°C up to +46°C in cooling mode and down to -17°C in heating mode
- 2 truly independent refrigerant circuits
- Reduced footprint thanks to the **V-shaped frame** (EWYQ160-230F-XS/XL & EWYQ160-220F-XR)
- Reliable and efficient scroll compressors with **high EER values**
- Chiller series design entirely based on new European directives (EN14511, EN14825)
- Top serviceability level thanks to reduced weight, compact footprint and optimized components accessibility
- The unit can be equipped with a hydraulic module optimizing installation time, space and cost
- Wide range of available options and accessories
- Inverter fans management for enhanced part load efficiencies
- Nordic kit option to improve the chiller working conditions in heating mode
- MicroTech III controller with superior control logic and easy interface

Heating & Cooling				**EWYQ-F-XS/XL**	**160**	**190**	**210**	**230**	**310**	**340**	**380**	**400**	**430**	**510**	**570**	**630**
Cooling capacity	Nom.			kW	164	184	205	231	304	335	376	401	427	502	565	624
Heating capacity	Nom.			kW	173	197	227	254	329	362	404	429	463	535	607	674
Power input	Cooling	Nom.		kW	57.6	63.3	70.3	79.3	102	114	129	138	145	172	195	214
	Heating	Nom.		kW	54.0	61.6	70.5	79.2	101	113	126	133	140	167	190	210
Capacity control	Method				Step											
	Minimum capacity			%	25.0									17.0		
EER					2.84	2.91	2.92		2.99	2.93	2.91	2.90	2.94	2.92	2.90	2.91
ESEER					3.73	3.89	3.81	3.71	4.07	4.19	3.99	3.96	4.14	4.20	3.98	4.06
COP					3.20		3.22	3.21	3.24	3.21		3.23	3.30	3.21	3.20	3.21
SCOP					2.78	2.85	2.81	2.80	2.87	2.89		2.84	2.90	2.83	2.82	2.84
IPLV					4.45	4.47	4.55	4.38	4.56	4.61	4.38	4.50	4.70	4.71	4.56	4.74
Dimensions	Unit	Height		mm	2,270				2,220							
		Width		mm	1,200				2,258							
		Depth		mm	4,370		5,270		4,125			5,025		5,925		6,825
Weight (XS)	Unit			kg	1,430	1,850	2,300	2,350	2,900	2,910	2,920	3,730	3,750	4,250	4,280	4,670
	Operation weight			kg	1,470	1,890	2,340	2,390	2,980	2,990	3,000	3,840	3,850	4,370	4,400	4,780
Weight (XL)	Unit			kg	1,520	1,940	2,400	2,440	3,060	3,070	3,080	3,890	3,900	4,400	4,440	4,820
	Operation weight			kg	1,570	1,980	2,440	2,480	3,130	3,150	3,160	3,990	4,010	4,520	4,550	4,940
Water heat exchanger	Type				Plate heat exchanger											
	Water volume			l	18				44			60		70		
	Water flow rate	Cooling	Nom.	l/s	7.8	8.8	9.8	11.1	14.6	16.0	18.0	19.2	20.4	24.0	27.1	29.9
		Heating	Nom.	l/s	8.3	9.5	10.9	12.2	15.9	17.5	19.5	20.7	22.3	25.8	29.3	32.5
	Water pressure drop	Cooling	Nom.	kPa	22	28	36	40	21	27	30	29	34	37	42	56
		Heating	Nom.	kPa	25	32	43	50	25	31	37	33	40	43	50	66
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler											
Compressor	Type				Scroll compressor											
	Quantity				4									6		
Fan	Type				Direct propeller											
	Quantity				4		5		8			10		12		14
	Air flow rate	Nom.		l/s	22,577	21,593	26,992		43,187			55,213	53,983	64,780		75,577
	Speed			rpm	900											
Sound power level (XS)	Cooling	Nom.		dBA	92	94	95		97		98	99			100	
Sound power level (XL)	Cooling	Nom.		dBA	89	92	93		95			96		97		98
Sound pressure level (XS)	Cooling	Nom.		dBA	72	74	75	76	77		78		79			80
Sound pressure level (XL)	Cooling	Nom.		dBA	70	73		74	75				76	77		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~15											
		Heating	Min.~Max.	°CDB	25~50											
	Air side	Cooling	Min.~Max.	°CDB	-10~46											
		Heating	Min.~Max.	°CDB	-17~20											
Refrigerant	Type / GWP				R-410A / 2,087.5											
	Circuits	Quantity			2											
Refrigerant charge	Per circuit			kg	16.0	20.0		24.0	35.0	36.0	35.0	46.0		55.0	52.5	68.0
	Per circuit			TCO_2Eq	33.4	41.8		50.1	73.1	75.2	73.1	96.0		114.8	109.6	142.0
Piping connections	Evaporator water inlet/outlet (OD)				2.5"				3"							
Unit	Maximum starting current			A	282	536	353	560	600	516	637	659	666	648	787	827
	Nominal running current (RLA)	Cooling		A	115	140	128	162	193	205	235	251	257	307	353	384
	Maximum running current			A	138	165	164	196	246	264	295	316	330	396	442	491
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400											

Air cooled multi-scroll heat pump, high efficiency, reduced sound



EWYQ-F-XS/XL/XR



MicroTech III

Heating & Cooling				EWYQ-F-XR	160	180	200	220	300	330	360	390	420	490	550	610
Cooling capacity	Nom.			kW	158	178	199	223	296	326	363	389	415	487	546	606
Heating capacity	Nom.			kW	173	197	227	254	329	362	404	429	463	535	607	674
Power input	Cooling	Nom.		kW	56.2	62.3	68.4	77.9	97.4	111	127	134	141	167	191	210
	Heating	Nom.		kW	54.0	61.6	70.5	79.2	101	113	126	133	140	167	190	210
Capacity control	Method				Step											
	Minimum capacity			%	25.0									17.0		
EER					2.81	2.86	2.92	2.87	3.04	2.93	2.86	2.90	2.93	2.91	2.85	2.89
ESEER					4.33	4.39	4.38	4.19	4.63	4.68	4.37	4.44	4.60	4.83	4.50	4.62
COP					3.20		3.22	3.21	3.24	3.21		3.23	3.30	3.21	3.20	3.21
SCOP					2.78	2.85	2.81	2.80	2.87	2.89		2.84	2.90	2.83	2.82	2.84
IPLV					5.11	5.18	5.22	4.96	5.25	5.35	4.97	5.08	5.25	5.54	5.13	5.36
Dimensions	Unit	Height		mm	2,270				2,220							
		Width		mm	1,200				2,258							
		Depth		mm	4,370		5,270		4,125			5,025		5,925		6,825
Weight	Unit			kg	1,520	1,940	2,400	2,440	3,060	3,070	3,080	3,890	3,900	4,400	4,440	4,820
	Operation weight			kg	1,570	1,980	2,440	2,480	3,130	3,150	3,160	3,990	4,010	4,520	4,550	4,940
Water heat exchanger	Type				Plate heat exchanger											
	Water volume			l	18				44			60		70		
	Water flow rate	Cooling	Nom.	l/s	7.5	8.5	9.6	10.7	14.2	15.6	17.4	18.6	19.8	23.3	26.1	29.0
		Heating	Nom.	l/s	8.3	9.5	10.9	12.2	15.9	17.5	19.5	20.7	22.3	25.8	29.3	32.5
	Water pressure drop	Cooling	Nom.	kPa	20	26	34	38	20	25	28	27	32	35	39	53
		Heating	Nom.	kPa	25	32	43	50	25	31	37	33	40	43	50	66
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler											
Compressor	Type				Scroll compressor											
	Quantity				4									6		
Fan	Type				Direct propeller											
	Quantity				4		5		8			10		12		14
	Air flow rate	Nom.		l/s	17,380	16,564	20,706		33,129			42,431	41,411	49,693		57,975
	Speed			rpm	700											
Sound power level	Cooling	Nom.		dBA	83	84	86		88		89	90		92		
Sound pressure level	Cooling	Nom.		dBA	64	65	66	67	69			70		71		
Operation range	Water side	Cooling	Min.~Max.	°CDB	-13~15											
		Heating	Min.~Max.	°CDB	25~50											
	Air side	Cooling	Min.~Max.	°CDB	-10~46											
		Heating	Min.~Max.	°CDB	-17~20											
Refrigerant	Type / GWP				R-410A / 2,087.5											
	Circuits	Quantity			2											
Refrigerant charge	Per circuit			kg	16.0	18.0	20.0	24.0	35.0	36.0	35.0	46.0		55.0		68.0
	Per circuit			TCO_2Eq	33.4	37.6	41.8	50.1	73.1	75.2	73.1	96.0		114.8		142.0
Piping connections	Evaporator water inlet/outlet (OD)				2.5"				3"							
Unit	Maximum starting current			A	276	530	346	553	589	505	626	645	652	631	770	807
	Nominal running current (RLA)	Cooling		A	114	138	126	160	187	201	232	245	252	301	350	379
	Maximum running current			A	133	160	157	189	235	253	283	302	316	379	425	471
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400											

Air cooled multi-scroll inverter heat pump, high efficiency, standard sound

- High efficiency **DC inverter scroll** compressors
- Advanced compressor and fan design resulting in low operating sound levels
- Dual independent refrigerant circuit for built-in redundancy and reliable operation
- Reduced footprint thanks to the **V-shaped frame** (EWYQ190GZXS/XR)
- Wide operating range in both heating and cooling mode
- MicroTech III controller with superior control logic and easy interface

Heating & Cooling				EWYQ-GZXS	190	260	310	330	380
Cooling capacity	Nom.			kW	193	261	310	327	380
Heating capacity	Nom.			kW	182	246	289	314	362
Power input	Cooling	Nom.		kW	72.2	93.8	122	116	143
	Heating	Nom.		kW	70.5	93.1	115	119	142
Capacity control	Method				Stepless				
	Minimum capacity			%	14.4	14.3	14.9	14.3	14.8
EER					2.67	2.78	2.55	2.81	2.65
ESEER					4.74	4.77	4.86	4.71	4.69
COP					2.57	2.65	2.52	2.63	2.56
SCOP					2.62	2.59	2.57	2.68	2.65
IPLV					5.03	5.18	5.29	5.10	5.14
Dimensions	Unit	Height		mm	2,270	2,223			
		Width		mm	1,290	2,234			
		Depth		mm	4,450	3,560		4,460	
Weight	Unit			kg	1,650	2,200	2,250	2,500	2,600
	Operation weight			kg	1,727	2,333	2,397	2,675	2,788
Water heat exchanger	Type				Plate heat exchanger				
	Water volume			l	29	61	75	79	92
	Water flow rate	Cooling	Nom.	l/s	9.2	12.5	14.8	15.6	18.1
		Heating	Nom.	l/s	8.8	11.9	14.0	15.2	17.5
	Water pressure drop	Cooling	Nom.	kPa	26	14	15	16	18
		Heating	Nom.	kPa	22	11	13	14	18
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler				
Compressor	Type				DC Inverter Scroll				
	Quantity				6	8	10		12
Fan	Type				Direct propeller				
	Quantity				4	6		8	
	Air flow rate	Nom.		l/s	17,473	26,209		34,946	
	Speed			rpm	920				
Sound power level	Cooling	Nom.		dBA	93	94		96	
Sound pressure level	Cooling	Nom.		dBA	76	78			79
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~20				
		Heating	Min.~Max.	°CDB	25~50				
	Air side	Cooling	Min.~Max.	°CDB	-18~43				
		Heating	Min.~Max.	°CDB	-10~20				
Refrigerant	Type / GWP				R-410A / 2,087.5				
	Circuits	Quantity			1	2			
Refrigerant charge	Per circuit			kg	48.0	36.0		48.0	
	Per circuit			TCO_2Eq	100.2	75.2		100.2	
Piping connections	Evaporator water inlet/outlet (OD)				2.5"	4.5"			
Unit	Maximum starting current			A	2				
	Nominal running current (RLA)	Cooling		A	114	155	195	188	226
	Maximum running current			A	155	236	281	286	309
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400				

Air cooled multi-scroll inverter heat pump, high efficiency, reduced sound



EWYQ-GZXS/XR MicroTech III

Heating & Cooling				EWYQ-GZXR	190	260	300	320	370
Cooling capacity	Nom.			kW	188	256	302	321	371
Heating capacity	Nom.			kW	182	246	289	314	362
Power input	Cooling	Nom.		kW	73.0	94.5	124	117	145
	Heating	Nom.		kW	70.5	93.1	115	119	142
Capacity control	Method				Stepless				
	Minimum capacity			%	14.4	14.3	14.9	14.3	14.8
EER					2.58	2.71	2.44	2.75	2.56
ESEER					4.77	4.83	4.99	5.00	4.98
COP					2.57	2.65	2.52	2.63	2.56
SCOP					2.62	2.59	2.57	2.68	2.65
IPLV					5.09	5.18		5.20	5.18
Dimensions	Unit	Height		mm	2,270	2,223			
		Width		mm	1,290	2,234			2,241
		Depth		mm	4,450	3,560		4,460	
Weight	Unit			kg	1,668	2,224	2,280	2,530	2,636
	Operation weight			kg	1,795	2,457	2,527	2,805	2,924
Water heat exchanger	Type				Plate heat exchanger				
	Water volume			l	29	61	75	79	92
	Water flow rate	Cooling	Nom.	l/s	9.0	12.2	14.5	15.3	17.7
		Heating	Nom.	l/s	8.8	11.9	14.0	15.2	17.5
	Water pressure drop	Cooling	Nom.	kPa	25	13	14	15	17
		Heating	Nom.	kPa	22	11	13	14	18
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler				
Compressor	Type				DC Inverter Scroll				
	Quantity				6	8	10		12
Fan	Type				Direct propeller				
	Quantity				4	6		8	
	Air flow rate	Nom.		l/s	15,131	22,697		30,263	
	Speed			rpm	715				
Sound power level	Cooling	Nom.		dBA	89	91		92	
Sound pressure level	Cooling	Nom.		dBA	72	74		75	
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~20				
		Heating	Min.~Max.	°CDB	25~50				
	Air side	Cooling	Min.~Max.	°CDB	-18~43				
		Heating	Min.~Max.	°CDB	-10~20				
Refrigerant	Type / GWP				R-410A / 2,087.5				
	Circuits	Quantity			1	2			
Refrigerant charge	Per circuit			kg	48.0	36.0		46.0	48.0
	Per circuit			TCO_2Eq	100.2	75.2		96.0	100.2
Piping connections	Evaporator water inlet/outlet (OD)				2.5"	4.5"			
Unit	Maximum starting current			A	2				
	Nominal running current (RLA)	Cooling		A	115	157	199	190	230
	Maximum running current			A	153	234	279	283	306
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400				

Air cooled screw inverter heat pump, standard efficiency, standard sound

- Optimised for use with R-134a
- Ideal solution **for commercial comfort cooling and/or heating applications**
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side to minimize pressure drops
- Low starting current
- Optimised defrost cycles
- Optimum ESEER values
- Partial and total heat recovery option available
- PID microprocessor control
- Power factor up to 0.95
- 2-3 truly independent refrigerant circuits

Heating & Cooling				**EWYD-BZSS**	**250**	**270**	**290**	**320**	**340**	**370**	**380**	**410**	**440**	**460**	**510**	**520**	**580**
Cooling capacity	Nom.			kW	253	272	291	323	337	363	380	411	433	455	502	519	580
Heating capacity	Nom.			kW	271	298	325	334	350	380	412	445	465	477	533	561	618
Power input	Cooling	Nom.		kW	91.3	101	110	117	125	135	144	154	165	163	182	189	218
	Heating	Nom.		kW	91.4	100	108	118	126	133	143	157	167	165	178	186	208
Capacity control	Method				Stepless												
	Minimum capacity			%	13.0									9.0			
EER					2.77	2.70	2.65	2.75	2.69	2.68	2.63	2.66	2.62	2.79	2.76	2.74	2.67
ESEER					3.93	3.92	3.89	3.95	3.89	3.90	3.82	3.91	3.89	4.18	4.01		3.93
COP					2.96	2.97	3.00	2.82	2.78	2.85	2.88	2.83	2.79	2.88	2.99	3.01	2.97
IPLV					4.58	4.62		4.75	4.64	4.71	4.67	4.73	4.69	4.85	4.89	4.85	4.78
Dimensions	Unit	Height		mm	2,335									2,280			
		Width		mm	2,254												
		Depth		mm	3,547			4,428				5,329		6,659			
Weight	Unit			kg	3,410	3,455	3,500	3,870		3,940	4,010	4,390		5,015	5,495	5,735	
	Operation weight			kg	3,550	3,595	3,640	4,010		4,068	4,138	4,518		5,255	5,724	5,964	5,953
Water heat exchanger	Type				Single pass shell & tube												
	Water volume			l	138			133		128				240	229		218
	Water flow rate	Cooling	Nom.	l/s	12.1	13.0	13.9	15.5	16.2	17.4	18.2	19.7	20.8	21.8	24.1	24.9	27.8
		Heating	Nom.	l/s	13.1	14.4	15.7	16.1	16.9	18.3	19.8	21.4	22.4	23.0	25.6	27.0	29.7
	Water pressure drop	Cooling	Nom.	kPa	40	46	44	50	55	60	65	74	80	47	85	91	61
		Heating	Nom.	kPa	30	35	52	37	40	45	51	59	64	42	63	69	59
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler												
Compressor	Type				Single screw compressor												
	Quantity				2									3			
Fan	Type				Direct propeller												
	Quantity				6			8				10		12			
	Air flow rate	Nom.		l/s	31,729	31,422	31,115	42,306		42,337	41,487	52,882		63,458	62,640	61,652	62,231
	Speed			rpm	900												
Sound power level	Cooling	Nom.		dBA	101							102		104			
Sound pressure level	Cooling	Nom.		dBA	82							83		84			
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15												
		Heating	Min.~Max.	°CDB	35~55												
	Air side	Cooling	Min.~Max.	°CDB	-10~45												
		Heating	Min.~Max.	°CDB	-10~20												
Refrigerant	Type / GWP				R-134a / 1,430												
	Circuits	Quantity			2									3			
Refrigerant charge	Per circuit			kg	43.0	44.0	43.0	46.0		46.5	47.0	50.0		47.0			49.0
	Per circuit			TCO_2Eq	61.5	62.9	61.5	65.8		66.5	67.2	71.5		67.2			70.1
Piping connections	Evaporator water inlet/outlet (OD)				139.7mm									219.1mm			
Unit	Maximum starting current			A	150			181		204		224	238	245	300	323	
	Nominal running current (RLA)	Cooling		A	137	150	164	176	188	202	214	229	244	246	270	281	322
	Maximum running current			A	211		212	254		288		316	336	329	398	432	
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400												

Air cooled screw inverter heat pump, standard efficiency, low sound



EWYD-BZSS/SL MicroTech II

Heating & Cooling				EWYD-BZSL	250	270	290	320	330	360	370	400	430	450	490	510	570
Cooling capacity	Nom.			kW	247	265	290	315	330	353	370	401	423	446	490	507	565
Heating capacity	Nom.			kW	271	298	325	334	350	380	412	445	465	477	533	561	618
Power input	Cooling	Nom.		kW	89.5	99.5	110	115	123	134	144	151	163	158	177	186	216
	Heating	Nom.		kW	91.4	100	108	118	126	133	143	157	167	165	178	186	208
Capacity control	Method				Stepless												
	Minimum capacity			%	13.0									9.0			
EER					2.76	2.66	2.62	2.75	2.68	2.64	2.57	2.66	2.59	2.83	2.77	2.73	2.61
ESEER					4.06	4.04	4.03	4.17	4.09	4.04	4.01	4.06	4.02	4.18	4.16	4.10	3.98
COP					2.96	2.97	3.00	2.82	2.78	2.85	2.88	2.83	2.79	2.88	2.99	3.01	2.97
IPLV					4.90	4.96	4.91	5.17	5.08	5.12	5.06	5.22	5.13	5.07	5.03	4.99	4.90
Dimensions	Unit	Height		mm	2,335									2,280			
		Width		mm	2,254												
		Depth		mm	3,547			4,428				5,329		6,659			
Weight	Unit			kg	3,750	3,795	3,840	4,210		4,280	4,350	4,730		5,525	6,005	6,245	
	Operation weight			kg	3,888	3,933	3,978	4,343		4,408	4,478	4,858		5,765	6,234	6,474	6,463
Water heat exchanger	Type				Single pass shell & tube												
	Water volume			l	138			133		128				240	229		218
	Water flow rate	Cooling	Nom.	l/s	11.8	12.7	13.9	15.1	15.8	16.9	17.7	19.2	20.3	21.4	23.5	24.3	27.1
		Heating	Nom.	l/s	13.1	14.4	15.7	16.1	16.9	18.3	19.8	21.4	22.4	23.0	25.6	27.0	29.7
	Water pressure drop	Cooling	Nom.	kPa	38	44	42	48	53	57	62	71	77	45	82	87	58
		Heating	Nom.	kPa	30	35	52	37	40	45	51	59	64	42	63	69	59
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler												
Compressor	Type				Single screw compressor												
	Quantity				2									3			
Fan	Type				Direct propeller												
	Quantity				6			8				10		12			
	Air flow rate	Cooling	Nom.	l/s	24,432	24,264	24,095	32,576		32,628	32,127	40,720		48,863	48,415	47,732	48,191
	Speed	Cooling	Nom.	rpm	700												
Sound power level	Cooling	Nom.		dBA	94			95						97			
Sound pressure level	Cooling	Nom.		dBA	76									77			
Operation range	Water side	Cooling	Min.~Max.	°CDB	-8~15												
		Heating	Min.~Max.	°CDB	35~55												
	Air side	Cooling	Min.~Max.	°CDB	-10~45												
		Heating	Min.~Max.	°CDB	-10~20												
Refrigerant	Type / GWP				R-134a / 1,430												
	Circuits	Quantity			2									3			
Refrigerant charge	Per circuit			kg	43.0	44.0	43.0	46.0		46.5	47.0	50.0		47.0			49.0
	Per circuit			TCO_2Eq	61.5	62.9	61.5	65.8		66.5	67.2	71.5		67.2			70.1
Piping connections	Evaporator water inlet/outlet (OD)				139.7mm									219.1mm			
Unit	Maximum starting current			A	145	146		176		199		217	231	234	288	311	305
	Nominal running current (RLA)	Cooling		A	134	148	163	171	184	199	212	224	240	238	263	275	319
	Maximum running current			A	202	203		243		277		302	322	313	381	415	406
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400												

Air cooled screw condensing unit, standard efficiency, standard sound

› One refrigerant circuit with single screw compressor
› Compact design
› Large operation range (ambient temperature down to -18°C)
› Extensive option list (heat recovery option available)

Cooling only				ERAD-E-SS	120	140	170	200	220	250	310	370	440	490
Cooling capacity	Nom.			kW	121	144	165	196	219	251	309	370	435	488
Power input	Cooling	Nom.		kW	42.1	51.2	57.7	65.6	74.2	77.0	93.8	123	148	161
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0									
EER					2.88	2.82	2.86	2.99	2.95	3.27	3.30	3.02	2.95	3.02
Dimensions	Unit	Height		mm	2,273						2,223			
		Width		mm	1,292						2,236			
		Depth		mm	2,165		3,065		3,965		3,070			
Weight	Unit			kg	1,584		1,741		1,936		2,679			
	Operation weight			kg	1,617		1,781		1,981		2,756			
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler									
Compressor	Type				Single screw compressor									
	Quantity				1									
Fan	Type				Direct propeller									
	Air flow rate	Nom.		l/s	10,924	10,576	16,386	15,865	21,848	21,153	32,772		31,729	
	Quantity				2		3		4		6			
	Speed	Cooling	Nom.	rpm	900									
Sound power level	Cooling	Nom.		dBA	92				93	94		95		
Sound pressure level	Cooling	Nom.		dBA	74					75				76
Operation range	Saturated suction temp.			°C	-9~12									
	Condenser inlet temp.			°C	-18~48									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1									
Piping connections	Evaporator water inlet/outlet (OD)				76mm							139.7mm		
Unit	Maximum starting current			A	151		195		288		330	410		
	Nominal running current (RLA)	Cooling		A	72	88	98	110	125	129	158	204	244	266
	Maximum running current			A	86	103	119	132	157	164	198	242	284	298
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Air cooled screw condensing unit, standard efficiency, low sound



ERAD-E-SS/SL

MicroTech III

Cooling only				ERAD-E-SL	120	140	160	190	210	240	300	350	410	460
Cooling capacity	Nom.			kW	116	137	159	187	209	243	298	352	409	462
Power input	Cooling	Nom.		kW	42.4	52.5	57.7	66.3	73.9	78.1	91.9	122	150	167
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0									
EER					2.74	2.61	2.75	2.83		3.11	3.24	2.88	2.73	2.76
Dimensions	Unit	Height		mm	2,273						2,223			
		Width		mm	1,292						2,236			
		Depth		mm	2,165		3,065		3,965		3,070			
Weight	Unit			kg	1,684		1,841		2,036		2,789			
	Operation weight			kg	1,717		1,881		2,081		2,886			
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler									
Compressor	Type				Single screw compressor									
	Quantity				1									
Fan	Type				Direct propeller									
	Air flow rate	Nom.		l/s	8,373	8,144	12,560	12,216	16,747	16,288	25,120		24,432	
	Quantity				2		3		4		6			
	Speed	Cooling	Nom.	rpm	700									
Sound power level	Cooling	Nom.		dBA	89		90		91	92				93
Sound pressure level	Cooling	Nom.		dBA	71					73				74
Operation range	Saturated suction temp			°C	-9~12									
	Condenser inlet temp			°C	-18~48									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1									
Piping connections	Evaporator water inlet/outlet (OD)				76mm							139.7mm		
Unit	Maximum starting current			A	151		195		288		330	410		
	Nominal running current (RLA)	Cooling		A	73	90	98	112	125	131	155	204	249	275
	Maximum running current			A	83	100	115	128	151	158	189	234	276	290
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Water cooled screw chiller, standard efficiency, standard sound

- All models are PED pressure vessel approved
- 1 or 2 stepless single-screw compressors
- One or two truly independent refrigerant circuits for outstanding reliability
- Shell and tube heat exchanger
- Optimised for use with **R-410A**
- Standard electronic expansion valve
- Compact design
- Partial heat recovery available
- MicroTech III controller with superior control logic and easy interface

Cooling only				**EWWQ-B-SS**	**380**	**460**	**560**	**640**	**730**	**800**	**860**	**870**	**960**	**C10**	**C11**	**C12**	**C13**	**C14**	**C15**	**C16**	**C17**	**C19**	**C20**
Cooling capacity	Nom.			kW	379	462	560	635	724	793	859	868	956	1,003	1,050	1,181	1,251	1,320	1,452	1,595	1,754	1,896	2,055
Power input	Cooling	Nom.		kW	89.2	109	133	150	170	179	207	199	218	247	243	268	285	303	337	373	407	441	477
Capacity control	Method				Stepless																		
	Minimum capacity			%	12.5					25.0	12.5	25.0		12.5	25.0								
EER					4.24		4.21	4.22	4.25	4.42	4.15	4.36	4.38	4.07	4.32	4.41	4.38	4.35	4.31	4.28	4.31	4.30	4.31
ESEER					4.64	4.69	4.70		4.46	5.08	4.35	5.07	5.03	4.28	5.04	5.05	5.06	5.00	4.66	4.76	4.61	4.63	4.54
IPLV					5.57	5.62		5.63	5.32	5.58	5.15	5.75	5.92	5.08	5.90	5.93		5.85	5.46	5.44	5.34	5.38	5.32
Dimensions	Unit	Height		mm	1,849		2,001		1,848	2,158	1,848	2,158		1,851	2,378	2,455			2,495				
		Width		mm	1,140		1,276		1,314	1,350	1,327	1,350		1,314	1,350								
		Depth		mm	3,373		3,454		3,535	5,020	3,535	5,020		3,535	4,894	5,070			4,892			4,865	
Weight	Unit			kg	1,933	1,967	2,283	2,332	2,407	3,921	2,427	3,949	3,988	2,457	4,344	4,529	4,536	4,607	4,988	4,999	5,053	5,204	5,289
	Operation weight			kg	2,135	2,169	2,543	2,628	2,777	4,422	2,795	4,463	4,496	2,812	4,780	5,186	5,200	5,280	5,602	5,615	5,670	5,881	5,970
Water heat exchanger - evaporator	Type				Single pass shell and tube																		
	Water volume			l	124	118	176	170	274	344	266	344	325	251	325	538			505		495	539	527
	Water flow rate	Nom.		l/s	18.1	22.1	26.8	30.4	34.7	38.0	41.1	41.6	45.8	48.0	50.3	56.5	59.9	63.2	69.5	76.5	84.1	91.0	98.7
	Water pressure drop	Cooling	Nom.	kPa	48	63	44	47	54	53	49	62	58	56	69	45	49	54	59	69	88	97	120
Water heat exchanger - condenser	Type				Single pass shell and tube																		
	Water flow rate	Nom.		l/s	22.4	27.4	33.2	37.7	43.1	23.3	51.3	23.3	28.2	60.1	28.2	34.7	34.8	38.9	43.0	43.4	52.0	52.3	60.9
	Water flow rate 2	Nom.		l/s	-					23.3	-	27.9	28.2	-	33.8	34.7	38.9		43.0	51.3	52.0	60.1	60.9
	Water pressure drop	Cooling	Nom.	kPa	59	63	67	65	16	64	20	64	67	26	67	73		69	16		17		15
	Water pressure drop 2	Cooling	Nom.	kPa	-					64	-	66	67	-	69	73	69		16	19	17	14	15
Compressor	Type				Single screw compressor																		
	Quantity				1					2	1	2		1	2								
Sound power level	Cooling	Nom.		dBA	100	101	102			105	102	105		103	105		107		106		107		108
Sound pressure level	Cooling	Nom.		dBA	82	83	84		83	84	85			86	87				86	87		88	
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-4~10																		
	Condenser	Cooling	Min.~Max.	°CDB	25~45																		
Refrigerant	Type / GWP				R-410A / 2,087.5																		
	Circuits	Quantity			1					2	1	2		1	2								
Refrigerant charge	Per circuit			kg	120.0	100.0	175.0	90.0	80.0	85.0	90.0	45.0	85.0	100.0	160.0	100.0	150.0		130.0		150.0	160.0	130.0
	Per circuit			TCO_2Eq	250.5	208.8	365.3	187.9	167.0	177.4	187.9	93.9	177.4	208.8	334.0	208.8	313.1		271.4		313.1	334.0	271.4
Piping connections	Evaporator water inlet/outlet			mm	152.4		203.2									254							
	Condenser water inlet/outlet			inch	5		6		5						6				5				
Unit	Maximum starting current			A	455				656	599	656	626		656	663		690		902	954		988	
	Nominal running current (RLA)	Cooling		A	149	175	211	237	269	299	329	325	352	391	387	423	449	476	539	596	650	702	755
	Maximum running current			A	179	214	259	294	308	358	372	393	427	434	473	519	553	587	615	679	744	771	830
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400																		

Water cooled screw chiller, high efficiency, standard sound



EWWQ-B-SS/XS MicroTech III

Cooling only				EWWQ-B-XS	420	520	640	730	800	970	C10	C11	C12	C13	C14	C15	C16	C17	C19	C20	C21
Cooling capacity	Nom.			kW	420	513	636	722	798	969	1,033	1,111	1,153	1,265	1,363	1,442	1,580	1,740	1,870	2,025	2,156
Power input	Cooling	Nom.		kW	88.7	107	131	149	166	201	213	239	238	262	281	299	324	361	397	436	474
Capacity control	Method				Stepless																
	Minimum capacity			%	12.5						25.0	12.5	25.0								
EER					4.74	4.79	4.84	4.83	4.81		4.86	4.64	4.85	4.83	4.85	4.83	4.88	4.81	4.71	4.64	4.55
ESEER					5.27	5.29	5.37	5.36	5.30	5.09	5.56	4.99	5.52		5.65	5.61	5.26	5.18	4.98	4.91	4.75
IPLV					6.36		6.45	6.42	6.35	6.06	6.11	5.92	6.06	6.07	6.23	6.19	5.82	5.92	6.03	5.81	5.93
Dimensions	Unit	Height		mm	2,001				2,003	2,001	2,454	2,003	2,454				2,495				
		Width		mm	1,276			1,268	1,314	1,446	1,350	1,446	1,350								
		Depth		mm	3,863			3,878		3,920	5,219	3,919	5,219				4,829			4,865	
Weight	Unit			kg	2,322	2,403	2,464	2,738	2,407	2,427	4,775	2,457	4,831	4,873	4,919	4,969	5,117		5,388	5,408	5,414
	Operation weight			kg	2,594	2,685	2,745	3,158	2,815	3,056	5,431	3,086	5,479	5,512	5,546	5,606	5,794	5,843	6,110	6,118	6,124
Water heat exchanger - evaporator	Type				Single pass shell and tube																
	Water volume			l	220	213	200	334	325	538	587	538	575	563	551		495	484	535	527	
	Water flow rate	Nom.		l/s	20.1	24.6	30.5	34.6	38.2	46.4	49.5	53.2	55.2	60.6	65.3	69.1	75.7	83.5	89.7	97.2	103.6
	Water pressure drop	Cooling	Nom.	kPa	55	68	71	64	57	53		68	64	55	67	74	69	88	90	111	124
Water heat exchanger - condenser	Type				Single pass shell and tube																
	Water flow rate	Nom.		l/s	24.4	29.8	36.8	41.8	46.3	56.2	29.9	64.7	30.2	36.7	37.2	41.8	45.7	46.2	54.4	55.1	63.1
	Water flow rate 2	Nom.		l/s	-						29.9	-	36.6	36.7	41.8		45.7	54.7	54.4	63.0	63.1
	Water pressure drop	Cooling	Nom.	kPa	50	39	42	47	59	64	40	82	36	48	49	46	44	45	60	61	78
	Water pressure drop 2	Cooling	Nom.	kPa	-						40	-	47	48	46		44	60		78	
Compressor	Type				Single screw compressor																
	Quantity				1						2	1	2								
Sound power level	Cooling	Nom.		dBA	101	102	103		102	103	105	104	106		107		106		107	108	
Sound pressure level	Cooling	Nom.		dBA	82	83	84		83	84	86	85	86	87			86	87		88	
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-4~10																
	Condenser	Cooling	Min.~Max.	°CDB	25~45																
Refrigerant	Type / GWP				R-410A / 2,087.5																
	Circuits	Quantity			1						2	1	2								
Refrigerant charge	Per circuit			kg	120.0	130.0	95.0	135.0	110.0	150.0	120.0	130.0	120.0	150.0	120.0	150.0	130.0		150.0		
	Per circuit			TCO_2Eq	250.5	271.4	198.3	281.8	229.6	313.1	250.5	271.4	250.5	313.1	250.5	313.1	271.4		313.1		
Piping connections	Evaporator water inlet/outlet			mm	152.4			203.2		254	203.2	254	203.2				254				
	Condenser water inlet/outlet			inch	8			6			5	6	5		6		8				
Unit	Maximum starting current			A	455				656		626	656	663		690		902	954		988	998
	Nominal running current (RLA)	Cooling		A	149	173	208	235	258	313	346	370	381	417	443	469	511	567	621	678	734
	Maximum running current			A	179	214	259	294	308	372	427	434	473	519	553	587	615	679	744	771	830
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400																

Water cooled scroll chiller

- One of the most **compact units** on the market: 600mmx600mmx600mm
- Standard integrated: main switch, water filter, flow switch, air purge, pressure ports
- Daikin scroll compressor
- Optimised for use with **R-407C**
- Electronic DDC controller
- Low operating sound level
- Low energy consumption
- Extension possible up to 195kW
- Low refrigerant volume
- Easy installation and maintenance
- Stainless steel plate heat exchanger
- Remote cooling or heating selection
- Water/water heat pump, with water reversibility
- Compatible with hydraulic module EHMC (see next page)
- µC^{2}SE controller featuring top-of-the-range performance and user friendliness




EWWP014-035KBW1N µC^{2}SE

Heating only & Cooling only				EWWP-KBW1N	014	022	028	035	045	055	065	090	100	110	120	130	145	155	165	175	185	195
Cooling capacity	Nom.			kW	12.9	21.4	27.8	32.3	42.8	55.7	64.7	85.7	98.6	112	121	130	141	154	167	176	185	194
Heating capacity	Nom.			kW	16.7	27.5	35.6	41.5	55.0	71.7	83.0	110	127	143	155	166	182	198	215	226	237	249
Power input	Cooling	Nom.		kW	3.75	6.13	7.85	9.12	12.2	16.0	18.2	24.2	28.0	31.9	34.0	36.2	40.2	43.9	47.7	49.8	52.0	54.1
	Heating	Nom.		kW	3.75	6.13	7.85	9.12	12.2	16.0	18.2	24.2	28.0	31.9	34.0	36.2	40.2	43.9	47.7	49.8	52.0	54.1
Capacity steps number					1				2			4					6					
EER					3.44	3.49	3.54		3.51	3.48	3.55	3.54	3.52	3.51	3.56	3.59	3.51		3.50	3.53	3.56	3.59
COP					4.45	4.49	4.54	4.55	4.51	4.48	4.56	4.55	4.54	4.48	4.56	4.59	4.53	4.51		4.54	4.56	4.60
Dimensions	Unit	HeightxWidthxDepth		mm	600x600x600				600x600x1,200			1,200x600x1,200					1,800x600x1,200					
Weight	Unit			kg	118	155	165	172	300	320	334	600	620	640	654	668	920	940	960	974	988	1,002
Water heat exchanger - evaporator	Type				Brazed plate																	
	Minimum water volume in the system			l	62	103	134	155	205	268	311	205	268		311		205		268			311
	Water flow rate	Min.		l/min	31	53	65	76	101	131	152	202	232	262	283	304	333	363	393	414	435	456
		Nom.		l/min	37	61	80	93	123	160	185	246	283	321	347	373	404	441	479	505	530	556
		Max.		l/min	74	123	159	185	245	319	371	491	565	642	694	745	808	883	957	1,009	1,061	1,112
Water heat exchanger - condenser	Type				Brazed plate																	
	Water flow rate	Min.		l/min	24	39	51	59	79	102	118	157	181	205	221	237	260	283	307	323	339	355
		Nom.		l/min	48	78	102	118	157	205	237	314	362	410	442	474	519	567	614	647	679	711
		Max.		l/min	95	157	203	237	314	410	474	629	724	819	883	948	1,038	1,133	1,229	1,293	1,357	1,422
Compressor	Type				Hermetically sealed scroll compressor																	
	Quantity				1				2			4	2	4	2		4		6	4		6
Compressor 2	Quantity				-								2	-	2	-	2		-	2		-
Sound power level	Cooling	Nom.		dBA	64			71	67		74	71			75	77	73			76	78	79
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-10~20																	
	Condenser	Cooling	Min.~Max.	°CDB	20~55																	
Refrigerant	Type / GWP				R-407C / 1,773.9																	
	Control				Thermostatic expansion valve																	
	Circuits	Quantity			1				2			4					6					
Refrigerant charge	Per circuit			kg	1.2	2.0	2.5	3.1	2.3		2.8	2.3			2.6	2.8	2.3			2.5	2.6	2.8
	Per circuit			TCO_2Eq	2.1	3.5	4.4	5.5	3.5		5.0	4.0			4.6	5.0	4.1			4.4	3.5	5.0
Piping connections	Evaporator water inlet/outlet (OD)				FBSP 25mm				FBSP 40mm			2 x 2 x FBSP 38mm					3 x 2 x FBSP 38mm					
	Evaporator water drain				Field installation																	
	Condenser water inlet/outlet (OD)				FBSP 25mm				FBSP 40mm			2 x 2 x FBSP 38mm					3 x 2 x FBSP 38mm					
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/400																	

EWWP-KBW1N

Water cooled scroll chiller

Combination table




Selection table		1 Module (KB-series)							2 Modules (KB-series)					3 Modules (KB-series)					
Capacity index		**014**	**022**	**028**	**035**	**045**	**055**	**065**	**090**	**100**	**110**	**120**	**130**	**145**	**155**	**165**	**175**	**185**	**195**
Cooling capacity (kW)		**12.9**	**21.4**	**27.8**	**32.3**	**42.8**	**55.7**	**64.7**	**85.7**	**98.6**	**112**	**121**	**130**	**141**	**154**	**167**	**176**	**185**	**194**
Heating capacity (kW)		**16.7**	**27.5**	**35.6**	**41.5**	**55.0**	**71.7**	**83.0**	**110**	**127**	**143**	**155**	**166**	**182**	**198**	**215**	**226**	**237**	**249**
Unit + Control (Factory mounted)	EWWP014KBW1N	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	EWWP022KBW1N	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	EWWP028KBW1N	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	EWWP035KBW1N	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	EWWP045KBW1N	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-
	EWWP055KBW1N	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-
	EWWP065KBW1N	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-
Modular units (Controller available as accessory)	EWWP045KAW1M	-	-	-	-	-	-	-	2	1	-	-	-	2	1	-	-	-	-
	EWWP055KAW1M	-	-	-	-	-	-	-	-	1	2	1	-	1	2	3	2	1	-
	EWWP065KAW1M	-	-	-	-	-	-	-	-	-	-	1	2	-	-	-	1	2	3
Control (Kit)	ECB2MUW	-	-	-	-	-	-	-	1	1	1	1	1	-	-	-	-	-	-
	ECB3MUW	-	-	-	-	-	-	-	-	-	-	-	-	1	1	1	1	1	1

For example: for a 121 kW HP system, select : EWWP055KBW1N + EWWP065KBW1N

EHMC

Hydraulic Module

- Accessory for EWWP-KBW1N chillers
- 3 models available
- 100 l tank for all sizes
- Freeze up protection
- High static pump (option)
- Standard drain kit (for indoor use)
- Standard dual pressure ports (before & behind the pump)



Legends

Pump characteristics

1. EHMC30AV1080
2. EHMC10AV1080 & EHMC15AV1080
3. EHMC30AV1010
4. EHMC10AV1010 & EHMC15AV1010

Hydraulic module + filter pressures losses

5. EHMC15/30AV1010 & EHMC15/30AV1080
6. EHMC10AV1010 & EHMC10AV1080



EHMC-AV

EHMC-AV			10		15		30	
			1010	1080	1010	1080	1010	1080
Nominal flow		l/min	62		88		187	
Nominal ESP		mH_2O	17	34	15	27	10	27
Nominal input		W	630	1,050	650	1,070	1,070	2,090
Dimensions (HxWxD)		mm	1,284x635x688		1,284x635x688		1,284x635x688	
Machine weight		kg	99	101	102	104	105	111
Sound power		dBA	63		63		63	
Sound pressure		dBA	52		52		52	
Power supply		V1	1~/230V/50Hz					
Operation range	Water side	°C	-10°C ~ 55°C					
	Air side	°CDB	-10°C ~ 43°C					
Piping connections	Water inlet/outlet		1" BSPF		2" BSPF		2-1/2" BSPF	
	Drain connection		1/2"					

Water cooled screw chiller, standard efficiency, standard sound

- All models are PED pressure vessel approved
- Stepless single-screw compressor
- Optimised for use with **R-134a**
- 1-2 truly independent refrigerant circuits
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side for easy oil circulation and return
- Partial and total heat recovery option available
- MicroTech III controller with superior control logic and easy interface

Heating only & Cooling only				**EWWD-G-SS**	**170**	**210**	**260**	**300**	**320**	**380**	**420**	**460**	**500**	**600**
Cooling capacity	Nom.			kW	165	200	252	279	332	370	401	446	492	554
Heating capacity	Nom.			kW	209	253	319	357	420	467	506	566	626	710
Power input	Cooling	Nom.		kW	43.8	52.6	67.4	78.5	87.5	96.4	105	119	134	157
	Heating	Nom.		kW	43.8	52.6	67.4	78.5	87.5	96.4	105	119	134	157
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0				12.5					
EER					3.77	3.80	3.74	3.55	3.80	3.84	3.80	3.74	3.68	3.53
ESEER					4.50	4.54	4.46	4.25	4.75	4.80	4.76	4.67	4.59	4.44
COP					4.77	4.80	4.74	4.55	4.80	4.84	4.80	4.74	4.68	4.53
IPLV					5.36	5.35	5.30	5.04	5.52	5.55		5.60	5.31	5.16
Dimensions	Unit	Height		mm	1,860				1,880					
		Width		mm	920				860					
		Depth		mm	3,435				4,305					
Weight	Unit			kg	1,393	1,410	1,503		2,687	2,697	2,702	2,757	2,762	
	Operation weight			kg	1,470	1,480	1,650		2,840	2,850	2,860	2,970		
Water heat exchanger - evaporator	Type				Single pass shell and tube									
	Water volume			l	60	56	123		118	113		173	168	
	Water flow rate	Nom.		l/s	7.9	9.6	12.1	13.4	15.9	17.7	19.2	21.4	23.6	26.5
	Water pressure drop	Cooling	Total	kPa	45	61	41	49	58	57	66	50		59
Water heat exchanger - condenser	Type				Single pass shell and tube									
	Water flow rate	Nom.		l/s	10.0	12.1	15.3	17.1	10.1	10.2	12.2	12.4	15.0	17.0
	Water flow rate 2	Nom.		l/s	-				10.1	12.2		14.8	15.0	17.0
	Water pressure drop	Cooling	Nom.	kPa	38	39	60	73	37	38	39	41	57	70
	Water pressure drop 2	Cooling	Nom.	kPa	-				37	39		56	57	70
Compressor	Type				Single screw compressor									
	Quantity				1				2					
Sound power level	Cooling	Nom.		dBA	88				90					
Sound pressure level	Cooling	Nom.		dBA	70				72					
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15									
	Condenser	Cooling	Min.~Max.	°CDB	20~55									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1				2					
Refrigerant charge	Per circuit			kg	60.0				55.0					
	Per circuit			TCO_2Eq	85.8				78.7					
Piping connections	Evaporator water inlet/outlet (OD)				88.9		114.3					139.7mm		
	Condenser water inlet/outlet (OD)				5"									
Unit	Maximum starting current			A	288				380	397		420		438
	Nominal running current (RLA)	Cooling		A	75	85	105	122	149	160	171	190	209	242
	Maximum running current			A	114	136	165	186	229	250	272	301	330	373
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Water cooled screw chiller, high efficiency, standard sound



EWWD-G-SS/XS MicroTech III

Heating only & Cooling only				EWWD-G-XS	190	230	280	320	380	400	460	500	550	650
Cooling capacity	Nom.			kW	185	222	276	306	365	407	443	495	539	602
Heating capacity	Nom.			kW	226	272	337	379	446	496	540	602	657	743
Power input	Heating	Nom.		kW	40.6	49.4	61.0	73.4	81.1	89.0	97.0	107	117	141
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0				12.5					
EER					4.57	4.50	4.53	4.17	4.50	4.58	4.57	4.61	4.59	4.26
ESEER					5.37	5.31	5.33	4.91	5.54	5.62	5.61	5.68	5.67	5.27
COP					5.57	5.50	5.53	5.17	5.50	5.58	5.6	5.61	5.59	5.26
IPLV					6.45	6.36	6.35	5.80	6.47	6.57	6.55	6.65	6.64	6.17
Dimensions	Unit	Height		mm	1,860				1,880					
		Width		mm	920				860					
		Depth		mm	3,435				4,305					
Weight	Unit			kg	1,650	1,665	1,680		2,800	2,945	2,955	2,975	2,990	
	Operation weight			kg	1,800	1,810	1,820		3,020	3,280	3,290	3,315	3,340	
Water heat exchanger - evaporator	Type				Single pass shell and tube									
	Water volume			l	125	120	110		170	285		280		
	Water flow rate	Nom.		l/s	8.9	10.6	13.2	14.6	17.5	19.5	21.2	23.7	25.8	28.8
	Water pressure drop	Cooling	Total	kPa	23	31	30	37	28	21	24	33	39	47
Water heat exchanger - condenser	Type				Single pass shell and tube									
	Water flow rate	Nom.		l/s	10.9	13.1	16.2	18.2	10.7	10.9	13.0	13.2	15.8	17.9
	Water flow rate 2	Nom.		l/s	-				10.7	13.0		15.8		17.9
	Water pressure drop	Cooling	Nom.	kPa	16	18	22	27	15				14	17
	Water pressure drop 2	Cooling	Nom.	kPa	-				15			14		17
Compressor	Type				Single screw compressor									
	Quantity				1				2					
Sound power level	Cooling	Nom.		dBA	88				90					
Sound pressure level	Cooling	Nom.		dBA	70				72					
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15									
	Condenser	Cooling	Min.~Max.	°CDB	20~55									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1				2					
Refrigerant charge	Per circuit			kg	60.0			65.0		60.0	65.0		60.0	
	Per circuit			TCO_2Eq	85.8			93.0		85.8	93.0		85.8	
Piping connections	Evaporator water inlet/outlet (OD)				114.3				139.7	168.3mm				
	Condenser water inlet/outlet (OD)				5"									
Unit	Maximum starting current			A	288				380	397		420		438
	Nominal running current (RLA)	Cooling		A	71	81	96	109	142	152	161	174	186	210
	Maximum running current			A	114	136	165	186	229	250	272	301	330	373
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Water cooled screw chiller, standard efficiency, standard sound

- All models are PED pressure vessel approved
- Stepless single-screw compressor
- Optimised for use with R-134a
- **One, two or three** truly independent **refrigerant circuits**
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side to minimize pressure drops
- Partial and total heat recovery option available
- MicroTech III controller with superior control logic and easy interface

Heating only & Cooling only				EWWD-I-SS	340	400	460	550	650	700	800	850	900	950	C10	C12	C13	C14	C15	C16	C17	C18
Cooling capacity	Nom.			kW	332	392	458	536	637	703	779	841	907	982	1,024	1,151	1,200	1,270	1,341	1,395	1,449	1,503
Heating capacity	Nom.			kW	405	481	562	660	783	863	955	1,032	1,112	1,207	1,267	1,412	1,475	1,560	1,648	1,721	1,793	1,866
Power input	Cooling	Nom.		kW	73.5	88.6	104	124	146	160	176	191	205	225	243	262	275	290	307	325	344	363
	Heating	Nom.		kW	73.5	88.6	104	124	146	160	176	191	205	225	243	262	275	290	307	325	344	363
Capacity control	Method				Stepless																	
	Minimum capacity			%	25.0				12.5							8.3						
EER					4.51	4.43	4.39	4.31	4.37	4.38	4.41	4.40	4.42	4.37	4.22	4.40	4.36	4.38	4.37	4.29	4.21	4.14
ESEER					4.55	4.46	4.44	4.37	4.99	5.18	5.00	5.13	4.92	5.05	4.82	4.96	5.00		4.99	5.00	4.91	4.79
COP					5.51	5.43	5.39	5.31	5.37	5.38	5.41	5.40	5.42	5.37	5.22	5.40	5.36	5.38	5.37	5.29	5.21	5.14
IPLV					5.41	5.28	5.26	5.19	5.83	6.27	5.81	6.16	5.76	5.90	5.64	5.71	5.74	5.76	5.74		5.65	5.45
Dimensions	Unit	Height	mm		1,821				2,103							2,323						
		Width	mm		1,466				1,350							2,130						
		Depth	mm		3,298				4,116							4,439						
Weight	Unit			kg	2,150	2,160	2,179	2,224	3,909	3,927	3,945	3,971	3,996	4,080	4,092	6,079	6,097	6,136	6,174	6,192	6,210	6,228
	Operation weight			kg	2,380	2,396	2,410	2,457	4,217	4,228	4,243	4,262	4,288	4,369	4,386	6,628	6,646	6,670	6,699	6,717	6,735	6,761
Water heat exchanger - evaporator	Type				Single pass shell and tube																	
	Water volume			l	193		183	172	271	263	256	248	241	233		472	504	489	472			
	Water flow rate	Nom.		l/s	15.9	18.8	21.9	25.7	30.5	33.6	37.3	40.3	43.4	47.0	49.0	55.1	57.4	60.8	64.2	66.8	69.4	72.0
	Water pressure drop	Cooling	Nom.	kPa	37	50	54	62	55	44	57	53	44	54	39	52	55	46	57	62	66	71
		Heating	Nom.	kPa	37	50	54	62	55	44	57	53	44	54	39	52	55	46	57	62	66	71
Water heat exchanger - condenser	Type				Single pass shell and tube																	
	Water flow rate	Nom.		l/s	19.5	23.1	27.0	31.7	18.8	19.1	23.0	23.2	26.8	27.2	30.5	22.6		22.9	26.4			29.9
	Water flow rate 2	Nom.		l/s	-				18.8	22.4	23.0	26.5	26.8	30.8	30.5	22.6		26.1	26.4		29.9	
	Water flow rate 3	Nom.		l/s	-											22.6	25.6	26.1	26.4		29.9	
	Water pressure drop	Cooling	Nom.	kPa	26	28	30	26	25		27	28	26	22	23	24		25	24			23
		Heating	Nom.	kPa	26	28	30	26	25	26	27	28	26	23		24		25	24			23
	Water pressure drop 2	Cooling	Nom.	kPa	-				25	26	27	26		23		24		23	24		23	
	Water pressure drop 3	Cooling	Nom.	kPa	-											24	22	23	24	23		
Compressor	Type				Single screw compressor																	
	Quantity				1				2							3						
Sound power level	Cooling	Nom.		dBA	94	97					98	99	100			101			103			
Sound pressure level	Cooling	Nom.		dBA	75	76	78				79	80	81			80	81		83			
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15																	
	Condenser	Cooling	Min.~Max.	°CDB	20~55																	
Refrigerant	Type / GWP				R-134a / 1,430																	
	Circuits	Quantity			1				2							3						
Refrigerant charge	Per circuit			kg	54.0	52.0	60.0	55.0	60.0	75.0	55.0		50.0			52.0	51.7	51.3	51.0	50.7	50.3	58.0
	Per circuit			TCO_2Eq	77.2	74.4	85.8	78.7	85.8	107.3	78.7		71.5			74.4	73.9	73.4	72.9	72.5	72.0	82.9
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm											219.1mm						
	Condenser water inlet/outlet (OD)				5"																	
Unit	Maximum starting current			A	330	464			493	627	650	681		703		836	867	898		920	942	
	Nominal running current (RLA)	Cooling		A	119	145	166	196	236	262	288	310	329	355	382	431	450	470	493	520	547	574
	Maximum running current			A	204	233	271	299	407	436	465	504	542	570	597	698	737	775	814	841	868	896
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400																	

Water cooled screw chiller, high efficiency, standard sound



EWWD-I-SS/XS

MicroTech III

Heating only & Cooling only				EWWD-I-XS	360	440	500	600	750	800	850	950	C10	C11	C12
Cooling capacity	Nom.			kW	360	431	504	570	717	791	863	929	971	1,035	1,130
Heating capacity	Nom.			kW	435	520	608	697	865	995	1,040	1,122	1,180	1,263	1,380
Power input	Cooling	Nom.		kW	74.5	89.5	104	127	148	163	178	193	208	228	250
	Heating	Nom.		kW	74.5	89.5	104	127	148	163	178	193	208	228	250
Capacity control	Method				Stepless										
	Minimum capacity			%	25.0				12.5						
EER					4.83	4.82		4.50	4.85	4.84	4.85	4.81	4.66	4.53	4.51
ESEER					4.81	4.74	4.70	4.60	5.52	5.68	5.41	5.53	5.31	5.45	5.10
COP					5.83	5.82		5.50	5.85	5.84	5.85	5.81	5.66	5.53	5.51
IPLV					5.72	5.63	5.57	5.47	6.45	6.89	6.33	6.63	6.19	6.35	5.97
Dimensions	Unit	Height		mm	1,883				2,245						
		Width		mm	1,430				1,350						
		Depth		mm	4,012				4,782						
Weight	Unit			kg	2,594	2,667	2,704		4,964	4,997	5,049	5,073	5,097	5,132	
	Operation weight			kg	2,998	3,078	3,116		5,582	5,615	5,671	5,695	5,729	5,741	
Water heat exchanger - evaporator	Type				Single pass shell and tube										
	Water volume			l	326	317	308		539		528			504	
	Water flow rate	Nom.		l/s	17.3	20.7	24.1	27.3	34.4	37.9	41.3	44.5	46.6	49.5	54.1
	Water pressure drop	Cooling	Nom.	kPa	64		54	68	58	68	56	64	72	46	52
		Heating	Nom.	kPa	64		54	68	58	68	56	64	72	46	52
Water heat exchanger - condenser	Type				Single pass shell and tube										
	Water flow rate	Nom.		l/s	20.9	25.0	29.2	33.4	20.8	21.0	25.0		28.3		33.1
	Water flow rate 2	Nom.		l/s	-				20.8	24.9	25.0	28.8	28.3	32.3	33.1
	Water pressure drop	Cooling	Nom.	kPa	48	47	51	66	48		47		50	51	65
		Heating	Nom.	kPa	48	47	51	66	48		47	50		65	
	Water pressure drop 2	Cooling	Nom.	kPa	-				48	47		50		65	
Compressor	Type				Single screw compressor										
	Quantity				1				2						
Sound power level	Cooling	Nom.		dBA	94	97					98	99	100		
Sound pressure level	Cooling	Nom.		dBA	75	76	78				79	80	81		
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15										
	Condenser	Cooling	Min.~Max.	°CDB	20~55										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			1				2						
Refrigerant charge	Per circuit			kg	100.0	87.0	130.0	105.0	90.0	88.5	87.0	86.0	85.0		
	Per circuit			TCO_2Eq	143.0	124.4	185.9	150.2	128.7	126.6	124.4	123.0	121.6		
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm				219.1mm						
	Condenser water inlet/outlet (OD)				5"										
Unit	Maximum starting current			A	330	464			493	627	650	681		703	
	Nominal running current (RLA)	Cooling		A	117	144	164	194	235	261	287	307	327	358	388
	Maximum running current			A	204	233	271	299	407	436	465	504	542	570	597
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

Water cooled screw chiller, standard efficiency, standard sound

- Compact design to allow **easy indoor installation or retrofit operations**
- Daikin semi-hermetic single screw stepless compressor
- **High energy efficiency both at full and part load conditions**
- Chilled water temperatures **down to -10°C** on standard unit
- Optimised for use with **R-134a**
- MicroTech III controller with superior control logic and easy interface



EWWD-J-SS



MicroTech III

Heating only & Cooling only				EWWD-J-SS	120	140	150	180	210	250	280	310	330	360	380	400	450	500	530	560
Cooling capacity	Nom.			kW	120	146	154	177	207	255	284	309	333	356	385	415	463	512	540	568
Heating capacity	Nom.			kW	148	180	194	223	258	315	354	388	417	446	486	515	573	631	669	709
Power input	Cooling	Nom.		kW	28.0	34.0	39.5	45.3	50.4	59.9	70.0	78.8	84.6	90.3	101		110	120	130	140
	Heating	Nom.		kW	28.0	34.0	39.5	45.3	50.4	59.9	70.0	78.8	84.6	90.3	101		110	120	130	140
Capacity control	Method				Stepless															
	Minimum capacity			%	25.0							12.5								
EER					4.28	4.29	3.90	3.91	4.11	4.26	4.06	3.92	3.94		3.82	4.12	4.20	4.28	4.16	4.05
ESEER					4.51	4.20		4.28	4.68	4.01		4.32	4.35	4.50	4.31	4.65	4.74	4.83	4.73	4.33
COP					5.28	5.29	4.90	4.91	5.11	5.26	5.06	4.92	4.94		4.82	5.12	5.20	5.28	5.16	5.05
IPLV					5.18	5.06		5.05	5.16	5.70	4.88	5.06	5.13	5.29	5.03	5.48	5.59	5.71	5.55	5.09
Dimensions	Unit	Height		mm	1,020							2,000								
		Width		mm	913															
		Depth		mm	2,684															
Weight	Unit			kg	1,177	1,233	1,334	1,366	1,416	1,600	1,607	2,668	2,700	2,732	2,782	2,832	3,016	3,200	3,207	3,215
	Operation weight			kg	1,211	1,276	1,378	1,415	1,473	1,663	1,675	2,755	2,792	2,830	2,888	2,946	3,136	3,327	3,338	3,350
Water heat exchanger - evaporator	Type				Plate heat exchanger															
	Water volume			l	14	18	14	17	20	26		29	31	33	37	41	46	52		
	Water flow rate	Nom.		l/s	5.7	7.0	7.4	8.5	9.9	12.2	13.6	14.8	15.9	17.0	18.4	19.8	22.1	24.5	25.8	27.2
	Water pressure drop	Cooling	Nom.	kPa	15	14	43	40	35	28	34	43	40		37	35	31	28	31	34
		Heating	Nom.	kPa	15	14	43	40	35	28	34	43	40		37	35	31	28	31	34
Water heat exchanger - condenser	Type				Single pass shell and tube															
	Water flow rate	Nom.		l/s	7.1	8.6	9.3	10.7	12.4	15.2	17.0	9.3		10.7	11.0	12.4		15.2	15.3	17.0
	Water flow rate 2	Nom.		l/s	-							9.3	10.7		12.4		15.2		16.9	17.0
	Water pressure drop	Cooling	Nom.	kPa	19	12		11	16	26		12			11		16		26	
		Heating	Nom.	kPa	19	12		11	16	26		12			11		16		26	
	Water pressure drop 2	Cooling	Nom.	kPa	-							12			11		16		26	
Compressor	Type				Single screw compressor															
	Quantity				1							2								
Sound power level	Cooling	Nom.		dBA	89							94								
Sound pressure level	Cooling	Nom.		dBA	79							82								
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-10~15															
	Condenser	Cooling	Min.~Max.	°CDB	23~60															
Refrigerant	Type / GWP				R-134a / 1,430															
	Circuits	Quantity			1							2								
Refrigerant charge	Per circuit			kg	18.0	35.0	34.0	37.0		38.0		33.0	33.5	34.0	35.0	36.0	37.0	38.0		
	Per circuit			TCO_2Eq	25.7	50.1	48.6	52.9		54.3		47.2	47.9	48.6	50.1	51.5	52.9	54.3		
Piping connections	Evaporator water inlet/outlet			mm	76.2															
	Condenser water inlet/outlet (OD)				2" 1/2	4"														
Unit	Maximum starting current			A	151		195			288		281	293		310		403	422	440	
	Nominal running current (RLA)	Cooling		A	48	57	67	74	83	97	109	134	141	149	157	165	180	195	206	218
	Maximum running current			A	76	97	107	122	143	167	189	215	230	245	265	286	311	335	357	378
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400															

Water cooled screw chiller, high efficiency, standard sound

- High energy efficient units: **full range Eurovent Class A**
- **Heat pump version** available
- **Flooded type heat exchangers**
- MicroTech III controller with superior control logic and easy interface



EWWD-H-XS MicroTech III

Heating only & Cooling only				EWWD-H-XS	370	450	530	610	750	830	930	980	C10	C11	C12
Cooling capacity	Nom.			kW	368	444	520	606	745	825	930	975	1,047	1,130	1,212
Heating capacity	Nom.			kW	432	520	608	709	873	965	1,083	1,141	1,224	1,321	1,416
Power input	Cooling	Nom.		kW	65.2	77.8	89.8	104	130	143	156	168	179	193	207
	Heating	Nom.		kW	64.0	76.7	88.4	103	128	140	154	166	177	191	204
Capacity control	Method				Stepless										
	Minimum capacity			%	25.0				12.5						
EER					5.64	5.70	5.78	5.81	5.74	5.79	5.95	5.80	5.84		5.85
ESEER					5.80	5.82	5.90	5.91	6.44	6.51	6.59	6.63	6.66	6.69	6.68
COP					6.75	6.79	6.88	6.89	6.84	6.87	7.06	6.89	6.93		6.94
IPLV					6.93	6.99	7.09	7.10	7.73	7.81	7.89	7.96	8.00	8.02	
Dimensions	Unit	Height		mm	2,121			2,048					2,161		
		Width		mm	1,353			1,384	1,689				1,711		
		Depth		mm	3,341		3,419	3,417	3,609				3,509		
Weight	Unit			kg	3,089	3,370	3,603	3,781	5,289	5,375	5,654	5,707	6,066	6,105	6,156
	Operation weight			kg	3,250	3,588	3,870	4,163	5,694	5,835	6,174	6,262	6,709	6,773	6,859
Water heat exchanger - evaporator	Type				Single pass shell and tube										
	Water volume			l	78	107	134	160	172	201	261	272	295	310	327
	Water flow rate	Nom.		l/s	17.6	21.2	24.9	29.0	35.7	39.5	44.5	46.7	50.1	54.1	58.0
	Water pressure drop	Cooling	Nom.	kPa	40	33		40	47	38	35	36	33	32	
		Heating	Nom.	kPa	40	33		40	47	38	35	36	33	32	
Water heat exchanger - condenser	Type				Single pass shell and tube										
	Water flow rate	Nom.		l/s	20.8	25.1	29.3	34.2	42.1	46.5	52.2	55.0	59.0	63.7	68.3
	Water pressure drop	Cooling	Nom.	kPa	31	26	28	23	30	28	33	31	29	30	
		Heating	Nom.	kPa	31	26	28	23	30	28	33	31	29	30	
Compressor	Type				Single screw compressor										
	Quantity				1				2						
Sound power level	Cooling	Nom.		dBA	97	98	99		100	101		102		103	
Sound pressure level	Cooling	Nom.		dBA	78	79	80		81	82		83		84	
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15										
	Condenser	Cooling	Min.~Max.	°CDB	18~60										
Refrigerant	Type / GWP				R-134a / 1,430										
	Circuits	Quantity			1										
Refrigerant charge	Per circuit			kg	180.0	210.0	230.0	250.0	270.0				300.0		320.0
	Per circuit			TCO_2Eq	257.4	300.3	328.9	357.5	386.1				429.0		457.6
Piping connections	Evaporator water inlet/outlet			mm	168.3			219.1							
	Condenser water inlet/outlet			inch	6			8							
Unit	Maximum starting current			A	330			464	448	471		492		626	646
	Nominal running current (RLA)	Cooling		A	107	124	141	166	213	231	249	266	283	307	330
	Maximum running current			A	148	176	202	228	296	323	351	378	404	430	456
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400										

Condenserless scroll chiller

- One of the most **compact units** on the market: 600mmx600mmx600mm
- Daikin scroll compressor
- Optimised for use with **R-407C**
- Electronic DDC controller
- Low operating sound level
- Low energy consumption
- Low refrigerant volume
- Easy installation and maintenance
- Stainless steel plate heat exchanger
- Compatible with hydraulic module EHMC
- Standard integrated: main switch, pressure ports, flow switch, filter, shut-off valves and air purge
- µC²SE controller featuring top-of-the-range performance and user friendliness




EWLP012-030KBW1N µC²SE

Cooling only				EWLP-KBW1N	012	020	026	030	040	055	065
Cooling capacity	Nom.			kW	12.1	20.0	26.8	31.2	40.0	53.7	62.4
Power input	Cooling	Nom.		kW	4.2	6.6	8.5	10.1	13.4	17.8	20.3
Capacity steps number					1				2		
EER					2.88	3.03	3.15	3.09	2.99	3.02	3.07
Dimensions	Unit	HeightxWidthxDepth		mm	600x600x600				600x600x1,200		
Weight	Unit			kg	108	141	147	151	252	265	274
Water heat exchanger - evaporator	Minimum water volume in the system			l	62	103	134	155	205	268	311
	Type				Brazed plate						
	Water flow rate	Min.		l/min	31	53	65	76	101	131	152
		Nom.		l/min	35	57	77	89	115	154	179
		Max.		l/min	69	115	154	179	229	308	357
	Model	Quantity			1						
Compressor	Type				Hermetically sealed scroll compressor						
	Quantity				1				2		
Sound power level	Cooling	Nom.		dBA	64			71	67		74
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-10~20						
	Condenser	Cooling	Min.~Max.	°CDB	25~60						
Refrigerant	Type / GWP				R-407C / 1,773.9						
	Control				Thermostatic expansion valve						
	Circuits	Quantity			1				2		
Piping connections	Evaporator water inlet/outlet (OD)				FBSP 25mm				FBSP 40mm		
	Evaporator water drain				Field installation						
Power supply	Phase/Frequency/Voltage			Hz/V	3N~/50/400						

Condenserless screw chiller, standard efficiency, standard sound

- Compact design to allow **easy indoor installation or retrofit operations**
- Daikin semi-hermetic single screw stepless compressor
- **High energy efficiency both at full and part load conditions**
- Chilled water temperatures **down to -10°C** on standard unit
- Optimised for use with **R-134a**
- MicroTech III controller with superior control logic and easy interface



EWLD-J-SS



MicroTech III

Cooling only				EWLD-J-SS	110	130	145	165	235	195	265	290	310	330	360	390	430	470	500	530
Cooling capacity	Nom.			kW	110	128	142	163	236	191	264	285	306	327	355	382	428	473	501	529
Power input	Cooling	Nom.		kW	31.2	38.4	43.8	50.4	66.0	56.0	75.3	87.4	94.0	100	106	111	122	132	141	150
Capacity control	Method				Stepless															
	Minimum capacity			%	25.0							12.5								
EER					3.51	3.33	3.25	3.24	3.58	3.42	3.51	3.26	3.25		3.35	3.43	3.52	3.59	3.55	3.52
Dimensions	Unit	Height		mm	1,020							2,000								
		Width		mm	913															
		Depth		mm	2,684															
Weight	Unit			kg	1,124	1,141	1,237	1,263	1,489	1,305	1,489	2,474	2,500	2,526	2,568	2,611	2,795	2,979		
	Operation weight			kg	1,138	1,159	1,253	1,281	1,518	1,327	1,518	2,505	2,533	2,562	2,608	2,655	2,845	3,036		
Water heat exchanger - evaporator	Type				Plate heat exchanger															
	Water volume			l	14	18	14	17	26	20	26	29	31	33	37	41	46	52		
	Water flow rate	Nom.		l/s	5.2	6.1	6.8	7.8	11.3	9.2	12.6	13.6	14.6	15.6	17.0	18.3	20.5	22.6	24.0	25.3
	Water pressure drop	Cooling	Nom.	kPa	14	13	39	37	26	33	32	39	37		34	33	29	26	29	32
Compressor	Type				Single screw compressor															
	Quantity				1							2								
Sound power level	Cooling	Nom.		dBA	89							94								96
Sound pressure level	Cooling	Nom.		dBA	79							82								83
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-10~15															
	Condenser	Cooling	Min.~Max.	°CDB	25~60															
Refrigerant	Type / GWP				R-134a / 1,430															
	Circuits	Quantity			1							2								
Piping connections	Evaporator water inlet/outlet (OD)				76.2 mm															
Unit	Maximum starting current			A	151		195		288	195	288	281	293		310		403	422	440	
	Nominal running current (RLA)	Cooling		A	52	62	72	81	107	91	120	145	153	162	171	181	197	214	227	241
	Maximum running current			A	76	97	107	122	167	143	189	215	230	245	265	286	311	335	357	378
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400															

Condenserless screw chiller, standard efficiency, standard sound

- Stepless single-screw compressor
- Optimised for use with **R-134a**
- **1-2 truly independent refrigerant circuits**
- Standard electronic expansion valve
- DX shell and tube evaporator – one pass refrigerant side for easy oil circulation and return
- All models are PED pressure vessel approved
- Partial heat recovery available
- MicroTech III controller with superior control logic and easy interface



EWLD-G-SS MicroTech III

Cooling only				EWLD-G-SS	160	190	240	280	320	360	380	420	480	550
Cooling capacity	Nom.			kW	160	188	243	269	315	350	379	426	474	524
Power input	Cooling	Nom.		kW	46.2	55.3	66.9	75.7	92.3	101	110	122	133	151
Capacity control	Method				Stepless									
	Minimum capacity			%	25.0				12.5					
EER					3.47	3.40	3.64	3.55	3.41	3.46	3.43	3.51	3.56	3.48
Dimensions	Unit	Height		mm	1,860				1,880	1,942				
		Width		mm	1,000				1,100					
		Depth		mm	3,700				4,400					
Weight	Unit			kg	1,280		1,398		2,442	2,446		2,501	2,506	
	Operation weight			kg	1,337		1,516		2,560			2,670		
Water heat exchanger - evaporator	Type				Single pass shell and tube									
	Water volume			l	60	56	123		118	113		173	168	
	Water flow rate	Nom.		l/s	7.7	9.0	11.6	12.9	15.1	16.8	18.2	20.4	22.7	25.1
	Water pressure drop	Cooling	Nom.	kPa	42	58	40	49	55	54	63	48	49	59
Compressor	Type				Single screw compressor									
	Quantity				1				2					
Sound power level	Cooling	Nom.		dBA	88				90					
Sound pressure level	Cooling	Nom.		dBA	70				72					
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15									
	Condenser	Cooling	Min.~Max.	°CDB	25~60									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1				2					
Piping connections	Evaporator water inlet/outlet (OD)				88.9mm		114.3mm					139.7mm		
Unit	Maximum starting current			A	288				380	397		420		438
	Nominal running current (RLA)	Cooling		A	79	90	107	120	157	169	181	197	213	240
	Maximum running current			A	114	136	165	186	229	250	272	301	330	373
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400									

Condenserless screw chiller, standard efficiency, standard sound

- DX shell and tube evaporator – one pass refrigerant side for easy oil circulation and return
- Stepless single-screw compressor
- Standard electronic expansion valve
- All models are PED pressure vessel approved
- Optimised for use with R-134a



EWLD-I-SS MicroTech III

Cooling only				EWLD-I-SS	320	400	420	500	600	650	750	800	850	900	950	C10	C11	C12	C13	C14	C15	C16	C17
Cooling capacity	Nom.			kW	315	374	437	509	607	670	740	802	865	935	975	1,029	1,097	1,144	1,210	1,278	1,330	1,381	1,433
Power input	Cooling	Nom.		kW	80.3	96.0	113	134	160	175	192	208	224	246	264	283	286	302	318	336	356	375	395
Capacity control	Method				Stepless																		
	Minimum capacity			%	25.0				12.5							8.3							
EER					3.93	3.89	3.88	3.79	3.80	3.82	3.86			3.81	3.69	3.64	3.83	3.79	3.80		3.74	3.68	3.63
Dimensions	Unit	Height		mm	1,899				2,325							2,415							
		Width		mm	1,464											2,135							
		Depth		mm	3,114				4,391							4,426							
Weight	Unit			kg	1,861		1,869	1,884	3,331	3,339	3,347	3,356	3,364	3,412		5,146	5,167		5,188	5,208			
	Operation weight			kg	2,054		2,052	2,056	3,602		3,603	3,604	3,605	3,645		5,667	5,671		5,677	5,680			
Water heat exchanger - evaporator	Type				Single pass shell and tube																		
	Water volume			l	193		183	172	271	263	256	248	241	233		504		489	472	504		489	472
	Water flow rate	Nom.		l/s	15.1	17.9	20.9	24.4	29.1	32.1	35.4	38.4	41.4	44.8	46.7	49.3	52.5	54.8	57.9	61.2	63.7	66.1	68.6
	Water pressure drop	Cooling	Total	kPa	34	46	49	56	50	40	52	49	40	49	36	54	47	51	43	53	57	61	65
Compressor	Type				Single screw compressor																		
	Quantity				1				2							3							
Sound power level	Cooling	Nom.		dBA	94	97					98	99	100					101		103			
Sound pressure level	Cooling	Nom.		dBA	75	76	78				79	80	81			80		81		83			
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-8~15																		
	Condenser	Cooling	Min.~Max.	°CDB	25~60																		
Refrigerant	Type / GWP				R-134a / 1,430																		
	Circuits	Quantity			1				2							3							
Piping connections	Evaporator water inlet/outlet (OD)				42mm																		
Unit	Maximum starting current			A	330	464			493	627	650	681		703		836		867	898		920	942	
	Nominal running current (RLA)	Cooling		A	131	157	181	214	260	287	313	338	361	391	420	448	470	493	517	542	571	601	631
	Maximum running current			A	204	233	271	299	407	436	465	504	542	570	597	670	698	737	775	814	841	868	896
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400																		

Water cooled centrifugal chiller, high efficiency, standard sound

› Totally oil-free operation resulting in reduced maintenance costs and increased reliability
› An inverter driven compressor allows the capacity to be adjusted precisely to match variations in room and outside temperatures
› Onboard digital electronics provide smart controls



EWWD-FZXS MicroTech II

Cooling only				EWWD-FZXS	320	430	520	640	860	C10
Cooling capacity	Min.			kW	113	133	170	113	133	169
	Max.			kW	316	439	520	639	887	1,054
Power input	Cooling	Min.		kW	20.6	25.5	32.7	20.5	25.5	32.6
		Max.		kW	65.1	90.4	106	129	179	208
Capacity control	Method				Stepless					
EER					4.85	4.86	4.93	4.97	4.95	5.06
ESEER					8.11	8.39	8.66	8.83	8.52	8.88
IPLV					9.25	9.64	9.89	9.50	9.74	10.06
Dimensions	Unit	Height		mm	1,823			1,755	1,748	1,794
		Width		mm	1,276			1,790	1,853	1,904
		Depth		mm	3,254		3,419	3,441	3,289	3,401
Weight	Unit			kg	2,360	2,416	2,546	3,709	4,095	4,765
	Operation weight			kg	2,520	2,634	2,812	4,074	4,548	5,330
Water heat exchanger - evaporator	Type				Flooded shell and tube					
	Water volume			l	78	107	134	184	210	302
	Water flow rate	Nom.		l/s	15.1	21.0	24.9	30.6	42.4	50.4
	Water pressure drop	Cooling	Nom.	kPa	30	32	33	35	33	31
Water heat exchanger - condenser	Type				Flooded shell and tube					
	Water flow rate	Nom.		l/s	18.3	25.5	30.1	36.9	51.3	60.7
	Water pressure drop	Cooling	Nom.	kPa	24	26	29	23	32	29
Compressor	Type				Oil free centrifugal compressor					
	Quantity				1			2		
Sound power level	Cooling	Nom.		dBA	89	90	91	92	94	95
Sound pressure level	Cooling	Nom.		dBA	71	72	73	74	75	76
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	2~15					
	Condenser	Cooling	Min.~Max.	°CDB	18~46					
Refrigerant	Type / GWP				R-134a / 1,430					
	Circuits	Quantity			1					
Refrigerant charge	Per circuit			kg	240.0	220.0	180.0	220.0		300.0
	Per circuit			TCO_2Eq	343.2	314.6	257.4	314.6		429.0
Piping connections	Evaporator water inlet/outlet (OD)				168.3mm		219.1mm			273mm
	Condenser water inlet/outlet (OD)				168.3mm			219.1mm		
Unit	Maximum starting current			A	2					
	Nominal running current (RLA)	Cooling		A	104	142	168	207	285	335
	Maximum running current			A	135	210	176	270	420	352
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400					


Water cooled centrifugal chiller, high efficiency, standard sound

- Optional Variable Frequency Drive (VFD) to improve the part load efficiency
- High efficiency flooded type shell and tube evaporator/ condensers
- Lower equipment, installation and annual operating costs than two single compressor chillers (DWDC)
- Main components can be removed or repaired without shutting down the unit as the chiller has two of everything (compressors, lubrication systems, control systems and starters) (DWDC)
- Unloading to 5% (DWSC) or 10% (DWDC) of full load provides improved stability of the chilled water temperature and less harmful cycling of compressors
- Single stage centrifugal compressor (DWSC)



DWSC-DWDC MicroTech II

Cooling only		DWDC/DWSC	DWDC	DWSC
Cooling capacity	Min.	kW	600	300
	Max.	kW	9,000	4,500
Compressor	Type		Single stage centrifugal compressor	
Refrigerant	Type / GWP		R-134a / 1,430	
	Charge	kg	700 - 1,400	300 - 1,000
	Charge	TCO_2Eq	1,001 - 2,002	429 - 1,430



Fan Coil Units are a highly efficient means of turning a water chiller, heat pump or hot water boiler into an efficient, quiet air conditioning system. These units are an effective solution to provide a comfortable environment for both commercial and residential applications. Daikin offers a wide range of Fan Coil Units for both concealed and exposed applications. Three models are available in flexible application. The only moving part in the units is the fan, making them ideal for use in offices, hotels and at home. The goal is to obtain the right solution, both technically and aesthetically.

Fan coil units

Why choose Daikin fan coil units? 354

Products overview 358

Cassette units

NEW	FWG-AT/AF	360
	FWC-BT/BF	361
	FWF-BT/BF	362
	FWF-CT	363

Floor standing unit

	FWZ-AT/AF	364
	FWV-DAT/DAF	365

Flexi type units

	FWR-AT/AF	366
	FWL-DAT/DAF	367
	FWS-AT/AF	368
	FWM-DAT/DAF	369

Wall mounted unit

	FWT-CT	370

Concealed ceiling units

	FWE-CT/CF	371 low ESP
	FWP-AT	372 medium ESP
	FWB-BT	373 medium ESP
	FWD-AT/AF	374 high ESP

For more information on Options & Accessories, please refer to page 462 of this catalogue.



Fan coil units with BLDC motor

Designed for tomorrow, available today

As more buildings undergo renovation, the need to be able to deliver high indoor air quality in a specific space in an **economic and cost-effective way** without having to do a radical re-fit of the entire HVAC system has made fan coil technology an obvious solution.

Daikin has a full capacity range of **aesthetically pleasing** fan coil units with advanced controls that reliably deliver **excellent comfort levels**. And by using a refined range of advanced DC fan motors, we are able to offer flexibility while maintaining very low noise levels.

Why choose Daikin fan coil units?

- The new brushless DC ranges reflect Daikin's commitment to developing highly efficient fan coil units that help to reduce energy consumption, without compromising on reliability and performance.
- High level quality is written large for us and we are pleased to offer high technology solutions to the market.

Benefits for the installer

› Reduced amount of sizes: less stock space needed
› Modular designs for multiple configurations
› Easy integration in BMS system via modbus protocol*

* except for FWG-AT/AF range

Benefits for the consultant


› Best solution in the market in order to have top efficiency, best comfort and lowest sound levels

Benefits for the end user

› High comfort level
› Up to 70% savings on running costs
› Controller with timer programmed operating mode

Marketing tools

Download the software:
Software Downloads > Sales Software
> Fan Coil Selection







Higher efficiency than AC (Alternative Current) motor

› Up to 70% energy savings
› No heat generation
› No power losses
› Higher efficiency than AC motors to reach set point

High comfort level

› Less fluctuation of air temperature and relative humidity
› More consistent output level
› Stepless speed change for gradual air output
› More accurate adjustments to reach set point

Low sound levels

› Lower minimum rotation speed
› No start-stop sequence
› Gradual air output

High flexibility level

› Multiple configurations: cassettes, floorstanding units, flexi type units with or without cabinet and ducted units
› Wide capacity range in heating and cooling
› Different piping topologies and connection valves



FWG-AT/AF



FWR-AT/AF



FWS-AT/AF



FWC-BT/BF



FWP-AT



FWZ-AT/AF



FWS-AT/AF
FLEXI TYPE UNIT



FWF-BT/BF
CEILING MOUNTED CASSETTE






FWC-BT/BF
CEILING MOUNTED CASSETTE




FWT-CT
WALL MOUNTED UNIT


FWR-AT/AF
FLOOR STANDING UNIT

Product overview

Type	Model	Product name		Capacity
Ceiling mounted cassette	4-way blow ceiling mounted cassette - Brushless DC fan motor unit for ceiling mounting - High efficiency, continuous air flow regulation and fan speed modulation - Reduced sound emissions - Easy installation and maintenance	FWG-AT/AF NEW		Cooling: 5.8~ 8.7 kW Heating: 7.5 ~ 12.1 kW
	Round flow cassette - Brushless DC fan motor unit for ceiling mounting - 360° air discharge ensures uniform air flow - Integrated fresh air intake - Easy installation in corners - Standard drain pump with 850 mm lift	FWC-BT/BF		Cooling: 2.0 - 5.2 kW Heating: 2.9 - 6.7 kW
	4-way blow ceiling mounted cassette - AC fan motor unit for ceiling mounting - Integrated fresh air intake - Horizontal auto swing - Easy installation in corners - Standard drain pump with 750 mm lift	FWF-BT/BF		Cooling: 2.49 - 4.54 kW Heating: 3.52 - 5.28 kW
	4-way blow ceiling mounted cassette - AC fan motor unit for ceiling mounting - Easy installation and maintenance - High power air flow - Standard drain pump with 700 mm lift	FWF-CT		Cooling: 2.64 - 10.08 kW Heating: 2.46 - 11.18 kW
Floor standing unit	Floor standing unit - Brushless DC fan motor for vertical mounting - Continuous air flow regulation and fan speed modulation - Up to 70% energy savings - Low sound levels	FWZ-AT/AF		Cooling: 2.64 - 10.08 kW Heating: 2.46 - 11.18 kW
	Floor standing unit - AC fan motor unit for horizontal or vertical concealed mounting - Insulated valve packages, no extra drain pan required - Fast-on connections for electrical options: no tools needed - Easy maintenance	FWV-DAT/DAF		Cooling: 1.46 -8.02 kW Heating: 1.90 - 10.03 kW
Flexi type unit	Flexi type unit with cabinet - Brushless DC fan motor unit for horizontal or vertical mouting - Continuous air flow regulation and fan speed modulation - Up to 70% energy savings - Low sound levels	FWR-AT/AF		Cooling: 2.64 - 10.08 kW Heating: 2.46- 11.18 kW
	Flexi type unit with cabinet - AC fan motor unit for horizontal or vertical concealed mounting - Insulated valve packages, no extra drain pan required - Fast-on connections for electrical options: no tools needed - Easy maintenance	FWL-DAT/DAF		Cooling: 1.46 - 8.02 kW Heating: 1.90 - 10.03 kW
	Flexi type unit without cabinet - Brushless DC fan motor unit for horizontal or vertical concealed mounting - Continuous air flow regulation and fan speed modulation - Up to 70% energy savings - Low sound levels	FWS-AT/AF		Cooling: 2.64 - 10.08 kW Heating: 2.46 - 11.18 kW
	Flexi type unit without cabinet - AC fan motor unit for horizontal or vertical concealed mounting - Insulated valve packages, no extra drain pan required - Fast-on connections for electrical options: no tools needed - Easy maintenance	FWM-DAT/DAF		Cooling: 1.46 -8.02 kW Heating: 1.90 - 10.03 kW
Wall mounted unit	Wall mounted unit - AC fan motor unit for wall mounting - High aesthetic cabinet design - Optimum air distribution - Easy installation - 3-speed fan motor	FWT-CT		Cooling: 2.43 - 5.28 kW Heating: 3.22 - 7.33 kW
Concealed ceiling unit	Low ESP ducted unit - AC fan motor unit for horizontal concealed mounting - Available static pressure up to 50 Pa - Easy installation and maintenance - 4-speed fan motor - High power air flow	FWE-CT/CF		Cooling: 2.10 - 9.96 kW Heating: 2.3 - 13.00 kW
	Medium ESP ducted unit - Brushless DC fan motor unit for horizontal concealed mounting - Instant adjustment to temperature and relative humidity changes - Available static pressure up to 80 Pa - Low sound levels	FWP-AT		Cooling: 2.61 - 6.47 kW Heating: 5.47 - 12.28 kW
	Medium ESP ducted unit - AC fan motor unit for horizontal concealed mounting - Available static pressure up to 80 Pa - 7-speed electrical motors (thermal protection on windings) - Easy maintenance	FWB-BT		Cooling: 2.61 - 10.34 kW Heating: 5.47 - 18.78 kW
	High ESP ducted unit - AC fan motor unit for horizontal or vertical concealed mounting - Available static pressure up to 120 Pa - Easy maintenance	FWD-AT/AF		Cooling: 3.90 - 18.30 kW Heating: 4.05 - 21.92 kW

Capacity class (kW)

	1	2	3	4	5	6	7	8	9	10	11	12	~	18
					●			●			●			
						●	●	●	●					
		●	●	●	●									
		●	●	●										
		●	●			●		●						
	●	●	●	●			●		●		●			
		●	●			●		●						
	●	●	●	●		●		●		●				
		●	●			●		●						
	●	●	●	●		●		●		●				
		●	●	●	●	●								
		●	●	●		●	●	●		●				
		●	●	●	●	●	●							
		●	●	●	●	●	●	●	●	●				
				●		●		●		●		●		●

4-way blow ceiling mounted cassette

BLDC fan motor unit for ceiling mounting. High efficiency, continuous air flow regulation and fan speed modulation

› Up to 70% **energy savings** with brushless DC motor technology compared to traditional technology
› Instant adjustment to temperature and relative humidity changes
› Continuous modulation of fan speed resulting in **reduced sound emissions**, in comparison with fixed speed AC motor fan coil units
› **Easy installation and maintenance**



FWG-AT/AF






BRC51A61

				FWG-AT/AF	05	08	11	05	08	11
					2-pipe			4-pipe		
Cooling capacity	Total capacity	High	kW		5.90	8.80	11.75	4.40	7.20	9.00
		Medium	kW		4.65	7.25	9.70	3.60	6.10	7.75
		Low	kW		3.50	5.80	7.85	2.80	5.00	6.50
		Quiet	kW		2.40	4.55	6.15	2.00	3.90	5.20
	Sensible capacity	High	kW		4.51	6.43	8.37	3.85	5.75	7.17
		Medium	kW		3.44	5.41	6.97	2.99	4.85	6.06
		Low	kW		2.54	4.26	5.54	2.24	3.81	4.90
		Quiet	kW		1.71	3.22	4.27	1.56	2.91	3.89
Heating capacity	2-Pipe	High	kW		7.10	11.20	13.70		-	
		Low	kW		4.45	7.00	9.25		-	
		Quiet	kW		3.30	5.40	7.05		-	
	4-Pipe	High	kW			-		7.65	11.20	15.65
		Low	kW			-		5.05	8.00	11.45
		Quiet	kW			-		3.75	6.40	9.35
Dimensions	Unit	Height	mm		265		300	265		300
		Width	mm		820					
		Depth	mm		820					
Weight	Unit		kg		26	28	32	26	28	32
Heat exchanger	Water volume		l		1.36	1.97	2.35	1.36	1.97	2.35
Water pressure drop	Cooling	High	kPa		24	20	41	18	19	32
	Heating	High	kPa		21	18	37	22	32	52
Fan	Type				Direct drive turbo fan					
	Air flow rate	High	m^3/h		1,053	1,512	1,801	1,053	1,512	1,801
		Low	m^3/h		595	951	1,155	595	951	1,155
Sound power level	High		dBA		46	57	59	46	57	59
	Quiet		dBA		30	40	43	30	40	43
Sound pressure level	High		dBA		37	47	51	37	47	51
Piping connections	Drain	OD	mm		19.05					
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240					
Control systems	Infrared remote control				included with decoration panel					
	Wired remote control				BRC51A61					


Round flow cassette

BLDC fan motor unit for ceiling mounting. 360° air discharge

- 360° air discharge ensures **uniform air flow** and temperature distribution
- Modern style decoration panel in white (RAL9010)
- **Fresh air intake integrated** in the same system thus reducing installation cost as no additional ventilation is required
- Comfortable horizontal air discharge ensures **draughtfree operation** and prevents ceiling soiling
- Possibility to shut 1 or 2 flaps for **easy installation in corners**



- Standard drain pump with 850mm lift increases flexibility and installation speed






			FWC-BT/BF	06	07	08	09	06	07	08	09
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Super high	kW	5.8	6.8	7.7	8.7	5.8	6.6	7.6	8.7
		High	kW	5.0	5.6	6.3	7.2	4.9	5.6	6.3	7.2
		Low	kW	4.1	4.7	4.9	5.7	4.0	4.6	4.8	5.7
	Sensible capacity	Super high	kW	4.1	4.7	5.6	6.5	4.1	4.7	5.6	6.5
		High	kW	3.4	4.0	4.5	5.3	3.4	3.9	4.4	5.2
		Low	kW	2.8	3.3	3.5	4.1	2.7	3.2	3.4	4.0
Heating capacity	2-Pipe	Super high	kW	8.0	8.9	10.6	12.1	-			
		High	kW	6.3	7.1	8.3	9.5	-			
		Low	kW	5.5	5.9	6.9	7.8	-			
	4-Pipe	Super high	kW	-				7.5	8.4	9.7	11.0
		High	kW	-				6.2	6.8	7.8	8.8
		Low	kW	-				5.5	5.9	6.7	7.8
Power input	Super high		W	45	54	77	107	46	55	77	107
	High		W	40	46	58	76	41	47	59	77
	Low		W	34	37	39	45	35	38	40	46
Dimensions	Unit	Height	mm	288							
		Width	mm	840							
		Depth	mm	840							
Weight	Unit		kg	26				29			
Fan	Type			Turbo fan							
	Quantity			1							
	Air flow rate	High	m^3/h	1,062	1,236	1,518	1,776	1,032	1,200	1,476	1,746
		Low	m^3/h	720	840	888	1,044	684	804	852	1,014
Sound power level	Super high		dBA	43	47	53	57	43	47	53	57
	High		dBA	36	39	44	49	36	39	44	49
Sound pressure level	Super high		dBA	29	33	39	43	29	33	39	43
	High		dBA	24	28	32	37	24	28	32	37
Piping connections	Drain	OD	mm	VP25 (External dia.32 / internal dia. 25)							
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240							
Control systems	Infrared remote control			BRC7E532F / BRC7E533F							
	Wired remote control			BRC315D7							

4-way blow ceiling mounted cassette

AC fan motor unit for ceiling mounting. Possibility to shut 1 or 2 flaps

- Modern style decoration panel in white (RAL9010)
- Compact casing enables unit to fit flush into ceilings and match standard architectural modules
- Comfortable horizontal auto swing ensures **draughtfree operation** and prevents ceiling soiling
- **Fresh air intake integrated** in the same system thus reducing installation cost as no additional ventilation is required
- Standard drain pump with **750mm lift**





FWF-BT/BF



BRC315D7



BRC7E530/531

			FWF-BT/BF	02	03	04	05	02	03	04	05
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Super high	kW	2.0	3.2	4.2	5.2	2.0	2.7	3.5	4.5
		High	kW	1.7	2.8	3.3	4.0	1.7	2.3	2.8	3.5
		Low	kW	1.5	2.5		2.9	1.4	1.8		2.6
	Sensible capacity	Super high	kW	1.5	2.0	2.8	3.5	1.5	1.7	2.4	3.3
		High	kW	1.3	1.7	2.1	2.7	1.3		1.7	2.3
		Low	kW	1.1	1.4		1.8	1.1	1.0		1.5
Heating capacity	2-Pipe	Super high	kW	2.9	4.0	5.4	6.7	-			
		High	kW	2.6	3.4	4.1	5.3	-			
		Low	kW	2.3	2.8		3.6	-			
	4-Pipe	Super high	kW	-				3.9	3.8	4.9	6.1
		High	kW	-				3.1	3.3	3.9	4.8
		Low	kW	-				2.3	2.8		3.5
Power input	Super high		W	74		90	118	74		94	121
	High		W	67		70	89	67	62	74	93
	Low		W	60		55	62	60	55		66
Dimensions	Unit	Height	mm	285							
		Width	mm	575							
		Depth	mm	575							
Weight	Unit		kg	19				20			
Fan	Type			Turbo fan							
	Quantity			1							
	Air flow rate	High	m^3/h	468		660	876	468	438	618	822
		Low	m^3/h	318			420	318	300		390
Sound power level	Super high		dBA	44		50	55	44	46	52	57
	High		dBA	40		44	49	40	42	46	51
Sound pressure level	Super high		dBA	31		40	45	31	33	42	47
	High		dBA	27		33	39	27	29	35	41
Piping connections	Drain	OD	mm	VP20 (External dia.26 / Internal dia. 20)							
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-440							
Control systems	Infrared remote control			BRC7E530 / BRC7E531							
	Wired remote control			BRC315D7							

4-way blow ceiling mounted cassette

AC fan motor unit for ceiling mounting

- 4 way air discharge and air swing
- Compact casing enables unit to fit flush into ceilings and match standard architectural modules
- **Air suction from underneath**
- Easy installation and maintenance
- Built-in high pressure drain pump with **700mm lift**
- Double-intake centrifugal fans
- High power air flow
- 3-speed fan motor



FWF-CT





BRC51A61/A62

				FWF-CT	02	03	04
					2-pipe		
Cooling capacity	Total capacity	High	kW		2.49	4.10	4.54
		Low	kW		1.91	2.78	3.37
	Sensible capacity	High	kW		1.91	2.93	3.37
		Low	kW		1.49	1.88	2.43
Heating capacity	2-Pipe	High	kW		3.52	4.69	5.28
		Low	kW		2.64	3.08	3.81
Power input	High		W		63	64	79
	Low		W		45	52	69
Dimensions	Unit	Height	mm		250		
		Width	mm		570		
		Depth	mm		570		
Weight	Unit		kg		22	23	
	Operation weight		kg		22	23	
Fan	Type				Direct drive turbo fan		
	Quantity				1		
	Air flow rate	High	m^3/h		646	680	748
		Low	m^3/h		391	374	476
Sound power level	High		dBA		52	54	56
Sound pressure level	High		dBA		42	45	48
Piping connections	Drain	OD	mm		19.05		
Water connections	Std. heat exchanger		inch		3/4		
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-440		
Current input	High		A		0.27	0.28	0.34
	Medium		A		0.22	0.25	0.31
	Low		A		0.19	0.22	0.35
Control systems	Infrared remote control				included with decoration panel		
	Wired remote control				MERCA / SRC-HPA		

Floor standing unit

BLDC fan motor unit for vertical mounting. Continuous air flow regulation and fan speed modulation

- Up to 70% **energy savings** with brushless DC motor technology compared to traditional technology
- **Instant adjustment** to temperature and relative humidity changes
- **Low operating sound level**
- Highly flexible solutions: multiple sizes, piping topologies and connection valves
- Requires **very little installation space**



FWZ-AT/AF



FWEC3A

			FWZ-AT/AF	02	03	06	08	02	03	06	08
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Min.	kW	0.61	0.88	1.19	1.79	0.60	0.88	1.19	1.79
		Max.	kW	2.64	4.96	6.32	10.08	2.64	4.96	6.32	10.08
	Sensible capacity	Min.	kW	0.41	0.58	0.79	1.20	0.40	0.58	0.79	1.20
		Max.	kW	1.95	3.60	4.80	7.43	1.95	3.60	4.80	7.43
Heating capacity	2-Pipe	Min.	kW	0.69	0.95	1.29	1.92	-			
		Max.	kW	3.47	6.40	7.51	11.18	-			
	4-Pipe	Min.	kW	-				0.82	1.18	1.76	2.83
		Max.	kW	-				2.46	4.19	6.45	10.06
Power input	Min.		W	2.2		3.4	4.2	2.2		3.24	4.2
	Max.		W	57.4	82.7	101.4	147	57.4	82.7	101.4	147
Dimensions	Unit	Height	mm	564							
		Width	mm	774	987	1,194	1,404	774	987	1,194	1,404
		Depth	mm	226		251		226			251
Weight	Unit		kg	20	25	31	41	21	26	33	44
Heat exchanger	Water volume		l	0.7	1	1.4	2.1	0.7	1	1.4	2.1
Additional heat exchanger	Water volume		l	-				0.2	0.3	0.4	0.6
Water flow	Cooling		l/h	454	853	1,084	1,728	454	853	1,084	1,728
	Heating		l/h	454	853	1,084	1,728	216	367	565	882
Fan	Type			Centrifugal multi-blade, double suction							
	Quantity			1	2			1	2		
	Air flow rate	Max.	m^3/h	560	900	1,200	1,660	560	900	1,200	1,660
		Min.	m^3/h	70	95	130	200	70	95	130	200
Sound power level	Max.		dBA	62	70	64	71	62	70	64	71
Piping connections	Drain	OD	mm	16							
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230							
Current input	Max.		A	0.50	0.72	0.88	1.27	0.50	0.72	0.88	1.27
	Min.		A	0.05		0.07	0.09	0.05		0.07	0.09
Control systems	Wired remote control			FWEC3A							

Floor standing unit

AC fan motor unit for vertical mounting

- **Pre-assembled 3-way/4-port on/off valves** are available
- **High efficiency** heat exchanger
- Valve packages are **insulated**, no extra drain pan required
- Valve packages contain balancing valves and sensor pocket
- Fast-on connections for electrical options: no tools needed
- **Washable air filter,** easily removable for maintenance
- Electric heater: no relay up to 2kW capacity
- Electric heater: equipped with two overheat cut-out thermostats



FWV-DAT/DAF



FWEC1,2,3A / ECFWMB6

			FWV-DAT/DAF	01	15	02	25	03	35	04	06	08	10	01	15	02	25	03	35	04	06	08	10
				2-pipe										4-pipe									
Cooling capacity	Total capacity	High	kW	1.54	1.74	1.96	2.42	2.93	3.51	4.33	4.77	6.71	8.02	1.46	1.69	1.79	2.38	2.87	3.46	4.26	4.67	6.64	7.88
		Low	kW	1.04	1.26	1.36	1.60	1.76	1.98	2.51	3.17	3.97	4.11	0.99	1.24	1.26	1.58	1.73	1.96	2.48	3.11	3.93	4.07
	Sensible capacity	High	kW	1.20	1.30	1.42	1.88	2.11	2.72	3.15	3.65	4.91	5.96	1.14	1.27	1.46	1.85	2.07	2.71	3.09	3.57	4.85	5.85
		Low	kW	0.79	0.95	1.00	1.18	1.26	1.45	1.80	2.32	2.84	3.05	0.75	0.93	0.98	1.17	1.24	1.44	1.78	2.28	2.82	3.02
Heating capacity	2-Pipe	High	kW	2.14	2.20	2.57	3.20	3.81	4.78	5.10	5.95	7.83	10.03	-									
		Low	kW	1.43	1.71	1.79	2.07	2.28	2.81	2.98	3.96	4.77	5.24	-									
	4-Pipe	High	kW	-										1.90	2.02	2.01	2.92	3.08	4.80	5.05	5.30	7.91	8.35
		Low	kW	-										1.50	1.56		2.06	2.18	3.21	3.60	4.04	5.69	5.50
Power input	High		W	37	53		57	56	98			182	244	37	53		57	56	98			182	244
	Low		W	21	25	24	29		37	38	47	86	109	21	25	24	29		37	38	47	86	109
Dimensions	Unit	Height	mm	564																			
		Width	mm	774			987		1,194			1,404		774			987		1,194			1,404	
		Depth	mm	226								251		226								251	
Weight	Unit		kg	19	20		25		30		31	41		20	21		26		32		33	44	
Heat exchanger	Water volume		l	0.5		0.7		1		1.4		2.1		0.5		0.7		1		1.4		2.1	
Additional heat exchanger	Water volume		l	-										0.2			0.3			0.4		0.6	
Water flow	Cooling		l/h	264	298	337	415	504	602	743	818	1,152	1,376	250	291	176	409	494	594	730	803	1,138	1,362
	Heating		l/h	264	298	337	415	504	602	743	818	1,152	1,376	167	177	182	257	270	421	443	465	694	733
Fan	Type			Centrifugal multi-blade, double suction																			
	Quantity			1			2							1			2						
	Air flow rate	High	m^3/h	319	344		442		640	706	785	1,011	1,393	307	330	327	432	431	628	690	763	998	1,362
		Low	m^3/h	178	211		241		320	361	470	570	642	174	205		238		316	356	460	565	636
Sound power level	High		dBA	47	49	50	48		52	53	56	61	67	45	49	50	48	47	51	56	59	60	66
Piping connections	Drain	OD	mm	16																			
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230																			
Current input	High		A	0.17	0.24		0.26	0.25	0.44		0.43	0.82	1.10	0.17	0.24		0.26	0.25	0.44		0.43	0.82	1.10
	Medium		A	0.13	0.16		0.21	0.20	0.29		0.31	0.57	0.76	0.13	0.16		0.21	0.20	0.29		0.31	0.57	0.76
	Low		A	0.10	0.12	0.11	0.14		0.19		0.22	0.39	0.50	0.10	0.12	0.11	0.14		0.19		0.22	0.39	0.50
Control systems	Wired remote control			FWEC1A / FWEC2A / FWEC3A / ECFWM36																			

Flexi type unit with cabinet

BLDC fan motor unit for horizontal or vertical mounting. Continuous air flow regulation and fan speed modulation

- Up to 70% **energy savings** with brushless DC motor technology compared to traditional technology
- **Instant adjustment** to temperature and relative humidity changes
- **Low operating sound level**
- Highly flexible solutions: multiple sizes, piping topologies and connection valves
- Requires very **little installation space**



FWR-AT/AF



FWEC3A

			FWR-AT/AF	02	03	06	08	02	03	06	08
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Min.	kW	0.61	0.88	1.19	1.79	0.60	0.88	1.19	1.79
		Max.	kW	2.64	4.96	6.32	10.08	2.64	4.96	6.32	10.08
	Sensible capacity	Min.	kW	0.41	0.58	0.79	1.20	0.40	0.58	0.79	1.20
		Max.	kW	1.95	3.60	4.80	7.43	1.95	3.60	4.80	7.43
Heating capacity	2-Pipe	Min.	kW	0.69	0.95	1.29	1.92	-			
		Max.	kW	3.47	6.40	7.51	11.18	-			
	4-Pipe	Min.	kW	-				0.82	1.18	1.76	2.83
		Max.	kW	-				2.46	4.19	6.45	10.06
Power input	Min.		W	2.2		3.4	4.2	2.2		3.24	4.2
	Max.		W	57.4	82.7	101.4	147	57.4	82.7	101.4	147
Dimensions	Unit	Height	mm	564							
		Width	mm	774	987	1,194	1,404	774	987	1,194	1,404
		Depth	mm	226			251	226			251
Weight	Unit		kg	21	27	33	44	22	28	35	46
Heat exchanger	Water volume		l	0.7	1	1.4	2.1	0.7	1	1.4	2.1
Additional heat exchanger	Water volume		l	-				0.2	0.3	0.4	0.6
Water flow	Cooling		l/h	454	853	1,084	1,728	454	853	1,084	1,728
	Heating		l/h	454	853	1,084	1,728	216	367	565	882
Fan	Type			Centrifugal multi-blade, double suction							
	Quantity			1	2			1	2		
	Air flow rate	Max.	m^3/h	560	900	1,200	1,660	560	900	1,200	1,660
		Min.	m^3/h	70	95	130	200	70	95	130	200
Sound power level	Max.		dBA	62	70	64	71	62	70	64	71
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230							
Current input	Max.		A	0.50	0.72	0.88	1.27	0.50	0.72	0.88	1.27
	Min.		A	0.05		0.07	0.09	0.05		0.07	0.09
Control systems	Wired remote control			FWEC3A							

Flexi type unit with cabinet

AC fan motor unit for horizontal or vertical mounting

- **Pre-assembled 3-way/4-port on/off valves** are available
- **High efficiency** heat exchanger
- Valve packages are **insulated**, no extra drain pan required
- Valve packages contain balancing valves and sensor pocket
- Fast-on connections for electrical options: no tools needed
- **Washable air filter**, easily removable for maintenance
- Electric heater: no relay up to 2kW capacity
- Electric heater: equipped with two overheat cut-out thermostats



FWL-DAT/DAF



FWEC1,2,3A / ECFWMB6

				FWL-DAT/DAF	01	15	02	25	03	35	04	06	08	10	01	15	02	25	03	35	04	06	08	10
					2-pipe										4-pipe									
Cooling capacity	Total capacity	High	kW		1.54	1.74	1.96	2.42	2.93	3.51	4.33	4.77	6.71	8.02	1.46	1.69	1.79	2.38	2.87	3.46	4.26	4.67	6.64	7.88
		Low	kW		1.04	1.26	1.36	1.60	1.76	1.98	2.51	3.17	3.97	4.11	0.99	1.24	1.26	1.58	1.73	1.96	2.48	3.11	3.93	4.07
	Sensible capacity	High	kW		1.20	1.30	1.42	1.88	2.11	2.72	3.15	3.65	4.91	5.96	1.14	1.27	1.46	1.85	2.07	2.71	3.09	3.57	4.85	5.85
		Low	kW		0.79	0.95	1.00	1.18	1.26	1.45	1.80	2.32	2.84	3.05	0.75	0.93	0.98	1.17	1.24	1.44	1.78	2.28	2.82	3.02
Heating capacity	2-Pipe	High	kW		2.14	2.20	2.57	3.20	3.81	4.78	5.10	5.95	7.83	10.03	-									
		Low	kW		1.43	1.71	1.79	2.07	2.28	2.81	2.98	3.96	4.77	5.24	-									
	4-Pipe	High	kW		-										1.90	2.02	2.01	2.92	3.08	4.80	5.05	5.30	7.91	8.35
		Low	kW		-										1.50	1.56		2.06	2.18	3.21	3.60	4.04	5.69	5.50
Power input	High		W		37	53		57	56	98			182	244	37	53		57	56	98			182	244
	Low		W		21	25	24	29		37	38	47	86	109	21	25	24	29		37	38	47	86	109
Dimensions	Unit	Height	mm		564																			
		Width	mm		774			987		1,194			1,404		774			987		1,194			1,404		
		Depth	mm		226								251		226								251	
Weight	Unit		kg		20	21		27		32		33	44		21	22		28		24	34	35	46	
Heat exchanger	Water volume		l		0.5		0.7		1		1.4		2.1		0.5		0.7		1		1.4		2.1	
Additional heat exchanger	Water volume		l		-										0.2			0.3		0.4			0.6	
Water flow	Cooling		l/h		264	298	337	415	504	602	743	818	1,152	1,376	250	291	176	409	494	594	730	803	1,138	1,362
	Heating		l/h		264	298	337	415	504	602	743	818	1,152	1,376	167	177	182	257	270	421	443	465	694	733
Fan	Type				Centrifugal multi-blade, double suction																			
	Quantity				1			2							1			2						
	Air flow rate	High	m^3/h		319	344		442		640	706	785	1,011	1,393	307	330	327	432	431	628	690	763	998	1,362
		Low	m^3/h		178	211		241		320	361	470	570	642	174	205		238		316	356	460	565	636
Sound power level	High		dBA		47	49	50	48		52	53	56	61	67	45	49	50	48	47	51	56	59	60	66
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/230																			
Current input	High		A		0.17	0.24		0.26	0.25	0.44		0.43	0.82	1.10	0.17	0.24		0.26	0.25	0.44		0.43	0.82	1.10
	Medium		A		0.13	0.16		0.21	0.20	0.29		0.31	0.57	0.76	0.13	0.16		0.21	0.20	0.29		0.31	0.57	0.76
	Low		A		0.10	0.12	0.11	0.14		0.19		0.22	0.39	0.50	0.10	0.12	0.11	0.14		0.19		0.22	0.39	0.50
Control systems	Wired remote control				FWEC1A / FWEC2A / FWEC3A / ECFWMB6																			

Flexi type unit without cabinet

BLDC fan motor unit for horizontal or vertical concealed mounting. Continuous air flow regulation and fan speed modulation

- **Blends unobtrusively** with any interior décor: only the suction and discharge grilles are visible
- Up to 70% **energy savings** with brushless DC motor technology compared to traditional technology
- **Instant adjustment** to temperature and relative humidity changes
- **Low operating sound level**
- Highly flexible solutions: multiple sizes, piping topologies and connection valves



FWS-AT/AF



FWEC3A

			FWS-AT/AF	02	03	06	08	02	03	06	08
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Min.	kW	0.61	0.88	1.19	1.79	0.60	0.88	1.19	1.79
		Max.	kW	2.64	4.96	6.32	10.08	2.64	4.96	6.32	10.08
	Sensible capacity	Min.	kW	0.41	0.58	0.79	1.20	0.40	0.58	0.79	1.20
		Max.	kW	1.95	3.60	4.80	7.43	1.95	3.60	4.80	7.43
Heating capacity	2-Pipe	Min.	kW	0.69	0.95	1.29	1.92	-			
		Max.	kW	3.47	6.40	7.51	11.18	-			
	4-Pipe	Min.	kW	-				0.82	1.18	1.76	2.83
		Max.	kW	-				2.46	4.19	6.45	10.06
Power input	Min.		W	2.2		3.4	4.2	2.2		3.24	4.2
	Max.		W	57.4	82.7	101.4	147	57.4	82.7	101.4	147
Dimensions	Unit	Height	mm	535							
		Width	mm	584	794	1,004	1,214	584	794	1,004	1,214
		Depth	mm	224		249		224			249
Weight	Unit		kg	15	19	23	32	16	20	25	34
Heat exchanger	Water volume		l	0.7	1	1.4	2.1	0.7	1	1.4	2.1
Additional heat exchanger	Water volume		l	-				0.2	0.3	0.4	0.6
Water flow	Cooling		l/h	454	853	1,084	1,728	454	853	1,084	1,728
	Heating		l/h	454	853	1,084	1,728	216	367	565	882
Fan	Type			Centrifugal multi-blade, double suction							
	Quantity			1	2			1	2		
	Air flow rate	Max.	m^3/h	560	900	1,200	1,660	560	900	1,200	1,660
		Min.	m^3/h	70	95	130	200	70	95	130	200
Sound power level	Max.		dBA	62	70	64	71	62	70	64	71
Piping connections	Drain	OD	mm	17							
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230							
Current input	Max.		A	0.50	0.72	0.88	1.27	0.50	0.72	0.88	1.27
	Min.		A	0.05		0.07	0.09	0.05		0.07	0.09
Control systems	Wired remote control			FWEC3A							

Flexi type unit without cabinet

AC fan motor unit for horizontal or vertical concealed mounting

- **Pre-assembled 3-way/4-port on/off valves** are available
- **High efficiency** heat exchanger
- Valve packages are **insulated**, no extra drain pan required
- Valve packages contain balancing valves and sensor pocket
- Fast-on connections for electrical options: no tools needed
- **Washable air filter,** easily removable for maintenance
- Electric heater: no relay up to 2kW capacity
- Electric heater: equipped with two overheat cut-out thermostats



FWM-DAT/DAF



FWEC1,2,3A

			FWM-DAT/DAF	01	15	02	25	03	35	04	06	08	10	01	15	02	25	03	35	04	06	08	10
				2-pipe										4-pipe									
Cooling capacity	Total capacity	High	kW	1.54	1.74	1.96	2.42	2.93	3.51	4.33	4.77	6.71	8.02	1.46	1.69	1.79	2.38	2.87	3.46	4.26	4.67	6.64	7.88
		Low	kW	1.04	1.26	1.36	1.60	1.76	1.98	2.51	3.17	3.97	4.11	0.99	1.24	1.26	1.58	1.73	1.96	2.48	3.11	3.93	4.07
	Sensible capacity	High	kW	1.20	1.30	1.42	1.88	2.11	2.72	3.15	3.65	4.91	5.96	1.14	1.27	1.46	1.85	2.07	2.71	3.09	3.57	4.85	5.85
		Low	kW	0.79	0.95	1.00	1.18	1.26	1.45	1.80	2.32	2.84	3.05	0.75	0.93	0.98	1.17	1.24	1.44	1.78	2.28	2.82	3.02
Heating capacity	2-Pipe	High	kW	2.14	2.20	2.57	3.20	3.81	4.78	5.10	5.95	7.83	10.03	-									
		Low	kW	1.43	1.71	1.79	2.07	2.28	2.81	2.98	3.96	4.77	5.24	-									
	4-Pipe	High	kW	-										1.90	2.02	2.01	2.92	3.08	4.80	5.05	5.30	7.91	8.35
		Low	kW	-										1.50	1.56		2.06	2.18	3.21	3.60	4.04	5.69	5.50
Power input	High		W	37	53		57	56	98			182	244	37	53		57	56	98			182	244
	Low		W	21	25	24	29		37	38	47	86	109	21	25	24	29		37	38	47	86	109
Dimensions	Unit	Height	mm	535																			
		Width	mm	584			794		1,004			1,214		584			794		1,004			1,214	
		Depth	mm	224								249		224								249	
Weight	Unit		kg	14	15		19		23			32		15	16		20		25			34	
Heat exchanger	Water volume		l	0.5		0.7		1		1.4		2.1		0.5		0.7		1		1.4		2.1	
Additional heat exchanger	Water volume		l	-										0.2			0.3			0.4		0.6	
Water flow	Cooling		l/h	264	298	337	415	504	602	743	818	1,152	1,376	250	291	176	409	494	594	730	803	1,138	1,362
	Heating		l/h	264	298	337	415	504	602	743	818	1,152	1,376	167	177	182	257	270	421	443	465	694	733
Fan	Type			Centrifugal multi-blade, double suction																			
	Quantity			1			2							1			2						
	Air flow rate	High	m^3/h	319	344		442		640	706	785	1,011	1,393	307	330	327	432	431	628	690	763	998	1,362
		Low	m^3/h	178	211		241		320	361	470	570	642	174	205		238		316	356	460	565	636
Sound power level	High		dBA	47	49	50	48		52	53	56	61	67	45	49	50	48	47	51	56	59	60	66
Piping connections	Drain	OD	mm	17																			
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230																			
Current input	High		A	0.17	0.24		0.26	0.25	0.44		0.43	0.82	1.10	0.17	0.24		0.26	0.25	0.44		0.43	0.82	1.10
	Medium		A	0.13	0.16		0.21	0.20	0.29		0.31	0.57	0.76	0.13	0.16		0.21	0.20	0.29		0.31	0.57	0.76
	Low		A	0.10	0.12	0.11	0.14		0.19		0.22	0.39	0.50	0.10	0.12	0.11	0.14		0.19		0.22	0.39	0.50
Control systems	Wired remote control			FWEC1A / FWEC2A / FWEC3A																			

Wall mounted unit

AC fan motor unit for wall mounting

› High **aesthetic cabinet design**
› **Optimum air distribution**
› Easy to install
› 3-speed fan motor
› **Low operating sound level** thanks to tangential fan
› Insulated with self-extinguishing class 1 heat insulation
› Removable washable air filter (self-extinguishing class 1)



FWT-CT



MERCA / SRC-HPA



WRC-HPC

				FWT-CT	02	03	04	05	06
							2-pipe		
Cooling capacity	Total capacity	High	kW		2.43	2.70	3.31	4.54	5.28
		Low	kW		2.11	2.23	2.78	3.81	4.40
	Sensible capacity	High	kW		1.85	2.02	2.64	3.43	4.10
		Low	kW		1.49	1.61	2.05	2.81	3.28
Heating capacity	2-Pipe	High	kW		3.22	3.52	4.40	6.01	7.33
		Low	kW		2.49	2.70	3.37	4.84	5.86
Power input	High		W		31	32	42	53	72
	Low		W		25	29	33	42	60
Dimensions	Unit	Height	mm		288			310	
		Width	mm		800			1,065	
		Depth	mm		206			224	
Weight	Unit		kg		9			14	
	Operation weight		kg		9.5	9.6		15	
Heat exchanger	Water volume		l		0.52	0.58		0.95	
Water flow	Cooling		l/h		420	460	570	780	910
	Heating		l/h		420	460	570	780	910
Fan	Type				Cross flow fan				
	Quantity				1				
	Air flow rate	High	m^3/h		442	476	629	866	1,053
		Low	m^3/h		340	374	442	663	782
Sound power level	High		dBA		45	48	55		59
Sound pressure level	High		dBA		34	35	42		46
Piping connections	Drain	OD	mm		19				
Water connections	Std. heat exchanger		inch		1/2				
Power supply	Phase/Frequency/Voltage		Hz/V		/-/-				
Current input	High		A		0.19	0.20	0.21	0.29	0.34
	Medium		A		0.18	0.20		0.26	0.32
	Low		A		0.17	0.19		0.25	0.31
Control systems	Infrared remote control				WRC-HPC				
	Wired remote control				MERCA / SRC-HPA				

Low ESP ducted unit

AC fan motor unit for horizontal concealed mounting

- **Easy installation and maintenance**
- **4-speed fan motor**
- High power air flow
- Wired electronic controllers range
- Available static pressure up to 50Pa
- Wide operating range
- Standard left and right side water connection
- **Extended drain pan** as standard
- **Factory mounted valve** (both left and right side)
- Nylon filter G2 class
- Polyethylene insulation



FWE-CT/CF




FWEC1,2,3A

				FWE-CT/CF	02	03	04	06	07	08	10	02	03	04	06	07	08	10
					2-pipe							4-pipe						
Cooling capacity	Total capacity	Super high	kW		2.17	3.22	4.34	6.06	6.83	7.84	9.96	2.10	3.16	3.98	6.05	6.78	7.79	9.91
		High	kW		1.81	2.78	3.49	5.32	5.68	6.92	8.64	1.76	2.69	3.22	5.20	5.61	6.79	8.61
		Low	kW		0.90	1.40	1.80	2.80	3.10	3.90	4.90	0.85	1.40	1.63	2.72	3.10	3.88	4.88
	Sensible capacity	Super high	kW		1.61	2.44	3.27	4.55	4.83	6.02	7.58	1.55	2.37	3.19	4.49	5.16	5.91	7.45
		High	kW		1.33	2.08	2.58	3.94	4.30	5.25	6.48	1.28	1.99	2.53	3.81	4.20	5.09	6.39
		Low	kW		0.70	1.20	1.40	2.10	2.50	3.10	3.70	0.66	1.18	1.35	2.02	2.47	3.05	3.65
Heating capacity	2-Pipe	Super high	kW		2.79	4.28	5.61	7.66	9.26	10.50	13.00	-						
		High	kW		2.31	3.67	4.44	6.65	7.62	9.18	11.10	-						
		Low	kW		1.20	2.00	2.30	3.40	4.40	5.30	6.30	-						
	4-Pipe	Super high	kW		-							2.3	3.53	4.56	6.17	7.6	8.52	10.4
		High	kW		-							1.94	3.06	3.76	5.37	6.42	7.52	9.16
		Low	kW		-							1.02	1.72	2.03	2.88	3.92	4.59	5.42
Power input	Super high		W		46	69	83	119	163	181	230	46	69	83	119	163	181	230
	High		W		39	54	59	93	128	145	180	39	54	59	93	128	145	180
	Low		W		29	40	42	60	89	102	121	29	40	42	60	89	102	121
Dimensions	Unit	Height	mm		253													
		Width	mm		590													
		Depth	mm		705	875	1,005	1,205	1,455	1,555	1,815	705	875	1,005	1,205	1,455	1,555	1,815
Weight	Unit		kg		17	20	24	28	37	39	46	18	22	25	30	40	41	49
	Operation weight		kg		17	20	24	28	37	39	46	18	22	25	30	40	41	49
Heat exchanger	Water volume		l		0.74	1.02	1.24	1.56	1.97	2.14	2.56	0.74	1.02	1.24	1.56	1.97	2.14	2.56
Additional heat exchanger	Water volume		l		-							0.25	0.34	0.41	0.52	0.66	0.71	0.85
Water flow	Cooling		l/h		360	540	756	1,044	1,188	1,368	1,728	360	540	720	1,044	1,188	1,332	1,728
	Heating		l/h		252	360	504	684	828	936	1,188	-						
	Additional heat exchanger		l/h		-							108	180	216	324	432	468	576
Water pressure drop	Additional heat exchanger		kPa		-							3.6	8.8	15.6	31.8	58.6	74.6	123
Fan	Type				Centrifugal (Blade: Forward - curve)													
	Quantity				1		2		3		4	1		2		3		4
	Air flow rate	Super high	m^3/h		430	638	910	1,195	1,559	1,753	2,177	416.13	626.11	834.52	1,193.03	1,547.59	1,741.82	2,166.07
		High	m^3/h		311	518	619	926	1,188	1,413	1,735	302.41	501.23	571.11	905.11	1,173.36	1,386.46	1,728.98
		Low	m^3/h		150	256	284	426	569	688	808	142	256	257.48	414.34	569	684.16	804.37
Sound power level	Super high		dBA		51	61	58	62		64	65	51	61	58	62		64	65
	High		dBA		49	56	48	55	57	58	60	49	56	48	55	57	58	60
Sound pressure level	Super high		dBA		41	51	48	52		54	55	41	51	48	52		54	55
	High		dBA		39	46	38	45	47	48	49	39	46	38	45	47	48	49
Piping connections	Drain	OD	mm		19.05													
Water connections	Std. heat exchanger		inch		3/4													
	Add. heat exchanger		inch		-							3/4						
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240													
Current input	Super high		A		0.206	0.309	0.372	0.533	0.731	0.811	1.031	0.206	0.309	0.372	0.533	0.731	0.811	1.031
	High		A		0.174	0.243	0.265	0.430	0.575	0.648	0.780	0.174	0.243	0.265	0.430	0.575	0.648	0.780
	Medium		A		0.150	0.208	0.217	0.325	0.472	0.523	0.648	0.150	0.208	0.217	0.325	0.472	0.523	0.648
	Low		A		0.128	0.177	0.188	0.271	0.400	0.456	0.540	0.128	0.177	0.188	0.271	0.400	0.456	0.540
Control systems	Wired remote control				FWEC1A / FWEC2A / FWEC3A													

Medium ESP ducted unit

BLDC fan motor unit for horizontal concealed mounting. Continuous air flow regulation and fan speed modulation

- **Blends unobtrusively** with any interior décor: only the suction and discharge grills are visible
- Up to 50% **energy savings** with brushless DC motor technology compared to traditional technology
- **Instant adjustment** to temperature and relative humidity changes
- **Low operating sound level**
- Highly flexible solutions: multiple sizes, piping topologies and connection valves



FWP-AT




FWEC3A

				FWP-AT	02	03	04	05	06	07
					2-pipe					
Cooling capacity	Total capacity	High	kW		2.61	3.14	3.49	5.08	5.45	6.47
		Low	kW		1.34	1.5	1.67	2.12	2.43	2.67
	Sensible capacity	High	kW		1.88	2.16	2.34	3.6	3.87	4.4
		Low	kW		0.95	1.02	1.1	1.52	1.67	1.78
Heating capacity	2-Pipe	High	kW		5.47	6.01	6.47	10.31	11.39	12.28
		Low	kW		2.77	2.91	3.00	4.56	4.77	4.94
	4-Pipe	High	kW			3.14			5.99	
		Low	kW			1.95			3.38	
Power input	High		W			46.4			80	
	Low		W			12.2			17.5	
Dimensions	Unit	Height	mm				239			
		Width	mm			1,039			1,389	
		Depth	mm				609			
Weight	Unit		kg		23	24	26	31	33	35
	Operation weight		kg		24	26	28	33	35	38
Heat exchanger	Water volume		l		1.1	1.5	2.2	1.6	2.1	3.2
Additional heat exchanger	Water volume		l			0.4			0.6	
Water flow	Cooling		l/h		448	539	598	873	936	1,111
	Heating		l/h		480	527	567	904	999	1,077
	Additional heat exchanger		l/h			275			526	
Water pressure drop	Additional heat exchanger		kPa			3			5	
Fan	Type						Centrifugal - forward blades - directly coupled on fan motor			
	Quantity						1			
	Air flow rate	High	m^3/h			400			800	
		Low	m^3/h			180			300	
	Available pressure	High	Pa			71			65	
Sound power level	High		dBA			55.6			60.6	
Sound pressure level	High		dBA			44.1			49.1	
Electric heater	Power input		kW			2			2.5	
Piping connections	Drain	OD	mm				16			
Water connections	Std. heat exchanger		inch				3/4			
	Add. heat exchanger		inch				3/4			
Power supply	Phase/Frequency/Voltage		Hz/V				1~/50/230			
Control systems	Wired remote control						FWEC3A			

Medium ESP ducted unit

AC fan motor unit for horizontal concealed mounting

- **Compact dimensions**, can easily be mounted in a narrow ceiling void
- 3, 4 or 6 stage row cooling coil
- Drain pan to collect the condensate from: heat exchanger and regulating valves
- **7-speed electrical motors** (with thermal protection on windings)
- All 7 speeds **pre-wired in the factory** in the terminal block of the switch box
- **Washable air filter**, easily removable for maintenance



FWB-BT




FWEC1,2,3A

				FWB-BT	02	03	04	05	06	07	08	09	10
					2-pipe								
Cooling capacity	Total capacity	High	kW		2.61	3.14	3.49	5.08	5.45	6.47	7.57	8.67	10.34
		Low	kW		1.34	1.50	1.67	2.12	2.43	2.67	4.18	4.64	5.35
	Sensible capacity	High	kW		1.88	2.16	2.34	3.6	3.87	4.4	5.23	5.96	6.9
		Low	kW		0.95	1.02	1.1	1.52	1.67	1.78	2.95	3.21	3.57
Heating capacity	2-Pipe	High	kW		5.47	6.01	6.47	10.31	11.39	12.28	15.05	16.85	18.78
		Low	kW		2.77	2.91	3.00	4.56	4.77	4.94	8.63	9.29	9.85
	4-Pipe	High	kW			3.14			5.99			12.8	
		Low	kW			1.95			3.38			7.67	
Power input	High		W			79			154			294	
	Low		W			28			64			155	
Dimensions	Unit	Height	mm						239				
		Width	mm			1,039			1,389			1,739	
		Depth	mm						609				
Weight	Unit		kg		23	24	26	31	33	35	43	45	48
	Operation weight		kg		24	26	28	33	35	38	45	48	52
Heat exchanger	Water volume		l		1.1	1.5	2.2	1.6	2.1	3.2	2.1	2.8	4.2
Additional heat exchanger	Water volume		l			0.4			0.6			1.7	
Water flow	Cooling		l/h		448	539	598	873	936	1,111	1,299	1,488	1,774
	Heating		l/h		480	527	567	904	999	1,077	1,319	1,479	1,647
	Additional heat exchanger		l/h			275			526			1,123	
Water pressure drop	Additional heat exchanger		kPa			3			5			8	
Fan	Type				Centrifugal - forward blades - directly coupled on fan motor								
	Quantity					1			2			3	
	Air flow rate	High	m^3/h			400			800			1,200	
		Low	m^3/h			180			300			600	
	Available pressure	High	Pa			71			65			59	
Sound power level	High		dBA			56			59			69	
Sound pressure level	High		dBA			44.5			47.5			57.5	
Electric heater	Power input		kW			2			2.5			3	
Piping connections	Drain	OD	mm						16				
Water connections	Std. heat exchanger		inch						3/4				
	Add. heat exchanger		inch				3/4					1	
Power supply	Phase/Frequency/Voltage		Hz/V					1~/50/230					
Current input	High		A			0.36			0.73			1.28	
	Medium		A			0.21			0.60			0.90	
	Low		A			0.14			0.33			0.70	
Control systems	Wired remote control							FWEC1A / FWEC2A / FWEC3A					

High ESP ducted unit

AC fan motor unit for horizontal or vertical concealed mounting

› Straight duct connector mounted to discharge side
› **Washable air filter**, easily removable for maintenance



FWD-AT/AF



FWEC1,2,3A

			FWD-AT/AF	04	06	08	10	12	16	18	04	06	08	10	12	16	18
				2-pipe							4-pipe						
Cooling capacity	Total capacity	High	kW	3.90	6.20	7.80	8.82	11.90	16.40	18.30	3.90	6.20	7.80	8.82	11.90	16.40	18.30
	Sensible capacity	High	kW	3.08	4.65	6.52	7.16	9.36	12.80	14.10	3.08	4.65	6.52	7.16	9.36	12.80	14.10
Heating capacity	2-Pipe	High	kW	4.05	7.71	9.43	10.79	14.45	19.81	21.92	-						
	4-Pipe	High	kW	-							4.49	6.62	9.21		15.86	21.15	
Power input	High		W	234	349	443		714	1,197		234	349	443		714	1,197	
	Low		W	130	247	261		328	704		130	247	261		328	704	
Dimensions	Unit	Height	mm	280				352			280				352		
		Width	mm	754	964	1,174			1,384		754	964	1,174			1,384	
		Depth	mm	559				718			559				718		
Weight	Unit		kg	33	41	47	49	65	77	80	35	43	50	52	71	83	86
Heat exchanger	Water volume		l	1.06	1.42	1.79	2.38	2.5	4.02	5.03	1.06	1.42	1.79	2.38	2.50	4.02	5.03
Additional heat exchanger	Water volume		l	-							0.35	0.47	0.59		1.42	1.72	
Water flow	Cooling		l/h	674	1,064	1,339	1,514	2,056	2,833	3,140	674	1,064	1,339	1,514	2,056	2,833	3,140
	Heating		l/h	674	1,064	1,339	1,514	2,056	2,833	3,140	349	581	808		1,392	1,856	
Fan	Type			Centrifugal multi-blade, double suction													
	Quantity			1	2						1	2					
	Air flow rate	High	m^3/h	800	1,250	1,600		2,200	3,000		800	1,250	1,600		2,200	3,000	
	Available pressure	High	Pa	66	58	68	64	97	145	134	63	53	63	59	92	138	128
Sound power level	High		dBA	66	69	72		74	78		66	69	72		74	78	
Piping connections	Drain	OD	mm	16													
Water connections	Std. heat exchanger		inch	3/4				1			3/4				1		
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230													
Current input	High		A	0.95	1.58	1.97		3.21	5.37		0.95	1.58	1.97		3.21	5.37	
	Medium		A	0.74	1.39	1.52		2.08	4.38		0.74	1.39	1.52		2.08	4.38	
	Low		A	0.57	1.18	1.20		1.50	3.26		0.57	1.18	1.20		1.50	3.26	
Control systems	Wired remote control			FWEC1A / FWEC2A / FWEC3A													





Daikin air handling units, with their plug-and-play design and inherent flexibility, can be configured and combined specifically to meet the exact requirements of any building, no matter what it is used for or who is to work there. Our systems are designed to be the most environmentally friendly and the most energy efficient on the market, thus reducing their ecological impact, while, at the same time, keeping costs down through the minimisation of energy consumption.

When combined with the small physical footprint of the system, these features make our air handling units ideal for all markets.

Air handling units

Why choose Daikin airhandling units? 378

Products overview 382

Software and Eurovent certification 383
The working principle at a glance 384
Compact 386
Professional 388
Easy 389
Energy 390
Fresh air package 392



Daikin Air handling units

Why choose Daikin air handling units?

- Energy efficiency and indoor air quality
- Wide range of air handling units
- **High quality** in component selection
- **Innovative** technology
- Operation **efficiency** and energy **savings**
- Outstanding **reliability** and **performance**
- Various applications are possible including air conditioning applications, industry-type process cooling, and large-scale district heat source systems.

Benefits for the installer

› Easy start-up and commissioning through pre-programmed DDC controller and external terminal connection avoiding drilling into unit panels
› Internal electrical wiring saves installation time
› Flush mounted electrical control panel avoids risk of damage during transportation and installation

Benefits for the consultant

› In-house developed ASTRA software with dedicated control interface allowing for a professional report in a few clicks

Benefits for the end user

› Higher degree of control than ever before, allowing the user to determine a wide range of settings, resulting in excellent operational flexibility
› For units higher than 800mm, the electrical panel is fully embedded into the unit



Marketing tools

› Watch the time-lapse video of a Daikin AHU construction on www.youtube.com/daikineurope
› Brochure on air handling units as a combined solution with refrigeration and chillers on commercial applications




Packaged control solution for Daikin AHU

› Electrical control panel complete with
› Direct Digital Control (DDC) controller
› Internal fitting of all sensors & pressure measurements devices
› Built-in temperature, humidity and CO_2 sensors
› Internal electrical wiring for all components

Energy efficient while focusing on maximum comfort

› Set points can be specified for supply, return or room temperature
› Control of all AHU components such as mixing dampers, heat recovery wheels, water valves, pressure switches for filters and fans, fan motors and inverters



Plug and play design

› Low voltage fast connectors in between AHU sections

Easy start-up and commissioning

› Pre-programmed and factory-tested controls ensuring all wiring is installed correctly
› Reduced energy and operating costs


SMART CONTROLS




ENERGY EFFICIENT FAN






COMMERCIAL AND
INDUSTRIAL APPLICATIONS



COMFORTABLE
INDOOR CLIMATE



Overview D-AHU range



Professional
› Pre-configured sizes
› Tailored to the individual customer
› Modular construction

Energy
› High-end solution for optimised energy consumption
› High efficiency components
› Strong Return on Investment

Easy
› Space-optimized unit
› Pre-configured sizes

NEW Compact
› Pre-configured sizes
› Plug & Play concept
› EC Fan Technology
› High Efficiency Heat Wheel
› Compact Design


Software

ASTRA Pro


ASTRA is the powerful software that Daikin has developed to offer a **quick** and **comprehensive service** for the customer in order to make the technical choice and the **economic valorization** of each air handling unit. It is a complete tool that can configure any type of product and respond exactly to the strictest design needs. The result is a comprehensive **economic** offer including all the technical data and drawings, the psychrometric diagram with the relative air treatment and the fans' performance curves. However, Daikin didn't stop there, they went further.

MECCANO is the other powerful software developed and designed to quickly **convert the offer in the executive order**. Technical drawings to be sent and approved by the client, executive drawings for the production, bill of material, code generation for each component used are just a few of the many functions of the instrument.

The ASTRA-MECCANO integration has therefore made possible the complete automated management of the process by **reducing the time of the offer** and of the delivery and improving the service to our customers.







NEW

ASTRA Xpress

› Quick AHU selection that will save you precious time, drastically reducing selection time through the new software interface.
› Very competitive solution available within the Wizard thanks to pre-uploaded parameters.
› High selection quality, thanks to the huge number of the pre-engineered units embedded within the software.

4 steps to configure an air handler in just 2 minutes

1. Select a configuration
2. Select coils
3. Select other components
4. Design conditions ----> Print report

Eurovent certification

Daikin is participating in the Eurovent Certification Programme for Air Handling Units. They are certified under the number 11.05.003 and presented on www.eurovent-certification.com


Daikin air handling units	Result sp65	Eurovent Classification according to EN1886					
		Casing mechanical strength					
Casing mechanical strength	D1	Casing Class	D1	D2	D3		
		Maximum relative deflection mm x m^{-1}	4.00	10.00	EXCEEDING10		
		Casing air leakage Negative pressure -400 Pa					
Casing air leakage Negative pressure -400 Pa	L1	Leakage Class	L1	L2	L3		
		Maximum leakage rate (f_{400}) l x s^{-1} x m^{-2}	0.15	0.44	1.32		
		Casing air leakage Positive pressure +700 Pa					
Casing air leakage Positive pressure +700 Pa	L1	Leakage Class	L1	L2	L3		
		Maximum leakage rate (f_{700}) l x s^{-1} x m^{-2}	0.22	0.63	1.90		
		Filter bypass leakage					
Filter bypass leakage	F9	Filter Class	F9	F8	F7	F6	G1 TO F5
		Maximum filter bypass leakage rate k in % of the volume flow rate	0.50	1	2	4	6
		Thermal transmittance					
Thermal transmittance	T2	Class	T1	T2	T3	T4	T5
		Thermal transmittance (U) W/m^2 x K	U <= 0.5	0.5 < U <= 1	1 < U <= 1.4	1.4 < U <= 2	No requirements
		Thermal Bridging of the casing					
Thermal bridging of the casing	TB2	Class	TB1	TB2	TB3	TB4	TB5
		Thermal bridging facto (kb) W x m^{-2} x K-1	0.75 < K_b <= 1	0.6 < K_b <= 0.75	0.45 < K_b <= 0.6	0.3 < K_b <= 0.45	No requirements

The working principle at a glance

Typical configurations for Daikin air handling units provide a versatile range of functions.
Our system offers numerous options for customisation through an extensive range of variations and added functionality.

Supply side

1. Damper section including ventilation grilles, factory-mounted actuators
2. Bag filter with factory-mounted differential pressure manometer and hinged door
3. Heat recovery system (plate heat exchanger or rotation heat exchanger)
4. Mixing box with damper and factory-mounted actuators
5. R-410A with heat recovery system with galvanised condensate tray and drip protection
6. Supply air fan (with hinged door, opening, drive monitoring, mounted and cabled lighting and ON/OFF switch)



Fans
- Forward curved fan
- Backward curved fan
- Backward airfoil blades fan
- Plug fan
- EC plug fan

Exchangers
- Water coils
- Steam coils
- Direct expansion coil
- Superheated water coils
- Electric coils


Humidifiers
- Evaporative humidifier without pump (loss water)
- Evaporative humidifier with re-circulating pump
- Air washer without pump (loss water)
- Air washer with re-circulating pump
- Steam humidifier with direct steam production
- Steam humidifier with local distributor
- Atomized water spray humidifier


Control system on plug and play solution basis

› Air temperature control
› Chilled water and DX cooling system control
› Free cooling
› CO_2 automatic control

Unique section to section thermal break profile

› Thermal bridge free for the entire AHU
› Smooth interior surface with improved IAQ (Indoor Air Quality)





Return side

7 Bag filter with factory-mounted differential pressure manometer and hinged door.

8 Exhaust air fan (with hinged door, opening, drive monitoring, mounted and cabled lighting and ON/OFF switch)

9 Mixing box with damper and factory-mounted actuators

10 Heat recovery system (plate heat exchanger or rotation exchanger)

11 Damper section including ventilation grilles, factory-mounted actuators

Heat recovery systems
› Heat wheel, sensible or sorption
› Plate heat exchanger (optional bypass)
› Run-around coils

Other section
› Attenuator section
› Mixing box section with actuators or manual controlled dampers
› Empty section

Filters
› Synthetic pleated filter
› Flat filter aluminium mesh
› Rigid bag filter
› Soft bag filter
› High efficiency filter
› Carbon absorption filter
› Carbon deodorizing filter

Accessories
› Control features
› Frost protection
› Manometers
› Drive guard
› Roof
› …


Compact

High-end solution with heat recovery


Energy efficiency and indoor air quality

- Predifined sizes
- Plug & Play design: prewired and factory-tested
- EC fan technology
- IE4 premium efficiency motor
- High efficiency heat wheel (heat recovery)
- Compact design
- Advanced control features
- Easy installation
- User friendly selection
- Eurovent certified
- Indoor air quality compliant with VDI 6022 hygiene guideline






- Control logic : Supply, Ambient and Return Temperature
- Operating limits from -25 °C, -40 °C with electric heaters, up to +46 °C ambient temperature
- DX or chilled water cooling coil
- VRV IV and ERQ coupling capability
- Silencers
- Humidifier module
- Indoor and outdoor versions
- Air flow or pressure control (Variable Air Volume - Constant Air Volume)
- Free cooling capability
- Economy and Night operation
- Time Scheduler
- IAQ through CO_2 sensor
- Monitoring and control through Daikin ITM
- Monitoring of the energy consumption



EC Fan

- Air flow control via measuring at the inlet nozzle (VAV - CAV)
- Easy commissioning
- Nominal air flow programmed at factory
- Silent operation



Installation – simple and safe


no need for cost-intensive adjustments before commissioning or for grounding and shielding measures. Plug-and-Play is that simple in ventilation and air-conditioning technology.

	D-AHU	1	2	3	4	5	6	7	8	9	10
Airflow rate	m³/h	1,200	1,700	2,700	4,100	5,500	6,100	7,000	9,100	11,500	15,000
Temp efficiency winter	%	81.3	81.1	81.4	81.6	82.6	81.2	82.7	81.4	81.5	83.2
ESP nominal	Pa	200	200	200	200	200	200	200	200	200	200
Power input	kW	0.311	0.447	0.748	0.992	1.29	1.48	1.65	1.88	1.37	1.76
Height	mm	1,320	1,320	1,540	1,740	1,740	1,920	1,920	2,180	2,460	2,570
Width	mm	1,700	1,700	1,800	1,980	2,080	2,280	2,400	2,450	2,280	2,400
Depth	mm	720	820	990	1,200	1,400	1,400	1,600	1,940	1,940	2,300
Weight	kg	325	350	475	575	750	790	950	1,330	1,410	1,750
SFPv	kW/m³/s	1,866	1,893	1,995	1,742	1,689	1,747	1,697	1,487	1,715	1,689
Power supply	Hz/V	1~ / 50 / 230			3N~ / 50 / 400						

Above data refers to standard air performance sizes

Air performance STD (standard performance)


(Pa) Max. available ESP (supply)



Size 1
Size 2
Size 3
Size 4
Size 5
Size 6
Size 7
Size 8
Size 9
Size 10

Air performance HP (high performance)

(Pa) Max. available ESP (supply)



Size 4
Size 5
Size 6
Size 7
Size 9
Size 10

Professional
The most flexible solution

Pre-defined family of sizes

Twenty-seven (27) fixed sizes optimized for the most cost effective selection and manufacturing standardization.

Infinitely variable sizing

› Dimensions (width and height) can vary with a 1cm small increment to match individual customer needs and to reach an increased efficiency of the heat wheel.
› Air flow from 500 m^3/h up to 140,000 m^3/h
› All the sizes are modular manufactured to facilitate the transport and the assembly on site.



Pre-defined sizes - Overall dimensions

Size	Air Flow (m^3/h)	Height - mm	Width - mm
1	1,105	550	850
2	1,550	600	900
3	1,980	650	950
4	2,600	780	1,100
5	3,170	780	1,150
6	3,550	800	1,150
7	4,000	800	1,250
8	4,800	850	1,300
9	5,560	900	1,350
10	6,600	900	1,550
11	7,950	1,100	1,550
12	9,320	1,100	1,650
13	10,050	1,150	1,650

Size	Air Flow (m^3/h)	Height - mm	Width - mm
14	13,200	1,400	1,850
15	19,200	1,500	2,100
16	25,300	1,580	2,650
17	31,500	1,750	2,750
18	37,000	1,800	3,240
19	43,400	2,100	3,090
20	51,300	2,250	3,340
21	58,000	2,250	3,820
22	67,500	2,400	4,040
23	78,000	2,450	4,490
24	84,700	2,700	4,490
25	98,000	2,850	4,890
26	111,000	2,850	5,490
27	124,000	3,000	5,990

Infinitely variable sizes

Flexible sizing for AHU optimization
› 1 cm increment for width & height dimensions
› No additional cost for customized unit size
› No additional lead time

Example

Air Flow (m^3/h)	Unit Size	Height - mm	Width - mm	Face Velocity m/s
15.000	STD 15	1,500	2,100	1,95
	1,500x1,750	1,500	1,750	2,46

Plug and play: More control, more flexibility

The new plug and play control system gives end-users a higher degree of control than ever before, allowing the user to determine a wide range of settings, resulting in excellent operational flexibility.
The factory-fitted electrical control panel, complete with Direct Digital Control (DDC) controller, is combined with in-built temperature, humidity and CO_2 sensors to control mixing dampers, heat recovery wheels, water valves, pressure switches for filters and fans, fan motors and inverters.
All these components are wired internally and individual AHU modules are linked by fast connectors.
The AHU control system can manage the chilled water coil, hot water coil, DX cooling and/or heating coil(s) (in conjunction with ERQ/VRV) of single or multiple refrigerant circuits (up to a maximum of four circuits per DX coil).

Easy

Quick solution for climate control

The range covers an area of air flow rates from 500 m³/h up to 30,000 m³/h*, with the possibility to choose the more appropriate face velocity, depending on the treatment required.



Pre-defined sizes

Fifteen fixed sizes optimized to reach the best compromise between competitiveness and manufacturing standardization.

Variable Dimensioning

Designed to overcome installation constraints where space requirements of the section "height x width" must be adapted to the available space. The system gives the possibility to tailor the unit sizes through increments of 1 cm average.

Pre-defined sizes - Overall dimensions

Size	Air Flow (m³/h) Speed 2.5 m/s	Height - mm	Width - mm
Std 1	1,105	550	850
Std 2	1,550	600	900
Std 3	1,980	650	950
Std 4	2,600	780	1,100
Std 5	3,170	780	1,150
Std 6	3,550	800	1,150
Std 7	4,000	800	1,250
Std 8	4,800	850	1,300
Std 9	5,560	900	1,350
Std 10	6,600	900	1,550
Std 11	7,950	1,100	1,550
Std 12	9,320	1,100	1,650
Std 13	10,050	1,150	1,650
Std 14	13,200	1,400	1,850
Std 15	19,200	1,500	2,100

Example

Air Flow (m³/h)	Unit Size	Height - mm	Width - mm	Face Velocity m/s
15,000	STD 15	1,500	2,100	1.95
	1.500x1.700	1,500	1,700	2.48


Infinitely variable sizes

Flexible sizing for AHU optimization


- 1 cm increment for width & height dimensions
- No additional cost for non-standard unit size
- No additional lead time

*Air Flow limits of 500 m³/h and 30,000 m³/h are calculated using non standard sizes (max dimensions 2,150x2,150) and considering 2.5 m/s coil face velocity

D-AHU Easy 1-8



D-AHU Easy 9-15



Energy


High-end solution for the highest energy efficiencies

High efficiency heat recovery

The D-AHU Energy series is equipped with high efficiency heat recovery system with rates up to 90%. Various models are available with a heat recovery system equipped with a condensation wheel, an enthalpy wheel or a sorption wheel.









Premium efficiency motor

Premium efficiency motors in line with EU regulation (EC) no. 640/2009 are available for the Energy series in order to further reduce electrical power consumption.



High efficiency fan

Fans with double-width, double-inlet and backward curved airfoil blades are available with efficiencies of up to 85% as well as reinforced bearings for longer lifespan.




Plug and play controls


Daikin has developed a control system to efficiently manage all components selected either independently or through an external supervision system. The control package includes the control panel, advanced microprocessor and in-built sensors for temperature, humidity and air quality.

Return on investment

An air handling unit is critical to an effective climate control system and, although the initial investment can appear high,
the savings generated by our advanced designs and operating efficiencies guarantee a rapid return on the investment made. Our D-AHU Energy series has been designed to deliver exceptional performance thus driving down the energy consumed and so lowering energy bills. Taken over the expected 15-year life-span of the equipment, this will result in an enormous saving, especially in a time of ever increasing energy prices.

AHU Life Cycle Cost (LCC)





Specific Fan Power (SFP) is a measure used in the evaluation of the energy consumed by an air handling unit. As defined in EN 13053 and EN 13779, the lower the SFP, the lower the power consumption of the entire air handling unit. The D-AHU Energy has been designed to deliver the lowest possible SFP by using the most efficient components designed to provide the perfect solution series to your needs. It is an optimized answer to the European directive on the energy performance of buildings (EPBD) that seeks to reduce the impact on global warming.




Daikin Fresh Air package

High Efficiency

Daikin heat pumps are renowned for their high energy efficiency. The VRV range offers both heat pump and heat recovery units with part load efficiencies as high as 9.02. Integrating the AHU with a heat recovery system is highly effective since an office system can frequently be in cooling mode while the outdoor air is too cold to be brought inside in an unconditioned state. In this case heat from the offices is merely transferred to heat up the cold incoming fresh air. In the absence of an AHU this 'free heating' of incoming fresh air would not be possible.

High Comfort Levels

Daikin ERQ and VRV units respond rapidly to fluctuations in supply air temperature, resulting in a steady indoor temperature and resultant high comfort levels for the end user.
The ultimate is the VRV range which improves comfort even more by offering continuous heating, also during defrost.




FERAG



Daikin offers a wide range of condensing units for cooling and freezing applications. Daikin refrigeration units combine efficiency and reliability with easy installation and maintenance.

Refrigeration

Why choose Daikin refrigeration? 396

ZEAS condensing units
LREQ-BY1 402

Conveni-Pack
LRYEQ-AY1 404

Booster unit
LCBKQ-AV1 409

Commercial condensing units
JEHCCU-M/L & JEHSCU-M 410

Large variable capacity condensing unit
ICU 413

For more information on Options & Accessories, please refer to page 466 of this catalogue.



Refrigeration

ICEBAR - London

Why choose Daikin refrigeration?

- High **efficient** solutions to match your refrigeration needs
- **For commercial and industrial** applications
- Innovative and **reliable** technology – proven and **tested** for VRV (ZEAS and Conveni-Pack)
- Compliant with **new F-Gas regulation** (R-410A)
- Across Europe, thousands of Daikin refrigeration systems running on R-410A, such as its ZEAS and Conveni-Pack ranges, are used in a wide range of applications, from food retail to industry.
- Urban proof solutions in terms of **compact dimensions** and low sound levels

Marketing tools

Visit the website: http://www.daikineurope.com/refrigeration
Download the software:
Extranet > Software Downloads > Refrigeration Xpress

Benefits for the installer

› Plug and play solutions
› Factory-tested
› Compact design for restricted installation space

Benefits for the consultant


› Daikin ZEAS identified as best available technology according to Eco-design
› Easy and intuitive selection of outdoor condensing units with Refrigeration Xpress
› Wide range to match most refrigeration needs

Benefits for the end user

› High efficient solutions with innovative technology for lower running costs
› Heat recovery technology on Conveni-Pack
› Proven reliability and high performance
› Ideal for urban applications

F-Gas compliant

Daikin refrigeration units are ready to meet the targets of the new F-Gas regulation.



01/01/2020
Ban onHFCs with GWPs of 2500 or more
Applies to stationary refrigeration equipment or it's associated remote plant. Equipment operating below -50 deg C is exempt

01/01/2022
Ban on HFCs with GWP of 150 and over
Applies to multipack centralized refrigeration systems for commercial use with a rated capacity of 40kW or more - except where used in the primary refrigerant circuit of cascade systems, where **HFCs with a GWP of less than 1500 may be used**

01/01/2020
Service ban on HFCs with GWPs of 2500 or more
Applies to refrigeration equipment with a charge size of 40 tonnes CO_2 eq or above.

01/01/2030
Service ban on reclaimed HFCs with GWPs of 2500 or more
Used for the maintenance or servicing of existing refrigeration equipment with a charge size of 40 tonnes of CO_2 eq or more – provided they are labelled appropriately.

01/01/2030
Service ban on recycled HFCs with GWPs of 2500 or more
Service ban on use in the maintenance or servicing of existing refrigeration equipment with a charge size of 40 tonnes of CO_2 eq or more - provided they have been recovered from the equipment. Can only be used by the firm that recovered it or by the firm whose installation it was recovered from.

* Regulation n° 517/2014 on fluorinated greenhouse gases of 16 April 2014

Your References

Project BÄKO WEST eG - Bochum (Germany)
Ingo Burmeister of BÄKO West explains: "We wanted a future-proof, energy efficient and proven technology with high reliability. At the same time, we sought to minimise on-going maintenance and repair costs along with lowering our energy bills."



Six Daikin ZEAS units provide a cooling capacity of 74 kW to the frozen foods area, while a further six providing a cooling capacity of 171 kW to the chilled foods zone.



A key challenge was to remodel an existing standard cooling area into a freezer room. This was possible after four weeks of drying.



ZEAS (LREQ-BY1)



ZIGGO DOME, EVENT HALL

ZEAS FOR COOLING (6) AND FREEZING (2)



CHILLED WITH ZEAS



BÄKO WEST EG, BAKERY CO-OPERATIVE
ZEAS FOR COOLING (6) AND FREEZING (6)



E. LECLERC, HYPERMARKET
ZEAS



EDEKA, SUPERMARKET
CONVENI-PACK (2) AND ZEAS (1)




KEEP COOL, SAVE MONEY

Daikin refrigeration products are designed to reduce environmental impact. That's why Daikin ZEAS and Conveni-Pack already comply with the new F-gas regulation that enters into force on 1 January 2015. Daikin systems also set industry standards when it comes to energy efficiency. Which enables you to save money while you help save the planet.
Learn more at www.daikineurope.com/refrigeration

DAIKIN

Products overview

Model	Product name	Capacity (kW)
Inverter condensing unit for commercial refrigeration	ZEAS LREQ-BY1	
	Multi ZEAS LREQ-BY1	
Integrated solution for chilling, freezing and comfort cooling and heating	Conveni-Pack LRYEQ-AY1	
Booster unit to allow both ZEAS and Conveni-Pack freezing applications	Booster unit LCBKQ-AV1	
Commercial condensing units with reciprocating technology	CCU JEHCCU-M1/M3/L1/L3 JEHCCU-CM1/CM3	
Commercial condensing units with scroll technology	SCU JEHSCU-M1/M3/L3 JEHSCU-CM1/CM3	
Inverter condensing unit for industrial refrigeration	ICU ICUHS-HA	





ZEAS condensing unit for refrigeration

Why choose ZEAS?

- Best available technology according to Eco-design
- R-410A refrigerant: already compliant with new F-Gas Regulation
- Small footprint
- Low sound level

High energy efficiency

› Daikin inverter scroll compressor with economizer technology
› DC inverter fan technology (Ecodesign compliant)
› Efficient floating evaporator pressure control
› High efficient oil recovery system

Fully packaged unit for excellent reliability and performance

› Error-proof component selection
› In-built controls
› Factory leak-tested and pre-charged

Small foot print and low weight

› Very compact design
› Easy to install, even in small spaces

Low sound level

› Low noise compressors
› High grade sound insulation on both panels and compressors
› Specially designed fan blades to limit sound emissions
› 3 additional low noise mode
› Night operation mode

Marketing tools

Visit the minisite on www.daikineurope.com
Download the selection software from the Extranet > Software Downloads > Refrigeration Xpress

Benefits for the installer

› Reduced delivery time thanks to European manufacturing plant
› Reduced piping requirements and installation time
› Compact design, with reduced foot print
› Integrated electrical & control box
› Unit already pre-charged with refrigerant

Benefits for the consultant

› One model can cover for most refrigeration needs in the market
› Wide capacity range (12.5 till 71.0*kW)
› High modularity of the refrigeration system
› Suitable to indoor installations through the use of high ESP fans

*Preliminary for 2xLREQ20BY1R

Benefits for the end user

› Reduced costs and low environmental impact
› Small footprint and low weight requiring only light weight supporting structures
› A neighbourhood-friendly choice with its special night operation mode

ZEAS condensing unit for commercial refrigeration with scroll technology



LREQ8-12BY1

Refrigeration solution for medium to large capacity applications featuring proven VRV technology

- Perfect solution for all cooling and freezing applications with variable load conditions and high energy efficiency requirements. In particular used in supermarkets, cold storage, blast coolers and freezers etc.
- DC inverter scroll compressor with economiser function results in high energy efficiency and reliable performance
- Reduced CO2 emissions thanks to the use of R-410A refrigerant
- Factory tested and pre-programmed for quick and easy installation and commissioning
- Increased installation flexibility thanks to limited dimensions
- Low sound level including „night mode" operation
- For small freezing capacity, single ZEAS units can be connected to a booster unit
- Multi combination of 2 x 15 HP or 2 x 20 HP resulting in less pipework and installation time

Medium and Low Temperature Refrigeration					LREQ-BY1	5	6	8	10	12	15	20	30	40
System	Outdoor unit module 1					-							LREQ15BY1R	LREQ20BY1R
	Outdoor unit module 2					-							LREQ15BY1R	LREQ20BY1R
Refrigerating capacity	Medium temperature	Nom.			kW	12.5	15.2	19.8	23.8	26.5	33.9	37.9	67.8	75.8
	Low temperature	Nom.			kW	5.51	6.51	8.33	10.0	10.7	13.9	15.4	27.8	29.6
Power input	Medium temperature	Nom.			kW	5.10	6.56	8.76	10.6	12.0	15.2	17.0	30.4	34.0
	Low temperature	Nom.			kW	4.65	5.88	7.72	9.27	9.89	12.8	14.1	25.6	27.6
Dimensions	Unit	Height			mm	1,680							-	
		Width			mm	635		930			1,240		-	
		Depth			mm	765							-	
Weight	Unit				kg	166		242			331	337	-	
Heat exchanger	Type					Cross fin coil							-	
Compressor	Type					Hermetically sealed scroll compressor							-	
	Piston displacement				m^3/h	11.18	13.85	19.68	23.36	25.27	32.24	35.8	-	
	Speed				rpm	5,280	6,540	4,320	6,060	6,960	5,280	6,960	-	
	Output				W	2,600	3,200	2,100	3,000	3,400	2,600	3,400	-	
	Starting method					Direct on line (inverter driven)							-	
Compressor 2	Speed				rpm	-		2,900					-	
	Output				W	-		3,600					-	
Compressor 3	Speed				rpm	-					2,900		-	
	Output				W	-					3,600		-	
Fan	Type					Propeller fan							-	
	Quantity					1					2		-	
	Air flow rate	Cooling	Nom.		m^3/min	95	102	171	179	191	230	240	-	
Fan motor	Output				W	350		750			350	750	-	
	Drive					Direct drive							-	
Fan motor 2	Output				W	-					350	750	-	
Sound pressure level	Nom.				dBA	55.0	56.0	57.0	59.0	61.0	62.0	63.0	65.0	66.0
Operation range	Evaporator	Cooling	Min.~Max.		°CDB	-45~10							-~-	
	Ambient temperature	Min.~Max.			°C	-20~43							-~-	
Refrigerant	Type / GWP					R-410A / 2,087.5							-	
	Charge				kg	5.2		7.9			11.5		-	
	Charge				TCO_2Eq	10.9		16.5			24.0		-	
	Control					Electronic expansion valve							-	
Refrigerant oil	Type					Daphne FVC68D							-	
	Charged volume				l	1.7 §§ 2.5		1.7 §§ 2.1 §§ 3.0			1.7 §§ 2.1 §§ 4.0		-	
Piping connections	Liquid	50m or less				ø 9.5 C1220T (Brazing connection)				ø 12.7 C1220T (Brazing connection)			ø 19.05 C1220T (Brazing connection)	
		50~130m				ø 9.5 C1220T (Brazing connection)		ø 12.7 C1220T (Brazing connection)					ø 19.05 C1220T (Brazing connection)	
	Gas	50m or less				ø 22.2 C1220T (Brazing connection)		ø 28.6 C1220T (Brazing connection)			ø 34.9 C1220T (Brazing connection)		ø 41.28 C1220T (Brazing connection)	
		50~130m				ø 22.2 C1220T (Brazing connection)		ø 28.6 C1220T (Brazing connection)			ø 34.9 C1220T (Brazing connection)		ø 41.28 C1220T (Brazing connection)	
Power supply	Phase/Frequency/Voltage				Hz/V	3~/50/380-415							/-/-	
Current	Running current (RLA)	Nom.			A	7.1/-/-	9.2/-/-	5.3/7.5/-	7.4/7.9/-	9.8/8.3/-	7.0/8.2/8.2	9.5/8.4/8.4	-/-/-	
Current	Starting current (MSC)				A	-		74	75		84		109	115




Conveni-Pack, integrated solutions for freezing, chilling, space heating and cooling

Why choose Conveni-Pack?

Conveni-Pack is designed for supermarkets and smaller retail outlets, to help lower energy consumption and reduce CO_2 emissions. It is the first mass-produced, whole-building system to combine normal and low temperature refrigeration with air conditioning, heating and ventilation in one circuit.
At the coldest times of the year, all the waste heat from food refrigeration is recovered and re-used for space heating, resulting in energy savings of up to 40%. The heat recovery function of Conveni-Pack together with its optimised controls and inverter compressor technology, ensures savings of up to 60% on energy costs during one year alone.

Energy efficient heat recovery

› Conveni-Pack recovers up to 100% of the heat extracted from supermarket refrigeration cases and re-uses it to heat the retail space at no additional cost.



Benefits for the installer

› VRV technology ensuring optimised installation and maintenance
› Reduced piping requirements and installation time

Benefits for the consultant

› Flexible configurations: multiple outdoor units can be positioned to make the best use of the space available
› Outdoor units can be positioned up to 35m above or 10m below the indoor units
› The piping length can be up to 130m between the outdoor unit and the furthest refrigeration cabinet or air conditioning indoor unit
› Suitable to indoor installations through the use of high ESP fans

Benefits for the end user

› Reduced energy consumption by up to 60% through heat recovery, together with its optimised controls and inverter compressor technology
› Maximised retail sales space available as Conveni-Pack has a footprint up to 60% smaller than conventional grocery refrigeration systems
› Quiet operation, thus ideal for densely populated urban areas.

Marketing tools

Download the selection software from the Extranet > Software Downloads > Refrigeration Xpress



Compact solution

› Small footprint
› Reduced piping requirements.

Flexible system for multiple applications

› Connectable to all grocery refrigeration applications and supplied with a wide range of air conditioning indoor units to meet shop requirements.
› Ideal climate solution for small shops and petrol stations.

Quiet in operation

› Improved acoustics thanks to night operation mode, inverter control and inverter driven fans with optimised blades and grills.

Internationally awarded

Since the introduction Conveni-Pack was recognized as innovative and environmentally – proof of which are the recent German and Irish award:
› Winner of 2014 Institute of Refrigeration Ireland (IRI) Environmental award
› Case: application of Carel controls to Daikin Conveni-Pack refrigeration at a Tesco store
› Environmental Friendliness category of the Top Retail Product Awards 2014 in Germany.

References

Edeka Buschkühle supermarket (Lippstadt, Germany)
The 2 Conveni-Pack systems supply 32 meters of service counters, 12.5 meter convenience fridges, one cooling storage room for fruit, an air curtain and 5 indoor units; the ZEAS system supplies two deep-freeze cabinets with a total capacity of 5 kW.






Indoor units for connection to Conveni-Pack

To respond to all shop requirements for comfort cooling and heating, a wide range of VRV indoor units and Biddle air curtains are available.

Capacity class (kW)

Model	Product name		50	63	80	100	125	200	250
Cooling capacity (kW)[1]			5.6	7.1	9.0	11.2	14.0	22.4	28.0
Heating capacity (kW)[2]			6.3	8.0	10.0	12.5	16.0	25.0	31.5
Round flow cassette	FXFQ-A		●	●	●	●	●		
2-way blow ceiling mounted cassette	FXCQ-A		●	●	●		●		
Ceiling mounted corner cassette	FXKQ-MA			●					
Concealed ceiling unit with inverter driven fan	FXSQ-P		●	●	●	●	●		
Concealed ceiling unit with inverter driven fan	FXMQ-P7		●	●	●	●	●		
Large concealed ceiling unit	FXMQ-MA							●	●
Ceiling suspended unit	FXHQ-A			●		●			
4-way blow ceiling suspended unit	FXUQ-A					●			
Floor standing unit	FXLQ-P		●	●					
Concealed floor standing unit	FXNQ-P		●	●					

Capacity class (kW)

Model	Product Name		80	100	125	140	200	250
Heating capacity (kW)[2]			7.4 - 9.2	11.6 - 13.4	15.6	16.2 - 19.9	29.4	29.4 - 31.1
Biddle air curtain free hanging	CYVS-DK		●	●	●	●	●	●
Biddle air curtain cassette	CYVM-DK		●	●	●	●	●	●
Biddle air curtain recessed	CYVL-DK		●	●	●	●	●	●

[1] Nominal cooling capacities are based on: indoor temperature: 27°CDB / 19°CWB, outdoor temperature: 35°CDB, piping length: 7.5m, level difference: 0m
[2] Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB / 6°CWB, piping length: 7.5m, level difference: 0m
[3] Optional

CONVENI-PACK

Conveni-Pack refrigeration system with heat recovery

Refrigeration solution for food retailers featuring award winning technology for heat recovery

- Integrates high and low temperature refrigeration and air conditioning (including heating) into one system
- Lower associated CO_2 emissions thanks to the heat pump technology
- The modularity of the Conveni-Pack system maximises installation flexibility. Outdoor units can be grouped into blocks or rows, or distributed around the building, to meet individual installation constraints
- The heat extracted from the refrigeration showcases or evaporators can be re-used for comfort heating of the shop at no extra cost
- Low sound level including „night mode" operation



LRYEQ16AY1

INVERTER

Medium Temperature Refrigeration				LRYEQ-AY1	16
Cooling capacity	Air conditioning	Nom.		kW	14.0
	Refrigeration (1)	Nom.		kW	21.8
Heating capacity (2)	Air conditioning	Nom.		kW	27.0
	Refrigeration (2)	Nom.		kW	21.8
Dimensions	Unit	Height		mm	1,680
		Width		mm	1,240
		Depth		mm	765
Weight	Unit			kg	370
Heat exchanger	Type				Cross fin coil
Compressor	Type				Hermetically sealed scroll compressor
	Piston displacement			m^3/h	13.34
	Speed			rpm	6,300
	Output			W	2,500
	Starting method				Direct on line (inverter driven)
	Frequency ON/OFF				Less than 6 times/hour
Compressor 2	Speed			rpm	2,900
	Output			W	3,600
Compressor 3	Speed			rpm	2,900
	Output			W	4,500
Fan	Type				Propeller fan
	Quantity				2
	Air flow rate	Cooling	Nom.	m^3/min	230
Fan motor	Output			W	750
	Drive				Direct drive
Sound pressure level	Nom.			dBA	62.0
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-20~10
	Cooling	Ambient	Min.~Max.	°CDB	-5~43
	Heating	Ambient	Min.~Max.	°CDB	-15~21
Refrigerant	Type / GWP				R-410A / 2,087.5
	Charge			kg	11.5
	Charge			TCO_2Eq	24.0
	Control				Electronic expansion valve
Refrigerant oil	Type				Daphne FVC68D
	Charged volume			l	1.7 / 2.1 / 2.1 / 4.0
Piping connections	Refrigeration	Liquid	50m or less		Ø 9.5 C1220T
			50~130m		Ø 12.7 C1220T
		Gas	50m or less		Ø 25.4 C1220T
			50~130m		Ø 28.6 C1220T
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/380-415

(1) Cooling priority mode: evaporating temp. -10°C; outdoor temp. 32°CDB; suction SH 10°C
(2) Heat recovery 100% mode: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; refrigeration load 18kW; piping length: 7.5m; level difference: 0m

Booster unit

- A booster unit allows to connect freezer showcases or cold rooms to ZEAS and Conveni-Pack outdoor units
- Reduced piping requirements, from 4 to 2 pipes, compared to a conventional system
- Low sound mode available reducing sound emissions significantly without giving in on refrigeration capacity



LCBKQ3AV19

Low Temperature Refrigeration					LCBKQ-AV1
Cooling capacity	Nom.			kW	3.35
Dimensions	Unit	Height		mm	480
		Width		mm	680
		Depth		mm	310
Weight	Unit			kg	47
Compressor	Type				Hermetically sealed swing compressor
	Piston displacement			m^3/h	10.16
	Number of revolutions			rpm	6,540
	Output			W	1,300
	Starting method				Direct on line (inverter driven)
	Frequency ON/OFF				Less than 6 times/hour
Fan	Type				Propeller fan
	Air flow rate	Cooling	Nom.	m^3/min	1.6
Operation range	Evaporator	Cooling	Min.~Max.	°CDB	-45~-20
	Ambient temperature	Min.~Max.		°C	-15~43
Refrigerant	Type / GWP				R-410A / 2,087.5
	Control				Electronic expansion valve
Refrigerant oil	Type				Daphne FVC50K + FVC68D
	Charged volume			l	0.85 / 0.5
Piping connections	Piping length	System	Booster unit - IU		30m or less
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240

(1) Evaporating temp. -35°C; outdoor temp. 32°C; suction SH 10K; saturated temp. to discharge pressure of booster unit -10°C

Condensing unit for commercial refrigeration with reciprocating technology

Refrigeration solution for small food retailers

- Designed specifically for small capacity refrigeration applications in small food stores (eg. in bakeries and butchers), cold rooms, bottle coolers and display cabinets
- Compact and lightweight for even the smallest of city centre locations
- All components can be accessed, making maintenance quick and easy
- Ideal for urban applications: sound proofing and low operating sound levels mean the unit is quiet
- The optimised compressor range and increased condenser surface deliver high levels of energy efficiency and reliability is ensured by using high quality components and production processes
- Micro channel heat exchanger technology reduces the amount of refrigerant used in the system, lowering environmental impact



JEHCCU-CM1/CM3

Medium Temperature Refrigeration				JEHCCU-CM1/CM3	0050	0067	0100	0113	0140CM1	0140CM3
Refrigerating capacity	Medium temperature	R-404A	Nom	kW	0.910	1.225	1.495	1.761	2.220	
		R-407A	Nom	kW	0.783	1.654	1.287	1.515	1.911	
		R-407F	Nom	kW	0.882	1.187	1.449	1.706	2.151	
Power input	Medium temperature	R-404A	Nom	kW	0.626	0.763	0.927	1.102	1.235	
		R-407A	Nom	kW	0.581	0.708	0.860	1.023	1.146	
		R-407F	Nom	kW	0.611	0.744	0.904	1.075	1.204	
COP	Medium temperature	R-404A			1.45	1.61	1.61	1.60	1.80	
		R-407A			1.35	1.49	1.50	1.48	1.67	
		R-407F			1.44	1.60	1.60	1.59	1.79	
Dimensions	Unit	Height		mm	607				662	
		Width		mm	876				1,101	
		Depth		mm	420				444	
Weight	Unit			kg	45	54		55	67.5	
Compressor	Type				Reciprocating compressor					
	Model				AE4460Z-FZ1C	CAJ9480Z	CAJ9510Z	CAJ9513Z	CAJ4517Z	TAJ4517Z
	Piston displacement			m^3/h	1.80	2.64	3.18	4.21	4.52	
	Oil	Charged volume		l	0.28	0.887				
	Oil Type				Uniqema Emkarate RL32CF					
Fan	Air flow rate	Cooling	Nom	m^3/h	1,300				2,700	
Sound pressure level	Nom.			dBA	30				34	
Refrigerant	Type / GWP				R-404A / 3,921.6					
	Type 2 / GWP 2				R-407A / 2,107					
	Type 3 / GWP 3				R-407F / 1,825					
Piping connections	Liquid line connection			inch	1/4"	3/8"				
	Suction line connection			inch	3/8	1/2				
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230					3~/50/400

(1) Refer to condition: Outside ambient temperature = 32°C, Evaporation temperature = -10°C and 10K superheat (medium temperature application)

Condensing unit for commercial refrigeration with scroll technology

Refrigeration solution for small food retailers

- Designed specifically for small capacity refrigeration applications in small food stores (eg. in bakeries and butchers), cold rooms, bottle coolers and display cabinets
- Compact and lightweight for even the smallest of city centre locations
- All components can be accessed, making maintenance quick and easy
- Ideal for urban applications: sound proofing and low operating sound levels mean the unit is quiet
- The optimised compressor range and increased condenser surface deliver high levels of energy efficiency and reliability is ensured by using high quality components and production processes
- Micro channel heat exchanger technology reduces the amount of refrigerant used in the system, lowering environmental impact



JEHSCU-CM1/CM3

Medium Temperature Refrigeration				JEHSCU-CM1/CM3	0200CM1	0200CM3	0250CM1	0250CM3	0300CM1	0300CM3	0350CM3
Refrigerating capacity	Medium temperature	R-134a	Nom	kW	2.170		2.480		3.060		3.480
		R-404A	Nom	kW	3.490		4.210		4.890		5.460
		R-407A	Nom	kW	3.306		3.971		4.684		5.007
		R-407F	Nom	kW	3.297		3.971		4.712		4.902
Power input	Medium temperature	R-134a	Nom	kW	1.025		1.165		1.455		1.675
		R-404A	Nom	kW	1.695		2.035		2.515		3.065
		R-407A	Nom	kW	1.676		2.017		2.457		2.996
		R-407F	Nom	kW	1.679		2.026		2.477		3.425
COP	Medium temperature	R-134a			2.12		2.13		2.10		2.08
		R-404A			2.06		2.07		1.94		1.78
		R-407A			1.97		1.97		1.91		1.67
		R-407F			1.96		1.96		1.90		1.43
Dimensions	Unit	Height		mm	662						
		Width		mm	1,101						
		Depth		mm	444						
Weight	Unit			kg	69.7		71.7		73.7		
Compressor	Type				Scroll compressor						
	Model				ZB15KQE-PFJ	ZB15KQE-TFD	ZB19KQE-PFJ	ZB19KQE-TFD	ZB21KQE-PFJ	ZB21KQE-TFD	ZB26KQE-TFD
	Piston displacement			m^3/h	5.90		6.80		8.60		9.90
	Oil	Charged volume		l	1.24		1.30	1.36	1.45		1.5
	Oil Type				Polyester oil						
Fan	Air flow rate	Cooling	Nom	m^3/h	2,700						
Sound pressure level	Nom.			dBA	33		36				40
Refrigerant	Type / GWP				R-134a / 1,430						
	Type 2 / GWP 2				R-404A / 3,921.6						
	Type 3 / GWP 3				R-407A / 2,107						
	Type 4 / GWP 4				R-407F / 1,825						
Piping connections	Liquid line connection			inch	3/8"						
	Suction line connection			inch	3/4						
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/230	3~/50/400	1~/50/230	3~/50/400	1~/50/230	3~/50/400	

(1) Refer to condition: Outside ambient temperature = 32°C, Evaporation temperature = -10°C and 10K superheat (medium temperature application) (2) Sound pressure level is measured at 10m in anechoic room

JEHCCU-M3/L1/L3
JEHSCU-M3/L3

Condensing unit for commercial refrigeration



Main benefits

› Low operation sound level
› Easy to install - fully equipped - packaged
› Energy efficiency and performance
› Robust and reliable design

Installer benefits

› Small, compact and robust for easy handling and installation in limited space
› Fully factory tested and pre-wired electrical box for quick and easy installation and commissioning
› Easy service thanks to very accessible components behind removable robust panels

End-user benefits

› Very quiet operation
› Strong anti-corrosion housing for long life, even in harsh environmental conditions
› Trustworthy units, with proven component reliability and fully qualified for the most demanding applications
› Reduced energy consumption, thanks to efficient compressors and condenser fan speed control (except series 1)
› Fully packaged unit at a competitive price

Series		Model	Performance					Compressor			O/S[d]	Oil type	Electrical Data							Airflow m³/h	Receiver	Connection		Dimensions			Weight (kg)	Sound pressure dB(A) at 1m[c]
			Cooling capacity (W) [a] R-404A	Cooling capacity (W) [a] R-134a	Cooling capacity (W) [a] R-407A	Cooling capacity (W) [a] R-407C	Cooling capacity (W) [a] R-407F	Type	Swept volume (m³/h)	Oil Charge (Liter)	Oil Charge (l)		Power input	Lock Rotor current (A)	MFA[b] (A) R-404A	R-134a	R-407A	R-407C	R-407F		Volume (Liter)	Suction (inch)	Liquid (inch)	Width (mm)	Depth (mm)	Height (mm)		
Medium temperature	3	JEHCCU0400M3	6,672	3,934	6,201	5,766	6,590	MTZ50-4VM	14.90	1.80	-	Oil B[f]	400V/3~/50Hz	48.5	15	15	15	15	15	6050	7.6	7/8	1/2	1347	556	884	122	57
		JEHCCU0500M3	8,017	4,546	7,620	7,137	8,042	MTZ64-4VM	18.94	1.80	-		400V/3~/50Hz	64.0	20	20	20	20	20	6050	7.6	7/8	1/2	1347	556	884	122	60
		JEHCCU0600M3	8,897	5,680	8,452	7,660	8,843	MTZ72-4VM	21.04	1.80	-		400V/3~/50Hz	80.0	20	20	20	20	20	5180	7.6	7/8	1/2	1347	556	884	126	60
		JEHCCU0675M3	9,756	6,153	9,268	8,930	10,097	MTZ81-4VM	23.63	1.80	-		400V/3~/50Hz	80.0	20	20	20	20	20	5180	7.6	1 1/8	1/2	1352	556	884	126	62
	4	JEHCCU0825M3	11,010	7,083	10,459	9,867	11,445	MTZ100-4VM	29.80	3.90	-		400V/3~/50Hz	90.0	25	25	25	25	25	6770	14.0	1 1/8	1/2	1261	594	1435	205	62
		JEHCCU1000M3	13,528	8,667	12,851	13,038	14,126	MTZ125-4VM	37.49	3.90	-		400V/3~/50Hz	105.0	30	25	30	30	30	6770	14.0	1 1/8	1/2	1261	594	1435	205	62
	1	JEHCCU0075L1	418	-	-	-	-	SC18CLX	3.08	0.60	-	Oil A[e]	230V/1~/50Hz	20.0	15	-	15	-	15	1910	1.2	3/8	1/4	884	430	489	46	50
Low temperature	2	JEHCCU0175L1	947	-	-	-	-	NTZ48-5VM	8.40	0.95	0.50	Oil B[f]	230V/1~/50Hz	37.0	15	-	15	-	15	3040	4.6	5/8	3/8	1104	478	650	86	55
		JEHCCU0175L3	947	-	-	-	-	NTZ48-4VM	8.40	0.95	0.50		400V/3~/50Hz	16.0	15	-	15	-	15	3040	4.6	5/8	3/8	1104	478	650	86	55
		JEHCCU0225L1	1,567	-	-	-	-	NTZ68-5VM	11.80	0.95	0.50		230V/1~/50Hz	53.0	20	-	20	-	20	2620	4.6	5/8	3/8	1104	478	650	92	58
		JEHCCU0225L3	1,567	-	-	-	-	NTZ68-4VM	11.80	0.95	0.50		400V/3~/50Hz	25.0	15	-	15	-	15	2620	4.6	5/8	3/8	1104	478	650	92	58
	3	JEHCCU0350L3	1,845	-	-	-	-	NTZ96-4VM	16.70	1.80	0.60		400V/3~/50Hz	32.0	15	-	15	-	15	6050	7.6	7/8	1/2	1347	556	884	125	58
		JEHCCU0400L3	2,824	-	-	-	-	NTZ136-4VM	23.60	1.80	0.60		400V/3~/50Hz	51.0	15	-	15	-	15	6050	7.6	1 1/8	1/2	1352	556	884	130	58
	4	JEHCCU0725L3	4,245	-	-	-	-	NTZ215-4VM	37.50	3.90	0.60		400V/3~/50Hz	74.0	25	-	25	-	25	6770	14.0	1 1/8	1/2	1261	594	1435	203	61
		JEHCCU0825L3	5,818	-	-	-	-	NTZ271-4VM	47.30	3.90	0.60		400V/3~/50Hz	96.0	25	-	25	-	25	6770	14.0	1 1/8	1/2	1261	594	1435	203	60
Medium Temperature	3	JEHSCU0400M3	6,690	4,300	6,869	-	7,180	ZB29KQE-TFD	11.4	1.36	-	Oil B[h]	400V/3~/50Hz	50.0	15	15	15	-	15	6050	7.6	7/8	1/2	1347	556	884	121	54
		JEHSCU0500M3	8,050	5,150	8,275	-	8,700	ZB38KQE-TFD	14.4	2.07	-		400V/3~/50Hz	65.5	20	15	20	-	20	6050	7.6	7/8	1/2	1347	556	884	126	55
		JEHSCU0600M3	9,150	6,150	9,272	-	10,050	ZB45KQE-TFD	17.1	1.89	-		400V/3~/50Hz	74.0	20	15	20	-	20	5180	7.6	7/8	1/2	1347	556	884	128	60
		JEHSCU0680M3	9,850	6,928	10,744	-	11,192	ZB48KQE-TFD	18.8	1.80	-		400V/3~/50Hz	101.0	20	20	20	-	20	5180	7.6	7/8	1/2	1347	556	884	129	60
	4	JEHSCU0800M3	12,000	7,800	11,543	-	11,790	ZB58KCE-TFD	22.1	2.50	-		400V/3~/50Hz	95.0	25	20	25	-	25	6770	14.0	1 1/8	1/2	1261	594	1435	201	64
		JEHSCU1000M3	14,200	9,900	14,630	-	15,075	ZB76KCE-TFD	29.1	3.20	-		400V/3~/50Hz	118.0	35	25	35	-	35	6770	14.0	1 3/8	1/2	1261	594	1435	201	64
Low Temperature	2	JEHSCU0200L3	1,260	-	-	-	1,188	ZF06K4E-TFD	5.9	1.30	0.50	Oil B[h]	400V/3~/50Hz	26.0	15	-	15	-	15	2620	4.6	3/4	3/8	1108	478	650	94	47
		JEHSCU0300L3	1,645	-	1,701	-	1,615	ZF09K4E-TFD	8.0	1.50	0.50		400V/3~/50Hz	40.0	15	-	15	-	15	2620	4.6	3/4	3/8	1108	478	650	96	48
	3	JEHSCU0400L3	2,485	-	2,090	-	2,280	ZF13K4E-TFD	11.8	1.90	0.60		400V/3~/50Hz	51.5	15	-	15	-	15	6050	7.6	7/8	1/2	1347	556	884	129	55
		JEHSCU0500L3	3,000	-	2,632	-	2,774	ZF15K4E-TFD	14.5	1.90	0.60		400V/3~/50Hz	64.0	15	-	15	-	15	6050	7.6	7/8	1/2	1347	556	884	130	56
		JEHSCU0600L3	3,600	-	3,145	-	3,335	ZF18K4E-TFD	17.1	1.90	0.60		400V/3~/50Hz	74.0	15	-	15	-	15	6050	7.6	7/8	1/2	1347	556	884	130	61
	4	JEHSCU0750L3	4,320	-	-	-	-	ZF24K4E-TWD	20.9	4.10	0.60		400V/3~/50Hz	99.0	20	-	20	-	20	6770	14.0	1 3/8	1/2	1261	594	1435	218	61
		JEHSCU1000L3	5,850	-	-	-	-	ZF33K4E-TWD	28.8	4.10	0.60		400V/3~/50Hz	127.0	30	-	30	-	30	6770	14.0	1 3/8	1/2	1261	594	1435	218	62

[a] Refer to condition: Outside ambient temperature= 32°C, Evaporation temperature = -10°C (medium temperature application); -35°C (low temperature application)
[b] MFA = Maximum Fuse Amps
[c] Sound pressure level measured in anechoic room
[d] O/S = Oil Separator
[e] Oil A = Polyester oil (Emkarate RL32H)ww
[f] Oil B = Polyester oil 160PZ
[g] Oil A = Polyester oil (Copeland Ultra 22 CC, Copeland Ultra 32 CC, Copeland Ultra 32-3MAF, Mobil EAL™ Arctic 22 CC, Uniqema Emkarate RL32CF)
[h] Oil B = Mobil Arctic 22CC
Note: condensing units are pre-charged with oil as stated in table
R-134a GWP = 1,430, R-407C GWP=1,773.85, R-407A GWP=2,107, R-407F GWP=1,825, R-404A GWP= 3,921.6

Condensing unit for industrial refrigeration



Designed for outdoor use, the large condensing units are a perfect medium to high capacity refrigeration solution for cold stores, distribution platforms, supermarkets, food processing, etc in low and medium temperature applications.


These industrial condensing units are real workhorses designed for maximum performance in minimum space.


- High energy efficiency: inverter controlled compressor, economizer, high performance condenser
- Possibility of having a stand-by compressor
- Easy installation, ready to connect evaporators
- Integrated starter and control panel with electronic controller
- Space saving construction due to the compact design of the condenser coils arranged in a 'W' configuration
- Low sound operation
- Approved according to EN 378: 2008 (Safety and environmental requirements)
- Refrigerants: R-404A, R-134a, R-407C, R-507A


A comprehensive product range with 1 or 2 compressors and 4, 6, 8 or 10 condenser fans

- Chilled application:
  R-404A | 113 - 417 kW
  R-134a | 72.5 kW - 315.4 kW
  R-407C | 100.3 kW - 430.2 kW
  (at T0 = -10°C / Tamb = +32°C)
- Frozen application:
  R-404A | 37 - 159 kW
  (at T0 = -35°C / Tamb = +32°C)


* R-134a GWP = 1,430, R-407C GWP=1,773.85, R-507A GWP=3,985, R-404A GWP=3,921.6







	Length	Width	Height	Weight
	mm	mm	mm	kg
From	2,240	2,235	2,340	2,405
To	4,940	2,235	2,340	4,496



Control Systems

Control Systems

Individual control systems	417
Wired / infrared remote controls	417
Online controller	420
Centralised control systems	422
Centralised remote control / Unified ON/OFF control / Schedule timer	422
DS-net	423
intelligent Touch Controller	423
Mini building management system	417
intelligent Touch Manager	424
Standard protocol interfaces	417
Modbus interface	426
KNX Interface	430
BACnet Interface	431
LonWorks Interface	432
Daikin Configuration Software	433
EKPCCAB3	433
Remote monitoring and maintenance	
ACNSS	434

Options & Accessories 436


Wireless room temperature sensor	436
Wired room temperature sensor	436
Other integration devices	437



ONLINE CONTROLLER



WIRED REMOTE CONTROL
BRC1E52A



INTELLIGENT
TOUCH MANAGER
DCM601A51



INFRARED REMOTE
CONTROLLER


BRC1D52


BRC944B2


ARC466A1


BRC4*/BRC7*

BRC944B2*/BRC1D52

Wired remote control

› Schedule timer:
Five day actions can be set as follows:
- set point: unit is switched ON and normal operation is maintained
- OFF: unit is switched OFF1
- limits: unit is switched ON and min./max. control (cf. limit operation for more details)

› Home leave (frost protection): during absence, the indoor temperature can be maintained at a certain level. This function can also switch the unit ON/OFF
› User friendly HRV function, thanks to the introduction of a button for ventilation mode and fan speed
› Constantly monitoring of the system for malfunctions in a total of 80 components
› Immediate display of fault location and condition
› Reduction of maintenance time and costs

Display

› Operating mode[1]
› Heat Recovery Ventilation (HRV) in operation
› Cool / heat changeover control
› Centralised control indication
› Group control indication
› Set temperature[1]
› Air flow direction[1]
› Programmed time
› Inspection test / operation
› Fan speed[1]
› Clean air filter
› Defrost / hot start
› Malfunction

[1] Only functions marked with '1' are available on BRC944B2

ARC4*/BRC4*/BRC7*

Infrared remote control

Operation buttons: ON / OFF, timer mode start / stop, timer mode on / off, programme time, temperature setting, air flow direction (1), operating mode, fan speed control, filter sign reset (2), inspection (2)/ test indication (2)
Display: Operating mode, battery change, set temperature, air flow direction (1), programmed time, fan speed, inspection / test operation (2)

1. Not applicable for FXDQ, FXSQ, FXNQ, FBDQ, FDXS, FBQ
2. For FX** units only
3. For all features of the remote control, refer to the operation manual

BRC2E52A / BRC3E52A NEW

Simplified wired remote control developed for hotel applications


› Symbol driven interface for intuitive control
› Functions restricted to basic customer needs
› Contemporary design
› Energy saving thanks key card, window contact integration and set point limitation
› Flexible setback function ensures room temperature remains within comfortable limits to ensure guest comfort
› Flat backpanel for easy installation
› Easy commissioning: intuitive interface for advanced menu settings
› 2 versions available:
  • Heat pump type: temperature, fan speed, ON/OFF
  • Heat recovery type: temperature, mode, fan speed, ON/OFF
› Replaces existing BRC2C51 & BRC3A61





User friendly remote control with contemporary design

BRC1E52A/B



Graphical display of indicative electricity consumption (Function available in combination with FCQG and FCGHQ)

A series of energy saving functions that can be individually selected

› Temperature range limit
› Setback function
› Presence & floor sensor connection (available on new round flow cassette)
› kWh indication
› Set temperature auto reset
› Off timer

Temperature range limit avoids excessive heating or cooling

Save energy by constraining the lower temperature limit in cooling and upper temperature limit in heating mode.

note : Also available in auto cooling/heating change over mode.

kWh indication keeps track of your consumption

The kWh indication shows an indicative electricity consumption of the last day/month/year.

Other functions

› Up to 3 independent schedules can be set, so the user can easily change the schedule himself throughout the year (e.g. Summer, winter, mid-season)
› Possibility to individually restrict menu functions Easy to use: all main functions directly accessible
› Easy setup: clear graphical user interface for advanced menu settings
› Real time clock with auto update to daylight saving time
› Built-in backup power: when a power failure occurs all settings remain stored up to 48 hours
› Supports multiple languages
English, German, Dutch, Spanish, Italian, Portuguese, French, Greek, Russian, Turkish, Polish (BRC1E52A)
English, German, Czech, Croatian, Hungarian, Romanian, Slovenian, Bulgarian, Slovak, Serbian, Albanian (BRC1E52B)

Daikin Altherma low temperature wired remote control

EKRUCBL1-7



The Daikin Altherma low temperature is equipped with an advanced user interface.
Commissioning, servicing and day-to-day operation become straightforward.
The multi-lingual and graphical interface provides full-text representation, easy menu navigation and intelligent control features

› Self-explanatory controller for easy and quick commissioning
› Possibility of preparing and uploading field settings via a PC
› Feedback on operation conditions and energy consumption

Siesta individual control systems

ARCWLA / ARCWB

Overview controllers for Siesta Sky Air

Siesta Sky Air indoor units	Controllers
ACQ-D 4-way blow, ceiling mounted cassette	• Standard infrared remote control (ARCWLA) in box of decoration panel ADP125A • Optional wired remote control ARCWB • Optional group controller R04084124324
AHQ-C ceiling suspended	• Standard infrared remote control in box of indoor unit ARCWLA • Optional wired remote control ARCWB • Optional group controller R04084124324
ABQ-C concealed ceiling	• Standard wired remote control (ARCWB) in box of indoor unit • Optional group controller R04084124324

Overview of features

	Feature		ARCWB
			Option for AHQ-C and ACQ-D Standard for ABQ-C
			
1	ON/OFF switch		Standard
2	Temperature setting	Default range 16-30°C	Standard
		Optional range 20-30°C	By dipswitch selection
		Switch between °C and °F	Standard
3	Room temperature sensor on remote control		Standard
4	Cool / Fan dry / Heat / Auto		Standard
5	Sleep mode		Standard
6	Fan Speed selection		Standard
7	Delay timer		1, 2 & 4 hours delay
8	7-days programmable timer		Standard
9	Real time clock display		Standard
10	Air swing selection	ON/OFF swing mode	Standard
		Change swing option (draft/soil prevention or standard)	Standard
11	LCD display without backlight		Standard
12	Key lock		Standard
13	Error code indication		Standard
14	IR receiver to enable compatibility with infrared remote control (disabled when lock function is activated)		Standard
15	Last state memory from indoor PCB		Standard
16	Silent mode		By dipswitch selection
17	Turbo mode		By dipswitch selection
18	Compressor test model (compressor force ON)		Standard
19	Daikin inverter error code		Standard
20	UART communication port (for Daikin protocol)		Standard
21	Backup battery		Standard

Specifications


› Dimensions (length x width x height) ARCWB: 0.15 m x 0.21 m x 0.04 m.
› ARCWB comes standard with a 10 meter wire, which can be extended to maximum wire length of 15 meter. ARCWB can only control one indoor unit at a time; group control is only possible when using option R04084124324.

Online controller


BRP069A41/42

Always in control,

no matter where you are



The plug-and-play Online Controller allows you to set and even schedule the temperature from anywhere using Apple or Android systems. So you can manage the unit when away from home, offering optimal climate control while saving energy.



With the Daikin Online Controller application in combination with the plug-and-play wireless LAN device and an active internet connection, you can manage your unit from anywhere, offering optimal climate control while saving energy.

The Daikin Online Controller application can control and monitor the status of up to 50 units and allows you to:

- Monitor the status of your heat pump unit
- Control the operation mode, set temperature, air flow rate and direction
- Schedule the set temperature and operation mode with up to 4 actions per day for 7 days

Connectable indoor units

BRP069A41

- FTXG-LW/S
- FTXJ-LW/S

BRP069A42

- FTXZ-N (available January '15)
- FTXS-K
- FTXM-K
- FTXS-G
- ATXS-K
- FTX-J3
- FTX-GV
- FTX-K
- ATX-J3
- FVXG-K
- FVXS-K
- FLXS-B
- FTXLS-K
- FTXL-JV
- ATXL-JV

Features Online Controller

The Daikin online controller can manage your unit in several ways.


You can operate it in-home by connecting your smartphone to a private wireless network or out-of-home by connecting your smartphone to a mobile network (e.g. 3G) or an external wireless network.

Connection	Between WLAN adaptor & indoor unit via S21 connector	BRP069A41	BRP069A42
Operation modes	Start	•	•
	Stop	•	•
	Automatic	•	•
	Cooling	•	•
	Heating	•	•
	Dry	•	•
	Fan Only	•	•
Temperature	Set point adjustment	•	•
Weekly schedule timer	Start/stop operation	•	•
	Select operation mode	•	•
	Set temperatures set point	•	•
	4 actions per day (max. 28 actions)	•	•
Fan	Set air flow	•	•
	Set air flow direction	•	•
General information	Current room temperature	•	•
	Current outdoor temperature	•	• (if unit is turned on)
	Remote adapter software updates	•	•
	Mulit-language interface	•	•
	Automatic time update (daylight saving time)	•	•
	Demo function	•	•

Centralised control of the Sky Air and VRV system can be achieved via 3 user friendly compact.
These controls may be used independently or in combination with 1 group = several (up to 16) indoor units in combination and 1 zone = several groups in combination.
A centralised remote control is ideal for use in tenanted commercial buildings subject to random occupation, enabling indoor units to be classified in groups per tenant (zoning).
The schedule timer programmes the schedule and operation conditions for each tenant and the control can easily be reset according to varying requirements.

DCS302C51

Centralised remote control



Providing individual control of 64 groups (zones) of indoor units.

› a maximum of 64 groups (128 indoor units, max. 10 outdoor units) can be controlled
› a maximum of 128 groups (128 indoor units, max. 10 outdoor units) can be controlled via 2 centralised remote controls in separate locations
› zone control
› group control
› malfunction code display
› maximum wiring length of 1,000m (total: 2,000m)
› air flow direction and air flow rate of HRV can be controlled
› expanded timer function

DCS301B51

Unified ON/OFF control



Providing simultaneous and individual control of 16 groups of indoor units.

› a maximum of 16 groups (128 indoor units) can be controlled
› 2 remote controls in separate locations can be used
› operating status indication (normal operation, alarm)
› centralised control indication
› maximum wiring length of 1,000m (total: 2,000m)

DST301B51

Schedule timer




Enabling 64 groups to be programmed.

› a maximum of 128 indoor units can be controlled
› 8 types of weekly schedule
› a maximum of 48 hours back up power supply
› a maximum wiring length of 1,000m (total: 2,000m)

DTA113B51

Basic solution for control of Sky Air and VRV


› Rotation function
› Backup operation function.



intelligent touch Controller

DCS601C51

Detailed & easy monitoring and operation of VRV systems (max. 64 indoor units groups).



Languages
› English
› French
› German
› Italian
› Spanish
› Dutch
› Portuguese

System layout
› Up to 64 indoor units can be controlled
› Touch panel (full colour LCD via icon display)

Management
› Easy management of electricity consumption
› Enhanced history function

Control
› Individual control (set point, start/stop, fan speed) (max. 64 groups/indoor units)
› Set back shedule
› Enhanced scheduling function (8 schedules, 17 patterns)
› Flexible grouping in zones
› Yearly schedule
› Fire emergency stop control
› Interlocking control
› Increased HRV monitoring and control function
› Automatic cooling / heating change-over
› Heating optimization
› Temperature limit
› Password security: 3 levels (general, administration & service)
› Quick selection and full control
› Simple navigation

Monitoring
› Visualisation via Graphical User Interface (GUI)
› Icon colour display change function
› Indoor units operation mode
› Indication filter replacement
› Multi PC

Cost performance
› Free cooling function
› Labour saving
› Easy installation
› Compact design: limited installation space
› Overall energy saving

Open interface
› Communication to any third party controller (domotics, BMS, etc.) is possible via open interface (http option)

Connectable to
› VRV
› HRV
› Sky Air
› Split (via interface adapter)

NEW Mini Building Management System

intelligent touch Manager

DCM601A51

Mini BMS

with full integration across all product pillars

- Price competitive mini BMS
- Cross-pillar integration of Daikin products
- Integration of third party equipment

System overview



Web Access

Internet
Extranet
LAN
3G
http interface



Integration of third party equiqment

Fire alarm

kWh meter

Di/Pi line
Max. 200m

intelligent touch Manager

DCM601A51



Full control of Daikin HVAC-R portfolio


ITM plus adaptor line

Max. 7 adapters



DCM601A52

Di/Pi port



Direct plug & play connection!

BACnet protocol

WAGO interface

Lighting

Fan

Pump

Sensor

I/O module

I/O module

Multi state objects

Elevator

Air handling unit

Alarm

Split
Sky Air
VRV
indoor units,
air curtain,
hydrobox,
air handling units



Fan coil units







Chillers and AHU






Refrigeration








touch intelligent Manager

User friendliness

› Intuitive user interface
› Visual lay out view and direct access to indoor unit main funtions
› All functions direct accessible via touch screen or via web interface




Smart energy management

› Monitoring if energy use is according to plan
› Helps to detect origins of energy waste
› Powerful schedules guarantee correct operation throughout the year
› Save energy by interlocking A/C operation with other equiment such as heating


Flexibility

NEW › Cross-pillar integration (heating, air conditioning, applied systems, refrigeration, air handling units)
NEW › BACnet protocol for 3rd party products integration
› I/O for integration of equipment such as lights, pumps… on WAGO modules
› Modular concept for small to large applications
› Control up to 2,560 indoor unit groups



Easy servicing and commissioning

› Remote refrigerant containment check preventing on site visit
› Simplified troubleshooting
› Save time on commissioning thanks to the pre-commissioning tool
› Auto registration of indoor units



Functions overview



Languages
› English
› French
› German
› Italian
› Spanish
› Dutch
› Portuguese

System layout
› Up to 2,560 unit groups can be controlled (ITM plus Integrator + 7 iPU (incl. iTM adaptor)
› Ethernet TCPIP

Management
› Web access
› Power Proportional Distribution (option)
› Operational history (malfunctions, operation hours, …)
› Smart energy management
- monitor if energy use is according to plan
- detect origins of energy waste
› Setback function
› Sliding temperature

Control
› Individual control (2,560 groups)
› Schedule setting (Weekly schedule, yearly calender, seasonal schedule)
› Interlock control
› Setpoint limitation
› Temperature limit

WAGO Interface
› Modular integration of 3rd party equipment
- WAGO coupler (interface between WAGO and Modbus)
- Di module
- Do module
- Ai module
- Thermistor module

Connectable to
- DX Split, Sky Air, VRV
- Chillers (via POL638.70 controller)
NEW - Daikin AHU
- Fan coils
- Daikin Altherma Flex type
- LT and HT hydroboxes
- Air curtains
- WAGO I/O
NEW - BACnet protocol

Modbus Interface

RTD

RTD-RA

› Modbus interface for monitoring and control of residential indoor units

RTD-NET

› Modbus interface for monitoring and control of Sky Air, VRV, VAM and VKM

RTD-10

› Advanced integration into BMS of Sky Air, VRV, VAM and VKM through either:
- Modbus
- Voltage (0-10V)
- Resistance

› Duty/standby function for server rooms

RTD-LT/CA

› Modbus interface for monitoring and control of Daikin Altherma low temperature (EHVH(X)-C / EHBH(X)-C)
› Voltage and resistance control
› Photovoltaic operation signal for energy saving

RTD-20

› Advanced control of Sky Air, VRV, VAM/VKM and air curtains
› Clone or independent zone control
› Increased comfort with integration of CO_2 sensor for fresh air volume control
› Save on runningcosts via
- pre/post and trade mode
- set point limitation
- overall shut down
- PIR sensor for adaptive deadband

RTD-HO


› Modbus interface for monitoring and control of Sky Air, VRV, VAM and VKM
› Intelligent hotel room controller

RTD-W

› Modbus interface for monitoring and control of Daikin Altherma Flex Type, VRV HT hydrobox and small inverter chiller



Overview functions







Main functions			RTD-RA	RTD-NET	RTD-10	RTD-20	RTD-HO
Dimensions	H x W x D	mm	80 x 80 x 37,5	100 x100 x 22			
Key card + window contact							✓
Set back function			✓				✓
Prohibit or restrict remote control functions (setpoint limitation, ...)			✓	✓	✓	✓**	✓
Modbus (RS485)			✓	✓	✓	✓	✓
Group control			✓(1)	✓	✓	✓	✓
0 - 10 V control					✓	✓	
Resistance control					✓	✓	
IT application			✓		✓		
Heating interlock					✓	✓	
Output signal (on/defrost, error)					✓	✓****	✓
Retail application						✓	
Partitioned room control						✓	
Air curtain				✓***	✓***	✓	

(1): By combining RTD-RA devices

Control functions	RTD-RA	RTD-NET	RTD-10	RTD-20	RTD-HO
On/Off	M,C	M	M,V,R	M	M*
Set point	M	M	M,V,R	M	M*
Mode	M	M	M,V,R	M	M*
fan	M	M	M,V,R	M	M*
Louver	M	M	M,V,R	M	M*
HRV Damper control		M	M,V,R	M	
Prohibit/Restrict functions	M	M	M,V,R	M	M*
Forced thermo off	M				

Monitoring functions	RTD-RA	RTD-NET	RTD-10	RTD-20	RTD-HO
On/Off	M	M	M	M	M
Set point	M	M	M	M	M
Mode	M	M	M	M	M
fan	M	M	M	M	M
Louver	M	M	M	M	M
RC temperature		M	M	M	M
RC mode		M	M	M	M
nbr units		M	M	M	M
Fault	M	M	M	M	M
Fault code	M	M	M	M	M
Return air temperature (Average /Min/Max)	M	M	M	M	M
Filter alarm		M	M	M	M
Termo on	M	M	M	M	M
Defrost		M	M	M	M
Coil In/Out temperature	M	M	M	M	M




Main functions			RTD-W	RTD-LT/CA
Dimensions	H x W x D	mm	100x100x22	
On/off prohibition			✓	✓
Modbus RS485			✓	✓
Dry contact control			✓	✓
Output signal (operation error)			✓	✓
Space heating / cooling operation			✓	✓
Domestic hot water control			✓	✓
Smart Grid control				✓

Control functions		
On/Off Space heating/cooling	M,C	M,C,V
Set point leaving water temperature (heating / cooling)	M,V	M,R,V
Room temperature setpoint	M	M
Operation mode	M	M
Domestic Hot water ON		M,C,V
Domestic Hot Water reheat	M,C	M,C
Domestic Hot Water reheat setpoint		M,R,V
Domestic Hot Water storage	M	
Domestic Hot Water Booster setpoint		M
Quiet mode	M,C	M,C
Weather dependent setpoint enable	M	M
Weather dependent curve shift	M	M
Fault/pump info relay choice		R
Control source prohibition	M	M

Smart grid mode control		
Prohibit Space heating/cooling		C
Prohibit DHW		C
Prohibit Electric heaters		C
Prohibit All operation		C
PV available for storage		C
Powerful boost		C


Monitoring functions		
On/Off Space heating/cooling	M,C	M,C
Set point leaving water temperature (H/C)	M	M
Room temperature setpoint	M	M
Operation mode	M	M
Domestic Hot Water reheat	M	M
Domestic Hot Water storage	M	M
Number of units in the group	M	M
Average leaving water temperature	M	
Remocon room temperature	M	M
Fault	M,C	M,C
Fault code	M	M
Circulation pump operation	M	M,C
Flow rate		M
Solar pump operation		M
Compressor status	M	M
Desinfection operation	M	M
Setback operation	M	
Defrost/ start up	M	M
Hot start		M
Booster Heater operation		M
3-Way valve status		M
Pump running hours accumulated	M	M
Compressor running hours accumulated		M
Actual leaving water temperature	M	M
Actual return water temperature	M	M
Actual DHW tank temperature (*)	M	M
Actual refrigerant temperature		M
Actual outdoor temperature	M	M

M : Modbus / R : Resistance / V : Voltage / C: control
* : only when room is occupied / ** : setpoint limitation / (*) if available
*** : no fan speed control on the CYV air curtain / **** : run & fault

DIII-net Modbus interface


EKMBDXA

Integrated control system for seamless connection between Sky Air and VRV and BMS systems



› Communication via Modbus RS485 protocol
› Detailed monitoring and control of the VRV total solution
› Easy and fast installation via DIII-net protocol
› As the Daikin DIII-net protocol is used only one modbus interface is needed per Daikin






			EKMBDXA7V1
Maximum number of connectable indoor units			64
Maximum number of connectable outdoor units			10
Communication	DIII-NET - Remark		DIII-NET (F1F2)
	Protocol - Remark		2 wire; communication speed: 9600 bps or 19200 bps
	Protocol - Type		RS485 (modbus)
	Protocol - Max. Wiring length	m	500
Dimensions	HeightxWidthxDepth	mm	124x379x87
Weight		kg	2.1
Ambient temperature - operation	Max.	°C	60
	Min.	°C	0
Installation			Indoor installation
Power supply	Frequency	Hz	50
	Voltage	V	220-240

Modbus interface

Integrate chillers, fan coil units and air handling units in BMS systems via modbus protocol



(1) The communication module is integrated in the controller (2) Connection to FWV-D, FWL-D & FWM-D (3) Connection to FWV-D, FWL-D, FWM-D and to FWZ-A, FWR-A, FWS-A

Integrate Refrigeration units in BMS systems via modbus protocol



* For all connectable indoor units and Biddle air curtains please refer to the Conveni-pack pages in this catalogue

KNX interface


KLIC-DD
KLIC-DI

Integration of Split, Sky Air and VRV in HA/BMS systems

Connect split indoor units to KNX interface for Home Automation system



Connect Sky Air / VRV indoor units to KNX interface for BMS integration



KNX interface line-up

The integration of Daikin indoor units through the KNX interface allows monitoring and control of several devices, such as lights and shutters, from one central controller. One particularly important feature is the ability to programme a 'scenario' - such as "Home leave" - in which the end-user selects a range of commands to be executed simultaneously once the scenario is selected. For instance in "Home leave", the air conditioner is off, the lights are turned off, the shutters are closed and the alarm is on.


KNX interface for

	 KLIC-DD Size 45x45x15mm	 KLIC-DI Size 90x60x35mm	
	Split	Sky Air	VRV
Basic control			
On/Off	●	●	●
Mode	Auto, heat, dry, fan, cool	Auto, heat, dry, fan, cool	Auto, heat, dry, fan, cool
Temperature	●	●	●
Fan speed levels	3 or 5 + auto	2 or 3	2 or 3
Swing	Stop or movement	Stop or movement	Swing or fixed positions (5)
Advanced functionalities			
Error management	Communication errors, Daikin unit errors		
Scenes	●	●	●
Auto switch off	●	●	●
Temperature limitation	●	●	●
Initial configuration	●	●	●
Master and slave configuration		●	●

BACnet Interface

Integrated control system for seamless connection between VRV, applied systems, air handling units and BMS systems


- Interface for BMS system
- Communication via BACnet protocol (connection via Ethernet)
- Unlimited sitesize
- Easy and fast installation
- PPD data is available on BMS system (only for VRV)



LonWorks Interface

Open network integration of VRV and applied systems monitoring and control functions into LonWorks networks

- Interface for Lon connection to LonWorks networks
- Communication via Lon protocol (twisted pair wire)
- Unlimited sitesize
- Quick and easy installation



Daikin Configurator Software

EKPCCAB3

Simplified commissioning: graphical interface to configure, commission and upload system settings

Simplified commissioning

The Daikin configurator for Daikin Altherma and VRV is an advanced software solution that allows for easy system configuration and commissioning:

- Less time is required on the roof configuring the outdoor unit
- Multiple systems at different sites can be managed in exactly the same way, thus offering simplified commissioning for key accounts
- Initial settings on the outdoor unit can be easily retrieved



Simplified commissioning

Retrieve initial system settings






ACNSS

Air Conditioning Network Service System

The challenge of your technical management is safeguarding in the long term optimal operation of your air conditioning system without incurring huge costs along the way. Daikin's Air Conditioning Network Service System improves the effectiveness of your management.

The network service system is a link via the internet, between the air conditioning system and Daikin's Remote Monitoring Centre. In so doing, expert service engineers monitor the operating status of the entire system nonstop all through the year. The 'ACNSS monitoring service' prevents troubles and prolongs the life of your equipment.

Thanks to the prediction of malfunctions and the technical advise following from data analysis, you not only maximise equipment availability, but also control cost without sacrificing comfort levels. Daikin's ACNSS is also supported by the optional 'ACNSS energy saving service' as energy use is one of the largest operating expenses of any business. This service enables you to optimise on power consumption without failing to keep the customer's amenity.



ACNSS monitoring service + ACNSS energy saving service

Comfort maintained

1 Data transmission

Air conditioners's running information and other necessary data are collected and compiled, and sent to the centre. Advance failure forecasts and monitoring data for accidental problems are transmitted.

2 Daikin Remote Monitoring Centre


Daikin's control implemented



OPTION:

energy-saving control determination

Operating information is analyzed, and the optimum energy-saving control settings are calculated according to weather data for the region.



Weather information

intelligent touch Controller







intelligent touch Manager

Information to customers, service company

3 data analysis & system monitoring

Reporting data is reviewed and system is monitored 24/7 for any occurances.

Energy-saving Report
Maintenance Report
Malfunction and prediction call

* A contract with Daikin is necessary for applying Energy-saving Air conditioning Network Service System. If you would like an estimation, please contact us.
* Contact your Daikin responsible for connectable units

Wireless room temperature sensor

K.RSS

Flexible and easy installation

- Accurate temperature measurement thanks to flexible placement of the sensor
- No need for wiring
- No need to drill holes
- Ideal for refurbishment

Connection diagram Daikin indoor unit PCB (FXSQ-P example)



Specifications

			Wireless room temperature sensor kit (K.RSS)	
			Wireless room temperature receiver	Wireless room temperature sensor
Dimensions		mm	50 x 50	ø 75
Weight		g	40	60
Power supply			16VDC, max. 20 mA	N/A
Battery life			N/A	+/- 3 years
Battery type			N/A	3 Volt Lithium battery
Maximum range		m	10	
Operation range		°C	0~50	
Communication	Type		RF	
	Frequency	MHz	868.3	

- Room temperature is sent to the indoor unit every 90 seconds or if the temperature difference is 0.2°C or larger.

Wired room temperature sensor



KRCS01-1B
KRCS01-4B

- Accurate temperature measurement, thanks to flexible placement of the sensor

Specifications

Dimensions (HxW)	mm	60 x 50
Weight	g	300
Length of branch wiring	m	12

ADAPTER PCBs


Simple solutions for unique requirements

Daikin's adapter PCBs provide simple solutions for unique requirements. They are a low cost option to satisfy simple control requirements and can be used on single or multiple units.

	**(E)KRP1B*** adapter for wiring	• Facilitates integration of auxiliary heating apparatus, humidifiers, fans, damper • Powered by and installed at the indoor unit
	**KRP2A*/KRP4A*** Wiring adapter for electrical appendices	• Remotely start and stop up to 16 indoor units (1 group) (KRP2A* via P1 P2) • Remotely start and stop up to 128 indoor units (64 groups) (KRP4A* via F1 F2) • Alarm indication/ fire shut down • Remote temperature setpoint adjustment
	**DTA104A*** Outdoor Unit External Control Adapter	• Individual or simultaneous control of VRV system operating mode • Demand control of individual or multiple systems • Low noise option for individual or multiple systems
	**KRP928*** Interface adapter for DIII-net	• Allows integration of split units to Daikin central controls
	**KRP413*** Wiring adapter normal open contact / normal open pulse contact	• Switch off auto restart after power failure • Indication of operation mode / error • Remotely start /stop • Remotely change operation mode • Remotely change fan speed
	KRP980* Adapter for split units without an S21 port	• Connect a wired remote control • Connect to Daikin central controls • Allow external contact

Concept and benefits

› Low cost option to satisfy simple control requirements
› Deployed on single or multiple units



AUTO-CLEANING PANEL





FILTERS



INTELLIGENT SENSORS

Options & accessories

Heating	440
Split	442
Sky Air	444
VRV	448
Ventilation and hot water	454
Chillers	456
Fan coil units	462
Air handling units	464
Refrigeration	466
Control Systems	467

Options - Heating

Daikin Altherma hybrid heat pump	
Remote user interface (DE, FR, NL, IT)	EKRUCBL1
Remote user interface (EN, SV, NO, FI)	EKRUCBL2
Remote user interface (EN, ES, EL, PT)	EKRUCBL3
Remote user interface (EN, TR, PL, RO)	EKRUCBL4
Remote user interface (DE, CS, SL, SK)	EKRUCBL5
Remote user interface (EN, HR, HU, BG)	EKRUCBL6
Remote user interface (EN, DE, RU, DA)	EKRUCBL7
Propane set	EKHY075787
Concentric connection Ø 80/125	EKHY090717
Eccentric connnection Ø 80	EKHY090707
Cover plate 35	EKHY093467
Installation jig	EKHYMNT1
Drain pan for reversible H/B	EKHYDP1
Thermistor recirculator	EKTH2
Roof Terminal PP/GLV 60/100 AR460	EKFGP6837
Weather Slate Steep Pb/GLV 60/100 18°-22°	EKFGS0518
Weather Slate Steep Pb/GLV 60/100 23°-27°	EKFGS0519
Weather Slate Steep PF 60/100 25°-45°	EKFGP7910
Weather Slate Steep Pb/GLV 60/100 43°-47°	EKFGS0523
Weather Slate Steep Pb/GLV 60/100 48°-52°	EKFGS0524
Weather Slate Steep Pb/GLV 60/100 53°-57°	EKFGS0525
Weather Slate Flat Alu 60/100 0°-15°	EKFGP1296
Weather Slate Flat Alu 60/100	EKFGP6940
Wall Terminal Kit PP/GLV 60/100	EKFGP2978
Wall Terminal Kit low profile PP/GLV 60/100	EKFGP2977
Extension PP/GLV 60/100 x 500mm	EKFGP4651
Extension PP/GLV 60/100 x 1000mm	EKFGP4652
Elbow PP/GLV 60/100 30°	EKFGP4664
Elbow PP/GLV 60/100 45°	EKFGP4661
Elbow PP/GLV 60/100 90°	EKFGP4660
Meas. Tee with Inspection Panel PP/GLV 60/100	EKFGP4667
Wall Bracket Dn.100	EKFGP4631
Wall Terminal Kit PP/GLV 60/100	EKFGP1292
Wall Terminal Kit low profile PP/GLV 60/100	EKFGP1293
Plume Managment Kit 60 UK Only	EKFGP1294
Flue Deflector 60 UK Only	EKFGP1295
PMK Elbow 60 90 UK Only	EKFGP1284
PMK Elbow 60 45° (2 pcs) UK Only	EKFGP1285
PMK Extension 60 L=1000 incl. breaket UK Only	EKFGP1286
Roof Terminal PP/GLV 80/125 AR300 Ral-9011	EKFGP6864
Weather Slate Steep Pb/GLV 80/125 18°-22°	EKFGT6300
Weather Slate Steep Pb/GLV 80/125 23°-27°	EKFGT6301

Daikin Altherma ground source heat pump	
Ground source filling kit	KGSFILL
Remote user interface (DE, FR, NL, IT)	EKRUCBL1
Remote user interface (EN, SV, NO, FI)	EKRUCBL2
Remote user interface (EN, ES, EL, PT)	EKRUCBL3
Remote user interface (EN, TR, PL, RO)	EKRUCBL4
Remote user interface (DE, CS, SL, SK)	EKRUCBL5
Remote user interface (EN, HR, HU, BG)	EKRUCBL6
Remote user interface (EN, DE, RU, DA)	EKRUCBL7
Digital I/O PCB	EKRP1HBAA
Demand PCB	EKRP1AHTA
Remote indoor sensor	KRCS01-1
PC cable	EKPCCAB2
Wire harness	EKGSCONBP1
Room thermostat (wired)	EKRTWA
Room thermostat (wireless)	EKRTR1
External sensor	EKRTETS

Daikin Altherma hybrid heat pump	
Weather Slate Steep PF 80/125 25°-45° Ral-9011	EKFGP7909
Weather Slate Steep Pb/GLV 80/125 43°-47°	EKFGT6305
Weather Slate Steep Pb/GLV 80/125 48°-52°	EKFGT6306
Weather Slate Steep Pb/GLV 80/125 53°-57°	EKFGT6307
Weather Slate Flat Alu 80/125 0°-15°	EKFGP1297
Weather Slate Flat Alu 80/125	EKFGW5333
Wall Terminal Kit PP/GLV 80/125	EKFGW6359
Extension PP/GLV 80/125 x 500mm	EKFGP4801
Extension PP/GLV 80/125 x 10000mm	EKFGP4802
Elbow PP/GLV 80/125 30°	EKFGP4814
Elbow PP/ALU 80/125 45°	EKFGP4811
Elbow PP/ALU 80/125 90°	EKFGP4810
Inspection Elbow Plus PP/ALU 80/125 90° EPDM	EKFGP4820
Wall Bracket Dn.100	EKFGP4481
Flex Kit PP Dn.60-80	EKFGP1856
Chimney Connection 60/100	EKFGP4678
Flex Kit PP Dn.80	EKFGP2520
Chimney Connection 80/125	EKFGP4828
Extension Flex PP 80 L=10 M	EKFGP6340
Extension Flex PP 80 L=15 M	EKFGP6344
Extension Flex PP 80 L=25 M	EKFGP6341
Extension Flex PP 80 L=50 M	EKFGP6342
Connector Flex-Flex PP 80	EKFGP6324
Spacer PP 80-100	EKFGP6333
Tee Flex 100 Boiler Connectionset 1	EKFGP6368
Flex 100-60 + Support Elbow	EKFGP6354
Tee Flex 130 Boiler Connectionset 1	EKFGP6215
Flex 130-60 + Support Elbow	EKFGS0257
Chimney Connection 60/100	EKFGP4678
Extension PP 60x500	EKFGP5461
Chimney Top PP 100 incl. Flue Pipe	EKFGP5497
Adapter Flex-Fixed PP 100	EKFGP6316
Support Breaket Top Inox Dn.100	EKFGP6337
Extension Flex PP 100 L=10 M	EKFGP6346
Extension Flex PP 100 L=15 M	EKFGP6349
Extension Flex PP 100 L=25 M	EKFGP6347
Connector Flex-Flex PP 100	EKFGP6325
Chimney Top PP 130 incl. Flue Pipe	EKFGP5197
Adapter Flex-Fixed PP 130	EKFGS0252
Support Breaket Top Inox Dn.130	EKFGP6353
Extension Flex PP 130 L=30 M	EKFGS0250
Connector Flex-Flex PP 130	EKFGP6366
Valve kit	EKVK1A
	EKVK2A
	EKVK3A
	EKHYPART

Daikin Altherma low temperature split	4-8 kW	11-16 kW
Drain pan for outdoor (excl heater)	EKDP008CA	
Drain pan heater	EKDPH008CA	
U-beams for outdoor	EKFT008CA	
Remote sensor for outdoor	EKRSCA1	
Remote user interface (DE, FR, NL, IT)	EKRUCBL1	
Remote user interface (EN, SV, NO, FI)	EKRUCBL2	
Remote user interface (EN, ES, EL, PT)	EKRUCBL3	
Remote user interface (EN, TR, PL, RO)	EKRUCBL4	
Remote user interface (DE, CS, SL, SK)	EKRUCBL5	
Remote user interface (EN, HR, HU, BG)	EKRUCBL6	
Remote user interface (EN, DE, RU, DA)	EKRUCBL7	
Indoor drain pan for new wall mounted H/B	EKHBDPCA2	
PC cable	EKPCCAB1	
Digital I/O PCB		EKRP1HBAA
Bottom plate heater		EKBPHTH16A
Drain kit		EKDK04
Snowcover		EK016SNCA
Demand PCB		EKRP1AHTA
Remote indoor sensor		KRCS01-1B
Drain pan for indoor wall munted		EKHBDPCA2
Booster heater for tank integrated design		EKBSHCA3V3

Daikin Altherma integrated solar unit	
Room thermostat	EHS157034
Mixer module	EHS157068
Gateway for apps	EHS157056
9kW backup heater	EKBU9C

Daikin Altherma low temperature monobloc	6-8 kW	11-16 kW
Back up heater	EKMBUHBA6V3	
Cable	EKCOMCAB1	
Digital I.O PCB		EKRP1HBAA
Bottom plate heater		EKBPHTH16A
Drain kit		EKDK04

Daikin Altherma high temperature split	
Bottom plate heater	EKBPHTH16A
Digital I/O PCB	EKRP1HBAA
Demand PCB	EKRP1AHTA
Remote user interface	EKRUAHTB
Back up heater for HT	EKBUHAA6V3
Back up heater for HT	EKBUHAA6W1
Refrigerant stop valves	EKRSVHTA
UK tank kit	EKUHWHTA
Compatibility kit 1	EKMKHT1A
Compatibility kit 2	EKMKHT2A

Daikin Altherma Flex Type

options for outdoor unit	EKHVMRD	EKHVMYD
Refnet header	KHRQ(M)22M29H8	KHRQ(M)23M29H8
Refnet header	KHRQ(M)22M64H8	KHRQ(M)23M64H8
Refnet joint	KHRQ(M)22M20T8	KHRQ(M)23M20T8
Refnet joint	KHRQ(M)22M29T8	KHRQ(M)23M29T8
Refnet joint	KHRQ(M)22M64T8	KHRQ(M)23M64T8
central drain pan kit	KWC25C450	KWC25C450

options for indoor unit	
Stand alone kit	EKFMAHTB
I/O PCB	EKRP1HBAA
Demand PCB	EKRP1AHTA
Remote user interface	EKRUAHTB
Individual billing - connection kit	EKMBIL1

Back up heater kit	EKBUHAA6V3
Back up heater kit	EKBUHAA6W1

Tanks	EKHWS	EKHWP	EKHTS
Wall bracket	EKWBSWW150		
Connection kit EKHWP300 for low temperature (heating only / heating and cooling)		EKDVCPLT3HX	
Connection kit EKHWP500 for low temperature (heating only)		EKDVCPLT5H	
Connection kit EKHWP500 for low temperature (heating and cooling)		EKDVCPLT5X	
Connection kit for high temperature and VRV indoor HXHD125 (EKHWP300/ EKHWP500)		EKEPHT3H / EKEPHT5H	
Connection kit for Daikiin Altherma Flex Type (heating only)		EKEPHT3H	
Connection kit for Daikiin Altherma Flex Type (heating and cooling)		EKEPHT3H + 156034	
3 way valve		3-W-UV2	
Booster heater with melting fuse (900mm)		EKBH3S	
Option kit (EKHTS / EKHTSU)			EKFMALTA / EKUHWHTA

Heat pump convector	
Valve kit	EKVKHPC

Solar collectors	
Mounting kit on roof (antracite)	EKSRCAP
Mounting kit on roof (red)	EKSRCRP
Mounting kit on roof (excl. Roof tile)	EKSRCP
Gravity brake	16 50 70
Flow sensor	FLS12
Flow regulating valve with flow rate indicator	FLG
Connection set for additional heat source	EWS
Hot water recirculation kit	ZKL
Thermostatic antiscald mixing valve + 1" screw connection set	VTA32 + 156016
Solar Expansion vessel 12l	MAGS12
Solar Expansion vessel 25l	MAGS25
Solar Expansion vessel 35l	MAGS35
Pressureless Connection piping between solar panel & pump station: 15 meter	CON 15
Pressureless Connection piping between solar panel & pump station: 20 meter	CON 20
Unpressurised elongation pipe 2.5 m including couplings	CON X 25
Unpressurised elongation pipe 5 m including couplings	CON X 50
Unpressurised elongation pipe 10 m including couplings	CON X 100
Unpressurised elongation for inlet pipe 8 meter	CON XV 80
Pressure solar pipe DN16 - 15m	CON15P16
Connectors DN16	CONXP16
Pressure solar pipe DN20 - 15m	CON15P20
Connectors DN20	CONXP20
Connectors DN20	CON CP16
Connectors DN20	CON CP20
Mounting kit IN-ROOF	RCIP
Mounting kit FLAT ROOF	RCFP
Additional roof breakthrough for opposite side connection	CON FE
Connection kit between 2 solar panels	FIX VBP
Connection kit between 2 rows of Collectors	CON RVP
Connection kit between 2 rows of Collectors	CON LCP
Mounting support for V26P	FIX MP 130
Mounting support for H26P	FIX MP 200
Mounting support for V21P	FIX MP 100
Suporting shell for pressureless connection pipe	TS
Standard mounting set for on-roof mounting suitable for roof tiles	FIX AD
Variable height mounting set for on-roof mounting suitable for roof tiles	FIX ADP
Mounting set for on-roof mounting	FIX ADD
Mounting set for on-roof mounting suitable for flat tiles e.g. shingles	FIX ADS
Mounting set for on-roof mounting suitable for corrugated plates	FIX - WD
Mounting set for on-roof mounting suitable for metal roofs	FIX BD
Basic IN ROOF installation kit for 2 EKSV21P	IBV21P
Extension IN ROOF installation kit for 1 additional EKSV21P	IEV21P
Basic IN ROOF installation kit for 2 EKSV26P	IBV26P
Extension IN ROOF installation kit for 1 additional EKSV26P	IEV26P
IN ROOF covering slate complementing kit	FIX-IES
Basic FLAT ROOF support frame for 2 EKSV26P	FB V26P
Extension FLAT ROOF support frame for additional EKSV26P	FE V26P
Basic FLAT ROOF support frame for 1 EKSH26P	FB H26P
Extension FLAT ROOF support frame for additional EKSH26P	FE H26P
Release tool	FIX LP
Glycol fluid 20 l	GFL

Options - Split

		FTXZ-N	FTXJ-LW/S	FTXG-LW/S	FTXM-K	CTXS15-35K FTXS20-25K	FTXS35-50K
Adapters and controls	**Wired remote control**	-	BRC944 (3)	BRC944 (3)	BRC944 (3) (5)	BRC944 (3) (5)	BRC944 (3)
	Wireless remote control	-	-	-	-	-	-
	Simplified remote control	-	-	-	-	-	-
	Remote control for hotel use	-	-	-	-	-	-
	Cord for wired remote control - 3m	-	BRCW901A03	BRCW901A03	BRCW901A03	BRCW901A03	BRCW901A03
	Cord for wired remote control - 8m	-	BRCW901A08	BRCW901A08	BRCW901A08	BRCW901A08	BRCW901A08
	Wiring adapter normal open contact / normal open pulse contact	KRP413A1S (1)	KRP413A1S (1)	KRP413A1S (1)	KRP413A1S (1) ((5) (20-25 class))	KRP413A1S (1) (5)	KRP413A1S (1)
	Centralised control board - up to 5 rooms	KRC72 (2)	KRC72 (2)	KRC72 (2)	KRC72 (2)	KRC72 (2)	KRC72 (2)
	Anti-theft protection for remote control	KKF936A4	KKF910A4	KKF910A4	KKF910A4 (20-25 class) KKF910A3 (35-42-50 class)	KKF910A4	KKF910A4
	Interface adapter for wired remote control	-	-	-	KRP980A1 (20-25 class)	KRP980A1	-
	Wiring adapter for electrical appendices	-	-	-	-	-	-
	Remote sensor	-	-	-	-	-	-
	Installation box for adapter PCB	-	-	-	-	-	-
	Electric box with earth terminal 3 blocks	-	-	-	-	-	-
	Electric box with earth terminal 2 blocks	-	-	-	-	-	-
	Interface adapter for DIII-net	KRP928A2S	KRP928BA2S	KRP928A2S	KRP928A2S (5)	KRP928A2S (5)	KRP928A2S (5)
	Online controller	BRP069A42 (available from 01/15)	BRP069A41	BRP069A41	BRP06942 (5) (20-25 class) BRP06941 (35-42-50 class)	BRP06942 (5)	BRP06942
	Modbus gateway	RTD-RA	RTD-RA	RTD-RA	RTD-RA	RTD-RA (5)	RTD-RA
	KNX gateway	KLIC-DD	KLIC-DD	KLIC-DD	KLIC-DD	KLIC-DD (5)	KLIC-DD
Others	**Titanium apatite photocatalytic air-purification filter without frame**	-	KAF970A46	-	KAF970A46 (20-25 class)	-	-
	Photocatalytic deodorising filter, with frame	-	-	-	-	-	-
	Photocatalytic deodorising filter, without frame	-	-	-	-	-	-
	Air purification filter, with frame	-	-	-	-	-	-
	Installation leg	-	-	-	-	-	-

(1) Wiring adapter supplied by Daikin. Time clock and other devices : to be purchased locally; (2) Wiring adapter is also required for each indoor unit; (3) Cord for wired remote control BRCW901A03 or BRCW901A08 required; (4) Standard there is no remote control delivered with this indoor unit. Wired or wireless control to be ordered separately; (5) Interface adapter KRP980A1 required.

		SIESTA INDOOR UNITS			
		ATXL-JV	ATXS-K	ATX-J3	ATX-K
Adapters and controls	**Wired remote control**	BRC944 (3) (5)	BRC944 (3)	BRC944 (3) (5)	BRC944 (3) (5)
	Wireless remote control	-	-	-	-
	Simplified remote control	-	-	-	-
	Remote control for hotel use	-	-	-	-
	Cord for wired remote control - 3m	BRCW901A03	BRCW901A03	BRCW901A03	BRCW901A03
	Cord for wired remote control - 8m	BRCW901A08	BRCW901A08	BRCW901A08	BRCW901A08
	Wiring adapter normal open contact / normal open pulse contact	-	KRP413AB1S (1)	-	-
	Centralised control board - up to 5 rooms	-	KRC72A (2)	-	-
	Anti-theft protection for remote control	KKF917A4	KKF910A4	KKF910A4	KKF917A4
	Interface adapter for wired remote control	KRP980A1	KRP980A1	KRP980A1	KRP980A1
	Wiring adapter for electrical appendices	-	-	-	-
	Remote sensor	-	-	-	-
	Installation box for adapter PCB	-	-	-	-
	Electric box with earth terminal 3 blocks	-	-	-	-
	Electric box with earth terminal 2 blocks	-	-	-	-
	Interface adapter for DIII-net	-	KRP928BB2S	-	-
	Online controller	BRP06942 (5)	BRP069A42	BRP06942 (5)	BRP06942 (5)
	Modbus gateway	RTD-RA (5)	-	RTD-RA (5)	RTD-RA (5)
	KNX gateway	KLIC-DD (5)	-	KLIC-DD (5)	KLIC-DD (5)
Others	**Titanium apatite photocatalytic air-purification filter without frame**	KAF971A42	-	KAF971A42	-
	Photocatalytic deodorising filter, with frame	-	-	-	-
	Photocatalytic deodorising filter, without frame	-	-	-	-
	Air purification filter, with frame	-	-	-	-
	Installation leg	-	-	-	-

		RXZ-N	RXJ-L	RXG-L	RXM-L	RXS-L(3)	RXS-F8
Others	**Air direction adjustment grille**	-	-	KPW945A4 (50 class)	-	-	-
	Drain plug	-	KKP945A4	-	KKP945A4	-	-
	Humidifying hose L joint (10 pcs.)	KPMJ983A4L	-	-	-	-	-
	L-shape cuffs for humidification (10pcs)	KPMH950A4L	-	-	-	-	-
	Humidifying hose extension set 2m	KPMH974A402	-	-	-	-	-
	Hose for humidification (10m)	KPMH974A42	-	-	-	-	-

Notes: (1) Wiring adapter supplied by Daikin. Time clock and other devices : to be purchased locally; (2) Wiring adapter is also required for each indoor unit; (3) Cord for wired remote control BRCW901A03 or BRCW901A08 required; (4) Standard there is no remote control delivered with this indoor unit. Wired or wireless control to be ordered separately; (5) Interface adapter KRP980A1 required.

INDOOR UNITS									
FTXS-G	**FTX-J3**	**FTX-GV**	**FTX-K**	**FVXG-K**	**FVXS-F**	**FDXS-F(9)**	**FLXS-B(9)**	**FTXLS-K**	**FTXL-JV**
BRC944 (3)	BRC944B2 (3) (5)	BRC944 (3)	BRC944B2 (3)	BRC944 (3)	-	BRC1D52 BRC1E52A BRC1E52B (4)	-	BRC944 (3)	BRC944 (3) (5)
-	-	-	-	-	-	BRC4C65	-	-	-
-	-	-	-	-	-	BRC2C51	-	-	-
-	-	-	-	-	-	BRC3A61	-	-	-
BRCW901A03	BRCW901A03	BRCW901A03	BRCW901A03	BRCW901A03	-	-	-	BRCW901A03	BRCW901A03
BRCW901A08	BRCW901A08	BRCW901A08	BRCW901A08	BRCW901A08	-	-	-	BRCW901A08	BRCW901A08
KRP413A1S (1)	-	KRP413A1S (1)	-	KRP413A1S (1)	KRP413A1S (1)	-	KRP413A1S (1)	KRP413A1S (1)	-
KRC72 (2)	-	KRC72 (2)	-	KRC72 (2)	KRC72 (2)	-	KRC72 (2)	KRC72 (2)	-
KKF910A4	KKF917A4	KKF917AA4	KKF917A4	KKF910A4	-	-	KKF917AA4	KKF910A4	KKF917A4
-	KRP980A1	-	KRP980A1	-	-	-	-	-	KRP980A1
-	-	-	-	-	-	KRP4A54	-	-	-
-	-	-	-	-	-	KRCS01-4	-	-	-
-	-	-	-	-	-	KRP1BA101	-	-	-
-	-	-	-	-	-	KJB311A	-	-	-
-	-	-	-	-	-	KJB212A			-
KRP928A2S	-	KRP928A2S	-	KRP928A2S	KRP928A2S	-	KRP928A2S	KRP928BB2S	-
BRP069A42	BRP06942 (5)	BRP069A42	BRP069A42	BRP069A42	BRP069A42	-	BRP069A42	BRP069A42	BRP06942 (5)
RTD-RA	RTD-RA (5)	RTD-RA	RTD-RA	RTD-RA	RTD-RA	RTD-NET	-	RTD-RA	RTD-RA (5)
KLIC-DD	KLIC-DD (5)	KLIC-DD		KLIC-DD	KLIC-DD	KLIC-DI	KLIC-DD	KLIC-DD	KLIC-DD (5)
-	KAF971A42	KAF952B42	KAF970A46	-	-	-	-	KAF970A46	KAF971A42
-	-	-	-	-	-	-	KAZ917B41	-	-
-	-	-	-	-	-	-	KAZ917B42	-	-
-	-	-	-	-	-	-	KAF925B41	-	-
-	-	-	-	BKS028	-	-	-	-	-

OUTDOOR UNITS									
RX-K	RX-GV(B)	RXLG-M	RXLS-M	RXL-M(3)	ARXL-M	ARXS-L(3)	ARX-K	MXS-E/F/G/H/K	AMX-G/E
KPW937C4	KPW945A4	-	-	-	-	-	KPW937C4	KPW945A4	-
KKP937A4	-	-	-	-	-	-	KKP937A4		-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-

*Note: blue cells contain preliminary data

	INDOOR UNITS					
Description	**FCQHG-F**	**FCQG-F**	**FFQ-C**	**ACQ-D**	**FDBQ-B**	**FBQ-D**
Wired remote control	BRC1D52 BRC1E52A (3) BRC1E52B (4)	BRC1D52 BRC1E52A (3) BRC1E52B (4)	BRC1D528 BRC1E52A (3) BRC1E52B(4)(9)	ARCWB	BRC1D52 BRC1E52A (3) BRC1E52B (4)	BRC1D52 BRC1E52A (3) BRC1E52B (4)
Intelligent touch controller	DCS601C51	DCS601C51	DCS601C51	-	-	DCS601C51 (2)
Infrared remote control (heat pump)	BRC7FA532F (5)	BRC7FA532F (5)	BRC7EB530W BRC7F530W BRC7F530S (8-9)	ADP125A (11)	-	BRC4C65
Simplified remote control (with operation mode selector button)	-	-	BRC2E52C (12)	-	-	BRC2E52C (12)
Simplified remote control (without operation mode selector button)	-	-	BRC3E52C (12)	-	-	-
Residential central remote control	-	-	-	-	-	-
Remote control for hotel use	BRC3A61	BRC3A61	-	-	-	BRC3E52C
Centralised remote control	DCS302C51	DCS302C51	DCS302B51	-	-	DCS302C51
Unified ON/OFF control	DCS301B51	DCS301B51	DCS301B51	-	-	DCS301B51
Schedule timer	DST301B51	DST301B51	DST301B51	-	-	DST301B51
Adapter for wiring (interlock for fresh air intake fan)	-	-	-	-	-	KRP1BA59
Adapter for external ON/OFF and monitoring/for electrical appendices	KRP1B57 KRP4A53 (1)(5)	KRP1B57 KRP4A53 (1)(5)	KRP1B57 KRP4A53(6)	-	-	KRP4A52 (1) KRP2A51 (1)
Interface adapter for Sky Air	-	-	-	-	-	DTA112B51
Installation box for adapter PCB	KRP1H98 (5)	KRP1H98 (5)	KRP1B101 KRP1BA101	-	-	KRP1B(A)101
Remote sensor	KRCS01-4	KRCS01-4	KRCS01-4	-	-	KRCS01-4B
Remote ON/OFF, forced OFF	EKRORO2	-	-	-	-	-
Electrical box with earth terminal (3 blocks)	KJB311A	KJB311A	-	-	-	-
Electrical box with earth terminal (2 blocks)	KJB212A	KJB212A	-	-	-	-
Electrical box with earth terminal	-	-	-	-	-	KJB411A
Adapter for wiring (hour meter)	EKRP1C11 (1)(5)	EKRP1C11 (1)(5)	EKRP1B2	-	EKRP1B2	-
Digital input adaptor	-	-	BRP7A51 (1) (13)	-	-	BRP7A51
Options PCB for external electrical heater, humidifier and/or hour meter	-	-	-	-	-	EKRP1B2A (7)
Option PCB for group control (NIM03)	-	-	-	R04084124324	-	-
Mounting plate for adapter PCB	-	-	-	-	-	-

Notes: (1) Installation box for adapter PCB is necessary; (2) Interface adapter for Sky Air series (DTA112B51) is necessary; (3) Including following languages: English, German, French, Italian, Spanish, Dutch, Greek, Russian, Turkish, Portuguese, Polish; (4) Including following languages: English, German, Czech, Croatian, Hungarian, Romanian, Slovenian, Bulgarian, Slovak, Serbian, Albanian; (5) Option not available in combination with BYCQ140*G; (6) Installation box for adapter PCB (KRP1B101) is necessary; (7) Electrical heater, humidifier and hour meter are field supply. These parts should not be installed inside the equipment; (8) Sensing function is not available; (9) Independently controllable flaps function is not available; (10) With the infrared remote control, the individual flap control and automatic air volume control cannot be controlled; (11) Including decoration panel; (12) Including following languages: English, German, French, Dutch, Spanish, Italian, Portuguese; (13) Only possible in combination with simplified remote control BRC2/3E52C; (14) For residential use only. Cannot be used with other centralised control equipment

INDOOR UNITS								
FDQ-C	**FDQ-B**	**ABQ-C**	**FAQ-C**	**FHQ-C**	**AHQ-C**	**FUQ-C**	**FNQ-A**	**FVQ-C**
BRC1D52 BRC1E52A (3) BRC1E52B (4)	BRC1D52 BRC1E52A (3) BRC1E52B (4)	-	BRC1D52 BRC1E52A (3) BRC1E52B (4)	BRC1D52 BRC1E52A (3) BRC1E52B (4)	ARCWB	BRC1D52 BRC1E52A (3) BRC1E52B (4)	BRC1D52 BRC1E51A BRC1E52A BRC1E52B	BRC1D52 BRC1E52A (3) BRC1E52B (4)
DCS601C51	-	-	DCS601C51	-	-	-	-	DCS301C51
BRC4C65	-	-	BRC7EB518	BRC7G53	-	BRC7C58 (10)	BRC4C65	-
-	-	-	BRC2C51	-	-	-	BRC2E52C (12)	BRC2E52C
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	DCS303A51	-
-	-	-	BRC3A61	-	-	-	BRC3E52C7 (3) (15)	BRC3A61
DCS302C51	DCS302C51	-	DCS302C51	DCS302C51	-	DCS302C51	DCS302CA51	DCS302C51
DCS301B51	DCS301B51	-	DCS301B51	DCS301B51	-	DCS301B51	DCS301BA51	DCS301B51
DST301B51	DST301B51	-	DST301B51	DST301B51	-	DST301B51	DST301BA51	DST301B51
KRP1C64	KRP1B54	-	-	-	-	-	-	-
KRP4A51	KRP4A51	-	KRP4A51 (1)	KRP1B54 KRP4A52(1)	-	KRP4A53 (1)	KRP4A54	KRP1B57 KRP4A52
-	DTA112B51	-	-	-	-	-	-	-
-	-	-	KRP4A93	KRP1D93A	-	KRP1B97	KRP1BA101	KRP4AA95
KRCS01-4B	-	-	KRCS01-1	KRCS01-4B	-	KRCS01-4	KRCS01-4B	-
EKRORO3	EKRORO	-	-	EKRORO4	-	EKRORO5	-	-
-	-	-	KJB311A	KJB311A	-	KJB311A	KJB212AA	-
-	-	-	KJB212A	KJB212A	-	KJB212A	KJB311AA	-
-	-	-	-	-	-	-	-	
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	BRP7A51 (1) (13)	
EKRP1B2	EKRP1B2	-	-	-	-	-	-	-
-	-	R04084124324	-	-	R04084124324	-	-	-
KRP4A96	-	-	-	-	-	-	-	-

*Note: blue cells contain preliminary data

Description	INDOOR UNITS					
	FCQHG-F	FCQG-F	FFQ-C	ACQ-D	FDBQ-B	FBQ-D
Replacement long-life filter	KAFP551K160	KAFP551K160	KAFQ441BA60	-	-	-
Drain pump kit	Standard	Standard	Standard	Standard	-	Standard
L-type piping kit (upward direction)	-	-	-	-	-	-
Sealing member of air discharge outlet	KDBHQ55B140 (4)	KDBHQ55B140 (4)	BDBHQ44C60	-	-	-
Decoration panel for air discharge	-	-	-	-	-	-
Decoration panel	BYCQ140D BYCQ140DW(1) BYCQ140DG (2)(3)	BYCQ140D BYCQ140DW(1) BYCQ140DG (2)(3)	BYFQ60B3 BYFQ60C2W1W BYFQ60C2W1S (6)	ADP125A (10)	-	BYBS32D (35 class) BYBS45D (50 class) BYBS71D (60-71 class) BYBS125D (100-140 class)
Kit for mounting of decoration panel direct onto unit	-	-	-	-	-	EKBYBSD (9)
Fresh air intake kit (direct installation type)	KDDQ55B140-1 (4) KDDQ55B140-2 (6)	KDDQ55B140-1 (4) KDDQ55B140-2 (6)	KDDQ44XA60	-	-	-
Air discharge adapter for round duct	-	-	-	-	-	KDAJ25K36A (35 class) KDAJ25K56A (50 class) KDAJ25K71A (60-71 class) KDAJ25K140A (100-140 class)
Panel spacer	-	-	KDBQ44B60	-	-	-
Sensor kit	BRYQ140A (5)	BRYQ140A (5)	BRYQ60A2W BRYQ60A2S (7)	-	-	-
Noise filter	-	-	-	-	-	-

Notes: (1) The BYCQ140DW has white insulations. Be informed that dirt is more visible on white insulation and that it is consequently not advised to install the BYCQ140DW decoration panel in environments

Description		OUTDOOR UNITS			
		RZQG-L9V1/L(8)Y1	RZQSG-L3/9V1/L(8)Y1	RZQ-C	AZQS-B8V1/BY1
Central drain plug		-	-	KWC26B280	-
Refrigerant branch piping	For twin	KHRQ22M20TA (KHRQ58T) [2]	KHRQ22M20TA (KHRQ58T) [2]	KHRQ22M20TA	-
	For triple	KHRQ127H (KHRQ58T) [2]	KHRQ127H (KHRQ58T)[2]	KHRQ250H7	-
	For double twin	KHRQ22M20TA (3x) (KHRQ58T)[2]	KHRQ22M20TA (3x) (KHRQ58T)[2]	KHRQ22M20TA (x3)	-
Demand adapter kit		KRP58M51MK	KRP58M51 (71 class) KRP58M51MK	KRP58M51	KRP58M51 (71 class) KRP58M51MK
Bottom plate heater		EKBPH140L7 1	-	-	-

Notes: (1) Bottom plate heater is only available for RZQG* models; (2) For combination of RZQ(S)G71-140 in combination with FCQG35-71F or FCQHG71F use the refrigerant branch piping mentioned between brackets; (3) For RZQG71

Description	ROOFTOPS	
	UATYQ-C	UATYP-AY1(B)
Rooftop controller	●	-
PCB	●	-
EXV	●	-
Gold Fin (NA549)	●	-
Scroll compressor	●	-
Saranet Air Filter	●	-
Side flow	●	-
Convertible	●	-
Filter drier	●	-
High pressure switch	●	-
Low pressure switch	●	-
Economiser	ECONO-AY1	-

INDOOR UNITS								
FDQ-C	**FDQ-B**	**ABQ-C**	**FAQ-C**	**FHQ-C**	**AHQ-C**	**FUQ-C**	**FNQ-A**	**FVQ-C**
-	-	-	-	KAFP501A56 (35-50 class) KAFP501A80 (60-71 class) KAFP501A160 (100-125 class)	-	KAFP551K160	-	KAFJ95L160
Standard	-	-	K-KDU572EVE	KDU50P60 (35-60 class) KDU50P140 (71-125 class)	-	-	-	-
-	-	-	-	KHFP5M35 (35 class) KHFP5N63 (50-60 class) KHFP5N160 (71-125 class)	-	-	-	-
-	-	-	-	-	-	KDBHP49B140	-	-
-	-	-	-	-	-	KDBTP49B140	-	-
BYBS125D(9)	BYBS125D(9)	-	-	-	-	-	-	-
EKBYBSD	EKBYBSD	-	-	-	-	-	-	-
-	-	-	-	KDDQ50A140	-	-	-	-
KDAJ25K140A	KDAJ25K140A	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	KEK26-1A	-	-	-	KEK26-1A	-

*Note: blue cells contain preliminary data

	VRV IV with continuous heating						VRV IV without	
	RYYQ8-12T	RYYQ14-20T	RYMQ8-12T	RYMQ14-20T	2-module systems	3-module systems	RXYQ8-12T	RXYQ14-20T
Multi-module connection kit (obligatory) - Connects multiple modules into a single refrigerant system	-	-	-	-	BHFQ22P1007	BHFQ22P1517	-	-
Extended level difference kit - Allows outdoor unit to be more than 50m above indoor units	-	-	-	-	-	-	-	-
Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan.	-	-	-	-	-	-	-	-
Heater tape kit - Optional electrical heater to guarantee trouble-free operation in extremely cold and humid climates (one per outdoor unit needed)	EKBPH012T + EKBPHPCBT	EKBPH020T + EKBPHPCBT	EKBPH012T + EKBPHPCBT	EKBPH020T + EKBPHPCBT	-	-	EKBPH012T + EKBPHPCBT	EKBPH020T + EKBPHPCBT
External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of Demand Limiting via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit*, BSVQ box, or VRV-WIII outdoor unit.	For installation into an indoor unit: exact adapter type depends on type of indoor unit. See Options & Accessories of indoor units							
BHGP26A1 - Digital pressure gauge kit – displays current condensing and evaporating pressures in the system as standard, or expansion valve positions and temperature sensor data in a special service mode. Connect to the outdoor unit PCB, for installation in the outdoor unit.	●	●	●	●	1 kit per system	1 kit per system	●	●
KRC19-26A - Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box.	●	●	●	●	●	●	●	●
BRP2A81 - Cool/heat selector PCB (required for VRV IV)	●	●	●	●	●	●	●	●
KKSA26A560* - Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined)	●	●	●	●	●	●	●	●
KJB111A - Installation box for remote cool/heat selector KRC19-26A	●	●	●	●	●	●	●	●
EKPCCAB3 - VRV configurator	●	●	●	●	●	●	●	●
BPMKS967A2/A3 - Branch provider (for connection of 2/3 RA indoor units)	●	●	-	-	-	-	●	●
KKPJ5F180 - Central drain plug	-	-	-	-	-	-	-	-
DTA104A61/62* - Demand PCB allowing external input to limit power consumption	●	●	●	●	●	●	●	●
KKSB2B61* - Demand PCB mounted plate. Needed to mount Demand PCB for some outdoor units.	-	●	-	●	-	-	-	●
DTA109A51 - DIII-net expander adapter	●	●	●	●	●	●	●	●

	VRV IV-Q Heat Pump Replacement VRV				
	RQYQ 140	RXYQQ8-12T	RXYQQ14-20T	2-module systems	3-module systems
Multi-module connection kit (obligatory) - Connects multiple modules into a single refrigerant system	-	-	-	BHFQ22P1007	BHFQ22P1517
Central drain pan kit - Installs onto the underside of the outdoor unit and collects drain water from all bottom plate outlets into a single outlet. In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan.	KWC26B160	-	-	-	-
Heater tape kit - Optional electrical heater to guarantee trouble-free operation in extremely cold and humid climates (one per outdoor unit needed)	-	EKBPH012T + EKBPHPCBT	EKBPH020T + EKBPHPCBT	-	-
External control adapter for outdoor unit - Allows to activate Low Noise Operation and three levels of Demand Limiting via external dry contacts. Connects to the F1/F2 communication line and requires power supply from an indoor unit*, BSVQ box, or VRV-WIII outdoor unit.	DTA104A53/61/62 For installation into an indoor unit: exact adapter type depends on type of indoor unit. See Options & Accessories of indoor units				
BHGP26A1 - Digital pressure gauge kit – displays current condensing and evaporating pressures in the system as standard, or expansion valve positions and temperature sensor data in a special service mode. Connect to the outdoor unit PCB, for installation in the outdoor unit.	●	●	●	1 kit per system	1 kit per system
KRC19-26A - Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box.	●	●	●	1 kit per system	1 kit per system
BRP2A81 - Cool/heat selector PCB (required for VRV IV)	-	●	●	●	●
KKSA26A560* - Cool/heat selector PCB mounting plate (only required when cool/heat selector PCB and Heater tape kit are combined)	-	-	●	●	●
KJB111A - Installation box for remote cool/heat selector KRC19-26A	●	●	●	1 kit per system	1 kit per system
EKPCCAB3 - VRV configurator	-	●	●	●	●
DTA104A61/62* - Demand PCB allowing external input to limit power consumption	-	●	●	●	●
KKSB2B61* - Demand PCB mounted plate. Needed to mount Demand PCB for some outdoor units.	-	-	●	-	-
DTA109A51 - DIII-net expander adapter	●	●	●	●	●

		Refnet Joints				Refnet Headers	
		Capacity index < 201	Capacity index 201~290	Capacity index 291~640	Capacity index > 640	Capacity index < 291	Capacity index 291~640
Heat Recovery systems (3-pipe)	Metric-size connections	KHRQM23M20T	KHRQM23M29T	KHRQM23M64T	KHRQM23M75T	KHRQM23M29H	KHRQM23M64H
	Imperial-size connections	KHRQ23M20T	KHRQ23M29T9	KHRQ23M64T	KHRQ23M75T	KHRQ23M29H	KHRQ23M64H
	Sound reduction kit (sound insulation)	-	-	-	-	-	-
	Mechanical cool/heat selector – allows to switch an entire Heat Pump system, or one BS-box of a Heat Recovery system between cooling, heating and fan only. Connects to the A-B-C terminals of the outdoor unit / BS-box.	-	-	-	-	-	-
	Installation box for remote cool/heat selector KRC19-26	-	-	-	-	-	-
	Closed pipe kit						
	Joint kit						
	Quiet kit						
Heat Pump systems (2-pipe)	Metric-size connections	KHRQM22M20T	KHRQM22M29T	KHRQM22M64T	KHRQM22M75T	KHRQM22M29H	KHRQM22M64H
	Imperial-size connections	KHRQ22M20T	KHRQ22M29T9	KHRQ22M64T	KHRQ22M75T	KHRQ22M29H	KHRQ22M64H

continuous heating		VRV III-S Mini VRV	VRV III-C Cold Region VRV			VRV Classic			VRV IV Heat Recovery				
2-module systems	3-module systems	RXYSQ	RTSYQ 10	RTSYQ 14~16	RTSYQ 20	RXYCQ8A	RXYCQ10-14A	RXYCQ16-20A	REYQ 8~12	REYQ 14~20	REMQ5	2-module systems	3-module systems
BHFQ22P1007	BHFQ22P1517	-	-	-	BHFQ22P1007	-	-	-	-	-	-	BHFQ23P907	BHFQ23P1357
-	-	-	-	-	-	-	-	-	Special order unit				
-	-	-	KWC26B280	KWC26B450	2x KWC26B280	KWC26B160	KWC26B280	KWC26B450	-	-	-	-	-
-	-	-	BEH22A10Y1L	BEH22A18Y1L	2x BEH22A10Y1L	-	-	-	EKBPH012T + EKBHPCBT	EKBPH020T + EKBHPCBT	EKBPH012T + EKBHPCBT	-	-
		For installation into an indoor unit: exact adapter type depends on type of indoor unit. See Options & Accessories of indoor units											
1 kit per system	1 kit per system	-	●	●	●	●	●	●	●	●	●	1 kit per system	1 kit per system
●	●	●	-	-	-	●	●	●	-	-	-	-	-
●	●	-	-	-	-	-	-	-	-	-	-	-	-
●	●	-	-	-	-	-	-	-	-	-	-	-	-
●	●	●	-	-	-	●	●	●	-	-	-	-	-
●	●	-	-	-	-	-	-	-	●	●	●	●	●
-	-	●	-	-	-	-	-	-	-	-	-	-	-
-	-	●	-	-	-	-	-	-	-	-	-	-	-
●	●	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-
●	●	●	●	●	●	●	●	●	●	●	●	●	●

VRV III-Q Heat Recovery Replacement VRV				VRV-W IV Water-cooled VRV				
					Heat Pump application		Heat Recovery application	
RQEQ 140~212	2-module systems	3-module systems	4-module systems	RWEYQ8-10T	2-module systems	3-module systems	2-module systems	3-module systems
-	BHFP26P36C	BHFP26P63C	BHFP26P84C	-	BHFQ22P1007	BHFQ22P1517	BHFQ23P907	BHFQ23P1357
KWC26B160	1 kit per module	1 kit per module	1 kit per module	-	-	-	-	-
-	-	-	-	-	-	-	-	-
DTA104A53/61/62 For installation into an indoor unit: exact adapter type depends on type of indoor unit. See Options & Accessories of indoor units				DTA104A62 Installation in the RWEYQ outdoor unit possible. For installation in indoor units, use appropriate type (DTA104A53/61/62) for particular indoor unit. See Options & Accessories of indoor units				
●	1 kit per system	1 kit per system	1 kit per system	-	-	-	-	-
-	-	-	-	●	1 kit per system	1 kit per system	-	-
-	-	-	-	●	1 kit per system	1 kit per system	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	●	1 kit per system	1 kit per system	-	-
-	-	-	-	●	●	●	●	●
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
●	●	●	●	●	●	●	●	●

	Heat Recovery Branch Selector Boxes (BS-Boxes)									
Capacity index	1-port	1-port	4-port	4-port	6-port	6-port	8-port	10-port	12-port	16-port
> 640	-	-	-	-	-	-	-	-	-	-
KHRQM23M75H	-	-	-	-		-	-	-	-	-
KHRQ23M75H	BS1Q-A	BSVQ-P8B	BS4Q14A	BSV4Q100PV	BS6Q14A	BSV6Q100PV	BS8Q14A	BS10Q14A	BS12Q14A	BS16Q14A
-	EKBSVQLNP	EKBSVQLNP	-	-	-	-				
-	-	KRC19-26	-	KRC19-26 1 kit per port necessary	-	KRC19-26 1 kit per port necessary				
-	-	KJB111A	-	KJB111A	-	KJB111A				
			KHFP26A100C		KHFP26A100C		KHFP26A100C	KHFP26A100C	KHFP26A100C	KHFP26A100C
			KHRP26A1250C		KHRP26A1250C		KHRP26A1250C	KHRP26A1250C	KHRP26A1250C	KHRP26A1250C
			KDDN26A4		KDDN26A8		KDDN26A8	KDDN26A12	KDDN26A12	KDDN26A16
KHRQM22M75H	-	-	-	-		-				
KHRQ22M75H	-	-	-	-		-				

*Note: blue cells contain preliminary data

		Ceiling mounted cassette units				
		Round flow (800x800)	4-way (600x600)	2-way blow		
		FXFQ 20~125A	FXZQ 15~50A	FXCQ 20~40A	FXCQ 50~63A	FXCQ 80 ~125A
Adapters and control	**BRC1E52A/B** Premium wired remote control with full-text interface and back-light	●	●	●	●	●
	BRC1D52 Standard wired remote control with weekly timer	●*4	●*4	●*4	●*4	●*4
	Infrared remote control including receiver	BRC7FA532F	BRC7F530W *9*10 (white panel) BRC7F530S *9*10 (grey panel) BRC7EB530 *9*10 (standard panel)	BRC7C52	BRC7C52	BRC7C52
	BRC2E52A Simplified wired remote control for heat recovery system	-	-	-	-	-
	BRC3E52A Simplified wired remote control for heat pump system	-	-	-	-	-
	DCS302C51 Central remote control	●	●	●	●	●
	DCS301B51 Unified ON/OFF control	●	●	●	●	●
	DST301B51 Schedule timer	●	●	●	●	●
	DCM601A51 Intelligent Touch Manager	●	●	●	●	●
	External wired temperature sensor	KRCS01-4	KRCS01-4	KRCS01-4	KRCS01-4	KRCS01-4
	External wireless temperature sensor	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS
	Adaptor for wiring (interlock for fresh air intake fan)	-	-	-	-	-
	Wiring adapter for external monitoring/control via dry contacts and setpoint control via 0-140Ω	KRP4A53 *2*7	KRP4A53 *2	KRP4A51	KRP4A51	KRP4A51
	Wiring adapter for external central monitoring/control (controls 1 entire system)	-	KRP2A52	KRP2A51	KRP2A51	KRP2A51
	Wiring adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output)	EKRP1C11 *2*7	EKRP1B2	EKRP1B2	EKRP1B2	EKRP1B2
	Wiring adapter with 2 output signals (Compressor / Error, Fan output)	KRP1B57 *2*7	KRP1B57	-	-	-
	Adapter for multi-tenant applications (24VAC PCB power supply interface)	DTA114A61	DTA114A61	-	-	-
	External control adapter for outdoor unit	-	-	DTA104A61	DTA104A61	DTA104A61
	Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox)	KRP1H98 *7	KRP1A101	KRP1C96	KRP1C96	KRP1C96
	Connector for forced-off contact	standard	-	standard	standard	standard
	Connection to centralized control	standard	-	-	-	-
	Electrical box with earth terminal (2 blocks)	KJB212A	-	KJB212A	KJB212A	KJB212A
	Electrical box with earth terminal (3 blocks)	KJB311A	-	KJB311A	KJB311A	KJB311A
	Electrical box with earth terminal	-	-	-	-	-
	Digital input adaptor	-	-	-	-	-
Others	Decoration panel (obligatory for cassette units, optional for others, rear panel for FXLQ)	BYCQ140D7GW1 (self clean) *5/*6 BYCQ140D7W1W (white) *3 BYCQ140D7W1 (standard)	BYFQ60CW (white panel) BYFQ60CS (grey panel) BYFQ60B3 (standard panel)	BYBCQ40H	BYBCQ63H	BYBCQ125H
	Kit for mounting of decoration panel direct onto unit	-	-	-	-	-
	Panel spacer for reducing required installation height	-	KDBQ44B60 (standard panel)	-	-	-
	Sealing kit for 3-directional or 2-directional air discharge	KDBHQ55B140 *7	BDBHQ44C60 (white & grey panel)	-	-	-
	Fresh air intake kit	KDDQ55B140-1 + KDDQ55B140-2 *7*8	KDDQ44XA60	-	-	-
	Air discharge adapter for round duct	-	-	-	-	-
	Filter chamber for bottom suction	-	-	KDDFP53B50	KDDFP53B80	KDDFP53B160
	Replacement long life filter	KAFP551K160	KAFQ441BA60	KAFP531B50	KAFP531B80	KAFP531B160
	Drain pump kit	standard	standard	standard	standard	standard
	Sensor kit	BRYQ140A	BRYQ60AW (white panel) BRYQ60AS (grey panel)	-	-	-
	Noise filter (for electromagnetic use only)	-	-	KEK26-1A	KEK26-1A	KEK26-1A

*2 Installation box is necessary for these adapters

*3 The BYCQ140D7W1W has white insulation
Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140D7W1W decoration panel in environments exposed to concentrations of dirt"

*4 Not recommended because of the limitation of the functions

*5 To be able to control the BYCQ140D7GW1 the controller BRC1E is needed

*6 The BYCQ140DGW1 is not compatible with Mini VRV, Multi and Split Non-Inverter Outdoor units

*7 Option not available in combination with BYCQ140D7GW1

*8 Both parts of the fresh air intake are needed for each unit

*9 Sensing function not available

*10 Independently controllable flaps function not available

		Concealed ceiling units (duct units)					
Corner (1-way blow)		Small	Slim	Standard			
FXKQ 25~40	FXKQ 63	FXDQ 20~25 M9	FXDQ 15~63A	FXSQ 15~32	FXSQ 40~50	FXSQ 63~80	FXSQ 100~140
●	●	●	●	●	●	●	●
●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4
BRC4C61	BRC4C61	BRC4C62	BRC4C65	BRC4C65	BRC4C65	BRC4C65	BRC4C65
-	-	●	●	●	●	●	●
-	-	●	●	●	●	●	●
●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●
KRCS01-1	KRCS01-1	KRCS01-1	KRCS01-4B	KRCS01-4	KRCS01-4	KRCS01-4	KRCS01-4
K.RSS	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS
-	-	-	-	KRP1BA59	KRP1BA59	KRP1BA59	KRP1BA59
KRP4A51	KRP4A51	KRP4A51	KRP4A54	KRP4A51	KRP4A51	KRP4A51	KRP4A51
KRP2A51	KRP2A51	KRP2A51	KRP2A53	KRP2A51	KRP2A51	KRP2A51	KRP2A51
KRP1B61	KRP1B61	EKRP1B2	KRP1B56	EKRP1B2	EKRP1B2	EKRP1B2	EKRP1B2
-	-	-	-	-	-	-	-
-	-	EKMTAC	DTA114A61	DTA114A61	DTA114A61	DTA114A61	DTA114A61
DTA104A61	DTA104A61	DTA104A61	DTA104A53	DTA104A61	DTA104A61	DTA104A61	DTA104A61
-	-	-	KRP1B101	tbc	tbc	tbc	tbc
Standard	Standard	Standard	-	Standard	Standard	Standard	Standard
Standard	Standard	Standard	-	Standard	Standard	Standard	Standard
-	-	-	KJB212A	KJB212A	KJB212A	KJB212A	KJB212A
-	-	-	KJB311A	KJB311A	KJB311A	KJB311A	KJB311A
-	-	-	-	KJB411A	KJB411A	KJB411A	KJB411A
-	-	-	-	BRP7A51	BRP7A51	BRP7A51	BRP7A51
BYK45F	BYK71F	-	-	BYBS32D	BYBS45D	BYBS71D	BYBS125D
-	-	-	-	tbc	tbc	tbc	tbc
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	tbc	tbc	tbc	tbc
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
Standard	Standard	KDAJ25K56	standard	Standard	Standard	Standard	Standard
-	-	-	-	-	-	-	-
-	-	-	KEK26-1A	-	-	-	-

*Note: blue cells contain preliminary data

						Ceiling s
				Large	1-way blow	
		FXMQ 50~80	FXMQ 100~125	FXMQ 200~250	FXHQ 32A	FXHQ 63A
Adapters and control	**BRC1E52A/B** Premium wired remote control with full-text interface and back-light	●	●	●	●	●
	BRC1D52 Standard wired remote control with weekly timer	●*4	●*4	●*4	●*4	●*4
	Infrared remote control including receiver	BRC4C65	BRC4C65	BRC4C65	BRC7G53	BRC7G53
	BRC2E52A Simplified wired remote control for heat recovery system	●	●	●	-	-
	BRC3E52A Simplified wired remote control for heat pump system	●	●	●	-	-
	DCS302C51 Central remote control	●	●	●	●	●
	DCS301B51 Unified ON/OFF control	●	●	●	●	●
	DCS601C51 Schedule timer	●	●	●	●	●
	DCM601A51 Intelligent Touch Controller	●	●	●	●	●
	External wired temperature sensor	KRCS01-4	KRCS01-4	KRCS01-1	KRCS01-4	KRCS01-4
	External wireless temperature sensor	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS
	Wiring adapter for external monitoring/control via dry contacts and setpoint control via 0-140Ω	KRP4A51	KRP4A51	KRP4A51	KRP4A52	KRP4A52
	Wiring adapter for external central monitoring/control (controls 1 entire system)	KRP2A51	KRP2A51	KRP2A51	KRP2A62	KRP2A62
	Wiring adapter with 4 output signals (Compressor / Error, Fan, Aux. heater, Humidifier output)	EKRP1B2	EKRP1B2	KRP1B61	-	-
	Wiring adapter with 2 output signals (Compressor / Error, Fan output)	-	-	-	KRP1B54	KRP1B54
	Adapter for multi-tenant applications (24VAC PCB power supply interface)	DTA114A61	DTA114A61	-	-	-
	External control adapter for outdoor unit	DTA104A61	DTA104A61	DTA104A61	DTA104A62	DTA104A62
	Installation box / Mounting plate for adapter PCBs (For units where there is no space in the switchbox)	KRP4A96	KRP4A96	-	KRP1D93A	KRP1D93A
	Connector for forced-off contact	Standard	Standard	Standard	EKRORO4	EKRORO4
	Connection to centralized control	Standard	Standard	Standard	-	-
	Electrical box with earth terminal (2 blocks)	-	-	-	KJB212A	KJB212A
	Electrical box with earth terminal (3 blocks)	-	-	-	KJB311A	KJB311A
Others	Decoration panel (obligatory for cassette units, optional for others, rear panel for FXLQ)	BYBS71D	BYBS125D	-	-	-
	Kit for mounting of decoration panel direct onto unit	EKBYBSD	EKBYBSD	-	-	-
	Panel spacer for reducing required installation height	-	-	-	-	-
	Sealing kit for 3-directional or 2-directional air discharge	-	-	-	-	-
	Decorationpanel for air discharge	-	-	-	-	-
	Fresh air intake kit	-	-	-	KDDQ50A140	KDDQ50A140
	Air discharge adapter for round duct	KDAJ25K71	KDAJ25K140	-	-	-
	Replacement long life filter	-	-	-	KAFP501A56	KAFP501A80
	Drain pump kit	Standard	Standard	-	KDU50P60	KDU50P140
	Sensor kit	-	-	-	-	-
	Noise filter (for electromagnetic use only)	-	-	-	KEK26-1	KEK26-1
	L-type piping kit (for upward direction)	-	-	-	KHFP5M35	KHFP5N63

*2 Installation box is necessary for these adapters

*3 The BYCQ140D7W1W has white insulation

Be informed that formation of dirt on white insulation is visibly stronger and that it is consequently not advised to install the BYCQ140D7W1W decoration panel in environments exposed to concentrations of dirt

*4 Not recommended because of the limitation of the functions

*5 To be able to control the BYCQ140D7GW1 the controller BRC1E is needed

*6 The BYCQ140DGW1 is not compatible with Mini VRV, Multi and Split Non-Inverter Outdoor units

*7 Option not available in combination with BYCQ140D7GW1

*8 Both parts of the fresh air intake are needed for each unit

*9 Sensing function not available

*10 Independently controllable flaps function not available

uspended units		Wall mounted units	Floor standing units			
	4-way blow		Concealed	Free-standing		
FXHQ 71~100A	FXUQ 71~100A	FXAQ 15~63	FXNQ 20~63	FXLQ 20~25	FXLQ 32~40	FXLQ 50~63
•	•	•	•	•	•	•
•*4	•*4	•*4	•*4	•*4	•*4	•*4
BRC7G53	BRC7C58	BRC7EB518	BRC4C65	BRC4C65	BRC4C65	BRC4C65
-	-	-	•	•	•	•
-	-	-	•	•	•	•
•	•	•	•	•	•	•
•	•	•	•	•	•	•
•	•	•	•	•	•	•
•	•	•	•	•	•	•
KRCS01-4	KRCS01-4	KRCS01-1	KRCS01-1	KRCS01-1	KRCS01-1	KRCS01-1
K.RSS	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS	K.RSS
KRP4A52	KRP4A53 *2	KRP4A51	KRP4A51	KRP4A51	KRP4A51	KRP4A51
KRP2A62	-	KRP2A51	KRP2A51	KRP2A51	KRP2A51	KRP2A51
-	-	-	KRP1B61	KRP1B61	KRP1B61	KRP1B61
KRP1B54	-	-	-	-	-	-
-	-	DTA114A61	EKMTAC	EKMTAC	EKMTAC	EKMTAC
DTA104A62	-	DTA104A61	-	-	-	-
KRP1D93A	KRP1B97	KRP4A93	-	-	-	-
EKRORO4	EKRORO5	Standard	Standard	Standard	Standard	Standard
-	-	Standard	Standard	Standard	Standard	Standard
KJB212A	KJB212A	-	-	-	-	-
KJB311A	KJB311A	-	-	-	-	-
-	-	-	-	EKRDP25A	EKRDP40A	EKRDP63A
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	KDBHP49B140	-	-	-	-	-
-	KDBTP49B140	-	-	-	-	-
KDDQ50A140	-	-	-	-	-	-
-	-	-	-	-	-	-
KAFP501A160	KAFP551K160	-	-	-	-	-
KDU50P140	-	K-KDU572EVE	-	-	-	-
-	-	-	-	-	-	-
KEK26-1	-	-	-	-	-	-
KHFP5N160	-	-	-	-	-	-

*Note: blue cells contain preliminary data

Options & accessories - Ventilation & hot water

		VAM150FA	VAM250FA	VAM350FB	VAM500FB	VAM650FB
Dust filters	EN779 Medium M6	-	-	EKAFV50F6	EKAFV50F6	EKAFV80F6
	EN779 Fine F7	-	-	EKAFV50F7	EKAFV50F7	EKAFV80F7
	EN779 Fine F8	-	-	EKAFV50F8	EKAFV50F8	EKAFV80F8
Silencer	Model name	-	-	-	KDDM24B50	KDDM24B100
	Nominal pipe Diameter (mm)	-	-	-	200	200
CO_2 sensor		-	-	BRYMA65	BRYMA65	BRYMA65
VH electrical heater for VAM		VH1B	VH2B	VH2B	VH3B	VH3B

Individual control systems	VAM-FA/FB	VKM-GB(M)
Wired remote control	BRC1E52A/B / BRC1D52	BRC1E52A/B / BRC1D52
VAM wired remote control	BRC301B61	-

Centralised control systems	VAM-FA/FB	VKM-GB(M)
Centralised remote control	DCS302C51	DCS302C51
Unified ON/OFF control	DCS301B51	DCS301B51
Schedule timer	DST301B51	DST301B51

Others	VAM150-250FA	VAM350-2000FB	VKM-GB(M)
Wiring adapter for electrical appendices (note 6)	KRP2A51	KRP2A51 (note 3)	BRP4A50A (note 4/5)
Adapter PCB for humidifier	KRP50-2	BRP4A50A (note 4/5)	BRP4A50A (note 4/5)
Adapter PCB for 3rd party heater	BRP4A50	BRP4A50A (note 4/5)	BRP4A50A (note 4/5)
Remote sensor	-	-	-

Notes

(1) Cool/heat selector required for operation

(2) Do not connect the system to DIII-net devices (Intelligent controller, Intelligent Manager, LonWorks interface, BACnet interface…).

(3) Installation box KRP1BA101 needed.

(4) Fixing plate EKMPVAM additionally needed for VAM1500-2000FB.

(5) 3rd party heater and 3rd party humidifier cannot be combined

(6) For external control and monitoring (ON/OFF control, operation signal, error indication)

	VH electrical heater for VAM
Supply voltage	220/250V ac 50/60 Hz. +/-10%
Output current (maximum)	19A at 40°C (ambient)
Temperature sensor	5k ohms at 25°C (table 502 1T)
Temperature control range	0 to 40°C / (0-10V 0-100%)
Run on timer	Adjustable from 1 to 2 minutes (factory set at 1.5 minutes)
Control fuse	20 X5 mm 250 m A
LED indicators	Power ON - Yellow Heater ON - Red (solid or flashing, indicating pulsed control) Airflow fault - Red
Mounting holes	98mm X 181mm centres 5 mm ø holes
Maximum ambient adjacent to terminal box	35°C (during operation)
Auto high temp. cutout	100°C Pre-set
Man. reset high temp. cutout	125°C Pre-set
Run relay	1A 120V AC or 1A 24V DC
BMS setpoint input	0-10VDC

Vh electrical heater for vam		vH1B	VH2B	VH3B	VH4B	VH4/AB	VH5B
Capacity	kW	1	1	1	1.5	2.5	2.5
Duct diameter	mm	100	150	200	250	250	350
Connectable VAM		VAM150FA	VAM250FA	VAM500FB	VAM800FB	VAM800FB	VAM1500FB
		-	VAM350FB	VAM650FB	VAM1000FB	VAM1000FB	VAM2000FB

VAM800FB	VAM1000FB	VAM1500FB	VAM2000FB	VKM50GB(M)	VKM80GB(M)	VKM100GB(M)
EKAFV80F6	EKAFV100F6	EKAFV100F6 x2	EKAFV100F6 x2	-	-	-
EKAFV80F7	EKAFV100F7	EKAFV100F7 x2	EKAFV100F7 x2	-	-	-
EKAFV80F8	EKAFV100F8	EKAFV100F8 x2	EKAFV100F8 x2	-	-	-
KDDM24B100	KDDM24B100	KDDM24B100 x2	KDDM24B100 x2	-	KDDM24B100	KDDM24B100
250	250	250	250	-	250	250
BRYMA100	BRYMA100	BRYMA200	BRYMA200	BRYMA65	BRYMA100	BRYMA200
VH4B / VH4/AB	VH4B / VH4/AB	VH5B	VH5B	-	-	-

EKEQFCB [2]	EKEQDCB [2]	EKEQMCB [2]
BRC1E52A/B / BRC1D52	BRC1E52A/B / BRC1D52 [1]	BRC1E52A/B / BRC1D52 [1]
-	-	-

EKEQFCB [2]	EKEQDCB [2]	EKEQMCB [2]
-	-	-
-	-	-
-	-	-

EKEQFCB [2]	EKEQDCB [2]	EKEQMCB [2]
-	-	-
-	-	-
-	-	-
	KRCS01-1	

	HXY080-125A	HXHD125A
Drain pan	EKHBDPCA2	-
Digital I/O PCB	EKRP1HBAA	-
Demand PCB - Required to connect room thermostat	EKRP1AHTA	-
Remote user interface (remocon) - Same controller as supplied with cascade unit can be mounted parallel or on other location. If 2 controllers are installed, the installer needs to select 1 master & 1 slave	EKRUAHTB	-
Back-up heater	EKBUHAA6(W1/V3)	-
Wired room thermostat - Requires demand PCB EKRP1AHTA	EKRTWA	-
Wireless room thermostat - Requires demand PCB EKRP1AHTA	EKRTR1	-
Remote sensor for room thermostat - Requires demand PCB EKRP1AHTA	EKRTETS	-
Domestic hot water tank - standward (stacked on top of hydrobox)	-	EKHTS200AC EKHTS260AC
Domestic hot water tank - with possibility for solar connection	-	EKHWP500B
Solar collector *1	-	EKSV26P (vertical) EKSH26P (horizontal)
Pump station	-	EKSRPS

*1 pump station is necessary for this option

Options - Chillers

Options - Small chillers

Chiller series	Integrated hydronics	LWE		Electrical
	Single pump	High Glycol	Low Glycol	Evaporator heater tape
	OPSP	OPZH	OPZL	OP10
EWAQ-ADVP	STD			STD
EWYQ-ADVP	STD			STD
EWAQ-ACV3	STD			STD
EWAQ-ACW1	STD			STD
EWYQ-ACV3	STD			STD
EWYQ-ACW1	STD			STD
EWWP-KBW1N		Option	Option	
EWLP-KBW1N		Option	Option	

(s) OP12 & OP03 need to be added to meet Swedish national law 1992: 16 (1) Impossible option combination: OPZH+OPZL

Options - Medium and large chillers (Part 1)

Description	Code	EWAQ~BAW EWYQ~BAW	EWAQ-E-XS EWAQ-F-SS/XS	EWAQ-E-XL/XR EWAQ-F-SL/SR/XL/XR	EWYQ-F-XS	EWYQ-F-XL	EWYQ-F-XR	EWAD-E-	EWAD-D-SS	EWAD-D-SL	EWAD-D-SR	EWAD-D-SX	EWAD-D-XS	EWAD-D-XR	EWAD-D-HS
Total heat recovery	01							Option	Option	Option	Option	Option	Option	Option	Option
Total heat recovery (1 circuit)	02								Option	Option	Option	Option	Option	Option	Option
Partial heat recovery	03		Option	Option	CF	CF	CF	Option	Option	Option	Option	Option	Option	Option	Option
Direct on line starter (DOL)	04		STD	STD	STD	STD	STD								
Wye-Delta compressor starter (Y-D)	05							STD	STD	STD	STD	STD	STD	STD	STD
Soft starter	06		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Heat pump version	07														
Heat pump version (including pursuit mode)	07a														
Brine version (down -8°C)	08a (1)														
Brine version (down -10°C)	08b (1)	Option													
Brine version (down -15°C)	08c (1)		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Double setpoint	10		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Compressor thermal overload relays	11		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Fans thermal relays	12														
Phase monitor	13		Option	Option	Option	Option	Option	STD	STD	STD	STD	STD	STD	STD	STD
Inverter compressor starter	14								Option(4)	Option(4)	Option(4)	Option(4)	Option(4)	Option(4)	Option(4)
Under / Over voltage control	15		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Energy meter	16		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Energy meter (including current limit)	16a														
Capacitors for power factor correction	17		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Auxiliary relay	18														
Current limit	19							Option	Option	Option	Option	Option	Option	Option	Option
Evaporator victaulic kit	20		STD	STD	STD	STD	STD		STD			STD	STD	STD	
Evaporator flange kit	21								Option			Option	Option	Option	
Evaporator marine waterbox victaulic (2 passes)	22														
Evaporator marine waterbox victaulic (1 pass)	22a														
Evaporator marine waterbox victaulic (3 passes)	23														
Evaporator marine waterbox flanged (2 passes)	24														
Evaporator marine waterbox flanged (1 pass)	24a														
Evaporator marine waterbox flanged (3 passes)	25														
Condenser double flanges kit	26														
Evaporator water side design pressure (10 Bar)	27								STD	STD	STD	STD	STD	STD	STD
Evaporator water side design pressure (16 Bar)	28														
20mm evaporator insulation	29		STD	STD	STD	STD	STD	Option	Option	STD	STD	Option	Option	Option	STD
Axial fans (100 Pa lift)	30														
McQuiet	31														
Axial fans (250 Pa lift)	32		CF						CF	CF	CF	CF	CF	CF	CF
20mm condenser insulation	33														
Fan silent mode	34														
Fans Speed Control Device (Phase Cut)	35														
Condenser victaulic kit	36														
Condenser flange kit	37														
Condenser marine waterbox victaulic (2 passes)	38														
Condenser marine waterbox victaulic (1 pass)	38a														
Condenser marine waterbox victaulic (3 passes)	39														
Condenser marine waterbox flanged (2 passes)	40														
Condenser marine waterbox flanged (1 pass)	40a														
Condenser marine waterbox flanged (3 passes)	41														
Speedtrol (fan speed control device - ON/OFF - up to -18°C)	42		Option	Option				Option	Option	Option	Option		Option	Option	Option
Speedtrol (fan speed control device - ON/OFF - down to -10°C in cooling)	42a				Option	Option									
Condenser coil guards	43		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Evaporator area guards	44		Option	Option	Option	Option	Option								
Cu-Cu condenser coil	45		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Cu-Cu-Sn condenser coil	46		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option

EWAD-C-	EWAD-CZ	EWAD-TZ	EWAQ-GZ	EWYQ-GZ	EWAD-CF	EWYD-BZSS	EWYD-BZSL	ERAD-E-	EWWQ-B-	EWWD-J-SS	EWWD-G-	EWWD-I-SS	EWWD-I-XS	EWWD-H-XS	EWLD-J-SS	EWLD-G-SS	EWLD-I-SS	EWWD-FZXS
Option	Option	Option						Option			Option	Option						
Option	Option	Option				Option	Option	Option	Option		Option	Option	Option			Option		
STD					STD			STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	
Option					Option			Option	Option	Option(4)	Option	Option	Option	Option	Option(4)	Option	Option	
														Option				
										Option	Option	Option	Option					
Option	Option	Option			Option	Option	Option		Option	Option	Option	Option	Option	NC-SO	Option	Option	Option	
			Option	Option														
STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD		STD	STD	
Option	STD	STD			Option			Option	Option	Option	Option	Option	Option	Option		Option	Option	
STD	STD	STD	Option	Option	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	
	STD	STD				STD	STD											STD
Option	Option	STD	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	
Option	Option		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
		Option																
Option					Option			Option	Option	Option	Option	Option	Option	Option		Option	Option	
Option	Option				Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	STD
STD	STD	STD	STD	STD		STD	STD		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Option	Option	Option			STD													
														Option				CF
														Option				
														Option				
														Option				
									Option	Option	Option	Option	Option	Option				Option
									STD		STD	STD	STD	STD		STD	STD	STD
STD	STD	STD	STD	STD	STD	Option	Option		Option	STD	Option	Option	Option	STD	STD	Option	Option	STD
									Option	Option	Option	Option	Option	Option				Option
									Option	STD	Option	Option	Option	STD				STD
														Option				CF
														Option				
														Option				
														Option				
Option	Option	Option	Option	Option				Option										
Option	Option	Option	Option	Option	Option	Option	Option	Option										
Option	Option		Option	Option	Option													
Option	Option	Option	Option	Option	Option	Option	Option	Option										
Option	Option	Option	Option	Option	Option	Option	Option	Option										

Options - Medium and large chillers (Part 2)

Description	Code	EWAQ~BAW EWYQ~BAW	EWAQ-E-XS EWAQ-F-SS/XS	EWAQ-E-XL/XR EWAQ-F-SL/ XR/XL/XR	EWYQ-F-XS	EWYQ-F-XL	EWYQ-F-XR	EWAD-E-	EWAD-D-SS	EWAD-D-SL	EWAD-D-SR	EWAD-D-SX	EWAD-D-XS	EWAD-D-XR
Condenser water side design pressure (16 Bar)	47													
Condenser water side design pressure (10 Bar)	47a													
Alucoat fins coil	49		Option	Option	STD	STD	STD	Option	Option	Option	Option	Option	Option	Option
Cu-Ni 90-10 condenser tubes	50													
Condenser 1 pass (ΔT 4-8 °C)	51													
Condenser 2 passes (ΔT 4-8 °C)	52													
Condenser 2 passes (ΔT 9-15 °C)	53													
Condenser 4 passes	54													
Water pressure differential switch on condenser	55													
Water pressure differential switch on evaporator	56									STD	STD			
Evaporator electric heater	57	Option	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Evaporator flow switch	58		STD	STD	STD	STD	STD	Option	Option	Option	Option	Option	Option	Option
Condenser flow switch	59													
Electronic expansion valve	60		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Discharge line shut-off valve	61		Option	Option	Option	Option	Option	STD	STD	STD	STD	STD	STD	STD
Suction line shut-off valve	62		Option	Option	Option	Option	Option	STD	STD	STD	STD	STD	STD	STD
High pressure side manometers	63		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Low pressure side manometers	64		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Ambient outside temperature sensor and setpoint reset	67		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Hour run meter	68		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
General fault contactor	69		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Container Kit	71		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Rubber anti vibration mounts	75		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Sound proof system	76													
Sound proof system (integral)	76-a													
Sound proof system (compressor)	76-b													
Spring anti vibration mounts	77		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
One centrifugal pump (low lift)	78	Option						Option						
One centrifugal pump --- SPK1	78-a		Option	Option	Option	Option	Option			Option	Option			
One centrifugal pump --- SPK2	78-b		Option	Option	Option	Option	Option			Option	Option			
One centrifugal pump --- SPK3	78-c		Option	Option	Option	Option	Option			Option	Option			
One centrifugal pump --- SPK4	78-d		Option	Option	Option	Option	Option			Option	Option			
One centrifugal pump --- SPK5	78-e								Option				Option	Option
One centrifugal pump --- SPK6	78-f								Option				Option	Option
One centrifugal pump --- SPK7	78-g								Option				Option	Option
One centrifugal pump --- SPK8	78-h								Option				Option	Option
One centrifugal pump --- SPK9	78-i												Option	
One centrifugal pump --- SPK10	78-j												Option	
One centrifugal pump --- SPK1a	78-l				Option	Option	Option							
One centrifugal pump --- SPK1b	78-m				Option	Option	Option							
One centrifugal pump --- SPK1c	78-n				Option	Option	Option							
One centrifugal pump (high lift)	79	Option						Option						
Two centrifugal pump (low lift)	80													
Two centrifugal pump --- DPK1	80-a									Option	Option			
Two centrifugal pump --- DPK2	80-b									Option	Option			
Two centrifugal pump --- DPK3	80-c									Option	Option			
Two centrifugal pump --- DPK4	80-d									Option	Option			
Two centrifugal pump --- DPK5	80-e								Option				Option	Option
Two centrifugal pump --- DPK6	80-f								Option				Option	Option
Two centrifugal pump --- DPK7	80-g								Option				Option	Option
Two centrifugal pump --- DPK8	80-h								Option				Option	Option
Two centrifugal pump (high lift)	81													
Witness test	82													
External tank without cabinet (500 L)	83 (3)		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
External tank without cabinet (1000 L)	84 (3)		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
External Tank (500 L) With CABINET RAL 7042	85													
External Tank (1000 L) With CABINET RAL 7042	86													
External tank with cabinet (500 L)	87 (3)		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
External tank with cabinet (1000 L)	88 (3)		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Acoustic test	89													
Setpoint reset, Demand limit and Alarm from external device	90		Option	Option	Option	Option	Option	STD	STD	STD	STD	STD	STD	STD
Double pressure relief valve with diverter	91		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
PW COMPRESSOR - PART WINDING START	92													
Low ambient kit for 1 circuit	93													
Low ambient kit for 2 circuits	94													
Compressors circuit breakers	95		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Fans circuit breakers	96		Option	Option	Option	Option	Option	STD	STD	STD	STD	STD	STD	STD
Main switch interlock door	97		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Emergency stop	98													
Fans speed regulation (+ fan silent mode)	99 (2)		Option	Option				Option	Option	Option	Option	STD	Option	Option
Fans speed regulation (inverter)	99a (2)				Option	Option	STD							
Refrigerant recovery unit	100													
Evaporator right water connections	101								SO	SO	SO	SO	SO	SO
Ground fault relay	102		Option	Option	Option	Option	Option							
Evaporator 1 pass	103													
Evaporator 2 passes	103a													
Evaporator double flange kit	104													
Liquid receiver	105													
Evaporator right water connections	106													
Rapid restart	110													
High temperature kit	111													
Transport kit	112		Option	Option	Option	Option		Option	Option	Option	Option	Option	Option	Option
Optimized free cooling (VFD fans regulation)	113-a													
Optimized free cooling (On/Off fans)	113-b													
Nordic kit	114				Option	Option	Option							
Water filter	115		STD	STD	STD	STD	STD							
Condenser coil protection panels	116		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Blygold coil treatment	117		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Inverter kit for pump (SPK1-SPK6)	120a													
Inverter kit for pump (SPK7-SPK10)	120b													
Inverter kit for pumps (DPK2-DPK6)	120c													
Inverter kit for pumps (DPK7-DPK10)	120d													
Refrigerant leak detection	121													

(1) Option 08 includes option 29 - (2) Option 99(a) includes 'Fan overload protection' - (3) Piping between the inertial tank and the unit is not included. Electric heater power supply has to be provided from external source - (4) The order of inverter compressor will have an impact on the delivery time: please contact the factory - (5) Unit performance will be affected; contact factory for information. It is mandatory to order the option 26 when selecting CU-Ni 90-10 condenser tubes - (6) Sound proof system - compressor enclosure - (7) Compressor enclosure - (8) Soundproof cabinet will be supplied in a separate kit and not assembled. For better performance the cabinet will be integral kind (around the whole chiller, not only around compressors). Cabinet assembly is not included in the supply (9) Special transport is required (flat rack truck and open top when option 01 is selected) for model sizes as follows: EWWDC12I-SS - EWWDC18I-SS (10) Forklift loading-unloading operations are not allowed when option 01

EWAD-D-HS	EWAD-C-	EWAD-CZ	EWAD-TZ	EWAQ-GZ	EWYQ-GZ	EWAD-CF	EWYD-BZSS	EWYD-BZSL	ERAD-E-	EWWQ-B-	EWWD-J-SS	EWWD-G-	EWWD-I-SS	EWWD-I-XS	EWWD-H-XS	EWLD-J-SS	EWLD-G-SS	EWLD-I-SS	EWWD-FZXS
										STD	STD	STD	STD	STD					
															STD				STD
Option	Option	Option	Option		STD	Option	Option	Option	Option										
										Option	Option(5)	Option (5)	Option (5)	Option (5)	Option (5)		Option (5)		Option (5)
												STD	STD		NC-SO		STD		
											STD			STD	STD				STD
													NC-SO						
														NC-SO					
															Option				STD
STD				STD	STD										Option				STD
STD	STD	STD	STD	STD	STD	STD	STD	STD		Option									
Option	Option	Option	Option			Option	Option	Option		Option	STD	Option	Option	Option	Option	STD	Option	Option	Option
															Option				Option
STD	STD	STD	STD	STD	STD	STD	STD	STD		STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
STD	STD	STD	STD	Option	Option	STD	STD	STD	STD	Option	STD	STD	Option	Option	STD	STD	STD	Option	
STD	Option	STD	STD	Option	Option	Option	STD	STD	STD	Option	STD	STD	Option	Option	Option	STD	STD	Option	Option
Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Option	Option	Option	Option	Option	Option	Option	Option	Option		Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
STD	STD	STD	STD	STD	STD	STD	STD	STD	STD										
STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Option	Option	Option	Option	Option	Option		Option	Option	Option	Option(11)	Option	Option	Option (9)	Option	Option	Option	Option	Option(11)	Option
Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
										Option (8)			Option (8)	Option (8)	Option (8)			Option (8)	Option (8)
											Option (6)	Option (7)				Option (6)	Option (7)		
Option	Option	Option	Option	Option	Option	Option	Option	Option	Option										
				Option	Option		Option												
Option	Option	Option				Option													
Option	Option	Option	Option			Option													
Option			Option																
Option			Option																
			Option																
			Option																
			Option																
			Option																
			Option																
			Option																
			Option																
							Option												
Option			Option	Option	Option		Option	Option											
Option			Option	Option	Option		Option	Option											
Option			Option	Option	Option		Option	Option											
Option			Option	Option	Option		Option	Option											
STD	STD	STD	STD	Option	Option	STD	Option	Option	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
Option	Option	Option	Option			Option	Option	Option	Option	Option	Option	Option	Option	Option	STD	Option	Option	Option	STD
Option	Option	Option	Option	Option	Option	Option			Option						Option				
STD	STD	STD	STD	STD	STD	STD	STD	STD	STD										
STD	STD	STD	STD	STD	STD	STD			STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	
	STD	STD				STD				STD	STD	STD	STD	STD	STD	STD	STD	STD	
Option	Option	Option	STD (14)			STD	Option	STD	Option										
	CF	CF																	
SO	SO	SO	Option			SO	Option	SO											
	Option	Option		Option	Option	Option				Option	Option	Option	Option	Option	Option	Option	Option	Option	
															NC-SO				NC-SO
															STD				STD
										Option		Option	Option	Option	Option		Option	Option	Option
																Option	Option	Option	
	Option	Option	Option			Option													
															Option				
Option	Option	Option	Option	Option	Option		Option	Option	Option	Option(12)	Option	Option	Option(10)	Option	Option	Option	Option	Option(12)	Option
						Option													
					Option	Option													
				STD	STD		Option	Option											
			STD (13)	Option	Option														
Option	Option	Option	Option			Option	Option	Option	Option										
Option	Option	Option	Option			Option			Option										
			Option																
			Option																
			Option																
			Option																
			Option																

is selected for model sizes as follows: EWWDC12I-SS - EWWDC18I-SS - (11) Special Transport is required (flat rack truck and open top) for model sizes as follows: EWLDC10I-SS - EWLDC17I-SS or EWWQC11B-SS - EWWQC20B-SS or EWWQC10B-XS, EWWQC12B-XS - EWWQC21B-XS - (12) Forklift loading-unloading operations are not allowed for model sizes as follows: EWLDC10I-SS - EWLDC17I-SS or EWWQC11B-SS - EWWQC20B-SS or EWWQC10B-XS, EWWQC12B-XS - EWWQC21B-XS - (13) STD only for single circuit unit (14) STD only for Premium and High efficiency version

CF = Contact the factory - STD = Standard - SO = Specify at Order entry - NC = No additional cost

Accessories - Chillers

	Air cooled chillers							
	EWA/YQ009-011ACV3 EWA/YQ009-013ACW1	EWA/YQ~BA* SEHVX+SERHQ	EWAD-E- ERAD-E-	EWAD~D-	EWYD-BZ	EWAD~C-	EWAD~CZ EWAD~TZ	EWAD-CF
Panels								
EKDSSP					●			
EKDSSP-S***			●	●		●	●	●
EKDDSP			●	●	●	●	●	●
EKPWPRO					●			
EKPWPROM					●			
Serial Cards & Comm. Modules								
EKAC10C								
EKAC200J					●			
EKACBAC					●			
EKACLON					●			
EKACLONP					●			
EKACRS232					●			
EKACWEB					●			
EKACBACMSTP					●			
EKACBACCERT								
EKCM200J			●	●		●	●	●
EKCMLON			●	●		●	●	●
EKCMBACMSTP			●	●		●	●	●
EKCMBACIP			●	●		●	●	●
Other Systems & Accessories								
RTD-W		●						
EKCC-W		●						
EKCON					●			
EKCONUSB					●			
EKMODEM					●			
EKGSMOD					●			
EKRP1HB	●							
EKRUPCJ					●			
EKRUPCS			●	●		●	●	●
EKPV2J					●			
EKPWPROEXT					●			
EKGWWEB					●			
EKGWMODEM					●			
EKRUMCA								
EHMC*								
EKRP1AHT		●						
DTA104A62		●						
EKRUAHTB		●						
Gauges								
BHGP26A1		●						
Soft starter								
EKSS								

* To install EKRUMCA => EKAC10C needs to be installed on the unit.

* EKAC10C allows direct connection to MODBUS BMS system

		Water cooled and condenserless chillers						
EWAQ-E-/F- EWYQ-F-	EWAQ-GZ EWYQ-GZ	EWW(L)P-KBW1N	EWW(L)D~G-	EWW(L)D~I-	EWWD~H-	EWWQ~B-	EWW(L)D~J-	DWSC & DWDC EWWD-FZXS
								●
●	●		●	●	●	●	●	
●	●		●	●	●	●	●	●
								●
								●
		●						
								●
								●
								●
								●
								●
								●
								●
●	●		●	●	●	●	●	
●	●		●	●	●	●	●	
●	●		●	●	●	●	●	
●	●		●	●	●	●	●	
								●
								●
								●
								●
●	●		●	●	●	●	●	●
								●
								●
								●
		●						
		●						
		● (014-045)						

Accessories - Fan coil units

Network & control systems	FWM~D / FWL~D / FWV~D	FWS~A / FWR~A / FWZ~A
Wired remot control (Standard)	FWEC1A	-
Temperature sensor kit	FWTSKA	FWTSKA
Relative humidity sensor kit	FWHSKA	FWHSKA
Fan stop thermostat	YFSTA6	-
Master slave interface	EPIMSB6	-
Power interface	-	-
Optional PCB for MOD-bus connection	-	-

	FWM~D / FWL~D / FWV~D										FWS~A / FWR~A / FWZ~A			
Valves	**1**	**15**	**2**	**25**	**3**	**35**	**4**	**6**	**8**	**10**	**2**	**3**	**6**	**8**
3-ways 230V on/off valve kit (2-pipe)	E2MV03A6						E2MV06A6		E2MV10A6		E2MV03A6			E2MV10A6
3-ways 230V on/off valve kit (4-pipe)	E1MV03A6						E4MV06A6		E4MV10A6		E4MV03A6			E4MV10A6
2-ways 230V on/off valve kit (cooling heat exchanger)	E2MV2B07A6								E2MV2B10A6		E2MV2B07A6			E2MV2B10A6
2-ways 230V on/off valve kit (additional heat exchanger)	E2MV2B07A6										E2MV2B07A6			
Simplified 3-ways 230V on/off valve kit (2-pipe)	E2MVD03A6						E2MVD06A6		E2MVD10A6		E2MVD03A6		E2MVD06A6	E2MVD10A6
Simplified 3-ways 230V on/off valve kit (4-pipe)	E4MVD03A6						E4MVD06A6		E4MVD10A6		E4MVD03A6		E4MVD06A6	E4MVD10A6
3-ways 24V on/off valve kit (2-pipe)	E2M2V03A6						E2M2V06A6		E2M2V10A6		E2M2V03A6		E2M2V06A6	E2M2V10A6
3-ways 24V on/off valve kit (4-pipe)	E4M2V03A6						E4M2V06A6		E4M2V10A6		E4M2V03A6		E4M2V06A6	E4M2V10A6
3-ways proportional valve kit (2-pipe)	E2MPV03A6						E2MPV06A6		E2MPV10A6		-			
3-ways proportional valve kit (4-pipe)	E4MPV03A6						E4MPV06A6		E4MPV10A6		-			
2-ways 24V on/off valve kit (cooling heat exchanger)	E2M2V207A6								E2M2V210A6		E2M2V207A6			E2M2V210A6
2-ways 24V on/off valve kit (additional heat exchanger)	E2M2V207A6										E2M2V207A6			
2-ways proportional valve kit (cooling heat exchanger)	E2MPV207A6								E2MPV210A6		-			
2-ways proportional valve kit (additional heat exchanger)	E2MPV207A6										-			
3-ways 230V on/off valve kit (additional heat exchanger)	-										-			
2-ways 230V on/off valve kit (2-pipe)	-										-			
2-ways 230V on/off valve kit (4-pipe)	-										-			

	FWF~C	FWG~AT	FWG~AF
Panels + valve	**All sizes**	**All sizes**	**All sizes**
Decoration panel 600x600 (2-pipe)	DCP600TC	-	-
Decoration panel + wireless controller	-	DCP900BTA	DCP900BFA
3-ways on/off valve	MCKCW2T3VN	MCKEW2T3VN	MCKEWH4T3VN

FWD~A		FWB~B	FWP~A	FWE ~C	FWT~CT	FWF~CT	FWG~A
FWEC1A		FWEC1A	-	FWEC1A	-	-	BRD51A61
FWTSKA		FWTSKA	FWTSKA	FWTSKA	-	-	-
FWHSKA		FWHSKA	FWHSKA	FWHSKA	-	-	-
YFSTA6		YFSTA6	-	-	-	-	-
EPIMSB6		EPIMSB6	-	EPIMSB6	-	-	-
-	EPIB6	-	-	-	-	-	-
-		-	-	-	-	-	-

FWD~A							FWB~B			FWP~A		FWE~C	FWC~B	FWF~B
4	6	8	10	12	16	18	2-4	5-7	8-10	2-4	5-7	All sizes	All sizes	All sizes
ED2MV04A6	ED2MV10A6			ED2MV12A6	ED2MV18A6		-			-		EK2MV3B10C5	EKMV3C09B	EKMV3C09B
ED2MV04A6	ED2MV10A6			2x ED2MV12A6	2xED2MV18A6		-			-		EK4MV3B10C5	2 xEKMV3C09B	2 x EKMV3C09B
-							E2MV207A6		E2MV210A6	E2MV207A6		-	-	-
-							E2MV207A6		E2MV210A6	E2MV207A6		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							-			-		-	-	-
-							E2MV307A6		E2MV310A6	E2MV307A6		-	-	-
-							-			-		EK2MV2B10C5	EKMV2C09B	EKMV2C09B
-							-			-		EK4MV2B10C5	2 xEKMV2C09B	2 xEKMV2C09B

	FWM~D / FWL~D / FWV~D										FWS~A /FWR~A / FWZ~A	
Other accessories	**1**	**15**	**2**	**25**	**3**	**35**	**4**	**6**	**8**	**10**	**2**	**3**
Electric heater (Standard)	EEH01A6	EEH02A6		EEH03A6		EEH06A6			EEH10A6		EEH02A6	EEH03A6
Electric heater (Big)	-										-	
Fresh air intake	EFA02A6			EFA03A6		EFA06A6			EFA10A6		EFA02A6	EFA03A6
Additional heat exchanger	ESRH02A6			ESRH03A6		ESRH06A6			ESRH10A6		ESRH02A6	ESRH03A6
Air intake & discharge grille	EAIDF02A6			EAIDF03A6		EAIDF06A6			EAIDF10A6		EAIDF02A6	EAIDF03A6
Rear panel	ERPV02A6			ERPV03A6		ERPV06A6			ERPV10A6		ERPV02A6	ERPV03A6
Supporting feet	ESFV06A6								ESFV10A6			ESFV06A6
Supporting feet & grille	ESFVG02A6			ESFVG03A6		ESFVG06A6			ESFVG10A6		ESFVG02A6	ESFVG03A6
Plenum box with circular connections	EPCC02A6 (only for FWM-D)			EPCC03A6 (only for FWM-D)		EPCC06A6 (only for FWM-D)			EPCC10A6 (only for FWM-D)		EPCC02A6 (only for FWS-A)	EPCC03A6 (only for FWS-A)
Vertical auxiliary drainpan	EDPVB6										EDPVB6	
Horizontal auxiliary drainpan	EDPHB6										EDPHB6	

Mechanical options	**FWC~BT/BF**	**FWF~BT/BF**
Decoration Panel - Standard (Round flow)	BYCQ140CW1	-
Decoration Panel - White (Round flow)	BYCQ140CW1W	-
Decoration Panel (4-way blow)	-	BYFQ60B3
Sealing member of air discharge outlet	KDBHQ55C140	KDBH44BA60
Long-life filter	KAFP551K160	KAFQ441BA60
Fresh air intake kit (20% fresh air) (Direct installation)	KDDQ55C140	-
Fresh air intake kit (Direct installation)	-	KDDQ44XA60
Panel spacer	KDBQ44B60	-

Control options	**FWF~BT/BF**	**FWC~BT/BF**
Infrared remote control (H/P)	BRC7E530	BRC7E532F
Infrared remote control (C/O)	BRC7E531	BRC7E533F
Remote sensor	KRCS01-1	KRCS01-4
Remote ON / OFF	EKROROA	-

Control options	**FWF~BT/BF - FWC~BT/BF**
Remote control wired	BRC315D7
Central remote control	DCS302CA51
Intelligent touch controller	DCS601C51C
Unified ON/OFF controller	DCS301BA51
Electrical installation box with earth terminal (2 blocks)	KJB212A
Electrical installation box with earth terminal (3 blocks)	KJB311A
Electrical installation box	KJB411A
Schedule timer	DST301BA51
Wiring adapter for electrical appendices	KRP4AA53
Wiring adapter for electrical appendices	KRP2A52
Noise filter (for electromagnetic interface use only)	KEK26-1A
Installation box for adaptor PCB	KRP1BA101
Installation box for adaptor PCB	KRP1H98
Optional PCB for MOD-bus connection	EKFCMBCB7
2-way valve - On / Off	EKMV2C09B7
3-way valve - On / Off	EKMV3C09B7
Valve control PCB	EKRP1C11

FWS~A / FWR~A / FWZ~A		FWD~A							FWB~B			FWP~A	
6	8	4	6	8	10	12	16	18	2-4	5-7	8-10	2-4	5-7
EEH06A6	EEH10A6	EDEH04A6	EDEHS06A6	EDEHS10A6		EDEHS12A6	EDEHS18A6		Factory mounted			Factory mounted	
-		EDEH04A6	EDEHB06A6	EDEHB10A6		EDEHB12A6	EDEHB18A6		-			-	
EFA06A6	EFA10A6	EDMFA04A6	EDMFA06A6	EDMFA10A6		EDMFA12A6	EDMFA18A6		-			-	
ESRH06A6	ESRH10A6	-							EAH04A6	EAH07A6	EAH10A6	EAH04A6	EAH07A6
EAIDF06A6	EAIDF10A6	-							-			-	
ERPV06A6	ERPV10A6	-							-			-	
	ESFV10A6	-							-			-	
ESFVG06A6	ESFVG10A6	-							-			-	
EPCC06A6 (only for FWS-A)	EPCC10A6 (only for FWS-A)	-							-			-	
EDPVB6		EDDPV10A617				EDDPV18A617			-			-	
EDPHB6		EDDPH10A621				EDDPH18A621			-			-	

D-AHU Professional

Construction type		SP 65	SP 45	FP 50	FP 25
Profile	Aluminium	standard	standard	standard	standard
	Anodized aluminium	option	option	option	option
	Aluminium with thermal break	option	option	option	option
	Anodized aluminium with thermal break	option	option	option	option
Corner	Glass fibre reinforced nylon	standard	standard	standard	standard
Panel insulation	Polyurethane foam density 45 kg/m³ thermal conductivity 0.020 W/m*K fire reaction class 1	standard	standard	standard	standard
	Mineral wool density 90 kg/m³ thermal conductivity 0.037 W/m*K (referred to 20°C) fire reaction class 0	option	option	option	option
External sheet material	Grey Plastisol covered galvanized steel	standard	standard	standard	standard
	Pre-coated galvanized steel	option	option	option	option
	Galvanized steel	option	option	option	option
	Aluminium	option	option	option	option
	AISI 304 stainless steel	option	option	option	option
Internal sheet material	Galvanized steel	standard	standard	standard	standard
	Pre-coated galvanized steel	option	option	option	option
	Grey Plastisol covered galvanized steel	option	option	option	option
	Aluminium	option	option	option	option
	AISI 304 stainless steel	option	option	option	option
Base frame	Aluminium	standard (from size 1 to size 17)	standard (from size 1 to size 17)	standard (from size 1 to size 17)	standard (from size 1 to size 17)
	Galvanized steel	standard (from size 18 to size 27)	standard (from size 18 to size 27)	standard (from size 18 to size 27)	standard (from size 18 to size 27)
Handle	Glass fibre reinforced nylon	standard	standard	standard	standard
Type	Compression type	standard	standard	standard	standard
	Hinge function type (possibility to remove door)	option	option	option	option

D-AHU Easy

Construction type		DS 50	DS 25
Profile	Aluminium	Standard	Standard
Corner	Glass fibre reinforced nylon	Standard	Standard
Panel insulation	Polyurethane foam thermal conductivity 0.024 W/m*K	Standard (density 45 kg/m³)	standard (density 47 kg/m³)
External sheet material	Pre-coated galvanized steel (RAL 9002)	Standard	Standard
Internal sheet material	Galvanized steel	Standard	Standard
Base frame	Aluminium	Standard	Standard
Handle	Glass fibre reinforced nylon	Standard	Standard
Type	Compression type	Standard	Standard

		Conveni-Pack	ZEAS						Multi-ZEAS	
		LRYEQ16AY1	LREQ5BY1	LREQ6BY1	LREQ8BY1	LREQ10BY1	LREQ12BY1	LREQ15BY1	LREQ20BY1	LREQ15BY1Rx2	LREQ20BY1Rx2
Digital pressure gauge kit		BHGP26A1	BHGP26A1								
Pressure gauge kit		-	KHGP26B140								
Snowbreak hood	Kit (Inlet + Outlet)	KPS26C504	KPS26C160		KPS26C280			KPS26C504			
	Air outlet	KPS26C504T	KPS26C160T		KPS26C280T			KPS26C504T			
	Left side air inlet	KPS26C504L	KPS26C504L								
	Right side aire inlet	KPS26C504R	KPS26C504R								
	Back side air inlet	KPS26C504B	KPS26C160B		KPS26C280B			KPS26C504B			
Central drain pan kit		KWC26C450*	KWC26C160		KPS26C280			KPS26C450		KPS26C450** x2	
Communication box		BRR9A1V1								BRR9A1V1***	
Booster unit		LCBKQ3AV19								-	
Suction branch pipe for multi		-	-							EKHRQZM****	

* In cold areas should be heated by a field-supplied heater to prevent drain water from freezing in the drain pan. ** required for each module
*** software update required (to be executed during commissioning) **** mandatory

		DCM601A51	DMS504B51	DMS502A51
		intelligent Touch Manager	LonWorks Interface	BACnet Interface
iTM plus adapter		DCM601A52		
iTM ppd software		DCM002A51		
iTM energy navigator software		DCM008A51		
iTM BACnet option		DCM009A51		
WAGO I/O	Modbus communication unit	WGDCMCPLR		
	DC24V power supply unit:	787-712		
	DC24V power supply unit:	750-613		
	Connector:	750-960		
	Terminator module:	750-600		
	Di module:	750-400, 750-432		
	Do module:	750-513/000-001		
	Ai module:	750-454, 750-479		
	Thermistor module:	750-461/020-000		
Interface adapter for connection to RA units			KRP928A2S	KRP928A2S
Interface adapter for connection to R-407C/R-22 Sky Air units			DTA102A52	DTA102A52
Interface adapter for connection to R-410A Sky Air units			DTA112B51	DTA112B51
DIII board				DAM411B51
Digital input/output				DAM412B51

Power supply

T1 = 3~, 220V, 50Hz
V1 = 1~, 220-240V, 50Hz
VE = 1~, 220-240V/220V, 50Hz/60Hz*
V3 = 1~, 230V, 50Hz
VM = 1~, 220~240V/220~230V, 50Hz/60Hz
W1 = 3N~, 400V, 50Hz
Y1 = 3~, 400V, 50Hz

* For VE power supply only 1~, 220-240V, 50Hz data is displayed in this catalogue.

Conversion table refrigerant piping

inch	mm
1/4″	6.4 mm
3/8″	9.5 mm
1/2″	12.7 mm
5/8″	15.9 mm
3/4″	19.1 mm
7/8″	22.2 mm
1 1/8″	28.5 mm
1 3/8″	34.9 mm
1 5/8″	41.3 mm
1 3/4″	44.5 mm
2″	50.8 mm
2 1/8″	54 mm
2 5/8″	66.7 mm

F-gas regulation

For fully/partially charged equipment: contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

For non pre-charged equipment (Chillers: split chiller (SEHVX/SERHQ), condensing units and condenserless chillers + refrigeration (LCBKQ-AV1, JEHCCU/JEHSCU and ICU): Its functioning relies on fluorinated greenhouse gases.

Measuring conditions

Air conditioning

1) Nominal cooling capacities are based on:	
Indoor temperature	27°CDB/19°CWB
Outdoor temperature	35°CDB
Refrigerant piping length	7.5m - 8/5m VRV
Level difference	0m
2) Nominal heating capacities are based on:	
Indoor temperature	20°CDB
Outdoor temperature	7°CDB/6°CWB
Refrigerant piping length	7.5m - 8/5m VRV
Level difference	0m

Applied systems

Air cooled	Cooling only	Evaporator: 12°C/7°C	Ambient: 35°CDB
	Heat pump	Evaporator: 12°C/7°C	Ambient: 35°C
		Condenser: 40°C/45°C	Ambient: 7°CDB/6°CWB
Water cooled	Cooling only	Evaporator: 12°C/7°C	
		Condenser: 30°C/35°C	
	Heating only	Evaporator: 12°C/7°C	
		Condenser: 40°C/45°C	
Condenserless chiller		Evaporator: 12°C/7°C	
		Condensing temperature: 45°C / liquid temperature: 40°C	
Fan coil units	Cooling	Room temperature: 27°CDB /19°CWB	
		Water inlet/outlet temperature: 7°C/12°C	
	Heating	Room temperature: 20°C 2 pipe: Water inlet temperature: 50°C (same water flow as in cooling mode) 4 pipe: Water inlet/outlet temperature: 70°C/60°C	

The sound pressure level is measured via a microphone at a certain distance from the unit. It is a relative value, depending on the distance and acoustic environment (for measuring conditions: please refer to the technical databooks).
The sound power level is an absolute value indicating the "power" which a sound source generates.
For more detailed information please consult our technical databooks.

Benefits

We care icons



Seasonal efficiency, smart use of energy
Seasonal efficiency gives a more realistic indication on how efficient air conditioners operate over an entire heating or cooling season.



Auto-cleaning filter
The filter automatically cleans itself once per day. Simplicity of upkeep means optimum energy efficiency and maximum comfort without the need for expensive or time-consuming maintenance.



Inverter technology
In combination with inverter controlled outdoor units



2 area intelligent eye
Air flow is sent to a zone other than where the person is located at that moment. If no people are detected, the unit will automatically switch over to the energy-efficient setting.



3 area intelligent eye
Air flow is sent to a zone other than where the person is located at that moment. Detection is done in 3 directions : left, front and right. If no people are detected, the unit will automatically switch over to the energy-efficient setting.



Energy saving during operation standby
Current consumption is reduced by about 80 % when operating on standby. If no people are detected for more than 20 minutes, the system will automatically switch to the current-saving mode.



Night set mode
Saves energy, by preventing overcooling or overheating during night time.



Econo mode
This function decreases the power consumption so that other applicances that need large power consumption can be used. This function is also energy saving.



Movement sensor
The sensor detects whether someone is in the room. When the room is empty, the unit switches to economy mode after 20 minutes and restarts when a person enters the room.



Home leave operation
During absence, the indoor temperature can be maintained at a certain level.



Fan only
The air conditioner can be used as fan, blowing air without cooling or heating.



Free cooling
By exploiting the low external air temperatures to cool the water, free cooling reduces the load on the compressors and decreases considerably the annual operating costs during the cold season.



Floor & presence sensor
The presence sensor directs the air away from any person detected in the room, when the air flow control is on. The floor sensor detects the average floor temperature and ensures an even temperature distribution between ceiling and floor.

Comfort



Comfort mode
The unit automatically changes the angle of the air discharge louvre depending on the mode. In cooling operation the air will be directed rather upwards to to avoid cold draught, while in heating operation the air will be directed rather downwards to avoid cold feet.



Powerful mode
If the temperature in the room is too high/low, it can be cooled down/heated quickly by selecting the 'powerful mode'. After the powerful mode is turned off, the unit returns to the preset mode.



Whisper quiet
Daikin indoor units are whisper quiet.



Outdoor unit silent operation
To ensure a quiet environment for the neighbourhood the user can lower the operation sound of the outdoor unit by 3 dB(A) via remote control.



Comfortable sleeping mode
Increased comfort function that follows a specific temperature fluctuation rhythm.



Draught prevention
When starting to warm up or when the thermostat is off, the air discharge direction is set horizontally and the fan to low speed, to prevent draught. After warming up, air discharge and fan speed are set as desired.



Auto cooling-heating changeover
Automatically selects cooling or heating mode to achieve the set temperature (heat pump types only).



Indoor unit silent operation
To ensure a quiet environment for studying or sleeping the user can lower the operation sound of the indoor unit by 3 dB(A) via remote control.



Night quiet mode (cooling only)
Lowers the operation sound of the outdoor unit automatically by 3dB(A) by removing a jumper wire on the outdoor unit. This function can be deactivated if the jumper wire is reinstalled on the outdoor unit.



Radiant heat
The front panel of the indoor unit radiates additional heat to add to your comfort on cold days

Air flow



Ceiling soiling prevention
A special function prevents air blowing out too long in horizontal position, to prevent ceiling stains.



Vertical auto swing
Possibility to select automatic vertical moving of the air discharge louvre, for uniform air flow and temperature distribution.



Auto fan speed
Automatically selects the necessary fan speed to reach or maintain the set temperature.



Individual flap control
Flexible installation thanks to the possibility of easily closing one flap via the wired remote controller, to suit any new room configuration. Optional closure kits are available as well.



3-D Air flow
This function combines Vertical and Horizontal auto-swing to circulate a stream of cool/warm air right to the corners of even large spaces.



Horizontal auto swing
Possibility to select automatic horizontal moving of the air discharge louvre, for uniform air flow and temperature distribution.



Fan speed steps
Allows to select up to the given number of fan speed.

Benefits

Humidity control



Ururu - humidification
Moisture is absorbed from the outdoor air and evenly distributed throughout the indoor areas.



Sarara - dehumidification
Reduces indoor humidity, without affecting the room temperature, by mixing cool, dry air with warm air.



Dry programme
Allows humidity levels to be reduced without variations in room temperature.

Air treatment



Flash streamer
The Flash Streamer generates high-speed electrons that powerfully break down bacteria, viruses and allergens, making the air more clean.



Titanium photocatalytic air purification filter
Removes airborne dust particles, and decomposes the odours of for example tobacco and pets. It also decomposes harmful organic chemical substances such as bacteria, viruses and allergens.



Photocatalytic deodorising filter
Removes airborne dust particles, decomposes odours and restrains the reproduction of bacteria, viruses and microbes, this to ensure a steady supply of clean air.



Air filter
Removes airborne dust particles to ensure a steady supply of clean air.

Remote control & timer



Weekly timer
Timer can be set to start operation anytime on a daily or weekly basis



24 Hour timer
Timer can be set to start cooling/heating anytime during a 24-hour period.



Timer
Allows to preset the air conditioner to start/stop at a specified time.



Infrared remote control
Infrared remote control with LCD to start, stop and regulate the air conditioner from a distance.



Wired remote control
Wired remote control to start, stop and regulate the air conditioner from a distance.



Centralised control
Centralised control to start, stop and regulate several air conditioners from one central point.



Online controller
Online controller (optional): control your indoor unit from any location via smartphone, laptop, pc, tablet or touch screen



Online controller via app
Control your indoor unit from any location via app. (optional WLAN adapter)

Other functions



Auto-restart
The unit restarts automatically at the original settings after power failure.



Self-diagnosis
Simplifies maintenance by indicating system faults or operating anomalies.



Twin/triple/double twin application
2, 3 or 4 indoor units can be connected to only 1 outdoor unit even if they have different capacities. All indoor units operate within the same mode (cooling or heating) from one remote control.



Multi model application
Up to 5 indoor units (even different capacities) can be connected to a single outdoor unit. All indoor units can individually be operated within the same mode.



VRV for residential application
Up to 9 indoor units (even different capacities and up to 71 class) can be connected to a single outdoor unit. All indoor units can individually be operated within the same mode.



Drain pump kit
Facilitates condensation draining from the indoor unit.



Multi tenant
The indoor unit's main power supply can be turned off when leaving the hotel or office building.



Swing compressor



Scroll compressor



Screw compressor



Centrifugal compressor



Guaranteed operation down to -25°C
Daikin is suitable for all climates, even withstanding severe winter conditions with an operation range down to -25°C



Guaranteed operation down to -20°C
Daikin is suitable for all climates, even withstanding severe winter conditions with an operation range down to -20°C

VRV IV Heat Recovery

360° efficiency

installation efficiency

operational efficiency

design efficiency

FAST design + **QUICK** installation + **MORE** free heat + **MAX** comfort

DAIKIN



Our new VRV IV heat recovery systems sets pioneering standards in all-round climate comfort efficiency.

Total design simplicity, rapid installation, full flexibility with absolute efficiency and comfort. Find out about all revolutionary changes on **www.daikineurope.com/vrviv**

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)

MIX Paper from responsible sources FSC® C109049

EUROVENT CERTIFIED PERFORMANCE www.eurovent-certification.com

Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

ECPEN15-500_P 600 · 10/14

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

The present publication supersedes ECPEN14-500_P2. Printed on non-chlorinated paper. Prepared by Platzer Kommunikation, Germany.