



MKS-B

*Multi model application -
inverter controlled*



2MKS40B



3MKS50B



4MKS58,75B



4MKS90B

CONNECTABLE INDOOR UNITS

	2MKS40BVMB	3MKS50BVMB**	4MKS58BVMB**	4MKS75BVMB**	4MKS90BVMB**
Wall mounted unit	FTKS20,25,35C	FTKS20,25,35C	FTKS20,25,35C/FTKS50B	FTKS20,25,35C/FTKS50,60,71B	FTKS20,25,35C/FTKS50,60,71B
Floor standing unit	-	FVKS25,35B	FVKS25,35,50B	FVKS25,35,50B	FVKS25,35,50B
Flexi type unit	FLKS25,35B	FLKS25,35B	FLKS25,35,50B	FLKS25,35,50,60B	FLKS25,35,50,60B
Concealed ceiling unit	CDKS25,35B	CDKS25,35B	CDKS25,35,50B/FDQ25B7/FDQ35,50B7	CDKS25,35,50,60B/FDQ25B7/FDQ35,50,60B7	CDKS25,35,50,60B/FDQ25B7/FDQ35,50,60B7
4-way blow ceiling mounted cassette	-	-	FCQ35,50B7	FCQ35,50,60B7	FCQ35,50,60B7
4-way blow ceiling mounted cassette (600x600)	-	-	FFQ25,35,50B	FFQ25,35,50,60BV	FFQ25,35,50,60B
Ceiling suspended cassette	-	-	FHQ35,50BU	FHQ35,50,60BU	FHQ35,50,60BU

** At least 2 indoor units should be connected to this Multi outdoor unit.

COOLING ONLY

INDOOR UNIT			FTKS20CVMB	FTKS25CVMB	FTKS35CVMB	FTKS50BVMB	FTKS60BVMB	FTKS71BVMB
Dimensions	HxWxD	mm	273x784x195			290x795x238	290x1050x238	
Weight		kg	75			9	12	12
Air flow rate (H/U/S)	cooling	m ³ /min	77/42/3.6	77/42/3.6	77/44/3.8	114/8.0/71	16.2/11.4/10.2	16.7/11.6/10.6
Sound pressure level (H/U/S)	cooling	dB(A)	38/25/22	38/25/22	39/26/23	44/35/32	45/36/33	46/37/34
Sound power level (H)	cooling	dB(A)	56	56	57	63	63	63
Infrared remote control			ARC433A2				ARC433A2	

INDOOR UNIT			FLKS25BVMB	FLKS35BVMB	FLKS50BVMB	FLKS60BVMB
Dimensions	HxWxD	mm	490x1050x200			
Weight		kg	16		17	
Air flow rate (H/L/S)	cooling	m ³ /min	76/6.0/5.2	8.6/6.6/5.6	11.4/8.5/7.5	12.0/9.3/8.3
Sound pressure level (H/L/S)	cooling	dB(A)	37/31/28	38/32/29	47/39/36	48/41/39
Sound power level (H)	cooling	dB(A)	53	54	63	64
Infrared remote control			ARC433A6			

INDOOR UNIT			FVKS25BVMB	FVKS35BVMB	FVKS50BVMB
Dimensions	HxWxD	mm	600x650x195		
Weight		kg	13		
Air flow rate (H/L/S)	cooling	m³/min	8.1/4.3/3.4	8.3/4.3/3.4	10.8/7.7/6.7
Sound pressure level (H/L/S)	cooling	dB(A)	38/26/23	39/27/24	44/36/33
Sound power level (H)	cooling	dB(A)	54	55	56
Infrared remote control			ARC433A6		

COOLING ONLY

INDOOR UNIT			CDKS25BVMB	CDKS35BVMB	CDKS50BVMB	CDKS60BVMB
Dimensions	HxWxD	mm	260x900x580			
Weight		kg	23			
Air flow rate (H/L) -410A	cooling	m ³ /min	12.7/10.7/9.0	13.0/11.0/9.3	13.0/11.0/10.1	14.5/11.5/10.2
Sound pressure level (H/L)	cooling	dB(A)	39/36/33	39/36/33	42/39/36	44/41/38
Sound power level (H)	cooling	dB(A)	55	55	58	60
Infrared remote control			ARC433A8			

INDOOR UNIT			FDBQ25B7V1			
Dimensions	HxWxD	mm	230x652x502			
Weight		kg	17			
Air flow rate (H/L) -410A	cooling	m ³ /min	6.5/5.2			
Sound pressure level (H/L)	cooling	dB(A)	35/28			
Sound power level (H)	cooling	dB(A)	55			
Wired remote control			BRC1D527			

INDOOR UNIT			FBQ35B7V1	FBQ50B7V1	FBQ60B7V1
Dimensions	unit	HxWxD	300x700x800		
Weight	unit	kg	30	31	41
Air flow rate (H/L) -410A	cooling	m ³ /min	11.5/9	14/10	19/14
Sound pressure level (H/L)	cooling	dB(A)	33/29	33/29	34/30
Sound power level (H)	cooling	dB(A)	52	53	60
Wired remote control			BRC1D527		
DECORATION PANEL			BYBS45DJW1		BYBS71DJW1
Dimensions (HxWxD)	decoration panel	mm	55x880x500		55x1100x500
Weight	decoration panel	kg	3.5		4.5

INDOOR UNIT			FCQ35B7V1	FCQ50B7V1	FCQ60B7V1
Dimensions	unit	HxWxD	230x840x840		
Weight	unit	kg	23		
Air flow rate (H/L) -410A	cooling	m ³ /min	14/10	15/11	18/14
Sound pressure level (H/L)	cooling	dB(A)			33/28
Sound power level (H)	cooling	dB(A)	48		50
Infrared remote control			BRC7C513W		
Wired remote control			BRC1D527		
DECORATION PANEL			BYC125KJW1		
Dimensions (HxWxD)	decoration panel	mm	40x950x950		
Weight	decoration panel	kg	5		

INDOOR UNIT			FFQ25B1B	FFQ35B1B	FFQ50B1B	FFQ60B1B
Dimensions	unit	HxWxD	286x575x575			
Weight	unit	kg	175			
Air flow rate (H/L) -410A	cooling	m ³ /min	9/6.5	10/6.5	12/8	15/10
Sound pressure level (H/L)	cooling	dB(A)	29.5/24.5	32/25	36/27	41/32
Sound power level (H)	cooling	dB(A)	46.5	49	53	58
Infrared remote control			BRC7E531W			
Wired remote control			BRC1D527			
DECORATION PANEL			BYFQ60BW1			
Dimensions (HxWxD)	decoration panel	mm	55x700x700			
Weight	decoration panel	kg	2.7			

INDOOR UNIT			FHQ35B1V1	FHQ50B1V1	FHQ60B1V1
Dimensions	HxWxD	mm	195x960x680		
Weight		kg	24	25	27
Air flow rate (H/L) -410A	cooling	m ³ /min	13/10	13/10	17/13
Sound pressure level (H/L)	cooling	dB(A)	37/32	38/33	39/33
Sound power level (H)	cooling	dB(A)	53	54	55
Infrared remote control			BRC7E66		
Wired remote control			BRC1D527		

OUTDOOR UNIT			2MKS40BVMB	3MKS50BVMB	4MKS58BVMB	4MKS75BVMB	4MKS90BVMB
Dimensions	HxWxD	mm	640x685x285	735x936x300			908x900x320
Weight		kg	39	59	55	58	66
Sound pressure level (H/L)	cooling	dB(A)	47/43	46/43	46/*	48/*	48/*
Sound power level (H)	cooling	dB(A)	62	59	59	61	61
Operation range	cooling	°CDB	10~46	-10~46			
Refrigerant type			R-410A				
Power supply			1~, 220-240/220-230V, 50/60Hz				

*This information was not available at the time of publication.