



MKS-D

Multi model application -
inverter controlled



2MKS40D



3MKS50D,4MKS58,75D



4MKS90D

CONNECTABLE INDOOR UNITS

	2MKS40DVB	3MKS50DVB	4MKS58DVB	4MKS75DVB	4MKS90DVB
New Wall mounted unit	FTKS20,25,35D	FTKS20,25,35D	FTKS20,25,35D / CTKS50D	FTKS20,25,35D / CTKS50D	FTKS20,25,35D / CTKS50D
Wall mounted unit	FTKS20,25,35C	FTKS20,25,35C	FTKS20,25,35C/FTKS50B	FTKS20,25,35C/FTKS50,60,71B	FTKS20,25,35C/FTKS50,60,71B
Floor standing unit	-	FVKS25,35B	FVKS25,35,50B	FVKS25,35,50B	FVKS25,35,50B
Flexi type unit	FLKS25,35B	FLKS25,35B	FLKS25,35,50B	FLKS25,35,50,60B	FLKS25,35,50,60B
Slim concealed ceiling unit	FDKS25,35C	FDKS25,35C	FDKS25,35C / CDKS50C	FDKS25,35C/CDKS50,60C	FDKS25,35C/CDKS50,60C
4-way blow ceiling mounted cassette (600x600)	-	-	FFQ25,35,50B	FFQ25,35,50,60B	FFQ25,35,50,60B
4-way blow ceiling mounted cassette (950x950)	-	-	FCQ35,50B	FCQ35,50,60B	FCQ35,50,60B
Ceiling suspended cassette	-	-	FHQ35,50BU	FHQ35,50,60BU	FHQ35,50,60BU

COOLING ONLY

NEW

INDOOR UNIT			FTKS20DVMW/L	FTKS25DVMW/L	FTKS35DVMW/L	CTKS50DVMW/L
Dimensions	HxWxD	mm	283x800x195			
Weight		kg	9	9	9	9
Air flow rate	H/L	m ³ /min	13~2.0~2.6	13~2.5~3.0	14~3.4~3.8	
Sound pressure level	cooling H/L/SL	dB(A)	38/25/22	38/25/22	39/26/23	46/35/32
Sound power level	cooling H	dB(A)	56	56	57	64
Infrared remote control			ARC433A43			

INDOOR UNIT			FTKS20CVMB	FTKS25CVMB	FTKS35CVMB	FTKS50BVMB	FTKS60BVMB	FTKS71BVMB
Dimensions	HxWxD	mm	273x784x195			290x795x238	290x1,050x238	
Weight		kg	75			9	12	12
Air flow rate	H/L	m ³ /min	7.7*	7.7*	7.7*	11.4/8.0/7.1	16.2/11.4/10.2	16.7/11.6/10.6
Sound pressure level	cooling H/L/SL	dB(A)	38/25/22	38/25/22	39/26/23	44/35/32	45/36/33	46/37/34
Sound power level	cooling H	dB(A)	56	56	57	63	63	63
Infrared remote control			ARC433A2			ARC433A22		

INDOOR UNIT			FLKS25BVMB	FLKS35BVMB	FLKS50BVMB	FLKS60BVMB
Dimensions	HxWxD	mm	490x1,050x200			
Weight		kg	16		17	17
Air flow rate	H/L	m ³ /min	7.6/6.0/5.2	8.6/6.6/5.6	11.4/8.5/7.5	12.0/9.3/8.3
Sound pressure level	cooling H/L/SL	dB(A)	37/31/28	38/32/29	47/39/36	48/41/39
Sound power level	cooling H	dB(A)	53	54	63	64
Infrared remote control			ARC433A6			

COOLING ONLY

INDOOR UNIT			FKVS25BVMB	FKVS35BVMB	FKVS50BVMB
Dimensions	HxWxD	mm	600x650x195		
Weight		kg	13		
Air flow rate	H/L	m ³ /min	8.1/4.3/3.4	8.3/4.3/3.4	10.8/7.7/6.7
Sound pressure level	H/USL	dB(A)	38/26/23	39/27/24	44/36/33
Sound power level	H	dB(A)	54	55	56
Infrared remote control			ARC433A6		

INDOOR UNIT			NEW FDKS25CVMB	NEW FDKS35CVMB	CDKS50CVMB	CDKS60CVMB
Dimensions	HxWxD	mm	200x900x620		260x900x580	200x1100x620
Weight		kg	25		27	30
Air flow rate	H/L	m ³ /min	9.5/8.0/6.7	10.0/8.5/7.0	12.0/10.0/8.4	16.0/13.5/11.2
Sound pressure level	H/USL	dB(A)	35/31/29	35/31/29	37/33/31	38/34/32
Sound power level	H	dB(A)	53	53	55	56
Infrared remote control			ARC433A8			

INDOOR UNIT			FDBQ25B7V1
Dimensions	HxWxD	mm	230x652x502
Weight		kg	17
Air flow rate	H/L	m ³ /min	6.5/5.2
Sound pressure level	H/L	dB(A)	35/28
Sound power level	H	dB(A)	55
Wired remote control			BRC1D527

INDOOR UNIT			FBQ35B7V1	FBQ50B7V1	FBQ60B7V1
Dimensions	HxWxD	mm	300x700x800		
Weight		kg	30	31	41
Air flow rate	H/L	m ³ /min	11.5/9	14/10	19/14
Sound pressure level	H/L	dB(A)	33/29	33/29	34/30
Sound power level	H	dB(A)	52	53	60
Wired remote control			BRC1D527		
DECORATION PANEL			BYB545DW1		BYB571DJW1
Dimensions	HxWxD	decoration panel	55x880x500		55x1100x500
Weight		decoration panel	3.5		4.5

INDOOR UNIT			FCQ35B7V1	FCQ50B7V1	FCQ60B7V1
Dimensions	HxWxD	mm	230x840x840		
Weight		kg	23	23	23
Air flow rate	H/L	m ³ /min	14/10	15/11	18/14
Sound pressure level	H/L	dB(A)	31/27	31/27	33/28
Sound power level	H	dB(A)	48	48	50
Infrared remote control			BRC7C513W		
Wired remote control			BRC1D527		
DECORATION PANEL			BYC125K7W1B		
Dimensions	HxWxD	decoration panel	40x950x950		
Weight		decoration panel	5		

INDOOR UNIT			FFQ25B7V1B	FFQ35B7V1B	FFQ50B7V1B	FFQ60B7V1B
Dimensions	HxWxD	mm	286x575x575			
Weight		kg	175	175	175	175
Air flow rate	H/L	m ³ /min	9/6.5	10/6.5	12/8	15/10
Sound pressure level	H/L	dB(A)	29.5/24.5	32/25	36/27	41/32
Sound power level	H	dB(A)	46.5	49	53	58
Infrared remote control			BRC7E531W7			
Wired remote control			BRC1D527			
DECORATION PANEL			BYFQ60B7W1			
Dimensions	HxWxD	decoration panel	55x700x700			
Weight		decoration panel	2.7			

INDOOR UNIT			FHQ35B7V1	FHQ50B7V1	FHQ60B7V1
Dimensions	HxWxD	mm	195x960x680		
Weight		kg	24	25	27
Air flow rate	H/L	m ³ /min	13/10	13/10	17/13
Sound pressure level	H/L	dB(A)	37/32	38/33	39/33
Sound power level	H/L	dB(A)	53/48	54/49	55/51
Infrared remote control			BRC7E66		
Wired remote control			BRC1D527		

INDOOR UNIT			2MKS40DVMB	3MKS50DVMB	4MKS58DVMB	4MKS75DVMB	4MKS90DVMB
Dimensions	HxWxD	mm	640x685x285		735x936x300		908x900x320
Weight		kg	39	55	55	58	66
Sound pressure level	H/L	dB(A)	47/43	46/*	46/*	48/*	48/*
Sound power level	H	dB(A)	62	59	59	61	61
Operation range	from ~ to	°CDB	+10 ~ 46			-10 ~ 46	
Refrigerant type			R-410A				
Power supply			1 ~, 220-240/220-230V, 50/60Hz				

* This information was not available at the time of publication.