



MKS-E/F/G



COOLING ONLY

Outdoor Units

Outdoor Units		WALL MOUNTED												FLEXI TYPE				FLOOR STANDING				SLIM CONCEALED CEILING				CONCEALED CEILING				ROUND FLOW CASSETTE				4-WAY BLOW CASSETTE 600X600				CEILING SUSPENDED																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
		FTKS-D						FTXS-G						FTKS-F				FLKS-B				FVXS-F				FDKS-E/C				F(D)BQ-B				FCQ-C				FFQ-B				FHQ-B																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
		20		25		35		42		50		60		71		25		35		50		60		25		35		50		25E		35E		50C		60C		25		35		50		60		35		50		60		25		35		50		60		35		50		60																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
		new⇒		2MKS40G		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•		•	

new⇒
new⇒



Indoor Units

Indoor Units			FTKS20D3VML	FTKS20D3VMW	FTKS25D3VML	FTKS25D3VMW	FTKS35D3VML	FTKS35D3VMW
Dimensions	(Height x Width x Depth)		283x800x195					
Weight			9.0					
Air Flow Rate	Cooling	H/M/L/SL	8.7 / 6.7 / 4.7 / 3.9				8.9 / 6.9 / 4.8 / 4.0	
Sound Power	Cooling	High	56.0				57.0	
Sound Pressure	Cooling	H/L/SL	38.0 / 25.0 / 22.0				39.0 / 26.0 / 23.0	
Refrigerant			R-410A					
Power Supply			1~/220-240/220-230V/50/60Hz					

COOLING ONLY

Indoor Units			FTXS42G2V1B			FTXS50G2V1B			
Dimensions	(Height x Width x Depth)		mm	295x800x215					
Weight			kg	10					
Air Flow Rate	Cooling	H/M/L/SL	m³/min	9.1 / 7.7 / 6.3 / 5.4			10.2 / 8.6 / 7.0 / 6.0		
	Heating	H/M/L/SL	m³/min	11.2 / 9.4 / 7.7 / 6.8			11.0 / 9.3 / 7.6 / 6.7		
Sound Power	Cooling	High	dBA	58			59		
	Heating	High	dBA	58			60		
Sound Pressure	Cooling	H/M/L/SL	dBA	42 / 38 / 33 / 30			43 / 39 / 34 / 31		
	Heating	H/M/L/SL	dBA	42 / 38 / 33 / 30			44 / 39 / 34 / 31		
Refrigerant			Type	R-410A					
Power Supply				1~/220-230-240V/50Hz					



COOLING ONLY

Indoor Units				FTKS60FV1B		FTKS71FV1B	
Dimensions	(Height x Width x Depth)		mm	290x1050x238			
Weight			kg	12			
Air Flow Rate	Cooling	H/M/L/SL	m³/min	16.2 / 13.6 / 11.4 / 10.2		17.4 / 14.6 / 11.6 / 10.6	
Sound Power	Cooling	Medium	dBA	61		62	
Sound Pressure	Cooling	H/M/L/SL	dBA	45 / 41 / 36 / 33		46 / 42 / 37 / 34	
Refrigerant			Type	R-410A			
Power Supply				1~/220-240V/50Hz			





COOLING ONLY

Indoor Units				FLKS25BAVMB	FLKS35BAVMB	FLKS50BAVMB	FLKS60BAVMB
Dimensions	(Height x Width x Depth)	mm		490x1050x200			
Weight		kg		16.0		17.0	
Air Flow Rate	Cooling	H/M/L/SL	m³/min	7.60 / 6.80 / 6.00 / 5.2	8.60 / 7.60 / 6.6 / 5.6	11.40 / 10.00 / 8.50 / 7.5	12.00 / 10.70 / 9.30 / 8.3
Sound Power	Cooling	High	dBA	53.0	54.0	63.0	64.0
Sound Pressure	Cooling	H/M/L/SL	dBA	37.0 / 34.0 / 31.0 / 28.0	38.0 / 35.0 / 32.0 / 29.0	47.0 / 43.0 / 39.0 / 36.0	48.0 / 45.0 / 41.0 / 39.0
Refrigerant		Type		R-410A			
Power Supply				1~/220-240/220-230V/50/60Hz			




COOLING ONLY

Indoor Units				FVXS25FV1B	FVXS35FV1B	FVXS50FV1B
Dimensions	(Height x Width x Depth)	mm		600x700x210		
Weight		kg		14		
Air Flow Rate	Cooling	H/M/L/SL	m³/min	8.2 / 6.5 / 4.8 / 4.1	8.5 / 6.7 / 4.9 / 4.5	10.7 / 9.2 / 7.8 / 6.6
	Heating	H/M/L/SL	m³/min	8.8 / 6.9 / 5.0 / 4.4	9.4 / 7.3 / 5.2 / 4.7	11.8 / 10.1 / 8.5 / 7.1
Sound Power	Cooling	High	dBA	54	55	56
	Heating	High	dBA	54	55	57
Sound Pressure	Cooling	H/M/L/SL	dBA	38 / 32 / 26 / 23	39 / 33 / 27 / 24	44 / 40 / 36 / 32
	Heating	H/M/L/SL	dBA	38 / 32 / 26 / 23	39 / 33 / 27 / 24	45 / 40 / 36 / 32
Refrigerant		Type		R-410A		
Power Supply				1~/220-240V/50Hz		



COOLING ONLY

Indoor Units				FDKS25EAVMB	FDKS35EAVMB
Dimensions	(Height x Width x Depth)	mm		200x700x620	
Weight		kg		21.0	
Air Flow Rate	Cooling	H/M/L/SL	m³/min	8.7 / 8.0 / 7.3 / 6.2	
Sound Power	Cooling	High	dBA	53.0	
Sound Pressure	Cooling	H/M/L/SL	dBA	35.0 / 33.0 / 31.0 / 29.0	
Refrigerant		Type		R-410A	
Power Supply				1~/220-240/220-230V/50/60Hz	



COOLING ONLY

Indoor Units				FDKS50CVMB	FDKS60CVMB
Dimensions	(Height x Width x Depth)	mm		200x900x620	200x1100x620
Weight		kg		27.0	30.0
Air Flow Rate	Cooling	H/M/L/SL	m³/min	12.0 / 11.0 / 10.0 / 8.4	16.0 / 14.8 / 13.5 / 11.2
Sound Power	Cooling	High	dBA	55.0	56.0
Sound Pressure	Cooling	H/M/L/SL	dBA	37.0 / 35.0 / 33.0 / 31.0	38.0 / 36.0 / 34.0 / 32.0
Refrigerant		Type		R-410A	
Power Supply				220-240/220-230V/50/60Hz	



COOLING ONLY

Indoor Units				FDBQ25B8V1
Dimensions	(Height x Width x Depth)	mm		230x652x502
Weight		kg		17.0
Air Flow Rate	Cooling	High/Low	m³/min	6.50 / 5.20
	Heating	High/Low	m³/min	6.95 / 5.20
Sound Power	Cooling	High/Low	dBA	55.0 / 49.0
	Heating	High/Low	dBA	55.0 / 49.0
Sound Pressure	Cooling	High/Low	dBA	35.0 / 28.0
	Heating	High/Low	dBA	35.0 / 29.0
Refrigerant		Type		R-410A
Power Supply				1~/230V/50Hz



COOLING ONLY

Indoor Units			FBQ35B8V1	FBQ50B8V1	FBQ60B8V1
Dimensions	(Height x Width x Depth)	mm	300x700x800		300x1000x800
Weight		kg	30	31	41
Air Flow Rate	Cooling	High/Low	m³/min	14 / 10	19 / 14
	Heating	High/Low	m³/min	14 / 10	19 / 14
Sound Power	Cooling	High	dBA	52	60
	Heating	High	dBA	52	60
Sound Pressure	Cooling	High/Low	dBA	33 / 29	34 / 30
	Heating	High/Low	dBA	33 / 29	34 / 30
Refrigerant		Type	R-410A		
Power Supply			1~/230V/50Hz		



COOLING ONLY

Indoor Units			FFQ25B8V1B	FFQ35B8V1B	FFQ50B8V1B	FFQ60B8V1B
Dimensions	(Height x Width x Depth)	mm	286x575x575			
Weight		kg	17.5			
Air Flow Rate	Cooling	High/Low	m³/min	9.0 / 6.5	10.0 / 6.5	12.0 / 8.0
	Heating	High/Low	m³/min	9.0 / 6.5	10.0 / 6.5	12.0 / 8.0
Sound Power	Cooling	High	dBA	46.5	49.0	53.0
Sound Pressure	Cooling	High/Low	dBA	29.5 / 24.5	32.0 / 25.0	36.0 / 27.0
	Heating	High/Low	dBA	29.5 / 24.5	32.0 / 25.0	36.0 / 27.0
Refrigerant		Type	R-410A			
Power Supply			1~/230V/50Hz			



COOLING ONLY

Indoor Units			FCQ35C7VEB	FCQ50C7VEB	FCQ60C7VEB
Dimensions	(Height x Width x Depth)	mm	204x840x840		
Weight		kg	19		
Air Flow Rate	Cooling	High/Low	m³/min	10.5 / 8.5	13.5 / 8.5
	Heating	High/Low	m³/min	12.5 / 10.0	13.5 / 8.5
Sound Power	Cooling	High	dBA	49	51
Sound Pressure	Cooling	High/Low	dBA	31 / 27	33 / 28
	Heating	High/Low	dBA	31 / 27	33 / 28
Refrigerant		Type	R-410A		
Power Supply			-		



COOLING ONLY

Indoor Units			FHQ35BVV1B	FHQ50BVV1B	FHQ60BVV1B
Dimensions	(Height x Width x Depth)	mm	195x960x680		195x1160x680
Weight		kg	24.0	25.0	27.0
Air Flow Rate	Cooling	High/Low	m³/min	13.0 / 10.0	17.0 / 13.0
	Heating	High/Low	m³/min	13.0 / 10.0	16.0 / 13.0
Sound Power	Cooling	High/Low	dBA	53.0 / 48.0	55.0 / 49.0
	Heating	High/Low	dBA	53.0 / 48.0	55.0 / 49.0
Sound Pressure	Cooling	High/Low	dBA	37.0 / 32.0	39.0 / 33.0
	Heating	High/Low	dBA	37.0 / 32.0	39.0 / 33.0
Refrigerant		Type	R-410A		
Power Supply			1~/220-240V/50Hz		



COOLING ONLY

INVERTER

Outdoor Unit			2MK540G2V1B	2MK550G2V1B
Dimensions	(Height x Width x Depth)	mm	550x765x285	
Weight		kg	38	42
Operation Range	Cooling	Min~Max °CDB	10~46	
Sound Power	Cooling	dB(A)	62	63
Sound Pressure (Low)	Cooling	dB(A)	43	44
Sound Pressure (High)	Cooling	dB(A)	47	48
Refrigerant		Type	R-410A	
Power Supply			1~/220-240V/50Hz	
Piping connections	Liquid (OD)/Drain	mm	6.35 / 18	-
	Liquid (OD)/Gas/Drain	mm	-	6.35 / 12.7 / 18
Piping Length (Maximum)		m	30 (for total of each room)	
Max. internunit level difference		m	7.5	



COOLING ONLY

INVERTER

Outdoor Unit			3MKS50E	4MKS58E	4MKS75F	5MKS90E
Dimensions	HxWxD	mm	735x936x300	735x936x300	735x936x300	770x900x320
Weight		kg	49	58	57	69
Operation range	Cooling	Min~Max °CDB	-10~46	-10~46	-10~46	-10~46
Sound Power	Cooling	dB(A)	59	59	61	62
Sound Pressure (low)	Cooling	dB(A)	-	-	-	-
Sound Pressure (high)	Cooling	dB(A)	46	46	48	48
Refrigerant		Type	R-410A			
Power Supply			1~/220-240V/50Hz	1~/220-240V/50Hz	1~/220-240V/50Hz	1~/220-240V/50Hz
Piping Connection	Liquid (OD)/Gas/Drain	mm	6.35/12.7/18	6.35/12.7/18	6.35/15.9/18	6.35/15.9/18
Piping Length (Maximum)		m	50	50	60	75
Max. internunit level difference		m	15	15	7.5	15