


Multi model application

- › Seasonal efficiencies up to A+++ in cooling
- › Outdoor units for multi model application.
- › Outdoor units are fitted with a swing compressor, renowned for its low noise and high energy efficiency
- › Up to 5 indoor units can be connected to 1 multi outdoor unit; all indoor units are individually controllable and do not need to be installed in the same room or at the same time. Each unit works individually and independently from the other regarding set point and fan speed but within the same cooling or heating mode
- › Different types of indoor units can be connected: e.g. wall mounted units, concealed ceiling units
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency



2MXM40-50M

Connectable indoor units	Wall mounted													Concealed ceiling						
	Daikin Emura FTXJ-MW/S				CTXM-M	FTXM-M								FDXM-F						
	20	25	35	50	15	20	25	35	42	50	60	71					25	35	50	60
2MXM40M	•	•	•		•	•	•	•									•	•		
2MXM50M	•	•	•	•	•	•	•	•	•	•							•	•	•	
3MXM40M	•	•	•		•	•	•	•									•	•		
3MXM52M	•	•	•	•	•	•	•	•	•	•							•	•	•	
3MXM68M	•	•	•	•	•	•	•	•	•	•	•						•	•	•	•
4MXM68M	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•	•
4MXM80M	•	•	•	•	•	•	•	•	•	•	•	•	•				•	•	•	•
5MXM90M	•	•	•	•	•	•	•	•	•	•	•	•	•				•	•	•	•

*Note: blue cells contain preliminary data

Outdoor unit				*2MXM40M	*2MXM50M	*3MXM40M	*3MXM52M	*3MXM68M	*4MXM68M	*4MXM80M	*5MXM90M
Dimensions	Unit	HeightxWidthxDepth	mm	550x765x285				735x870x320			
Weight	Unit		kg	-							
Sound power level	Cooling		dB(A)	60	61	59		61		62	66
Sound pressure level	Cooling	Nom.	dB(A)	46	48	46		48		49	52
	Heating	Nom.	dB(A)	48	50	47		48		49	52
Power supply	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 220-240							
Operation range	Cooling	Ambient	Min.-Max. °CDB	-10~46							
	Heating	Ambient	Min.-Max. °CWB	-15~24							
Refrigerant	Type/Charge kg-TCO ₂ Eq/GWP			R-32/1.2/-/675	R-32/1.6/-/675	R-32/2/-/675	R-32/2/-/675	R-32/2.59/-/675	R-32/2.6/-/675	R-32/2.99/-/675	R-32/2.99/-/675
Piping connections	Piping length	OU - IU	Max.	20		25					
	Level difference	IU - OU	Max.	15							
Current - 50Hz	Maximum fuse amps (MFA)		A	-							

*Note: blue cells contain preliminary data