



Air Conditioning

Technical Data

Wall mounted unit



EEDEN14-030

ATX-JV

TABLE OF CONTENTS

ATX-JV

1	Features	2
2	Specifications	3
	Technical Specifications	3
	Electrical Specifications	4
3	Dimensional drawings	5
4	Centre of gravity	6
5	Piping diagrams	7
6	Wiring diagrams	8
	Wiring Diagrams - Single Phase	8
7	Sound data	9
	Sound Pressure Spectrum	9

1 Features

- Whisper quiet operation: down to 22dBA sound pressure level
- ECONO mode decreases power consumption so that other appliances that need large power consumption can be used
- Night set mode saves energy by preventing overcooling or overheating during night time
- Comfort mode guarantees draught free operation by preventing that warm or cold air is directly blown on to the body
- Powerful mode can be selected for rapid heating or cooling; after the powerful mode is turned off, the unit returns to the preset mode.
- Indoor unit silent operation: "silent" button on the remote control lowers the operation sound of the indoor unit by 3dBA
- Titanium apatite photocatalytic air purification filter removes airborne microscopic particles, powerfully decomposes odours and helps to prevent the propagation of bacteria, viruses, microbes to ensure a steady supply of clean air
- Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room



Econo mode



Night set mode



Fan only



Comfort mode



Powerful mode



Auto cooling-
heating
changeover



Whisper quiet



Indoor unit
silent operation



Vertical auto
swing



Auto fan speed



Fan speed
steps



Dry programme



Titanium apatite
photocatalytic
air purification
filter



24 hour timer



Infrared remote
control



Auto-restart



Self diagnosis

2 Specifications

2-1 Technical Specifications					ATX20JV		ATX25JV		ATX35JV			
Power input	Cooling		Nom.		kW		0.040					
	Heating		Nom.		kW		0.040					
Casing	Colour					White						
Dimensions	Unit		Height/Width/Depth		mm		283/770/198					
	Packed unit		Height/Width/Depth		mm		345/846/266					
Weight	Unit				kg		7					
	Packed unit				kg		11					
Heat exchanger	Length				mm		610					
	Rows		Quantity			2						
	Fin pitch				mm		1.4					
	Stages		Quantity			14						
	Tube type					ø7 Hi-XA						
	Fin		Type			ML fin (Multi louver)						
Fan	Type					Cross flow fan						
	Air flow rate	Cooling	High	m³/min	9.1	9.2		9.3				
				cfm	321	325		328				
			Nom.	m³/min	7.4	7.6		7.7				
				cfm	261	268		272				
			Low	m³/min	5.9	6.0		6.1				
				cfm	208	212		215				
		Silent operation	m³/min	4.7	4.8		4.9					
			cfm	166	169		173					
		Heating	High	m³/min	9.4	9.7		10.1				
				cfm	331	342		356				
			Nom.	m³/min	7.8	8.0		8.4				
				cfm	276	283		295				
			Low	m³/min	6.3		6.7					
				cfm	222		235					
		Silent operation	m³/min	5.5		5.7						
			cfm	194		201						
Fan motor	Model					MM6C02J2VA						
	Speed	Steps				5 + silent, + auto						
		Cooling	High/Medium/Low/Silent operation	rpm	1,210/990/780/630		1,250/1,030/820/630		1,300/1,070/850/680			
		Heating	High/Medium/Low/Silent operation	rpm	1,260/1,090/920/820		1,300/1,110/920/820		1,340/1,150/960/850			
	Output		High		W	16						
Sound power level	Cooling				dBA		55		58			
	Heating				dBA		55		58			
Sound pressure level	Cooling	High/Nom./Low/Silent operation			dBA		39/33/25/22		40/33/26/22		41/34/27/23	
	Heating	Super high/High/Nom./Low/Silent operation			dBA		-/39/34/28/25		-/40/34/28/25		-/41/35/29/26	
Refrigerant	Type					R-410A						
Piping connections	Liquid		OD			6.35						
	Gas		OD			9.5						
	Drain					18						
	Heat insulation					Both liquid and gas pipes						

2 Specifications

2-1 Technical Specifications		ATX20JV	ATX25JV	ATX35JV
Temperature control		Microcomputer control		
Air direction control		Right, Left, Horizontal, Downward		
Air filter	Type	Removable / washable / mildew proof		

Standard Accessories : ; Quantity : Titanium apatite photocatalytic air purification filter without frame;

Standard Accessories : Batteries; Quantity : 2;

Standard Accessories : Remote control holder; Quantity : 1;

Standard Accessories : Titanium apatite photocatalytic air purification filter; Quantity : 2;

Standard Accessories : Mounting plate; Quantity : 1;

Standard Accessories : Wireless remote control; Quantity : 1;

Standard Accessories : Indoor unit fixing screws; Quantity : 2;

Standard Accessories : Operation manual; Quantity : 1;

Standard Accessories : Installation manual; Quantity : 1;

Standard Accessories : Infrared remote control;

Standard Accessories : Titanium apatite photocatalytic air purification filter without frame;

2-2 Electrical Specifications				ATX20JV	ATX25JV	ATX35JV
Power supply	Name			V1		
	Phase			1~		
	Frequency	Hz		50		
	Voltage	V		220-230-240		
Current	Nominal running current (RLA) - 50Hz	Cooling	A	0.18		
		Heating	A	0.18		
Wiring connections - 50Hz	For power supply	Remark		3 for power supply, 4 for interunit wiring (Earth wire included)		


Notes

(1) SL: The silent fan level of the air flow rate setting

3 Dimensional drawings

3 - 1 Dimensional Drawings

ATX20-35J2V1B



NOTES


1. The mark (→) shows piping direction.

3D058483A

4 Centre of gravity

4 - 1 Centre of Gravity


ATX-JV



4D059099G

5 Piping diagrams


5 - 1 Piping Diagrams



6 Wiring diagrams

6 - 1 Wiring Diagrams - Single Phase

ATX20-35J2V1B



FG	Frame ground	R1T, R2T	Thermistor
F1U	Fuse	S6~S602	Connector
H1~H3	Harness	S1W	Operation switch
H1P, H2P	Pilot lamp	X1M	Terminal strip
M1F	Fan motor	⊕	Protective earth
M1S	Swing motor		
PCB1~PCB3	Printed circuit board		

3D058454B



NOTE

- 1 PCB3 is showing the case of option connection.

7 Sound data

7 - 1 Sound Pressure Spectrum

ATX20J2V1B



NOTES

- Over All (dB): (B,G,N is already rectified)
- Measuring place: measure in anechoic room.
- Operation noise differs with operation and ambient conditions.
- Location of microphone.
JISC9612
The operation noise measuring method is in accordance with JISC9612



Scale	50Hz 230V	
	H	L
A	39	25

NOTES



- Over All (dB): (B,G,N is already rectified)
- Measuring place: measure in anechoic room.
- Operation noise differs with operation and ambient conditions.
- Location of microphone.
JISC9612
The operation noise measuring method is in accordance with JISC9612



Scale	50Hz 230V	
	H	L
A	39	28

3D058955A

ATX25J2V1B



NOTES

- Over All (dB): (B,G,N is already rectified)
- Measuring place: measure in anechoic room.
- Operation noise differs with operation and ambient conditions.
- Location of microphone.
JISC9612
The operation noise measuring method is in accordance with JISC9612



Scale	50Hz 230V	
	H	L
A	40	26

NOTES

- Over All (dB): (B,G,N is already rectified)
- Measuring place: measure in anechoic room.
- Operation noise differs with operation and ambient conditions.
- Location of microphone.
JISC9612
The operation noise measuring method is in accordance with JISC9612





Scale	50Hz 230V	
	H	L
A	40	28

3D058956A

7 Sound data

7 - 1 Sound Pressure Spectrum

ATX35J2V1B



NOTES

- 1 Over All (dB):
(B,G,N is already rectified)
- 2 Measuring place: measure in anechoic room.
- 3 Operation noise differs with operation and ambient conditions.
- 4 Location of microphone.
JISC9612
The operation noise measuring method is in accordance with JISC9612



Scale	50Hz 230V	
	H	L
A	41	27

NOTES

- 1 Over All (dB):
(B,G,N is already rectified)
- 2 Measuring place: measure in anechoic room.
- 3 Operation noise differs with operation and ambient conditions.
- 4 Location of microphone.
JISC9612
The operation noise measuring method is in accordance with JISC9612



Scale	50Hz 230V	
	H	L
A	41	29

3D058957A



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check on-going validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

BARCODE

Daikin products are distributed by: