



# Wall Mounted Unit



FAQ / RZQ-D(BW1)



Wired remote control (standard)



Wireless remote control (optional)



These popular indoor units can be mounted on virtually any type of wall, leaving space free for furniture, decoration and fittings. Wall mounted units are very quiet in operation. An automatic air flow director ensures uniform air flow and temperature distribution by moving the air discharge horizontally and/or vertically.

- **Super inverter system:** reduces power consumption by up to 70% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- **Application flexibility:** Comms, computer and server room cooling possible. Also suitable for use in R-22 replacement projects.
- **Wired remote controller with weekly timer:** provides a 7-day schedule timer, enabling daily or weekly programming. Up to 5 actions per day possible.
- **Home Leave operation:** in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level, by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- **Dry programme:** Daikin's special dry programme reduces humidity in the rooms without variations in internal temperature.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air. It can easily be removed and washed.
- **Forced off:** The optional forced off enables the unit to switch off automatically, for example when a window is opened.
- **Fan speed:** 2 fan speeds can be selected, high or low.
- **Easy clean:** Horizontal flaps and front panel can easily be removed and cleaned.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

Height	290mm
Width	1050mm
Depth	230mm



FAQ71B

Height	770mm
Width	900mm
Depth	320mm



RZQ71D

See tables overleaf for full list of dimensions

ENERGY LABEL:  
UP TO CLASS  
A

# HEAT PUMP

# SUPER INVERTER

Indoor Units				FAQ71B	FAQ100B	
Capacity	Cooling capacity	Standard	kW	7.1	10	
	Heating capacity	Standard	kW	8.0	11.2	
EER / COP	Cooling / Heating			3.11 / 3.43	3.04 / 3.49	
Annual energy consumption			kWh	1141	1645	
Energy Label	cooling / heating			B / B	A / C	
Dimensions	(Height x Width x Depth)		mm	290x1050x230	360x1570x200	
Weight			kg	13.0	26.0	
Air Flow Rate	Cooling	High/Low	m <sup>3</sup> /min	19.0 / 15.0	23.0 / 19.0	
	Heating	High/Low	m <sup>3</sup> /min	19.0 / 15.0	23.0 / 19.0	
Sound Power	Cooling	High/Low	dBA	59.0 / 53.0	61.0 / 57.0	
	Heating	High/Low	dBA	59.0 / 53.0	61.0 / 57.0	
Sound Pressure	Cooling	High/Low	dBA	43.0 / 37.0	45.0 / 41.0	
	Heating	High/Low	dBA	43.0 / 37.0	45.0 / 41.0	
Refrigerant			Type	R-410A		
Power Supply				1~/220-240V/50Hz		
Controller	Wired/Wireless			BRC1D52 (Standard) / BRC7E618 (Optional)	BRC1D52 (Standard) / BRC7C510 (Optional)	
Outdoor Unit				RZQ71DV1	RZQ100DV1	RZQ100BW1
Dimensions	(Height x Width x Depth)		mm	770x900x320	1345x900x320	
Weight			kg	67	108	106
Operation Range	Cooling	Min~Max	°CDB	-15.0~-50.0		
	Heating	Min~Max	°CWB	-20.0~-15.5		
Sound Power	Cooling		dBA	64	65	
Sound Pressure (Standard)	Cooling		dBA	48	50	
	Heating		dBA	50	52	
Sound Level (Night quiet)	Sound Pressure		dBA	43	45	
Refrigerant			Type	R-410A		
Power Supply				1~/220-240V/50Hz		3N~/400V/50Hz
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26		
Piping Length (Maximum)			m	50	75	
Max. internunit level difference			m	0.5		
Max Installation Height Difference			m	30		



Authorised User No. 02061

Visit [www.eca.gov.uk/etl](http://www.eca.gov.uk/etl) and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

[www.daikin.co.uk](http://www.daikin.co.uk)

Daikin products are distributed by:

FSC



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.