



FBQ-C8 / RZQSG-LV1(LY1)

Concealed Ceiling Unit

Seasonal Classic



RZQSG100LV1

Outdoor Unit

RZQSG71	H x W x D	770 x 900 x 320mm
RZQSG100/125	H x W x D	990 x 940 x 320mm
RZQSG140	H x W x D	1430 x 940 x 320mm

Accessories

Wireless remote controller (BRC4C65)
Wireless room mounted temperature sensor (K.RSS)
Decoration grille for return air suction (BYBS71D / BYBS125B)

Daikin's concealed ceiling unit is a ducted type fan coil that has been re-engineered for Seasonal Efficiency, combining improved efficiencies in year round conditions with functionality to suit commercial environments.

Quiet, with noise levels as low as 29 decibels, the FBQ-C8 series has a slim profile to allow it to be fitted into narrow ceiling voids. It is able to be connected to flexible duct-work to provide heating and cooling in unusual shaped or long rooms.

Energy savings can be made using the remote controller which gives control over set-point ranges and day-to-day use of controls. The controller can also be connected to an optional wireless temperature sensor to allow give accurate readings of room temperature for better comfort levels.

The Seasonal Classic can be used on existing R22 pipework, making the Concealed ceiling unit ideal for refurbishment projects.

FEATURES

BENEFITS

R22 Replacement technology

Re-use of existing R22 and R407C piping possible, allowing only fan-coil and condensers to be replaced

D3 connection as standard

Allows integration and control of split system with Daikin building management systems

Integral drain-pump

Built in pump allows drain-up of 625mm for connection to condensate drain tube in ceiling void

Automatic air-flow adjustment via remote control

Simpler to commission the system and achieve optimum air-flow

Indoor Units			Single Phase				3 Phase			
			FBQ71C8	FBQ100C8	FBQ125C8	FBQ140C8	FBQ100C8	FBQ125C8	FBQ140C8	
Cooling Capacity	Nominal	kW	6.8	9.5	12	13.4	9.5	12	13.4	
	UK Total	kW	7.28	10.8	13.6	14.9	10.8	13.6	14.9	
	UK Sensible	kW	4.99	7.44	9.3	10.25	7.44	9.3	10.25	
Heating Capacity	Nominal	kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A				C			
		Pdesign	kW	6.8	9.5	12.0	-	9.5	12.0	-
		SEER		5.11		4.35	-	5.11	4.35	-
	Heating (Average climate)	Annual energy consumption	kWh	466	651	966	-	651	966	-
		Energy label		A				A		
		Pdesign	kW	6.0	7.6		-	7.6	-	
SCOP		3.81				3.81				
Annual energy consumption	kWh	2,202	2,783		-	2,783	-			
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER		3.28	3.31	3.21	3.02	3.31	3.21	3.02	
	COP		3.61	3.65	3.51	3.41	3.65	3.51	3.41	
	Annual energy consumption	kWh	1,037	1,435	1,870	2,220	1,435	1,870	2,220	
	Energy label	Cooling/Heating	A/A		A/B		B/B		B/B	
Nominal Power Input	Cooling / Heating	kW	2.07 / 2.08	2.87 / 2.96	3.74 / 3.85	4.44 / 4.54	2.87 / 2.96	3.74 / 3.85	4.44 / 4.54	
Dimensions	Height x Width x Depth	mm	300 x 1000 x 700			300 x 1400 x 700				
Weight		kg	38	45			45			
Air Flow Rate	High / Low	m³/min	18 / 15	32 / 23	39 / 28	39 / 28	32 / 23	39 / 28	39 / 28	
External Static Pressure	High / Nom.	Pascals	100 / 30	120 / 40	120 / 50	120 / 50	120 / 40	120 / 50	120 / 50	
Sound Power	High	dB(A)	65	69	67	69	69	67	69	
Sound Pressure	High / Low	dB(A)	37 / 29	38 / 32	40 / 33	40 / 33	38 / 32	40 / 33	40 / 33	
Refrigerant	Type		R410A				R410A			
Power Supply			From outdoor unit				From outdoor unit			
Controller			BRC1E52A wired				BRC1E52A wired			

Outdoor Unit			RZQSG71LV1	RZQSG100LV1	RZQSG125LV1	RZQSG140LV1	RZQSG100LV1	RZQSG125LV1	RZQSG140LV1
Dimensions	Height x Width x Depth	mm	770 x 900 x 320	990 x 940 x 320		1430 x 940 x 320	990 x 940 x 320		1430 x 940 x 320
Weight		kg	67	81		102	82		101
Operation Range	Cooling Min~Max	°CDB	-5°C to +46°C				-5°C to +46°C		
	Heating Min~Max	°CWB	-15°C to +15.5°C				-15°C to +15.5°C		
Sound Power	High	dB(A)	65	69	67	69	69	67	69
Sound Pressure	Nom.	dB(A)	49	53	51	53	53	51	53
Refrigerant	Type		R410A				R410A		
Power Supply			1~ / 50Hz / 220 - 240v				3~ / 50Hz / 400v		
Piping Connections	Liquid (OD)/Gas	inches	3/8 / 5/8				3/8 / 5/8		
Piping Length (Maximum)		m	30	50		50			
Max Installation Height Difference		m	15	30		30			



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.

