

Low Height Roundflow Cassette



FCQ-C / RZQS-D



White with grey louvres



White with white louvres



Wired remote control (standard)



Wireless remote control (optional)



The unique 360° radial air pattern ensures uniform air flow and temperature distribution. The slim FCQ-C model has a low installation height perfect for applications in restricted false ceilings.

- **Inverter technology:** reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- **Air flow flexibility:** a wide selection of 23 different airflow patterns enables unit installation in corners or small rooms.
- **Horizontal air discharge:** ensures draught free operation and prevents ceiling soiling.
- **Wired remote controller with weekly timer:** provides a 7-day schedule timer, enabling daily or weekly programming. Up to 5 actions per day possible.
- **Home Leave operation:** automatically keeps the room temperature at a specified favourite comfort level during extended absence, by switching to heating when it reaches the minimum level and to cooling at the maximum level.
- **Dry programme:** Daikin's special dry programme reduces humidity in the rooms without variations in internal temperature.
- **Forced off:** The optional forced off enables the unit to switch off automatically, for example when a window is opened.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air. It can easily be removed and washed.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.
- Modern style decoration panel in pure white.

Height	204mm
Width	840mm
Depth	840mm



FCQ71C

Height	770mm
Width	900mm
Depth	320mm



RZQS71D

See tables overleaf for full list of dimensions

ENERGY LABEL:
UP TO CLASS
B

HEAT PUMP

COMFORT INVERTER

Indoor Units				FCQ71C	FCQ100C	FCQ125C	FCQ140C
Capacity	Cooling capacity	Standard	kW	7.1	10.0	12.5	14.0
	Heating capacity	Standard	kW	8.0	11.2	14.0	16.0
EER / COP	Cooling / Heating			3.11 / 3.41	3.11 / 3.41	3.11 / 3.45	2.61 / 3.21
Annual energy consumption			kWh	1,141	1,608	2,010	2,680
Energy Label	cooling / heating				B / B		D / C
Dimensions	(Height x Width x Depth)			204x840x840	246x840x840		
Weight				21	23		
Air Flow Rate	Cooling	High/Low	m ³ /min	15.5 / 9.0	23.5 / 16.0	27.5 / 19.0	
	Heating	High/Low	m ³ /min	16.0 / 9.5	23.5 / 16.0	27.5 / 19.0	
Sound Power	Cooling	High	dB(A)	51	54	58	
Sound Pressure	Cooling	High/Low	dB(A)	33 / 28	37 / 32	41 / 35	
	Heating	High/Low	dB(A)	34 / 28	37 / 32	41 / 35	42 / 35
Refrigerant				R-410A			
Power Supply				1~/220-240V/50/60Hz			
Decoration Panel	Model	BYCQ140CW1 / BYCQ140CW1W					
	Colour	White with grey louvres (RAL 9010) / White with white louvres (RAL 9010)					
	HxWxD	mm			50x950x950		
	Weight	kg			5.5		
Controller	Wired/Wireless			BRC1D52 (Standard) / BRC7F532F (Optional)			
Outdoor Unit				RZQS71DV1	RZQS100DV1	RZQS125DV1	RZQS140DV1
Dimensions	(Height x Width x Depth)			770x900x320	1170x900x320		
Weight				68	103		
Operation Range	Cooling	Min~Max	°CDB	-5~46			
	Heating	Min~Max	°CWB	-15~15.5			
Sound Power	Cooling		dB(A)	65	67	68	
Sound Pressure (Standard)	Cooling		dB(A)	49	51	52	
	Heating		dB(A)	51	55	53	54
Sound Level (Night quiet)	Sound Pressure		dB(A)	47	49	50	
Refrigerant				R-410A			
Power Supply				1~/220-240V/50Hz			
Piping connections	Liquid (OD)/Gas/Drain			mm			
Piping Length (Maximum)				30	50		
Max Interunit Level Difference				0.5			
Max Installation Height Difference				15	30		



Authorised User No. 02061

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

www.daikin.co.uk

Daikin products are distributed by:

FSC



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.