




High Efficiency Roundflow Cassette



FCQH-D8 / RZQS-D



BRC1D52
Wired remote control (standard)



Self-cleaning option



BRC1E51A
Wired remote control (optional)



Wireless remote control (optional)



The unique 360° radial air pattern ensures uniform air flow and temperature distribution. The FCQH model combined with the comfort inverter achieves a great balance of efficiency and value.

- **Comfort Inverter technology:** reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, low noise and reliability.
- **Air flow flexibility:** a wide selection of 23 different airflow patterns enables unit installation in corners or small rooms.
- **Horizontal air discharge:** ensures draught free operation and prevents ceiling soiling.
- **Wired remote controller:** provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible (BRC1D52 standard / BRC1E51A optional).
- **BRC1E51A – New optional wired controller:** allows easy navigation through menu items, via a personalised display and minimal number of buttons.
- **Self-cleaning panel (available as accessory):** Maintenance time and costs and energy consumption reduced. It is equipped with a special rounded filter, which automatically cleans itself once a day. The dust from this filter is stored in the indoor unit and can be removed with a normal vacuum cleaner.
- **Home Leave operation:** in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level, by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.
- Modern style decoration panel in pure white. Standard model also available with white louvres.

Height	246mm
Width	840mm
Depth	840mm



FCQH71D8

Height	770mm
Width	900mm
Depth	320mm



RZQS71D

See tables overleaf for full list of dimensions

ENERGY LABEL:
UP TO CLASS
A

HEAT PUMP

COMFORT INVERTER

Indoor Units				FCQH71D8	FCQH100D8	FCQH125D8	FCQH140D8
Capacity	Cooling capacity	Standard	kW	7.1	10.0	12.5	14.0
	Heating capacity	Standard	kW	8.0	11.2	14.0	16.0
EER / COP	Cooling / Heating			3.3 / 3.7	3.45 / 3.80	3.22 / 3.69	3.01 / 3.41
Annual energy consumption			kWh	1,076	1449	1940	2326
Energy Label	cooling / heating				A / A		B / B
Dimensions	(Height x Width x Depth)		mm	246x840x840		288x840x840	
Weight			kg	23		25	
Air Flow Rate	Cooling	High/Low	m³/min	21.9 / 12.1	34.2 / 17.6	34.2 / 21.2	34.2 / 23.8
	Heating	High/Low	m³/min	21.9 / 12.1	34.2 / 17.6	34.2 / 21.3	34.2 / 23.9
Sound Power	Cooling	High	dBA	54		62	
Sound Pressure	Cooling	High/Low	dBA	36 / 28	45 / 32	45 / 36	45 / 38
	Heating	High/Low	dBA	36 / 28	45 / 32	45 / 36	45 / 38
Refrigerant			Type	R-410A			
Power Supply				1~/220-240V;220V/50Hz;60Hz			
Decoration Panel	Model	BYCQ140CW1 ¹ / BYCQ140CW1W ² / BYCQ140CGW1 ³					
	Colour	Pure white (RAL 9010)					
	HxWxD	mm		50x950x950 / 50x950x950 / 130x950x950			
	Weight	kg		5.5 / 5.5 / 11.5			
Controllor	Wired/Wireless			BRC1D52 (standard) / BRC7F532F (optional) BRC1E51A (optional) /			
Outdoor Unit				RZQS71DV1	RZQS100DV1	RZQS125DV1	RZQS140DV1
Dimensions	(Height x Width x Depth)		mm	770x900x320		1170x900x320	
Weight			kg	68		103	
Operation Range	Cooling	Min~Max	°CDB		-5~-46		
	Heating	Min~Max	°CWB		-15~-15.5		
Sound Power	Cooling		dBA	65		67	68
Sound Pressure (Standard)	Cooling		dBA	49		51	52
	Heating		dBA	51	55	53	54
Sound Level (Night quiet)	Sound Pressure		dBA	47		49	50
Refrigerant			Type	R-410A			
Power Supply				1~/220-240V/50Hz			
Piping connections	Liquid (OD)/Gas/Drain	mm		9.52 / 15.9 / 26			
Piping Length (Maximum)			m	30		50	
Max. internunit level difference			m	0.5			
Max installation height difference			m	15		30	

¹ Pure white standard panel with grey louvres; ² Pure white standard panel with white louvres; ³ Pure white auto cleaning panel

your comfort. our world.



Authorised User No. 02061

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

www.daikin.co.uk

Daikin products are distributed by:



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.