



FDQ200-250B



RZQ200-250C



BRC1E52A/B

- › Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- › Up to 250Pa external static pressure allows extensive ductwork runs and flexible application: ideal for use in large areas
- › Up to 26.4kW in heating mode
- › Standard built-in drain pump increases reliability of the drain system



Heating & Cooling



INDOOR UNIT			FDQ200B		FDQ250B	
Cooling capacity	Min./Nom./Max.	kW	-/20.0/-		-/24.1/-	
Heating capacity	Min./Nom./Max.	kW	-/23.0/-		-/26.4/-	
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER		3.21		2.81	
	COP		3.41		3.21	
	Annual energy consumption		kWh		3,115	
	Energy label		Cooling/Heating		-/-	
Casing	Colour		Unpainted			
Dimensions	Unit	HeightxWidthxDepth	mm			
Required ceiling void >			450x1,400x900			
			450			
Weight	Unit		kg		89.0	
Fan - Air flow rate	Cooling	Nom.	m³/min		89.0	
Fan - External static pressure	High/Nom./Low		Pa			
Sound power level	Cooling	Nom.	dBA		81.0	
Sound pressure level	Cooling	High	dBA		45.0	
	Heating	Low	dBA		45.0	
Piping	Liquid	OD	mm		9.52	
connections	Gas	OD	mm		22.2	
Power supply	Phase / Frequency / Voltage		Hz / V			
			1 ~ / 50 / 230			

OUTDOOR UNIT				RZQ200C		RZQ250C	
Dimensions	Unit	HeightxWidthxDepth		mm	1,680x930x765		
Weight	Unit			kg	183		
Fan - Air flow rate	Cooling	Nom.		m³/min	171		
	Heating	Nom.		m³/min	171		
Fan - External static pressure	Max.			Pa	78		
Sound power level	Nom.			dBA	78		
Sound pressure level	Nom.			dBA	57		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5.0~46.0		
	Heating	Ambient	Min.~Max.	°CWB	-15.0~15.0		
Refrigerant	Type/GWP				R-410A/-		
Power supply	Phase / Frequency / Voltage			Hz / V	3N~ / 50 / 380-415		
Current - 50Hz	Maximum fuse amps (MFA)			A	20		

(1) EER/COP according to Eurovent 2012