



# 4-Way Blow Ceiling Mounted Cassette

**INVERTER** (600mm X 600mm) FFQ-B / RK(X)S-G/F



Daikin ceiling mounted cassettes are integrated perfectly into the ceiling, which enables you to keep all the available space for your furniture, equipment and decoration. Its size makes the FFQ indoor unit fit exactly into standard architectural modules of 600mm x 600mm. Surrounding ceiling tiles cutting is no longer needed.

Height	286mm
Width	575mm
Depth	575mm



FFQ25B

Height	550mm
Width	765mm
Depth	285mm



RXS25G

See tables overleaf for full list of dimensions

- Inverter technology: reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- Wired remote controller with weekly timer: provides a 7-day schedule timer, enabling daily or weekly programming. Up to 5 actions per day possible.
- Home Leave operation: in case of extended absence, this function automatically keeps the room temperature at a specified favourite comfort level, by switching to heating when it reaches the minimum level and to cooling when it reaches the maximum level.
- Dry programme: Daikin's special dry programme reduces humidity in the rooms without variations in internal temperature.
- Vertical auto-swing function: flaps automatically swing up and down to ensure efficient air and temperature distribution which also prevents ceiling soiling.
- Air purification filter: removes airborne dust particles to ensure a steady supply of clean air. It can easily be removed and washed.
- Forced off: The optional forced off enables the unit to switch off automatically, for example when a window is opened.
- Fan speed: 2 fan speeds can be selected, high or low.
- Self diagnosis digital display: in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- Auto-restart function: after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

**ENERGY LABEL:  
UP TO CLASS  
A**

## COOLING ONLY

## INVERTER

Indoor Units				FFQ25BV	FFQ35BV	FFQ50BV	FFQ60BV	
Capacity	Cooling capacity	Standard	kW	2.5	3.4	4.7	5.8	
EER	Nominal			3.42	3.09	2.61	2.80	
Annual energy consumption			kWh	365	550	900	1035	
Energy Label	cooling			A	B	D	D	
Dimensions	(Height x Width x Depth)			mm	286x575x575	286x575x575	286x575x575	
Weight				kg	17.5	17.5	17.5	
Air Flow Rate	Cooling	High/Low	m³/min	9.0 / 6.5	10.0 / 6.5	12.0 / 8.0	15.0 / 10.0	
Sound Power	Cooling	High	dB(A)	46.5	49.0	53.0	58.0	
Sound Pressure	Cooling	High/Low	dB(A)	29.5 / 24.5	32.0 / 25.0	36.0 / 27.0	41.0 / 32.0	
Refrigerant				Type R-410A				
Power Supply				1~/230V/50Hz				
Decoration Panel	Model			BYFQ60BAW1				
	Colour			White (RAL 9010)				
	HxWxD			mm 55x700x700				
	Weight			kg 2.7				
Controller	Wired/Wireless			BRC1D52 (Standard) / BRC7E531 (Optional)				
Outdoor Unit				RKS25G	RKS35G	RKS50G	RKS60F	
Dimensions	(Height x Width x Depth)			mm	550x765x285	550x765x285	735x825x300	735x825x300
Weight				kg	34	34	48	47
Operation Range	Cooling	Min~Max	°CDB	-10~46	-10~46	-10~46	-10~46	
Sound Power	Cooling		dB(A)	61	62	61	63	
Sound Pressure (Low)	Cooling		dB(A)	43	44	44	46	
Sound Pressure (High)	Cooling		dB(A)	46	48	48	49	
Refrigerant				Type R-410A				
Power Supply				1~/220-240V/50Hz				
Piping connections	Liquid (OD)/Gas			mm	6.35 / 9.52		6.35 / 12.7	
Piping Length (Maximum)				m	20		30	
Max Installation Height Difference				m	15		20	

## HEAT PUMP

## INVERTER

Indoor Units				FFQ25BV	FFQ35BV	FFQ50BV	FFQ60BV	
Capacity	Cooling capacity	Standard	kW	2.5	3.4	4.7	5.8	
	Heating capacity	Standard	kW	3.2	4.0	5.5	7.0	
EER / COP	Cooling / Heating			3.42 / 3.48	3.09 / 3.33	2.61 / 2.81	2.80 / 2.81	
Annual energy consumption			kWh	365	550	900	1035	
Energy Label	cooling / heating			A / B	B / C	D / D	D / D	
Dimensions	(Height x Width x Depth)			mm	286x575x575	286x575x575	286x575x575	
Weight				kg	17.5	17.5	17.5	
Air Flow Rate	Cooling	High/Low	m³/min	9.0 / 6.5	10.0 / 6.5	12.0 / 8.0	15.0 / 10.0	
	Heating	High/Low	m³/min	9.0 / 6.5	10.0 / 6.5	12.0 / 8.0	15.0 / 10.0	
Sound Power	Cooling	High	dB(A)	46.5	49.0	53.0	58.0	
Sound Pressure	Cooling	High/Low	dB(A)	29.5 / 24.5	32.0 / 25.0	36.0 / 27.0	41.0 / 32.0	
	Heating	High/Low	dB(A)	29.5 / 24.5	32.0 / 25.0	36.0 / 27.0	41.0 / 32.0	
Refrigerant				Type R-410A				
Power Supply				1~/230V/50Hz				
Decoration Panel	Model			BYFQ60BAW1				
	Colour			White (RAL 9010)				
	HxWxD			mm 55x700x700				
	Weight			kg 2.7				
Controller	Wired/Wireless			BRC1D52 (Standard) / BRC7E530 (Optional)				
Outdoor Unit				RXS25G	RXS35G	RXS50G	RXS60F	
Dimensions	(Height x Width x Depth)			mm	550x765x285	550x765x285	735x825x300	735x825x300
Weight				kg	34	34	48	48
Operation Range	Cooling	Min~Max	°CDB	-10~46	-10~46	-10~46	-10~46	
	Heating	Min~Max	°CWB	-15~20	-15~20	-15~18	-15~18	
Sound Power	Cooling		dB(A)	61	63	62	63	
Sound Pressure (Low)	Cooling		dB(A)	43	44	44	46	
	Heating		dB(A)	44	45	45	46	
Sound Pressure (High)	Cooling		dB(A)	46	48	48	49	
	Heating		dB(A)	47	48	48	49	
Refrigerant				Type R-410A				
Power Supply				1~/220-240V/50Hz				
Piping connections	Liquid (OD)/Gas			mm	6.35/9.52		6.35/12.7	
Piping Length (Maximum)				m	20		30	
Max Installation Height Difference				m	15		20	

[www.daikin.co.uk](http://www.daikin.co.uk)

Visit [www.eca.gov.uk/etl](http://www.eca.gov.uk/etl) and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

Daikin products are distributed by:

FSC



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.