



FTN-C / RN-C

Wall mounted unit



- Lightweight and compact
- Easily washable front panel
- Air purification filter with photocatalytic deodorising function
- Powerful mode can be selected for rapid cooling
- Energy efficient

- Automatic air flow director ensures uniform air flow and temperature distribution



COOLING ONLY

NON-INVERTER

INDOOR UNIT			FTN20CVMB	FTN25CVMB	FTN35CVMB
Cooling capacity	nominal	kW	2.00	2.25	3.15
Nominal input	cooling	nominal	0.620	0.700	1.045
EER			3.23	3.21	3.01
Energy label			A		B
Annual energy consumption		kWh	310	350	523
Dimensions	HxWxD	mm	273x784x185		
Weight		kg	75		
Air flow rate (H/L)	cooling	m ³ /min	77*	77*	77*
Sound pressure level (H/L)	cooling	dB(A)	38/26	38/26	39/26
Sound power level (H)	cooling	dB(A)	56	56	57
Refrigerant type			R-410A		
Power supply		VM	1 ~ , 220 ~ 240/220 ~ 230V, 50/60Hz		
Infrared remote control			ARC433A24		

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT			RN20CVMB	RN25CVMB	RN35CVMB
Dimensions	HxWxD	mm	560x695x265		
Weight		kg	31		
Sound pressure level (H/L)	cooling	dB(A)	46*	46*	48*
Sound power level (H)	cooling	dB(A)	61	61	63
Operation range	from ~ to	°CDB	10 ~ 46		
Refrigerant type			R-410A		
Power supply		VM	1 ~ , 220-240/220-230V, 50/60Hz		

* This information was not available at the time of publication.