



FTS-B / RS-B

Wall mounted unit



- Lightweight and compact
- Easily washable front panel
- Air purification filter with photocatalytic deodorising function
- Powerful mode can be selected for rapid cooling
- Energy efficient

- Automatic air flow director ensures uniform air flow and temperature distribution



COOLING ONLY

INDOOR UNIT (air cooled)			NON-INVERTER	
			FTS50BVM	FTS60BVM
Cooling capacity	nominal	kW	5.00	6.00
Nominal input	nominal	kW	1.66	2.12
EER			3.01	2.83
Energy label			8	C
Annual energy consumption	cooling	kWh	830	1,060
Dimensions	HxWxD	mm	290x795x230	290x1,050x230
Weight		kg	9	12
Air flow rate (H/L)	H/L	m ³ /min	115/8.3	16.4/11.6
Sound pressure level (H/L)	H/L	dB(A)	44/35	45/36
Sound power level (H)	H	dB(A)	63	63
Refrigerant type			R-410A	
Power supply		VM	1 ~, 220 ~ 240/220 ~ 230V, 50/60Hz	
Infrared remote control			ARC433A24	

Notes:

- 1) Energy label: scale from A (most efficient) to G (less efficient).
- 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
- 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT			RS50BVM	RS60BVM
Dimensions	HxWxD	mm	735x825x300	
Weight		kg	49	53
Sound pressure level	H/L	dB(A)	47/*	49/*
Sound power level	H	dB(A)	63	64
Operation range	from ~ to	°CDB	-10 ~ 46	
Refrigerant type			R-410A	
Power supply		VM	1 ~, 220 ~ 240/220 ~ 230V, 50/60Hz	