



FTYS-B / RYS-B

Wall mounted unit



- Lightweight and compact
- Easily washable front panel
- Air purification filter with photocatalytic deodorising function
- Powerful mode can be selected for rapid cooling and/or heating
- Energy efficient

- Automatic air flow director ensures uniform air flow and temperature distribution



HEAT PUMP

NON-INVERTER

INDOOR UNIT (air cooled)				FTYS50BVMB	FTYS60BVMB
Cooling capacity		nominal	kW	5.00	6.00
Heating capacity		nominal	kW	5.80	7.00
Nominal input	cooling	nominal	kW	1.66	2.12
	heating	nominal	kW	1.70	2.09
EER	cooling			3.01	2.83
	heating			3.41	3.35
Energy label	cooling			B	C
	heating			B	C
Annual energy consumption			kWh	830	1,060
Dimensions		HxWxD	mm	290x795x230	290x1,050x230
Weight			kg	9	12
Air flow rate	cooling	H/L	m ³ /min	11.5/8.3	16.4/11.6
	heating	H/L	m ³ /min	12.2/8.8	17.5/12.8
Sound pressure level	cooling	H/L	dB(A)	44/35	45/36
	heating	H/L	dB(A)	42/*	44/*
Sound power level	cooling	H	dB(A)	63	63
Refrigerant type	R-410A				
Power supply	1 ~, 220 ~ 240/220 ~ 230V, 50/60Hz				
Infrared remote control	ARC433A23				

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT				RYS50BVMB	RYS60BVMB
Dimensions		HxWxD	mm	735x825x300	
Weight			kg	49	53
Sound pressure level	cooling	H/L	dB(A)	47/*	49/*
	heating	H/L	dB(A)	48/*	49/*
Sound power level	cooling	H	dB(A)	63	64
Operation range	cooling	from ~ to	°CDB	-10 ~ 46	
	heating	from ~ to	°CWB	-15 ~ 18	
Refrigerant type	R-410A				
Power supply	1 ~, 220-240/220-230V, 50/60Hz				