



FTN-E/RN-E

Wall mounted unit

new ➡



FTN50,60E



RN50,60E

- Flat front panel: stylish and more easy to clean
- Lightweight and compact
- Titanium apatite photocatalytic air purification filter
- Powerful mode can be selected for rapid cooling

- Energy efficient
- Automatic air flow director ensures uniform air flow and temperature distribution



COOLING ONLY

INDOOR UNIT (air cooled)			NON-INVERTER	
			FTN50E	FTN60E
Cooling capacity	nominal	kW	5.0	6.0
Nominal input	nominal	kW	1.55	1.99
EER			3.23	3.02
Energy label			A	B
Annual energy consumption		kWh	775	995
Dimensions	HxWxD	mm	290x1,050x238	
Weight		kg	12	
Air flow rate	H/L	m ³ /min	14.7/10.3	16.2/11.4
Sound pressure level	H/L	dB(A)	43/34	45/36
Sound power level	H	dB(A)	59	61
Refrigerant type			R-410A	
Power supply		V1	1 ~, 220 ~ 240V, 50Hz	
Infrared remote control			ARC433823	

Notes:

- 1) Energy label: scale from A (most efficient) to G (less efficient).
- 2) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT			RN50E	RN60E
Dimensions	HxWxD	mm	735x825x300	
Weight		kg	47	
Sound pressure level	H	dB(A)	47	49
Sound power level	H	dB(A)	61	63
Operation range	from ~ to	°CDB	-10 ~ 46	
Refrigerant type			R-410A	
Power supply		V1	1 ~, 220 ~ 240V, 50Hz	
Piping connections	liquid/gas	mm	ø6.4/ø12.7	
Max. piping length/Max. level difference		m	30/20	