

FTKS-C / RKS-C / RKH-C

Wall mounted unit



- Flat front panel: stylish appearance and more easy to clean
- lightweight and compact
- Consumes up to 30% less energy than non-inverter units
- Achieves set temperature more quickly
- Home leave operation saves energy during absence
- Movement sensor automatically saves power consumption in unoccupied rooms
- Dual air discharge flow for better air distribution

- Air purification filter with photocatalytic deodorising function
- Powerful mode can be selected for rapid cooling
- Indoor unit silent operation
- Outdoor unit silent operation (only in combination with RKS-C outdoor units)
- Night quiet mode (only in multi application + cooling mode)



COOLING ONLY

DC-INVERTER

INDOOR UNIT				FTKS20CVMB	FTKS25CVMB	FTKS35CVMB
Cooling capacity	min~nom~max	kW	13~2.0~2.6	13~2.5~3.0	14~3.4~3.8	
Nominal input	cooling min~nom~max	kW	0.30~0.50~0.98	0.30~0.695~0.98	0.30~1.06~1.30	
EER			4.00	3.60	3.21	
Energy label			A	A	A	
Annual energy consumption		kWh	250	348	530	
Dimensions	HxWxD	mm		273x784x195		
Weight		kg		75		
Air flow rate (H/L)	cooling	m ³ /min	7.7*	7.7*	7.7*	
Sound pressure level (H/LSL)	cooling	dB(A)	38/25/22	38/25/22	39/26/23	
Sound power level (H)	cooling	dB(A)	56	56	57	
Refrigerant type			R-410A			
Power supply	VM		1~, 220~240/220~230V, 50/60Hz			
Infrared remote control			ARC433A2			

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT			RKS20CVMB	RKS25CVMB	RKS35CVMB	RKH20CVMB	RKH25CVMB	RKH35CVMB
Dimensions	HxWxD	mm	550x765x285			560x695x265		
Weight		kg	30		32	31		33
Sound pressure level (H/L)	cooling	dB(A)	46/43	46/43	47/44	46/*	46/*	48/*
Sound power level (H)	cooling	dB(A)	61	61	62	61	61	63
Operation range	cooling	from~to	-10~46			10~46		
Refrigerant type			R-410A			R-410A		
Power supply	VM		1~, 220-240/220-230V, 50/60Hz			1~, 220-240/220-230V, 50/60Hz		

* This information was not available at the time of publication.