



FUQ-C / RZQG-L7V1 (LY1)

Under Ceiling Cassette

Seasonal Smart



RZQG125L7V1

Outdoor Unit

RZQG71	H x W x D	990 x 940 x 320mm
RZQG100/125	H x W x D	1430 x 940 x 320mm

Accessories

Wireless remote controller (BRC7CB58)

Daikin's Under Ceiling Cassette is a unique product – a 4 way blow system that can be installed under the ceiling in rooms that have solid ceilings or narrow voids that may prevent a traditional cassette being installed.

The Under Ceiling Cassette exceeds Energy Related Products Directive minimum efficiency standards for Seasonal Efficiency, combining industry leading efficiencies with smart looks and functionality to suit office and retail applications.

The re-designed profile of the unit means it is less obtrusive when installed. Air discharge louvres close completely when the unit is not operating, adding to the aesthetic.

Energy savings can be made using the remote controller which gives control over set-point ranges and day-to-day use of controls. This can give occupants some flexibility over room conditions without compromising energy usage.

Energy efficiencies can be improved by utilising the selectable evaporating and condensing temperature option, making the Seasonal Smart Under Ceiling Cassette the ideal solution for energy conscious building managers.



FEATURES

BENEFITS

Programmable air discharge outlets via remote control	Can be changed to 2, 3 or 4 way blow if room configuration requires it
Selectable evaporating and condensing temperatures	Improves energy efficiency of the 'out of the box' system by 20%, saving money on running costs
D3 connection as standard	Allows integration of split system into Daikin building management systems
Drain pump with 500m lift as standard	Drain condensate liquid away from unit
Automatic air-flow adjustment	Can improve comfort levels as the unit will automatically change fan-speed according to room temperature

Indoor Units			Single Phase			3 Phase			
			FUQ71C	FUQ100C	FUQ125C	FUQ71C	FUQ100C	FUQ125C	
Cooling Capacity	Nominal	kW	6.8	9.5	12.0	6.8	9.5	12.0	
	UK Total	kW	7.76	10.8	13.6	7.76	10.8	13.6	
	UK Sensible	kW	5.32	7.44	9.3	5.32	7.44	9.3	
Heating Capacity	Nominal	kW	7.5	10.8	13.5	7.5	10.8	13.5	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A++	A+	B	A++	A+	B	
		Pdesign	kW	6.80	9.50	12.00	6.80	9.50	12.00
		SEER		6.23	5.62	5.03	6.23	5.62	5.03
	Heating (Average climate)	Annual energy consumption	kWh	382	592	835	382	592	835
		Energy label		A+	A	A+	A+	A	A+
		Pdesign	kW	7.60	11.30	14.13	7.60	11.30	14.13
	Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	SCOP		4.08	3.93	4.44	4.08	3.93	4.44
		Annual energy consumption	kWh	2,607	4,027	4,456	2,607	4,027	4,456
		Energy label Cooling/Heating		A/A			A/A		
Nominal Power Input	Cooling / Heating	kW	1.67 / 1.68	2.33 / 2.67	3.53 / 3.34	1.67 / 1.68	2.33 / 2.67	3.53 / 3.34	
Dimensions	Height x Width x Depth	mm	198 x 950 x 950			198 x 950 x 950			
Weight		kg	25	26		25	26		
Air Flow Rate	High / Low	m³/min	23 / 16	31 / 20	32.5 / 20.5	23 / 16	31 / 20	32.5 / 20.5	
Sound Power	High	dBA	59	64	65	59	64	65	
Sound Pressure	High / Low	dBA	41 / 35	46 / 39	47 / 40	41 / 35	46 / 39	47 / 40	
Refrigerant	Type		R410A			R410A			
Power Supply			From outdoor unit			From outdoor unit			
Controller			BRC1E52A wired			BRC1E52A wired			

Outdoor Unit			RZQG71L7V1	RZQG100L7V1	RZQG125L7V1	RZQG71LY1	RZQG100LY1	RZQG125LY1
Dimensions	(Height x Width x Depth)	mm	990 x 940 x 320	1430 x 940 x 320		990 x 940 x 320	1430 x 940 x 320	
Weight		kg	78	102		80	101	
Operation Range	Cooling Min~Max	°CDB	-15°C to +50°C			-15°C to +50°C		
	Heating Min~Max	°CWB	-20°C to +15.5°C			-20°C to +15.5°C		
Sound Power	Nom.	dBA	64	66	67	64	66	67
Sound Pressure	Nom.	dBA	48	50	51	48	50	51
Refrigerant	Type		R410A			R410A		
Power Supply			1~ / 50Hz / 220 - 240v			3~ / 50Hz / 400v		
Piping connections	Liquid (OD)/Gas	inches	3/8 / 5/8			3/8 / 5/8		
Piping Length (Maximum)		m	50	75		50	75	
Max Installation Height Difference		m	30			30		



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin products are distributed by: