



CEILING SUSPENDED 4-WAY BLOW CASSETTE

FUYP-B

COOLING ONLY			FUYP71BV1	FUYP100BV1	FUYP125BV1
INDOOR UNIT					
Capacity	kW		7.1	10.0	12.5
Power input	kW		2.66/2.64/2.64	3.64/3.61/3.61	4.66/4.66
Dimensions	HxWxD	mm	165x895x895	230x895x895	
Weight	kg		25	31	
Colour			white		
Air flow rate	H/L	m ³ /min	19/14	29/21	32/23
Fan speed			2 steps		
Sound pressure level	H/L	dB(A)	40/35	43/38	44/39
Sound power level	H/L	dB(A)	56/51	59/54	60/55
Piping connections	liquid (flare)	mm	Ø 9.5	Ø 9.5	Ø 9.5
	gas (flare)	mm	Ø 15.9	Ø 19.1	Ø 19.1
	drain (VP20)	ID mm	Ø 20	Ø 20	Ø 20
		OD mm	Ø 26	Ø 26	Ø 26
Heat insulation			both liquid and gas pipes		
OUTDOOR UNIT: pair application			RP71B7V1/W1/T1	RP100B7V1/W1/T1	RP125B7W1/T1
See page			23	23	23
ACCESSORIES	See page		29	29	29

HEAT PUMP			FUYP71BV1	FUYP100BV1	FUYP125BV1
INDOOR UNIT					
Capacity	cooling	kW	7.1	10.0	12.5
	heating	kW	7.7	11.0	14.0
Power input	cooling	kW	2.66/2.64	3.64/3.61	4.66
	heating	kW	2.62/2.60	3.60/3.57	4.91
Dimensions	HxWxD	mm	165x895x895	230x895x895	
Weight	kg		25	31	
Colour			white		
Air flow rate	cooling	m ³ /min	19/14	29/21	32/23
	(H/L) heating	m ³ /min	19/14	29/21	32/23
Fan speed			2 steps		
Sound pressure level	cooling	dB(A)	40/35	43/38	44/39
	(H/L) heating	dB(A)	40/35	43/38	44/39
Sound power level	cooling	dB(A)	56/51	59/54	60/55
	(H/L) heating	dB(A)	56/51	59/54	60/55
Piping connections	liquid (flare)	mm	Ø 9.5	Ø 9.5	Ø 9.5
	gas (flare)	mm	Ø 15.9	Ø 19.1	Ø 19.1
	drain (VP20)	ID mm	Ø 20	Ø 20	Ø 20
		OD mm	Ø 26	Ø 26	Ø 26
Heat insulation			both liquid and gas pipes		
OUTDOOR UNIT: pair application			RYP71B7V1/W1	RYP100B7V1/W1	RYP125B7W1
See page			24	24	24
ACCESSORIES	See page		29	29	29