



Floor Standing Unit



FVQ-B / RZQS-C



Wired remote controller

Sky Air FUQ floor standing units are specially designed for stores and offices with high ceilings. They are extremely quiet in operation and the use of a high efficiency, long life filter reduces maintenance time and cost.

- **Inverter technology:** reduces the power consumption by up to 30% compared to non inverter units and ensures maximum comfort, operating silence and reliability.
- **Auto swing function:** flaps automatically swing from left to right to distribute air effectively throughout the entire room. Vertical air flow pattern can be adjusted manually to match requirements in different sized interiors or irregularly shaped rooms.
- **Dry programme:** Daikin's special dry programme reduces humidity in the rooms without variations in internal temperature.
- **High efficiency long-life filter:** removes airborne dust particles to ensure a steady supply of clean air.
- **Fan speed:** 2 fan speeds can be selected, high or low.
- **Controller:** A wired remote controller is mounted on the front of the unit (standard).
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.

Height	1850mm
Width	600mm
Depth	270mm



FVQ71B

Height	770mm
Width	900mm
Depth	320mm



RZQS71C

See tables overleaf for full list of dimensions

ENERGY LABEL:
UP TO CLASS
C

HEAT PUMP

COMFORT INVERTER

Indoor Units				FVQ71B	FVQ100B	FVQ125B			
Capacity	Cooling capacity	Standard	kW	7.1	10.0	12.5			
	Heating capacity	Standard	kW	8.0	11.2	14.0			
EER / COP	Cooling / Heating			2.81	3.21	2.49	2.81	2.81	3.21
Annual energy consumption			kWh	1265	2010	2225			
Energy Label	cooling / heating			C / C	E / D	C / C			
Dimensions	(Height x Width x Depth)		mm	1850x600x270	1850x600x350	1850x600x350			
Weight			kg	39	46	47			
Sound Power	Cooling	High/Low	dBA	54 / 48	60 / 54	62 / 56			
	Heating	High/Low	dBA	54 / 48	60 / 54	62 / 56			
Sound Pressure	Cooling	High/Low	dBA	42 / 36	48 / 42	50 / 44			
	Heating	High/Low	dBA	42 / 36	48 / 42	50 / 44			
Refrigerant			Type	R-410A					
Power Supply				220-240V/50Hz					
Controller				BRC1C61					
Outdoor Unit				RZQS71CV1	RZQS100CV1	RZQS125CV1			
Dimensions	(Height x Width x Depth)		mm	770x900x320	770x900x320	1170x900x320			
Weight			kg	68		103			
Operation Range	Cooling	Min~Max	°CDB	-5~46					
	Heating	Min~Max	°CWB	-15~15.5					
Sound Power	Cooling		dBA	65	67				
Sound Pressure (Standard)	Cooling		dBA	49	51				
	Heating		dBA	51	55	53			
Sound Level (Night quiet)	Sound Pressure		dBA	47	49				
Refrigerant			Type	R-410A					
Power Supply				1~/220-240V/50Hz					
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26					
Piping Length (Maximum)			m	30	50				
Max. internunit level difference			m	0.5					
Max installation height difference			m	15	30	30			



Authorised User No. 02061

Visit www.eca.gov.uk/etl and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

www.daikin.co.uk

Daikin products are distributed by:

FSC

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.



Daikin units comply with the European regulations that guarantee the safety of the product.



Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.