



FVKS-B / RKS-B

Floor standing unit



FVKS25,35B



RKS25,35B

- Consumes up to 30% less energy than non-inverter units
- Achieves set temperature more quickly
- Home leave operation saves energy during absence
- Dual air discharge flow for better air distribution
- lightweight and compact
- Easy washable grille
- Can be installed against a wall or recessed

- Air purification and photocatalytic deodorising filter
- Powerful mode can be selected for rapid cooling
- Indoor unit silent operation
- Outdoor unit silent operation
- Night quiet mode (only in multi application + cooling mode)



COOLING ONLY

DC-INVERTER

NON-INVERTER

INDOOR UNIT				FVKS25BVMB	FVKS35BVMB	FVKS50BVMB	FVKS50BVMB
Cooling capacity	min ~ nom ~ max	kW		1.00 ~ 2.50 ~ 3.00	1.00 ~ 3.50 ~ 3.70	0.90 ~ 4.80 ~ 5.30	4.80 (nominal)
Nominal input	cooling	min ~ nom ~ max	kW	0.24 ~ 0.70 ~ 0.925	0.24 ~ 1.16 ~ 1.30	0.45 ~ 1.70 ~ 2.35	1.70 (nominal)
EER				3.57	3.02	2.82	2.82
Energy label				A	B	C	C
Annual energy consumption		kWh		350	580	850	850
Dimensions	HxWxD	mm		600x650x195			
Weight		kg		13			
Air flow rate (H/L)	cooling	m ³ /min		8.1/4.3/3.4	8.3/4.3/3.4	10.8/7.7/6.7	10.8/7.7/6.7
Sound pressure level (H/L)	cooling	dB(A)		38/26/23	39/27/24	44/36/33	44/36/33
Sound power level (H)	cooling	dB(A)		54	55	56	56
Refrigerant type				R-410A			
Power supply		VM		1 ~, 220-240/220-240V, 50/60Hz			
Infrared remote control				ARC433A6			

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT				RKS25BVMB	RKS35BVMB	RKS50BVMB9	RS50BVMB
Dimensions	HxWxD	mm		560x695x265		735x825x300	735x825x300
Weight		kg		37		49	49
Sound pressure level (H/L)	cooling	dB(A)		46/43	47/44	47**	47**
Sound power level (H)	cooling	dB(A)		59	60	63	63
Operation range	from ~ to	°CDB		-10 ~ 46		-10(-15**) ~ 46	-10 ~ 46
Refrigerant type				R-410A			
Power supply				1 ~, 220-240/220-230V, 50/60Hz			

* This information was not available at the time of publication.

** Possibility to extend the operation range down to -15°C by turning ON the switch on the outdoor unit PCB. In this case, the unit will stop operation at -20°C or lower and will recover when temperature rises again.