



FVXS-B / RXS-B

Floor standing unit



- Consumes up to 30% less energy than non-inverter units
- Achieves set temperature more quickly
- Home leave operation saves energy during absence
- Dual air discharge flow for better air distribution
- lightweight and compact
- Easy washable grille
- Can be installed against a wall or recessed
- Air purification and photocatalytic deodorising filter
- Powerful mode can be selected for rapid cooling and/or heating
- Indoor unit silent operation
- Outdoor unit silent operation
- Night quiet mode (only in multi application + cooling mode)



HEAT PUMP

| INDOOR UNIT | | | | FVXS25BVM | FVXS35BVM | FVXS50BVM |
|--------------------------------|-------------|---------------------|-----------------|-------------------------------|----------------|-----------|
| Cooling capacity | min~nom~max | kW | 100~250~300 | 100~350~370 | 0.90~4.80~5.30 | |
| Heating capacity | min~nom~max | kW | 100~340~500 | 100~450~500 | 0.90~6.00~7.70 | |
| Nominal input | cooling | min~nom~max | 0.24~0.70~0.925 | 0.24~116~130 | 0.45~1.70~2.35 | |
| | heating | min~nom~max | 0.24~0.84~1.43 | 0.24~1.285~1.83 | 0.31~1.87~2.60 | |
| EER | cooling | | 3.57 | 3.02 | 2.82 | |
| COP | heating | | 4.05 | 3.50 | 3.21 | |
| Energy label | cooling | | A | B | C | |
| | heating | | A | B | C | |
| Annual energy consumption | | kWh | 350 | 580 | 850 | |
| Dimensions | HxWxD | mm | | 600x650x195 | | |
| Weight | | kg | | 13 | | |
| Air flow rate (H/L/S/L) | cooling | m ³ /min | 8.1/4.3/3.4 | 8.3/4.3/3.4 | 10.8/7.7/6.7 | |
| | heating | m ³ /min | 9.2/4.8/3.5 | 9.2/5.0/3.6 | 13.2/9.4/8.3 | |
| Sound pressure level (H/L/S/L) | cooling | dB(A) | 38/26/23 | 39/27/24 | 44/36/33 | |
| | heating | dB(A) | 38/26/23 | 39/29/36 | 45/36/33 | |
| Sound power level (H) | cooling | dB(A) | 54 | 55 | 56 | |
| Refrigerant type | | | | R-410A | | |
| Power supply | | VM | | 1~, 220-230/220-240V, 50/60Hz | | |
| Infrared remote control | | | | ARC433A5 | | |

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

| OUTDOOR UNIT | | | | RXS25BVM | RXS35BVM | RXS50BVM |
|----------------------------|---------|-------|-------|-------------------------------|----------|-------------|
| Dimensions | HxWxD | mm | | 560x695x265 | | 735x825x300 |
| Weight | | kg | | 37 | | 49 |
| Sound pressure level (H/L) | cooling | dB(A) | 46/43 | 47/44 | 47* | |
| | heating | dB(A) | 47/44 | 48/45 | 48* | |
| Sound power level (H) | cooling | dB(A) | 59 | 60 | 63 | |
| | heating | dB(A) | 59 | 60 | 63 | |
| Operation range | cooling | °CDB | | -10~46 | | |
| | heating | °CWB | | -15~20 | | |
| Refrigerant type | | | | R-410A | | |
| Power supply | | | | 1~, 220-240/220-230V, 50/60Hz | | |

* This information was not available at the time of publication.