



# FVKS-B / RKS-D/B

## Floor standing unit



- Consumes up to 30% less energy than non-inverter units
- Achieves set temperature more quickly
- Home leave operation saves energy during absence
- Dual air discharge flow for better air distribution
- lightweight and compact
- Easy washable grille
- Can be installed against a wall or recessed

- Air purification and photocatalytic deodorising filter
- Powerful mode can be selected for rapid cooling
- Indoor unit silent operation
- Outdoor unit silent operation
- Night quiet mode (only in multi application + cooling mode)



### COOLING ONLY

### INVERTER

### NON-INVERTER

INDOOR UNIT (air cooled)			FVKS25BVMB	FVKS35BVMB	FVKS50BVMB	FVKS50BVMB
Cooling capacity	min~nom~max	kW	13~25~3.0	14~35~3.8	0.90~4.80~5.30	4.80 (nominal)
Nominal input	min~nom~max	kW	0.30~0.70~0.92	0.30~1.09~1.25	0.45~1.70~2.35	1.70 (nominal)
EER			3.57	3.21	2.82	2.82
Energy label			A	A	C	C
Annual energy consumption	cooling	kWh	350	545	850	850
Dimensions	HxWxD	mm		600x650x195		600x650x195
Weight		kg		13		13
Air flow rate	H/L/SL	m <sup>3</sup> /min	8.1/**	8.3/**	10.8/7.7/6.7	10.8/7.7/6.7
Sound pressure level	H/L/SL	dB(A)	38/26/23	39/27/24	44/36/33	44/36/33
Sound power level	H	dB(A)	54	55	56	56
Refrigerant type				R-410A		R-410A
Power supply	VM			1~, 220-230/220-240V, 50/60Hz		1~, 220-230/220-240V, 50/60Hz
Infrared remote control				ARC433A6		ARC433A6

Notes: 1) Energy label: scale from A (most efficient) to G (less efficient).  
 2) The Energy Label Directive 2002/31/EC will enter into force once the relevant measurement standard will be published in the European Official Standard.  
 3) Annual energy consumption: based on average use of 500 running hours per year full load (= nominal capacity).

OUTDOOR UNIT			RKS25DVMB	RKS35DVMB	RKS50BVBMB9	R550BVBMB
Dimensions	HxWxD	mm		550x765x285	735x825x300	735x825x300
Weight		kg	30	32	49	49
Sound pressure level	H/L	dB(A)	46/43	47/44	47**	47**
Sound power level	H	dB(A)	61	62	63	63
Operation range	from~to	°CDB		-10~46	-10(-15)**~46	-10~46
Refrigerant type				R-410A	R-410A	R-410A
Power supply	VM			1~, 220-240/220-230V, 50/60Hz	1~, 220-240/220-230V, 50/60Hz	1~, 220-240/220-230V, 50/60Hz

\* This information was not available at the time of publication.  
 \*\* Possibility to extend the operation range down to -15°C by turning ON the switch on the outdoor unit PCB. In this case, the unit will stop operation at -20°C or lower and will recover when temperature rises again.