

FXAQ-P

Wall mounted unit



BRC1E51




BRC7E618



FXAQ40-63P

- Modern style flat front panel
- Vertical auto-swing function moves the discharge flaps up and down for efficient air distribution throughout the room
- 5 different discharge angles can be programmed via the remote control



- Both horizontal flaps and front panel can easily be removed and washed
- All maintenance operations can be carried out from the front of the unit
- Ideal for refurbishment projects
- Allows multi tenant applications (option PCB required)
- **BRC1E51A – new wired controller:** allows easy navigation through menu items, via a personalised display and minimal number of buttons. Provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible

FXAQ-P				INVERTER					
Indoor units				20	25	32	40	50	63
Capacity	Cooling	Nominal	kW	2.20	2.80	3.60	4.50	5.60	7.10
	Heating	Nominal	kW	2.50	3.20	4.00	5.00	6.30	8.00
Power input (50Hz)	Cooling	Nominal	kW	0.019	0.028	0.030	0.020	0.033	0.050
	Heating	Nominal	kW	0.029	0.034	0.035	0.020	0.039	0.060
Dimensions	(Height x Width x Depth)		mm	290x795x238			290x1,050x238		
Weight			kg	11			14		
Air flow rate	Cooling	HH/H/M/L	m³/min	- / 7.5 / - / 4.5	- / 8 / - / 5	- / 8.5 / - / 5.5	- / 12 / - / 9	- / 15 / - / 12	- / 19 / - / 14
Refrigerant				R-410A					
Sound power	Cooling	Nominal	dBA	-					
Sound pressure	Cooling	HH/H/M/L	dBA	- / 35 / - / 29	- / 36 / - / 29	- / 37 / - / 29	- / 39 / - / 34	- / 42 / - / 36	- / 46 / - / 39
Power supply				1~/220-240V/50Hz					
Piping connections	Liquid (OD)/Gas/Drain	mm		6.35 / 12.7 / VP13 (I.D. 13/O.D. 18)					9.52/15.9/VP13 (I.D. 13/O.D. 18)
Casing colour				White (3.0/8.5 / 0.5)					