



FXAQ15-32P



BRC1E52A/B

BRC7E63

- > Ideal solution for shops, restaurants or offices without false ceilings
- > Low energy consumption thanks to DC fan motor
- > Can be installed in both new and existing buildings
- > Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > 5 different discharge angles can be programmed via the remote control
- > Maintenance operations can be performed from the front of the unit



INDOOR UNIT				FXAQ15P	FXAQ20P	FXAQ25P	FXAQ32P	FXAQ40P	FXAQ50P	FXAQ63P
Cooling capacity	Nom.		kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	Nom.	kW	0.017	0.019	0.028	0.030	0.020	0.033	0.050
	Heating	Nom.	kW	0.025	0.029	0.034	0.035	0.020	0.039	0.060
Casing Colour				White (3.0Y8.5/0.5)						
Dimensions	Unit	HeightxWidthxDepth	mm	290x795x238				290x1,050x238		
Weight	Unit		kg	11				14		
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min	7.0/4.5	7.5/4.5	8/5	8.5/5.5	12/9	15/12	19/14
Sound power level	Cooling	Nom.	dB(A)	-						
Sound pressure level	Cooling	High/Low	dB(A)	34.0/29.0	35.0/29.0	36.0/29.0	37.5/29.0	39.0/34.0	42.0/36.0	47.0/39.0
Refrigerant	Type			R-410A						
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/VP13 (I.D. 13/O.D. 18)						9.52/15.9/VP13 (I.D. 13/O.D. 18)
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)		A	16						