



FXCQ-M8

2-way blow ceiling mounted cassette



BRC1E51




BRC7C62



FXCQ20,25,32M8

- Compact dimensions, can easily be mounted in a ceiling void of only 355mm



- Auto-swing function ensures efficient air and temperature distribution and prevents ceiling soiling
- Drain up pump with 600mm lift fitted as standard
- Leaves maximum floor and wall space for furniture, decorations and fittings
- Easy to clean flat suction grille
- **BRC1E51A – new wired controller:** allows easy navigation through menu items, via a personalised display and minimal number of buttons. Provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible

FXCQ-M8			20	25	32	40	50	63	80	125	
Indoor Units											
Capacity	Cooling	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	14.00	
	Heating	kW	2.50	3.20	4.00	5.00	6.30	8.00	10.00	16.00	
Power input	Cooling	kW	0.077	0.092		0.130		0.161		0.256	
	Heating	kW	0.044	0.059		0.097		0.126		0.176	
Dimensions	(Height x Width x Depth)		305x780x600			305x995x600		305x1,180x600		305x1,670x600	
Weight			26			31		32		35	
Air flow rate	Cooling	High/Low	m ³ /min		7.0 / 5.0	9.0 / 6.5		12.0 / 9.0		16.5 / 13.0	
	Heating	High/Low	m ³ /min		7.0 / 5.0	9.0 / 6.5		12.0 / 9.0		16.5 / 13.0	
Sound power (nominal)	Cooling		dBA		45.0	50.0		52.0		54.0	
Sound pressure	Cooling	High/Low	dBA		33.0 / 28.0	35.0 / 29.0		35.5 / 30.5		38.0 / 33.0	
	Heating	High/Low	dBA		33.0 / 28.0	35.0 / 29.0		35.5 / 30.5		38.0 / 33.0	
Refrigerant			R-410A								
Power supply			1~/230V/50Hz								
Piping connections	Liquid (OD)/Gas/Drain	mm	6.35 / 12.7 / 32						9.5 / 15.9 / 32		
Decoration panel	Model		BYBC32GJW1			BYBC50GJW1		BYBC63GJW1		BYBC125GJW1	
	Colour		White (10Y9/0.5)								
	HeightxWidthxDepth	mm	53x1030x680			53x1245x680		53x1430x680		53x1920x680	
	Weight	kg	8.0			8.5		9.5		12.0	