



FXDQ-M9

Concealed ceiling unit (small)



BRC1E51



BRC4C62



FXDQ20,25M9

- Designed for hotel bedrooms
- Compact dimensions (230mm high & 652mm deep), can easily be mounted in a ceiling void
- The air suction direction can be altered from rear to bottom suction
- Air suction filter fitted as standard
- For easy mounting, the drain pan can be located to the left or the right of the unit
- Allows multi tenant application
- **BRC1E51A – new wired controller:** allows easy navigation through menu items, via a personalised display and minimal number of buttons. Provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible

FXDQ-M9					
Indoor Units				20	25
Capacity	Cooling		kW	2.20	2.80
	Heating		kW	2.50	3.20
Power input	Cooling		kW	0.050	
	Heating		kW	0.050	
Dimensions	(Height x Width x Depth)		mm	230x502x652	
Weight			kg	17	
Air Flow Rate	Cooling	High/Low	m ³ /min	6.70 / 5.20	7.40 / 5.80
	Heating	High/Low	m ³ /min	6.70 / 5.20	7.40 / 5.80
Sound power (nominal)	Cooling		dBA	50.0	
Sound Pressure	Cooling	High/Low	dBA	37.0 / 32.0	
	Heating	High/Low	dBA	37.0 / 32.0	
Refrigerant				R-410A	
Power Supply				1~/230V/50Hz	
Piping connections	Liquid (OD)/Gas/Drain (OD)		mm	6.4 / 12.7 / 27.2	