



FXDQ-M9



BRC1E52A/B

BRC4C62

- > Designed for hotel bedrooms
- > Compact dimensions (230mm high & 652mm deep), can easily be mounted in a ceiling void
- > Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- > The air suction direction can be altered from rear to bottom suction
- > For easy mounting, the drain pan can be located to the left or right of the unit



INDOOR UNIT				FXDQ20M9	FXDQ25M9
Cooling capacity	Nom.		kW	2.2	2.8
Heating capacity	Nom.		kW	2.5	3.2
Power input - 50Hz	Cooling	Nom.	kW		0.050
	Heating	Nom.	kW		0.050
Casing Colour				Unpainted	
Dimensions	Unit	HeightxWidthxDepth	mm	230x502x652	
Required ceiling void >			mm	250	
Weight	Unit		kg	17	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min	6.7/5.2	7.4/5.8
	Heating	High/Low	m ³ /min	6.7/5.2	7.4/5.8
Sound power level	Cooling	Nom.	dB(A)	50	
Sound pressure level	Cooling	High/Low	dB(A)	37/32	
	Heating	High/Low	dB(A)	37/32	
Refrigerant	Type			R-410A	
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/I.D. 21.6, O.D. 27.2	
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/230	
Current - 50Hz	Maximum fuse amps (MFA)		A	16	