




FXDQ15-32A



BRC1E52A/B BRC4C65

- > Compact dimensions, can easily be mounted in a ceiling void of only 240mm
- > Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > Low energy consumption thanks to DC fan motor
- > Medium external static pressure facilitates unit use with flexible ducts of varying lengths
- > Standard drain pump with 750mm lift



INDOOR UNIT			FXDQ15A	FXDQ20A	FXDQ25A	FXDQ32A	FXDQ40A	FXDQ50A	FXDQ63A	
Cooling capacity	Nom.	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1	
Heating capacity	Nom.	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0	
Power input - 50Hz	Cooling	Nom.	0.071				0.078	0.099	0.110	
	Heating	Nom.	0.068				0.075	0.096	0.107	
Dimensions	Unit	HeightxWidthxDepth	200x750x620				200x950x620		200x1,150x620	
Weight	Unit	kg	22				26		29	
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low	7.5/7.0/6.4	8.0/7.2/6.4			10.5/9.5/8.5	12.5/11.0/10.0	16.5/11.0/13.0	
Fan - External static pressure - 50Hz	High/Nom.	Pa	30/10				44/15			
Sound power level	Cooling	Nom.	50	51			52	53	54	
Sound pressure level	Cooling	High/Low	to be confirmed							
	Heating	High/Nom./Low	32/31/27	33/31/27			34/32/28	35/33/29	36/34/30	
Refrigerant	Type		R-410A							
Piping connections	Liquid/OD/Gas/OD/Drain	mm	6.35/12.7/VP20(O.D.26/I.D.20)							9.52/15.90/VP20(O.D.26/I.D.20)
Power supply	Phase/Frequency/Voltage	Hz/V	1~ / 50/60 / 220-240/220							
Current - 50Hz	Maximum fuse amps (MFA)	A	16							