



UK.FXDQ15-63A



BRC1E52A/B

BRC4C65



UK.FXDQ-A **Concealed Low Wall Ducted Unit** VRV Indoor unit

The concealed low wall units cover a wide range of capacities, and with ductwork connection possible can be installed discreetly with a high degree of flexibility.

The Daikin VRV indoor unit range is one of the widest on the market, offering no less than 26 stylish and elegant models in 116 different variants - all designed to maximise comfort, minimise operating noise and simplify installation and servicing.

Designed to fit rooms of any size and shape, Daikin indoor units are also user friendly, ultra reliable, easy to control and quiet in operation.

From January 2013, all indoor units will have to comply with the Ecodesign legislation on fans. As a market leader, Daikin has ensured that all indoors units comply with this legislation by adopting DC fans in all indoor units, improving their energy efficiency even further.

Features and Benefits

- › Its low height means the unit fits perfectly beneath a window
- › Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- › Low energy consumption thanks to DC fan motor
- › Medium external static pressure means unit can be used with flexible ducts of varying lengths
- › Standard drain pump with 750mm lift
- › Requires very little installation space

Indoor Units			UK.FXDQ15A	UK.FXDQ20A	UK.FXDQ25A	UK.FXDQ32A	UK.FXDQ40A	UK.FXDQ50A	UK.FXDQ63A	
Capacity	UK Total Cooling	kW	1.40	1.80	2.30	2.90	3.60	4.50	5.70	
	UK Sensible Cooling	kW	1.30	1.60	1.90	2.20	2.80	3.50	4.30	
	UK Heating	kW	1.30	1.91	2.44	3.05	3.81	4.80	6.10	
	UK Heating VRV/III HR only	kW	1.39	2.05	2.62	3.28	4.10	5.16	6.56	
	Nominal Cooling	kW	1.70	2.20	2.80	3.60	4.50	5.60	7.10	
	Nominal Heating	kW	1.70	2.50	3.20	4.00	5.00	6.30	8.00	
Air Flow Rate	High	m3/sec	0.13	0.13	0.13	0.13	0.18	0.21	0.28	
	Nom	m3/sec	0.12	0.12	0.12	0.12	0.16	0.18	0.24	
	Low	m3/sec	0.11	0.11	0.11	0.11	0.14	0.17	0.22	
External Static Pressure	High	Pa	30.0	30.0	30.0	30.0	44.0	44.0	44.0	
	Low	Pa	10.0	10.0	10.0	10.0	15.0	15.0	15.0	
Dimensions	Height x width x depth	mm	620 x 750 x 200				620 x 950 x 200		620 x 1150 x 200	
Weight		kg	22	22	22	22	26	26	29	
Electrical Details	Power Supply	Phase	1ph							
		Hz	50							
		V	230							
	Running Current	amps	0.3	0.3	0.3	0.3	0.4	0.4	0.5	
	Fuse Rating	amps	5							
Sound Level	Sound Pressure	Hi Hi	dBA	32.0	33.0	33.0	33.0	34.0	35.0	36.0
		High	dBA	31.0	31.0	31.0	31.0	32.0	33.0	34.0
		Low	dBA	29.0	29.0	29.0	29.0	28.0	29.0	30.0
	Sound Power	dBA	-	-	-	-	-	-	-	
Piping Connections	Liquid	inches	1/4	1/4	1/4	1/4	1/4	1/4	3/8	
	Gas	inches	1/2	1/2	1/2	1/2	1/2	1/2	5/8	



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin products are distributed by: