




FXXQ-M

Ceiling mounted corner cassette

FXXQ63M





- Specific design for use in rooms with shallow ceiling voids
- Auto-swing mechanism ensures even room air and temperature distribution
- Choice of 3 auto-swing positions for maximum comfort : standard, draught prevention or ceiling soiling prevention



Note:
Set standard to 1-way discharge when shipped.
High ceiling types 1 and 2 will be set for remote control operation.

- Optimum air flow conditions are created by either downward or frontal air discharge (via optional grille) or a combination of both



- Leaves maximum floor and wall space for furniture, decoration and fittings

FXXQ-MVE

INDOOR UNIT		25	32	40	63
Cooling capacity	kW	2.8	3.6	4.5	7.1
Heating capacity	kW	3.2	4.0	5.0	8.0
Nominal input	cooling	66	66	76	105
	heating	46	46	56	85
Dimensions (HxWxD)	mm	215x110x710			215x1310x710
Weight	kg	31			34
Air flow rate (H/L)	m ³ /min	11/9	11/9	13/10	18/15
Sound pressure level (H/L)(220V)	dB(A)	38/33	38/33	40/34	42/37
Sound power level	dB(A)	*	*	*	*
Refrigerant type		R-410A			
Power supply	VE	1 ~, 50Hz, 220-240V			
Infrared remote control	cooling	BRC4C63			
	heating	BRC4C61			
		BRC1D517			
Wired remote control		BYK45FW1			
DECORATION PANEL		BYK1240x800			BYK1440x800
Dimensions (HxWxD)	mm	70x1,240x800			70x1,440x800
Weight	kg	85			95

* Sound power levels were not available at time of publication