




FXKQ-MA



BRC1E52A/B BRC4C61

- > Compact dimensions, can easily be mounted in a narrow ceiling void (only 220mm ceiling space required, 195 with panel spacer, available as accessory)
- > Optimum air flow conditions are created by either downward air discharge or frontal air discharge (via optional grille) or a combination of both



- > Standard drain pump with 500mm lift



INDOOR UNIT			FXKQ25MA	FXKQ32MA	FXKQ40MA	FXKQ63MA
Cooling capacity	Nom.	kW	2.8	3.6	4.5	7.10
Heating capacity	Nom.	kW	3.2	4.0	5.0	8.00
Power input - 50Hz	Cooling	Nom.	0.066		0.076	0.105
	Heating	Nom.	0.046		0.056	0.085
Dimensions	Unit	HeightxWidthxDepth	215x1,110x710			215x1,310x710
Weight	Unit	kg	31			34
Decoration panel	Model	BYK45FJW1				BYK71FJW1
	Colour	White				
	Dimensions	HeightxWidthxDepth	70x1,240x800			70x1,440x800
	Weight	kg	8.5			9.5
Fan-Air flow rate - 50Hz	Cooling	High/Low	11/9		13/10	18/15
Sound power level	Cooling	Nom.	-			
Sound pressure level	Cooling	High/Low	38.0/33.0		40.0/34.0	42.0/37.0
Refrigerant	Type	R-410A				
Piping connections	Liquid/OD/Gas/OD/Drain	mm	6.35/12.7/VP25 (O.D. 32 / I.D. 25)			9.52/15.9/VP25 (O.D. 32 / I.D. 25)
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220			
Current - 50Hz	Maximum fuse amps (MFA)	A	15			