



FXLQ-MAVE

Floor Standing Unit




BRC1D52

BRC4C64/62

FXLQ20,25MAVE

- Ideal for installation beneath a window
- Requires very little installation space
- Running the pipes from connections at the back, enables the unit to be wall mounted which in turn allows cleaning beneath the unit where dust tends to accumulate



- Long life filter fitted as standard



FXLQ-MAVE

Indoor Units			FXLQ20MAVE	FXLQ25MAVE	FXLQ32MAVE	FXLQ40MAVE	FXLQ50MAVE	FXLQ63MAVE
Capacity	Cooling	kw	2.20	2.80	3.60	4.50	5.60	7.10
	Heating	kw	2.50	3.20	4.00	5.00	6.30	8.00
Power input	Cooling	kw	0.049		0.090		0.110	
	Heating	kw	0.049		0.090		0.110	
Dimensions	(Height x Width x Depth)		600x1000x222		600x1,140x222		600x1,420x222	
Weight			kg		25		30	
Air Flow Rate	Cooling	High/Low	m³/min		7.00 / 6.00		8.00 / 6.00	
Sound Pressure	Cooling	High/Low	dBA		35.0 / 32.0		38.0 / 33.0	
Refrigerant			R-410A					
Power Supply			1~/220-240V/50Hz					
Piping connections	Liquid (OD)/Gas/Drain	mm	6.4 / 12.7 / O.D. 21					9.5 / 15.9 / O.D. 21