



FXLQ20-25P



BRC1E52A/B

BRC7C62

- › Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011)
- › Unit can be installed as free standing model by use of optional back plate
- › Its low height enables the unit to fit perfectly beneath a window
- › Requires very little installation space
- › Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate



- › Wired remote control can easily be integrated in the unit



INDOOR UNIT				FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
Cooling capacity	Nom.		kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.		kW	2.5	3.2	4.0	5.0	6.3	8.000
Power input - 50Hz	Cooling	Nom.	kW	0.049		0.090		0.110	
	Heating	Nom.	kW	0.049		0.090		0.110	
Casing Colour				Fresh white (RAL9010) / Dark grey (RAL7011)					
Dimensions	Unit	HeightxWidthxDepth	mm	600x1,000x232		600x1,140x232		600x1,420x232	
Weight	Unit		kg	27		32		38	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m³/min	7/6		8/6	11/8.5	14/11	16/12
Sound power level	Cooling	Nom.	dBA	-					
Sound pressure level	Cooling	High/Low	dBA	35/32		38/33		39/34	40/35
Refrigerant	Type			R-410A					
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/					9.52/15.9/
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)		A	15					