



FXMQ-MA



BRC1E52A/B BRC4C65

- › Up to 270Pa external static pressure allows extensive ductwork runs and flexible application: ideal for use in large areas
- › Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- › Up to 31.5kW in heating mode



| INDOOR UNIT                         |                         |                    |                     | FXMQ200MA            | FXMQ250MA      |
|-------------------------------------|-------------------------|--------------------|---------------------|----------------------|----------------|
| Cooling capacity                    | Nom.                    |                    | kW                  | 22.4                 | 28.0           |
| Heating capacity                    | Nom.                    |                    | kW                  | 25.0                 | 31.5           |
| Power input - 50Hz                  | Cooling                 | Nom.               | kW                  | 1.294                | 1.465          |
|                                     | Heating                 | Nom.               | kW                  | 1.294                | 1.465          |
| Dimensions                          | Unit                    | HeightxWidthxDepth | mm                  | 470x1,380x1,100      |                |
| Weight                              | Unit                    |                    | kg                  | 137                  |                |
| Fan-Air flow rate - 50Hz            | Cooling                 | High/Low           | m <sup>3</sup> /min | 58/50                | 72/62          |
| Fan-External static pressure - 50Hz | High/Nom.               |                    | Pa                  | 221/132              | 270/191        |
| Sound power level                   | Cooling                 | Nom.               | dBA                 | -                    |                |
| Sound pressure level                | Cooling                 | High/Low           | dBA                 | 48/45                |                |
| Refrigerant                         | Type                    |                    |                     | R-410A               |                |
| Piping connections                  | Liquid/OD/Gas/OD/Drain  |                    | mm                  | 9.52/19.1/PS1B       | 9.52/22.2/PS1B |
| Power supply                        | Phase/Frequency/Voltage |                    | Hz/V                | 1~/50/60/220-240/220 |                |
| Current - 50Hz                      | Maximum fuse amps (MFA) |                    | A                   | 15                   |                |