



FXNQ-MAVE

Concealed Floor Standing Unit




FXNQ20,25MA



BRC1D52

BRC4C64/C62

- Ideal for installation beneath a window
- All models are available with remote control
- Long life filter fitted as standard
- Requires very little installation space
- The connecting port faces downward, eliminating the need to attach auxiliary piping



FXNQ-MAVE

Indoor Units			FXNQ20MAVE	FXNQ25MAVE	FXNQ32MAVE	FXNQ40MAVE	FXNQ50MAVE	FXNQ63MAVE	
Capacity	Cooling	kw	2.20	2.80	3.60	4.50	5.60	7.10	
	Heating	kw	2.50	3.20	4.00	5.00	6.30	8.00	
Power input	Cooling	kw	0.049		0.090		0.110		
	Heating	kw	0.049		0.090		0.110		
Dimensions	(Height x Width x Depth)		610x930x220		610x1070x220		610x1350x220		
Weight			19		23		27		
Air Flow Rate	Cooling	High/Low	7.00 / 6.00		8.00 / 6.00		11.00 / 8.50		
Sound Pressure	Cooling	High/Low	35.0 / 32.0		38.0 / 33.0		39.0 / 34.0		
Refrigerant			R-410A						
Power Supply			1~/220-240V/50Hz						
Piping connections	Liquid (OD)/Gas/Drain	mm	6.4 / 12.7 / O.D. 21					9.5 / 15.9 / O.D. 21	