



FXUQ-MA

4-way blow ceiling suspended cassette



BRC1E51




BRC7C528



FXUQ71MA

- Group control with other VRV indoor units possible
- 5m maximum distance between FXUQ unit and junction box
- Air can be discharged in any of 4 directions
- Possibility to shut 1 or 2 flaps for easy installation in corners



- Auto-swing function ensures efficient air and temperature distribution
- Air flow distribution for ceiling heights up to 3.5m without loss of capacity
- Air can be discharged at 5 different angles between 0 and 60 degrees
- Air filter, drain pan and heat exchanger fin are mildew proof and anti-bacterial treated
- Drain up pump with 500mm lift fitted as standard
- **BRC1E51A – new wired controller:** allows easy navigation through menu items, via a personalised display and minimal number of buttons. Provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible

FXUQ-MA			71	100	125	
Indoor units						
Capacity	Cooling	kW	8.0	11.2	14.0	
	Heating	kW	9.0	12.5	14.0	
Power input	Cooling	kW	0.180	0.289		
	Heating	kW	0.160	0.269		
Dimensions	(Height x Width x Depth)		165x895x895		230x895x895	
Weight			25	31		
Air flow rate	Cooling	High/Low	m ³ /min	19.00 / 14.00	29.00 / 21.00	32.00 / 23.00
	Heating	High/Low	m ³ /min	19.00 / 14.00	29.00 / 21.00	32.00 / 23.00
Sound power (nominal)	Cooling		dBA	56.0	59.0	60.0
Sound pressure	Cooling	High/Low	dBA	40.0 / 35.0	43.0 / 38.0	44.0 / 39.0
	Heating	High/Low	dBA	40.0 / 35.0	43.0 / 38.0	44.0 / 39.0
Refrigerant			R-410A			
Power supply			1~/220-240V/50Hz			
Piping connections	Liquid (OD)/Gas/Drain (OD)	mm	9.5 / 15.9 / 26			
Combination with junction box			BEVQ71MA	BEVQ100MA	BEVQ125MA	

BEVQ-MA			71	100	125
Dimensions	HxWxD	mm	100x350x225		
Weight		kg	3.0	3.0	3.5
Casing			Galvanised steel plate		
Power supply			1~, 50Hz, 220-240V		