



# FXZQ-M

## 4-Way blow ceiling mounted cassette (600 mm x 600 mm)


FXZQ-M



- New and extremely compact casing (575mm in depth) enables unit to fit flush into ceilings and match standard architectural modules, without cutting ceiling tiles
- Modern style decoration panel in super white (RAL9010)
- Whisper quiet operation with sound pressure levels as low as 25dBA

### Excellent low draught characteristics

- **Auto swing:** Vertical auto swing moves the discharge flaps up and down to distribute air effectively throughout the room. Since the flaps can move to a 0-degree position, virtually no draught can be experienced




- **5 different air flow patterns:** Any one of 5 air flow patterns can be freely selected between 0 and 60 degrees and will then be maintained during the operational cycle of the air conditioner.
- Air can be discharged in any of 4 directions. Possibility to shut 1 or 2 flaps for easy installation in corners



### 2-way blow



### 4-way blow



### 3-way blow

## FXZQ-M7V1B

INDOOR UNIT			20	25	32	40	50
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3
Nominal input	cooling	W	73	73	76	89	115
	heating	W	64	64	68	80	107
Dimensions (HxWxD)		mm	286x575x575				
Weight		kg	18				
Air flow rate (H/L)		m <sup>3</sup> /min	9.0/7.0	9.0/7.0	9.5/7.0	11.0/8.0	14.0/10.0
Sound pressure level (H/L)(220V)		dB(A)	30/25	30/25	32/26	36/28	41/33
Sound power level		dB(A)	47	47	49	53	58
Refrigerant type			R-410A				
Power supply		VE	1~, 50Hz, 220-240V				
Infrared remote control	cooling		BRC7E531W				
	heating		BRC7E530W				
Wired remote control			BRC1D527				
<b>DECORATION PANEL</b>			BYFQ60B7W1				
Dimensions (HxWxD)		mm	55x700x700				
Weight		kg	2.7				