



FXZQ-M8

4-Way blow ceiling mounted cassette (600 mm x 600 mm)

FXZQ-M8

new




- New and extremely compact casing (575mm in depth) enables unit to fit flush into ceilings and match standard architectural modules, without cutting ceiling tiles
- Modern style decoration panel in super white (RAL9010)
- Whisper quiet operation with sound pressure levels as low as 25dB(A)

- **5 different air flow patterns:** Any one of 5 air flow patterns can be freely selected between 0 and 60 degrees and will then be maintained during the operational cycle of the air conditioner.
- Air can be discharged in any of 4 directions. Possibility to shut 1 or 2 flaps for easy installation in corners



Excellent low draught characteristics


- **Auto swing:** Vertical auto swing moves the discharge air flaps up and down to distribute air effectively throughout the room. Since the flaps can move to a 0-degree position, virtually no draught can be experienced



2-way blow



4-way blow



3-way blow

FXZQ-M8

INDOOR UNIT		20	25	32	40	50
Cooling capacity	kW	2.2	2.8	3.6	4.5	5.6
Heating capacity	kW	2.5	3.2	4.0	5.0	6.3
Nominal input	cooling	73	73	76	89	115
	heating	64	64	68	80	107
Dimensions (HxWxD)	mm	286x575x575				
Weight	kg	18				
Air flow rate (H/L)	m ³ /min	9.0/7.0	9.0/7.0	9.5/7.0	11.0/8.0	14.0/10.0
Sound pressure level (H/L)(220V)	dB(A)	30/25	30/25	32/26	36/28	41/33
Sound power level	dB(A)	47	47	49	53	58
Refrigerant type		R-410A				
Power supply	VE	1~, 50Hz, 220-240V				
Piping connections	liquid/gas	ø6.4/ø12.7				
Infrared remote control	cooling	BRC7E531				
	heating	BRC7E530				
Wired remote control		BRC1052				
		BYFQ60B				
DECORATION PANEL						
Dimensions (HxWxD)	mm	55x700x700				
Weight	kg	2.7				