



# FXZQ-M9


## 4-Way Blow Ceiling Mounted Cassette (600mm x 600mm)




- Extremely compact casing (575mm in width and depth) enables unit to fit flush into ceilings and match standard architectural modules, without cutting ceiling tiles
- Modern style decoration panel in white (RAL9010)
- Low noise operation: down to 25 dBA sound pressure level
- Excellent low draught characteristics
- Vertical auto-swing function moves the discharge flaps up and down for efficient air distribution throughout the room
- Since the flaps can move to a 0 degree position, virtually no draught can be experienced



- Drain up pump with 750mm lift fitted as standard
- Allows multi tenant applications (option PCB required)
- 5 different air flow patterns: Any one of 5 air flow patterns can be freely selected between zero and 40 degrees and will then be maintained during the operational cycle of the air conditioner,
- Air can be discharged in any of 4 directions
- Possibility to shut 1 or 2 flaps for easy installation in corners



### Examples of air flow patterns possible



FXZQ-M9V1B			20	25	32	40	50
<b>Indoor Units</b>							
Capacity	Cooling	kW	2.20	2.80	3.60	4.50	5.60
	Heating	kW	2.50	3.20	4.00	5.00	6.30
Power input	Cooling	kW		0.073	0.076	0.089	0.115
	Heating	kW		0.064	0.068	0.080	0.107
Dimensions	(Height x Width x Depth)		mm				
Weight			kg				
Air Flow Rate	Cooling	High/Low	m <sup>3</sup> /min		9.50 / 7.00	11.00 / 8.00	14.00 / 10.00
Sound power (nominal)	Cooling		dBA		47.0	49.0	53.0
Sound Pressure	Cooling	High/Low	dBA		30.0 / 25.0	32.0 / 26.0	36.0 / 28.0
Refrigerant			R-410A				
Power Supply			1~/220-240V/50Hz				
Piping connections	Liquid (OD)/Gas/Drain (OD)	mm	6.4 / 12.7 / 32				
Decoration Panel	Model		BYFQ60B7W1				
	Colour		White (Ral 9010)				
	HeightxWidthxDepth	mm	55x700x700				
	Weight	kg	2.7				