



FXZQ-A (matt crystal white panel)



FXZQ-A (silver and matt crystal white panel)



BRC1E52A/B BRC7F530W/S*



FXZQ-A


Fully Flat Cassette

VRV Indoor unit

Unique in the market, the fully flat cassette is a remarkable blend of iconic design and engineering excellence, with an elegant matt crystal white or a silver and matt crystal white finish. Fitting flush within the ceiling modules and fully flat with the ceiling itself, the cassette is both stylish and unobtrusive.

Features and Benefits

- › Unique design in the market: integrates fully flat into the ceiling and fits flush into architectural ceiling modules
- › 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms and small offices
- › The presence sensor (optional) adjusts the set point if no one is detected in the room. It also automatically directs air flow away from people to avoid draughts
- › The floor sensor (optional) detects the average floor temperature and ensures even temperature distribution between ceiling and floor (BRYQ60A/W for floor and presence sensor)
- › Individual flap control: one or more flaps can be easily closed via the wired remote controller (BRC1E52A/B) when refurbishing or rearranging the interior
- › Low energy consumption thanks to a specially developed small tube heat exchanger, DC fan motor and drain pump
- › Fresh air intake for a healthier environment (optional)
- › Standard drain pump with 750mm lift



* Control of presence and floor sensor, and individual flap control function not possible.

- › Modern decoration panel is available in 3 different variations:
 - pure white (RAL9010) fully flat panel with silver louvers
 - pure white (RAL9010) fully flat panel with white louvers
 - pure white (RAL9010) standard panel with white louvers

INDOOR UNIT			FXZQ15A	FXZQ20A	FXZQ25A	FXZQ32A	FXZQ40A	FXZQ50A	
Cooling capacity	Nom.	kW	1.7	2.2	2.8	3.6	4.5	5.6	
Heating capacity	Nom.	kW	1.9	2.5	3.2	4.0	5.0	6.3	
Power input - 50Hz	Cooling	Nom.	to be confirmed						
	Heating	Nom.	to be confirmed						
Dimensions	Unit	HeightxWidthxDepth	260x575x575						
Weight	Unit	kg	17.5			18			
Decoration panel 1	Model (fully flat)		BYFQ60CW						
	Colour		Fresh white (N9.5)						
	Dimensions	HeightxWidthxDepth	46x620x620						
Decoration panel 2	Model (fully flat)		BYFQ60CS						
	Colour		Fresh white (N9.5) + Silver (B471)						
	Dimensions	HeightxWidthxDepth	46x620x620						
Decoration panel 3	Model (original)		BYFQ60B2						
	Colour		Pure White (RAL 9010)						
	Dimensions	HeightxWidthxDepth	55x700x700						
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low	m ³ /min	8.5/7.0/6.5	8.7/7.5/6.5	9/8/6.5	10/8.5/7	11.5/9.5/8	14.5/12.5/10
Sound power level	Cooling	Nom.	dBA	49	49	50	51	54	60
Sound pressure level	Cooling	High/Nom./Low	dBA	31.5/28/25.5	32/29.5/25.5	33/30/25.5	33.5/30/26	37/32/28	43/40/33
Refrigerant	Type		R-410A						
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/	6.35/12.7/	6.35/12.7/	6.35/12.7/	6.35/12.7/	6.35/12.7/
Power supply	Phase/Frequency/Voltage		Hz/V	1~ / 50/60 / 220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)		A	to be confirmed					

BYFQ60CW = panel in matt crystal white, BYFQ60CS = panel in a combination of silver and matt crystal white, BYFQ60B2 = standard panel

See data book for option details.



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin products are distributed by: