



RWEYQ-MY1

Water-cooled VRV



RWEYQ10M

- Wide condensing unit range: 10, 20 & 30HP via 1 single refrigerant circuit
- High COP values: 5.21 nominal value
- Up to 32 indoor units connectable to a 30HP condensing unit
- Wide range of indoor units: 13 different models in a total of 75 variations
- Compact design
- Operation range (inlet water temperature): 10-45°C
- Connectable to current Daikin control systems: DS-net, Intelligent Touch Controller, Intelligent Manager, BACnet Gateway, DMS-IF
- Flexible piping length

HEAT RECOVERY

Outdoor Unit				RWEYQ10MY1	RWEYQ20MY1	RWEYQ30MY1
Capacity range		HP		10	20	30
Capacity	Cooling	kw		26.70	53.40	80.10
	Heating	kw		31.50	63.00	94.50
Power input (Nominal)	Cooling	kw		6.03	12.10	18.10
	Heating	kw		6.05	12.10	18.20
Dimensions	(Height x Width x Depth)	mm		1000x780x550	-	
Weight		kg		150	300	450
Sound Level	Sound Pressure	Cooling	dBA	51.0	54.0	56.0
Refrigerant				R-410A		
Power Supply				3~/380-415V/50Hz		
Max n° of indoor units to be connected				16	20	32
Piping connections	Liquid (OD)/Discharge Gas	mm		9.5 / 22.2 / 19.1	15.9 / 28.6 / 22.2	19.1 / 34.9 / 28.6

HEAT PUMP

Outdoor Unit				RWEYQ10MY1	RWEYQ20MY1	RWEYQ30MY1
Capacity range		HP		10	20	30
Capacity	Cooling	kw		26.70	53.40	80.10
	Heating	kw		31.50	63.00	94.50
Power input (Nominal)	Cooling	kw		6.03	12.10	18.10
	Heating	kw		6.05	12.10	18.20
Dimensions	(Height x Width x Depth)	mm		1000x780x550	-	
Weight		kg		150	300	450
Sound Level	Sound Pressure	Cooling	dBA	51.0	54.0	56.0
Refrigerant				R-410A		
Power Supply				3~/380-415V/50Hz		
Max n° of indoor units to be connected				16	20	32
Piping connections	Liquid (OD)/Discharge Gas	mm		9.5/22.2	15.9/28.6	19.1/34.9